

AUTOMATIC **oi**



UV Flame Detector X2200/X2200G/X2200M



DESCRIPTION



The X2200 UV Flame Detector meets the most stringent requirements worldwide with advanced detection capabilities and immunity to extraneous sources, combined with a superior mechanical design. The detector is equipped with both automatic and manual **oi** test capability. The detector has Division and Zone explosion-proof ratings and is suitable for use in indoor and outdoor applications.

The standard output configuration includes fire, fault and auxiliary relays. An optional 0 to 20 mA output with HART can be provided in addition to the three relays. A model with pulse output is available for easy retrofitting into existing Det-Tronics controller based systems. Auxiliary relay and 0 to 20 mA output are not available with the pulse model. A tri-color LED on the detector faceplate indicates normal condition and notifies personnel of fire alarm or fault conditions.

The X2200M UV detector utilizes a molybdenum (moly) sensing element. Moly-based sensors have an increased spectral range of 1850 to 2650 angstroms, which is better suited for detecting substances with unusual chemistry, sulfur fires, and some black powders.

The X2200 housing is available in aluminum or stainless steel, with NEMA 4X and IP66/IP67 rating.

Typical applications include:

- Hydrogen storage
- Munitions
- Silane storage
- HVDC converter stations

HIGHLIGHTS

- ▲ Complies with FM 3260
- ▲ EN54 certified
- ▲ Certified SIL 2 capable
- ▲ ATEX Directive compliant
- ▲ EQP models available
- ▲ Advanced signal processing
- ▲ Arc — unequaled false alarm rejection
- ▲ HART models available
- ▲ Responds to a fire in the presence of modulated blackbody radiation (i.e. heaters, ovens, turbines) without false alarm
- ▲ High speed capability
- ▲ Automatic, manual or magnetic **oi**[®] (optical integrity) testing — no external test lamp required
- ▲ Easily replaceable **oi** plate
- ▲ Fire, fault and auxiliary relays standard
- ▲ MODBUS RS-485 communication
- ▲ 0 to 20 mA isolated output (optional)
- ▲ Pulse output for compatibility with controller based systems (optional)
- ▲ A tri-color LED on the detector faceplate indicates normal condition and notifies personnel of fire alarm or fault conditions
- ▲ Mounting arm allows easy sighting
- ▲ Integral wiring compartment for ease of installation
- ▲ Class A wiring per NFPA-72
- ▲ Meets NFPA-33 response requirement for under 0.5 seconds (available when model selected)
- ▲ RFI and EMC Directive compliant
- ▲ Built-in data logging / event monitoring

SPECIFICATIONS

Operating Voltage	24 Vdc. Operating range is 18 to 30 Vdc Maximum ripple is 2 volts peak-to-peak.
Power Consumption	2.5 watts @ 24 Vdc nominal 76 watts @ 30 Vdc with EOL resistor installed.
Relays	Contacts rated 5 amperes at 30 Vdc <u>Fire Alarm:</u> — Form C (NO and NC contacts) — normally de-energized — latching/non-latching <u>Fault:</u> — Form A (NO contacts) — normally energized — latching/non-latching <u>Auxiliary*:</u> — Form C (NO and NC contacts) — normally energized — latching/non-latching.
Current Output* (Optional)	0–20 mA (± 0.3 mA), with a maximum loop resistance of 500 ohms from 18–19.9 Vdc, 600 ohms from 20–30 Vdc.
Temperature Range	<u>Operating:</u> –40°C to +75°C (–40°F to +167°F) <u>Storage:</u> –55°C to +85°C (–67°F to +185°F) Hazardous location ratings from –55°C to +75°C available on flameproof model.
Humidity Range	0 to 95% relative humidity, can withstand 100% condensing humidity for short periods of time.
Spectral Sensitivity Range	X2200/X2200G wavelength range 185-245 nanometers. X2200M wavelength range 185-265 nanometers.
Field of View	The detector has a 90 degree cone of vision (horizontal) with the highest sensitivity lying along its central axis.
Source Tube	Contains radioactive isotope Krypton 85 (Kr ⁸⁵) Calculated Activity: 14,800 Becquerels (0.4µCi) Note: Not applicable to model X2200G.
Warranty	3 years.
Enclosure Material	Copper-free aluminum (painted) or stainless steel (316/CF8M cast).
Conduit Entry Size	3/4 inch NPT or M25.
Wiring	16 AWG or 2.5 mm ² shielded cable is recommended.
Shipping Weight (Approximate)	<u>Aluminum:</u> 7 lbs. (3.2 kg) <u>Stainless Steel:</u> 14.6 lbs. (6.7 kg).

Response Characteristics

Very High Sensitivity

Fuel	Size	Distance Feet (m)	Typical Response Time (seconds)	Mode
n-Heptane	1 x 1 foot	85 (25.9)	3	Low Arc
Methane	32 inch plume	100 (30.5)	2	Low Arc

NOTE: Refer to the X2200 instruction manual 95-8549 for details regarding detector response.

*Auxiliary relay and 0 to 20 mA output are not available on pulse output model.

Certification



Class I, Div. 1, Groups B, C & D (T5);
Class II, Div 1, Groups E, F & G (T5);
Class I, Div. 2, Groups A, B, C & D (T3);
Class II, Div 2, Groups F & G (T3);
Class III.
Enclosure NEMA/Type 4X.

For FM Zone approval information, refer to the X2200 instruction manual (95-8549).



IEC 61508

Certified SIL 2 Capable
Applies to specific models –
Refer to the SIL 2 Certified
X2200 Safety Manual (95-8672).



VNIIFTRI

Certificate of Conformity to TP TC 012/2011
TC RU C-US. BH02.B.00234
2ExdeIICT6/T5 IP66
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C)
– OR –
1ExdIICT6/T5 IP66
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C).



VNIPO
Certificate of Conformity to technical regulations, GOST R 53325-2012.



Approvals to EN54-10
See X2200 instruction manual (95-8549) for details.



DEMKO 01 ATEX 132195X
Increased Safety Model

CE 0539 Ex II 2 G II 2 D

Ex db eb IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb –50°C to +60°C)
T5 (Tamb –50°C to +75°C)
IP66/IP67.

Flameproof Model

CE 0539 Ex II 2 G II 2 D

Ex db IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb –55°C to +60°C)
T5 (Tamb –55°C to +75°C)
IP66/IP67.



IECEx Certificate of Conformity

IECEx ULD 06.0018X
Ex db eb IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb = –50°C to +60°C).
T5 (Tamb = –50°C to +75°C).
IP66/IP67.
– OR –
Ex db IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb = –55°C to +60°C).
T5 (Tamb = –55°C to +75°C).
IP66/IP67.



UL-BR 170216X

Ex db eb IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb = –50°C to +60°C)
T5 (Tamb = –50°C to +75°C)
IP66/IP67
– OR –
Ex db IIC T6...T5
Ex tb IIIC T80°C
T6 (Tamb = –55°C to +60°C)
T5 (Tamb = –55°C to +75°C)
IP66/IP67.

Specifications subject to change without notice.

All trademarks are the property of their respective owners.
© 2020 Detector Electronics Corporation. All rights reserved.

Det-Tronics manufacturing system is certified to ISO 9001—
the world's most recognized quality management standard.



Corporate Office
6901 West 110th Street
Minneapolis, MN 55438 USA
www.det-tronics.com

Phone: +1 952.941.6665
Toll-free: +1 800.765.3473
Fax: 952.829.8750
det-tronics@carrier.com

