

AUTOMATIC



Shown with Q9033A
Aluminum Swivel Mount

Multispectrum IR Flame Detector X3301



DESCRIPTION

Y E A R
5
WARRANTY

The X3301 Multispectrum IR Flame Detector is the future generation detector for performance and technology. The detector uses signal processing algorithms, supported by an embedded 32-bit microprocessor, to provide continuous protection in the presence of false alarm sources where hydrocarbon fires and infrared radiation exist. It is suitable for indoor and outdoor applications that

require the highest level of false alarm rejection and fire detection performance. The detector is available in aluminum (painted) or stainless steel (316/CF8M cast) for installation in the harshest environments. The X3301 has a detection range to a 1 x 1 foot (0.3 x 0.3 m) n-Heptane fire at 210 feet, and a solid cone of vision for methane fire. The detector features standard fire alarm, fault and auxiliary relays, with an isolated 0 to 20 mA output model with optional HART communication.

The X3301 provides superior performance in applications that are at the extremes, and where background infrared radiation is a normal condition:

- Hangars
- Offshore production platforms
- Offshore production ships
- Refineries
- Production facilities
- Loading racks
- Compressor stations
- Turbine enclosures
- Airport water curtains
- Automotive Painting
- LNG/LPG
- Gas Separation Plants
- Warehousing
- Marine

HIGHLIGHTS

X3301 TECHNOLOGY FEATURES

- ▲ Complies with FM 3260
- ▲ EN54 certified
- ▲ Certified SIL 2 capable
- ▲ ATEX Directive compliant
- ▲ Certified performance to multiple fuel types and fire sizes
- ▲ EQP models available
- ▲ Long detection range to carbonaceous fires
- ▲ HART models available
- ▲ FDT/DTM capable
- ▲ Multiple sensitivity levels
- ▲ Maximum false alarm rejection
- ▲ Reliable flame detection with modulated IR background
- ▲ Microprocessor controlled heated optics
- ▲ Calibrated automatic optical check for each sensor eliminates need for testing with external test lamp
- ▲ RFI and EMC Directive compliant
- ▲ Event logging with time and date stamp
- ▲ Integral wiring compartment for ease of installation
- ▲ Operates under adverse weather conditions and in dirty environments

BENEFITS

- ▲ Single detector for multiple hydrocarbon fuels
- ▲ Low cost of coverage
- ▲ Ability to detect smaller fires earlier
- ▲ Solid cone of vision to 100 feet for methane
- ▲ Better detection zoning capability
- ▲ Best combination of flame detection and false alarm rejection
- ▲ Low maintenance costs
- ▲ Reliable fault diagnostics
- ▲ Suitable for heavy industrial applications
- ▲ Explosion/flame proof (Ex d) or increased safety installations (Ex d e) in hazardous locations

SPECIFICATIONS

Operating Voltage	24 Vdc nominal. Operating range is 18 to 30 Vdc. Maximum ripple is 2 volts peak-to-peak.
Power Consumption	4 watts minimum (without heater), 17 watts at 30 Vdc with EOL resistor installed and heater on maximum.
Relays	Contacts rated 5 amperes at 30 Vdc. <u>Fire Alarm:</u> — Form C (NO and NC contacts) — normally de-energized — latching/non-latching. <u>Fault:</u> — Form A (NO contacts) — normally energized — latching/non-latching. <u>Auxiliary:</u> — Form C (NO and NC contacts) — normally energized/de-energized — latching/non-latching.
Current Output (Optional)	0–20 mA (± 0.3 mA), with a maximum loop resistance of 500 ohms from 18–19.9 Vdc, 600 ohms from 20–30 Vdc.
Temperature Range	<u>Operating:</u> –40°F to +167°F (–40°C to +75°C). <u>Storage:</u> –67°F to +185°F (–55°C to +85°C). Hazardous location ratings from –55°C to +125°C.
Humidity Range	0 to 95% relative humidity, can withstand 100% condensing humidity for short periods of time.
Wiring	16 AWG or 2.5 mm ² shielded cable is recommended.
Enclosure Material	Copper-free aluminum (painted) or stainless steel (316/CF8M Cast).
Conduit Entry Size	3/4 inch NPT or M25.
Warranty	5 years.

Response Characteristics

	Fuel	Size	Distance Ft (m)	Average Response Time (seconds)***
Very High Sensitivity	n-Heptane	1 x 1 foot	210 (64)*	11
	n-Heptane**	1 x 1 foot	210 (64)*	6
	n-Heptane	1 x 1 foot	100 (30.5)	3
	n-Heptane	6 in. x 6 in.	80 (24.4)	3
	Isopropanol	6 in. x 6 in.	70 (21.3)	4
	Diesel**	1 x 1 foot	150 (45.7)*	14
	Ethanol	1 x 1 foot	210 (64)	11
	Methanol	6 in. x 6 in.	40 (12.2)	3
	Methanol	1 x 1 foot	150 (45.7)*	18
	Methanol**	1 x 1 foot	150 (45.7)*	7
	Methane	30 inch plume	100 (30.5)	3
	JP-5**	1 x 1 foot	150 (45.7)*	2
	JP-5**	2 x 2 feet	210 (64)*	4
	JP-5**	2 x 2 feet	100 (30.5)	2
Medium Sensitivity	Office Paper 0.5 lb.	19" x 19" x 8"	100 (30.5)	4
	Corrugated Panel	18" x 36"	100 (30.5)	8
	n-Heptane	1 x 1 foot	100 (30.5)	12
	n-Heptane	1 x 1 foot	50 (15.2)	2
	Diesel**	1 x 1 foot	70 (21.3)	4
	Ethanol	1 x 1 foot	85 (25.9)	13
	Methanol	1 x 1 foot	70 (21.3)	10
	Methane	30 inch plume	65 (19.8)	3
Methane	30 inch plume	55 (16.8)	2	
JP-5**	2 x 2 feet	100 (30.5)	3	
Office Paper 0.5 lb.	19" x 19" x 8"	50 (15.2)	6	
Corrugated Panel	18" x 36"	50 (15.2)	2	

* Outdoor test condition.
 ** 10 second pre-burn from ignition.
 *** Add 2 seconds for EQP Model.

NOTE: Refer to the X3301 instruction manual (95-8527) for additional sensitivity levels.

Shipping Weight (Approximate)	<u>Aluminum:</u> 7 lbs. (3.2 kg). <u>Stainless Steel:</u> 13.8 lbs. (6.3 kg).
Field of View	90° horizontal by 75° vertical, at a minimum of 70% of the on-axis detection distance.

Certification



Class I, Div. 1, Groups B, C & D (T4A);
 Class II, Div 1, Groups E, F & G (T4A);
 Class I, Div. 2, Groups A, B, C & D (T3C);
 Class II, Div 2, Group F & G (T3C);
 Class III
 Enclosure NEMA/Type 4X.

For FM and CSA Zone approval information, refer to the X3301 instruction manual (95-8527).



IEC 61508
 Certified SIL 2 Capable.
 Applies to specific models –
 Refer to the SIL 2 Certified
 X3301 Safety manual (95-8582).



AFNOR Identification Number LIR 007 A0.



VNIIFTRI
 Certificate of Conformity to
 TP TC 012/2011
 2ExdIICT6/T5 IP66
 T6 (Tamb = –50°C to +60°C)
 T5 (Tamb = –50°C to +75°C).
 – or –
 1ExdIICT6/T5/T4 IP66
 T6 (Tamb = –55°C to +60°C)
 T5 (Tamb = –55°C to +75°C)
 T4 (Tamb = –55°C to +125°C).



VNIPO
 Certificate of Conformity to Technical
 Regulations, GOST R 53325-2009.



Approvals to EN54-10. See instruction manual for details.



US Coast Guard
 Coast Guard Approval No. 161.002/49/0.

Lloyd's Register
 Type Approval Certificate Number
 09/00027.



DEMKO 01 ATEX 130204X
Increased Safety Model
CE 0539 Ex II 2 G
 II 2 D

Ex d e IIC T6–T5 Gb
 Ex tb IIIC T130°C
 T6 (Tamb –50°C to +60°C)
 T5 (Tamb –50°C to +75°C)
 IP66/IP67.

Flameproof Model

CE 0539 Ex II 2 G
 II 2 D

Ex d IIC T6–T4 Gb
 Ex tb IIIC T130°C
 T6 (Tamb –55°C to +60°C)
 T5 (Tamb –55°C to +75°C)
 T4 (Tamb –55°C to +125°C)
 IP66/IP67.



IECEx Certificate of Conformity
 IECEx ULD 06.0017X
 Ex d e IIC T6–T5 Gb
 Ex tb IIIC T130°C
 T6 (Tamb = –50°C to +60°C)
 T5 (Tamb = –50°C to +75°C)
 IP66/IP67.
 – or –
 Ex d IIC T6–T4 Gb
 Ex tb IIIC T130°C
 T6 (Tamb = –55°C to +60°C)
 T5 (Tamb = –55°C to +75°C)
 T4 (Tamb = –55°C to +125°C)
 IP66/IP67.



UL-BR 12.0093X
 Ex d e IIC T6–T5 Gb IP66/IP67
 Ex tb IIIC T130°C
 T6 (Tamb = –50°C to +60°C)
 T5 (Tamb = –50°C to +75°C).
 – or –
 Ex d IIC T6–T4 Gb IP66/IP67
 Ex tb IIIC T130°C
 T6 (Tamb = –55°C to +60°C)
 T5 (Tamb = –55°C to +75°C)
 T4 (Tamb = –55°C to +125°C).



DNV
 Type Approval Certificate Number A-13151.
 DNV Certificate Number MED-B-8184.

Specifications subject to change without notice.

All trademarks are the property of their respective owners.
 © 2020 Detector Electronics Corporation. All rights reserved.



Corporate Office
 6901 West 110th Street | Minneapolis, MN 55438 USA
 Operator: +1 952.941.5665 or +1 800.468.3244
 Customer Service: +1 952.946.6491 or +1 800.765.3473
www.det-tronics.com | Email: det-tronics@carrier.com