

# Natural Gas Technologies

## Application Guide - Edition VIII



Engineered pressure and flow control solutions.

# Natural Gas Technologies Application Guide

## Welcome

This Application Guide is designed to help you quickly and easily select pressure regulator products that solve your particular pressure control problems. In addition, the Application Guide provides background information on the principles of various products and their applications to specific industry segments, such as Air, Steam, Liquids, Process Gases, Fuel Gases, Sanitary and Tank Blanketing and Vapor Recovery. A Technical section provides a rich source of general and specific information to aid you in sizing a particular product.

## Product Sizing Information

We highly recommend that you keep this book in an easily accessible place for quick reference. If you are an experienced engineer, you will be able to completely size a product from the information presented in this book before calling your local sales representative. For those with a less extensive engineering background, the Quick Selection Guides will be especially useful.

## Finding What You Want

A complete Table of Contents and the Index at the back of the book are organized by product type and the common name, which will easily guide you to the appropriate section of the guide to find a product description.

## Ordering What You Need

After selecting a product type or sizing that fits your application, contact your local Sales Office to place an order. Your local Sales Office will ensure that you receive the right product in the shortest possible time.

## Other Application Guides Available

Should your application or project require natural gas regulators or LP-Gas regulation or storage, please request a Natural Gas Technologies Application Guide or LP-Gas Regulators and Equipment Application Guide. The Natural Gas Technologies Application Guide features detailed information on products used for natural gas applications in transmission, distribution and utilization. The LP-Gas Application Guide offers pressure regulators and valves and related equipment for regulation, transfer and storage of LP-Gas. The Tank Management Catalog offers fully integrated solutions for tank protection.



## Additional Information Online

You can view and download pressure regulator bulletins, instruction manuals, product schematics and many other helpful documents at [emerson.com](http://emerson.com). Much of the same information is also available on the Emerson Automation Solutions Regulator Tool Kit.

Download the Regulator Tool Kit:  
[www.emerson.com/regulator toolkit](http://www.emerson.com/regulator toolkit)

United States:  
**1 800 558 5853**

Europe:  
**+39 051 419 0611**

Outside the U.S.:  
**1 972 548 3574**

Asia-Pacific:  
**+65 6770 8337**

Middle East  
and Africa:  
**+971 4811 8100**

## Welcome / Introduction

Table of Contents .....	i
Emerson Automation Solutions.....	ii
Industry Commitment.....	iv
Real-World Simulation.....	v
History .....	vi

## Natural Gas

Application Maps .....	2 to 9
Oil and Gas Production / Transmission.....	2
City Gate / Distribution.....	4
Commercial / Industrial Service .....	6
Residential / Utilization Service.....	8
Product Availability .....	10
Quick Selection Guide.....	12 to 26
Farm Tap / Field.....	12
City Gate / Distribution.....	13
Commercial / Industrial Service .....	15
Residential / Utilization Service.....	19
Fixed Factor Billing / Pressure Factor Management... ..	20
Fuel Gas Regulators .....	21
Supply Regulators .....	22
Stand Alone Shutoff Devices .....	23
Relief Valves / Backpressure Regulators .....	24
Odorizing System.....	26
Applications.....	27
Products .....	30

## Technical

Technical Table of Contents .....	537
Reference Data .....	618
Conversion Tables.....	629
Glossary of Terms .....	676

## Index

Notes.....	xii
------------	-----

## Worldwide Contact Information

## Contents Notice

The contents of this publication are presented for informational purposes only and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.

## Our Trademarks <sup>TM</sup>

Big Joe <sup>TM</sup>	Smart Bleed <sup>TM</sup>
Fisher <sup>TM</sup>	Secondary Seat <sup>TM</sup>
FloBoss <sup>TM</sup>	Tartarini <sup>TM</sup>
Francel <sup>TM</sup>	TESCOM <sup>TM</sup>
Micro-Form <sup>TM</sup>	Topworx <sup>TM</sup>
PlantWeb <sup>TM</sup>	True-Monitor <sup>TM</sup>
Pop <sup>TM</sup>	Whisper Trim <sup>TM</sup>

Note: The Emerson logo is a trademark and service mark of Emerson Electric Co. All other marks are the property of their prospective owners.

## Other Trademarks <sup>TM</sup> and Service Marks <sup>®</sup>

- Aflas<sup>®</sup>** is a mark of Asahi Glass Co., Ltd.
- Chemraz<sup>®</sup>** is a mark owned by Greene, Tweed Technologies, Inc.
- Delrin<sup>®</sup>** is a mark owned by E.I. du Pont de Nemours and Co.
- Durimet<sup>®</sup>** is a mark owned by Duriron Company, Inc.
- Fluoraz<sup>®</sup>** is a trade name of Greene, Tweed Technologies, Inc.
- Fluorel<sup>®</sup>** is a mark owned by 3M Company
- Hastelloy<sup>®</sup> C** is a mark owned by Haynes International, Inc.
- Hydrin<sup>®</sup>** is a mark owned by Zeon Chemicals L.P.
- Hypalon<sup>®</sup>** is a mark owned by E.I. du Pont de Nemours and Co.
- Inconel<sup>®</sup>** is a mark owned by Special Metals Corporation
- Kalrez<sup>®</sup>** is a mark owned by E.I. du Pont de Nemours and Co.
- Monel<sup>®</sup>** is a mark owned by Special Metals Corporation
- Stellite<sup>®</sup>** is a mark owned by Kennametal Inc.
- Thiokol<sup>®</sup>** is a mark owned by Alliant Techsystems Inc.
- Viton<sup>®</sup>** is a mark owned by The Chemours Company FC, LLC

\* All other marks mentioned in this publication are the property of their respective owners.

# Emerson Automation Solutions


## Solving Your Toughest Challenges

Industries are under constant pressure to cut costs, increase output, reduce energy use and improve safety and emissions. That is why companies around the world turn to Emerson Automation Solutions for technologies, services and expertise to solve problems and deliver proven results.




## Expertise and Innovation To Deliver Proven Results

Emerson Automation Solutions is the automation innovator with the depth of expertise and breadth of technologies to take on our customers' toughest challenges and bring predictable success anytime, anywhere.




### Capital Projects

Accelerate ROI and deliver projects confidently with Project Certainty.



### Operational Excellence

Safely optimize production with improved reliability and lower emissions.



### Industrial IoT

Harness the digital revolution for real-time insights and borderless expertise.

## Industry Served

### Products, Services and Expertise to Meet your Needs

For more than a century we've worked side-by-side with customers to understand their challenges and help implement effective solutions. This wealth of experience enables us to provide a broad range of industry-specific products and services — and the expertise to put them to work for you.



Alternative Energy



Chemical



Food and Beverage



Industrial Energy



Life Sciences



Marine



Metals and Mining



Oil and Gas



Power



Pulp and Paper



Refining



Water and Wastewater



# Control Your System with Certainty

Emerson brings together technology and engineering to provide an expanding array of innovative manufacturing and processing solutions for industrial, commercial and consumer markets. We offer the world’s largest collection of pressure control, flow control and relief valve solutions for process and specialty gases, liquids, steam, natural gas and liquid propane industries.

Our regulators are renowned for setting industry standards for performance and extended service life, while Emerson product sales, service and technical support teams are unrivaled in their ability to serve you locally from offices located strategically around the globe.

## Natural Gas Solutions

Emerson leads the way in providing best in-class natural gas conditioning, metering, pressure regulating products and customized skids to the natural gas industry. From regulators to skids, Emerson products offer design innovation, superior performance and unbeatable reliability and durability under extreme conditions in even the world’s most rugged environments. Around the clock, around the world, look to Emerson for natural gas solutions.

## LP-Gas Solutions

Throughout the world, Emerson supplies leading liquefied petroleum gas (LP-Gas) suppliers with the broadest available line of Fisher™ commercial service LP-Gas regulators and bulk storage and transport equipment. Renowned as the propane

industry standard for reliable pressure regulation, Fisher LP-Gas valves and regulators provide high value solutions across a range of stationary storage and mobile applications. With more than 2,000 technical experts at over 200 locations worldwide, our service and support remains second to none.

## Gas, Liquid and Steam Solutions

Emerson offers a dynamic range of direct- and pilot-operated pressure regulators, relief valves and tank management products for industrial gas, liquid and steam applications. Suitable for use in a wide range of environments, from the wellhead to the pharmaceutical plant, their versatility, stability, ease of maintenance and rigorous adherence to ISO-9001 standards for quality and reliability have made them the pressure regulators of choice in tens of thousands of installations worldwide.

# A Complete Line of Valves, Actuators and Regulators



### Natural Gas Solutions

- Regulators
- Relief Valves
- Slam-Shuts



### LP-Gas Solutions

- Regulators
- Bulk Storage and Transport Equipment



### Industrial Gas, Liquid and Steam and Tank Solutions

- Regulators
- Flame and Detonation Arrestors
- Tank Vents and Hatches
- Pressure and Safety Relief Valves
- Steam Traps, Valves and Level Gauges

# Industry Commitment

## Quality

Emerson ensures the highest quality and safety standards through our global brands – Fisher™, Crosby™, Yarway™, Anderson Greenwood™, Penberthy™ and our regional specific brands Enardo™ and Jeon.

For more than a century we have worked side-by-side with customers to understand their challenges and help implement effective solutions. Our systems, processes and employees are committed to providing defect-free products, information and services that satisfy your expectations on time, every time.

Emerson is dedicated to delivering only the highest product quality and performance utilizing efficient operations. We create value by delivering best-in-class pressure and flow control equipment, systems, services and solutions for an unparalleled range of applications. We execute new product development plans with advanced technologies and solutions that deliver undisputed quality.

To achieve consistent operational and product excellence globally we strive to attract the most talented people and support continuous development of our workforce, products and processes at every level.

## Reliability

With more than 125 years of experience, Emerson has built a solid reputation for reliability.

Our regulators, valves and flow control systems are engineered to exacting standards, each carefully designed, thoroughly tested and developed to handle higher pressures while providing increased delivery capacity, reduced noise output and zero emission. We go beyond baseline industry standards to ensure our equipment operates reliably in even the most extreme conditions anywhere in the world.

At Emerson, we are committed to continually raising the bar in our efforts to develop still higher quality, more advanced systems that operate safely and reliably well into the future.

## Technology

Emerson's innovative technologies creates pressure and flow control solutions more productive, efficient and cost-effective. Our proven results are what make us the leader in the industry.

Spanning the globe, our test and evaluation facilities provide the engineering expertise required to ensure superior quality product design and high performance results wherever our products are deployed. At these facilities, we test all sizes and types of regulators under real-world plant conditions to ensure production performance, efficiency, environmental compliance and safety before actual installation at your site.


Our test and evaluation facilities are dedicated to tackling the toughest engineering challenges facing today's process manufacturing and energy industries, including helping companies deliver record volumes of natural gas and other forms of energy, consume less energy, reduce costs, operate more quietly and reduce greenhouse emissions.

## Service

With over 2,000 local technical experts to serve you from nearly 200 locations around the world, our sales and service network is one of the largest in the industry.

Whether you need an emergency replacement regulator or need expert assistance on a long-range growth and expansion plan, there is a local Sales Office to respond quickly and professionally.

## Emerson Automation Solutions Facilities



You Demand High Performance.  
**We Ensure It.**



## Real-World Simulation

### Flow Testing

- Simulates real-world operating conditions using pipelines up to NPS 32 / DN 800 with compressible and incompressible fluids up to 30,000 psig / 2068 bar
- Ensures product performance, efficiency, environmental compliance, life span and safety

### Materials Testing

- Develops and tests materials to improve regulator performance and reliability
- Ensures materials meet customer requirements, national standards, and our own, still higher, brandstandards
- Analyzes and troubleshoots field installations for contamination and composition at an elemental level

### Environmental Testing

- Simulates real-world operating conditions from the deserts of the Middle East to the Arctic North
- Validates product lifecycles at field conditions to extend service life
- Verifies product corrosion resistance using extended salt-spray exposure to ensure environmental protection of process equipment

You demand products to withstand your toughest conditions, while delivering continued optimal performance, efficiency, reliability and safety.

Our design, test and evaluation technologies and techniques validate a full range of product offerings in each of these critical areas, providing flow, material and environmental testing under real-world operating conditions before you place them in your application.

With more than 130 years of application experience in the process industry, our reputation for solving challenging problems and developing products to specifications exceeding regulatory guidelines. Count on Emerson worldwide to deliver the highest quality products available to your site.

# History:


## Our Path to Technology Leadership

In 1880, Fisher™ Controls was founded in Marshalltown, Iowa, by William Fisher. Fisher Controls grew steadily over the years, evolving into an industry leader offering customers the most complete range of flow control products in the world.

William Fisher came to America from England as a boy of 14. As his family ventured west in the new land, they settled along the Mississippi in Clinton, Iowa. It was there, as a mechanic in a small engine shop for 10 years, that William learned about steam, the major source of power in the late 1800s. Because of his experience in water and steam, William, who was 24 at the time, was invited to Marshalltown to help install the water works.

The idea of a control device was born in the engineer's mind as a fire raged in the city. Working through the night, William Fisher hand-throttled the steam-driven pumps to maintain pressure in the city's mains. During that fire, he saw a need for a device that would both control the steam-driven pumps and maintain them at a constant pressure. Many months and trials later, William Fisher was finally satisfied with one of his designs and began manufacturing what we know today as the Fisher Type 1 constant pressure pump governor. He was granted a patent in 1884.

One thing remained the same since William Fisher's first Type 1 pump governor: a pledge to unequalled quality. Today, the brand name Fisher is synonymous with quality throughout the world.



Type 1 Pump Governor 1880

### The Fisher Years

- 1880 Type 1 pump governor is invented by William Fisher.
- 1888 The Fisher Governor Company is incorporated on Dec. 26.
- 1906 William Fisher dies. His wife, Martha, becomes president.
- 1912 Jasper Fisher assumes presidency; first sales offices are established.
- 1937 Serial number 500,000 assigned to a Type 1 pump governor on Nov. 5.
- 1938 Jasper Fisher dies.
- 1940 First Western Union teletype machine is installed to speed communication.
- 1943 One millionth serial number assigned June 9.
- 1944 Mrs. J.H. Fisher is elected president.
- 1946 Sales department holds first school for field representatives.
- 1950 Two-millionth controller made. Fisher enters licensee agreement with Elliott Automation to manufacture products for England and Europe.
- 1954 Mrs. J.H. Fisher retires; J.W. (Bill) Fisher is elected president.
- 1955 New office building opens in Marshalltown.
- 1960 Ball valves are added to Fisher's product line. Licensing agreement reached to manufacture in Japan.
- 1965 Gas regulator department moves to McKinney, Texas.
- 1967 Governor Road facility, the most advanced machine shop of its kind in the world, begins operation in Marshalltown.
- 1969 Fisher begins manufacturing electronic instrumentation. Bill Fisher remains as Chairman of the Board until 1974.
- 1970 Our first European facility opens at Cornwall, England, to manufacture electronic instrumentation.

- 1972 The R.A. Engel Technical Center, Marshalltown, is completed, housing the world's most advanced flow test laboratory.
- 1975 A new electronics manufacturing facility is opened in Marshalltown.
- 1976 Production of our new line of rotary valves begins in Sherman, Texas. Fisher Brazil opens its doors.
- 1979 Fisher Controls Corporation of Delaware forms a stronger manufacturing, sales and service organization.
- 1980 Fisher celebrates a Century of Control.
- 1992 ISO 9001 original registration validated, McKinney, Texas

### The Emerson Years

- 1993 Fisher Controls and Rosemount, merge under ownership of Emerson Electric.
- 1994 Francel™, Gallardon, France, acquired, expanding manufacturing and distribution in Europe, Middle East and Africa.
- 1996 Type 299 pilot-operated regulator introduced to natural gas market.
- 1997 The 50th anniversary of the Type 99. The FloBoss™ 503 and Regulator Vault are introduced.
- 1998 Fisher Regulators FROMEX manufacturing plant opens in Nuevo Laredo, Mexico.
- 1999 Revolutionary Type EZR pressure regulator introduced.
- 2001 Tartarini™, Bologna, Italy, acquired, extending Fisher's brand and distribution capability in Europe and Asia.
- 2003 Manufacturing capability expanded with opening of Shanghai Plant.
- 2003 New, state-of-the-art flow test laboratory opens in McKinney, Texas.

- 2004 Introduced digitally controlled odorant injection system.
- 2004 Jeon, Chengdu, China, acquired, expanding Fisher's presence in China's low-pressure regulator market.
- 2005 Fisher celebrates its 125th anniversary.
- 2005 EZ Family product lines, Types EZR, EZH and EZL pressure regulators expanded.
- 2005 Customer Center opened to display new regulator technology and train customers and sales channel.
- 2005 Tescom™ Corporation, Elk River, Minnesota and Selmsdorf, Germany, manufacturer of high-pressure, high-purity pressure regulators, acquired.
- 2006 Type SR stainless steel Sanitary Regulator introduced.
- 2007 Commercial Service Regulators platform introduced featuring True Monitor™ Protection, Slam-Shut and Secondary Seat™ Protection options.
- 2007 Cluj, Romania, manufacturing location online.
- 2008 Regulator Division becomes Emerson Process Management Regulator Technologies, Inc.
- 2013 Enardo™, Tulsa, Oklahoma, acquired, expands Fisher's storage tank solutions for oil and gas, petrochemical and chemical industries.
- 2014 New Global Regulator Technologies Headquarters opens in McKinney, Texas.
- 2015 Type CS804 regulator with integral slam-shut is added to CS800 Series.
- 2015 New product launches for MR95 and MR98 Series.
- 2015 Emerson celebrates its 125th year anniversary.
- 2017 Acquisition of Pentair's valves and controls business positions Emerson as a main valve partner to its customers.
- 2019 Emerson acquires Spence and Nicholson Steam Technology product lines from Circor International.





**Natural gas** (methane) is a clean-burning fuel gas used for many residential, commercial and industrial applications. This colorless, odorless, naturally occurring gas can be found in many countries around the world.

Natural gas production companies tap gas pools using wells and pipelines. They clean and prepare the gas for sale and transport the gas through pipelines to gas suppliers.

High-pressure transmission pipelines move the gas from the production company's cleaning plants to gas distribution companies for sale to consumers. Regulators and control valves control the high-pressure gas as it moves along the pipeline. At city gate stations and farm taps, regulators reduce the pipeline gas pressure to distribution pressure. Before distribution, an odorant is added to the gas so people can detect the gas in the event of a leak. To provide a constant, measurable gas pressure, service regulators control the gas pressure before it enters the customer's residence or building.

Worldwide, natural gas is used for residential, commercial and industrial applications. Residential applications use natural gas for heating and cooling homes, heating water and fueling gas ranges. Commercial applications, such as grocery stores and office buildings, use natural gas for heating and cooling. For industrial applications, natural gas is used as a feedstock for making chemicals, such as anhydrous ammonia and as a fuel for boilers and furnaces.

# Natural Gas Application: Oil & Gas Production / Transmission

## Introduction










Emerson is a global leader in offering solutions and services tailored to the natural gas industry. Our portfolio ranges from mechanical components like regulators, slam-shuts, isolation valves and relief valves, accurate custody transfer solutions to real time monitoring and control capabilities using flow computers and SCADA systems.


Many of our solutions, including regulators such as Types EZR, FL, 1098-EGR and the CSR family have become industry standards for performance and extended service life.

## Typical Usage Shown

The application maps on the following pages show typical product applications only. These maps and the product information in this Application Guide are presented to familiarize you with the broad range of pressure regulators, over pressure protection solutions, network monitoring and custody transfer solutions available for natural gas applications.

- ### Features
- Versatility
  - High Speed Response
  - Easy Maintenance
  - Flexibility
  - High Capacity
  - Proven Construction Materials
  - Safe Operation
  - Control Accuracy
  - Installation Adaptability

-  Regulator
-  Slam-Shut Positive Shutoff Technology
-  Electronic Pressure Recorder
-  Electronic Flow Estimation and Measurement
-  High Pressure Transmission:  $\leq 1480$  psi / 102 bar
-  Medium/Low Pressure Distribution:  $\leq 580$  psi / 40.0 bar
-  Odorization
-  Gas Chromatograph
-  Meter



  
**1808**  
 Page 193

  
**T205\***

  
**99**  
 Page 57

  
**630 "Big Joe"**  
 Page 152

  
**MR98\***

  
**MR95\***

\*See separate product Bulletin.




**Transmission Skid**  
Page 517



**289**  
Page 76



**HSR**  
Page 463



**Type B**  
Page 205



**627**  
Page 120



**630**  
Page 152



**FL Series**  
Page 447



**310A**  
Page 112



**630**  
Page 152



**63EG**  
Page 30

**Compressor Station**

**Natural Gas Transmission**



**99**  
Page 57




**EZH**  
Page 375

**NATURAL GAS PRODUCTION**




**Cronos Series**  
Page 257

**T205\***




**627**  
Page 120




**Storage Field**

\*See separate product Bulletin.

# Natural Gas Application: City Gate / Distribution





**Odorizer System**  
Page 361

**EZR**  
Page 406

**EZR Relief**  
Page 426

**FL Series**  
Page 447

**EZH**  
Page 375

**EZL**  
Page 395

**99**  
Page 57

**1098-EGR**  
Page 173

**EZHOSX**  
Page 375

**EZH**  
Page 375

**EZROX**  
Page 406

**EZR**  
Page 406

**Transmission Skid**  
Page 517

**SS**

**EFM  
M GC O**

**SS**

**SS**

**FL Series**  
Page 447

**Cronos Series**  
Page 257

**Distribution Skid**  
Page 517

# Natural Gas Application: Commercial / Industrial



**99**  
Page 57



**1805**  
Page 186



**EZR Relief**  
Page 426



**289**  
Page 76



**1805P**  
Page 190



**299H**  
Page 88



**133**  
Page 64



**63EG**  
Page 30



**CS404**  
Page 279

COMMERCIAL



**299HV**  
Page 88



**R/70**  
Page 502



**MF Series**  
Page 480




**Commercial Skid**  
Page 517



**EZROX**  
Page 406



INDUSTRIAL



# Natural Gas Application: Residential / Utilization



**EZR**  
Page 406




**R622**  
Page 506



**HSR**  
Page 463



**1098-EGR**  
Page 173



## Products by Application

Application ..... Page

### Farm Tap/Field

627 Series	120
Type 630	152

### City Gate/District Station

Type 99	57
133 Series	64
Type 310A	112
Type 627	120
Type 627OSX	144
Type 971	170
Type 1098-EGR	173
Type BLE, BLX	214
Cronos Series	257
EZH Series	375
EZL Series	395
EZR Series	406
FL Series	447
M Series	480

### Commercial/Industrial Service

Type 99	57
133 Series	64
299H Series	88
627 Series	120
Type 627F	138
Type 912N	167
Type 1098-EGR	173
A/100 Series	199
A/140 Series	202
B/240 Series	211
CP200 Series	233
CP400 Series	240
Cronos Series	257
CS200 Series	264
CS400 Series	279
CS800 Series	301
CSB400 Series	335
CSB600 Series	343
CSB700 Series	352
EZL Series	395
R Series	502

### Commercial/Industrial Service

Regal 3 Series	511
----------------	-----


### Residential/Utilization Service

Type 912N	167
Type B	205
Type B NG	208
Type HSR	463
R Series	502
Type R622	506

### Fixed Factor/Billing

Type 99	57
299H Series	88
Type 627F	138
Type 1098-EGR	173
CP200 Series	233
CP400 Series	240
CS200 Series	264
CS400 Series	279
CS800 Series	301
CSB400 Series	335





## Products by Application

Application ..... Page

### Fuel Gas Regulators

66 Series.....	44
Type 99.....	57
133 Series.....	64
299H Series.....	88
Type 912N.....	167
Type 1098-EGR.....	173
CP200 Series.....	233
CP400 Series.....	240
CS200 Series.....	264
CS400 Series.....	279
CS800 Series.....	301
CSB400 Series.....	335

### Supply Regulators

67C Series.....	49
1301 Series.....	182

### Stand Alone Shutoff Devices

634 Series.....	164
BM5 Series.....	217
Type BM6X.....	222
Type BM7.....	226
Type OSE.....	496

### Relief Valve/Backpressure Regulators

Type 63EG.....	30
289 Series.....	76
Type 289P.....	83
Type 1805.....	186
Type 1805P.....	190
1808 Series.....	193
Type EZH Relief.....	390
Type EZR Relief.....	426
FL Relief Series.....	454
Type H120.....	459
H200 Series.....	461
V Series.....	530

### Odorizing System

Type Dosaodor-D.....	361
Type DO200.....	371
OL Series.....	495

### Accessories

Type 252.....	74
CNF, CN, CF Series.....	229
FA, FAG Series.....	436
Type P590.....	501
Type RPE.....	515
Types SR, SR11, SRS, STP, STL and Whisper Trim™.....	519
VFA Series.....	527
V Series.....	530

### Skids .....517

### Underground Modules

MIC, MIF, MIR Series.....	490
---------------------------	-----

# Natural Gas Product Availability

PRODUCT TYPE NUMBER	WORLD AVAILABILITY <sup>(1)</sup>				PED 2014/68/ EU CATEGORY
	NORTH AMERICA	EUROPE, MIDDLE EAST AND AFRICA	ASIA PACIFIC	LATIN AMERICA	
63EG	●	●	●	●	SEP and II
66	●	●	●	●	SEP
67C	●	●	●	●	SEP
99	●	●	●	●	I <sup>(2)</sup>
133	●	●	●	●	I
252	●	●	●	●	SEP
289	●	●	●	●	SEP and I
289P	●	●	●	●	SEP
299H	●	●	●	●	I
310A	●	●	●	●	SEP and III
627	●	●	●	●	SEP and II
627F	●	●	●	●	SEP and II
630	●	●	●	●	SEP
634	●			●	----
912N	●	●	●	●	SEP
971	●	●	●	●	III
1098-EGR	●	●	●	●	SEP and II
1301	●	●	●	●	SEP
1805	●	●	●	●	----
1805P	●	●	●	●	----
1808	●	●	●	●	----
A/100		●	●	●	----
A/140		●	●	●	I and IV
B		●	●	●	SEP
B NG		●	●	●	SEP
B/240		●	●	●	I and IV
BLE, BLX		●	●	●	IV
BM5		●	●	●	IV
BM6X		●	●	●	IV
BM7		●	●	●	----
CNF, CN, CF		●	●	●	MAX. IV
CP200	●	●	●	●	----
CP400	●	●	●	●	----
CRONOS		●	●	●	IV
CS200	●	●	●	●	----
CS400	●	●	●	●	I and IV
CS800	●	●	●	●	I and IV



# Natural Gas Product Availability

PRODUCT TYPE NUMBER	WORLD AVAILABILITY <sup>(1)</sup>				PED 2014/68/ EU CATEGORY
	NORTH AMERICA	EUROPE, MIDDLE EAST AND AFRICA	ASIA PACIFIC	LATIN AMERICA	
CSB400	●	●	●	●	I and IV
CSB600	●	●	●	●	I and IV
CSB700	●	●	●	●	I and IV
DOSAODOR-D / ELECTRONIC CONTROL UNIT		●	●		II <sup>(3)</sup>
DOSAODOR-D / ROC 809	●			●	II <sup>(3)</sup>
DO200	●	●	●	●	----
EZH	●	●	●	●	IV
EZH RELIEF	●	●	●	●	IV
EZL	●	●	●	●	----
EZR	●	●	●	●	II, III, IV and SEP
EZR RELIEF	●	●	●	●	III
FA AND FAG FILTERS		●	●	●	MAX. IV
FL	●	●	●	●	IV
FL RELIEF (VS-FL)	●	●	●	●	IV
H120	●	●	●	●	SEP
H200	●	●	●	●	SEP
HSR	●	●	●	●	SEP
M SERIES		●	●	●	I, II, IV and SEP
MIC, MIF, MIR		●	●	●	----
OL ODORIZER		●	●	●	IV
OSE	●	●	●	●	II, III and IV
P590	●	●	●	●	SEP
R SERIES		●	●	●	SEP
R622	●	●	●	●	SEP
REGAL 3		●	●	●	I
RPE		●	●	●	II
SR, SRII, SRS, STP, STL AND WHISPER TRIM™	●	●	●	●	----
VFA		●	●	●	MAX. III
V SERIES		●	●	●	MAX. I and SEP
VS100	●	●	●	●	IV

NOTES: 1. Product availability and PED status are listed in this table. Some products, systems and/or accessories may not be available in a particular country or PED approved. Please consult your local Sales Office for current product availability or PED status.  
2. Inlet pressure limited to 275 psig / 19.0 bar.  
3. Only with cylindrical tank with volume > 1 liter.

# Natural Gas Quick Selection Guide

## Farm Tap / Field

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
1500 psig / 103 bar	3 to 500 psig / 0.21 to 34.5 bar	130,000 SCFH / 3480 Nm <sup>3</sup> /h		<b>Type 630</b> Page 152
2000 psig / 138 bar	5 to 500 psig / 0.34 to 34.5 bar	179,000 SCFH / 4797 Nm <sup>3</sup> /h		<b>627 Series</b> Page 120

# Natural Gas Quick Selection Guide

## City Gate / District Station

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
1500 psig / 138 bar	5 to 500 psig / 0.34 to 34.5 bar	145,800 SCFH / 3908 Nm <sup>3</sup> /h		<b>Type 627OSX</b> Page 144
150 psig / 10.3 bar	-1 in. w.c. to 60 psig / -3 mbar to 4.1 bar	372,000 SCFH / 9970 Nm <sup>3</sup> /h		<b>133 Series</b> Page 64
284 psig / 19.6 bar	0.15 to 43.5 psig / 10 mbar to 3.0 bar	741,604 SCFH / 21,000 Sm <sup>3</sup> /hr		<b>M Series</b> Page 480
290 psig / 20.0 bar	2 to 350 psig / 140 mbar to 24.1 bar	2,427,000 SCFH / 65,000 Sm <sup>3</sup> /h		<b>Type EZLOSX</b> Page 395
290 psig / 20.0 bar	2 to 350 psig / 140 mbar to 24.1 bar	2,534,000 SCFH / 67,911 Nm <sup>3</sup> /h		<b>Type EZL</b> Page 395
363 psig / 25.0 bar	0.15 to 1160 psig / 0.01 to 80 bar	6,866,000 SCFH / 184,000 Nm <sup>3</sup> /h		<b>Type FL-BP</b> Page 447
400 psig / 27.6 bar	4 in. w.c. to 300 psig / 10 mbar to 20.7 bar	11,331,000 SCFH / 304,000 Nm <sup>3</sup> /h		<b>Type 1098-EGR</b> Page 173

# Natural Gas Quick Selection Guide

## City Gate / District Station (Continued)

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
1000 psig / 69.0 bar	2 in. w.c. to 100 psig / 5 mbar to 6.9 bar	265,000 SCFH / 7102 Nm <sup>3</sup> /h		<b>Type 99</b> Page 57
1050 psig / 72.4 bar	6 in. w.c. to 1000 psig / 15 mbar to 68.9 bar	16,124,000 SCFH / 432,000 Nm <sup>3</sup> /h		<b>Type EZROX</b> Page 406
1050 psig / 72.4 bar	6 in. w.c. to 1000 psig / 15 mbar to 68.9 bar	26,138,000 SCFH / 700,500 Nm <sup>3</sup> /h		<b>Type EZR</b> Page 406
1450 psig / 100 bar	4.1 in. w.c. to 1160 psig / 10 mbar to 80.0 bar	9,590,000 SCFH / 257,000 Nm <sup>3</sup> /h		<b>Cronos Series</b> Page 257
1480 psig / 102 bar	4.1 in. w.c. to 1160 psig / 10 mbar to 80.0 bar	100,535,000 SCFH / 2,694,000 Nm <sup>3</sup> /h		<b>FL Series</b> Page 447
1500 psig / 103 bar	14.5 to 1160 psig / 1.00 to 80.0 bar	26,861,000 SCFH / 720,000 Nm <sup>3</sup> /h		<b>Type EZHOSX</b> Page 375
1500 psig / 103 bar	14.5 to 1160 psig / 1.00 to 80.0 bar	57,831,000 SCFH / 1,549,000 Nm <sup>3</sup> /h		<b>Type EZH</b> Page 375

# Natural Gas Quick Selection Guide

## Commercial / Industrial Service

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
1500 psig / 103 bar	10 to 700 psig / 0.69 to 48.3 bar	21,170,000 SCFH / 567,400 Nm <sup>3</sup> /h		<b>Type 310A</b> Page 112
87 psig / 6.0 bar	0.22 to 7.25 psig / 15 to 500 mbar	31,783 SCFH / 852 Nm <sup>3</sup> /h		<b>A/140 Series</b> Page 202
87 psig / 6.0 bar	0.22 to 7.25 psig / 15 to 500 mbar	10,594 SCFH / 284 Nm <sup>3</sup> /h		<b>B/240 Series</b> Page 211
116 psig / 8.0 bar	0.14 to 4.35 psig / 10 to 300 mbar	21,188 SCFH / 568 Nm <sup>3</sup> /h		<b>A/100 Series</b> Page 199
125 psig / 8.6 bar	3.5 in. w.c. to 2 psig / 9 mbar to 0.14 bar	7600 SCFH / 204 Nm <sup>3</sup> /h		<b>CS200 Series</b> Page 264
125 psig / 8.6 bar	3.5 in. w.c. to 5.5 psig / 9 mbar to 0.38 bar	12,010 SCFH / 322 Nm <sup>3</sup> /h		<b>CS400 Series</b> Page 279
125 psig / 8.6 bar	3.5 in. w.c. to 10 psig / 9 mbar to 0.69 bar	36,270 SCFH / 972 Nm <sup>3</sup> /h		<b>CS800 Series</b> Page 301

# Natural Gas Quick Selection Guide

## Commercial / Industrial Service (Continued)

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
125 psig / 8.6 bar	1 to 20 psig / 69 mbar to 1.4 bar	8800 SCFH / 236 Nm <sup>3</sup> /h		<b>CP200 Series</b> Page 233
125 psig / 8.6 bar	1 to 20 psig / 69 mbar to 1.4 bar	23,300 SCFH / 624 Nm <sup>3</sup> /h		<b>CP400 Series</b> Page 240
145 psig / 10.0 bar	3.2 in. w.c. to 43.5 psig / 8 mbar to 3 bar	126,866 SCFH / 3400 Nm <sup>3</sup> /h		<b>Regal 3 Series</b> Page 511
145 psig / 10.0 bar	0.22 to 4.35 psig / 15 mbar to 0.30 bar	3531 SCFH / 95 Nm <sup>3</sup> /h		<b>R Series</b> Page 502
150 psig / 10.3 bar	-1 in. w.c. to 60 psig / -3 mbar to 4.1 bar	372,000 SCFH / 9970 Nm <sup>3</sup> /h		<b>133 Series</b> Page 64
175 psig / 12.1 bar	3.5 in. w.c. to 16 psig / 9 mbar to 1.1 bar	88,170 SCFH / 2363 Nm <sup>3</sup> /h		<b>299HV Series</b> Page 88



# Natural Gas Quick Selection Guide

## Commercial / Industrial Service (Continued)

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
175 psig / 12.1 bar	3.5 in. w.c. to 60 psig / 9 mbar to 4.1 bar	108,120 SCFH / 2898 Nm <sup>3</sup> /h		<b>299H Series</b> Page 88
58 psig / 4.0 bar	6.8 in. w.c. to 43.5 psig / 17 mbar to 3 bar	36,197 SCFH / 970 Nm <sup>3</sup> /h		<b>CSB400 Series</b> Page 335
232 psig / 16 bar	0.13 to 58.0 psig / 9.0 mbar to 4 bar	189,989 SCFH / 5092 Nm <sup>3</sup> /h		<b>CSB600 Series</b> Page 343
232 psig / 16 bar	0.13 to 58.0 psig / 9 mbar to 4 bar	267,186 SCFH / 7161 Nm <sup>3</sup> /h		<b>CSB700 Series</b> Page 352
250 psig / 17.2 bar	3 in. w.c. to 5 psig / 7 mbar to 0.34 bar	1030 SCFH / 27.6 Nm <sup>3</sup> /h		<b>Type 912N</b> Page 167
250 psig / 17.2 bar	5 to 100 psig / 0.34 to 6.9 bar	37,600 SCFH / 1008 Nm <sup>3</sup> /h		<b>Type 627F</b> Page 138
290 psig / 20.0 bar	2 to 350 psig / 140 mbar to 24.1 bar	2,427,000 SCFH / 65,044 Nm <sup>3</sup> /h		<b>Type EZLOSX</b> Page 395

# Natural Gas Quick Selection Guide

## Commercial / Industrial Service (Continued)

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
290 psig / 20.0 bar	2 to 350 psig / 140 mbar to 24.1 bar	2,534,000 SCFH / 67,911 Nm <sup>3</sup> /h		<b>Type EZL</b> Page 395
363 psig / 25.0 bar	0.15 to 1160 psig / 0.01 to 80 bar	6,866,000 SCFH / 184,000 Nm <sup>3</sup> /h		<b>Type FL-BP</b> Page 447
400 psig / 27.6 bar	4 in. w.c. to 300 psig / 10 mbar to 20.7 bar	11,331,000 SCFH / 304,000 Nm <sup>3</sup> /h		<b>Type 1098-EGR</b> Page 173
1000 psig / 69.0 bar	2 in. w.c. to 100 psig / 5 mbar to 6.9 bar	265,000 SCFH / 7102 Nm <sup>3</sup> /h		<b>Type 99</b> Page 57
1450 psig / 100 bar	4 in. w.c. to 1160 psig / 10 mbar to 80.0 bar	9,590,000 SCFH / 257,000 Nm <sup>3</sup> /h		<b>Cronos Series</b> Page 257
2000 psig / 138 bar	5 to 500 psig / 0.34 to 34.5 bar	179,000 SCFH / 4797 Nm <sup>3</sup> /h		<b>627 Series</b> Page 120








# Natural Gas Quick Selection Guide

## Residential / Utilization Service

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
58 psig / 4.0 bar	3.6 to 161 in. w.c. / 9 to 400 mbar	1791 SCFH / 48 Nm <sup>3</sup> /h		<b>Type B</b> Page 205
72.5 psig / 5.0 bar	3.6 to 20 in. w.c. / 9 to 50 mbar	410 SCFH / 11 Nm <sup>3</sup> /h		<b>Type B NG</b> Page 208
125 psig / 8.6 bar	1.8 in. w.c. to 2.2 psig / 4 mbar to 0.15 bar	1285 SCFH / 34,4 Nm <sup>3</sup> /h		<b>Type R622</b> Page 506
125 psig / 8.6 bar	4 in. w.c. to 2.2 psig / 10 mbar to 0.15 bar	4800 SCFH / 129 Nm <sup>3</sup> /h		<b>Type HSR</b> Page 463
145 psig / 10.0 bar	0.22 in. w.c. to 4.35 psig / 15 mbar to 0.30 bar	3531 SCFH / 95 Nm <sup>3</sup> /h		<b>R Series</b> Page 502
250 psig / 17.2 bar	3 in. w.c. to 5 psig / 7 mbar to 0.34 bar	1030 SCFH / 27.6 Nm <sup>3</sup> /h		<b>Type 912N</b> Page 167

# Natural Gas Quick Selection Guide

## Fixed Factor Billing / Pressure Factor Management

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
125 psig / 8.6 bar	3.5 in. w.c. to 10 psig / 9 mbar to 0.69 bar	36,270 SCFH / 972 Nm <sup>3</sup> /h		<b>CS800 Series</b> Page 301
125 psig / 8.6 bar	3.5 in. w.c. to 5.5 psig / 9 mbar to 0.38 bar	12,010 SCFH / 322 Nm <sup>3</sup> /h		<b>CS400 Series</b> Page 279
125 psig / 8.6 bar	1 to 20 psig / 69 mbar to 1.4 bar	8800 SCFH / 236 Nm <sup>3</sup> /h		<b>CP200 Series</b> Page 233
125 psig / 8.6 bar	1 to 20 psig / 69 mbar to 1.4 bar	23,300 SCFH / 624 Nm <sup>3</sup> /h		<b>CP400 Series</b> Page 240
175 psig / 12.1 bar	3.5 in. w.c. to 60 psig / 9 mbar to 4.1 bar	108,120 SCFH / 2898 Nm <sup>3</sup> /h		<b>299H Series</b> Page 88
58 psig / 4.0 bar	6.8 in. w.c. to 43.5 psig / 17 mbar to 3 bar	36,197 SCFH / 970 Nm <sup>3</sup> /h		<b>CSB400 Series</b> Page 335
250 psig / 17.2 bar	5 to 100 psig / 0.34 to 6.9 bar	37,600 SCFH / 1008 Nm <sup>3</sup> /h		<b>Type 627F</b> Page 138
400 psig / 27.6 bar	4 in. w.c. to 300 psig / 10 mbar to 20.7 bar	11,331,000 SCFH / 304,000 Nm <sup>3</sup> /h		<b>Type 1098-EGR</b> Page 173
1000 psig / 68.9 bar	2 in. w.c. to 100 psig / 5 mbar to 6.9 bar	265,000 SCFH / 7102 Nm <sup>3</sup> /h		<b>Type 99</b> Page 57




# Natural Gas Quick Selection Guide

## Fuel Gas Regulators



Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
10 psig / 0.69 bar	2 in. w.c. to 5 psig / 5 mbar to 0.34 bar	77,500 SCFH / 2077 Nm <sup>3</sup> /h		<b>66 Series</b> Page 44
125 psig / 8.6 bar	3.5 in. w.c. to 5.5 psig / 9 mbar to 0.38 bar	12,010 SCFH / 322 Nm <sup>3</sup> /h		<b>CS400 Series</b> Page 279
125 psig / 8.6 bar	3.5 in. w.c. to 10 psig / 9 mbar to 0.69 bar	36,270 SCFH / 972 Nm <sup>3</sup> /h		<b>CS800 Series</b> Page 301
150 psig / 10.3 bar	-1 in. w.c. to 60 psig / -3 mbar to 4.1 bar	372,000 SCFH / 9970 Nm <sup>3</sup> /h		<b>133 Series</b> Page 64
175 psig / 12.1 bar	3.5 in. w.c. to 16 psig / 9 mbar to 1.1 bar	88,170 SCFH / 2363 Nm <sup>3</sup> /h		<b>299HV Series</b> Page 88
175 psig / 12.1 bar	3.5 in. w.c. to 60 psig / 9 mbar to 4.1 bar	108,120 SCFH / 2898 Nm <sup>3</sup> /h		<b>299H Series</b> Page 88
250 psig / 17.2 bar	3 in. w.c. to 5 psig / 7 mbar to 0.34 bar	1030 SCFH / 27.6 Nm <sup>3</sup> /h		<b>Type 912N</b> Page 167

# Natural Gas Quick Selection Guide

## Fuel Gas Regulators (Continued)







Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
400 psig / 27.6 bar	4 in. w.c. to 300 psig / 10 mbar to 20.7 bar	11,331,000 SCFH / 304,000 Nm <sup>3</sup> /h		<b>Type 1098-EGR</b> Page 173
1500 psig / 103 bar	10 to 700 psig / 0.69 to 48.3 bar	21,170,000 SCFH / 567,140 Nm <sup>3</sup> /h		<b>Type 310A</b> Page 112
1000 psig / 68.9 bar	2 in. w.c. to 100 psig / 5 mbar to 6.9 bar	265,000 SCFH / 7102 Nm <sup>3</sup> /h		<b>Type 99</b> Page 57

## Supply Regulators

Maximum Inlet Pressure	Outlet Pressure Range	Maximum Capacity		Type Number
400 psig / 27.6 bar	0 to 150 psig / 0 to 10.3 bar	5612 SCFH / 150 Nm <sup>3</sup> /h		<b>67C Series</b> Page 49
6000 psig / 414 bar	10 to 500 psig / 0.69 to 34.5 bar	5808 SCFH / 156 Nm <sup>3</sup> /h		<b>1301 Series</b> Page 182

# Natural Gas Quick Selection Guide

## Stand Alone Shutoff Devices

Maximum Inlet Pressure	Trip Pressure Range	Maximum Capacity	High and Low Pressure Shutoff		Type Number
203 psig / 14 bar	2.8 in. w.c. to 72.5 psig / 7 mbar to 5 bar	36,194 SCFH / 970 Nm <sup>3</sup> /h	Yes		<b>Type BM7</b> Page 226
232 psig / 16.0 bar	12 in. w.c. to 79.8 psig / 30 mbar to 5.5 bar	C <sub>g</sub> : 306 C <sub>i</sub> : 52	Yes		<b>VS100 Series</b> Page 521
1450 psig / 100 bar	4.2 in. w.c. to 1160 psig / 10 mbar to 80 bar	9,627,000 SCFH / 258,000 Nm <sup>3</sup> /h	Yes		<b>BM5 Series</b> Page 217
1450 psig / 100 bar	4.2 in. w.c. to 1160 psig / 10 mbar to 80 bar	63,433,000 SCFH / 1,700,000 Nm <sup>3</sup> /h	Yes		<b>Type BM6X</b> Page 222
1470 psig / 101 bar	4.02 in. w.c. to 1470 psig / 10 mbar to 101 bar	12,916,000 SCFH / 346,000 Nm <sup>3</sup> /h	Yes		<b>Type OSE</b> Page 496
1500 psig / 103 bar	20 to 88 psig / 1.38 to 6.1 bar	65,000 SCFH / 1742 Nm <sup>3</sup> /h	High Pressure Only		<b>634 Series</b> Page 164

# Natural Gas Quick Selection Guide

## Relief Valve / Backpressure Regulators

Relief Set Pressure Range	Maximum Capacity		Type Number
5 in. w.c. to 75 psig / 12 mbar to 5.2 bar	100,000 SCFH / 2680 Nm <sup>3</sup> /h		<b>289 Series</b> Page 76
10 in. w.c. to 580 psig / 25 mbar to 40.0 bar	102,611 SCFH / 2750 Nm <sup>3</sup> /h		<b>V Series</b> Page 530
14 in. w.c. to 100 psig / 35 mbar to 6.9 bar	111,000 SCFH / 2975 Nm <sup>3</sup> /h		<b>Type 289P</b> Page 83
3 to 125 psig / 0.21 to 8.6 bar	258,000 SCFH / 6912 Nm <sup>3</sup> /h		<b>1808 Series</b> Page 193
5 to 125 psig / 0.34 to 8.6 bar	100,000 SCFH / 2680 Nm <sup>3</sup> /h		<b>Type 1805</b> Page 186
10 to 100 psig / 0.69 to 6.9 bar	136,000 SCFH / 3645 Nm <sup>3</sup> /h		<b>Type 1805P</b> Page 190






# Natural Gas Quick Selection Guide

## Relief Valve / Backpressure Regulators (continued)

Relief Set Pressure Range	Maximum Capacity		Type Number
10 to 400 psig / 0.69 to 27.6 bar	8,795,000 SCFH / 235,706 Nm <sup>3</sup> /h		<b>Type 63EG</b> Page 30
29 to 1160 psig / 2.0 to 80.0 bar	10,375,000 SCFH / 278,000 Nm <sup>3</sup> /h		<b>Type EZH Relief</b> Page 390
20 to 1160 psig / 1.4 to 80.0 bar	28,155,000 SCFH / 754,554 Nm <sup>3</sup> /h		<b>Type EZR Relief</b> Page 426
29 to 1160 psig / 2.0 to 80.0 bar	74,442,000 SCFH / 1,995,000 Nm <sup>3</sup> /h		<b>Type FL Relief</b> Page 454
25 to 300 psig / 1.7 to 20.7 bar	195,000 SCFH / 5226 Nm <sup>3</sup> /h		<b>H200 Series</b> Page 461
35 to 350 psig / 2.4 to 24.2 bar	34,560 SCFH / 926 Nm <sup>3</sup> /h		<b>Type H120</b> Page 459

# Natural Gas Quick Selection Guide

## Odorizing System

Odorization Type	Maximum Working Pressure	Maximum Gas Flow Rate		Type Number
Injection	Supply: 1450 psig / 100 bar Injection: 870 psig / 60 bar	49,440,000 SCFH / 1,400,000 Sm <sup>3</sup> /h		<b>Type Dosaodor-D</b> Pages 361 and 367
Absorption	1305 psig / 90 bar	3,531,000 SCFH / 100,000 Sm <sup>3</sup> /h		<b>OL Series</b> Page 495
Injection	Supply: 1450 psig / 100 bar Injection: 870 psig / 60 bar	49,440,000 SCFH / 1,400,000 Sm <sup>3</sup> /h		<b>Type DO200</b> Page 371

## District Stations

District stations are located throughout larger towns and cities. They essentially are smaller city gates used to regulate distribution pressure.

Depending upon the size of the district station, any of the following regulators are used: Types 99 and 1098-EGR and Series EZR, EZL, 133, 299H and Cronos.

## Services

A service is the point of delivery to the consumer. This point of delivery is where the consumer takes responsibility of the pipeline and devices in the pipeline. Types B, HSR, 912N and R622 regulators are all used for residential and utilization services.

Types 627F, 99, 1098-EGR, REGAL 3 and Series 627, 133, 299H, CSB400, CS800, CS400 and CP400 regulators are used for commercial, industrial and utilization services.

## Fixed Factor Billing/Pressure Factor Measurement

Most residential consumers have a meter outside their home that records the exact amount of gas that is being used. This is known as exact consumption billing. Some commercial and small industrial customers need more pressure than the standard 7 in. w.c. / 17 mbar, but they do not use enough gas to install a more expensive pressure-compensated meter. In this case, the gas company can use fixed factor billing.

Fixed factor billing uses an extremely accurate regulator to keep the gas pressure at  $\pm 1$  percent of P2 absolute. A normal residential meter is used to measure the gas flow. A fixed factor billing is determined between the measured pressure and the actual pressure. This factor is then used to determine the customer's corrected usage.

Types 1098-EGR, 627F, 99 and Series 299H and CP400 are commonly used when accuracy of  $\pm 1$  percent is desired.

## Fuel Gas Regulators

Fuel gas regulators are used to control the gas pressure to a burner. There are three main characteristics important to the selection of a regulator for a fuel gas burner: accuracy, shutoff and speed of response.

Accurate pressure control is a vital factor that affects the efficiency of the burner. The regulator must maintain the pressure within a specified range regardless of flow to ensure perfect combustion of the fuel. The ideal mix of air and fuel will give the desired energy output from the burner. Tight shutoff and fast speed of response are usually necessary because of the controls that are on the burner. A solenoid valve is often used to turn the burner on and off. This requires the regulator to also react at the same speed.

If it does not, it can cause problems with the low-pressure and high-pressure safety cut-outs. If the regulator does not open fast enough it will starve the system of gas and the low-pressure switch will trip. If the regulator does not close fast enough, the high-pressure switch will trip. This high-pressure switch also may be tripped if the regulator does not shut off tight.

For these reasons the regulator chosen must be very accurate, have fast response and have elastomeric seats that shut off tight. Types 1098-EGR, 99 and Series 66 and CS800 are examples of regulators used for fuel gas applications.

## Overpressure Protection

To prevent personal injury, equipment damage or leakage due to escaping gas or bursting of pressure-containing parts, it is necessary to install adequate overpressure protection when installing a pressure reducing regulator. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure. Some regulators are made with internal overpressure relief, whereas others require the installation of a separate relief valve or an additional regulator to act as a monitor. There are also shutoff devices that are designed specifically to handle overpressure. Pressure relief valves, monitors and automatic shutoffs are used for overpressure protection.

## Pressure Relief Valves

A pressure relief valve is used to limit pressure build-up (i.e., prevent overpressure) at its location in a system. The relief valve opens to prevent a rise of internal pressure in excess of a specified value. Pressure relief valves can be direct-operated or pilot-operated. The following are pressure relief valves:

289, 1805 and H200 Series and Types 63EG, EZR, EZH, FL and 1808.

## Monitors

Monitor regulators are used in city gate and district stations as overpressure protection. A monitor regulator is installed in series with a regulator that is controlling the flow of gas. The monitor regulator is set to take over if the working regulator fails open. Upstream regulators must always have an external control line. Monitor style constructions are available in the following regulators:

Types 1098-EGR, 99, CS800EN, EZR, EZH, EZL and Series 299H, 133, FL and Cronos.

# Natural Gas Applications

## Automatic Shutoffs/Slam-Shuts

A pressure shutoff or slam-shut device shuts off the flow whenever the sensed control pressure violates a set limit. Depending on the capability of the device selected, it may be able to shut off in response to a low-pressure condition only, a high-pressure condition only or both. The R and 299HS Series and Types CSB404, CS404 and CS804 are all pressure reducing regulators with integral shutoff devices. Types OSE, BM5, VS100 and 634 Series are stand alone shutoff devices.

## Other Applications

### Skids

Skids are prefabricated pressure reducing stations. The regulator stations are designed to the customer's specifications, then built to order and include piping, regulators and manual isolation valves (Figure 2).

Skids reduce overall costs and may frequently include components such as gauges, slam-shuts and filters.

### ROCs and Flow Computers

The family of Remote Operations Controllers (ROCs) and FloBoss™ Flow Computers are designed to meet the wide-ranging measurement and control needs of the natural gas industry. These products are suited to applications at wellheads, meter runs, custody transfer stations, compressor stations and gate stations. They provide on-site, round-the-clock monitoring, measurement, totalizing, alarming, communications and control. Using microprocessor technology, these products stand alone or network to a data gathering system. Monitored values are processed and stored for easy access by personnel in the field or can be relayed through telephone, radio or satellite transmissions to remote locations.



**Figure 2.** Skid

*Fabricated pressure reducing station designed and built to meet specific customer requirements.*

Both ROCs and flow computers use operating systems that support configurable I/O, historical databases, audit trails, user programmability, smart transmitters and self-testing. Plus, standard application programs make AGA calculations, PID control and logic/sequencing control easy to implement.

### Odorization

Federal safety regulations require the injection of odorant, usually with mercaptan or Tetrahydrothiophene (THT) into natural gas distribution lines in order to warn or alert public of possible leaks. Natural gas (almost pure methane) is a combustible, odorless gas; odorants are introduced to give it a familiar gas smell. To ensure public safety, odorized gas must be detectable at one-fifth (20%) of the lower flammable or explosive limit. Types DO200 and Dosaodor-D injection systems provide computerized uniform odorant distribution as well as reliable redundancy and backup options for reliable odorization.

## Natural Gas Devices

There are several devices and accessories used in a natural gas system. Your local Sales Office can assist you in selecting the proper regulators and accessories for your system. The purpose of this Application Guide is to familiarize you with some of the products used to control natural gas and briefly explain some of the many natural gas applications.

## Applications

### Pressure Reducing Regulators

A pressure reducing regulator maintains a desired outlet pressure while providing the required flow to satisfy a variable downstream demand. The level at which the reduced pressure is maintained is the outlet pressure setting of the regulator. Pressure reducing regulators can be direct-operated or pilot-operated.

In a natural gas system, pressure reducing regulators are used both for transmission and distribution which includes farm taps and field regulators; city gates; district stations; residential, commercial, industrial and utilization services; and fixed factor billing or pressure factor measurement (PFM). Pressure reducing regulators control gas pressure inside industrial plants. They are also used as monitors in city gate and district stations.

### Transmission

Transmission pipelines move natural gas from one place to another, usually over long distances. Control valves,

pilot-operated regulators and relief valves are used to control the pressure and flow of gas through the pipelines. Types EZR, EZH, 310A and FL and Cronos Series are examples of regulators used in transmission pipelines. The Types EZROSX, EZHOSX, FL and Cronos have optional slam-shut devices for overpressure and/or underpressure protection.

## Distribution

### Farm Tap/Field

Farm taps are points along a transmission pipeline where a distribution tap serves a farm or small community. The major difference between a farm tap and a city or district gate is the volume of gas required to supply the load. Farm taps supply less volume. Types 630, 627 and 627F are examples of regulators used for farm taps. The Type CSB454 has an optional integral slam-shut device for over/underpressure protection.

### City Gate Stations

When a natural gas pipeline nears a city, the high-pressure gas needs to be reduced to a distribution level. A city gate is a pressure reducing point. Control valves and pressure reducing regulators are used to reduce the gas pressure. The city gate is usually the point where the local distribution company takes control of the gas. Typically, Types EZR, EZH, 310A, EZL, 133HP, 1098-EGR and Series FL and 971 are used in city gates (Figure 1).



**Figure 1. Natural Gas Distribution**  
A typical dual run city gate station utilizes Type EZR's in a monitor configuration.

# Type 63EG

## Relief Valve or Backpressure Regulator

FISHER™

### Introduction

Types 63EG and 1098-63EGR pilot-operated relief valves or backpressure regulators are suitable for both liquid and gas service and may also be used for throttling backpressure applications, such as on oilfield separators. These relief valves are combined with the 6358 Series pilots.

### Body Sizes and End Connection Styles

See Table 1

### Flow Coefficients

See Table 3

### IEC Sizing Coefficients

See Table 4

### Flow Capacities

See Tables 8 through 13

### Maximum Relief (Inlet) Pressures

**Type 63EG:** 400 psig / 27.6 bar including build-up or body rating, whichever is lower  
**Type 1098-63EGR:** 82 psig / 5.6 bar including build-up

### Relief Set Pressure Ranges

**Type 63EG:** 10 to 400 psig / 0.69 to 27.6 bar  
**Type 1098-63EGR:** 3 to 65 psig / 0.21 to 4.5 bar

### Pressure Registration

External (factory connected to body tap)

### Temperature Capabilities

#### Nitrile (NBR):

-20 to 180°F / -29 to 82°C

#### Fluorocarbon (FKM):

0 to 300°F / -18 to 149°C,

Water is limited to 0 to 180°F / -18 to 82°C

Ethylene propylene (EPR):

-20 to 275°F / -29 to 135°C

Perfluoroelastomer (FFKM):

0 to 425°F / -18 to 218°C

### Approximate Weights (including pilot)

#### Type 63EG

NPS 1 / DN 25: 35 lbs / 16 kg

NPS 2 / DN 50: 55 lbs / 25 kg

NPS 3 / DN 80: 95 lbs / 43 kg

NPS 4 / DN 100: 145 lbs / 66 kg

NPS 6 / DN 150: 330 lbs / 150 kg

NPS 8 x 6 / DN 200 x 150: 670 lbs / 304 kg

NPS 12 x 6 / DN 300 x 6: 1150 lbs / 521 kg

#### Type 1098-63EGR

NPS 1 / DN 25: 65 lbs / 29 kg

NPS 2 / DN 50: 85 lbs / 39 kg

NPS 3 / DN 80: 125 lbs / 57 kg

### Type 1098-63EGR (continued)

NPS 4 / DN 100: 175 lbs / 79 kg

NPS 6 / DN 150: 360 lbs / 163 kg

NPS 8 x 6 / DN 200 x 150: 700 lbs / 318 kg

NPS 12 x 6 / DN 300 x 6: 1180 lbs / 535 kg

### Options

- Whisper Trim™ Cage Construction
- NACE Construction
- Aluminum or Stainless steel Type 252 pilot supply filter
- Brass Type P594-1 filter
- Pressure gauges

### Additional Technical Data

Scan or Click the QR code for more information on this product.


[www.Emerson.com](http://www.Emerson.com)



08/19

### Features

- NACE Construction
- Noise Reduction Capability
- Easy In-Line Maintenance
- Oxygen Service
- Fast Pilot Reseat
- Low Buildup Capability
- Versatility
- Time Tested
- Reliable
- Robust




W6955

Figure 1. Type 63EG Relief Valve or Backpressure Regulator



W3003-1

Figure 2. Type 1098-63EGR Relief Valve or Backpressure Regulator



E0101

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE
- LOADING PRESSURE

Figure 3. Type 63EG Operational Schematic




Figure 4. Type 1098-63EGR Relief Valve Operational Schematic

Table 1. Body Size and End Connection Style

BODY SIZE		BODY MATERIAL	
NPS	DN	CAST IRON	STEEL OR STAINLESS STEEL
1 or 2	25 or 50	NPT, CL125 FF flanged	NPT, SWE, BWE, CL150 RF, CL300 RF, CL600 RF or PN 16/25/40 flanged
3, 4, 6	80, 100, 150	CL125 FF flanged	BWE, CL150 RF, CL300 RF, CL600 RF or PN 16/25/40 flanged
8 x 6 or 12 x 6	200 x 150 or 300 x 150	----	CL150, CL300, CL600 or BWE

Table 2. Main Valve Construction Material

BODY AND BODY FLANGE	SEAT RING AND VALVE PLUG	CAGE	SPRING	PISTON RING	O-RING, GASKET AND OTHER ELASTOMER PART
WCC Steel, Cast iron or CF8M Stainless steel	410/416 Stainless steel (standard) and 316 Stainless steel	Stainless steel (standard linear), 416 or 316 Stainless steel (Whisper Trim™ III)	Zinc-plated steel (standard) or Inconel® X750 (optional)	Polytetrafluoroethylene (PTFE)	Nitrile (NBR) (standard), Fluorocarbon (FKM) or Ethylenepropylene (EPR)

Table 3a. Flow Coefficients at Maximum Rated Travels, Line Size Equals Body Size

BODY SIZE		PIPING STYLE									K <sub>m</sub>
NPS	DN	Linear Cage			Whisper Trim III Cage			Quick Opening Trim			
		C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	
1	25	600	17.2	35.7	576	17.0	33.7	769	23.9	32.2	0.71
2	50	2280	63.3	36.0	1970	54.7	36.0	2460	68.3	36.0	0.71
3	80	4630	132	35.1	3760	107	35.0	4790	141	33.9	0.71
4	100	7320	202	36.2	6280	180	34.8	8120	229	35.4	0.71
6	150	12,900	397	32.5	9450	295	32.0	14,915	445	33.5	0.71
8 x 6	200 x 150	18,480	578	32.0	10,660	305	35.0	15,770	478	33.0	0.71
12 x 6	300 x 150	21,180	662	32.0	11,050	316	35.0	15,770	478	33.0	0.71

-continued-

Inconel® is a mark owned by Special Metals Corporation.

# Type 63EG

## Relief Valve or Backpressure Regulator

FISHER™

**Table 3b. Flow Coefficients at Maximum Rated Travels, 2:1 Line Size to Body Size**

BODY SIZE		PIPING STYLE									K <sub>m</sub>
NPS	DN	Linear Cage			Whisper Trim III Cage			Quick Opening Trim			
		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	
1	25	568	16.8	33.0	529	15.5	34.0	728	24.5	29.8	0.71
2	50	2050	59.6	34.4	1830	52.2	35.0	2214	64.4	34.4	0.71
3	80	4410	128	34.4	3630	106	34.2	4571	137	33.3	0.71
4	100	6940	198	35.0	6020	171	35.2	7701	225	34.2	0.71
6	150	12,100	381	31.7	9240	291	31.7	14,571	435	33.5	0.71
8 x 6	200 x 150	17,370	543	32.0	10,020	286	35.0	15,410	467	33.0	0.71
12 x 6	300 x 150	19,900	622	32.0	10,380	297	35.0	15,410	467	33.0	0.71

**Table 4. IEC Sizing Coefficient**

BODY SIZE		X <sub>t</sub>	F <sub>d</sub>	F <sub>i</sub>
NPS	DN			
1	25	0.81	0.43	0.84
2	50	0.82	0.35	
3	80	0.78	0.30	
4	100	0.83	0.28	
6 and 8 x 6	150 and 200 x 150	0.67	0.28	

**Table 5. Port Diameter and Valve Plug Travel**

BODY SIZE		PORT DIAMETER		VALVE PLUG TRAVEL	
NPS	DN	In.	mm	In.	mm
		1	25	1.31	33
2	50	2.38	60	1.13	29
3	80	3.38	86	1.50	38
4	100	4.38	111	2.00	51
6, 8 x 6 and 12 x 6	150, 200 x 150 and 300 x 150	7.19	183	2.00	51

**Table 6. Relief Set Pressure and Backpressure Control Range**

TYPE	PILOT TYPE	RELIEF SET PRESSURE RANGE <sup>(1)</sup>		SPRING PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
		psig	bar			In.	mm	In.	mm
63EG	6358	10 to 40	0.69 to 2.8	1E392527022	Yellow	0.148	3.76	2.00	50.8
		35 to 125	2.4 to 8.6	1K748527202	Red	0.187	4.75	2.19	55.6
	6358B	10 to 30	0.69 to 2.1	1B788327022	Silver	0.142	3.61	2.13	54.1
		30 to 60	2.1 to 4.1	1B788427022	Blue	0.182	4.62	1.94	49.3
		60 to 125	4.1 to 8.6	1K748527202	Red	0.187	4.75	2.19	55.6
	6358EB	85 to 140	5.9 to 9.6	17b1261X012	Green	0.225	5.72	3.70	94.0
		130 to 200	9.0 to 13.8	17b1263X012	Blue	0.262	6.65	3.85	97.8
		180 to 350	12.4 to 24.1	17b1264X012	Red	0.294	7.47	4.22	107
6358EBH	250 to 400	17.2 to 27.6	17b1263X012	Blue	0.262	6.65	3.85	97.8	
1098-63EGR	6358B	3 to 18	0.21 to 1.2	1B986027212	Green	0.120	3.05	2.12	53.8
		15 to 40	1.0 to 2.8	1E392527022	Yellow	0.148	3.76	2.00	50.8
		35 to 65	2.4 to 4.5	1K748527202	Red	0.187	4.75	2.19	55.6

1. Set pressure plus buildup should not exceed maximum differential pressure of 400 psig / 27.6 bar.





**Table 7. Minimum and Maximum Differential Pressure**

BODY SIZE		MAIN VALVE SPRING RANGE		MAIN VALVE SPRING PART NUMBER	MAIN VALVE SPRING COLOR	TYPE 63EG				TYPE 63EG WITH TYPE 1098 SIZE 40 ACTUATOR			
						Minimum Differential Pressure Required for Full Stroke		Maximum Differential Pressure		Minimum Differential Pressure Required for Full Stroke		Maximum Differential Pressure	
						psig	bar	psig	bar	psig	bar	psig	bar
1	25	30 to 125	2.1 to 8.6	14A9687X012	Green	70	4.8	125	8.6	2.5	0.17	60	4.1
		85 to 400	5.9 to 27.6	14A9679X012	Red	150	10.3	400	27.6	----	----	----	----
2	50	10 to 40	0.69 to 2.8	14A6768X012	Yellow	22	1.5	40	2.8	2	0.14	20	1.4
		30 to 125	2.1 to 8.6	14A6626X012	Green	30	2.1	125	8.6	3	0.21	60	4.1
		85 to 400	5.9 to 27.6	14A6628X012	Red	90	6.2	400	27.6	----	----	----	----
3	80	10 to 40	0.69 to 2.8	14A6771X012	Yellow	19	1.3	40	2.8	2.5	0.17	20	1.4
		30 to 125	2.1 to 8.6	14A6629X012	Green	25	1.7	125	8.6	4	0.28	60	4.1
		85 to 400	5.9 to 27.6	14A6631X012	Red	60	4.1	400	27.6	----	----	----	----
4	100	10 to 40	0.69 to 2.8	14A6770X012	Yellow	16	1.1	40	2.8	3.5	0.24	20	1.4
		30 to 125	2.1 to 8.6	14A6632X012	Green	20	1.4	125	8.6	5	0.34	60	4.1
		85 to 400	5.9 to 27.6	14A6634X012	Red	55	3.8	400	27.6	----	----	----	----
6, 8 x 6, 12 x 6	150, 200 x 150, 300 x 150	10 to 40	0.69 to 2.8	15A2253X012	Yellow	16	1.1	40	2.8	6	0.41	20	1.4
		30 to 125	2.1 to 8.6	14A9686X012	Green	20	1.4	125	8.6	9.5	0.66	60	4.1
		85 to 400	5.9 to 27.6	15A2615X012	Red	55	3.8	400	27.6	----	----	----	----

**Table 8. Type 63EG Relief Capacities for NPS 1 / DN 25 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING			
					psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h		
1	25	6358	Green	35 to 125 / 2.4 to 8.6	60	4.1	8.5	0.59	10.0	0.69	5.0	0.34	62,000	1662		
				1K748527202	80	5.5	3.0	0.21	3.0	0.21			72,000	1930		
				Red	100	6.9	2.5	0.17	3.5	0.24			87,000	2332		
					125	8.6	2.5	0.17	3.5	0.24			105,000	2814		
		6358B	Green	60 to 125 / 4.1 to 8.6	60	4.1	2.7	0.19	10.0	0.69	1.0	0.07	62,000	1662		
				1K748527202	80	5.5			3.0	0.21			3.0	0.21	72,000	1930
				Red	100	6.9			2.5	0.17			3.5	0.24	87,000	2332
					125	8.6			2.5	0.17			3.5	0.24	105,000	2814
		6358EB	Red	85 to 140 / 5.9 to 9.6	85	5.7	2.5	0.17	72	5.0	2.0	0.14	126,000	3377		
				17B1261X012	100	6.9	2.5	0.17	57	3.9			131,000	3511		
				Green	125	8.6	3.0	0.21	32	2.2			148,000	3966		
					140	9.6	3.0	0.21	17	1.2			166,000	4449		
6358EBH	Red	130 to 200 / 9.0 to 13.8	140	9.6	5.0	0.34	17.0	1.2	3.0	0.21	126,000	3377				
		17B1263X012	150	10.3	5.0	0.34	14.0	0.97			131,000	3511				
		Blue	175	12.1	6.0	0.41	12.0	0.83			148,000	3966				
			200	13.8	6.0	0.41	12.0	0.83			166,000	4449				
6358EBH	Red	180 to 350 / 12.4 to 24.1	200	13.8	6.0	0.41	12.0	0.83	3.0	0.21	166,000	4449				
		17B1264X012	250	17.2			12.0	0.83			203,000	5440				
		Red	300	20.7			12.0	0.83			239,000	6405				
			350	24.1			12.0	0.83			276,000	7397				
6358EBH	Red	250 to 400 <sup>(5)</sup> / 17.2 to 27.6 <sup>(5)</sup>	300	20.7	7.0	0.48	13.0	0.90	6.0	0.41	240,000	6432				
		17B1263X012	350	24.1	7.0	0.48	13.0	0.90			277,000	7424				
		Blue	375	25.9	8.0	0.55	14.0	0.97			296,000	7933				

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).  
 2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
 3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.  
 4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.  
 5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.

# Type 63EG

## Relief Valve or Backpressure Regulator



**Table 9. Type 63EG Relief Capacities for NPS 2 / DN 50 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING	
					psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
2	50	6358	Yellow	10 to 40 / 0.69 to 2.8 1E392527022 Yellow	10	0.69	5.5	0.38	12.0	0.83	5.0	0.34	95,000	2546
					15	1.0	2.0	0.14	7.0	0.48			95,000	2546
					20	1.4	1.7	0.12	2.5	0.17			96,000	2573
					30	2.1	1.7	0.12	2.0	0.14			122,000	3270
		6358	Green	35 to 125 / 2.4 to 8.6 1K748527202 Red	40	2.8	2.0	0.14	2.5	0.17	1.0	0.07	151,000	4047
					50	3.4	2.0	0.14	2.5	0.17			178,000	4770
					60	4.1	2.0	0.14	2.5	0.17			204,000	5467
					80	5.5	2.4	0.17	3.0	0.21			258,000	6914
		6358B	Yellow	10 to 30 / 0.69 to 2.1 1B788327022 Silver	10	0.69	5.5	0.38	12.0	0.83	2.0	0.14	95,000	2546
					15	1.0	2.0	0.14	7.0	0.48			95,000	2546
					20	1.4	1.7	0.12	2.5	0.17			96,000	2573
					30	2.1	1.7	0.12	2.0	0.14			122,000	3270
6358B	Green	30 to 60 / 2.1 to 4.1 1B788327022 Blue	30	2.1			2.5	0.17	3.0	0.21	124,000	3323		
			40	2.8	1.7	0.12	2.0	0.14			149,000	3993		
			50	3.4			2.0	0.14			176,000	4717		
			60	4.1			2.0	0.14			203,000	5440		
6358B	Green	60 to 125 / 4.1 to 8.6 1K748527202 Red	60	4.1	2.0	0.14	2.5	0.17	6.0	0.41	204,000	5467		
			80	5.5	2.4	0.17	3.0	0.21			258,000	6914		
			100	6.9	2.4	0.17	3.0	0.21			311,000	8335		
			125	8.6	2.4	0.17	3.0	0.21			377,000	10,104		
6358EB	Red	85 to 140 / 5.9 to 9.6 17B1261X012 Green	85	5.9	1.7	0.12	10.0	0.69	2.0	0.14	290,000	7772		
			100	6.9	1.7	0.12	4.0	0.28			314,000	8415		
			125	8.6	2.2	0.15	4.0	0.28			380,000	10,184		
		6358EB	Red	130 to 200 / 9.0 to 13.8 17B1263X012 Blue	140	9.6	4.0	0.28	7.0	0.48	3.0	0.21	428,000	11,470
					150	10.3	4.0	0.28	7.0	0.48			454,000	12,167
					175	12.1	5.0	0.34	8.0	0.55			523,000	14,016
6358EB	Red	180 to 350 / 12.4 to 24.1 17B1264X012 Red	200	13.8	5.0	0.34	8.0	0.55	6.0	0.41	589,000	15,785		
			250	17.2	5.0	0.34	8.0	0.55			721,000	19,323		
			300	20.7	5.5	0.38	8.5	0.59			855,000	22,914		
6358EBH	Red	250 to 400 <sup>(5)</sup> / 17.2 to 27.6 <sup>(5)</sup> 17B1263X012 Blue	350	24.1	6.0	0.41	10.0	0.69	6.0	0.41	987,000	26,452		
			375	25.9	7.0	0.48	11.0	0.76			859,000	23,021		
											991,000	26,559		

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).  
 2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
 3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.  
 4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.  
 5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.



**Table 10. Type 63EG Relief Capacities for NPS 3 / DN 80 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING	
					psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h
3	80	6358	Yellow	10 to 40 / 0.69 to 2.8	10	0.69	3.5	0.24	9.0	0.62	5.0	0.34	185,000	4958
				1E392527022	15	1.0	1.3	0.09	4.0	0.28			185,000	4958
				Yellow	20	1.4	1.2	0.08	2.0	0.14			203,000	5440
					30	2.1	1.2	0.08	1.5	0.10			260,000	6968
		6358	Green	35 to 125 / 2.4 to 8.6	40	2.8	2.0	0.14	2.5	0.17	1.0	0.07	324,000	8683
				1K748527202	50	3.4	2.0	0.14	2.5	0.17			382,000	10,238
				Red	60	4.1	2.0	0.14	2.5	0.17			439,000	11,765
					80	5.5	2.0	0.14	2.5	0.17			555,000	14,874
		6358B	Yellow	10 to 30 / 0.69 to 2.1	10	0.69	3.5	0.24	9.0	0.62	2.0	0.14	185,000	4958
				1B788327022	15	1.0	1.3	0.09	4.0	0.28			185,000	4958
				Silver	20	1.4	1.2	0.08	2.0	0.14			203,000	5440
					30	2.1	1.2	0.08	1.5	0.10			260,000	6968
6358B	Green	30 to 60 / 2.1 to 4.1	30	2.1	1.6	0.11	2.0	0.14	3.0	0.21	263,000	7048		
		1B788327022	40	2.8	1.6	0.11	2.0	0.14			322,000	8630		
		Blue	50	3.4	2.0	0.14	2.5	0.17			379,000	10,157		
			60	4.1	2.0	0.14	2.5	0.17			439,000	11,765		
6358B	Red	60 to 125 / 4.1 to 8.6	60	4.1	2.0	0.14	2.5	0.17	3.0	0.21	553,000	14,820		
		1K748527202	80	5.5	2.0	0.14	2.5	0.17			670,000	17,956		
		Red	100	6.9	2.4	0.17	3.0	0.21			670,000	17,956		
			125	8.6	2.4	0.17	3.0	0.21			812,000	21,762		
6358EB	Red	85 to 140 / 5.9 to 9.6	85	5.9	1.7	0.12	3.0	0.21	3.0	0.21	584,000	15,651		
		17B1261X012	100	6.9	1.7	0.12	3.0	0.21			670,000	17,956		
		Green	125	8.6	2.2	0.15	3.5	0.24			815,000	21,842		
			140	9.7	2.2	0.15	3.5	0.24			900,000	24,120		
		130 to 200 / 9.0 to 13.8	140	9.6	4.0	0.28	6.0	0.41			914,000	24,495		
		17B1263X012	150	10.3	4.0	0.28	6.0	0.41			971,000	26,023		
6358EB	Red	Blue	175	12.1	5.0	0.34	7.0	0.48	1,119,000	29,989				
			200	13.8	5.0	0.34	7.0	0.48	1,261,000	33,795				
		180 to 350 / 12.4 to 24.1	200	13.8	5.0	0.34	7.0	0.48	1,261,000	33,795				
6358EB	Red	Red	250	17.2	5.0	0.34	7.0	0.48	1,546,000	41,433				
			300	20.7	5.5	0.38	7.5	0.52	1,833,000	49,124				
			350	24.1	5.5	0.38	7.5	0.52	1,833,000	49,124				
			350	24.1	5.5	0.38	7.5	0.52	2,117,000	56,736				
6358EBH	Red	250 to 400 <sup>(5)</sup> / 17.2 to 27.6 <sup>(5)</sup>	300	20.7	6.0	0.41	8.5	0.59	6.0	0.41	1,839,000	49,285		
		17B1263X012	350	24.1	6.0	0.41	8.5	0.59			2,123,000	56,896		
		Blue	375	25.9	7.0	0.48	9.5	0.66			2,271,000	60,863		

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).  
 2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
 3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.  
 4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.  
 5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.

# Type 63EG

## Relief Valve or Backpressure Regulator



**Table 11. Type 63EG Relief Capacities for NPS 4 / DN 100 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING	
					psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
4	100	6358	Yellow	10 to 40 / 0.69 to 2.8 1E392527022 Yellow	10	0.69	1.5	0.10	6.0	0.41	5.0	0.34	259,000	6941
					15	1.0	1.2	0.08	2.0	0.14			269,000	7209
					20	1.4	1.2	0.08	1.5	0.10			313,000	8388
					30	2.1	1.2	0.08	1.5	0.10			408,000	10,934
		6358	Green	35 to 125 / 2.4 to 8.6 1K748527202 Red	40	2.8	1.6	0.11	2.5	0.17	5.0	0.34	509,000	13,641
					50	3.4	1.6	0.11	2.5	0.17			600,000	16,080
					60	4.1	1.6	0.11	2.5	0.17			691,000	18,519
					80	5.5	2.0	0.14	2.5	0.17			873,000	23,396
		6358B	Yellow	10 to 30 / 0.69 to 2.1 1B788327022 Silver	10	0.69	1.5	0.10	6.0	0.41	1.0	0.07	259,000	6941
					15	1.0	1.2	0.08	2.0	0.14			269,000	7209
					20	1.4	1.2	0.08	1.5	0.10			313,000	8388
					30	2.1	1.2	0.08	1.5	0.10			408,000	10,934
6358B	Green	30 to 60 / 2.1 to 4.1 1B788327022 Blue	30	2.1	1.2	0.08	1.5	0.10	1.0	0.07	408,000	10,934		
			40	2.8							500,000	13,400		
			50	3.4							591,000	15,839		
			60	4.1							682,000	18,278		
6358B	Green	60 to 125 / 4.1 to 8.6 1K748527202 Red	60	4.1	1.6	0.11	2.0	0.14	1.0	0.07	686,000	18,385		
			80	5.5	2.0	0.14	2.5	0.17			870,000	23,316		
			100	6.9	2.4	0.17	3.0	0.21			1,054,000	28,247		
			125	8.6	2.4	0.17	3.0	0.21			1,278,000	34,250		
6358EB	Red	85 to 140 / 5.9 to 9.6 17B1261X012 Green	85	5.9	1.7	0.12	2.7	0.19	2.0	0.14	917,000	24,576		
			100	6.9	1.7	0.12	2.7	0.19			1,051,000	28,167		
			125	8.6	2.2	0.15	3.2	0.22			1,279,000	34,277		
	6358EB	Red	130 to 200 / 9.0 to 13.8 17B1263X012 Blue	140	9.6	4.0	0.28	5.5	0.38	3.0	0.21	1,434,000	38,431	
				150	10.3	4.0	0.28	5.5	0.38			1,524,000	40,843	
				175	12.1	5.0	0.34	6.5	0.45			1,757,000	47,088	
	6358EB	Red	180 to 350 / 12.4 to 24.1 17B1264X012 Red	200	13.8	5.0	0.34	6.5	0.45	3.0	0.21	1,980,000	53,064	
				250	17.2	5.0	0.34	6.5	0.45			2,428,000	65,070	
				300	20.7	5.5	0.38	7.0	0.48			2,880,000	77,184	
6358EBH	Red	250 to 400 <sup>(5)</sup> / 17.2 to 27.6 <sup>(5)</sup> 17B1263X012 Blue	300	20.7	6.0	0.41	8.0	0.55	6.0	0.41	2,889,000	77,425		
			350	24.1	6.0	0.41	8.0	0.55			3,337,000	89,432		
			375	25.9	7.0	0.48	9.0	0.62			3,569,000	95,649		

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).
2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.
4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.
5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.



**Table 12. Type 63EG Relief Capacities for NPS 6 / DN 150 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING						
					psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h					
6	150	6358	Yellow	10 to 40 / 0.69 to 2.8 1E392527022 Yellow	10 15 20 30	0.69 1.0 1.4 2.1	2.5 1.2 1.2 1.2	0.17 0.08 0.08 0.08	6.0 2.0 1.5 1.5	0.41 0.14 0.10 0.10	5.0	0.34	479,000 496,000 573,000 736,000	12,837 13,293 15,356 19,725					
				Green	35 to 125 / 2.4 to 8.6 1K748527202 Red	40 50 60 80 100 125	2.8 3.4 4.1 5.5 6.9 8.6	1.6 1.6 1.6 2.0 2.4 2.4	0.11 0.11 0.11 0.14 0.17 0.17	2.5 2.5 2.5 2.5 3.0 3.0			0.17 0.17 0.17 0.17 0.21 0.21	911,000 1,071,000 1,230,000 1,553,000 1,875,000 2,273,000	24,415 28,703 32,964 41,620 50,250 60,916				
					6358B	Yellow	10 to 30 / 0.69 to 2.1 1B788327022 Silver	10 15 20 30	0.69 1.0 1.4 2.1	2.5 1.2 1.2 1.2			0.17 0.08 0.08 0.08	6.0 2.0 1.5 1.5	0.41 0.14 0.10 0.10	1.0	0.07	479,000 496,000 573,000 736,000	12,837 13,293 15,356 19,725
							Green	30 to 60 / 2.1 to 4.1 1B788327022 Blue	30 40 50 60	2.1 2.8 3.4 4.1			1.2 1.2 1.2 1.2	0.08 0.08 0.08 0.08	1.5 1.5 1.5 1.5			0.10 0.10 0.10 0.10	736,000 895,000 1,055,000 1,214,000
		Red	60 to 125 / 4.1 to 8.6 1K748527202 Red			60 80 100 125		4.1 5.5 6.9 8.6	1.6 2.0 2.4 2.4	0.11 0.14 0.17 0.17	2.0 2.5 3.0 3.0	0.14 0.17 0.21 0.21	1,222,000 1,549,000 1,875,000 2,273,000	32,750 41,513 50,250 60,916					
			6358EB	Red		85 to 140 / 5.9 to 9.6 17B1261X012 Green	85 100 125 140	5.9 6.9 8.6 9.6	1.7 1.7 2.2 2.2	0.12 0.12 0.15 0.15	2.7 2.7 3.2 3.2	0.19 0.19 0.22 0.22	2.0	0.14	1,598,000 1,832,000 2,231,000 2,465,000			42,826 49,098 59,791 66,062	
		Blue			130 to 200 / 9.6 to 13.8 17B1263X012 Blue		140 150 175 200	9.6 10.3 12.1 13.8	4.0 4.0 5.0 5.0	0.28 0.28 0.34 0.34	5.5 5.5 6.5 6.5	0.38 0.38 0.45 0.45			3.0	0.21	2,501,000 2,657,000 3,062,000 3,453,000	67,027 71,208 82,062 92,540	
					Red		180 to 350 / 12.4 to 24.1 17B1264X012 Red	200 250 300 350	13.8 17.2 20.7 24.1	5.0 5.0 5.5 5.5	0.34 0.34 0.38 0.38	6.5 6.5 7.0 7.0			0.45 0.45 0.48 0.48	3.0	0.21	3,453,000 4,233,000 5,021,000 5,802,000	92,540 113,444 134,563 155,494
		6358EBH		Red		250 to 400 <sup>(5)</sup> / 17.2 to 27.6 <sup>(5)</sup> 17B1263X012 Blue	300 350 375	20.7 24.1 25.9	6.0 6.0 7.0	0.41 0.41 0.48	8.0 8.0 9.0	0.55 0.55 0.62	6.0	0.41	5,037,000 5,817,000 6,223,000	134,992 155,896 166,776			

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).  
 2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
 3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.  
 4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.  
 5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.

# Type 63EG

## Relief Valve or Backpressure Regulator



**Table 13. Type 63EG Relief Capacities for NPS 8 x 6 / DN 200 x 150 Body with 2:1 Line Size to Body Size Piping**

MAIN VALVE SIZE		PILOT TYPE	MAIN VALVE SPRING COLOR	PILOT SPRING RANGE, PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESET PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING	
					psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h
8 x 6	200 x 150	6358	Yellow	10 to 40 / 0.69 to 2.8 1E392527022 Yellow	10	0.69	2.5	0.17	6.0	0.41	5.0	0.34	660,000	17,688
				15	1.0	1.2	0.08	2.0	0.14	684,000			18,331	
				20	1.4	1.2	0.08	1.5	0.10	791,000			21,199	
				30	2.1	1.2	0.08	1.5	0.10	1,019,000			27,309	
		Green	35 to 125 / 2.4 to 8.6 1K748527202 Red	40	2.8	1.6	0.11	2.5	0.17	5.0	0.34	1,262,000	33,822	
			50	3.4	1.6	0.11	2.5	0.17	1,482,000			39,718		
			60	4.1	1.6	0.11	2.5	0.17	1,703,000			45,640		
			80	5.5	2.0	0.14	2.5	0.17	2,144,000			57,459		
		6358B	Yellow	10 to 30 / 0.69 to 2.1 1B788327022 Silver	10	0.69	2.5	0.17	6.0	0.41	1.0	0.07	660,000	17,688
				15	1.0	1.2	0.08	2.0	0.14	684,000			18,331	
				20	1.4	1.2	0.08	1.5	0.10	791,000			21,199	
				30	2.1	1.2	0.08	1.5	0.10	1,019,000			27,309	
Green	30 to 60 / 2.1 to 4.1 1B788427022 Blue	30	2.1	1.2	0.08	1.5	0.10	1.0	0.07	1,019,000	27,309			
	40	2.8	1.2	0.08	1.5	0.10	1,240,000			33,232				
	50	3.4	1.2	0.08	1.5	0.10	1,460,000			39,128				
	60	4.1	1.2	0.08	1.5	0.10	1,681,000			45,051				
6358EB	Red	60 to 125 / 4.1 to 8.6 1K748527202 Red	60	4.1	1.6	0.11	2.0	0.14	1.0	0.07	1,692,000	45,346		
		80	5.5	2.0	0.14	2.5	0.17	1,244,000			57,459			
		100	6.9	2.4	0.17	3.0	0.21	2,596,000			69,573			
		125	8.6	2.4	0.17	3.0	0.21	3,148,000			84,366			
6358EB	Red	85 to 140 / 5.9 to 9.6 17B1261X012 Green	85	5.9	1.7	0.12	2.7	0.19	2.0	0.14	2,259,000	60,541		
		100	6.9	1.7	0.12	2.7	0.19	2,590,000			69,412			
		125	8.6	2.2	0.15	3.2	0.22	3,152,000			84,474			
		140	9.6	2.2	0.15	3.2	0.22	3,483,000			93,344			
	Red	130 to 200 / 9.0 to 13.8 17B1263X012 Blue	140	9.6	4.0	0.28	5.5	0.38	3.0	0.21	3,534,000	94,711		
		150	10.3	4.0	0.28	5.5	0.38	3,754,000			100,607			
Red	175	12.1	5.0	0.34	6.5	0.45	3.0	0.21	4,328,000	115,990				
	200	13.8	5.0	0.34	6.5	0.45			4,879,000	130,757				
6358EBH	Red	180 to 350 / 12.4 to 24.1 17B1264X012 Red	200	13.8	5.0	0.34	6.5	0.45	3.0	0.21	4,879,000	130,757		
		250	17.2	5.0	0.34	6.5	0.45	5,982,000			160,318			
		300	20.7	5.5	0.38	7.0	0.48	7,096,000			190,173			
350	24.1	5.5	0.38	7.0	0.48	8,199,000	219,733							

1. Capacities based on set pressure plus buildup to achieve full opening using a standard linear cage and standard high-gain pilot restriction (or restriction plug on Type 6358).
2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.
4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.
5. Set pressure plus buildup should not exceed maximum differential pressure of 400 psi / 27.6 bar.



**Table 14. Type 1098-63EGR Relief Capacities with 1:1 Line Size Body Piping**


BODY SIZE		SET PRESSURE RANGE, SPRING PART NUMBER AND COLOR, psig / bar	PILOT SET PRESSURE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(3)</sup>		BUILDUP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(4)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESEAT PILOT		CAPACITIES <sup>(1)</sup> OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 1:1 LINE SIZE TO BODY SIZE PIPING					
NPS	DN		psig	bar	psig	bar	psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h				
1	25	3 to 18 / 0.21 to 1.2 1B986027212 Green	3 5 10 15	0.21 0.34 0.69 1.0	0.7	0.048	1.0	0.07	1.0	0.07	10,000	268				
		15 to 40 / 1.0 to 2.8 1E392527022 Yellow	15 20 30 40	1.0 1.4 2.1 2.8							0.8	0.055	1.1	0.076	22,000	590
		35 to 65 / 2.4 to 4.5 1K748527202 Red	40 50 60 65	2.8 3.4 4.1 4.5							1.2	0.08	1.6	0.11	43,000	1152
2	50	3 to 18 / 0.21 to 1.2 1B986027212 Green	3 5 10 15	0.21 0.34 0.69 1.0	0.9	0.062	1.3	0.09			40,000	1072				
		15 to 40 / 1.0 to 2.8 1E392527022 Yellow	15 20 30 40	1.0 1.4 2.1 2.8							0.8	0.055	1.1	0.076	84,000	2251
		35 to 65 / 2.4 to 4.5 1K748527202 Red	40 50 60 65	2.8 3.4 4.1 4.5							1.3	0.09	1.7	0.12	164,000	4395
3	80	3 to 18 / 0.21 to 1.2 1B986027212 Green	3 5 10 15	0.21 0.34 0.69 1.0	0.9	0.062	1.5	0.10			48,000	1260				
		15 to 40 / 1.0 to 2.8 1E392527022 Yellow	15 20 30 40	1.0 1.4 2.1 2.8							0.8	0.055	1.1	0.076	101,000	2707
		35 to 65 / 2.4 to 4.5 1K748527202 Red	40 50 60 65	2.8 3.4 4.1 4.5							1.3	0.09	1.7	0.12	224,000	6003
4	100	3 to 18 / 0.21 to 1.2 1B986027212 Green	3 5 10 15	0.21 0.34 0.69 1.0	1.3	0.09	2.3	0.16			138,000	1796				
		15 to 40 / 1.0 to 2.8 1E392527022 Yellow	15 20 30 40	1.0 1.4 2.1 2.8							0.9	0.062	1.2	0.08	270,000	7236
		35 to 65 / 2.4 to 4.5 1K748527202 Red	40 50 60 65	2.8 3.4 4.1 4.5							1.4	0.097	1.8	0.12	486,000	13,025
6	150	3 to 18 / 0.21 to 1.2 1B986027212 Green	3 5 10 15	0.21 0.34 0.69 1.0	1.7	0.12	6.4	0.44	173,000	4636						
		15 to 40 / 1.0 to 2.8 1E392527022 Yellow	15 20 30 40	1.0 1.4 2.1 2.8					0.9	0.062	1.2	0.08	331,000	8871		
		35 to 65 / 2.4 to 4.5 1K748527202 Red	40 50 60 65	2.8 3.4 4.1 4.5					1.5	0.10	1.9	0.13	456,000	12,221		

1. Capacities based on set pressure plus buildup to achieve full opening using a size 40 actuator, green main spring, standard linear cage, and standard high-gain pilot restriction.  
 2. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
 3. Crack point of the main valve is the inlet pressure buildup over the set pressure at which the main valve starts audible flow.  
 4. Inlet pressure buildup over the set pressure for the main valve to achieve wide-open capacity.


# Type 63EG

Relief Valve or Backpressure Regulator

FISHER™



STANDARD PILOT SPRING CASE IS 1/4 NPT TAPPED WITH REMOVABLE VENT INSTALLED



15A8029\_E

In. /  
mm


TYPE 63EG WITH 6358 SERIES PILOT

NOTE:  
FOR DIMENSIONS OF RELIEF VALVES WITH EN (OR OTHER) END CONNECTIONS, CONSULT THE LOCAL SALES OFFICE.

Figure 5. Dimensions







TYPE 1098-63EGR WITH 6358B SERIES PILOT

15A8031\_M

NOTE:  
FOR DIMENSIONS OF RELIEF VALVES WITH EN (OR OTHER) END CONNECTIONS, CONSULT THE LOCAL SALES OFFICE.

Figure 5. Dimensions (continued)

Table 15. Dimension																											
BODY SIZE		COMMON DIMENSION																		DIMENSION SPECIFIC FOR TYPE 63EG			DIMENSION SPECIFIC FOR TYPE 1098-63EGR				
		A										D (With Travel Indicator)	E (Without Travel Indicator)	G		V		H	M	AR							
		NPT		Cast Iron			Steel/Stainless Steel																				
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm		
1	25	8.25	209	7.25	184	7.75	197	7.25	184	7.75	197	8.25	209	8.19	208	4.94	125	2.19	55.6	11.38	289	5.44	138	7.25	184	3.00	76.2
2	50	11.25	286	10	254	10.5	267	10	254	10.5	267	11.25	286	8.69	221	5.44	138	2.84	72.1	12.62	320	5.94	151	7.69	195	3.12	79.2
3	80	----	----	11.75	298	12.5	317	11.75	298	12.5	317	13.25	337	11.25	286	7.00	178	3.5	88.9	16.25	413	7.25	184	8.19	208	3.88	98.6
4	100	----	----	13.88	353	14.5	368	13.88	353	14.5	368	15.5	394	12.62	321	8.38	213	4.81	122	18.88	479	8.62	219	8.88	226	5.12	130
6	150	----	----	17.75	451	18.62	473	17.75	451	18.62	473	20	508	13.44	341	9.19	233	5.19	132	20	508	8.81	224	14.56	370	6.62	168
8 x 6	200 x 150	----	----	----	----	----	----	21.38	543	22.38	568	24	610	15.00	381	10.75	273	7.19	183	23.5	597	10.5	267	14.56	370	6.62	168
12 x 6	300 x 150	----	----	----	----	----	----	29	737	30.5	775	32.3	820	17.72	450	13.47	342	10	254	23.5	597	13.2	335	14.56	370	6.62	168

# Type 63EG

Relief Valve or Backpressure Regulator

FISHER™

## Ordering Guide

### Type (Select One)

- 63EG\*\*\*
- 1098-63EGR\*\*

### Body Size (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 x 6 / DN 200 x 150\*\*\*
- NPS 12 x 16 / DN 300 x 150

### End Connection Style (Select One)

#### Cast Iron

- NPT (available in NPS 1 or 2 / DN 25 or 50 body size only)\*\*\*
- CL125 FF\*\*\*

#### Steel, Stainless Steel and Other Alloys

- NPT (available in NPS 1 or 2 / DN 25 or 50 body size only)\*\*\*
- SWE (available in NPS 1 or 2 / DN 25 or 50 body size only)\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- BWE\*\*
- PN 16/25/40 \_\_\_\_\_ (please specify)\*

### Body and Flange Material (Select One)

- Cast iron\*\*\*
- Steel\*\*\*
- Stainless steel\*\*\*

### Cage Material (Select One)

- Linear, Stainless steel\*\*\*
- Whisper Trim™, 416 Stainless steel\*\*\*
- Whisper Trim, 316 Stainless steel\*\*\*
- Quick-Open, 316 Stainless steel\*\*\*

### Seat Ring and Valve Plug Material (Select One)

- 410/416 Stainless steel\*\*\*
- 316 Stainless steel\*

### Gasket and O-ring Material (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*\*
- Ethylenepropylene (EPR)\*\*\*

### Main Valve Spring (Select One)

#### Type 63EG

- Yellow (NPS 1 / DN 25 not available)
- Green
- Red

#### Type 1098-63EGR

- Green
- Yellow

### Set Pressure Range (Select One)

#### Type 63EG

##### Type 6358 Backpressure

- 10 to 40 psig / 0.69 to 2.8 bar, Yellow
- 35 to 125 psig / 2.4 to 8.6 bar, Red

##### Type 6358B Relief

- 10 to 30 psig / 0.69 to 2.1 bar, Silver
- 30 to 60 psig / 2.1 to 4.1 bar, Blue
- 60 to 125 psig / 4.1 to 8.6 bar, Red

##### Type 6358EB Relief

- 85 to 140 psig / 5.9 to 9.6 bar, Green
- 130 to 200 psig / 9.0 to 13.8 bar, Blue
- 180 to 350 psig / 12.4 to 24.1 bar, Red

##### Type 6358EBH Relief

- 250 to 400 psig / 17.2 to 27.6 bar, Blue

#### Type 1098-63EGR

##### Type 6358B

- 3 to 18 psig / 0.21 to 1.2 bar, Green
- 15 to 40 psig / 1.0 to 2.8 bar, Yellow
- 35 to 65 psig / 2.4 to 4.5 bar, Red

### Pilot Body Material (for Types 6358 and 6358B only) (Select One)

- Aluminum (for Types 6358 and 6358B only)\*\*\*
- Stainless steel\*\*\*

### Pilot Diaphragm and O-ring Material (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*

### Travel Indicator (Optional)

- Yes\*\*

### Tubing and Fittings (Select One)

- Stainless steel tubing and steel fittings\*\*\*
- Stainless steel tubing and Stainless steel fittings\*\*\*

- continued -

## Ordering Guide (continued)

**Pilot Supply Filter (Optional)**

**Type 252**  
**Aluminum Construction**

- Standard length without drain valve
- Standard length with drain valve
- Extended length without drain valve
- Extended length with drain valve

**Stainless Steel Construction**

- Standard length without drain valve
- Standard length with drain valve
- Extended length without drain valve
- Extended length with drain valve

**P590 Series Pilot Supply Filter (Optional)**

Type P594-1 brass filter

**Pressure Gauge (Optional)**

- Pressure gauge for Type 63EG
- Pressure gauge for Type 1098-63EGR

**Special Cleaning Services (Optional)**

- Pure Gas
- Oxygen

**NACE Construction (Optional)**

Yes

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

**Quick Change Trim Package (Optional)**

Yes, send one trim package to match this order.

**Main Valve Parts Kit (Optional)**

Yes, send one parts kit to match this order.

**Pilot Parts Kit (Optional)**

Yes, send one parts kit to match this order.

**Wireless Position Monitor Mounting Kit (Optional)**

Yes, send one mounting kit for mounting the Topworx™ 4310 or the Fisher™ 4320 wireless position monitor (requires Travel Indicator option).

Specification Worksheet
<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**

Adequate overpressure protection should be installed to protect the regulator from overpressure. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure.

# 66 Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The 66 Series direct-operated pressure reducing regulators are widely used in burner control and other applications where precise control of low-pressure industrial gases is needed.

### Body Sizes and End Connection Styles

See Table 1

### Spring Case Vent

3/4 NPT **standard** with removable Type Y602-10 vent assembly

### Flow Coefficients

See Table 3

### IEC Sizing Coefficients

$X_r$ : 0.775

$F_D$ : NPS 2 / DN 50: 0.35

NPS 3 / DN 80: 0.34

NPS 4 / DN 100: 0.30

$F_L$ : 0.89

### Maximum Inlet Pressures

#### Emergency Inlet Pressure:

25 psig / 1.7 bar

#### Maximum Pressure to Avoid Internal Parts Damage:

10 psig / 0.69 bar

### Maximum Outlet (Casing) Pressure

8 psig / 0.55 bar

### Outlet Pressure Ranges

2 in. w.c. to 5 psig / 5 mbar to 0.34 bar in 11 ranges

See Table 4

### Pressure Registrations

#### Cast Iron Body:

Internal (**standard**) or external

#### Steel Body:

External (**standard**) or internal

### Material Temperature Capabilities

#### Nitrile (NBR) (standard):

-40 to 180°F / -40 to 82°C

#### Fluorocarbon (FKM):

0 to 350°F / -18 to 177°C

Ethylene propylene (EPDM):

-40 to 275°F / -40 to 135°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/19

### Features

- Sensitive Response to Pressure Changes
- Seat Protection Without Sacrifice in Shutoff Capability
- Accuracy
- Application Flexibility
- Severe Service and Sour Gas Capability





Figure 1. Type 66 Pressure Reducing Regulator



A6550

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

Figure 2. Type 66 Operational Schematic

**Table 1. Body Size and End Connection Style**

BODY SIZE		BODY MATERIAL	
NPS	DN	Cast Iron	Steel
2	50	NPT or CL125 FF	NPT, CL150 FF, CL150 RF or CL300 RF
3 and 4	80 and 100	CL125 FF	CL150 RF

**Table 2. Construction Material**

BODY	SPRING CASE	DIAPHRAGM PLATE	DIAPHRAGM AND VALVE PLUG O-RING	GASKET	TRIM
Cast iron (standard), Steel, or 316 Stainless steel	Steel or 304 Stainless steel (optional)	Plated steel	Nitrile (NBR) (standard), Fluorocarbon (FKM) (high-temperature), Ethylenepropylene (EPDM), Polytetrafluoroethylene (PTFE)	Composition and Neoprene (CR)	Brass or 316 Stainless steel

**Table 3. Flow Coefficient**

OUTLET PRESSURE RANGE		DROOP		REGULATING C <sub>g</sub>			REGULATING C <sub>v</sub>			WIDE-OPEN C <sub>g</sub>			WIDE-OPEN C <sub>v</sub>			C <sub>1</sub>
psig	bar	psig	mbar	NPS 2 / DN 50	NPS 3 / DN 80	NPS 4 / DN 100	NPS 2 / DN 50	NPS 3 / DN 80	NPS 4 / DN 100	NPS 2 / DN 50	NPS 3 / DN 80	NPS 4 / DN 100	NPS 2 / DN 50	NPS 3 / DN 80	NPS 4 / DN 100	
				0.75 to 1.5	0.05 to 0.10	0.2 0.3	10 20	765 1150	1865 2800	3330 5000	21.9 32.9	53.3 80	95.1 143	1260	3400	
1 to 2	0.07 to 0.14	0.3 0.4	20 30	825 1100	1650 2200	3150 4200	23.6 31.4	47.1 62.9	90 120							
1.5 to 3	0.10 to 0.21	0.4 0.6	30 40	665 1000	1165 1750	2500 3750	19 28.6	33.3 50	71.4 107							
3 to 5	0.21 to 0.34	0.6 0.8 1.0	40 60 70	540 720 900	725 970 1210	----	15.4 20.6 25.7	20.7 27.7 34.6	----							

**Table 4. Outlet Pressure Range**

BODY SIZE		OUTLET PRESSURE RANGE		CONTROL SPRING INFORMATION																						
NPS	DN	In. w.c.	mbar	Part Number	Color	Free Length		Wire Diameter																		
						In.	mm	In.	mm																	
2	50	4 to 11 <sup>(1)</sup> 8 to 28 <sup>(1)</sup> 2 to 5 4 to 8	10 to 27 <sup>(1)</sup> 20 to 70 <sup>(1)</sup> 5 to 12 10 to 20	0B019727052 1E611427022 1D892527022 1D892627022	Purple Stripe Orange Stripe Brown Stripe Red Stripe	6.00 6.00 6.12 7.53	152 152 155 191	0.148 0.200 0.109 0.112	3.76 5.08 2.77 2.85	35																
											7 to 12 10 to 17 14 to 28	17 to 30 25 to 42 35 to 70	1D892727012 1D892827032 1D892927032	Black Stripe Orange Stripe Purple Stripe	7.88 7.75 7.53	200 197 191	0.130 0.148 0.162	3.30 3.76 4.12								
																			0.75 to 1.5 psig 1 to 2 psig 1.5 to 3 psig 3 to 5 psig	0.05 to 0.10 bar 0.07 to 0.14 bar 0.10 to 0.21 bar 0.21 to 0.34 bar	1D765727032 <sup>(2)</sup> 1D765827032 <sup>(2)</sup> 1D962627032 <sup>(2)</sup> 1N506427142 <sup>(3)</sup>	Red Stripe Unpainted Unpainted Black Stripe	6.09 6.00 6.25 6.31	155 152 159 160	0.207 0.225 0.262 0.283	5.26 5.72 6.66 7.19
		7 to 12 10 to 17 14 to 28	17 to 30 25 to 42 35 to 70	1D892827032 1D893227032 1D89327032	Orange Stripe White Stripe Green Stripe	7.75 7.50 7.25	197 191 184	0.148 0.156 0.182	3.76 3.96 4.62																	
											0.75 to 1.5 psig 1 to 2 psig 1.5 to 3 psig 3 to 5 psig	0.05 to 0.10 bar 0.07 to 0.14 bar 0.10 to 0.21 bar 0.21 to 0.34 bar	1D765827032 <sup>(2)</sup> 1D962627032 <sup>(2)</sup> 1E204427032 <sup>(2)</sup> 1N506527142 <sup>(3)</sup>	Unpainted Unpainted White and Red Stripe Brown and Purple Stripe	6.00 6.25 6.38 6.38	152 159 162 162	0.225 0.262 0.306 0.362	5.72 6.66 7.77 9.20								
																			4 to 11 <sup>(1)</sup> 8 to 28 <sup>(1)</sup> 2 to 5 4 to 8	10 to 27 <sup>(1)</sup> 20 to 70 <sup>(1)</sup> 5 to 12 10 to 20	1D527527022 1D527627032 1D892627022 1D893427022	Gray Stripe Gray and White Stripe Red Stripe Green Stripe	7.75 7.75 7.53 7.75	197 197 191 197	0.170 0.225 0.112 0.135	4.32 5.72 2.85 3.43
		7 to 12 10 to 17 14 to 28	17 to 30 25 to 42 35 to 70	1D893227032 1D893527032 1D893627032	White Stripe Yellow Stripe Light Blue Stripe	7.50 7.75 7.81	191 197 198	0.156 0.170 0.207	3.96 4.32 5.26																	

1. 1 psi / 0.07 bar minimum differential pressure required with this range.  
 2. Heavy head construction required.  
 3. Extra heavy head construction required.

# 66 Series

## Pressure Reducing Regulator



**Table 5. 66 Series Flow Capacities**

BODY SIZE, In. / DN	OUTLET PRESSURE RANGE AND PART NUMBER, In. w.c. / mbar	OUTLET PRESSURE SETTING, In. w.c. / mbar	ACCURACY RANGE, In. w.c. / mbar	CAPACITIES IN SCFH / Nm <sup>3</sup> /H OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
				Inlet Pressure Capacities Based on D (Droop) or B (Boost)							
				8.3 in. w.c. / 20 mbar	11.1 in. w.c. / 30 mbar	20.8 in. w.c. / 50 mbar	1.0 psig / 0.07 bar	1.5 psig / 0.10 bar	2.0 psig / 0.14 bar	3.0 psig / 0.21 bar	5 to 10 psig / 0.34 to 0.69 bar
2 / 50	2 to 5 / 5 to 12 1D892527022	2.0 / 5	-1/2 to 3/4 / -1 to 2	4900 / 131 D	6700 / 180 D	8250 / 221 D	10,000 / 268 D	9300 / 249 B	9150 / 245 B	8500 / 228 B	8500 / 228 B
		4.0 / 10		3900 / 105 D	6200 / 166 D	7850 / 210 D	9550 / 256 D	11,750 / 315 B	10,800 / 289 B	10,800 / 289 B	10,300 / 276 B
	4 to 8 / 10 to 20 1D892627022	6.0 / 15	-3/4 to 1-1/8 / -2 to 3	2840 / 76.1 D	5800 / 155 D	7600 / 204 D	9550 / 256 D	12,100 / 324 D	13,500 / 362 B	10,800 / 289 B	10,300 / 276 B
		9.0 / 22		----	3200 / 85.8 D	6450 / 173 D	8700 / 233 D	11,100 / 297 D	13,400 / 359 B	15,100 / 405 B	13,400 / 359 B
	7 to 12 / 17 to 30 1D892727012	12 / 30	-1-1/4 to 1-7/8 / -3 to 5	----	----	4500 / 121 D	6450 / 173 D	10,600 / 284 D	13,300 / 356 D	15,500 / 415 D	13,900 / 373 B
		16 / 40		----	----	----	4650 / 125 D	9000 / 241 D	12,900 / 346 D	16,750 / 449 D	16,450 / 441 B
	14 to 28 / 35 to 70 1D892927032	20 / 50	-2 to 3 / -5 to 7	----	----	----	----	8400 / 225 D	12,250 / 328 D	16,100 / 431 B	18,000 / 482 B
24 / 60		----		----	----	----	7750 / 208 D	11,600 / 311 D	15,500 / 415 D	20,000 / 536 B	
28 / 70		----		----	----	----	----	----	12,900 / 346 D	20,000 / 536 B	
3 / 80	2 to 5 / 5 to 12 1D893027022	2.0 / 5	-1/2 to 3/4 / -1 to 2	9000 / 241 D	12,900 / 346 D	15,500 / 415 D	21,300 / 571 D	26,400 / 708 D	29,600 / 793 B	25,100 / 673 B	23,200 / 622 B
		4.0 / 10		8700 / 233 D	12,900 / 346 D	15,500 / 415 D	21,300 / 571 D	26,400 / 708 D	29,600 / 793 B	25,100 / 673 B	23,200 / 622 B
	4 to 8 / 10 to 20 1D893127012	6.0 / 15	-3/4 to 1-1/8 / -2 to 3	6125 / 164 D	12,250 / 328 D	16,750 / 449 D	18,000 / 482 D	23,200 / 622 D	30,000 / 804 B	36,100 / 967 B	31,000 / 831 B
		9.0 / 22		----	8250 / 221 D	12,900 / 346 D	18,000 / 482 D	23,200 / 622 D	33,500 / 898 D	37,400 / 1002 D	46,400 / 1244 D
	7 to 12 / 17 to 30 1D892827032	12 / 30	-1-1/4 to 1-7/8 / -3 to 5	----	----	8400 / 225 D	14,200 / 381 D	20,600 / 552 D	28,400 / 761 D	36,750 / 985 D	46,400 / 1244 D
		16 / 40		----	----	----	7750 / 208 D	18,000 / 482 D	23,200 / 622 D	36,100 / 967 D	49,000 / 1313 D
	14 to 28 / 35 to 70 1D893327032	20 / 50	-2 to 3 / -5 to 7	----	----	----	----	12,900 / 346 D	20,600 / 552 D	32,200 / 863 D	46,400 / 1244 D
24 / 60		----		----	----	----	11,600 / 311 D	19,300 / 517 D	25,800 / 691 D	46,400 / 1244 D	
28 / 70		----		----	----	----	----	----	23,200 / 622 D	46,400 / 1244 D	
4 / 100	2 to 5 / 5 to 12 1D892627022	2.0 / 5	-1/2 to 3/4 / -1 to 2	15,500 / 415 D	23,200 / 622 D	28,400 / 761 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B
		4.0 / 10		15,500 / 415 D	23,200 / 622 D	28,400 / 761 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B	36,100 / 967 B
	4 to 8 / 10 to 20 1D893427022	6.0 / 15	-3/4 to 1-1/8 / -2 to 3	11,600 / 311 D	18,000 / 482 D	24,500 / 657 D	34,800 / 933 D	38,700 / 1037 B	43,800 / 1174 B	43,000 / 1152 B	43,800 / 1174 B
		9.0 / 22		----	12,900 / 346 D	20,600 / 552 D	33,500 / 898 D	41,300 / 1107 D	51,500 / 1380 B	51,500 / 1380 B	51,500 / 1380 B
	7 to 12 / 17 to 30 1D893227032	12 / 30	-1-1/4 to 1-7/8 / -3 to 5	----	----	12,900 / 346 D	22,600 / 606 D	38,700 / 1037 D	51,500 / 1380 D	58,000 / 1554 D	56,700 / 1520 D
		16 / 40		----	----	----	20,600 / 552 D	36,100 / 967 D	51,500 / 1380 D	64,500 / 1729 D	61,800 / 1656 D
	14 to 28 / 35 to 70 1D893627032	20 / 50	-2 to 3 / -5 to 7	----	----	----	----	27,000 / 724 D	46,400 / 1244 D	61,800 / 1656 D	71,000 / 1903 D
24 / 60		----		----	----	----	----	41,300 / 1107 D	61,800 / 1656 D	77,500 / 2077 D	
28 / 70		----		----	----	----	----	----	58,000 / 1554 D	77,500 / 2077 D	






Figure 3. Dimensions

Table 6. Dimension																	
BODY SIZE		A								C		E		G			
		NPT Cast Iron Body		NPT Steel Body		CL125 FF Cast Iron or CL150 RF <sup>(1)</sup> Steel Body		CL300 RF Steel Body						NPT Steel Body		All Other	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
2	50	7.25	184	9.25	235	10.00	254	10.50	267	13.88	353	15.00	381	3.31	84.1	3.25	82.6
3	80	----	----	----	----	11.75	298	----	----	16.00	406	17.62	448	----	----	4.62	117
4	100	----	----	----	----	13.88	353	----	----	18.00	457	21.25	540	----	----	5.38	137

1. Dimension also is same for NPS 2 / DN 50 CL150 FF steel body.

Table 7. Shipping Weight					
BODY SIZE		APPROXIMATE SHIPPING WEIGHT			
		NPT End		Flanged End	
NPS	DN	LB	kg	LB	kg
2	50	50	22.7	55	25
3	80	----	----	100	45.4
4	100	----	----	155	70.3

# 66 Series

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Body, Body Size and End Connection Style (Select One)

#### Cast Iron Body

- 2 NPT\*\*
- NPS 2 / DN 50, CL125 FF\*\*
- NPS 3 / DN 80, CL125 FF\*\*
- NPS 4 / DN 100, CL125 FF\*\*

#### Steel Body (External Pressure Registration Only)

- 2 NPT\*\*
- NPS 2 / DN 50, CL150 FF\*\*
- NPS 2 / DN 50, CL150 RF\*\*
- NPS 2 / DN 50, CL300 RF\*\*
- NPS 3 / DN 80, CL150 RF\*\*
- NPS 4 / DN 100, CL150 RF\*\*

### Outlet Pressure Range (Select One)

- 2 to 5 in. w.c. / 5 to 12 mbar\*\*
- 4 to 8 in. w.c. / 10 to 20 mbar\*\*
- 4 to 11 in. w.c. / 10 to 27 mbar\*\*
- 7 to 12 in. w.c. / 17 to 30 mbar\*\*
- 8 to 28 in. w.c. / 20 to 70 mbar\*\*
- 10 to 17 in. w.c. / 25 to 42 mbar\*\*
- 14 to 28 in. w.c. / 35 to 70 mbar\*\*
- 0.75 to 1.5 psig / 0.05 to 0.10 bar\*\*
- 1 to 2 psig / 0.07 to 0.14 bar\*\*
- 1.5 to 3 psig / 0.10 to 0.21 bar\*\*
- 3 to 5 psig / 0.21 to 0.34 bar\*\*  
(not available in NPS 4 / DN 100 body)\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Trim Material (Select One)

- Brass\*\*
- 316 Stainless steel\*\*

### Pressure Registration (Select One)

- Internal (cast iron) (standard)\*\*
- External (required for steel, optional for cast iron)\*\*

### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

When a regulator appears unable to pass the published flow rate, be sure to check the inlet pressure measured at the regulator body inlet connection. Piping up to and away from regulators can cause significant flowing pressure losses.





### Introduction

The 67C Series regulators are typically used to provide constantly controlled, reduced pressure to pneumatic and electro-pneumatic controllers and other instruments. These direct-operated regulators are suitable for most air or gas applications. Other applications include providing reduced pressure to air chucks, air jets and spray guns.

### Body Size, Inlet and Outlet Connection Style

1/4 NPT

### Maximum Inlet Pressure (Body Rating)

Types 67C, 67CR, 67CF, 67CFR, 67CFS and 67CFSR: 250 psig / 17.2 bar  
Types 67CS and 67CSR: 400 psig / 27.6 bar

### Outlet Pressure Ranges

See Table 1

### Maximum Emergency Outlet Pressure

50 psi / 3.4 bar over outlet pressure setting

### Wide-Open Flow Coefficients

Main Valve:  $C_g$ : 11.7;  $C_v$ : 0.36;  $C_f$ : 32.2

Internal Relief Valve:  $C_g$ : 1.45;  $C_v$ : 0.045;  $C_f$ : 32.8

### IEC Sizing Coefficients

Main Valve:  $X_r$ : 0.66;  $F_D$ : 0.50;  $F_L$ : 0.89

### Types 67CR, 67CSR, 67CFR and 67CFSR Internal Relief Performance

Low capacity for minor seat leakage only; other overpressure protection must be provided if inlet pressure can exceed the maximum pressure rating of downstream equipment or exceeds maximum outlet pressure rating of the regulator.

### Pressure Registration

Internal

### Temperature Capabilities

#### With Nitrile (NBR)

Standard Bolting: -20 to 180°F / -29 to 82°C

Stainless Steel Bolting: -40 to 180°F / -40 to 82°C

#### With Fluorocarbon (FKM):

Polyethylene Filter<sup>(1)</sup> (standard): 0 to 180°F / -18 to 82°C

Polyvinylidene (PVDF), Stainless steel or Glass Filter (Optional): 0 to 300°F / -18 to 149°C

#### With Silicone (VMQ)<sup>(2)</sup> Diaphragm and Low Temperature Bolting:

-60 to 180°F / -51 to 82°C

With Gauges: -40 to 180°F / -40 to 82°C

### Types 67CF, 67CFR, 67CFS and 67CFSR Filter Capabilities

Free Area: 12 times pipe area

#### Micron Rating:

Polyethylene Filter<sup>(1)</sup> (standard): 5 microns

Glass Fiber Filter (Optional): 5 microns

PVDF Filter (Optional): 40 microns

Stainless Steel Filter (Optional): 40 microns

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/19

### Features

- Designed for Digital Instrumentation
- Optional Smart Bleed™ Construction
- Optional Stainless Steel Construction
- Compact and Light Weight
- No Air Loss
- Easy Maintenance
- Optional Integral Filter
- Optional Internal Relief Valve
- Rugged Construction



W8438

Figure 1. 67C Series Instrument Supply Regulator



W7412

Figure 2. 67CF Series Filter Regulator shown with Optional Pressure Gauge




Figure 3. 67C Series Operational Schematics

**Table 1. Outlet Pressure Range and Control Spring Data**

TYPE	OUTLET PRESSURE RANGE		CONTROL SPRING DATA						
			Color	Material	Part Number	Wire Diameter		Free Length	
	psig	bar				In.	mm	In.	mm
67C, 67CR, 67CF and 67CFR	0 to 20	0 to 1.4	Green stripe	Music Wire	GE07809T012	0.135	3.43	1.43	36.2
	0 to 35	0 to 2.4	Silver		T14059T0012	0.156	3.96		
	0 to 60	0 to 4.1	Blue stripe		T14058T0012	0.170	4.32		
	0 to 125	0 to 8.6	Red stripe		T14060T0012	0.207	5.26		
67CS, 67CSR, 67CFS and 67CFSR	0 to 35	0 to 2.4	Silver stripe	Inconel®	T14113T0012	0.156	3.96	1.43	36.2
	0 to 60	0 to 4.1	Blue		T14114T0012	0.172	4.37		
	0 to 125	0 to 8.6	Red		T14115T0012	0.207	5.26		
	0 to 150	0 to 10.3	Black		T141730X012	0.250	6.35		

**Table 2. 67C Series Construction Material**

PART NAME	TYPE			
	67C and 67CR	67CF and 67CFR	67CS and 67CSR	67CFS and 67CFSR
BODY AND SPRING CASE	Aluminum (ASTM B85/Alloy 380)		CF8M/CF3M Stainless steel	
BOTTOM PLATE	316 Stainless steel	----	316 Stainless steel	----
PUSHER POST AND VALVE CARTRIDGE	Polyester resin			
UPPER SPRING SEAT	Zinc-plated Steel		316 Stainless steel	
LOWER SPRING SEAT, DIAPHRAGM PLATE	Chromate conversion coated aluminum		316 Stainless steel	
CONTROL SPRING	Plated Steel or Inconel® (NACE)		Inconel®	
VALVE PLUG	Brass stem with Nitrile (NBR) plug, Aluminum stem with Nitrile (NBR) or Fluorocarbon (FKM) plug, or Stainless steel stem with Nitrile (NBR) plug		316 Stainless steel stem with Nitrile (NBR) or Fluorocarbon (FKM) plug	
VALVE SPRING	Stainless steel or Inconel® (NACE)		Inconel®	
DIAPHRAGM AND O-RING	Nitrile (NBR), Fluorocarbon (FKM) or Silicone (VMQ) <sup>1)</sup>			
SOFT SEAT AND GASKET	Nitrile (NBR) or Fluorocarbon (FKM)			
BOLTING, ADJUSTING SCREW, LOCKNUT	Zinc-plated steel or Stainless steel		Stainless steel	
HANDWHEEL	Zinc-plated steel screw with resin handwheel			
FILTER RETAINER	----	Plated Steel	----	316 Stainless steel
FILTER ELEMENT		Polyethylene, Glass fiber, 316 Stainless steel or PVDF (Plastic)		Polyethylene, Glass fiber, 316 Stainless steel or PVDF (Plastic)
DRAIN VALVE		Brass or Stainless steel		316 Stainless steel or 18-8 Stainless steel
DRIPWELL		Aluminum (ASTM B85/Alloy 380)		CF8M/CF3M Stainless steel

1. Silicone (VMQ) diaphragm is only available with internal relief (Types 67CR, 67CSR, 67CFR and 67CFSR).

Inconel® is a mark owned by Special Metals Corporation.

# 67C Series

## Instrument Supply Regulator

FISHER™




Figure 4. 67C Series Vent and Drain Valve Positions

Table 3. Capacities

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR, psig / bar	OUTLET PRESSURE		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
					Types 67C, 67CR, 67CS and 67CSR				Types 67CF, 67CFR, 67CFS and 67CFSR			
					10% Droop		20% Droop		10% Droop		20% Droop	
	psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
0 to 35 / 0 to 2.4 T14059T0012 Silver T14113T0012 Silver stripe	15	1.0	50	3.4	323	8.7	555	14.9	323	8.7	555	14.9
			75	5.2	439	11.8	787	21.1	387	10.4	890	23.9
			100	6.9	555	14.9	1032	27.7	426	11.4	1290	34.6
			150	10.3	877	23.5	1548	41.5	516	13.8	2064	55.3
			250	17.2	1677	44.9	2451	65.7	581	15.6	2322	62.2
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	503	13.5	2387	64.0	----	----	----	----
	20	1.4	50	3.4	400	10.7	593	15.9	452	12.1	645	17.3
			75	5.2	542	14.5	903	24.2	684	18.3	1058	28.4
			100	6.9	800	21.4	1213	32.5	968	25.9	1419	38.0
			150	10.3	1238	33.2	1871	50.1	1806	48.4	2064	55.3
			250	17.2	2000	53.6	2774	74.3	3290	88.2	3483	93.3
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	1548	41.5	3548	95.1	----	----	----	----
35	2.4	50	3.4	503	13.5	632	16.9	503	13.5	645	17.3	
		75	5.2	761	20.4	1097	29.4	826	22.1	1058	28.4	
		100	6.9	993	26.6	1484	39.8	1084	29.1	1419	38.0	
		150	10.3	1548	41.5	2258	60.5	1871	50.1	2129	57.1	
		250	17.2	2838	76.1	3483	93.3	3161	84.7	3483	93.3	
		400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	3677	98.5	4451	119	----	----	----	----	
0 to 60 / 0 to 4.1 T14058T0012 Blue stripe T14114T0012 Blue	35	2.4	50	3.4	400	10.7	568	15.2	426	11.4	606	16.2
			75	5.2	568	15.2	864	23.2	645	17.3	942	25.2
			100	6.9	722	19.4	1161	31.1	903	24.2	1290	34.6
			150	10.3	1006	27.0	1742	46.7	1355	36.3	2000	53.6
			250	17.2	1871	50.1	2838	76.1	2580	69.1	3354	89.9
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	993	26.6	3225	86.4	----	----	----	----
	60	4.1	75	5.2	671	18.0	929	24.9	671	18.0	929	24.9
			100	6.9	968	25.9	1355	36.3	993	26.6	1290	34.6
			150	10.3	1419	38.0	2193	58.8	1419	38.0	2064	55.3
			250	17.2	2645	70.9	3677	98.5	3161	84.7	3548	95.1
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	4128	111	5547	149	----	----	----	----
0 to 125 / 0 to 8.6 T14060T0012 Red stripe T14115T0012 Red	80	5.5	100	6.9	645	17.3	1032	27.7	684	18.3	1006	27.0
			150	10.3	968	25.9	1548	41.5	1006	27.0	1548	41.5
			250	17.2	1548	41.5	2645	70.9	1613	43.2	2838	76.1
	125	8.6	150	10.3	1161	31.1	1613	43.2	1161	31.1	1484	39.8
			250	17.2	2012	53.9	3161	84.7	2129	57.1	3161	84.7
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	2838	76.1	5612	150	----	----	----	----
0 to 150 / 0 to 10.3 <sup>(1)</sup> 10C1730X012 Black	80	5.5	250	17.2	710	19.0	1548	41.5	710	19.0	1548	41.5
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	516	13.8	1419	38.0	----	----	----	----
	135	9.3	250	17.2	1251	33.5	2322	62.2	1419	38.0	2322	62.2
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	1084	29.1	3032	81.3	----	----	----	----
	150	10.3	250	17.2	1419	38.0	2387	64.0	1419	38.0	2387	64.0
			400 <sup>(2)</sup>	27.6 <sup>(2)</sup>	1213	32.5	3225	86.4	----	----	----	----

1. Available for Types 67CS, 67CSR, 67CFS and 67CFSR only.  
2. Inlet pressures above 250 psig / 17.2 bar with a maximum of 400 psig / 27.6 bar are only available on Types 67CS and 67CSR.




Figure 5. Types 67C, 67CR, 67CS and 67CSR Dimensions

Table 4. Types 67C, 67CR, 67CS and 67CSR Dimension

TYPE	STANDARD DIMENSION				DIMENSION WITH CLOSING CAP		PANEL MOUNT OPTION WITH HANDWHEEL DIMENSION					
	A		B		A		A		C		D	
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
67C and 67CR	3.50	89	1.51	38	4.60	117	4.69	119	1.08	27	2.33	59
67CS and 67CSR	4.13	105	1.62	41	4.93	125	5.00	127	1.14	29	2.65	67

# 67C Series

## Instrument Supply Regulator

FISHER™




Figure 6. Types 67CF and 67CFR Dimensions

## Ordering Guide

<p><b>Type (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 67C (Aluminum without internal relief)***</li> <li><input type="checkbox"/> 67CR (Aluminum with internal relief)***</li> <li><input type="checkbox"/> 67CS (Stainless steel without internal relief)***</li> <li><input type="checkbox"/> 67CSR (Stainless steel with internal relief)***</li> <li><input type="checkbox"/> 67CF (Aluminum with filter and without internal relief)***</li> <li><input type="checkbox"/> 67CFR (Aluminum with filter and internal relief)***</li> <li><input type="checkbox"/> 67CFS (Stainless steel with filter and without internal relief)***</li> <li><input type="checkbox"/> 67CFSR (Stainless steel with filter and internal relief)***</li> </ul>
<p><b>Quantity (Specify)</b></p> <input style="width: 100%; height: 20px;" type="text"/>
<p><b>Spring Case Style (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Drilled hole vent (Types 67C, 67CR, 67CF and 67CFR) <b>(standard)</b>***</li> <li><input type="checkbox"/> 1/4 NPT vent (Types 67CS, 67CSR, 67CFS and 67CFSR) <b>(standard)</b>***</li> <li><input type="checkbox"/> Single hole panel mount***</li> <li><input type="checkbox"/> 3-hole panel mount (Types 67C, 67CR, 67CF and 67CFR only)***</li> </ul>
<p><b>Adjusting Screw (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Square head (Types 67C, 67CR, 67CF and 67CFR) <b>(standard)</b>***</li> <li><input type="checkbox"/> Square head with closing cap (Types 67CS, 67CSR, 67CFS and 67CFSR) <b>(standard)</b>***</li> <li><input type="checkbox"/> Handwheel***</li> </ul>
<p><b>Outlet Pressure Range (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 0 to 20 psig / 0 to 1.4 bar***</li> <li><input type="checkbox"/> 0 to 35 psig / 0 to 2.4 bar***</li> <li><input type="checkbox"/> 0 to 60 psig / 0 to 4.1 bar***</li> <li><input type="checkbox"/> 0 to 125 psig / 0 to 8.6 bar***</li> <li><input type="checkbox"/> 0 to 150 psig / 0 to 10.3 bar (Types 67CS, 67CSR, 67CFS and 67CFSR only)***</li> </ul>
<p><b>Diaphragm, O-rings and Valve Plug (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Nitrile (NBR) <b>(standard)</b>***</li> <li><input type="checkbox"/> Fluorocarbon (FKM)**</li> <li><input type="checkbox"/> Silicone (VMQ) diaphragm, O-rings and Nitrile (NBR) valve plug*</li> </ul>

<p><b>Filter Material (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Polyethylene (5 microns) <b>(standard)</b>***</li> <li><input type="checkbox"/> Glass Fiber (5 microns)***</li> <li><input type="checkbox"/> PVDF (Plastic) (40 microns)***</li> <li><input type="checkbox"/> Stainless steel (40 microns)***</li> </ul>
<p><b>Dripwell (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Standard</li> <li><input type="checkbox"/> Large capacity with manual drain valve</li> <li><input type="checkbox"/> Large capacity with automatic drain valve, Nitrile (NBR)</li> <li><input type="checkbox"/> Large capacity with automatic drain valve, Fluorocarbon (FKM)</li> </ul>
<p><b>Drain Valve (For Manual Drain Only) (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Brass (Types 67CF and 67CFR) <b>(standard)</b>***</li> <li><input type="checkbox"/> Stainless steel (Types 67CFS and 67CFSR) <b>(standard)</b>***</li> </ul>
<p><b>Drain Valve Location (for Standard Dripwell Only) (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Position 1 - Aligned with inlet <b>(standard)</b>***</li> <li><input type="checkbox"/> Position 2</li> <li><input type="checkbox"/> Position 3</li> <li><input type="checkbox"/> Position 4</li> </ul>
<p><b>Spring Case Vent Location (Select One)</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Position 1 - Aligned with inlet <b>(standard)</b>***</li> <li><input type="checkbox"/> Position 2</li> <li><input type="checkbox"/> Position 3</li> <li><input type="checkbox"/> Position 4</li> </ul>
<p><b>Fixed Bleed for Type 67CR, 67CSR, 67CFR or 67CFSR (Optional)</b></p> <input type="checkbox"/> Yes**
<p><b>Smart Bleed™ Internal Check Valve Airset (Optional - Types 67CFR and 67CFSR only)</b></p> <input type="checkbox"/> Yes**

- continued -

### Ordering Guide (continued)

#### Second Outlet (Select One)

- Open (Types 67C, 67CR, 67CF and 67CFR) (standard)\*\*\*
- Plugged with pipe plug (Types 67CS, 67CSR, 67CFS and 67CFSR) (standard)\*\*\*
- Tire Valve\*\*\*
- Pressure Gauge (see below)

#### Triple Scale Pressure Gauge (Optional)

- Brass Gauge or  Stainless steel Gauge
- 0 to 30 psig / 0 to 0.2 MPa / 0 to 2.1 bar\*\*\*
- 0 to 60 psig / 0 to 0.4 MPa / 0 to 4.1 bar\*\*\*
- 0 to 160 psig / 0 to 1.1 MPa / 0 to 11.0 bar\*\*\*

1. Product complies with the material requirements of NACE MR0175. Environmental limits may apply.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### NACE MR0175 Construction (Optional)<sup>(1)</sup>

- Yes (not available with gauge)\*\*

#### NACE MR0103 Construction (Optional)

- Yes (not available with gauge)\*\*

#### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

#### Specification Worksheet

<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

#### Regulator Tip:

All regulators should be installed and used in accordance with federal, state and local codes and regulations.



### Introduction

Type 99 regulator typically provides fuel gas to boilers, furnaces, ovens, mixers and large commercial or industrial installations. It is available with a Type 61L (low pressure), 61H (high pressure) or 61HP (extra high pressure) pilot integrally mounted to the actuator (see Figure 2).

### Body Size and End Connection Style

See Table 1

### Outlet (Control) Pressure Ranges

2 in. w.c. to 100 psig / 5 mbar to 6.9 bar  
See Table 3

### Differential Pressures

See Table 5

### Flow and Sizing Coefficients

See Table 6

### Flow Capacities

See Table 8

### Maximum Inlet Pressures

**Type 61LD Pilot:** 160 psig / 11.0 bar

**Types 61L and 61H Pilots:**

400 psig / 27.6 bar

Type 61HP Pilot: 1000 psig / 69.0 bar with Type 1301F pilot supply regulator and Type H110 relief valve (1/2 in. / 13 mm orifice only)

### Maximum Actuator Pressures

**Operating:** 100 psig / 6.9 bar

**Emergency:** 110 psig / 7.6 bar

### Pressure Registration

External

### Temperature Capabilities

**With Nitrile (NBR) / Neoprene (CR) / Nylon (PA):** -20 to 180°F / -29 to 82°C

**With Fluorocarbon (FKM):** 0 to 300°F / -18 to 149°C

### Approximate Shipping Weight

115 lbs / 52 kg

### Options

- Disk or O-ring Seat Design
- 1000 psig / 69.0 bar Inlet Pressure Regulator
- O-ring Stem Seal for Upstream Regulator
- Electronic Remote Control Capability
- Handwheel for Type 61L Pilot
- Travel Indicator

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/16

### Features

- Wide Variety of Applications
- High Accuracy
- No Atmospheric Bleed
- High Capacity Pressure Control
- Excellent Low Flow Control
- Easy to Maintain
- Easy to Modify for Special Service




Figure 1. Type 99 Pressure Reducing Regulator




Figure 2. Type 99 Operational Schematic

# Type 99

## Pressure Reducing Regulator

FISHER™

**Table 1. Body Size and End Connection Style**

BODY SIZE		BODY MATERIAL		
NPS	DN	Cast Iron	WCC Steel	Brass
2	50	NPT, CL125 FF or CL250 RF	NPT, CL150 RF, CL300 RF or SWE	NPT

**Table 2. Construction Material**

BODY	SPRING CASE AND DIAPHRAGM CASE	MAIN VALVE SEAT DISK	DIAPHRAGM	MAIN VALVE TRIM	PILOT TRIM	TUBING	FITTING
Cast iron, WCC Steel or Brass	Cast iron	Neoprene (CR), Nitrile (NBR), Fluorocarbon (FKM), Nylon (PA) or Polytetrafluoroethylene (PTFE)	Nitrile (NBR) or Fluorocarbon (FKM)	Brass or Stainless steel	Steel, Stainless steel, Cast iron, Aluminum, Zinc or Brass	Copper or Stainless steel	Brass, Steel or Stainless steel

**Table 3. Outlet (Control) Pressure Range**

PILOT TYPE	MAXIMUM PILOT SUPPLY PRESSURE		OUTLET (CONTROL) PRESSURE RANGE		PILOT CONTROL SPRING					
					PART NUMBER	COLOR CODE	WIRE DIAMETER		FREE LENGTH	
	psig	bar	psig	bar			In.	mm	In.	mm
61L	400	27.6	2 to 4 in. w.c. <sup>(1)</sup> 3 to 12 in. w.c. <sup>(1)</sup>	5 to 10 mbar <sup>(1)</sup> 7 to 30 mbar <sup>(1)</sup>	1B558527052 1C680627222 1B886327022	Orange Unpainted Red	0.072 0.080 0.109	1.83 2.03 2.77	3.78 3.00 2.75	96.0 76.2 69.9
61LD	160	11.0	0.25 to 2 1 to 5	0.02 to 0.14 0.07 to 0.35	1J857827022 1B886427022	Yellow Blue	0.142 0.172	3.61 4.37	2.75 2.88	69.9 73.2
61LE	400	27.6	2 to 10 5 to 15 10 to 20	0.14 to 0.69 0.35 to 1.0 0.69 to 1.4	1J857927142 1B886527022	Brown Green	0.187 0.207	4.75 5.26	3.03 3.13	77.0 79.5
61H	400	27.6	10 to 65	0.69 to 4.5	0Y066427022	Green stripe	0.363	9.22	6.00	152
61HP	600	41.0	35 to 100	2.4 to 6.9	1D387227022	Blue	0.200	5.08	1.69	42.9

1. Type 61LD pilot only.

**Table 4. Approximate Proportional Band**

TYPE	PILOT CONTROL SPRING		APPROXIMATE PROPORTIONAL BAND	
	Part Number	Color Code	In. w.c.	mbar
61LD	1B558527052	Orange	0.1 to 0.5	0.25 to 1
	1C680627222	Unpainted		
61L	1B886327022	Red	1 to 2	2 to 5
61LD			0.25 to 1	0.62 to 2
61LE			5 to 8	12 to 20
61L, 61LD, 61LE			1B886527022	Green
	1J857927142	Brown		
	1B886427022	Blue		
	1J857827022	Yellow		
61H	0Y066427022	Green stripe	0.1 to 0.3 psi	0.01 to 0.02 bar
61HP	1D387227022	Blue	1 to 2 psi	0.07 to 0.14 bar

**Table 5. Maximum Inlet Pressure, Allowable Pressure Drop and Minimum Differential Pressure**

MAXIMUM ALLOWABLE INLET PRESSURE/ PRESSURE DROP		MAIN VALVE SPRING				MINIMUM DIFFERENTIAL PRESSURE FOR FULL STROKE		DISK MATERIAL		MAXIMUM ORIFICE SIZE <sup>(1)(5)</sup>	
		PART NUMBER	WIRE DIAMETER		FREE LENGTH						
psig	bar			In.	mm	In.	mm	psid	bar d	In.	mm
25	1.7	1C277127022	0.148	3.76	6	152	0.75	0.05	Nitrile (NBR) Disk Type Option and Fluorocarbon (FKM)	1-1/8	29
50	3.4	1N801927022	0.156	3.96	7.13	181	1.5	0.10	Neoprene (CR) and Fluorocarbon (FKM)	1-1/8	29
150	10.3	1B883327022	0.187	4.75	6.63	168	3	0.21	Nitrile (NBR) O-ring Type Option, Neoprene (CR) and Fluorocarbon (FKM)	1-1/8	29
175 <sup>(2)</sup>	12.1 <sup>(2)</sup>	1B883327022	0.187	4.75	6.63	168	3	0.21	Nitrile (NBR) O-ring Type Option, Neoprene (CR) and Fluorocarbon (FKM)	7/8	22
250	17.2	1B883327022	0.187	4.75	6.63	168	3	0.21	Neoprene (CR) and Fluorocarbon (FKM)	7/8	22
300	20.7	0W019127022	0.281	7.22	6	152	10	0.69	Nylon (PA)	1-1/8 <sup>(3)</sup>	29 <sup>(3)</sup>
400	27.6	0W019127022	0.281	7.22	6	152	10	0.69	Nylon (PA) and PTFE	7/8	22
1000	69.0	0W019127022	0.281	7.22	6	152	10	0.69	Nylon (PA)	1/2 <sup>(4)</sup>	13 <sup>(4)</sup>

1. Can use all orifice sizes up to maximum size listed. See Table 6.

2. CL125 FF flanged body only.

3. 1-1/8 in. / 29 mm is the only orifice available for 300 psig / 20.7 bar maximum inlet pressure regulator.

4. 1/2 in. / 13 mm is the only orifice available for 1000 psig / 69.0 bar maximum inlet pressure regulator.

5. O-ring seat construction is only available for 7/8 and 1-1/8 in. / 22 and 29 mm orifice sizes.






Figure 3. Typical Wide-Open Monitor Installations




Figure 4. Working Monitor Installation

Table 6. Orifice Size and Flow and Sizing Coefficient

TRIM CONSTRUCTION	ORIFICE SIZE		WIDE-OPEN FOR RELIEF SIZING		REGULATING		C <sub>1</sub>	IEC SIZING COEFFICIENT		
	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>g</sub>	C <sub>v</sub>		X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
Restricted capacity trim, Straight bore-Elastomer disk seat only	1/2 <sup>(1)</sup>	13 <sup>(1)</sup>	200	5.71	155	4.43	35	0.78	0.50	0.89
	3/4	19	425	12.14	330	9.43				
Restricted capacity trim, Stepped bore-Elastomer disk seat only	7/8 x 3/8	22 x 9.5	115	3.29	110	3.14				
	7/8 x 1/2	22 x 13	200	5.71	190	5.43				
	7/8 x 5/8	22 x 16	300	8.57	280	8.00				
Full capacity trim, Elastomer disk or O-ring seat	7/8	22	550	15.71	408	11.66				
	1-1/8	29	850	24.29	680	19.43				

1. 1/2-inch / 13 mm is the only orifice size available for 1000 psig / 69.0 bar maximum inlet pressure regulator.

# Type 99

## Pressure Reducing Regulator




**Table 7. Working Monitor Performance**

MONITORING PILOT INFORMATION									MINIMUM PRESSURE AT WHICH WORKING MONITOR REGULATOR CAN BE SET
Construction	Spring Range		Part Number	Pilot Spring					
				Wire Diameter		Free Length			
	psig	bar		In.	mm	In.	mm		
Type 161AYW with 1/8 in. / 3.2 mm orifice size and 150 psig / 10.3 bar maximum allowable inlet pressure	3 to 12 in. w.c. 11 to 25 in. w.c.	7 to 30 mbar 27 to 62 mbar	1B653927022 1B537027052	0.105 0.114	2.67 2.90	3.750 4.312	95.2 109	3 in. w.c. / 7 mbar over normal distribution pressure	
	0.9 to 2.5 2.5 to 4.5 4.5 to 7	0.06 to 0.17 0.17 to 0.31 0.31 to 0.48	1B537127022 1B537227022 1B537327052	0.156 0.187 0.218	3.96 4.75 5.54	4.060 3.937 3.980	103 100 101	0.5 psi / 0.03 bar over normal distribution pressure	
	5 to 20 15 to 40	0.34 to 1.4 1.0 to 2.8	10B3076X012 10B3077X012	0.170 0.207	4.32 5.26	3.190 3.190	81.0 81.0	3.0 psi / 0.21 bar over normal distribution pressure	
3/4 NPT Type 627-109 with 1/8 in. / 3.2 mm orifice size and 1000 psig / 69.0 bar maximum inlet pressure (body rating) for ductile iron body	35 to 80 70 to 150	2.1 to 5.5 4.8 to 10.3	10B3078X012 10B3079X012	0.262 0.313	6.65 7.95	3.200 3.070	81.3 78.0	5.0 psi / 0.34 bar over normal distribution pressure	

**Table 8. Capacities**

ORIFICE SIZE	INLET PRESSURE		CAPACITIES <sup>(1)</sup> IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(2)</sup>																							
			Outlet Pressure, psig / bar																							
			0.25 / 0.02		0.5 / 0.03		2 / 0.14		5 / 0.35		10 / 0.69		15 / 1.0		20 / 1.4		30 / 2.1		40 / 2.8		60 / 4.1		100 / 6.9			
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h			
7/8 in. / 22 mm	5	0.34	7.2	0.2	7.2	0.2	6.6	0.2																		
	10	0.69	11.4	0.3	11.4	0.3	10	0.3	8.4	0.2																
	20	1.4	18.6	0.5	18.6	0.5	18.6	0.5	18	0.5	14.4	0.4	10.8	0.3												
	30	2.1	23	0.6	23	0.6	23	0.6	23	0.6	23	0.6	20	0.5	17	0.5	19	0.5								
	40	2.8	28	0.8	28	0.8	28	0.8	28	0.8	28	0.8	28	0.8	26	0.7	19	0.5								
	60	4.1	42	1.1	42	1.1	42	1.1	42	1.1	42	1.1	42	1.1	42	1.1	37	1.0	30	0.8						
100	6.9	59	1.6	59	1.6	59	1.6	59	1.6	59	1.6	59	1.6	59	1.6	59	1.6	59	1.6	53	1.4					
150	10.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	86	2.3	72	1.9			
200	13.8	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9	108	2.9			
250	17.2	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5	132	3.5			
300	20.7	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3	162	4.3			
350	24.1	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0	188	5.0			
400	27.6	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8	215	5.8			
1-1/8 in. / 29 mm	5	0.34	12	0.3	12	0.3	10	0.3																		
	10	0.69	19	0.5	19	0.5	17	0.5	14	0.4																
	20	1.4	31	0.8	31	0.8	31	0.8	30	0.8	24	0.6	18	0.5												
	30	2.1	39	1.0	39	1.0	39	1.0	39	1.0	39	1.0	34	0.9	28	0.8										
	40	2.8	47	1.3	47	1.3	47	1.3	47	1.3	47	1.3	47	1.3	43	1.2	32	0.9								
	60	4.1	65	1.7	65	1.7	65	1.7	65	1.7	65	1.7	65	1.7	65	1.7	62	1.7	50	1.3						
100	6.9	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7	99	2.7			
150	10.3	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8	143	3.8			
200	13.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8	180	4.8			
250	17.2	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9	220	5.9			
300	20.7	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1	265	7.1			



Blank areas show no capacity due to differential pressure requirement.  
 1. When sizing a regulator, always use the lowest inlet pressure, the highest outlet pressure and the maximum capacity desired.  
 2. Requires 0.75 psig / 0.05 bar minimum differential pressure construction.






Figure 5. Dimensions

# Type 99

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Body Material and End Connection Style (Select One)

#### NPS2 / DN 50 Cast Iron Body

- NPT\*\*\*
- CL125 FF\*\*\*
- CL250 RF\*\*\*

#### NPS 2 / DN 50 WCC Steel Body

- NPT\*\*\*
- CL150 RF\*\*
- CL300 RF\*\*
- SWE\*

#### 2 NPT Brass Body

- NPT\*

### Orifice Size (Select One)

- 1/2 in. / 13 mm\*\*\*
- 3/4 in. / 19 mm\*\*\*
- 7/8 in. / 22 mm\*\*\*
- 1-1/8 in. / 29 mm\*\*\*
- 7/8 x 3/8 in. / 22 x 9.53 mm\*
- 7/8 x 1/2 in. / 22 x 13 mm\*\*
- 7/8 x 5/8 in. / 22 x 16 mm\*\*

### Main Valve Spring (See Table 6) (Select One)

#### Maximum Allowable Differential Pressure and Spring Part Number

- 25 psi / 1.7 bar, 1C277127022\*\*\*
- 50 psi / 3.4 bar, 1N801927022\*\*\*
- 100 psig / 6.9 bar, 1B883327022\*\*\*
- 150 psig / 10.3 bar, 1B883327022\*\*\*
- 175 psig / 12.1 bar, 1B883327022\*\*\*
- 250 psi / 17.2 bar, 1B883327022\*\*\*
- 300 psig / 20.7 bar, 0W019127022\*\*
- 400 psig / 27.6 bar, 0W019127022\*\*
- 1000 psi / 69.0 bar, 0W019127022\*\*\*

### Trim Material Main Valve and Pilot (Select One)

- Brass with disk seat (**standard**)\*\*\*
- Stainless steel with disk seat\*\*
- Brass with O-ring seat (7/8 or 1-1/8 in. / 22 or 29 mm orifice)\*\*\*
- Stainless steel with O-ring seat (7/8 or 1-1/8 in. / 22 or 29 mm orifice)\*\*

### Seat Material (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*
- Neoprene (CR)\*\*
- Nylon (PA)\*\*
- PTFE\*\*

### Tubing and Fittings (Select One)

- Copper tubing and brass fittings (**standard**)\*\*\*
- Stainless steel tubing and stainless steel fittings\*\*
- Stainless steel tubing and steel fittings\*\*

### Outlet Pressure Range (See Table 3) (Select One)

- 2 to 4 in. w.c. / 5 to 10 mbar, Orange\*
- 3 to 12 in. w.c. / 7 to 30 mbar, Unpainted\*\*\*
- 0.25 to 2 psig / 0.02 to 0.14 bar, Red\*\*\*
- 1 to 5 psig / 0.07 to 0.34 bar, Yellow\*\*\*
- 2 to 10 psig / 0.14 to 0.69 bar, Blue\*\*
- 5 to 15 psig / 0.34 to 1.0 bar, Brown\*\*\*
- 10 to 20 psig / 0.69 to 1.4 bar, Green\*\*
- 10 to 65 psig / 0.69 to 4.5 bar, Green Stripe\*\*\*
- 35 to 100 psig / 2.4 to 6.9 bar, Blue\*\*\*

### Upstream Regulator O-ring Stem Seal (Optional)

- Yes

### Travel Indicator (Optional)

- Yes

### Electronic Remote Control Capability (Optional)

- Yes

### Handwheel for Type 61L Pilot (Optional)

- Yes

### Main Valve Parts Kit (Optional)

- Yes, please send me one parts kit to match this order.

### Pilot Parts Kit (Optional)

- Yes, please send me one parts kit to match this order.

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

If two or more available springs have published pressure ranges that include the desired pressure setting, use the spring with the lower range for better accuracy.

# 133 Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The 133 Series direct-operated gas regulators are primarily designed for industrial and commercial applications supplying gas to furnaces, burners and other appliances. The 133 Series balancing system enables the regulator to provide accurate control of gas pressure for maximum combustion efficiency despite varying inlet pressure conditions. The single port construction provides bubble-tight shutoff. An external downstream control line is required for the operation of the regulator. 133 Series regulators are available in a 2 in. / DN 50 body size with either NPT or flanged end connections.

An optional restriction collar can be installed if wide-open capacity is too high for applications using a relief valve as overpressure protection. The collar reduces wide-open capacity to 25%, 40% or 60% of standard wide-open capacity.

### Body Size and End Connection Styles

**Cast Iron Body:** NPS 2 / DN 50 NPT or CL125 FF flanged

**WCC Steel Body:** NPS 2 / DN 50 NPT or CL150 RF flanged

### Pressure Registration

External; downstream control line is required

### Flow and Sizing Coefficients

See Table 2

### Maximum Inlet Pressures

See Table 2

### Maximum Emergency Outlet (Casing) Pressure

See Table 2

### Outlet Pressure Ranges

See Table 3

### Temperature Capabilities

-20 to 150°F / -29 to 66°C

### Construction Materials

**Body:** Cast iron or WCC Steel

**Orifice and Cage:** Aluminum

**Valve Disk:** Aluminum/Neoprene (CR) or Aluminum/Fluorocarbon (FKM)<sup>(1)</sup>

**O-rings:** Nitrile (NBR) or Fluorocarbon (FKM)<sup>(1)</sup>

**Diaphragms:** Nitrile (NBR) / Nylon (PA) (Neoprene (CR) in actuator) or Fluorocarbon (FKM)<sup>(1)</sup> / Polymer Thermoplastic

**Guide Bushing:** Nylon (PA)

**Stem and Stem Sleeve:** Stainless steel

**Diaphragm Plate:** Steel

**Balancing Diaphragm Plate:** Plated steel

**Spring Case and Closing Cap:**

Type 133HP: Cast Iron

Types 133H, 133L and 133Z: Aluminum

**Lower Casing:**

Types 133H, 133L and 133Z: Aluminum

Type 133HP: Steel

**Adjusting Screw:**

Types 133H and 133Z: Brass

Type 133L: Aluminum

Type 133HP: Steel

**Optional Restriction Collar:** Aluminum

### Approximate Weights

**Types 133H, 133L, and 133Z NPT**

**End Connections:** 35 pounds / 16 kg

**Types 133H, 133L, and 133Z Flanged**

**End Connections:** 40 pounds / 18 kg

Type 133HP NPT End Connections:

56.5 pounds / 26 kg

**Type 133HP Flanged End Connections:**

62.5 pounds / 28 kg

### Options

Restriction collar to reduce wide-open capacity to approximately 25, 40 or 60% of standard wide-open capacity

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



06/13

### Features

- Wide Pressure Range Capability with Single Regulator
- Types 133L, 133H and 133HP Suitable for Monitoring Applications
- Excellent Shock Characteristics and Fast Speed of Response
- Bubble-Tight Shutoff
- Easy Access to Trim Parts



W1327

Figure 1. Types 133H, 133L and 133Z Regulators




W5803

Figure 2. Type 133HP Pressure Reducing Regulator

1. Available for Types 133L and 133H only.






A6555

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE
- BOOST PRESSURE

**Figure 3.** Type 133L Operational Schematic  
(Also Typical of Type 133H)



A6883

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE
- BOOST PRESSURE

**Figure 4.** Type 133HP Operational Schematic

**Table 1. Flow Coefficient**

PERCENT CAPACITY	WIDE-OPEN C <sub>g</sub>	WIDE-OPEN C <sub>v</sub>	C <sub>i</sub>	IEC SIZING COEFFICIENT		
				X <sub>r</sub>	F <sub>o</sub>	F <sub>L</sub>
25% <sup>(1)</sup>	490	17.4	28.2	0.78	0.72	0.89
40% <sup>(1)</sup>	760	26.1	29.1			
60% <sup>(1)</sup>	1150	36.2	31.8			
100%	1800	51.4	35.0			

1. Optional restriction collar used.

**Table 2. Outlet Pressure Range**

TYPE	OUTLET PRESSURE RANGE		SPRING PART NUMBER	SPRING COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	psig	bar			In.	mm	In.	mm
133H <sup>(1)</sup>	1.5 to 3	0.10 to 0.21	1H975927032	Orange	0.250	6.35	6.91	176
	2 to 5	0.14 to 0.34	10A9440X012	Yellow	0.283	7.19	6.47	164
	5 to 10	0.34 to 0.69	1J146927142	Blue	0.375	9.53	6.19	157
133HP <sup>(2)</sup>	2 to 5	0.14 to 0.34	17B8632X012	Yellow	0.282	7.16	8.5	216
	4.5 to 10	0.31 to 0.69	17B8633X012	Orange	0.343	8.71	8.5	216
	6 to 20	0.41 to 1.4	10C1238X012	Silver	0.375	9.52	8.25	210
	16 to 30	1.1 to 2.1	10C1240X012	Red	0.438	11.1	8.25	210
	26 to 40	1.8 to 2.8	10C1241X012	Blue	0.500	12.7	8.25	210
	36 to 50	2.5 to 3.4	10C1242X012	Green	0.500	12.7	8.25	210
133L <sup>(1)</sup> and 133H <sup>(2)</sup>	45 to 60	3.1 to 4.1	10C1243X012	White	0.531	13.5	8.25	210
	2 to 4 in. w.c.	5 to 10 mbar	1D892527022	Brown	0.109	2.77	6.12	156
	3.5 to 6 in. w.c.	9 to 15 mbar	1D892627022	Red	0.112	2.84	7.53	191
	5 to 9 in. w.c.	12 to 22 mbar	1D892727012	Black	0.130	3.30	7.88	200
	8.5 to 18 in. w.c.	21 to 45 mbar	1D893227032	White	0.156	3.96	7.50	190
	14 to 28 in. w.c.	35 to 70 mbar	1D893327032	Green	0.182	4.62	7.25	184
133Z <sup>(1)</sup>	0.75 to 2	0.05 to 0.14	1H975827032	Blue	0.225	5.72	7.09	180
	-1 to 1 in. w.c.	-3 to 3 mbar	1K633427012 (Extension Spring)	Unpainted	0.075	1.91	2	50.8
	0 to 4 in. w.c.	0 to 10 mbar	1K633427012 (Extension Spring) and 1D892527022 (Compression Spring)	Unpainted Brown	0.075 0.109	1.91 2.77	2 6.13	50.8 156

1. Pressure ranges shown are correct if the regulator is installed with the actuator portion above the body portion. If the regulator is installed with the actuator portion below the body, the pressure ranges will be lowered by approximately 2 in. w.c. / 5 mbar for the Type 133L and by approximately 3 in. w.c. / 7 mbar for Type 133H.
2. The 2 in. w.c. to 2 psig / 5 mbar to 0.14 bar springs shown for the Type 133L may also be used in the Type 133H. However, the outlet pressure ranges will increase by approximately 1 in. w.c. / 2 mbar due to the weight of the Type 133H parts (assuming that the actuator portion is installed above the body portion).

# 133 Series

## Pressure Reducing Regulator



**Table 3. Maximum Inlet and Outlet Pressure**

PRESSURE	TYPE							
	133H		133HP		133L		133Z	
	psig	bar	psig	bar	psig	bar	psig	bar
Maximum Operating Inlet Pressure	60	4.1	150	10.3	60	4.1	20	1.4
Maximum Emergency Inlet Pressure	125	8.6			125	8.6	125	8.6
Maximum Operating Outlet Pressure	10	0.69	Setpoint plus 40	Setpoint plus 2.8	2	0.14	4 in. w.c.	10 mbar
Maximum Outlet Pressure Over Outlet Pressure Setting	3	0.21			3	0.21	3	0.21
Maximum Emergency Outlet (Casing) Pressure	15	1.0	150	10.3	15	1.0	15	1.0

1. With highest spring range available only.

**Table 4. Full-Capacity Type 133H Regulated Flow**

INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS AT 14.7 psia / 1 bar AND 60°F / 15°C									
		Outlet Pressure Setting <sup>(1)</sup> , Spring Part Number and Outlet Pressure Range									
		3 psig / 0.21 bar 1H975927032 1.5 to 3 psig / 0.10 to 0.21 bar		2 psig / 0.14 bar 10A9440X012 2 to 5 psig / 0.14 to 0.34 bar		5 psig / 0.34 bar 10A9440X012 2 to 5 psig / 0.14 to 0.34 bar		5 psig / 0.34 bar 1J146927142 5 to 10 psig / 0.34 to 0.69 bar		10 psig / 0.69 bar 1J146927142 5 to 10 psig / 0.34 to 0.69 bar	
psig	bar	10% droop	20% droop	10% droop	20% droop	10% droop	20% droop	10% droop	20% droop	10% droop	20% droop
3	0.21	----	----	6.5 / 0.17	11.5 / 0.31	----	----	----	----	----	----
5	0.34	14 / 0.38	22 / 0.59	11 / 0.30	18 / 0.48	----	----	----	----	----	----
7	0.48	21.5 / 0.58	31 / 0.83	13 / 0.35	22 / 0.59	15.5 / 0.42	24 / 0.64	9 / 0.24	15 / 0.40	----	----
10	0.69	28 / 0.75	42 / 1.13	15 / 0.40	27 / 0.72	24 / 0.64	35 / 0.94	14 / 0.38	22 / 0.59	----	----
15	1.03	40 / 1.07	57 / 1.53	25.5 / 0.68	39 / 1.04	35 / 0.94	51 / 1.37	19 / 0.51	31.5 / 0.84	21 / 0.56	35 / 0.94
20	1.38	52 / 1.39	72 / 1.93	35 / 0.94	52 / 1.39	46 / 1.23	67 / 1.80	24 / 0.64	41 / 1.10	31 / 0.83	51 / 1.37
30	2.07	76 / 2.04	96 / 2.57	49 / 1.31	73 / 1.96	68 / 1.82	95 / 2.55	35 / 0.94	58 / 1.55	44 / 1.18	74 / 1.98
40	2.76	98 / 2.63	119 / 3.19	66 / 1.77	97 / 2.60	88 / 2.36	117 / 3.14	44 / 1.18	73 / 1.96	56 / 1.50	97 / 2.60
50	3.44	118 / 3.16	141 / 3.78	84 / 2.25	112 / 3.00	103 / 2.76	138 / 3.70	57 / 1.53	89 / 2.38	74 / 1.98	117 / 3.14
60	4.14	136 / 3.64	165 / 4.42	104 / 2.79	132 / 3.54	122 / 3.27	156 / 4.18	65 / 1.74	106 / 2.84	91 / 2.44	136 / 3.64

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.

**Table 5. Restricted-Capacity Type 133H Regulated Flow**

INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS AT 14.7 psia / 1 bar AND 60°F / 15°C															
		Outlet Pressure Setting <sup>(1)</sup> , Spring Part Number and Outlet Pressure Range															
		5 psig / 0.34 bar 10A9440X012 2 to 5 psig / 0.14 to 0.34 bar				10 psig / 0.69 bar 1J146927142 5 to 10 psig / 0.34 to 0.69 bar				5 psig / 0.34 bar 10A9440X012 2 to 5 psig / 0.14 to 0.34 bar				10 psig / 0.69 bar 1J146927142 5 to 10 psig / 0.34 to 0.69 bar			
psig	bar	10% Droop		20% Droop		10% Droop		20% Droop		10% Droop		20% Droop		10% Droop		20% Droop	
SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7	0.48	8.0	0.21	9.0	0.24	----	----	11.0	0.30	15.0	0.40	----	----	13.0	0.35	17.0	0.46
10	0.69	12.3	0.33	13.0	0.35	----	----	16.5	0.44	20.0	0.54	----	----	20.0	0.54	25.0	0.67
15	1.0	----	----	13.0	0.35	15.5	0.42	----	----	16.5	0.44	23.5	0.63	----	----	20.0	0.54
20	1.4	20.8	0.56	21.2	0.57	17.5	0.47	20.0	0.54	31.5	0.84	33.5	0.90	23.5	0.63	30.5	0.82
40	2.8	33.5	0.90	33.5	0.90	33.0	0.88	33.5	0.90	52.0	1.39	53.2	1.43	46.0	1.23	53.2	1.43
60	4.1	45.5	1.22	45.5	1.22	45.5	1.22	45.5	1.22	72.7	1.95	72.7	1.95	67.0	1.80	72.7	1.95

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.

**Table 6. Full-Capacity Type 133L Regulated Flow**

INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS AT 14.7 psia / 1 bar AND 60°F / 15°C													
		Outlet Pressure Setting <sup>(1)</sup> , Spring Part Number and Outlet Pressure Range													
		4 in. w.c. / 10 mbar 1D892527022 2 to 4 in. w.c. / 5 to 10 mbar		6 in. w.c. / 15 mbar 1D892627022 3.5 to 6 in. w.c. / 9 to 15 mbar		7 in. w.c. / 17 mbar 1D892727012 5 to 9 in. w.c. / 12 to 22 mbar		14 in. w.c. / 35 mbar 1D893227032 8.5 to 18 in. w.c. / 21 to 45 mbar		14 in. w.c. / 35 mbar 1D893327032 14 to 28 in. w.c. / 35 to 70 mbar		1 psig / 69 mbar 1D893327032 14 to 28 in. w.c. / 35 to 70 mbar		2 psig / 0.14 bar 1H975827032 0.75 to 2 psig / 52 mbar to 0.14 bar	
psig	bar	1 in. w.c. / 2.5 mbar droop		1 in. w.c. / 2.5 mbar droop		1 in. w.c. / 2.5 mbar droop		1 in. w.c. / 2.5 mbar droop		2 in. w.c. / 5 mbar droop		10% droop	20% droop	10% droop	20% droop
1	0.07	14 / 0.38	13 / 0.35	12 / 0.32	5 / 0.134	8.40 / 0.22	----	----	----	----	----	----	----	----	----
2	0.14	20.8 / 0.56	20 / 0.54	17 / 0.46	8.20 / 0.22	15.20 / 0.41	----	----	----	----	----	11.5 / 0.31	16 / 0.43	----	----
3	0.21	26 / 0.70	24.5 / 0.66	21 / 0.56	12 / 0.32	19.50 / 0.52	----	----	----	----	----	15.5 / 0.42	21.5 / 0.58	12.5 / 0.34	18.5 / 0.50
5	0.34	35 / 0.94	33 / 0.88	32 / 0.86	16 / 0.43	28 / 0.75	14 / 0.38	23 / 0.62	24 / 0.64	31.5 / 0.84	20.5 / 0.55	28 / 0.75	28 / 0.75	28 / 0.75	28 / 0.75
10	0.69	52 / 1.39	52 / 1.39	48 / 1.29	34 / 0.91	45 / 1.21	26 / 0.70	38 / 1.02	37.5 / 1.00	44 / 1.18	38 / 1.02	46 / 1.23	46 / 1.23	46 / 1.23	46 / 1.23
20	1.38	78 / 2.09	77 / 2.06	79 / 2.12	69 / 1.85	76 / 2.04	60 / 1.61	69 / 1.85	70 / 1.88	77 / 2.06	62 / 1.66	76 / 2.04	76 / 2.04	76 / 2.04	76 / 2.04
30	2.07	101 / 2.71	100 / 2.68	100 / 2.68	91 / 2.44	97 / 2.60	87 / 2.33	93 / 2.49	90 / 2.41	101 / 2.71	87 / 2.33	101 / 2.71	101 / 2.71	101 / 2.71	101 / 2.71
40	2.76	124 / 3.32	122 / 3.27	124 / 3.32	109 / 2.92	116 / 3.11	107 / 2.87	115 / 3.08	110 / 2.95	122 / 3.27	105 / 2.81	121 / 3.24	121 / 3.24	121 / 3.24	121 / 3.24
50	3.45	146 / 3.91	144 / 3.86	145 / 3.89	130 / 3.48	136 / 3.64	132 / 3.54	137 / 3.67	127 / 3.40	145 / 3.89	124 / 3.32	145 / 3.89	145 / 3.89	145 / 3.89	145 / 3.89
60	4.14	170 / 4.56	168 / 4.50	166 / 4.45	155 / 4.15	161 / 4.32	152 / 4.07	158 / 4.23	149 / 3.99	167 / 4.48	145 / 3.89	170 / 4.56	170 / 4.56	170 / 4.56	170 / 4.56

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.



**Table 7. Full-Capacity Type 133Z Regulated Flow**

INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS AT 14.7 psia / 1 bar AND 60°F / 15°C			
		1 in. w.c. / 3 mbar Outlet Pressure Setting <sup>(1)</sup> (Either Spring Range)			
		0.5 in. w.c. / 1 mbar droop		1 in. w.c. / 3 mbar droop	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
8 in. w.c.	20 mbar	2.4	0.06	5.1	0.14
14 in. w.c.	35 mbar	4.1	0.11	7.4	0.20
1	0.07	6.5	0.17	12	0.32
2	0.14	11.5	0.31	18	0.48
5	0.34	22	0.59	32	0.86
10	0.69	44	1.18	50	1.34
20	1.4	76	2.04	78	2.09

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.

**Table 8. Type 133HP Regulator 100% Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING <sup>(1)</sup>		INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS AT 14.7 psia / 1 bar AND 60°F / 15°C					
					Droop from Setpoint					
					10%		20%		30%	
					psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h
2 to 5 psig / 0.14 to 0.34 bar 17B8632X012 Yellow	2	0.14	10	0.69	10.4	0.28	18.9	0.51	27.5	0.74
			20	1.4	16.4	0.44	29.8	0.80	43.3	1.16
			60	4.1	37.1	0.99	67.5	1.81	97.9	2.62
			100	6.9	57.1	1.53	103.9	2.78	150.6	4.04
			150	10.3	82.0	2.20	149.1	4.00	216.3	5.80
4.5 to 10 psig / 0.31 to 0.69 bar 17B8633X012 Orange	5	0.34	10	0.69	20.2	0.54	41.5	1.11	42.8	1.15
			40	2.8	59.6	1.60	121.3	3.25	121.5	3.26
			60	4.1	82.4	2.21	167.9	4.50	168.0	4.50
			80	5.5	104.9	2.81	213.6	5.72	213.6	5.72
			150	10.3	182.7	4.90	371.8	9.96	371.8	9.96
6 to 20 psig / 0.41 to 1.4 bar 10C1238X012 Silver	10	0.69	10	0.69	11.4	0.31	21.4	0.57	32.0	0.86
			20	1.4	19.6	0.52	36.4	0.98	53.4	1.43
			60	4.1	45.7	1.22	84.7	2.27	123.7	3.32
			100	6.9	70.5	1.89	130.6	3.50	190.7	5.11
			150	10.3	101.2	2.71	187.5	5.02	273.8	7.34
16 to 30 psig / 1.1 to 2.1 bar 10C1240X012 Red	20	1.4	25	1.7	40.3	1.08	80.5	2.16	81.7	2.19
			40	2.8	59.9	1.60	119.1	3.19	119.7	3.21
			60	4.1	84.0	2.25	166.8	4.47	167.1	4.48
			80	5.5	107.4	2.88	213.0	5.71	213.2	5.71
			150	10.3	187.5	5.02	371.8	9.96	371.8	9.96
26 to 40 psig / 1.8 to 2.8 bar 10C1241X012 Blue	30	2.1	35	2.4	28.9	0.78	59.6	1.60	88.2	2.36
			80	5.5	76.4	2.05	146.0	3.91	208.0	5.57
			125	8.6	116.0	3.11	220.0	5.90	314.0	8.42
			150	10.3	137.0	3.67	260.0	6.97	371.0	9.94
			45	3.1	43.5	1.17	96.2	2.58	106.0	2.84
36 to 50 psig / 2.5 to 3.4 bar 10C1242X012 Green	40	2.8	80	5.5	78.1	2.09	150.0	4.02	204.0	5.47
			100	6.9	97.9	2.62	187.0	5.01	253.0	6.78
			150	10.3	145.0	3.89	276.0	7.40	370.0	9.92
			55	3.8	50.4	1.35	112.0	3.00	124.0	3.32
			100	6.9	116.0	3.11	227.0	6.08	248.0	6.65
45 to 60 psig / 3.1 to 4.1 bar 10C1243X012 White	50	3.4	150	10.3	176.0	4.72	338.0	9.06	368.0	9.86
			55	3.8	43.5	1.17	92.7	2.48	124.0	3.32
			100	6.9	99.0	2.65	191.0	5.12	248.0	6.65
			150	10.3	149.0	3.99	285.0	7.64	368.0	9.86
			65	4.5	57.5	1.54	127.0	3.40	143.0	3.83
16 to 30 psig / 1.1 to 2.1 bar 10C1240X012 Red	30	2.1	80	5.5	76.4	2.05	146.0	3.91	208.0	5.57
			100	6.9	97.9	2.62	187.0	5.01	253.0	6.78
			150	10.3	145.0	3.89	276.0	7.40	370.0	9.92
			100	6.9	97.9	2.62	187.0	5.01	253.0	6.78
			150	10.3	145.0	3.89	276.0	7.40	370.0	9.92

■ - Shaded area is equal to maximum flow capacity.

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.

# 133 Series

## Pressure Reducing Regulator



**Table 9. Type 133HP Regulator 25% Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING <sup>(1)</sup>		INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY GAS AT 14.7 psia AND 60°F					
					Droop from Setpoint					
	psig	bar	psig	bar	10%		20%		30%	
					SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
2 to 5 psig / 0.14 to 0.34 bar  17B8632X012  Yellow	2	0.14	10	0.69	4.0	0.11	7.8	0.21	13.4	0.36
			40	2.8	10.5	0.28	20.6	0.55	34.9	0.94
			80	5.5	18.4	0.49	36.0	0.97	61.1	1.64
			100	6.9	22.3	0.60	43.7	1.17	74.0	1.98
			150	10.3	32.0	0.86	62.7	1.68	106.2	2.85
	5	0.34	10	0.69	8.3	0.22	11.5	0.31	11.9	0.32
			40	2.8	25.4	0.68	34.6	0.93	34.7	0.93
			60	4.1	35.2	0.94	47.9	1.28	48.0	1.29
			80	5.5	44.8	1.20	61.0	1.64	61.0	1.64
			150	10.3	78.1	2.09	106.2	2.85	106.2	2.85
4.5 to 10 psig / 0.31 to 0.69 bar  17B8633X012  Orange	5	0.34	10	0.69	4.4	0.12	8.7	0.23	11.9	0.32
			40	2.8	13.3	0.36	26.1	0.70	34.7	0.93
			80	5.5	23.4	0.63	46.1	1.24	61.0	1.64
			100	6.9	28.4	0.76	55.9	1.50	74.0	1.98
			150	10.3	40.8	1.09	80.2	2.15	106.2	2.85
	10	0.69	25	1.7	17.0	0.46	22.6	0.61	23.0	0.62
			40	2.8	25.5	0.68	33.8	0.91	34.0	0.91
			60	4.1	35.9	0.96	47.5	1.27	47.6	1.28
			80	5.5	45.9	1.23	60.8	1.63	60.9	1.63
			150	10.3	80.2	2.15	106.2	2.85	106.2	2.85
6 to 20 psig / 0.41 to 1.4 bar  10C1238X012  Silver	10	0.69	15	1	6.3	0.17	13.3	0.36	14.1	0.38
			20	1.4	8.8	0.24	18.3	0.49	18.9	0.51
			40	2.8	16.4	0.44	33.8	0.91	34.0	0.91
			100	6.9	35.8	0.96	73.9	1.98	73.9	1.98
			150	10.3	51.5	1.38	106.2	2.85	106.2	2.85
	20	1.4	25	1.7	15.7	0.42	16.8	0.45	18.6	0.50
			60	4.1	45.9	1.23	46.1	1.24	46.5	1.25
			80	5.5	59.8	1.60	60.0	1.61	60.2	1.61
			125	8.6	89.8	2.41	89.8	2.41	89.9	2.41
			150	10.3	106.1	2.84	106.1	2.84	106.2	2.85
16 to 30 psig / 1.1 to 2.1 bar  10C1240X012  Red	20	1.4	25	1.7	9.2	0.25	16.8	0.45	18.6	0.50
			60	4.1	26.6	0.71	46.1	1.24	46.5	1.25
			80	5.5	34.6	0.93	60.0	1.61	60.2	1.61
			100	6.9	61.3	1.64	106.1	2.84	106.2	2.85
			150	10.3	61.3	1.64	106.1	2.84	106.2	2.85
	30	2.1	35	2.4	18.5	0.50	20.2	0.54	23.0	0.62
			60	4.1	37.1	0.99	43.6	1.17	44.6	1.20
			100	6.9	62.1	1.66	72.3	1.94	72.7	1.95
			125	8.6	76.6	2.05	89.2	2.39	89.4	2.40
			150	10.3	90.9	2.44	105.7	2.83	105.9	2.84
26 to 40 psig / 1.8 to 2.8 bar  10C1241X012  Blue	30	2.1	35	2.4	10.3	0.28	20.2	0.54	23.0	0.62
			60	4.1	23.4	0.63	43.6	1.17	44.6	1.20
			80	5.5	31.6	0.85	58.4	1.56	59.0	1.58
			100	6.9	39.1	1.05	72.3	1.94	72.7	1.95
			150	10.3	57.3	1.54	105.7	2.83	105.9	2.84
	40	2.8	45	3.1	15.5	0.42	23.7	0.64	27.5	0.74
			80	5.5	39.9	1.07	56.0	1.50	57.2	1.53
			100	6.9	50.6	1.36	70.7	1.90	71.5	1.92
			125	8.6	63.2	1.69	88.1	2.36	88.6	2.37
			150	10.3	75.4	2.02	105.0	2.81	105.4	2.82
36 to 50 psig / 2.5 to 3.4 bar  10C1242X012  Green	40	2.8	45	3.1	12.5	0.34	23.7	0.64	27.5	0.74
			80	5.5	32.1	0.86	56.0	1.50	57.2	1.53
			100	6.9	40.7	1.09	70.7	1.90	71.5	1.92
			125	8.6	50.8	1.36	88.1	2.36	88.6	2.37
			150	10.3	60.6	1.62	105.0	2.81	105.4	2.82
	50	3.4	55	3.8	17.5	0.47	27.0	0.72	31.9	0.86
			80	5.5	37.1	0.99	52.5	1.41	54.6	1.46
			100	6.9	48.7	1.30	68.4	1.83	69.8	1.87
			125	8.6	61.9	1.66	86.6	2.32	87.5	2.34
			150	10.3	74.5	2.00	103.9	2.78	104.5	2.80
45 to 60 psig / 3.1 to 4.1 bar  10C1243X012  White	50	3.4	55	3.8	14.8	0.40	27.0	0.72	31.9	0.86
			80	5.5	31.1	0.83	52.5	1.41	54.6	1.46
			100	6.9	40.9	1.10	68.4	1.83	69.8	1.87
			125	8.6	52.0	1.39	86.6	2.32	87.5	2.34
			150	10.3	62.5	1.68	103.9	2.78	104.5	2.80
	60	4.1	65	4.5	19.5	0.52	30.4	0.82	36.4	0.98
			100	6.9	46.3	1.24	65.2	1.75	67.4	1.81
			125	8.6	60.4	1.62	84.5	2.26	85.9	2.30
			150	10.3	73.5	1.97	102.4	2.74	103.4	2.77

■ - Shaded area is equal to maximum flow capacity.

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.



**Table 10. Type 133HP Regulator 40% Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING <sup>(1)</sup>		INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY GAS AT 14.7 psia / 1 bar AND 60°F					
					Droop from Setpoint					
	psig	bar	psig	bar	10%		20%		30%	
					SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
2 to 5 psig / 0.14 to 0.34 bar  17B8632X012  Yellow	20	1.4	10	0.69	6.9	0.18	13.2	0.35	19.7	0.53
			40	2.8	16.6	0.44	31.9	0.86	47.2	1.26
			100	6.9	34.8	0.93	66.9	1.79	99.0	2.65
			150	10.3	50.0	1.34	96.0	2.57	142.1	3.81
			10	0.69	14.5	0.39	19.8	0.53	20.4	0.55
	5	0.34	20	1.4	24.4	0.65	32.8	0.88	32.9	0.88
			40	2.8	39.5	1.06	52.9	1.42	52.9	1.42
			100	6.9	82.9	2.22	111.0	2.98	111.0	2.98
			150	10.3	119.1	3.19	159.3	4.27	159.3	4.27
			10	0.69	3.8	0.10	7.1	0.19	10.4	0.28
4.5 to 10 psig / 0.31 to 0.69 bar  17B8633X012  Orange	5	0.34	20	1.4	5.8	0.16	10.7	0.29	15.7	0.42
			40	2.8	9.2	0.25	17.0	0.46	24.9	0.67
			100	6.9	19.3	0.52	35.7	0.96	52.2	1.40
			150	10.3	27.7	0.74	51.3	1.38	75.0	2.01
			25	1.7	28.2	0.76	37.0	0.99	37.4	1.00
	10	0.69	30	2.1	32.5	0.87	42.6	1.14	42.8	1.15
			40	2.8	40.5	1.08	52.9	1.42	52.9	1.42
			100	6.9	85.2	2.28	111.0	2.98	111.0	2.98
			150	10.3	122.4	3.28	159.3	4.27	159.3	4.27
			15	1.03	11.3	0.30	23.6	0.63	24.7	0.66
6 to 20 psig / 0.41 to 1.4 bar  10C1238X012  Silver	10	0.69	20	1.4	15.1	0.40	30.9	0.83	31.5	0.84
			40	2.8	26.3	0.70	52.9	1.42	52.9	1.42
			100	6.9	55.2	1.48	111.0	2.98	111.0	2.98
			150	10.3	79.3	2.12	159.3	4.27	159.3	4.27
			25	1.7	28.5	0.76	31.2	0.84	33.2	0.89
	20	1.4	40	2.8	50.4	1.35	51.2	1.37	51.9	1.39
			60	4.1	72.0	1.93	72.2	1.94	72.3	1.94
			100	6.9	111.0	2.98	111.0	2.98	111.0	2.98
			150	10.3	159.3	4.27	159.3	4.27	159.3	4.27
			25	1.7	17.2	0.46	31.2	0.84	33.2	0.89
16 to 30 psig / 1.1 to 2.1 bar  10C1240X012  Red	20	1.4	40	2.8	29.8	0.80	51.2	1.37	51.9	1.39
			60	4.1	42.5	1.14	72.2	1.94	72.3	1.94
			100	6.9	65.5	1.76	111.0	2.98	111.0	2.98
			150	10.3	94.0	2.52	159.3	4.27	159.3	4.27
			35	2.4	34.4	0.92	38.7	1.04	41.8	1.12
	30	2.1	60	4.1	61.2	1.64	71.0	1.90	71.6	1.92
			80	5.5	79.7	2.14	91.5	2.45	91.6	2.46
			100	6.9	96.9	2.60	111.0	2.98	111.0	2.98
			150	10.3	139.1	3.73	159.3	4.27	159.3	4.27
			35	2.4	19.7	0.53	38.7	1.04	41.8	1.12
26 to 40 psig / 1.8 to 2.8 bar  10C1241X012  Blue	30	2.1	60	4.1	39.0	1.04	71.0	1.90	71.6	1.92
			80	5.5	50.7	1.36	91.5	2.45	91.6	2.46
			100	6.9	61.6	1.65	111.0	2.98	111.0	2.98
			150	10.3	88.4	2.37	159.3	4.27	159.3	4.27
			45	3.1	30.3	0.81	46.2	1.24	50.4	1.35
	40	2.8	60	4.1	48.0	1.29	67.8	1.82	69.7	1.87
			80	5.5	65.6	1.76	90.5	2.42	91.2	2.44
			100	6.9	80.9	2.17	110.9	2.97	111.0	2.98
			150	10.3	116.6	3.12	159.3	4.27	159.3	4.27
			45	3.1	24.6	0.66	46.2	1.24	50.4	1.35
36 to 50 psig / 2.5 to 3.4 bar  10C1242X012  Green	40	2.8	60	4.1	38.8	1.04	67.8	1.82	69.7	1.87
			80	5.5	52.9	1.42	90.5	2.42	91.2	2.44
			100	6.9	65.3	1.75	110.9	2.97	111.0	2.98
			150	10.3	94.0	2.52	159.3	4.27	159.3	4.27
			55	3.8	34.8	0.93	53.7	1.44	59.0	1.58
	50	3.4	80	5.5	62.9	1.69	88.1	2.36	89.8	2.41
			100	6.9	79.7	2.14	110.0	2.95	110.7	2.97
			125	8.6	98.7	2.64	135.2	3.62	135.2	3.62
			150	10.3	116.6	3.12	159.3	4.27	159.3	4.27
			55	3.8	29.5	0.79	53.7	1.44	59.0	1.58
45 to 60 psig / 3.1 to 4.1 bar  10C1243X012  White	50	3.4	80	5.5	53.0	1.42	88.1	2.36	89.8	2.41
			100	6.9	67.2	1.80	110.0	2.95	110.7	2.97
			125	8.6	83.1	2.23	135.2	3.62	135.2	3.62
			150	10.3	98.1	2.63	159.3	4.27	159.3	4.27
			65	4.5	39.5	1.06	61.3	1.64	67.6	1.81
	60	4.1	100	6.9	77.8	2.08	108.0	2.89	109.6	2.94
			125	8.6	98.1	2.63	134.6	3.61	135.1	3.62
			150	10.3	116.8	3.13	159.3	4.27	159.3	4.27

■ - Shaded area is equal to maximum flow capacity.

1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.

# 133 Series

## Pressure Reducing Regulator




**Table 11. Type 133HP Regulator 60% Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING <sup>(1)</sup>		INLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY GAS AT 14.7 psia / 1 bar AND 60°F					
					Droop from Setpoint					
	psig	bar	psig	bar	10%		20%		30%	
					SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
2 to 5 psig / 0.14 to 0.34 bar  17B8632X012  Yellow	2	0.14	10	0.69	9.1	0.24	17.7	0.47	26.4	0.71
			40	2.8	24.2	0.65	47.1	1.26	70.0	1.88
			60	4.1	33.5	0.90	65.2	1.75	96.9	2.60
			150	10.3	74.5	2.00	145.0	3.89	215.6	5.78
	5	0.34	10	0.69	18.8	0.50	26.1	0.70	27.0	0.72
			40	2.8	57.8	1.55	78.4	2.10	78.5	2.10
			60	4.1	80.5	2.16	109.1	2.92	109.2	2.93
			80	5.5	102.9	2.76	139.4	3.74	139.4	3.74
			100	7.0	118.2	3.30	164.5	4.41	164.5	4.41
			150	10.3	180.2	4.83	244.0	6.54	244.0	6.54
4.5 to 10 psig / 0.31 to 0.69 bar  17B8633X012  Orange	5	0.34	10	0.69	10.0	0.27	20.0	0.54	27.0	0.72
			40	2.8	30.4	0.82	59.5	1.60	78.5	2.10
			60	4.1	42.3	1.13	82.9	2.22	109.2	2.93
			100	6.9	65.7	1.76	128.6	3.45	169.4	4.54
	10	0.69	150	10.3	94.6	2.54	185.2	4.96	244.0	6.54
			25	1.7	38.3	1.03	51.2	1.40	52.1	1.40
			40	2.8	57.8	1.55	76.6	2.07	77.1	2.07
			60	4.1	81.8	2.19	108.0	2.90	108.3	2.90
			80	5.5	105.1	2.82	138.6	3.72	138.8	3.72
			150	10.3	184.9	4.96	243.7	6.53	243.8	6.53
6 to 20 psig / 0.41 to 1.4 bar  10C1238X012  Silver	10	0.69	15	1	14.6	0.39	31.1	0.83	32.7	0.88
			40	2.8	37.3	1.00	76.6	2.05	77.1	2.07
			60	4.1	52.7	1.41	108.0	2.89	108.3	2.90
			100	6.9	82.5	2.21	168.8	4.52	168.9	4.53
	20	1.4	150	10.3	119.1	3.19	243.7	6.53	243.8	6.53
			25	1.7	36.9	0.99	40.9	1.10	44.2	1.18
			60	4.1	103.6	2.78	104.7	2.81	105.7	2.83
			80	5.5	135.5	3.63	136.3	3.65	136.9	3.67
			100	6.9	166.5	4.46	167.0	4.48	167.6	4.49
			150	10.3	242.3	6.49	242.7	6.50	243.0	6.51
16 to 30 psig / 1.1 to 2.1 bar  10C1240X012  Red	20	1.4	25	1.7	22.0	0.59	40.9	1.10	44.2	1.18
			40	2.8	40.5	1.08	71.1	1.90	72.7	1.95
			100	6.9	96.9	2.60	167.0	4.48	167.6	4.49
			150	10.3	141.0	3.78	242.7	6.50	243.0	6.51
	30	2.1	35	2.4	39.1	1.05	50.7	1.36	55.7	1.49
			60	4.1	84.3	2.26	99.7	2.67	101.8	2.73
			100	6.9	141.2	3.78	164.5	4.41	165.6	4.44
			150	10.3	207.9	5.57	241.2	6.46	241.8	6.48
			35	2.4	25.0	0.67	50.7	1.36	55.7	1.49
			60	4.1	53.4	1.43	99.7	2.67	101.8	2.73
26 to 40 psig / 1.8 to 2.8 bar  10C1241X012  Blue	30	2.1	100	6.9	89.3	2.39	164.5	4.41	165.6	4.44
			150	10.3	131.4	3.52	241.2	6.46	241.8	6.48
			45	3.1	38.5	1.03	60.5	1.62	67.1	1.80
			100	6.9	115.0	3.08	161.0	4.32	162.9	4.37
	40	2.8	125	8.6	144.0	3.86	200.5	5.37	201.9	5.41
			150	10.3	172.1	4.61	239.1	6.41	240.2	6.44
			45	3.1	31.2	0.84	60.5	1.62	67.1	1.80
			80	5.5	73.1	1.96	128.1	3.43	130.7	3.50
			100	6.9	92.6	2.48	161.0	4.32	162.9	4.37
			150	10.3	138.5	3.71	239.1	6.41	240.2	6.44
36 to 50 psig / 2.5 to 3.4 bar  10C1242X012  Green	40	2.8	55	3.8	44.2	1.18	70.3	1.88	78.6	2.11
			80	5.5	84.8	2.27	121.7	3.26	125.9	3.37
			100	6.9	110.9	2.97	156.4	4.19	159.4	4.27
			150	10.3	169.7	4.55	236.5	6.34	238.2	6.38
	50	3.4	55	3.8	37.3	1.00	70.3	1.88	78.6	2.11
			80	5.5	71.4	1.91	121.7	3.26	125.9	3.37
			100	6.9	93.2	2.50	156.4	4.19	159.4	4.27
			125	8.6	118.4	3.17	197.1	5.28	199.3	5.34
			65	4.5	50.0	1.34	80.1	2.15	90.1	2.42
			80	5.5	77.0	2.06	113.2	3.03	119.8	3.21
45 to 60 psig / 3.1 to 4.1 bar  10C1243X012  White	50	3.4	100	6.9	105.8	2.84	150.5	4.03	155.0	4.15
			150	10.3	167.4	4.49	233.2	6.25	235.8	6.32
			65	4.5	50.0	1.34	80.1	2.15	90.1	2.42
			80	5.5	77.0	2.06	113.2	3.03	119.8	3.21
	60	4.1	100	6.9	105.8	2.84	150.5	4.03	155.0	4.15
			150	10.3	167.4	4.49	233.2	6.25	235.8	6.32
			65	4.5	50.0	1.34	80.1	2.15	90.1	2.42
			80	5.5	77.0	2.06	113.2	3.03	119.8	3.21
			100	6.9	105.8	2.84	150.5	4.03	155.0	4.15
			150	10.3	167.4	4.49	233.2	6.25	235.8	6.32

■ - Shaded area is equal to maximum flow capacity.  
1. Outlet pressure setting was made at approximately 10% of the maximum capacity for the listed conditions.





GE29263

Figure 5. 133 Series Assembly Positions for Body/Spring Case Orientation




Figure 6. Dimensions

# 133 Series

## Pressure Reducing Regulator

FISHER™




Figure 6. Dimensions (continued)

## Ordering Guide

### Type (Select One)

- 133L
- 133H
- 133Z
- 133HP

### Body Material and End Connection Style (Select One)

#### Cast Iron

- NPT
- CL125 FF

#### Steel

- NPT
- CL150 RF

### Outlet Pressure Range (Select One)

#### Types 133L and 133H

- 2 to 4 in. w.c. / 5 to 10 mbar, Brown
- 3.5 to 6 in. w.c. / 9 to 15 mbar, Red
- 5 to 9 in. w.c. / 12 to 22 mbar, Black
- 8.5 to 18 in. w.c. / 21 to 45 mbar, White
- 14 to 28 in. w.c. / 35 to 70 mbar, Green
- 21 in. w.c. to 2 psig / 52 mbar to 0.14 bar, Blue

#### Type 133H

- 1.5 to 3 psig / 0.10 to 0.21 bar, Orange
- 2 to 5 psig / 0.14 to 0.34 bar, Yellow
- 5 to 10 psig / 0.34 to 0.69 bar, Blue

#### Type 133Z

- 1 to 1 in. w.c. / -2 to 2 mbar, Unpainted
- 0 to 4 in. w.c. / 0 to 10 mbar, Brown
- 5 to 10 psig / 0.34 to 0.69 bar, Blue

#### Type 133HP

- 2 to 5 psig / 0.14 to 0.34 bar, Yellow
- 4.5 to 10 psig / 0.31 to 0.69 bar, Orange
- 6 to 20 psig / 0.41 to 1.4 bar, Silver
- 16 to 30 psig / 1.1 to 2.1 bar, Red
- 26 to 40 psig / 1.8 to 2.8 bar, Blue
- 36 to 50 psig / 2.5 to 3.4 bar, Green
- 45 to 60 psig / 3.1 to 4.1 bar, White



## Ordering Guide (continued)

### Trim, Percent of Full Capacity (Select One)

- 100 percent (**standard**)
- 60 percent
- 40 percent
- 25 percent

### Elastomers (Select One)

- Nitrile (NBR) (**standard**)
- Fluorocarbon (FKM) (Available for Types 133L and 133H only)

### Body Position (Refer to Figure 5) (Select One)

- Position 1 (**standard**)
- Position 2
- Position 3
- Position 4

### Vent Position (refer to Figure 5) (Select One)

- Position C (**standard** for Type 133HP)
- Position D
- Position E (**standard** for Types 133L, 133H and 133Z)
- Position F

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Droop is the reduction of outlet pressure experienced by pressure-reducing regulators as the flow rate increases. It is stated as a percent, in inches of water column / mbar or in pounds per square inch / bar and indicates the difference between the outlet pressure setting made at low flow rates and the actual outlet pressure at the published maximum flow rate. Droop is also called offset or proportional band.

# Type 252 Filters

FISHER™

## Introduction

The Type 252 filter is designed to clean supply gas or air before it enters the pilot on a pilot-operated regulator, pneumatic instrument or other device that requires clean gas to operate properly. The extended length filter has a larger drip chamber to hold more moisture and debris. Filter materials comply with the recommendations of NACE International MR-0175.

## End Connection Size

1/4 NPT

## Maximum Working Pressure

Aluminum: 2150 psig / 148 bar  
Stainless Steel: 2750 psig / 190 bar

## Maximum Differential

100 psig / 6.9 bar

## Flow and Sizing Coefficients

C<sub>g</sub>: 20  
C<sub>v</sub>: 0.57  
C<sub>i</sub>: 35

## Filter Rating

20 microns

## Temperature Capability

-40 to 180°F / -40 to 82°C

## Approximate Shipping Weights

### Standard Body:

Aluminum: 0.8 lb / 0.4 kg  
Stainless Steel: 2.2 lbs / 1 kg

### Extended Body:

Aluminum: 1 lb / 0.5 kg  
Stainless Steel: 2.2 lbs / 1 kg

## Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/19

## Features

- Excellent Filtration
- Clean Pilot Supply Drainage
- NACE Construction
- High Flow Rate




Figure 1. Type 252 Filters




Figure 2. Type 252 Operational Schematic




Figure 2. Type 252 Operational Schematic (continued)




Figure 3. Typical Flow Capabilities

BODY	O-RING	UPPER AND LOWER SEAT	FILTER CARTRIDGE	DRAIN VALVE (OPTIONAL)
316 Stainless steel or Aluminum	Nitrile (NBR)	Acetal	Polyethylene	316 Stainless steel




Figure 4. Dimensions

## Ordering Guide

Construction Materials	
<input type="checkbox"/>	Stainless steel
<input type="checkbox"/>	Aluminum

Length	
<input type="checkbox"/>	Standard
<input type="checkbox"/>	Extended

Drain Valve	
<input type="checkbox"/>	With Stainless steel drain valve
<input type="checkbox"/>	Without Stainless steel drain valve

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.

Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.

### Regulator Tip:

When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.

# 289 Series

## Relief Valve

### Introduction

The 289 Series relief valve is a throttling relief valve used downstream of pressure regulators to protect the downstream system from overpressure. A smooth throttling action minimizes pressure surges in the system during emergency operation. The 289 Series relief valves are ideal for low-pressure settings due to the increased sensitivity provided by a large diaphragm area.

### Body Sizes and End Connection Styles

#### Inlet Connections

Type 289L: 3/4 or 1 NPT  
 Types 289A and 289U: 1/4 NPT  
 Type 289H: 1 or 2 NPT  
 Type 289HH: 1 NPT

#### Outlet (Vent) Connections

Same size as inlet connection

### IEC Sizing Coefficients

See Table 3

### Maximum Allowable Relief (Inlet) Pressures

100 psig / 6.9 bar  
 See Table 2

### Relief Set Pressure Ranges

5 in. w.c. to 75 psig / 12 mbar to 5.2 bar  
 See Table 2

### Pressure Registration

Internal

### Temperature Capabilities

**With Nitrile (NBR) and Neoprene (CR) Elastomers:** -20 to 150°F / -29 to 66°C

**With Fluorocarbon (FKM):** 20 to 300°F / -7 to 149°C

Available with Types 289H and 289HH only

### Options

- Polytetrafluoroethylene (PTFE) diaphragm protector (Types 289A and 289U only)
- Wire-seal on closing cap (1 NPT Type 289L only)

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/14

### Features

- Throttling Type Relief
- High Flow Rates
- Small Size
- Reliable Due to Simplicity

Table 1. Construction Material

TYPE	VALVE BODY AND SPRING CASE	DIAPHRAGM	GASKET	SPRING
289A	Zinc	Neoprene (CR)	Composition	Zinc-Plated Steel
289H - 1 NPT	Aluminum	Nitrile (NBR) or Fluorocarbon (FKM)		
289H - 2 NPT	Cast iron Body with Aluminum Spring Case			
289HH	Aluminum	Nitrile (NBR)	Neoprene (CR)	
289L	Aluminum		Composition	
289U	Zinc			



W18701

Figure 1. 1 NPT Types 289H and 289HH



18702N

Figure 2. 2 NPT Type 289H



W1870\_1

Figure 3. Type 289L



W1870\_2

Figure 4. Types 289A and 289U




Figure 5. 289 Series Operational Schematics


**Table 2. Spring Range and Maximum Allowable Relief (Inlet) Pressure**

TYPE	BODY SIZE, NPT	SPRING PART NUMBER	COLOR CODE	SPRING RANGE (RELIEF PRESSURE SETTING)		MAXIMUM ALLOWABLE RELIEF (INLET) PRESSURE <sup>(1)</sup>	
				psig	bar	psig	bar
289A	1/4	0Z056327022 1B268227022	Silver Silver	3 to 13 11 to 22	0.21 to 0.90 0.76 to 1.5	45	3.1
289H	1	1F826927052 1D892327022 1D751527022 1D7455T0012	Pink	1 to 4.5	0.07 to 0.31	100	6.9
			Red	4 to 15	0.28 to 1.0		
Silver	10 to 20		0.69 to 1.4				
Green	15 to 50		1.0 to 3.4				
289H	2	1B536527052 1B536627052 1B536827062 1B536927052	Dark Blue	7 to 18 in. w.c.	17 to 45 mbar	25	1.7
			Gray	0.5 to 2.25	0.03 to 0.16		
			Dark Green	1.75 to 7	0.12 to 0.48		
			Red Stripe	4 to 10	0.28 to 0.69		
289HH	1	1D7455T0012	Green	45 to 75	3.1 to 5.2	100	6.9
289L	3/4 or 1	13A7917X012 13A7916X012	Silver Red Stripe	10 to 18 in. w.c. 12 to 40 in. w.c.	25 to 45 mbar 30 to 99 mbar	7	0.48
289U	1/4	0V060227022 0F058227022	Silver Silver	5 to 25 in. w.c. 20 in. w.c. to 3 psig	12 to 62 mbar 50 to 207 mbar	10	0.69

1. This value indicates the relief pressure setting plus pressure build-up.

**Table 3. IEC Sizing Coefficient**

BODY SIZE, NPS	X <sub>r</sub>	F <sub>d</sub>	F <sub>L</sub>
1/4	0.775	0.50	0.89
3/4	0.775		
1	0.648		
2	0.616		




**NOTE:**

- LESS THAN A 5% CAPACITY LOSS CAN BE EXPECTED WITH THE VENT SCREEN INSTALLED ON THE 2 NPT TYPE 289H AT MAXIMUM FLOW.
- WHEN SELECTING ANY RELIEF VALVE FOR INSTALLATION DOWNSTREAM OF THE REGULATOR, THE CAPACITY OF THE RELIEF VALVE SHOULD BE COMPARED WITH THE WIDE-OPEN CAPACITY OF THE REGULATOR.
- BUBBLE POINT RELIEF SETTING AND SPRING PART NUMBER ARE NOTED ON EACH CURVE.
- TO CONVERT TO EQUIVALENT CAPACITIES OF OTHER GASES, MULTIPLY VALUES OBTAINED FROM CURVE BY THE FOLLOWING FACTORS: AIR = 0.78, PROPANE = 0.628, BUTANE = 0.548, NITROGEN = 0.789.

**Figure 6. Type 289H Capacities**






NOTE:

1. LESS THAN A 5% CAPACITY LOSS CAN BE EXPECTED WITH THE VENT SCREEN INSTALLED ON THE 2 NPT TYPE 289H AT MAXIMUM FLOW.
2. WHEN SELECTING ANY RELIEF VALVE FOR INSTALLATION DOWNSTREAM OF THE REGULATOR, THE CAPACITY OF THE RELIEF VALVE SHOULD BE COMPARED WITH THE WIDE-OPEN CAPACITY OF THE REGULATOR.
3. BUBBLE POINT RELIEF SETTING AND SPRING PART NUMBER ARE NOTED ON EACH CURVE.
4. TO CONVERT TO EQUIVALENT CAPACITIES OF OTHER GASES, MULTIPLY VALUES OBTAINED FROM CURVE BY THE FOLLOWING FACTORS: AIR = 0.78, PROPANE = 0.628, BUTANE = 0.548, NITROGEN = 0.789.


Figure 6. Type 289H Capacities (continued)



NOTE:

1. WHEN SELECTING ANY RELIEF VALVE FOR INSTALLATION DOWNSTREAM OF THE REGULATOR, THE CAPACITY OF THE RELIEF VALVE SHOULD BE COMPARED WITH THE WIDE-OPEN CAPACITY OF THE REGULATOR.
2. BUBBLE POINT RELIEF SETTING IS NOTED ON EACH CURVE.
3. TO CONVERT TO EQUIVALENT CAPACITIES OF OTHER GASES, MULTIPLY VALUES OBTAINED FROM CURVE BY THE FOLLOWING FACTORS: AIR = 0.78, PROPANE = 0.628, BUTANE = 0.548, NITROGEN = 0.789.


Figure 7. Type 289L Capacities



**NOTE:**

1. WHEN SELECTING ANY RELIEF VALVE FOR INSTALLATION DOWNSTREAM OF THE REGULATOR, THE CAPACITY OF THE RELIEF VALVE SHOULD BE COMPARED WITH THE WIDE-OPEN CAPACITY OF THE REGULATOR.
2. BUBBLE POINT RELIEF SETTING AND SPRING PART NUMBER ARE NOTED ON EACH CURVE.
3. TO CONVERT TO EQUIVALENT CAPACITIES OF OTHER GASES, MULTIPLY VALUES OBTAINED FROM CURVE BY THE FOLLOWING FACTORS: AIR = 0.78, PROPANE = 0.628, BUTANE = 0.548, NITROGEN = 0.789.

Figure 8. Type 289HH Capacities



**NOTE:**

1. WHEN SELECTING ANY RELIEF VALVE FOR INSTALLATION DOWNSTREAM OF THE REGULATOR, THE CAPACITY OF THE RELIEF VALVE SHOULD BE COMPARED WITH THE WIDE-OPEN CAPACITY OF THE REGULATOR.
2. BUBBLE POINT RELIEF SETTING AND SPRING PART NUMBER ARE NOTED ON EACH CURVE.
3. TO CONVERT TO EQUIVALENT CAPACITIES OF OTHER GASES, MULTIPLY VALUES OBTAINED FROM CURVE BY THE FOLLOWING FACTORS: AIR = 0.78, PROPANE = 0.628, BUTANE = 0.548, NITROGEN = 0.789.

Figure 9. Type 289U Capacities






Figure 10. Dimensions

Table 4. Shipping Weight

TYPE	BODY SIZE, NPS	APPROXIMATE SHIPPING WEIGHT	
		lb	kg
289A and 289U	1/4	0.75	0.3
289H	1	4	2
	2	15	7
289HH	1	4	2
289L	3/4 or 1	15	7

## Ordering Guide

Type, Body Size and Material (Select One)
<b>Type 289A</b>
<input type="checkbox"/> 1/4 NPT, Zinc***
<b>Type 289H</b>
<input type="checkbox"/> 1 NPT Aluminum***
<input type="checkbox"/> 2 NPT Cast iron with aluminum spring case***
<b>Type 289HH</b>
<input type="checkbox"/> 1 NPT Aluminum***
<b>Type 289L</b>
<input type="checkbox"/> 3/4 NPT Aluminum***
<input type="checkbox"/> 1 NPT Aluminum***
<b>Type 289U</b>
<input type="checkbox"/> 1/4 NPT, Zinc***

Relief Set Pressure Range (Select One)
<b>Type 289A</b>
<input type="checkbox"/> 3 to 13 psig / 0.21 to 0.90 bar***
<input type="checkbox"/> 11 to 22 psig / 0.76 to 1.5 bar***
<b>Type 289H, 1 NPT</b>
<input type="checkbox"/> 1 to 4.5 psig / 0.07 to 0.31 bar***
<input type="checkbox"/> 4 to 15 psig / 0.28 to 1.0 bar***
<input type="checkbox"/> 10 to 20 psig / 0.69 to 1.4 bar***
<input type="checkbox"/> 15 to 50 psig / 1.0 to 3.4 bar***

- continued -

### Ordering Guide (continued)

#### Relief Set Pressure Range (Select One) (continued)

##### Type 289H, 2 NPT

- 7 to 18 in. w.c. / 17 to 45 mbar\*\*\*
- 0.5 to 2.25 psig / 0.03 to 0.16 bar\*\*\*
- 1.75 to 7 psig / 0.12 to 0.48 bar\*\*\*
- 4 to 10 psig / 0.28 to 0.69 bar\*\*\*

##### Type 289HH

- 45 to 75 psig / 3.1 to 5.2 bar\*\*\*

##### Type 289L

- 10 to 18 in. w.c. / 25 to 45 mbar\*\*\*
- 12 to 40 in. w.c. / 30 to 99 mbar\*\*\*

##### Type 289U

- 5 to 25 in. w.c. / 12 to 62 mbar\*\*\*
- 20 in. w.c. to 3 psig / 50 to 207 mbar\*\*\*

#### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### Specification Worksheet

<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

#### Regulator Tip:

When using relief valves, be sure to remember that the reset point is lower than the start-to-bubble point. To avoid seepage, keep the relief valve setpoint far enough above the regulator setpoint.

### Introduction

Type 289P is an accurate, low-cost, pilot-operated relief valve. This relief valve is suitable for service on natural gas, air, propane and other operating media compatible with the internal parts. The external control line provides quick, accurate pressure registration. Pilot operation requires very little buildup over set pressure to completely open the main valve for maximum relief capacity.

### Body Sizes and End Connection Styles

1 or 2 NPT

### Flow and Sizing Coefficients

See Table 7

### Maximum Relief (Inlet) Pressures

1 NPT: 50 psig / 3.4 bar over relief pressure setting or 110 psig / 7.6 bar, whichever is lower  
 2 NPT: 15 psig / 1.0 bar

### Set Pressure Ranges

1 NPT: 10 to 100 psig / 0.69 to 6.9 bar  
 2 NPT: 14 in. w.c. to 10 psig / 35 mbar to 0.69 bar  
 See Table 4

### Pressure Registration

External

### Temperature Capabilities

**With Nitrile (NBR):**  
 -20 to 180°F / -29 to 82°C  
**With Fluorocarbon (FKM):**  
 0 to 300°F / -18 to 149°C

### Approximate Weights

1 NPT: 5 lbs / 2.3 kg  
 2 NPT: 15 lbs / 6.8 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/19


### Features

- Fast Reseat After Operation
- Economical
- High Relief Capacity With Low Buildup
- Accurate
- Fast Reseat After Operation
- Ease of Maintenance
- Rugged Construction
- Power Paint Coating
- Corrosion Resistant Fasteners
- Full Usable Capacity




W6834

Figure 1. 1 NPT Type 289P Pilot-Operated Relief Valve



W3167\_3

Figure 2. 2 NPT Type 289P Pilot-Operated Relief Valve



# Type 289P

## Relief Valve/Backpressure Regulator

FISHER™

**Table 1. Main Valve Construction Material**

BODY SIZE	BODY	SPRING CASE	DIAPHRAGM AND O-RING	PITOT TUBE OR STEM	STEM GUIDE
1 NPT	Aluminum	Aluminum	Nitrile (NBR) or Fluorocarbon (FKM)	Aluminum	Brass and Stainless steel, Zinc and brass
2 NPT	Cast iron	Aluminum	Nitrile (NBR)	Brass	Cast iron and Brass

**Table 2. Type 6358B Pilot Construction Material**

BODY AND SPRING CASE	VALVE PLUG AND STEM	DIAPHRAGM	PILOT SPRING
Aluminum	Nitrile (NBR) or Fluorocarbon (FKM) and Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)	Steel

**Table 3. Type 6365 Pilot Construction Material**

BODY AND SPRING CASE	DIAPHRAGM	STEM GUIDE	SPRING
Aluminum	Nitrile (NBR)	416 Stainless steel	Steel

**Table 4. Relief Set Pressure and Pilot Control Spring Information**

MAIN VALVE BODY SIZE	PILOT TYPE	RELIEF SET PRESSURE RANGE		PILOT CONTROL SPRING INFORMATION					
		psig	bar	Part Number	Color	Wire Diameter		Free Length	
						In.	mm	In.	mm
1 NPT	6358B	10 to 18	0.69 to 1.2	1B986027212	Green Unpainted Red	0.120	3.05	2.13	54.1
		18 to 30	1.2 to 2.1	1B788327022		0.142	3.61		
		30 to 100	2.1 to 6.9	1K748527202		0.187	4.75		
2 NPT	6365	14 in. w.c. to 2 psig	35 mbar to 0.14 bar	14A9672X012	Yellow	0.070	1.78		
	6358B	2 to 10	0.14 to 0.69	14A9673X012	Black	0.102	2.59		

**Table 5. Capacities for 1 NPT Main Valve Body and Type 6358B Pilot Information**

MAIN VALVE SPRING, PART NUMBER AND COLOR	SET PRESSURE RANGE		SET PRESSURE <sup>(1)</sup>		BUILDUP OVER SET PRESSURE TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILDUP OVER SET PRESSURE TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE TO RESEAT PILOT		CAPACITIES OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(4)</sup>	
	psig	bar	psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h
For set pressures up to 30 psig / 2.1 bar 1F826927052 Pink	10 to 18	0.69 to 1.2	10 15 18	0.69 1.0 1.2	0.8	0.05	1.0	0.07	1.0	0.07	23,000 29,000 32,000	616 777 858
	18 to 30	1.2 to 2.1	18 25 30	1.2 1.7 2.1	0.9	0.06	1.2	0.08	1.0	0.07	32,000 39,000 44,000	858 1045 1179
For set pressures over 30 psig / 2.1 bar 1D892327022 Red	30 to 100	2.1 to 6.9	30	2.1	1.4	0.10	1.9	0.13	1.0	0.07	44,000	1179
			40	2.8							54,000	1447
			50	3.4							64,000	1715
			60	4.1	1.6	0.11	2.1	0.15	1.0	0.07	73,000	1956
			70	4.8							83,000	2224
			80	5.5							92,000	2466
90	6.2	102,000	2734									
100	6.9	111,000	2975									

1. Set pressure is defined as the pressure at which the pilot exhaust starts-to-bubble (discharge).
2. Crack pressure is the inlet pressure at which the main valve starts audible flow.
3. Inlet pressure buildup over the set pressure to achieve wide-open capacity.
4. Capacities with inlet piping equal to body size and without outlet piping.

**Table 6. Capacities for 2 NPT Main Valve Body and Types 6365 and 6358B Pilot Information**

PILOT TYPE	RELIEF SET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	SET PRESSURE <sup>(1)</sup>		BUILDUP OVER SET PRESSURE TO FULLY OPEN MAIN VALVE <sup>(2)</sup>		PRESSURE DROP BELOW SET PRESSURE TO RESEAT PILOT		CAPACITIES OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(3)</sup>	
		psig	bar	psig	mbar	psi	mbar	SCFH	Nm <sup>3</sup> /h
6365	14 in. w.c. to 2 psig / 35 mbar to 0.14 bar 14A9672X012 Yellow	0.5	0.03	0.25	17	0.25	17	18,700	501
		1.0	0.07					24,000	643
		1.5	0.10					28,400	761
		2.0	0.14					32,100	860
6358B	2 to 10 psig / 0.14 to 0.69 bar 14A9673X012 Black	2.0	0.14	0.30	21	0.30	21	32,500	871
		4.0	0.28					44,300	1187
		6.0	0.41					53,700	1439
		8.0	0.55					62,000	1662
		10.0	0.69					69,500	1863


1. Set pressure is defined as the pressure at which the pilot exhaust starts-to-bubble (discharge).
2. Inlet pressure buildup over the set pressure to achieve wide-open capacity.
3. Capacities with inlet piping equal to body size and without outlet piping.

**Table 7. Flow and Sizing Coefficient**

MAIN VALVE BODY SIZE	LINE SIZE EQUALS BODY SIZE		2:1 LINE SIZE TO BODY SIZE PIPING		C <sub>1</sub>	IEC SIZING COEFFICIENT		
	C <sub>g</sub>	C <sub>v</sub>	C <sub>g</sub>	C <sub>v</sub>		X <sub>r</sub>	F <sub>0</sub>	F <sub>L</sub>
1 NPT	740	23.1	2290	73.4	32	0.648	0.50	0.89
2 NPT	560	17.5	2050	65.7	31.2	0.616		


Note: Wide-open flow coefficients without outlet piping and outlet screen.





17B4932

1 NPT BODY SIZE



16A014\_B2

2 NPT BODY SIZE

IN. /  
mm

Figure 4. Type 289P-6365 Dimensions

# Type 289P

Relief Valve/Backpressure Regulator

FISHER™

## Ordering Guide

### 1 NPT Type 289P

#### Main Valve Diaphragm (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Main Valve O-ring (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Main Valve Stem Guide Assembly (Select One)

- Brass with Stainless steel bushing **(standard)**\*\*\*
- Zinc with brass bushing\*\*

#### Relief Set Pressure Range (Select One)

- 10 to 18 psig / 0.69 to 1.2 bar, Green\*\*\*
- 18 to 30 psig / 1.2 to 2.1 bar, Unpainted\*\*\*
- 30 to 100 psig / 2.1 to 6.9 bar, Red\*\*\*

#### Pilot Valve Plug and Stem (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Pilot Diaphragm (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Pilot O-ring and Gasket (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Main Valve Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

#### Pilot Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

### 2 NPT Type 289P

#### Relief Set Pressure Range (Select One)

##### Type 6365 Pilot

- 14 in. w.c. to 2 psig / 35 mbar to 0.14 bar, Yellow\*\*\*

##### Type 6358B Pilot

- 2 to 10 psig / 0.14 to 0.69 bar, Black\*\*\*

#### Type 6358B Pilot Valve Plug and Stem (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Type 6358B Pilot Diaphragm (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Type 6358B Pilot O-ring and Gasket (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

#### Main Valve Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

#### Pilot Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.

# 299H Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The 299H Series pressure reducing regulators provide a broad capacity of controlled pressure ranges and capacities in a wide variety of distribution, industrial and commercial applications. A 299H Series regulator has a pilot integrally mounted to the actuator casing. The 299H Series regulators can handle inlet pressures up to 175 psig / 12.1 bar depending on orifice size.

The integral token relief on the Types 299HR and 299HVR regulators is located in the pilot and alerts you to an increase in downstream pressure beyond the regulator setpoint.

The Type 299HV provides overpressure or overpressure and underpressure protection by completely shutting off the flow of gas to the downstream system. It comes with a Type VSX8 (299HV) slam-shut device which can be configured for Overpressure Shutoff (OPSO) or Overpressure and Underpressure Shutoff (OPSO/UPSO). The slam-shut device's actions are independent of the main valve and of variations to the inlet pressure. The Type VSX8 (299HV) slam-shut device has internal or external registration. External registration requires a downstream sensing line.

**Body Size and End Connection Styles**  
See Table 1

**Maximum Operating Inlet Pressure by Orifice Size<sup>(1)</sup>**  
175 psig / 12.1 bar  
See Table 3

**Outlet (Control) Pressure Ranges<sup>(1)(2)</sup>**  
See Table 4

**Maximum Set Pressure for Slam Shut Device<sup>(1)</sup>**  
See Table 4

**Maximum Casing and Emergency Outlet Pressure<sup>(1)</sup>**  
66 psig / 4.5 bar

**Maximum Set Pressure for Type 299HV<sup>(1)</sup>**  
16 psig / 1.1 bar

**Minimum and Maximum Slam-Shut Trip Pressure Ranges Types 299HV and 299HVR:**  
21 psig / 1.45 bar



Figure 1. 299H Series Pressure Reducing Regulators

### Flow Coefficients

See Table 5

### Flow Capacities

See Tables 7 through 12

### Minimum Differential Pressure For Full stroke

1.5 psid / 0.10 bar d

### Temperature Capabilities<sup>(1)(5)</sup>

-20 to 150°F / -29 to 66°C

### Approximate Weight

21 lbs / 10 kg

### Pressure Registration

Internal, External or Dual Registration  
See Figures 2 and 3

### Fixed Restriction Sizes

0.044 in. / 1.1 mm, Red (standard gain)  
0.071 in. / 1.8 mm, Green (low gain)  
0.082 in. / 2.1 mm, Blue (lower gain)

### Options

**Filter<sup>(3)</sup>:** A P590 Series filter installed in the pilot supply tubing between main body and pilot  
**Filtered pilot supply regulator<sup>(3)(4)</sup>:**  
A Type 67CF supply regulator with integral 5 micron Polyethylene filter  
**Reed switch:** An optional remote notification switch can be installed offering the capability to remotely notify the operator should VSX8 Series shut off occur. (Types 299HV and 299HVR only)

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

08/19

### Features

- Compact size
- Unique no Bleed Monitor system
- ±1% accuracy for Fixed Factor Billing (PFM)
- Wide Variety of applications
- Economical, labor-saving Installation
- High-Capacity pressure Control
- Easy registration conversion

1. The pressure/temperature limits in this Application Guide and any applicable standard or code limitation should not be exceeded.  
2. For optimum performance, a pilot supply regulator may be installed in the pilot supply tubing between the main valve and pilot.  
3. A pilot supply regulator or a P590 Series filter (only one may be used, not both) may be ordered with the Type 299H, but not both.  
4. For in. w.c., use a pilot supply regulator if actual inlet pressure varies more than ±20 psi / ±1.4 bar and published accuracy is required.  
5. Product has passed Emerson Process Management Regulator Technologies, Inc. testing for lockup, relief start-to-discharge and reseal down to -40°.






Figure 2. Type 299H Operational Schematic




Figure 3. Type 299HV Operational Schematic

# 299H Series

## Pressure Reducing Regulator

FISHER™

**Table 1. Body Size and End Connection Style**

BODY SIZE	BODY MATERIAL AND END CONNECTION STYLE		
	Cast Iron (For Types 299H and 299HR only)	Ductile Iron	Steel (For Types 299H and 299HR only)
NPS 1-1/4 NPS 1-1/2	NPT NPT	---- NPT	---- NPT
NPS 2 / DN 50	NPT, CL125 FF Flanged <sup>(1)</sup>	NPT, CL125 FF and CL250 RF Flanged, PN 10/16 Flanged	NPT, CL150 RF Flanged

1. This flange is available with a face-to-face dimension of 7.5 or 10 In. / 191 or 254 mm.

**Table 2. Main Valve Construction Material**

VALVE BODY	ACTUATOR CASING AND PILOT SPRING CASE	DIAPHRAGM, DISK AND O-RING	ORIFICE, VALVE STEM AND DISK HOLDER	TUBING AND FITTING
Cast iron, Ductile iron or Steel	Aluminum	Nitrile (NBR)	Aluminum	Stainless steel tubing with steel fittings (Standard) or Stainless steel tubing and fittings

**Table 3. Maximum Operating Inlet Pressure<sup>(1)</sup>**

ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE	
In.	mm	psig	bar
1/4 x 3/8	6.4 x 9.5	175	12.1
3/8	9.5	175	12.1
1/2	13	175	12.1
3/4	19	150	10.3
7/8 <sup>(2)</sup>	22 <sup>(2)</sup>	125	8.6
1 <sup>(2)</sup>	25 <sup>(2)</sup>	100	6.9
1-3/16 <sup>(2)</sup>	30 <sup>(2)</sup>	80	5.5

1. The pressure/temperature limits in this document and any applicable standard or code limitation should not be exceeded.  
2. This orifice size is not available for Types 299HV and 299HVR.

**Table 4. Outlet Pressure Range**

OUTLET (CONTROL) PRESSURE RANGE		TYPE		PILOT CONTROL SPRING					
		299H	299HR, 299HV and 299HVR	Part Number	Color	Free Length		Wire Diameter	
						In.	mm	In.	mm
In. w.c.	mbar								
3.5 to 6 <sup>(1)</sup>	9 to 15 <sup>(1)</sup>	X	X	T13707T0012	Black	1.86	47.2	0.055	1.40
5 to 9 <sup>(1)</sup>	12 to 22 <sup>(1)</sup>	X	X	T13589T0012	Yellow	2.05	52.1	0.051	1.30
7 to 20 <sup>(1)</sup>	17 to 50 <sup>(1)</sup>	X	X	1N3112X0012	Unpainted	2.18	55.4	0.075	1.90
16 to 40 <sup>(1)</sup>	40 to 99 <sup>(1)</sup>	X	X	1B413727222	Purple	2.12	53.8	0.092	2.34
1 to 3.25 psig	69 mbar to 0.22 bar	X	X	T13593T0012	Light blue	2.12	53.8	0.105	2.67
2.75 to 6 psig	0.19 to 0.41 bar	X	X	T13671T0012	Orange	2.40	61.0	0.120	3.05
5 to 16 psig	0.34 to 1.1 bar	X	X	T13600T0012	Red	2.10	53.3	0.142	3.61
14 to 35 psig	0.97 to 2.4 bar	X	----	19B0432X012	Zinc	2.15	54.6	0.207	5.26
30 to 60 psig	2.1 to 4.1 bar	X	----	19B0432X022	Green	2.75	69.8	0.225	5.71

1. Use a pilot supply regulator if actual inlet pressure varies more than  $\pm 20$  psi /  $\pm 1.4$  bar and the published accuracy is required.

**Table 5. Flow Coefficient**

TYPE	ORIFICE DIAMETER		WIDE-OPEN		REGULATING <sup>(1)</sup>		C <sub>v</sub> WHEN $\Delta P < 10$ psi / 0.69 bar	C <sub>v</sub> WHEN $\Delta P > 10$ psi / 0.69 bar
	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>g</sub>	C <sub>v</sub>		
299H / 299HR	1/4 x 3/8	6.4 x 9.5	53	2.0	50	1.9	26	26
	3/8	9.5	117	4.2	115	4.0	30	28
	1/2	13	203	7.0	200	6.9	30	28
	3/4	19	437	14.1	430	13.9	32	30
	7/8	22	544	16.5	534	16.2	34	32
	1	25	725	20.7	710	20.3	36	34
	1-3/16	30	910	25.3	885	24.6	37	35
299HV / 299HVR	1/4 x 3/8	6.4 x 9.5	53	2.0	50	1.9	26	26
	3/8	9.5	117	4.1	115	4.0	30	28
	1/2	13	184	5.0	180	4.9	38	36
	3/4	19	421	11.9	415	11.7	36	35

1. For external/dual registration only.

**Table 6a. Type VSX8 High and Low Trip Pressure Ranges (North American Overpressure Shut-off OPSO Ranges Only)**

REGULATOR			SLAM SHUT DEVICE			
Type	Typical Setpoint	Spring Range	Type	OPSO		OPSO <sup>(1)</sup> Typical Set
				Set Range Over UPSO Setpoint	Spring Part Number and Color	
	In. w.c.	In. w.c.		In. w.c.		In. w.c.
299HV 299HVR	4.0	3.5 to 6.0	VSX8L	12.0 to 24.0	GF02168X012, Brown	19.0
	7.0	5.0 to 9.0				22.0
	11.0	7.0 to 20.0		16.0 in. w.c. to 1.6 psig	GF02169X012, Red	25.0
	14.0			24.0 in. w.c. to 2.8 psig	GF02170X012, Orange	1.1 psig
	1 psig	16.0 in. w.c. to 1.4 psig		2.0 to 7.3 psig	GF02172X012, Green	2.0 psig
	2.0 psig	1.0 to 3.3 psig				3.5 psig
	3.0 psig	2.8 to 6.0 psig		3.2 to 11.0 psig	GF02173X012, Silver	5.0 psig
	5.0 psig					7.0 psig
	10.0 psig	5.0 to 16.0 psig		5.8 to 21.0 psig	GF04353X012, Yellow	12.0 psig
	15.0 psig					19.0 psig

1. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 7.  
 Note: Other spring combinations are available. Please contact your local Sales Office for additional information.

**Table 6b. Type VSX8 High and Low Trip Pressure Ranges (European Overpressure Shut-off OPSO Ranges Only)**

REGULATOR			SLAM SHUT DEVICE			
Type	Typical Setpoint	Spring Range	Type	OPSO		OPSO <sup>(1)</sup> Typical Set
				Set Range Over UPSO Setpoint	Spring Part Number and Color	
	mbar	mbar		mbar		mbar
299HV 299HVR	21	12 to 22	VSX8L	30 to 60	GF02168X012, Brown	45
	35	17 to 50		40 to 110	GF02169X012, Red	67
	50	40 to 100		60 to 190	GF02170X012, Orange	90
	60					104
	75	70 to 224		140 to 500	GF02172X012, Green	128
	100					170
	150	190 to 414		220 to 760	GF02173X012, Silver	248
	300	345 to 1103		400 to 1450	GF04353X012, Yellow	450
	500					700

1. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 7.  
 Note: Other spring combinations are available. Please contact your local Sales Office for additional information.

# 299H Series

## Pressure Reducing Regulator

FISHER™

**Table 6c. Type VSX8 High and Low Trip Pressure Ranges  
(North American Overpressure and Underpressure Shut-off UPSO/OPSO Ranges)**

REGULATOR			SLAM SHUT DEVICE							
Type	Typical Setpoint	Spring Range	Type	UPSO		OPSO		Typical Set		
	In. w.c.	In. w.c.		Set Range <sup>(1)</sup>	Spring Part Number and Color	Set Range Over UPSO Setpoint	Spring Part Number and Color	UPSO	Adjusted OPSO Range	OPSO <sup>(2)</sup>
				In. w.c.		In. w.c.		In. w.c.		In. w.c.
299HV 299HVR	7.0 <sup>(3)</sup>	5.0 to 9.0	VSX8L	3.0 to 12.0	ERAA05835A0 White	18 in. w.c. to 1.1 psig	GF02168X012 Brown	3 <sup>(3)</sup>	21 in. w.c. to 1.2 psig	22.0
	11.0 <sup>(3)</sup>	7.0 to 20.0						6 <sup>(3)</sup>	24 in. w.c. to 1.3 psig	25.0
	14.0 <sup>(3)</sup>			4.0 in. w.c. to 1.1 psig	T14169T0012 Blue	25 in. w.c. to 1.9 psig	GF02169X012 Red	9 <sup>(3)</sup>	27 in. w.c. to 1.3 psig	1.1 psig
	1.0 psig <sup>(3)</sup>	16.0 in. w.c. to 1.4 psig						14 <sup>(3)</sup>	1.4 to 2.4 psig	2.0 psig
	2.0 psig <sup>(4)</sup>	1.0 psig to 3.3 psig		10.0 in. w.c. to 2.3 psig	T14170T0012 Silver	1.2 to 3.2 psig	GF02170X012 Orange	1.0 psig <sup>(4)</sup>	2.2 to 4.2 psig	3.5 psig
	3.0 psig <sup>(4)</sup>	2.8 to 6.0 psig		1.5 to 7.3 psig	FA142869X12 Orange Stripe	2.6 to 5.6 psig	GF02171X012 Pink	2.0 psig <sup>(4)</sup>	4.4 to 7.4 psig	5.0 psig
	5.0 psig <sup>(4)</sup>							3.0 psig <sup>(4)</sup>	6.5 to 11.2 psig	7.0 psig
	10.0 psig <sup>(5)</sup>	5.0 to 16.0 psig		1.5 to 10.9 psig	T14171T0012 Olive	6.7 to 13.5 psig	GF02172X012 Green	5.0 psig <sup>(5)</sup>	10.5 to 15.2 psig	12 psig
15.0 psig <sup>(5)</sup>	7.0 psig <sup>(5)</sup>		13.7 to 20.5 psig					19.0 psig		

1. If Non-Factory UPSO setpoints are specified, a minimum differential of 4 in. w.c. between UPSO setpoint and regulator setpoint must be maintained in order to ensure a secure latch of the Slam-Shut.
  2. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 7.
  3. For an internally registered Type VSX8, UPSO cannot be used with this main valve spring range to provide underpressure shutoff under flowing conditions. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
  4. For an internally registered Type VSX8, 70% of regulator setpoint is the minimum allowable UPSO setting used with this main valve spring range. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
  5. For an internally registered Type VSX8, 75% of regulator setpoint is the minimum allowable UPSO setting used with this main valve spring range. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
- Note: Other spring combinations are available. Please contact your local Sales Office for additional information.

**Table 6d. Type VSX8 High and Low Trip Pressure Ranges  
(European Overpressure and Underpressure Shut-off UPSO/OPSO Ranges)**

REGULATOR			SLAM SHUT DEVICE							
Type	Typical Setpoint, mbar	Spring Range, mbar	Type	UPSO		OPSO		Typical Set		
				Set Range <sup>(1)</sup>	Spring Part Number and Color	Set Range Over UPSO Setpoint	Spring Part Number and Color	UPSO	Adjusted OPSO Range	OPSO <sup>(2)</sup>
				mbar		mbar		mbar		mbar
299HV 299HVR	21 <sup>(3)</sup>	12 to 22	VSX8L	7 to 30	ERAA05835A0 White	40 to 55	GF02167X012 Black	10 <sup>(3)</sup>	50 to 65	55
	35 <sup>(3)</sup>	17 to 50				45 to 76	GF02168X012 Brown	18 <sup>(3)</sup>	63 to 94	67
	50 <sup>(3)</sup>	40 to 100		10 to 75	T14169T0012 Blue	50 to 80	GF02169X012 Red	25 <sup>(3)</sup>	75 to 105	90
	60 <sup>(3)</sup>					62 to 132	30 <sup>(3)</sup>	80 to 110	104	
	75 <sup>(3)</sup>	70 to 224		25 to 160	T14170T0012 Silver	83 to 221	GF02170X012 Orange	38 <sup>(3)</sup>	100 to 170	128
	100 <sup>(4)</sup>					100 to 500	FA142869X12 Orange Stripe	179 to 386	GF02171X012 Pink	50 <sup>(4)</sup>
	150 <sup>(4)</sup>	190 to 414		100 to 750	T14171T0012 Olive	460 to 932	GF02173X012 Silver	75 <sup>(4)</sup>	158 to 296	248
	300 <sup>(4)</sup>					345 to 1103	250 <sup>(5)</sup>	710 to 1182	710	
500 <sup>(5)</sup>						500 <sup>(5)</sup>	960 to 1432	1320		

1. If Non-Factory UPSO setpoints are specified, a minimum differential of 10 mbar between UPSO setpoint and regulator setpoint must be maintained in order to ensure a secure latch of the Slam-Shut.
  2. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 7.
  3. For an internally registered Type VSX8, UPSO cannot be used with this main valve spring range to provide underpressure shutoff under flowing conditions. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
  4. For an internally registered Type VSX8, 70% of regulator setpoint is the minimum allowable UPSO setting used with this main valve spring range. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
  5. For an internally registered Type VSX8, 75% of regulator setpoint is the minimum allowable UPSO setting used with this main valve spring range. If protection against loss of inlet pressure is the only required function for the Type VSX8 then an internally registered Type VSX8 may be used with the same minimum trip pressures as an externally registered Type VSX8.
- Note: Other spring combinations are available. Please contact your local Sales Office for additional information.















# 299H Series

## Pressure Reducing Regulator

FISHER™

**Table 8. Types 299H and 299HR Flow Capacities<sup>(1)</sup> for 1-1/2 NPT Internal Registration (continued)**

OUTLET PRESSURE RANGE, SETTING, ACCURACY, SPRING PART NUMBER AND COLOR	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
			Orifice Size, In. / mm											
			1/4 x 3/8 / 6.4 x 9.5		3/8 / 9.5		1/2 / 13		3/4 / 19		1 / 25		1-3/16 / 30	
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
14 to 35 psig / 0.97 to 2.4 bar  25 psig / 1.7 bar ±1% psia / bar  19B0432X012 Zinc	30	2.1	2070	55.5	4230	113	7360	197	14,300	383	16,880	452	17,700	474
	40	2.8	3320	89.0	7350	197	12,780	343	16,810	451	24,040	644	24,090	646
	50	3.4	4140	111	9340	250	16,250	436	21,090	565	24,430	655	23,500	630
	60	4.1	4830	129	11,030	296	18,050	484	25,240	676	28,260	757	27,400	734
	80	5.5	6110	164	14,050	377	22,050	591	28,250	757	30,200	809	28,500	764
14 to 35 psig / 0.97 to 2.4 bar  30 psig / 2.1 bar ±1% psia / bar  19B0432X012 Zinc	40	2.8	2980	79.9	6520	175	11,330	304	15,750	422	18,100	485	19,080	511
	50	3.4	4020	108	8950	240	15,560	417	21,220	569	25,240	676	22,500	603
	60	4.1	4800	129	10,850	291	18,200	483	27,150	728	30,390	814	28,000	750
	80	5.5	6110	164	14,050	377	23,130	620	31,370	841	30,500	817	32,300	866
	100	6.9	7400	198	17,020	456	27,630	740	35,690	956	32,500	871		
14 to 35 psig / 0.97 to 2.4 bar  35 psig / 2.4 bar ±1% psia / bar  19B0432X012 Zinc	40	2.8	2350	63.0	4790	128	8330	223	13,640	366	19,570	524	20,850	559
	50	3.4	3770	101	8300	222	14,430	387	21,350	572	26,060	698	22,000	590
	60	4.1	4700	126	10,510	282	18,270	490	29,060	779	32,530	872	29,000	777
	80	5.5	6120	164	14,000	375	24,350	653	34,490	924	34,500	925	33,600	900
	100	6.9	7400	198	17,020	456	29,600	793	39,920	1070	38,200	1024		
30 to 60 psig / 2.1 to 4.1 bar  40 psig / 2.8 bar ±1% psia / bar  19B0432X022 Green	50	3.4	2400	64.3	6000	161	10,000	268	14,000	375	20,000	536	20,000	536
	60	4.1	3470	93.0	8000	214	13,670	366	22,000	590	26,000	697	22,667	607
	80	5.5	5600	150	12,000	322	21,000	563	38,000	1018	30,000	804	28,000	750
	100	6.9	6400	172	14,500	389	27,000	724	38,000	1018	34,000	911		
	125	8.6	7600	204	19,500	523	33,000	884	38,000	1018				
30 to 60 psig / 2.1 to 4.1 bar  50 psig / 3.4 bar ±1% psia / bar  19B0432X022 Green	60	4.1	3000	80.4	6500	174	9500	255	16,250	436	22,500	603	25,000	670
	80	5.5	5250	141	10,750	288	17,750	476	28,750	771	31,250	838	32,500	871
	100	6.9	6750	181	15,000	402	26,000	697	41,250	1106	40,000	1072		
	125	8.6	8250	221	17,500	469	32,500	871	43,750	1173				
	150	10.3	9500	255	21,750	583	37,750	1012	46,250	1240				
30 to 60 psig / 2.1 to 4.1 bar  60 psig / 4.1 bar ±1% psia / bar  19B0432X022 Green	80	5.5	2750	73.7	7200	193	13,000	348	18,750	503	27,500	737	32,500	871
	100	6.9	2750	73.7	10,600	284	15,500	415	25,000	670	40,000	1072		
	125	8.6	3250	87.1	3000	80.4	22,000	590	46,250	1240				
19B0432X022 Green	150	10.3	3130	83.9	2900	77.7	18,000	482	11,250	302				
	175	12.1	3000	80.4	2800	75.0	14,000	375						

□ - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Downstream piping may affect actual capacity. It may be necessary to use enlarged downstream piping to obtain published capacities.





**Table 9. Types 299H and 299HR Flow Capacities<sup>(1)</sup> for NPS 2 / DN 50 Internal Registration**

OUTLET PRESSURE RANGE, SETTING, ACCURACY, SPRING PART NUMBER AND COLOR	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
			Orifice Size, In. / mm												
			1/4 x 3/8 / 6.4 x 9.5		3/8 / 9.5		1/2 / 13		3/4 / 19		1 / 25		1-3/16 / 30		
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
14 to 35 psig / 0.97 to 2.4 bar	30	2.1	2070	55.5	4230	113	7360	197	14,980	401	22,310	598	23,270	624	
	40	2.8	3320	89.0	7350	197	12,780	343	23,420	628	40,220	1078	33,260	891	
	50	3.4	4140	111	9340	250	16,250	436	34,040	912	42,110	1129	50,000	1340	
	60	4.1	4830	129	11,030	296	19,190	514	40,630	1089	50,050	1341	54,000	1447	
	100	6.9	7400	198	17,020	456	29,600	793	56,050	1502	60,000	1608	60,000	1608	
25 psig / 1.7 bar ±1% psia / bar	80	5.5	6110	164	14,050	377	24,440	655	51,360	1376	62,000	1662	60,000	1608	
1980432X012 Zinc	125	8.6	9020	242	20,730	556	36,050	966	63,640	1706					
	150	10.3	10,630	285	24,440	655	42,500	1139	77,000	2064					
	175	12.1	11,000	295	26,500	710	46,000	1233							
	40	2.8	2980	79.9	6520	175	11,330	304	23,190	621	24,580	659	30,810	826	
	50	3.4	4020	108	8950	240	15,560	417	32,300	866	42,430	1137	50,000	1340	
30 psig / 2.1 bar ±1% psia / bar	60	4.1	4800	129	10,850	291	18,870	506	39,600	1061	52,560	1409	54,000	1447	
	80	5.5	6110	164	14,050	377	24,440	655	51,480	1380	72,000	1930	72,000	1930	
	100	6.9	7400	198	17,020	456	29,600	793	59,840	1604	76,000	2037			
	125	8.6	9020	242	20,730	556	36,050	966	70,570	1891					
	150	10.3	10,630	285	24,440	655	42,500	1139	84,000	2251					
175	12.1	10,200	273	25,000	670	48,000	1286								
14 to 35 psig / 0.97 to 2.4 bar	40	2.8	2350	63.0	4790	128	8330	223	16,920	453	20,350	545	28,360	760	
	50	3.4	3770	101	8300	222	14,430	387	29,690	796	42,740	1145	48,000	1286	
	60	4.1	4700	126	10,510	282	18,270	490	38,050	1020	55,080	1476	60,000	1608	
	80	5.5	6120	164	14,000	375	24,350	653	51,600	1383	70,000	1876	74,000	1983	
	100	6.9	7400	198	17,020	456	29,600	793	63,630	1705	76,000	2037			
35 psig / 2.4 bar ±1% psia / bar	125	8.6	9020	242	20,730	556	36,050	966	77,500	2077					
	150	10.3	10,630	285	24,440	655	42,500	1139	87,000	2332					
	175	12.1	11,200	300	25,500	683	49,000	1313							
	50	3.4	1600	42.9	6500	174	9000	241	20,000	536	28,000	750	34,000	911	
	60	4.1	2800	75.0	8170	219	17,000	456	33,000	884	48,000	1286	52,000	1394	
40 psig / 2.8 bar ±1% psia / bar	80	5.5	5200	139	11,500	308	23,000	616	48,000	1286	66,000	1769	68,000	1822	
	100	6.9	7600	204	13,500	362	29,000	777	31,000	831	76,000	2037			
	125	8.6	8200	220	19,000	509	35,000	938	76,000	2037					
	150	10.3	9800	263	22,750	610	42,000	1126	91,000	2439					
	175	12.1	11,400	306	26,500	710	47,000	1260							
30 to 60 psig / 2.1 to 4.1 bar	60	4.1	3400	91.1	7000	188	10,000	268	21,000	563	32,000	858	45,000	1206	
	80	5.5	5800	155	11,000	295	21,000	563	45,000	1206	69,000	1849	74,000	1983	
	100	6.9	6200	166	15,000	402	26,000	697	59,000	1581	88,000	2358			
	125	8.6	8400	225	19,500	523	35,000	938	77,000	2064					
	150	10.3	9600	257	23,000	616	42,000	1126	89,000	2385					
175	12.1	10,800	289	26,500	710	49,000	1313								
50 psig / 3.4 bar ±1% psia / bar	1980432X022 Green	80	5.5	2800	75.0	3500	93.8	17,000	456	36,000	965	52,000	1394	53,000	1420
	100	6.9	3600	96.5	9500	255	23,000	616	50,000	1340	64,000	1715			
	125	8.6	2800	75.0	15,000	402	22,000	590	69,000	1849	90,000	2412			
	150	10.3	4600	123	11,000	295	18,000	482	89,000	2385					
	175	12.1	6400	172	7000	188	18,000	482							

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

1. Downstream piping may affect actual capacity. It may be necessary to use enlarged downstream piping to obtain published capacities.









**Table 11. Types 299HV and 299HVR Flow Capacities<sup>(1)(2)</sup> for 1-1/2 NPT and NPS 2 / DN 50 Internal Registration (continued)**

OUTLET PRESSURE RANGE SETTING, CONTROL, SPRING PART NUMBER AND COLOR	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
			Orifice Size, In. / mm												
			1/4 x 3/8 / 6.4 x 9.5		3/8 / 9.5		1/2 / 13		3/4 / 19		1 / 25		1-3/16 / 30		
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h		
1 to 3.25 psig / 69 mbar to 0.22 bar  2 psig / 0.14 bar ±1% psia / bar  T13593T0012 Light blue	5	0.34	1020	27.3	2900	77.7	4000	107	5660	152	10,146	272	3	0	
	10	0.69	1550	41.5	3600	96.5	5500	147	7,840	210	16,652	446	18,337	491	
	15	1.0	1920	51.5	4300	115	7500	201	10,210	273	16,884	452	23,809	638	
	20	1.4	2240	60.0	5000	134	8500	228	12,100	324	20,709	555	28,791	772	
	25	1.7	2570	68.9	5550	149	10,000	268	11,880	318	24,308	651	31,522	845	
	30	2.1	2890	77.5	6100	163	11,000	295	12,800	343	27,520	738	24,784	664	
	40	2.8	3530	94.6	7750	208	14,000	375	13,960	374	33,891	908	26,046	698	
	50	3.4	4180	112	9400	252	14,380	385	10,940	293	19,543	524	36,155	969	
	60	4.1	4820	129	10,530	282	15,510	416	9810	263	21,023	563	20,026	537	
	80	5.5	6110	164	8580	230	12,000	322	3700	99	14,926	400			
	100	6.9	6850	184	3290	88	1130	30	2910	78					
	125	8.6	7070	189	3050	82	2220	60	2910	78					
	150	10.3	7300	196	3200	86	2090	56	2910	78					
	175	12.1	4560	122	5540	148	2090	56							
2.75 to 6 psig / 0.19 to 0.41 bar  5 psig / 0.34 bar ±1% psia / bar  T13671T0012 Orange	10	0.69	1390	37.3	2800	75	5000	134	6540	175	13,850	371	11,743	315	
	15	1.0	1870	50.1	3750	101	7000	188	9680	259	20,557	551	21,885	587	
	20	1.4	2240	60.0	4700	126	8500	228	11,480	308	25,547	685	28,040	751	
	25	1.7	2570	68.9	5700	153	9500	255	12,420	333	22,097	592	32,687	876	
	30	2.1	2890	77.5	6430	172	11,000	295	13,050	350	27,576	739	37,211	997	
	40	2.8	3530	94.6	7900	212	13,000	348	15,780	423	33,919	909	29,920	802	
	50	3.4	4180	112	9300	249	16,000	429	15,110	405	35,931	963	30,031	805	
	60	4.1	4790	128	10,700	287	15,200	407	10,710	287	31,207	836	41,617	1115	
	80	5.5	5740	154	13,350	358	13,170	353	8670	232	21,999	590			
	100	6.9	6680	179	16,000	429	2,430	65	8670	232	15,606	418			
	125	8.6	7170	192	4740	127	1700	46	7300	196					
	150	10.3	7650	205	3530	95	1910	51	6470	173					
	175	12.1	4400	118	3530	95	3050	82							
	5 to 16 psig / 0.34 to 1.1 bar  10 psig / 0.69 bar ±1% psia / bar  T13600T0012 Red	15	1.0	1800	48.2	3200	85.8	4000	107	7250	194	11,639	312	14,732	395
20		1.4	2200	59	4300	115	12,000	322	9870	265	22,403	600	23,228	623	
25		1.7	2600	69.7	5400	145	9000	241	12,240	328	26,281	704	27,637	741	
30		2.1	3000	80.4	6600	177	10,000	268	13,490	362	28,080	753	35,678	956	
40		2.8	3650	97.8	7800	209	13,000	348	17,230	462	36,123	968	44,046	1180	
50		3.4	4300	115	9000	241	16,000	429	18,520	496	41,283	1106	49,610	1330	
60		4.1	4950	133	10,460	280	16,050	430	20,460	548	44,057	1181	35,915	963	
80		5.5	6250	168	13,400	359	15,950	427	10,780	289	37,078	994	54,401	1458	
100		6.9	7600	204	16,110	432	15,030	403	11,250	302	30,874	827			
125		8.6	9300	249	19,500	553	16,250	436	11,250	302					
150		10.3	6320	169	4960	133	1970	53	6590	177					
175		12.1	5810	156	3270	88	1970	53							
5 to 16 psig / 0.34 to 1.1 bar  15 psig / 1.0 bar ±1% psia / bar  T13600T0012 Red		20	1.4	1900	50.9	3400	91.1	6000	161	8,860	237	15,265	409	15,327	411
		25	1.7	2450	65.7	4550	122	8000	214	10,900	292	24,397	654	24,228	649
	30	2.1	3000	80.4	5700	153	10,000	268	13,870	372	30,686	822	31,796	852	
	40	2.8	3700	99.2	7600	204	13,000	348	19,100	512	31,184	836	44,116	1182	
	50	3.4	4320	116	8900	239	15,000	402	20,300	544	39,146	1049	53,217	1426	
	60	4.1	4950	133	10,330	277	16,900	453	20,660	554	44,294	1187	58,091	1557	
	80	5.5	6200	166	13,200	354	18,730	502	21,940	588	50,086	1342	46,125	1236	
	100	6.9	7350	197	16,000	429	21,260	570	16,310	437	42,814	1147			
	125	8.6	8800	236	19,500	523	23,920	641	13,970	374					
	150	10.3	10,220	274	22,950	615	25,900	694	10,600	284					
	175	12.1	7300	196	6500	174	5910	158							

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Capacities are limited to 15,000 SCFH / 402 Nm<sup>3</sup>/h when the Type VSX8 is used without a control line.  
 2. Due to slam-shut properties, capacities cannot be calculated with critical flow equation.



**Table 12. Types 299HV and 299HVR Flow Capacities<sup>(1)(2)</sup> for 2 NPT Internal Registration (continued)**


OUTLET PRESSURE RANGE SETTING, CONTROL, SPRING PART NUMBER AND COLOR	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
			Orifice Size, In. / mm												
			1/4 x 3/8 / 6.4 x 9.5		3/8 / 9.5		1/2 / 13		3/4 / 19		1 / 25		1-3/16 / 30		
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h		
1 to 3.25 psig / 69 mbar to 0.22 bar  2 psig / 0.14 bar ±1% psia / bar  T13593T0012 Light blue	5	0.34	1020	27.3	2900	77.7	4000	107	6000	161					
	10	0.69	1550	41.5	3600	96.5	5500	147	10,500	281					
	15	1.0	1920	51.5	4300	115	7500	201	14,500	389					
	20	1.4	2240	60.0	5000	134	8500	228	18,000	482					
	25	1.7	2670	71.6	5550	149	10,000	268	20,000	536					
	30	2.1	2890	77.5	6100	163	11,000	295	24,000	643					
	40	2.8	3530	94.6	7750	208	14,000	375	28,000	750					
	50	3.4	4180	112	9400	252	16,000	429	23,000	616					
	60	4.1	4820	129	10,730	288	19,000	509	18,000	482					
	80	5.5	6110	164	13,400	359	24,000	643	8000	214					
	100	6.9	6850	184	10,770	289	6500	174	8000	214					
	125	8.6	7070	189	7500	201	7500	201	8000	214					
	150	10.3	7300	196	7500	201	7500	201	9500	255					
	175	12.1	7300	196	7500	201	7500	201							
2.75 to 6 psig / 0.19 to 0.41 bar  5 psig / 0.34 bar ±1% psia / bar  T13671T0012 Orange	10	0.69	1390	37.3	2800	75	5000	134	8000	214					
	15	1.0	1870	50.1	3750	101	7000	188	13,000	348					
	20	1.4	2240	60.0	4700	126	8500	228	17,000	456					
	25	1.7	2570	68.9	5700	153	9500	255	20,000	536					
	30	2.1	2890	77.5	6430	172	11,000	295	23,000	616					
	40	2.8	3530	94.6	7900	212	13,000	348	29,000	777					
	50	3.4	4180	112	9300	249	16,000	429	30,000	804					
	60	4.1	4790	128	10,700	287	18,000	482	20,000	536					
	80	5.5	5740	154	13,350	358	23,000	616	20,000	536					
	100	6.9	6680	179	16,000	429	8000	214	20,000	536					
	125	8.6	7170	192	12,800	343	8000	214	20,000	536					
	150	10.3	7650	205	9600	257	8000	214	20,000	536					
	175	12.1	7650	205	9600	257	8000	214							
	5 to 16 psig / 0.34 to 1.1 bar  10 psig / 0.69 bar ±1% psia / bar  T13600T0012 Red	15	1.0	1800	48.2	3200	85.8	4000	107	8500	228				
20		1.4	2200	59	4300	115	12,000	322	14,000	375	20,857	559	22,041	591	
25		1.7	2600	69.7	5400	145	9000	241	19,000	509	22,081	592	26,422	708	
30		2.1	3000	80.4	6600	177	10,000	268	22,000	590	22,228	596	34,273	919	
40		2.8	3650	97.8	7800	209	13,000	348	28,000	750	29,015	778	40,155	1076	
50		3.4	4300	115	9000	241	16,000	429	34,000	911	30,428	815	45,392	1217	
60		4.1	4950	133	10,460	280	18,000	482	39,000	1045	47,113	1263	46,916	1257	
80		5.5	6250	168	13,400	359	23,000	616	25,000	670	57,406	1538	46,983	1259	
100		6.9	7600	204	16,110	432	29,000	777	25,000	670	60,228	1614			
125		8.6	9300	249	19,500	523	35,000	938	25,000	670					
150		10.3	9,900	265	15,050	403	10,000	268	25,000	670					
175		12.1	10,500	281	10,600	284	10,000	268							
5 to 16 psig / 0.34 to 1.1 bar  15 psig / 1.0 bar ±1% psia / bar  T13600T0012 Red		20	1.4	1900	50.9	3400	91.1	6000	161	10,000	268				
		25	1.7	2450	65.7	4550	122	8000	214	15,000	402	22,951	615	24,816	665
	30	2.1	3000	80.4	5700	153	10,000	268	20,000	536	27,742	743	29,280	785	
	40	2.8	3700	99.2	7600	204	13,000	348	28,000	750	24,420	654	41,172	1103	
	50	3.4	4320	116	8900	239	15,000	402	35,000	938	30,384	814	37,525	1006	
	60	4.1	4950	133	10,330	277	18,000	482	40,000	1072	35,110	941	53,476	1433	
	80	5.5	6200	166	13,200	354	23,000	616	51,000	1367	56,966	1527	53,793	1442	
	100	6.9	7350	197	16,000	429	29,000	777	35,000	938	65,280	1750			
	125	8.6	8800	236	19,500	523	36,000	965	30,000	804					
	150	10.3	10,220	274	22,950	615	40,000	1072	30,000	804					
	175	12.1	11,650	312	26,400	708	40,000	1072							

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Capacities are limited to 15,000 SCFH / 402 Nm<sup>3</sup>/h when the Type VSX8 is used without a control line.  
 2. Due to slam-shut properties, capacities cannot be calculated with critical flow equation.

# 299H Series

## Pressure Reducing Regulator

FISHER™



IN. / mm


A7274

Figure 4. Types 299H and 299HR Dimensions

Table 13. Types 299H and 299HR Dimensions

DIMENSION	END CONNECTION STYLE AND FACE-TO-FACE DIMENSION											
	NPT		CL125 FF <sup>(1)</sup>		CL125 FF		CL150 RF		CL250 RF <sup>(2)</sup>		PN 10 OR 16 <sup>(2)</sup>	
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
A	6.12	155	7.50	199	10.00	254	10.00	254	10.50	267	9.06	230

1. Available in Cast iron only.  
2. Available in Ductile iron only.



ERAA23274\_AB

Figure 5. Types 299HV and 299HVR Dimensions




Figure 6. Body and Vent Positions

Table 14. Types 299HV and 299HVR Dimensions (See Figure 5)

DIMENSION	BODY SIZE AND END CONNECTION									
	1-1/2 NPT		2 NPT		NPS 2 / DN 50, CL125 FF		NPS 2 / DN 50, CL250 RF		NPS 2 / DN 50, PN 10/16 RF	
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
A	6.12	155	6.12	155	10.00	254	10.50	267	9.06	230

# 299H Series

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Type (Select One)

- 299H\*\*\*
- 299HR\*\*\*
- 299HV\*\*\*
- 299HVR\*\*\*

### Body Size, Material and End Connection Style (Select One)

#### 1-1/4 NPT

- Cast iron (For Types 299H and 299HR only)\*\*\*

#### 1-1/2 NPT

- Cast iron (For Types 299H and 299HR only)\*\*\*
- Ductile iron\*\*\*
- Steel (For Types 299H and 299HR only)\*\*\*

#### NPS 2 / DN 50

Cast iron (For Types 299H and 299HR only)

- NPT\*\*\*
- CL125 FF - 7.5 In. / 191 mm\*\*\*
- CL125 FF - 10 In. / 254 mm\*\*\*

Ductile iron

- NPT\*\*\*
- CL125 FF - 10 In. / 254 mm\*\*\*
- CL250 RF\*\*\*

PN 10/16 Flanged\*

Steel (For Types 299H and 299HR only)

- NPT\*\*\*
- CL150 RF\*\*\*

### Orifice Size (Select One)

- 1/4 x 3/8 In. / 6.4 x 9.5 mm\*\*\*
- 3/8 In. / 9.5 mm\*\*\*
- 1/2 In. / 13 mm\*\*\*
- 3/4 In. / 19 mm\*\*\*
- 7/8 In. / 22 mm (For Types 299H and 299HR only)\*\*\*
- 1 In. / 25 mm (For Types 299H and 299HR only)\*\*\*
- 1-3/16 In. / 30 mm (For Types 299H and 299HR only)\*\*\*

### Outlet Pressure Range (Select One)

- 3.5 to 6 In. w.c. / 9 to 15 mbar, Black\*\*\*
- 5 to 9 In. w.c. / 12 to 22 mbar, Yellow\*\*\*
- 7 to 20 In. w.c. / 17 to 50 mbar, Unpainted\*\*\*
- 16 to 40 In. w.c. / 40 to 99 mbar, Purple\*\*\*
- 1 to 3.25 psig / 69 mbar to 0.22 bar, Light Blue\*\*\*
- 2.75 to 6 psig / 0.19 to 0.41 bar, Orange\*\*\*
- 5 to 16 psig / 0.34 to 1.1 bar, Red\*\*\*
- 14 to 35 psig / 0.97 to 2.4 bar (Type 299H only), Zinc\*\*\*
- 30 to 60 psig / 2.1 to 4.1 bar (Type 299H only), Green\*\*\*

### Pressure Registration (Select One)

- Internal\*\*\*
- External\*\*\*
- Dual\*\*\*

### Fixed Restriction (Select One)

- 0.044 In. / 1.1 mm, Red (standard gain)\*\*\*
- 0.071 In. / 1.8 mm, Green (low gain)\*\*\*
- 0.082 In. / 2.1 mm, Blue (lower gain)\*\*\*

### VSX Series Slam-Shut Trip Pressure Setting

(Select one if applicable and specify setpoint/s, see Tables 6a, 6b, 6c and 6d.) \_\_\_\_\_

### Overpressure Protection Only (OPSO)

- Yes, please send one parts kit to match this order.

### Overpressure and Underpressure Protection (OPSO/UPSO)

- Supply overpressure setpoint required  
\_\_\_\_\_
- Supply underpressure setpoint required  
\_\_\_\_\_

### Type P590 Pilot Supply Filter (Optional)

- Type P593-1, Aluminum
- Type 594-1, Brass

### Type 67CF Filtered Pilot Supply Regulator (Optional)

- Yes, please add a Type 67CF regulator to this order.

### Main Valve Parts Kit (Optional)

- Yes, please send one parts kit to match this order.

### Pilot Parts Kit (Optional)

- Yes, please send one parts kit to match this order.

- continued -

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

When adjusting setpoint, the regulator should be flowing at least five percent of the normal operating flow.

# Type 310A

## Pressure Reducing Regulator

FISHER™

### Introduction

The Type 310A pilot-operated high-pressure regulator is used where high capacity and accurate control are essential. This regulator includes one Type 32A pilot assembly mounted on the main valve for pressure-reducing or wide-open monitoring applications (see Figure 2) or two Type 32A pilots mounted on the main valve for working monitor applications (see Figure 3).

### Body Sizes and End Connection Styles

See Table 1

### Outlet Pressure Ranges

See Table 5

### Flow and Sizing Coefficients

See Tables 6 through 8

### IEC Sizing Coefficients

See Table 9

### Flow Capacities

See Tables 10 through 14

### Maximum Inlet and Pilot Supply Pressures<sup>(1)</sup>

NPT or CL600 RF: 1500 psig / 103 bar

CL300 RF: 750 psig / 51.7 bar

### Maximum Outlet Pressure<sup>(1)</sup>

**Operating:** 700 psig / 48.3 bar

To Avoid Internal Part Damage: 800 psig / 55.2 bar, exceeding this pressure may result in gas venting from pilot spring case

**Emergency (Casing):** 1500 psig / 103 bar or maximum inlet pressure whichever is lower

### Maximum Pressure Drop<sup>(1)</sup>

NPT or CL600 RF: 1425 psig / 98.3 bar

CL300 RF: 720 psig / 49.6 bar

### Minimum Differential Pressure<sup>(1)</sup>

15 psig / 1.0 bar

### Pressure Registration

External

### Maximum Temperature Capabilities<sup>(1)</sup>

**Nitrile (NBR) With Wiper Ring:**

-20 to 150°F / -29 to 66°C

**Fluorocarbon (FKM) With Wiper Ring:**

0 to 150°F / -18 to 66°C

**Fluorocarbon (FKM) Without Wiper Ring:**

0 to 300°F / -18 to 149°C

### Options

- Main valve body without pilot for on-off service
- Type 252 pilot supply filter
- Travel indicator
- Pressure loaded pilot
- Backpressure protection system
- Restricted Trim (30%, 50% or 70%)
- NACE construction
- Inlet tap
- Turbine Start-up Trim for high turndown applications

### Approximate Shipping Weights

See Table 15




Figure 1. Type 310A Pressure Reducing Regulator with Type 32A Pilot

### Features

- High Capacity
- Tight Shutoff
- Accurate Control
- Minimum Installation Space Required
- Fast Speed of Response
- Reduced Relief Requirements

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/17




Figure 2. Type 310A-32A Operational Schematic






Figure 3. Type 310A-32A-32A Working Monitor Regulator Operational Schematic

Table 1. Body Size and End Connection Style		
BODY SIZE		END CONNECTION STYLE
NPS	DN	
1	25	NPT, CL300 RF or CL600 RF
2, 3, 4 or 4 x 6	50, 80, 100 or 100 x 150	CL300 RF or CL600 RF

Table 2. Maximum Travel			
BODY SIZE		MAXIMUM TRAVEL	
NPS	DN	Inches	mm
1	25	0.5	13
2	50	0.875	22
3	80	1	25
4	100	1.125	28
4 x 6	100 x 150	1.5	38

Table 3. Main Valve Construction Material				
BODY	THROTTLING SLEEVE AND VALVE PLUG	SEAT	MAIN SPRING AND DIAPHRAGM PLATE	O-RING AND DIAPHRAGM
WCC Steel	Stainless steel	Polytetrafluoroethylene (PTFE)	Steel	Nitrile (NBR) (standard) or Fluorocarbon (FKM)

Table 4. Type 32A Pilot Construction Material				
SPRING CASE AND PILOT BODY	DIAPHRAGM	YOKE ORIFICE ASSEMBLY AND BLEED VALVE	PILOT MAIN SPRING	VALVE DISK ASSEMBLY
Cast steel	Nitrile (NBR) (standard) or Fluorocarbon (FKM)	Stainless steel	Plated steel	Stainless steel / Nitrile (NBR) (standard) or Stainless steel / Fluorocarbon (FKM)

# Type 310A

## Pressure Reducing Regulator

FISHER™

**Table 5. Outlet Pressure Range and Proportional Band**

OUTLET PRESSURE RANGE		PILOT SPRING PART NUMBER	SPRING COLOR	PROPORTIONAL BAND		WIRE DIAMETER		FREE LENGTH		RECOMMENDED MINIMUM DIFFERENTIAL BETWEEN MONITORING PILOT SETTING AND DISTRIBUTION PRESSURE
psig	bar			psig	bar	In.	mm	In.	mm	
10 to 100	0.69 to 6.9	1E392527022	Yellow	2	0.14	0.15	3.76	2.00	50.8	5.0 psig / 0.34 bar, over normal distribution pressure
100 to 250 250 to 600 400 to 700 <sup>(1)</sup>	6.9 to 17.2 17.2 to 41.4 27.6 to 48.3 <sup>(1)</sup>	1D387227022 1D465127142 13A5543X012	Blue Red Green	5 12 20	0.34 0.83 1.4	0.20 0.24 0.28	5.08 6.17 7.19	1.69 1.69 2.00	42.9 42.9 50.8	10 psig / 0.69 bar, over normal distribution pressure 15 psig / 1.0 bar, over normal distribution pressure 20 psig / 1.4 bar, over normal distribution pressure

1. Available with Nitrile (NBR) pilot diaphragm only.

**Table 6. Wide-Open Flow Coefficient for Relief Valve Sizing**

TRIM SIZE		BODY SIZE, NPS / DN				
		1 / 25	2 / 50	3 / 80	4 / 100	4 x 6 / 100 x 150
30%	C <sub>g</sub>	238	835	1810	3080	4400
	C <sub>v</sub>	8.6	30.6	64.6	114.9	181.8
	C <sub>i</sub>	27.7	27.3	28	26.8	24.2
50%	C <sub>g</sub>	313	1240	2810	4620	6600
	C <sub>v</sub>	10.3	46.3	99.3	172.4	280.9
	C <sub>i</sub>	30.4	26.8	28.3	26.8	23.5
70%	C <sub>g</sub>	----	1800	3780	6660	9000
	C <sub>v</sub>	----	69	129	213	360
	C <sub>i</sub>	----	26.2	29.3	31.3	25
100%	C <sub>g</sub>	612	2610	5510	8830	16,200
	C <sub>v</sub>	22	95	200	322	661
	C <sub>i</sub>	28.1	27.5	27.5	27.4	24.5

**Table 7. Regulating Flow Coefficient for Body Size Piping**

COEFFICIENT AT PERCENT OF MAXIMUM TRAVEL		TRIM SIZE (PERCENT OF FLOW CAPACITY) BY BODY SIZE, NPS / DN																		
		1 / 25			2 / 50				3 / 80				4 / 100				4 x 6 / 100 x 150			
		100%	50%	30%	100%	70%	50%	30%	100%	70%	50%	30%	100%	70%	50%	30%	100%	70%	50%	30%
10%	C <sub>g</sub>	65	60	56	210	200	190	185	346	340	325	305	805	725	615	510	895	800	780	760
	C <sub>v</sub>	2.2	2.0	2.0	7.6	7.5	6.9	7.0	12.5	11.6	11.3	10.8	29.6	24.0	22.6	19.2	36.5	32.0	33.2	31.4
20%	C <sub>g</sub>	115	93	83	460	396	311	260	810	735	615	460	1800	1310	1040	705	2235	1680	1420	1160
	C <sub>v</sub>	4.0	3.2	3.0	16.6	14.9	11.3	9.8	29.3	25.2	21.4	16.3	66.2	43.4	38.2	26.6	91.2	67.2	60.4	47.9
30%	C <sub>g</sub>	210	124	107	810	583	430	325	1520	1120	85	606	3100	1990	1480	917	3800	2550	2050	1550
	C <sub>v</sub>	7.3	4.2	3.8	29.2	21.9	15.6	12.3	55.1	38.4	3.0	21.4	114.0	65.9	54.4	34.6	155.1	102.0	87.2	64.0
40%	C <sub>g</sub>	343	151	126	1120	758	540	385	2380	1480	1130	755	4350	2650	1900	1130	5510	3300	2650	1940
	C <sub>v</sub>	11.9	5.1	4.5	40.4	28.5	19.6	14.6	86.2	50.7	39.4	26.7	159.9	87.7	69.9	42.6	224.9	132.0	112.8	80.2
50%	C <sub>g</sub>	427	178	140	1440	925	646	444	3270	1840	1380	902	5480	3280	2300	1340	7300	4150	3250	2330
	C <sub>v</sub>	14.8	6.0	5.0	52.0	34.8	23.4	16.8	118.5	63.0	48.1	31.9	201.5	108.6	84.6	50.6	298.0	166.0	138.3	96.3
60%	C <sub>g</sub>	485	204	150	1750	1090	744	502	3890	2190	1630	1060	6310	3950	2730	1540	9010	5010	3840	2720
	C <sub>v</sub>	16.8	6.9	5.4	63.2	41.0	27.0	19.0	140.9	75.0	56.8	37.5	232.0	130.8	110.4	58.1	367.8	200.4	163.4	112.4
70%	C <sub>g</sub>	523	226	159	2040	1240	841	561	4410	2540	1880	1210	7040	4550	3140	1740	10,580	5870	4430	3110
	C <sub>v</sub>	18.2	7.7	5.7	73.6	46.6	30.5	21.3	159.8	87.0	65.5	42.8	258.8	150.7	115.4	65.7	431.8	234.8	188.5	128.5
80%	C <sub>g</sub>	549	250	168	2260	1400	946	624	4820	2900	2130	1360	7640	5110	3540	1950	12,100	6720	5030	3500
	C <sub>v</sub>	19	8	6	82	53	34	24	175	99	74	48	281	169	130	74	493.9	269	214	145
90%	C <sub>g</sub>	573	272	177	2430	1550	1040	690	5080	3210	2380	1510	8140	5700	3950	2200	13,600	7570	5650	3870
	C <sub>v</sub>	20	9	6	88	58	38	26	184	110	83	53	299	189	145	83	555.1	303	240	160
100%	C <sub>g</sub>	597	289	184	2520	1700	1130	761	5330	3530	2640	1670	8670	6390	4390	2680	14,900	8450	6320	4120
	C <sub>v</sub>	21	10	7	91	64	41	29	193	121	92	59	319	212	161	101	608.2	338	269	174
	C <sub>i</sub>	28.8	29.5	28	27.7	26.6	27.6	26.4	27.6	29.2	28.7	28.3	27.2	30.2	27.2	26.5	24.5	25	23.5	24.2



**Table 8. Regulating Flow Coefficient for 2:1 Swaged Piping and 100% Trim**

COEFFICIENT AT PERCENT OF MAXIMUM TRAVEL		TRIM SIZE (PERCENT OF FLOW CAPACITY) BY BODY SIZE, NPS / DN				
		1 / 25	2 / 50	3 / 80	4 / 100	4 x 6 / 100 x 150
10%	C <sub>g</sub>	60	210	340	810	850
	C <sub>v</sub>	2.0	7.1	11.6	28.1	29.8
20%	C <sub>g</sub>	115	450	825	1700	2050
	C <sub>v</sub>	3.8	15.2	28.3	59.0	71.9
30%	C <sub>g</sub>	205	795	1540	3050	3300
	C <sub>v</sub>	6.7	26.8	52.7	105.9	115.8
40%	C <sub>g</sub>	330	1110	2350	4300	4650
	C <sub>v</sub>	10.8	37.4	80.5	149.3	163.2
50%	C <sub>g</sub>	395	1380	3025	5400	6050
	C <sub>v</sub>	13.0	46.5	103.6	187.5	212.3
60%	C <sub>g</sub>	450	1610	3550	6200	7430
	C <sub>v</sub>	14.8	54.2	121.6	215.3	260.7
70%	C <sub>g</sub>	490	1800	3900	3900	8700
	C <sub>v</sub>	16.1	60.6	133.6	135.4	305.3
80%	C <sub>g</sub>	515	1960	4200	7400	9860
	C <sub>v</sub>	17	66	144	257	346
90%	C <sub>g</sub>	533	2055	4440	7800	10,800
	C <sub>v</sub>	17	69	152	271	379
100%	C <sub>g</sub>	548	2140	4610	8150	11,600
	C <sub>v</sub>	18	72	158	283	407
C <sub>i</sub>		30.5	29.7	29.2	28.8	28.5

**Table 9. IEC Sizing Coefficient**

BODY SIZE, NPS / DN	1 / 25	2 / 50	3 / 80	4 / 100	4 X 6 / 100 X 150
X <sub>r</sub>	0.53	0.49	0.48	0.47	0.38
F <sub>b</sub>	0.66	0.59	0.56	0.48	0.58
F <sub>l</sub>	0.74	0.74	0.74	0.74	0.74

**Table 10. NPS 1 / DN 25 Body Size Capacities with 100% Trim and Body Size Piping**

INLET PRESSURE, psig / bar	CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
	Outlet Pressure, psig / bar													
	25 / 1.7	50 / 3.4	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	300 / 20.7	350 / 24.1	400 / 27.6	450 / 31.0	500 / 34.5	550 / 38.0	600 / 41.4	700 / 48.3
50 / 3.5	48 / 1.3													
100 / 6.9	88 / 2.4	87 / 2.3												
200 / 13.8	165 / 4.4	165 / 4.4	163 / 4.4	139 / 3.7										
300 / 20.7	243 / 6.5	243 / 6.5	243 / 6.5	240 / 6.4	223 / 6.0	178 / 4.8								
400 / 27.6	320 / 8.6	320 / 8.6	320 / 8.6	320 / 8.6	317 / 8.5	303 / 8.1	272 / 7.3	211 / 5.7						
500 / 34.5	397 / 10.6	397 / 10.6	397 / 10.6	397 / 10.6	397 / 10.6	393 / 10.5	381 / 10.2	357 / 9.6	314 / 8.4	239 / 6.4				
600 / 41.4	474 / 12.7	474 / 12.7	474 / 12.7	474 / 12.7	474 / 12.7	474 / 12.7	470 / 12.6	459 / 12.3	438 / 11.7	404 / 10.8	351 / 9.4	264 / 7.1		
700 / 48.3	551 / 14.8	551 / 14.8	551 / 14.8	551 / 14.8	551 / 14.8	551 / 14.8	551 / 14.8	547 / 14.7	536 / 14.4	518 / 13.9	490 / 13.1	448 / 12.0	385 / 10.3	
800 / 55.2	628 / 16.8	628 / 16.8	628 / 16.8	628 / 16.8	628 / 16.8	628 / 16.8	628 / 16.8	628 / 16.8	623 / 16.7	614 / 16.5	597 / 16.0	572 / 15.3	537 / 14.4	416 / 11.1
1000 / 69.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	782 / 21.0	781 / 20.9	777 / 20.8	768 / 20.6	754 / 20.2	705 / 18.9
1200 / 82.7	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	936 / 25.1	935 / 25.1	930 / 24.9	908 / 24.3
1400 / 96.5	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1090 / 29.2	1082 / 29.0

Blank areas indicate where no flow occurs because outlet pressure is equal to or greater than inlet pressure.

# Type 310A

## Pressure Reducing Regulator

FISHER™

**Table 11. NPS 2 / DN 50 Body Size Capacities with 100% Trim and Body Size Piping**

INLET PRESSURE, psig / bar	CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
	Outlet Pressure, psig / bar													
	25 / 1.7	50 / 3.4	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	300 / 20.7	350 / 24.1	400 / 27.6	450 / 31.0	500 / 34.5	550 / 38.0	600 / 41.4	700 / 48.3
50 / 3.4	205 / 5.5													
100 / 6.9	373 / 10.0	369 / 9.9												
200 / 13.8	698 / 18.7	698 / 18.7	695 / 18.6	602 / 16.1										
300 / 20.7	1024 / 27.4	1024 / 27.4	1024 / 27.4	1020 / 27.3	959 / 25.7	775 / 20.8								
400 / 27.6	1349 / 36.2	1349 / 36.2	1349 / 36.2	1349 / 36.2	1345 / 36.0	1298 / 34.8	1175 / 31.5	917 / 24.6						
500 / 34.5	1674 / 44.9	1674 / 44.9	1674 / 44.9	1674 / 44.9	1674 / 44.9	1670 / 44.8	1631 / 43.7	1537 / 41.2	1361 / 36.5	1041 / 27.9				
600 / 41.4	2000 / 53.6	2000 / 53.6	2000 / 53.6	2000 / 53.6	2000 / 53.6	2000 / 53.6	1995 / 53.5	1961 / 52.6	1884 / 50.5	1748 / 46.8	1526 / 40.9	1152 / 30.9		
700 / 48.3	2325 / 62.3	2325 / 62.3	2325 / 62.3	2325 / 62.3	2325 / 62.3	2325 / 62.3	2325 / 62.3	2320 / 62.2	2289 / 61.3	2223 / 59.6	2112 / 56.6	1939 / 52	1677 / 44.9	
800 / 55.2	2650 / 71.0	2650 / 71.0	2650 / 71.0	2650 / 71.0	2650 / 71.0	2650 / 71.0	2650 / 71.0	2650 / 71.0	2645 / 70.9	2617 / 70.1	2558 / 68.6	2463 / 66.0	2321 / 62.2	1814 / 48.6
1000 / 69.0	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3301 / 88.5	3295 / 88.3	3270 / 87.6	3222 / 86.4	3038 / 81.4
1200 / 82.7	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3952 / 106	3945 / 106	3878 / 104
1400 / 96.5	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123	4602 / 123

Blank areas indicate where no flow occurs because outlet pressure is equal to or greater than inlet pressure.

**Table 12. NPS 3 / DN 80 Body Sizes Capacities with 100% Trim and Body Size Piping**

INLET PRESSURE, psig / bar	CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
	Outlet Pressure, psig / bar													
	25 / 1.7	50 / 3.4	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	300 / 20.7	350 / 24.1	400 / 27.6	450 / 31.0	500 / 34.5	550 / 38.0	600 / 41.4	700 / 48.3
50 / 3.4	434 / 11.6													
100 / 6.9	739 / 19.8	781 / 20.9												
200 / 13.8	1477 / 39.6	1477 / 39.6	1471 / 39.4	1276 / 34.2										
300 / 20.7	2165 / 58.0	2165 / 58.0	2165 / 58.0	2159 / 57.9	2032 / 54.5	1643 / 44.0								
400 / 27.6	2854 / 76.5	2854 / 76.5	2854 / 76.5	2854 / 76.5	2847 / 76.3	2749 / 73.7	2491 / 66.8	1946 / 52.2						
500 / 34.5	3542 / 94.9	3542 / 94.9	3542 / 94.9	3542 / 94.9	3542 / 94.9	3534 / 94.7	3453 / 92.5	3256 / 87.3	2886 / 77.3	2209 / 59.2				
600 / 41.4	4230 / 113	4230 / 113	4230 / 113	4230 / 113	4230 / 113	4230 / 113	4222 / 113	4151 / 111	3990 / 107	3705 / 99.3	3237 / 86.8	2445 / 65.5		
700 / 48.3	4918 / 132	4918 / 132	4918 / 132	4918 / 132	4918 / 132	4918 / 132	4918 / 132	4909 / 132	4846 / 130	4709 / 126	4475 / 120	4111 / 110	3556 / 95.3	
800 / 55.2	5606 / 150	5606 / 150	5606 / 150	5606 / 150	5606 / 150	5606 / 150	5606 / 150	5606 / 150	5597 / 150	5539 / 148	5418 / 145	5219 / 140	4919 / 132	3847 / 103
1000 / 69.0	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6982 / 187	6972 / 187	6922 / 186	6823 / 183	6437 / 173
1200 / 82.7	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8358 / 224	8347 / 224	8210 / 220
1400 / 96.5	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9735 / 261	9375 / 251

Blank areas indicate where no flow occurs because outlet pressure is equal to or greater than inlet pressure.



**Table 13. NPS 4 / DN 100 Body Size Capacities with 100% Trim and Body Size Piping**

INLET PRESSURE, psig / bar	CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS														
	Outlet Pressure, psig / bar														
	25 / 1.7	50 / 3.4	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	300 / 20.7	350 / 24.1	400 / 27.6	450 / 31.0	500 / 34.5	550 / 38.0	600 / 41.4	700 / 48.3	
50 / 3.4	709 / 19.0														
100 / 6.9	1284 / 34.4	1274 / 34.1													
200 / 13.8	2403 / 64.4	2403 / 64.4	2396 / 64.2	2094 / 56.1											
300 / 20.7	3522 / 94.4	3522 / 94.4	3522 / 94.4	3517 / 94.3	3327 / 89.2	2701 / 72.4									
400 / 27.6	4642 / 124	4642 / 124	4642 / 124	4642 / 124	4636 / 124	4495 / 120	4087 / 110	3202 / 85.8							
500 / 34.5	5761 / 154	5761 / 154	5761 / 154	5761 / 154	5761 / 154	5756 / 154	5641 / 151	5335 / 143	4741 / 127	3638 / 97.5					
600 / 41.4	6880 / 184	6880 / 184	6880 / 184	6880 / 184	6880 / 184	6880 / 184	6875 / 184	6778 / 182	6531 / 175	6078 / 163	5322 / 143	4027 / 108			
700 / 48.3	8000 / 214	8000 / 214	8000 / 214	8000 / 214	8000 / 214	8000 / 214	8000 / 214	7994 / 214	7909 / 212	7701 / 206	7334 / 197	6751 / 181	5850 / 157		
800 / 55.2	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9119 / 244	9113 / 244	9038 / 242	8857 / 237	8546 / 229	8070 / 216	6331 / 170
1000 / 69.0	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,357 / 304	11,352 / 304	11,288 / 303	11,144 / 299	10,545 / 283
1200 / 82.7	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,596 / 364	13,590 / 364	13,403 / 359
1400 / 96.5	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424	15,835 / 424

Blank areas indicate where no flow occurs because outlet pressure is equal to or greater than inlet pressure.

**Table 14. NPS 4 x 6 / DN 100 x 150 Body Size Capacities with 100% Trim and 2:1 Swaged Piping**


INLET PRESSURE, psig / bar	CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																
	Outlet Pressure, psig / bar																
	25 / 1.7	50 / 3.4	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	300 / 20.7	325 / 22.4	350 / 24.1	400 / 27.6	425 / 29.3	450 / 31.0	500 / 34.5	550 / 38.0	600 / 41.4	700 / 48.3	
50 / 3.4	933 / 25.0																
100 / 6.9	1716 / 46.0	1686 / 45.2															
200 / 13.8	3213 / 86.1	3213 / 86.1	3180 / 85.2	2720 / 72.9													
300 / 20.7	4709 / 126	4709 / 126	4709 / 126	4672 / 125	4353 / 117	3488 / 93.5											
400 / 27.6	6206 / 166	6206 / 166	6206 / 166	6206 / 166	6163 / 165	5906 / 158	5312 / 142	4822 / 129	4123 / 110								
500 / 34.5	7702 / 206	7702 / 206	7702 / 206	7702 / 206	7702 / 206	7653 / 205	7430 / 199	7233 / 194	6965 / 187	6139 / 165	5519 / 148	4675 / 125					
600 / 41.4	9198 / 247	9198 / 247	9198 / 247	9198 / 247	9198 / 247	9198 / 247	9144 / 245	9064 / 243	8943 / 240	8552 / 229	8266 / 222	7903 / 212	6874 / 184	5170 / 139			
700 / 48.3	10,695 / 287	10,695 / 287	10,695 / 287	10,695 / 287	10,695 / 287	10,695 / 287	10,695 / 287	10,679 / 286	10,634 / 285	10,449 / 280	10,299 / 276	10,107 / 271	9565 / 256	8753 / 235	7542 / 202		
800 / 55.2	12,191 / 327	12,191 / 327	12,191 / 327	12,191 / 327	12,191 / 327	12,191 / 327	12,191 / 327	12,191 / 327	12,190 / 327	12,125 / 325	12,052 / 323	11,950 / 320	11,643 / 312	11,173 / 299	10,494 / 281	8159 / 219	
1000 / 69.0	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,184 / 407	15,177 / 407	15,105 / 405	14,946 / 401	14,686 / 394	13,783 / 369
1200 / 82.7	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,177 / 487	18,162 / 487	18,086 / 485	17,706 / 475	
1400 / 96.5	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,170 / 567	21,066 / 565	

Blank areas indicate where no flow occurs because outlet pressure is equal to or greater than inlet pressure.

# Type 310A


## Pressure Reducing Regulator

FISHER™



1480914-K

TYPE 310A REGULATOR WITH TYPE 32A PILOT



4484135-B

TYPE 310A REGULATOR WITH TWO TYPE 32A PILOTS FOR WORKING MONITOR SERVICE

Figure 4. Dimensions

Table 15. Dimension and Shipping Weight

BODY SIZE, NPS / DN	DIMENSION, IN. / mm												
	A			B			C	D	E	F	G	L	M
	CL150 RF	CL300 RF	CL600 RF	CL150 RF	CL300 RF	CL600 RF							
1 / 25	----	7.78 / 198	8.28 / 210	----	2.94 / 75	3.19 / 81	9.62 / 244	8.25 / 210	10.56 / 268	2.25 / 57	3.06 / 78	3.56 / 90	4.00 / 102
2 / 50	10.06 / 256	10.53 / 267	11.28 / 287	3.19 / 81	3.44 / 87	3.81 / 97	10.68 / 271	11.25 / 286	11.56 / 294	3.12 / 79	4.44 / 113	4.56 / 116	5.44 / 138
3 / 80	----	12.53 / 318	13.28 / 337	----	3.81 / 97	4.19 / 106	11.50 / 292	13.25 / 337	12.38 / 314	3.12 / 79	5.25 / 133	5.38 / 137	6.25 / 159
4 / 100	----	14.53 / 369	15.53 / 394	----	4.88 / 124	5.38 / 137	13.38 / 340	15.50 / 394	14.25 / 362	3.88 / 99	7.12 / 181	7.25 / 184	8.12 / 206
4 x 6 / 100 x 150	----	16.19 / 411	17.38 / 441	----	4.88 / 124	5.38 / 137	13.38 / 340	15.50 / 394	14.25 / 362	3.88 / 99	7.12 / 181	7.25 / 184	8.00 / 203

## Ordering Guide

### Type (Select One)

- 310A-32A (one pilot for standard pressure reducing and wide-open monitor applications)\*\*\*
- 310A-32A-32A (two pilots for working monitor applications)\*\*\*

### Body Size and Material (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 4 x 6 / DN 100 x 150\*\*\*

### End Connection Style (Select One)

- NPT (available for NPS 1 / DN 25 body only)\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*

### Trim, Percent of Full Capacity (Select One)

- 100 % (standard)\*\*\*
- 70 % (Not Available for NPS 1 / DN 25 body)
- 50 %
- 30 %

- continued -

## Ordering Guide (continued)

**Outlet Pressure Range (Select One)**

10 to 20 psig / 0.69 to 1.4 bar\*\*\*

10 to 100 psig / 0.69 to 6.9 bar\*\*\*

100 to 250 psig / 6.9 to 17.2 bar\*\*\*

250 to 600 psig / 17.2 to 41.4 bar\*\*\*

400 to 700 psig / 27.6 to 48.3 bar, [only available in Nitrile (NBR)]\*\*\*

**Main Valve Diaphragm and O-rings (Select One)**

Nitrile (NBR) (standard)\*\*\*

Fluorocarbon (FKM)\*\*

**Pilot Diaphragm (Select One)**

Stainless Steel/Nitrile (NBR) (standard)\*\*\*

Stainless Steel/Fluorocarbon (FKM)\*\*

**Inlet Body Tap with Prepiped Pilot Supply (Optional)**

Yes\*

**Type 252 Pilot Supply Filter (Optional)**

Material	Length	Drain Valve
<input type="checkbox"/> Stainless steel***	<input type="checkbox"/> Standard***	<input type="checkbox"/> Yes***
<input type="checkbox"/> Aluminum**	<input type="checkbox"/> Extended**	<input type="checkbox"/> No**

1. Product complies with the material requirements of NACE MR0175. Environmental limits may apply.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

**DVGW Approval Required (Optional)**

Yes\*

**NACE MR0175 Construction (Optional)<sup>(1)</sup>**

Yes\*

**Main Valve Replacement Parts Kit (Optional)**

Yes, send one replacement parts kit to match this order.

**Pilot Replacement Parts Kit (Optional)**

Yes, send one replacement parts kit to match this order.

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure (P <sub>1max</sub> ):	
Minimum Inlet Pressure (P <sub>1min</sub> ):	
Downstream Pressure Setting(s) (P <sub>2</sub> ):	
Maximum Flow (Q <sub>max</sub> ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

Do not undersize the monitor set. It is important to realize that the monitor regulator, even though it is wide-open, will require pressure drop for flow. Using two identical regulators in a monitor set will yield approximately 70 percent of the capacity of a single regulator.

# 627 Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The 627 Series direct-operated pressure reducing regulators are for low-pressure and high-pressure systems. The 627 Series can be used as farm tap or small city gate regulators, monitoring regulators or high-pressure industrial gases. See Table 1 for available constructions.

### Body Sizes and End Connection Styles

See Table 3

### Flow Coefficients

See Table 4

### IEC Sizing Coefficients

See Table 5

### Maximum Inlet Pressure

**NPT Stainless steel:**

2000 psig / 138 bar

**Flanged Stainless steel:**

1440 psig / 99.2 bar

**NPT Steel:**

2000 psig / 138 bar

**Flanged Steel:**

1500 psig / 103 bar

**Ductile Iron:**

1000 psig / 69 bar

### Maximum Spring and Diaphragm

**Casing Pressures**

See Table 7

### Outlet Pressure Ranges

5 to 500 psig / 0.34 to 34.5 bar in 6 ranges

See Table 8

### Internal Relief Performance

**Type 627R:**

See Table 9

**Type 627LR:**

See Table 10

**Type 627MR:**

Limited by field-installed control line piping

### Pressure Registrations

See Table 1

### Shipping Weights

See Table 23

### Temperature Capabilities

-40 to 180°F / -40 to 82°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.


[www.Emerson.com](http://www.Emerson.com)



02/19

### Features

- Extended Body Option
- Internal Relief Valve Available
- Relief Operation Indicator
- Easy to Maintain
- Installation Adaptability
- Application Versatility
- Tamper-Resistant
- Wide Range of Flow Capabilities
- Tight Shutoff Capability
- NACE Configuration Available
- DVGW Approved



W4793

Figure 1. Type 627 Direct-Operated Pressure Reducing Regulator




Figure 2. Type 627 Operational Schematic



**Table 1. Available Construction**

TYPE	CONFIGURATION
627	Direct-operated pressure reducing regulator equipped with a pitot tube for greater regulated capacities.
627R	Type 627 with internal relief and open throat.
627LR	Type 627R with light rate relief spring.
627M	Type 627 with a stem seal between the body outlet pressure and diaphragm case. Pressure is measured under the diaphragm through the 1/4 NPT downstream control line connection.
627MR	Type 627M with internal relief.
627H	Type 627 with a diaphragm limiter to deliver a higher outlet pressure.
627HM	Type 627H with a stem seal between the body outlet pressure and diaphragm case. Pressure is measured under the diaphragm through the 1/4 NPT downstream control line connection.

**Table 2. Construction Material**

BODY	SPRING AND DIAPHRAGM CASING	ORIFICE	DIAPHRAGM		DISK HOLDER	DISK
			Types 627H and 627HM	All Other		
Ductile iron, WCC steel or Stainless steel	Ductile iron, Aluminum, WCC steel or Stainless steel	Aluminum (standard) or Stainless steel	Neoprene (CR)	Nitrile (NBR) or Fluorocarbon (FKM)	Aluminum or Stainless steel	Nylon (PA), Nitrile (NBR) or Fluorocarbon (FKM)

**Table 3. Body Size and End Connection Style**

BODY SIZE		END CONNECTION STYLE	CONSTRUCTION AVAILABLE
NPS	DN		
3/4	----	NPT <sup>(1)</sup>	All
1	25	NPT <sup>(1)</sup> , CL150 RF, CL300 RF, CL600 RF and Long Body	
2	50	NPT <sup>(1)</sup> , CL150 RF, CL300 RF, CL600 RF and Long Body	

1. Ductile iron bodies are only available with NPT end connection.

**Table 4. Wide-Open Flow Coefficient for Relief Sizing**

ORIFICE SIZE		3/4 NPT BODY			NPS 1 / DN 25 BODY			NPS 2 / DN 50 BODY		
In.	mm	Wide-Open		C <sub>i</sub>	Wide-Open		C <sub>i</sub>	Wide-Open		C <sub>i</sub>
		C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>	
3/32	2.4	6.9	0.24	29.2	6.9	0.24	28.5	6.9	0.23	29.7
1/8	3.2	12.5	0.43	29.1	12.5	0.43	29.4	12.5	0.42	29.5
3/16	4.8	29	1.01	28.6	29	0.93	31.2	29	1.02	28.5
1/4	6.4	50	1.63	30.6	50	1.71	29.3	52	1.66	31.3
3/8	9.5	108	2.99	36.1	108	3.42	31.6	115	3.39	33.9
1/2	13	190	4.87	39.0	190	5.29	35.9	200	5.01	39.9

**Table 5. IEC Sizing Coefficient**

ORIFICE SIZE		X <sub>r</sub>			F <sub>D</sub>	F <sub>L</sub>
In.	mm	3/4 NPT Body	NPS 1 / DN 25 Body	NPS 2 / DN 50 Body		
3/32	2.4	0.539	0.514	0.558	0.50	0.85
1/8	3.2	0.536	0.547	0.539		0.79
3/16	4.8	0.517	0.616	0.514		0.85
1/4	6.4	0.592	0.543	0.620		0.87
3/8	9.5	0.824	0.632	0.727		0.89
1/2	13	0.962	0.815	1.01		0.86

# 627 Series

## Pressure Reducing Regulator

FISHER™




Figure 3. Spring Case Orientation and Vent Location

Table 6. Maximum Cold Working Pressure of Body Inlet (Body Rating)<sup>(1)(2)</sup>

BODY SIZE		BODY MATERIAL	END CONNECTION	MAXIMUM INLET PRESSURE		
NPS	DN			psig	bar	
3/4	20	Ductile iron	NPT	1000	69.0	
		Steel	NPT	2000	138	
		Stainless steel	NPT	2000	138	
1 and 2	25 and 50	Steel	Ductile iron	NPT	1000	69.0
			NPT	2000	138	
			CL150 RF	290	20.0	
			CL300 RF	750	51.7	
			CL600 RF	1500	103	
			PN 16/25/40	580	40.0	
1 and 2	25 and 50	Stainless steel	CL150 RF	275	19.0	
			CL300 RF	720	49.6	
			CL600 RF	1440	99.3	
			PN 16/25/40	580	40.0	

1. The pressure/temperature limits in this Application Guide, and any applicable standard or code should not be exceeded.  
2. Temperature may decrease these maximum pressures.

Table 7. Maximum Spring and Diaphragm Casing Pressure<sup>(1)</sup>

MAXIMUM PRESSURE DESCRIPTION	DIAPHRAGM CASING MATERIAL	TYPE 627		TYPES 627R AND 627LR		TYPE 627M		TYPE 627MR		TYPES 627H AND 627HM	
		psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
Maximum pressure to spring and diaphragm casings to prevent leak to atmosphere other than relief action (internal parts damage may occur).	Die cast aluminum	250	17.2	250	17.2	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
	Ductile iron	250	17.2	250	17.2	250	17.2	Not Available	Not Available	Not Available	Not Available
	Steel or Stainless steel	250	17.2	250	17.2	250	17.2	250	17.2	800	55.2
Maximum pressure to spring and diaphragm casings to prevent burst of casings during abnormal operation (leak to atmosphere and internal parts damage may occur).	Die cast aluminum	375	25.9	375	25.9	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
	Ductile iron	465	32.1	465	32.1	465	32.1	465	32.1	Not Available	Not Available
	Steel or Stainless steel	1500	103	1500	103	1500	103	1500	103	1500	103
Maximum diaphragm casing overpressure (above setpoint) to prevent damage to internal parts.	All materials	60	4.1	120	8.3	60	4.1	120	8.3	120	8.3

1. If the spring case is pressurized, a metal adjusting screw cap is required. Contact your local Sales Office for details.

**Table 8. Maximum Inlet and Outlet Pressure Range**

TYPE	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	ORIFICE SIZE		MAXIMUM INLET PRESSURE <sup>(1)</sup>					
				Nylon (PA) Disk		Nitrile (NBR) Disk		Fluorocarbon (FKM) Disk	
		In.	mm	psig	bar	psig	bar	psig	bar
627 and 627M <sup>(3)</sup>	5 <sup>(2)</sup> to 20 psig / 0.34 to 1.4 bar  10B3076X012 Yellow	3/32	2.4	2000	138	1000	69.0	300	20.7
		1/8	3.2	1000	69.0	1000	69.0	300	20.7
		3/16	4.8	750	51.7	750	51.7	300	20.7
		1/4	6.4	500	34.5	500	34.5	300	20.7
		3/8	9.5	300	20.7	300	20.7	300	20.7
	1/2	13	250	17.2	250	17.2	250	17.2	
	15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	3/32	2.4	2000	138	1000	69.0	300	20.7
		1/8	3.2	1500	103	1000	69.0	300	20.7
		3/16	4.8	1000	69.0	1000	69.0	300	20.7
		1/4	6.4	750	51.7	750	51.7	300	20.7
		3/8	9.5	500	34.5	500	34.5	300	20.7
	1/2	13	300	20.7	300	20.7	300	20.7	
35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	3/32	2.4	2000	138	1000	69.0	300	20.7	
	1/8	3.2	2000	138	1000	69.0	300	20.7	
	3/16	4.8	1750	121	1000	69.0	300	20.7	
	1/4	6.4	1500	103	1000	69.0	300	20.7	
	3/8	9.5	1000	69.0	1000	69.0	300	20.7	
1/2	13	750	51.7	750	51.7	300	20.7		
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	3/32	2.4	2000	138	1000	69.0	300	20.7	
	1/8	3.2	2000	138	1000	69.0	300	20.7	
	3/16	4.8	2000	138	1000	69.0	300	20.7	
	1/4	6.4	1750	121	1000	69.0	300	20.7	
	3/8	9.5	1250	86.2	1000	69.0	300	20.7	
1/2	13	750	51.7	750	51.7	300	20.7		
627R and 627MR	5 <sup>(2)</sup> to 20 psig / 0.34 to 1.4 bar  10B3076X012 Yellow	3/32	2.4	2000	138	1000	69.0	300	20.7
		1/8	3.2	1000	69.0	1000	69.0	300	20.7
		3/16	4.8	750	51.7	750	51.7	300	20.7
		1/4	6.4	500	34.5	500	34.5	300	20.7
		3/8	9.5	300	20.7	300	20.7	300	20.7
	1/2	13	200	13.8	200	13.8	200	13.8	
	15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	3/32	2.4	2000	138	1000	69.0	300	20.7
		1/8	3.2	1500	103	1000	69.0	300	20.7
		3/16	4.8	1000	69.0	1000	69.0	300	20.7
		1/4	6.4	750	51.7	750	51.7	300	20.7
		3/8	9.5	300	20.7	300	20.7	300	20.7
	1/2	13	200	13.8	200	13.8	200	13.8	
35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	3/32	2.4	2000	138	1000	69.0	300	20.7	
	1/8	3.2	1750	121	1000	69.0	300	20.7	
	3/16	4.8	1000	69.0	1000	69.0	300	20.7	
	1/4	6.4	750	51.7	750	51.7	300	20.7	
	3/8	9.5	300	20.7	300	20.7	300	20.7	
1/2	13	200	13.8	200	13.8	200	13.8		
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	3/32	2.4	2000	138	1000	69.0	300	20.7	
	1/8	3.2	1000	69.0	1000	69.0	300	20.7	
	3/16	4.8	500	34.5	500	34.5	300	20.7	
	1/4	6.4	300	20.7	300	20.7	300	20.7	
	3/8	9.5	200	13.8	200	13.8	200	13.8	
1/2	13	200	13.8	200	13.8	200	13.8		
627LR	15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	3/32	2.4			1000	69.0	300	20.7
		1/8	3.2			1000	69.0	300	20.7
	3/16	4.8			750	51.7	300	20.7	
	1/4	6.4			500	34.5	300	20.7	
627H and 627HM <sup>(3)</sup>	140 to 250 psig / 9.6 to 17.2 bar  10B3078X012 Blue	3/32	2.4	2000	138	1000	69.0		
		1/8	3.2	2000	138	1000	69.0		
		3/16	4.8	1750	121	1000	69.0		
		1/4	6.4	1500	103	1000	69.0		
	240 to 500 psig / 16.5 to 34.5 bar  10B3079X012 Red	3/8	9.5	1000	69.0	750	51.7		
		1/2	13	750	51.7	500	34.5		
		3/32	2.4	2000	138	1000	69.0		
		1/8	3.2	2000	138	1000	69.0		
		3/16	4.8	1750	121	1000	69.0		
		1/4	6.4	1500	103	1000	69.0		
		3/8	9.5	1000	69.0	1000	69.0		
		1/2	13	750	51.7	750	51.7		

1. For inlet pressure in excess of 1000 psig / 69.0 bar, refer to the maximum body and disk pressure ratings in the Specifications section.  
 2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.  
 3. The unbalance forces change from the wide-open monitor mode to an active regulator mode such that the Type 627M or 627HM should have a 3/8 in. / 9.5 mm or larger orifice.  
 - Shaded areas indicate that Fluorocarbon (FKM) / Nylon (PA) disk material is not available.

# 627 Series

## Pressure Reducing Regulator

FISHER™

**Table 9. Type 627R Internal Relief Performance<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		MAXIMUM ALLOWABLE DOWNSTREAM SYSTEM PRESSURE		MAXIMUM INLET PRESSURE TO KEEP MAXIMUM ALLOWABLE DOWNSTREAM SYSTEM PRESSURE FROM BEING EXCEEDED <sup>(2)</sup>											
					Orifice Size, In. / mm											
					3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
					psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
5 <sup>(3)</sup> to 20 psig / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	60	4.1	1250	86.2	740	51.0	320	22.1	190	13.1	95	6.6	75	5.2
			100	6.9	2000	138	1500	103	620	42.7	390	26.9	180	12.4	130	9.0
			125	8.6	2000	138	1900	131	830	57.2	480	33.1	220	15.2	160	11.0
			175	12.1	2000	138	2000	138	1100	75.8	670	46.2	320	22.1	220	15.2
			200	13.8	2000	138	2000	138	1300	89.6	770	53.1	360	24.8	260	17.9
	250	17.2	2000	138	2000	138	1600	110	960	66.2	450	31.0	320	22.1		
	20	1.4	60	4.1	850	58.6	490	33.8	210	14.5	130	9.0	80	5.5	65	4.5
			100	6.9	2000	138	1300	89.6	600	41.4	360	24.8	170	11.7	120	8.3
			125	8.6	2000	138	1800	124	800	55.2	480	33.1	220	15.2	160	11.0
			175	12.1	2000	138	2000	138	1100	75.8	670	46.2	320	22.1	220	15.2
200			13.8	2000	138	2000	138	1300	89.6	770	53.1	360	24.8	260	17.9	
250	17.2	2000	138	2000	138	1600	110	960	66.2	450	31.0	320	22.1			
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	20	1.4	60	4.1	630	43.4	200	13.8	150	10.3	100	6.9	70	4.8	65	4.5
			100	6.9	2000	138	1200	82.7	550	37.9	330	22.8	160	11.0	120	8.3
			125	8.6	2000	138	1700	117	760	52.4	450	31.0	210	14.5	160	11.0
			175	12.1	2000	138	2000	138	1100	75.8	630	43.4	320	22.1	220	15.2
			200	13.8	2000	138	2000	138	1300	89.6	770	53.1	360	24.8	260	17.9
	250	17.2	2000	138	2000	138	1600	110	960	66.2	450	31.7	320	22.1		
	30	2.1	100	6.9	2000	138	950	65.5	450	31.0	260	17.9	140	9.7	110	7.6
			125	8.6	2000	138	1500	103	670	46.2	400	27.6	190	13.1	150	10.3
			175	12.1	2000	138	2000	138	1000	69.0	610	42.1	300	20.7	220	15.2
			200	13.8	2000	138	2000	138	1200	82.7	760	52.4	360	24.8	260	17.9
			250	17.2	2000	138	2000	138	1600	110	970	66.9	460	31.7	320	22.1
	40	2.8	100	6.9	1500	103	700	48.3	330	22.8	200	13.8	120	8.3	108	7.5
			125	8.6	2000	138	1300	89.6	560	38.6	340	23.4	180	12.4	140	9.7
			175	12.1	2000	138	1800	124	1000	69.0	550	37.9	290	20.0	220	15.2
			200	13.8	2000	138	2000	138	1200	82.7	730	50.3	350	24.1	250	17.2
250			17.2	2000	138	2000	138	1600	110	970	66.9	460	31.7	320	22.1	
35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	40	2.8	125	8.6	2000	138	1100	75.8	500	34.5	300	20.7	170	11.7	140	9.7
			150	10.3	2000	138	1600	110	750	51.7	440	30.3	230	15.9	180	12.4
			175	12.1	2000	138	2000	138	980	67.6	580	40.0	290	20.0	220	15.2
			200	13.8	2000	138	2000	138	1200	82.7	720	49.6	340	23.4	250	17.2
			250	17.2	2000	138	2000	138	1600	110	940	64.8	450	31.0	320	22.1
	60	4.1	125	8.6	900	62.1	450	31.0	270	18.6	190	13.1	140	9.7	130	9.0
			150	10.3	1700	117	1100	75.8	540	37.2	300	20.7	190	13.1	160	11.0
			175	12.1	2000	138	1700	117	780	53.8	470	32.4	250	17.2	200	13.8
			200	13.8	2000	138	2000	138	1000	69.0	610	42.1	310	21.4	230	15.9
			250	17.2	2000	138	2000	138	1400	96.5	880	60.7	420	29.0	310	21.4
	80	5.5	150	10.3	800	55.2	500	34.5	300	20.7	200	13.8	160	11.0	150	10.3
			175	12.1	1500	103	1200	82.7	550	37.9	330	22.8	210	14.5	190	13.1
			200	13.8	2000	138	1700	117	800	55.2	480	33.1	270	18.6	220	15.2
			250	17.2	2000	138	2000	138	1200	82.7	770	53.1	390	26.9	300	20.7
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	80	5.5	175	12.1	1400	96.5	250	17.2	240	16.5	200	13.8	190	13.1	175	12.1
			200	13.8	2000	138	960	66.2	520	35.9	330	22.8	240	16.5	210	14.5
			250	17.2	2000	138	2000	138	1000	69.0	620	42.7	350	24.1	280	19.3
	100	6.9	200	13.8	1500	103	250	17.2	240	16.5	230	15.9	210	14.5	210	14.5
			250	17.2	2000	138	1600	110	770	53.1	520	35.9	320	22.1	270	18.6
			150	10.3	250	17.2	1200	82.7	260	17.9	260	17.9	260	17.9	260	17.9

- The internal relief performance values are obtained by removing the disk assembly.
  - For inlet pressures in excess of 1000 psig / 69.0 bar, refer to the maximum body and disk pressure ratings in the Specifications.
  - For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.
- Shaded areas indicate maximum inlet pressures allowed during system malfunction only. Table 8 gives the maximum inlet pressure for normal regulator operation.

**Table 10. Type 627LR Internal Relief Performance<sup>(1)</sup>**

OUTLET PRESSURE RANGE AND CONTROL SPRING INFORMATION	OUTLET PRESSURE SETTING		MAXIMUM ALLOWABLE DOWNSTREAM SYSTEM PRESSURE		MAXIMUM INLET PRESSURE TO KEEP MAXIMUM ALLOWABLE DOWNSTREAM SYSTEM PRESSURE FROM BEING EXCEEDED <sup>(2)</sup>							
					Orifice Diameter, In. / mm							
					3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4	
					psig	bar	psig	bar	psig	bar	psig	bar
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	30	2.1	55	3.8	500	34.5	270	18.6	110	7.6	80	5.5
			60	4.1	850	58.6	480	33.1	200	13.8	120	8.3
			66	4.5	1000	69.0	660	45.5	290	20.0	175	12.1
	40	2.8	66	4.5	380	26.2	190	13.1	85	5.9	80	5.5
			70	4.8	700	48.3	370	25.5	150	10.3	115	7.9
			75	5.2	1000	69.0	560	38.6	240	16.5	160	11.0

- The internal relief performance values are obtained by removing the disk assembly.
- For inlet pressures in excess of 1000 psig / 69.0 bar, refer to the maximum body and disk pressure ratings in the Specifications section.



**Table 11. Types 627, 627M and 627MR Capacities for 3/4 NPT Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
					3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
					psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar	10	0.69	20	1.4	280	7.5	455	12.2	1130	30.3	1790	48.0	3000	80.4	4300	115	
			60	4.1	640	17.2	1170	31.4	2550	68.3	4240	114	6270	168	7370	198	
			100	6.9	990	26.5	1800	48.2	3800	102	5980	160	7440	199	7900	212	
			200	13.8	1850	49.6	3370	90.3	6970	187	7250	194	8200	220	8300	222	
			500	34.5	4010	107	8090	217	8060	216	8100	217					
	10B3076X012 Yellow	20	1.4	750	51.7	4400	118	8930	239	8950	240						
				1000	69.0	4450	119	10,300	276								
				1250	86.2	4540	122										
				1500	103	4880	131										
				1750	121	5230	140										
2000	138	5900	158														
15 to 40 psig / 1.0 to 2.8 bar	40	2.8	30	2.1	350	9.4	620	16.6	1400	37.5	2490	66.7	4360	117	6290	169	
			60	4.1	640	17.2	1170	31.4	2640	70.8	4680	125	8340	224	8940	240	
			100	6.9	990	26.5	1800	48.2	3980	107	7220	193	11,500	308	12,600	338	
			200	13.8	1850	49.6	3370	90.3	7340	197	12,000	322	13,200	354	13,700	367	
			500	34.5	4400	118	8090	217	18,300	490	15,100	405					
	10B3077X012 Green	60	4.1	750	51.7	6600	177	12,000	322	23,000	616	24,200	649				
				1000	69.0	8700	233	16,000	429	24,400	654						
				1250	86.2	11,000	295	18,000	482								
				1500	103	12,000	322	21,000	563								
				1750	121	13,000	348										
2000	138	14,000	375														
35 to 80 psig / 2.4 to 5.5 bar	60	4.1	60	4.1	610	16.3	1090	29.2	2530	67.8	4350	117	8140	218	9420	252	
			100	6.9	990	26.5	1790	48.0	4070	109	7220	193	13,200	354	15,300	410	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,500	362	18,000	482	18,500	496	
			500	34.5	4400	118	8090	217	18,300	490	24,000	643	27,000	724			
			1000	69.0	8700	233	16,000	429	24,400	654							
	10B3078X012 Blue	80	5.5	1250	86.2	11,000	295	18,000	482								
				1500	103	13,000	348	22,000	590	30,400	815	36,000	965				
				1750	121	15,000	402	25,000	670	34,000	911						
				2000	138	17,000	456	28,000	750								
				100	6.9	900	24.1	1600	42.9	3750	101	6490	174	12,200	327	17,300	464
70 to 150 psig / 4.8 to 10.3 bar	100	6.9	200	13.8	1850	49.6	3370	90.3	7630	204	12,000	322	21,300	571	25,700	689	
			500	34.5	4400	118	8090	217	18,300	490	31,800	852	39,000	1045	39,200	1051	
			750	51.8	6600	177	12,000	322	27,200	729	39,000	1045	39,200	1051	45,900	1230	
			1000	69.0	8700	233	16,000	429	36,100	967	40,000	1072	40,500	1085			
			1250	86.2	11,000	295	19,000	509	39,000	1045	40,500	1085	41,000	1099			
	10B3079X012 Red	150	10.3	1500	103	13,000	348	22,000	590	43,000	1152	44,000	1179				
				1750	121	15,000	402	25,000	670	45,000	1206	47,000	1260				
				2000	138	17,000	456	28,000	750	46,000	1233						
				200	13.8	1760	47.2	3200	85.8	7290	195	12,500	335	21,400	574	30,600	820
				500	34.5	4400	118	8090	217	18,300	490	32,500	871	48,900	1311	59,700	1600
750	51.8	6600	177	12,000	322	27,200	729	48,300	1294	59,000	1581	72,000	1930				
1000	69.0	8700	233	16,000	429	36,100	967	64,100	1718	81,100	2173	85,000	2278				
1250	86.2	11,000	295	19,000	509	45,000	1206	68,000	1822	90,000	2412						
1500	103	13,000	348	22,000	590	54,000	1447	72,000	1930								
1750	121	15,000	402	25,000	670	63,000	1688	77,000	2064								
2000	138	17,000	456	28,000	750	71,000	1903										

1. Capacity is based on 20% droop unless otherwise noted below.  
 2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.  
 [Shaded] - Shaded areas indicate where a Type 627MR regulator should not be used because unbalanced forces can cause the internal relief valve to start-to-discharge during normal operation. Refer to Table 9.

# 627 Series

## Pressure Reducing Regulator

FISHER™

**Table 12. Types 627, 627M and 627MR Capacities for NPS 1 / DN 25 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	280	7.5	490	13.1	1150	30.8	2050	54.9	3380	90.6	4410	118	
			60	4.1	640	17.2	1170	31.4	2600	69.7	4710	126	8140	218	13,700	367	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	12,500	335	16,000	429	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	18,000	482	18,500	496	
			500	34.5	4400	118	8090	217	15,700	421	20,000	536					
	750	51.7	5400	145	12,000	322	18,000	482									
	1000	69.0	5800	155	14,000	375											
	1250	86.2	6300	169													
	1500	103	6600	177													
	1750	121	6800	182													
2000	138	7600	204														
10B3077X012 Green	20	1.4	30	2.1	350	9.4	620	16.6	1450	38.9	2580	69.1	4360	117	6290	169	
			60	4.1	640	17.2	1170	31.4	2640	70.8	4750	127	9690	260	14,500	389	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	13,900	373	23,300	624	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	26,600	713	39,100	1048	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882					
	750	51.7	6600	177	12,000	322	23,600	632									
	1000	69.0	8900	239	16,000	429											
	1250	86.2	10,000	268													
	1500	103	10,400	279													
	1750	121	12,000	322													
2000	138	14,000	375														
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	40	2.8	60	4.1	610	16.3	1090	29.2	2530	67.8	4510	121	9290	249	9420	252	
			100	6.9	990	26.5	1790	48.0	4070	109	7310	196	14,700	394	21,900	587	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	27,100	726	46,400	1244	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	63,900	1713			
			750	51.7	6600	177	12,000	322	27,200	729	39,400	1056					
	1000	69.0	8700	233	16,000	429	36,100	967									
	1250	86.2	11,000	295	19,000	509	45,000	1206									
	1500	103	13,000	348	22,000	590	54,000	1447									
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750											
35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	60	4.1	100	6.9	970	26.0	1740	46.6	4010	107	7000	188	13,000	348	19,300	517	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	24,000	643	42,200	1131	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	64,000	1715	94,300	2527	
			750	51.8	6600	177	12,000	322	27,200	729	43,380	1163	66,000	1769	130,000	3484	
			1000	69.0	8700	233	16,000	429	36,100	967	50,300	1348	67,700	1814			
	1250	86.2	11,000	295	19,000	509	45,000	1206	57,000	1528							
	1500	103	13,000	348	22,000	590	54,000	1447	63,000	1688							
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750											
	10B3079X012 Red	80	5.5	100	6.9	900	24.1	1600	42.9	3750	101	6650	178	12,200	327	18,600	498
200				13.8	1850	49.6	3370	90.3	7630	204	13,700	367	28,400	761	44,100	1182	
500				34.5	4400	118	8090	217	18,300	490	32,900	882	71,600	1919	110,000	2948	
750				51.8	6600	177	12,000	322	27,200	729	48,900	1311	105,500	2827	135,000	3618	
1000				69.0	8700	233	16,000	429	36,100	967	64,900	1739	118,000	3162			
1250		86.2	11,000	295	19,000	509	45,000	1206	80,000	2144							
1500		103	13,000	348	22,000	590	54,000	1447	96,000	2573							
1750		121	15,000	402	25,000	670	63,000	1688									
2000		138	17,000	456	28,000	750											
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red		100	6.9	200	13.8	1850	49.6	3370	90.3	7630	204	12,000	322	21,300	571	34,100	914
	500			34.5	4400	118	8090	217	18,300	490	31,800	852	66,500	1782	83,900	2249	
	750			51.8	6600	177	12,000	322	27,200	729	47,300	1268	95,300	2554	117,000	3136	
	1000			69.0	8700	233	16,000	429	36,100	967	59,700	1600	100,000	2680			
	1250			86.2	11,000	295	19,000	509	45,000	1206	72,000	1930	114,000	3055			
	1500	103	13,000	348	22,000	590	54,000	1447	86,000	2305							
	1750	121	15,000	402	25,000	670	63,000	1688	95,000	2546							
	2000	138	17,000	456	28,000	750	71,000	1903									
	150	10.3	200	13.8	1760	47.2	3200	85.8	7290	195	12,900	346	21,400	574	33,600	900	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	70,300	1884	111,000	2975	
750			51.8	6600	177	12,000	322	27,200	729	48,900	1311	104,000	2787	160,000	4288		
1000			69.0	8700	233	16,000	429	36,100	967	64,800	1737	138,000	3698	162,000	4342		
1250			86.2	11,000	295	19,000	509	45,000	1206	80,000	2144	150,000	4020				
1500	103	13,000	348	22,000	590	54,000	1447	96,000	2573								
1750	121	15,000	402	25,000	670	63,000	1688	112,000	3002								
2000	138	17,000	456	28,000	750	71,000	1903										

1. Capacity is based on 20% droop unless otherwise noted below.

2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.

Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

Shaded areas indicate where a Type 627MR regulator should not be used because unbalanced forces can cause the internal relief valve to start-to-discharge during normal operation. Refer to Table 9.



**Table 13. Type 627 Capacities for NPS 2 / DN 50 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	280	7.5	490	13.1	1150	30.8	1880	50.4	2610	69.9	3830	103	
			60	4.1	640	17.2	1170	31.4	2600	69.7	4750	127	7250	194	17,800	477	
			100	6.9	990	26.5	1790	48.0	4070	109	7310	196	16,200	434	28,700	769	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	22,700	608	24,000	643	
			500	34.5	4400	118	8090	217	18,300	490	21,000	563					
	20	1.4	750	51.7	6600	177	12,000	322	27,200	729							
			1000	69.0	8700	233	16,000	429									
			1250	86.2	11,000	295											
			1500	103	13,000	348											
			1750	121	15,000	402											
2000	138	6300	169														
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	40	2.8	60	4.1	610	16.3	1090	29.2	2530	67.8	4370	117	8680	233	13,300	356	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	16,200	434	25,400	681	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	30,400	815	53,900	1445	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	22,000	590			
			750	51.7	6600	177	12,000	322	27,200	729	28,000	750					
	60	4.1	1000	69.0	8700	233	16,000	429	36,100	967							
			1250	86.2	11,000	295	19,000	509									
			1500	103	13,000	348	22,000	590									
			1750	121	15,000	402	25,000	670									
			2000	138	17,000	456	28,000	750									
35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	80	5.5	100	6.9	900	24.1	1630	43.7	3750	101	6400	172	12,800	343	20,400	547	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	30,400	815	53,900	1445	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	48,000	1286	
			750	51.8	6600	177	12,000	322	27,200	729	48,900	1311	53,000	1420	32,000	858	
			1000	69.0	8700	233	16,000	429	36,100	967	43,000	1152	52,000	1394			
	100	6.9	1250	86.2	11,000	295	19,000	509	45,000	1206	70,000	1876					
			1500	103	13,000	348	22,000	590	54,000	1447	43,000	1152					
			1750	121	15,000	402	25,000	670	63,000	1688							
			2000	138	17,000	456	28,000	750									
			1000	69.0	8700	233	16,000	429	36,100	967	64,800	1737	82,000	2198			
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	150	10.3	200	13.8	1760	47.2	3200	85.8	7290	195	13,000	348	24,000	643	38,000	1018	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	129,000	3457	
			750	51.8	6600	177	12,000	322	27,200	729	48,900	1311	108,000	2894	62,000	1662	
			1000	69.0	8700	233	16,000	429	36,100	967	64,800	1737	144,000	3859			
			1250	86.2	11,000	295	19,000	509	45,000	1206	80,000	2144	81,000	2171			
	100	6.9	1500	103	13,000	348	22,000	590	54,000	1447	96,000	2573					
			1750	121	15,000	402	25,000	670	63,000	1688	112,000	3002					
			2000	138	17,000	456	28,000	750	71,000	1903							
			1000	69.0	8700	233	16,000	429	36,100	967	64,800	1737					
			1250	86.2	11,000	295	19,000	509	45,000	1206	80,000	2144					

1. Capacity is based on 20% droop unless otherwise noted below.  
 2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

# 627 Series

## Pressure Reducing Regulator



**Table 14. Types 627M and 627MR Capacities for NPS 2 / DN 50 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	280	7.5	490	13.1	1150	30.8	1880	50.4	2610	69.9	3830	103	
			60	4.1	640	17.2	1170	31.4	2600	69.7	4750	127	7250	194	15,000	402	
			100	6.9	990	26.5	1790	48.0	4070	109	7310	196	14,600	391	23,000	616	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	27,300	732	43,000	1152	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882					
	750	51.7	6600	177	12,000	322	27,200	729									
	1000	69.0	8700	233	16,000	429											
	1250	86.2	11,000	295													
	1500	103	13,000	348													
	1750	121	15,000	402													
2000	138	17,000	456														
10B3076X012 Yellow	20	1.4	30	2.1	350	9.4	620	16.6	1450	38.9	2480	66.5	4300	115	6110	164	
			60	4.1	640	17.2	1170	31.4	2640	70.8	4750	127	8400	225	15,000	402	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	14,600	391	23,000	616	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	27,300	732	43,000	1152	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882					
	750	51.7	6600	177	12,000	322	27,200	729									
	1000	69.0	8700	233	16,000	429											
	1250	86.2	11,000	295													
	1500	103	13,000	348													
	1750	121	15,000	402													
2000	138	17,000	456														
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	40	2.8	60	4.1	610	16.3	1090	29.2	2530	67.8	4370	117	8680	233	13,300	356	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	14,600	391	25,400	681	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	27,300	732	48,000	1286	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	65,000	1742			
			750	51.7	6600	177	12,000	322	27,200	729	48,900	1311					
	1000	69.0	8700	233	16,000	429	36,100	967									
	1250	86.2	11,000	295	19,000	509	54,000	1447									
	1500	103	13,000	348	22,000	590	63,000	1688									
	1750	121	15,000	402	25,000	670											
	2000	138	17,000	456	28,000	750											
10B3077X012 Green	60	4.1	100	6.9	970	26.0	1740	46.6	4010	107	7000	188	15,000	402	20,400	547	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	30,400	815	48,500	1300	
			500	34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	116,000	3109	
			750	51.8	6600	177	12,000	322	27,200	729	48,900	1311	108,000	2894	172,000	4610	
			1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742	144,000	3859			
	1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171							
	1500	103	13,000	348	22,000	590	54,000	1447	97,000	2600							
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750											
	10B3078X012 Blue	80	5.5	100	6.9	900	24.1	1630	43.7	3750	101	6400	172	12,800	343	20,400	547
200				13.8	1850	49.6	3370	90.3	7630	204	13,700	367	30,400	815	48,500	1300	
500				34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	116,000	3109	
750				51.8	6600	177	12,000	322	27,200	729	48,900	1311	108,000	2894	172,000	4610	
1000				69.0	8700	233	16,000	429	36,100	967	65,000	1742	144,000	3859			
1250		86.2	11,000	295	19,000	509	45,000	1206	81,000	2171							
1500		103	13,000	348	22,000	590	54,000	1447	97,000	2600							
1750		121	15,000	402	25,000	670	63,000	1688									
2000		138	17,000	456	28,000	750											
10B3078X012 Blue		100	6.9	200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	22,000	590	33,000	884
	500			34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	116,000	3109	
	750			51.8	6600	177	12,000	322	27,200	729	48,900	1311	108,000	2894	172,000	4610	
	1000			69.0	8700	233	16,000	429	36,100	967	64,800	1737	144,000	3859			
	1250			86.2	11,000	295	19,000	509	45,000	1206	80,000	2144	179,000	4797			
	1500	103	13,000	348	22,000	590	54,000	1447	96,000	2573							
	1750	121	15,000	402	25,000	670	63,000	1688	112,000	3002							
	2000	138	17,000	456	28,000	750	71,000	1903									
	10B3079X012 Red	150	10.3	200	13.8	1760	47.2	3200	85.8	7290	195	13,000	348	24,000	643	38,000	1018
				500	34.5	4400	118	8090	217	18,300	490	32,900	882	73,000	1956	116,000	3109
750				51.8	6600	177	12,000	322	27,200	729	48,900	1311	108,000	2894	172,000	4610	
1000				69.0	8700	233	16,000	429	36,100	967	64,800	1737	144,000	3859			
1250				86.2	11,000	295	19,000	509	45,000	1206	80,000	2144	179,000	4797			
1500		103	13,000	348	22,000	590	54,000	1447	96,000	2573							
1750		121	15,000	402	25,000	670	63,000	1688	112,000	3002							
2000		138	17,000	456	28,000	750	71,000	1903									

1. Capacity is based on 20% droop unless otherwise noted below.

2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.

Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

Shaded areas indicate where a Type 627MR regulator should not be used because unbalanced forces can cause the internal relief valve to start-to-discharge during normal operation. Refer to Table 9.





**Table 15. Types 627H and 627HM Capacities for 3/4 NPT Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32   2.4		1/8   3.2		3/16   4.8		1/4   6.4		3/8   9.5		1/2   13		
140 to 250 psig / 9.7 to 17.2 bar  10B3078X012 Blue	150	10.3	200	13.8	1760	47.2 <sup>(2)</sup>	3200	85.8 <sup>(2)</sup>	7290	195	11,500	308	21,600	579	31,000	831	
			250	17.2	2260	60.6 <sup>(2)</sup>	4100	110 <sup>(2)</sup>	9200	247	15,400	413	28,600	766	40,000	1072	
			300	20.7	2700	72.4	4910	132	11,200	300	19,300	517	31,000	831	46,000	1233	
			400	27.6	3600	96.5	6500	174	14,800	397	24,700	662	40,000	1072	50,000	1340	
			500	34.5	4400	118	8090	217	18,300	490	29,700	796	51,000	1367			
			750	51.7	6600	177	12,000	322	27,200	729	43,000	1152					
	1000	69.0	8700	233	16,000	429	36,100	967	57,000	1528							
	1250	86.2	11,000	295	19,000	509	45,000	1206									
	1500	103	13,000	348	22,000	590	54,000	1447									
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750	71,000	1903									
	250	17.2	2160	57.9 <sup>(2)</sup>	3850	103 <sup>(2)</sup>	8400	225	15,000	402	31,000	831	41,000	1099			
	300	20.7	2700	72.4 <sup>(2)</sup>	4910	132 <sup>(2)</sup>	11,200	300	19,500	523	36,000	965	52,000	1394			
	400	27.6	3600	96.5	6500	174	14,800	397	25,500	683	52,000	1394	68,000	1822			
	500	34.5	4400	118	8090	217	18,300	490	31,000	831	61,000	1635					
	750	51.7	6600	177	12,000	322	27,200	729	45,500	1219							
	1000	69.0	8700	233	16,000	429	36,100	967	60,000	1608							
	1250	86.2	11,000	295	19,000	509	45,000	1206									
1500	103	13,000	348	22,000	590	54,000	1447										
1750	121	15,000	402	25,000	670	63,000	1688										
2000	138	17,000	456	28,000	750	71,000	1903										
240 to 500 psig / 16.5 to 34.5 bar  10B3079X012 Red	250	17.2	300	20.7	2500	67.0 <sup>(2)</sup>	4500	121 <sup>(2)</sup>	9900	265	18,500	496	37,000	992	52,000	1394	
			400	27.6	3600	96.5 <sup>(2)</sup>	6400	172 <sup>(2)</sup>	14,300	383	26,000	697	55,000	1474	74,000	1983	
			500	34.5	4400	118	8090	217	18,300	490	33,000	884	64,000	1715	87,000	2332	
			750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	93,000	2492			
			1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742					
			1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171					
	1500	103	13,000	348	22,000	590	54,000	1447									
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750	71,000	1903									
	500	34.5	4300	115 <sup>(2)</sup>	7700	206 <sup>(2)</sup>	16,800	450	33,000	884	62,000	1662	90,000	2412			
	600	41.4	4900	131 <sup>(2)</sup>	8800	236 <sup>(2)</sup>	19,400	520	37,000	992	70,000	1876	104,000	2787			
	750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	88,000	2358	137,000	3672			
	1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742	130,000	3484					
	1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171							
	1500	103	13,000	348	22,000	590	54,000	1447	97,000	2600							
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750	71,000	1903									

1. Capacity is based on 20% droop unless otherwise noted.  
 2. Small orifices and low-pressure drops may cause the setpoint to shift ±15 psig / 1.0 bar.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

# 627 Series

## Pressure Reducing Regulator

FISHER™

Table 16. Types 627H and 627HM Capacities for NPS 1 / DN 25 Body Size<sup>(1)</sup>

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
					Orifice Size, In. / mm											
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
140 to 250 psig / 9.7 to 17.2 bar 10B3078X012 Blue	150	10.3	200	13.8	1760	47.2 <sup>(2)</sup>	3200	85.8 <sup>(2)</sup>	7290	195	11,500	308	21,600	579	31,000	831
			250	17.2	2260	60.6 <sup>(2)</sup>	4100	110 <sup>(2)</sup>	9200	247	15,400	413	28,600	766	40,000	1072
			300	20.7	2700	72.4	4910	132	11,200	300	19,300	517	31,000	831	46,000	1233
			400	27.6	3600	96.5	6500	174	14,800	397	25,000	670	40,000	1072	50,000	1340
			500	34.5	4400	118	8090	217	18,300	490	32,000	858	51,000	1367		
	750	51.7	6600	177	12,000	322	27,200	729	46,000	1233						
	1000	69.0	8700	233	16,000	429	36,100	967	57,000	1528						
	1250	86.2	11,000	295	19,000	509	45,000	1206								
	1500	103	13,000	348	22,000	590	54,000	1447								
	1750	121	15,000	402	25,000	670	63,000	1688								
2000	138	17,000	456	28,000	750	71,000	1903									
240 to 500 psig / 16.5 to 34.5 bar 10B3079X012 Red	250	17.2	300	20.7	2500	67.0 <sup>(2)</sup>	4500	121 <sup>(2)</sup>	9900	265	18,500	496	37,000	992	52,000	1394
			400	27.6	3600	96.5 <sup>(2)</sup>	6400	172 <sup>(2)</sup>	14,300	383	26,000	697	55,000	1474	74,000	1983
			500	34.5	4400	118	8090	217	18,300	490	33,000	884	64,000	1715	87,000	2332
			750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	102,000	2734		
			1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742				
	1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171						
	1500	103	13,000	348	22,000	590	54,000	1447								
	1750	121	15,000	402	25,000	670	63,000	1688								
	2000	138	17,000	456	28,000	750	71,000	1903								
	500	34.5	4300	115 <sup>(2)</sup>	7700	206 <sup>(2)</sup>	16,800	450	33,000	884	62,000	1662	90,000	2412		
750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	88,000	2358	140,000	3752			
1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742	130,000	3484					
1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171							
1500	103	13,000	348	22,000	590	54,000	1447	97,000	2600							
1750	121	15,000	402	25,000	670	63,000	1688									
2000	138	17,000	456	28,000	750	71,000	1903									

1. Capacity is based on 20% droop unless otherwise noted.  
 2. Small orifices and low-pressure drops may cause the setpoint to shift ±15 psig / 1.0 bar.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.



**Table 17. Types 627H and 627HM Capacities for NPS 2 / DN 50 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
140 to 250 psig / 9.7 to 17.2 bar  10B3078X012 Blue	150	10.3	200	13.8	1760	47.2 <sup>(2)</sup>	3200	85.8 <sup>(2)</sup>	7290	195	13,700	367	24,100	646	31,000	831	
			400	27.6	3600	96.5	6500	174	14,800	397	25,000	670	40,000	1072	50,000	1340	
			500	34.5	4400	118	8090	217	18,300	490	32,000	858					
			750	51.7	6600	177	12,000	322	27,200	729	48,000	1286					
			1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742					
			1250	86.2	11,000	295	19,000	509	45,000	1206							
	1500	103	13,000	348	22,000	590	54,000	1447									
	1750	121	15,000	402	25,000	670	63,000	1688									
	2000	138	17,000	456	28,000	750	71,000	1903									
	250	17.2	300	20.7	2500	67.0 <sup>(2)</sup>	4500	121 <sup>(2)</sup>	9900	265	18,500	496	37,000	992	75,000	2010	
			500	34.5	4400	118	8090	217	18,300	490	33,000	884	64,000	1715	95,000	2546	
			750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	102,000	2734			
1000			69.0	8,700	233	16,000	429	36,100	967	65,000	1742						
1250			86.2	11,000	295	19,000	509	45,000	1206	81,000	2171						
1500			103	13,000	348	22,000	590	54,000	1447								
240 to 500 psig / 16.5 to 34.5 bar  10B3079X012 Red	250	17.2	300	20.7	2500	67.0 <sup>(2)</sup>	4500	121 <sup>(2)</sup>	9300	249	14,000	375	25,000	670	37,000	992	
			500	34.5	4400	118	8090	217	18,300	490	26,300	705	42,000	1126	62,000	1662	
			750	51.7	6600	177	12,000	322	27,200	729	37,100	994	57,000	1528			
			1000	69.0	8700	233	16,000	429	36,100	967	47,400	1270					
			1250	86.2	11,000	295	19,000	509	45,000	1206	57,000	1528					
			1500	103	13,000	348	22,000	590	54,000	1447							
	300	20.7	350	24.2	2900	77.7 <sup>(2)</sup>	5150	138 <sup>(2)</sup>	11,300	303	18,400	493	31,000	831	45,000	1206	
			500	34.5	4400	118	8090	217	18,300	490	32,000	858	53,000	1420	67,000	1796	
			750	51.7	6600	177	12,000	322	27,200	729	48,000	1286	80,000	2144			
			1000	69.0	8700	233	16,000	429	36,100	967	62,000	1662					
			1250	86.2	11,000	295	19,000	509	45,000	1206	79,000	2117					
			1500	103	13,000	348	22,000	590	54,000	1447							
400	27.6	450	31.1	3600	96.5 <sup>(2)</sup>	6400	172 <sup>(2)</sup>	14,000	375	25,000	670	47,000	1260	67,000	1796		
		500	34.5	4400	118 <sup>(2)</sup>	8090	217 <sup>(2)</sup>	18,300	490	32,000	858	54,000	1447	77,000	2064		
		750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	91,000	2439				
		1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742						
		1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171						
		1500	103	13,000	348	22,000	590	54,000	1447								
500	34.5	550	37.9	4300	115 <sup>(2)</sup>	7700	206 <sup>(2)</sup>	16,800	450	33,000	884	62,000	1662	90,000	2412		
		600	41.4	4900	131 <sup>(2)</sup>	8800	236 <sup>(2)</sup>	19,400	520	37,000	992	70,000	1876	104,000	2787		
		750	51.7	6600	177	12,000	322	27,200	729	49,000	1313	88,000	2358	140,000	3752		
		1000	69.0	8700	233	16,000	429	36,100	967	65,000	1742	130,000	3484				
		1250	86.2	11,000	295	19,000	509	45,000	1206	81,000	2171						
		1500	103	13,000	348	22,000	590	54,000	1447	97,000	2600						

1. Capacity is based on 20% droop unless otherwise noted.  
 2. Small orifices and low-pressure drops may cause the setpoint to shift ± 15 psig / 1.0 bar.  
 □ - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

# 627 Series

## Pressure Reducing Regulator

FISHER™

**Table 18. Type 627R Capacities for 3/4 NPT Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	280	7.5	450	12.1	1070	28.7	1740	46.6	2700	72.4	3800	102	
			60	4.1	640	17.2	1170	31.4	2460	65.9	3690	98.9	5270	141	6120	164	
			100	6.9	990	26.5	1690	45.3	3540	94.9	4790	128	6200	166	7600	204	
			200	13.8	1850	49.6	3070	82.3	4200	113	6200	166	6380	171	7680	206	
			500	34.5	4010	107	4240	114	5640	151	6520	175					
			750	51.7	4400	118	5120	137	6400	172							
	1000	69.0	4450	119	6220	167											
	1250	86.2	4540	122													
	1500	103	4880	131													
	1750	121	5230	140													
	2000	138	5900	158													
	10B3076X012 Yellow	20	1.4	30	2.1	350	9.4	590	15.8	1390	37.3	2480	66.5	4350	117	4970	133
60				4.1	640	17.2	1170	31.4	2610	69.9	4680	125	7800	209	8900	239	
100				6.9	990	26.5	1800	48.2	3980	107	6700	180	9750	261	10,400	279	
200				13.8	1850	49.6	3370	90.3	7050	189	9000	241	10,200	273	10,800	289	
500				34.5	4400	118	5200	139	7400	198	9760	262					
750				51.7	6600	177	5360	144	8870	238							
1000		69.0	7300	196	6500	174											
1250		86.2	7500	201													
1500		103	7800	209													
1750		121	8400	225													
2000		138	8600	230													
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green		40	2.8	60	4.1	610	16.3	1090	29.2	2270	60.8	4230	113	8100	217	9100	244
	100			6.9	990	26.5	1790	48.0	4070	109	6840	183	11,900	319	13,400	359	
	200			13.8	1850	49.6	3370	90.3	7630	204	11,000	295	16,300	437	17,100	458	
	500			34.5	4400	118	8090	217	14,500	389	14,800	397					
	750			51.8	6600	177	10,800	289	14,800	397	14,900	399					
	1000			69.0	8700	233	13,100	351	16,300	437							
	1250	86.2	11,000	295	13,800	370											
	1500	103	12,000	322	14,000	375											
	1750	121	13,000	348													
	2000	138	14,000	375													
	35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	60	4.1	75	5.2	700	18.8	1230	33.0	2760	74.0	4700	126	8170	219	12,600	338
				100	6.9	970	26.0	1740	46.6	3910	105	6690	179	11,900	319	14,400	386
200				13.8	1850	49.6	3370	90.3	7630	204	12,400	332	18,400	493	21,200	568	
500				34.5	4400	118	8090	217	18,300	490	20,000	536					
750				51.8	6600	177	12,000	322	18,900	507	21,400	574					
1000				69.0	8700	233	16,000	429	19,000	509							
1250		86.2	11,000	295	18,700	501											
1500		103	13,000	348	19,000	509											
1750		121	15,000	402	20,000	536											
2000		138	17,000	456													
10B3078X012 Blue		80	5.5	100	6.9	900	24.1	1630	43.7	3570	95.7	6490	174	12,000	322	17,200	461
				200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	23,000	616	29,000	777
	500			34.5	4400	118	8090	217	18,300	490	29,000	777					
	750			51.8	6600	177	12,000	322	23,100	619	30,900	828					
	1000			69.0	8700	233	16,000	429	27,400	734							
	1250			86.2	11,000	295	19,000	509									
	1500	103	13,000	348	22,000	590											
	1750	121	15,000	402	25,000	670											
	2000	138	17,000	456													
	70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	100	6.9	150	10.3	1170	31.4	2510	67.3	5540	148	8310	223	15,500	415	20,300	544
				200	13.8	1850	49.6	3370	90.3	7630	204	12,000	322	20,100	539	25,700	689
				500	34.5	4400	118	8090	217	18,300	490						
750				51.8	6600	177	12,000	322									
1000				69.0	8700	233	16,000	429									
1250				86.2	11,000	295											
1500		103	13,000	348													
1750		121	15,000	402													
2000		138	17,000	456													
150		10.3	200	13.8	1760	47.2	3200	85.8	7020	188	12,500	335	21,400	574	30,600	820	
			500	34.5	4400	118	8090	217	18,300	490							
			750	51.8	6600	177	12,000	322									
	1000		69.0	8700	233	16,000	429										
	1250		86.2	11,000	295												
	1500		103	13,000	348												
1750	121	15,000	402														
2000	138	17,000	456														

1. Capacity is based on 20% droop unless otherwise noted below.

2. For pressure setting under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 / 6.9 bar so that setpoint adjustment can be obtained.

Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.



**Table 19. Type 627R Capacities for NPS 1 and 2 / DN 25 and 50 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar 10B3076X012 Yellow	10	0.69	15	1.0	210	5.6	390	10.5	840	22.5	1480	39.7	2300	61.6	2930	78.5	
			20	1.4	280	7.5	500	13.4	1100	29.5	1880	50.4	2700	72.4	3830	103	
			60	4.1	640	17.2	1170	31.4	2460	65.9	3690	98.9	5650	151	6900	185	
			100	6.9	990	26.5	1800	48.2	3540	94.9	4790	128	7520	202	8150	218	
			200	13.8	1850	49.6	3370	90.3	5620	151	6360	170	11,000	295	12,900	346	
			500	34.5	4400	118	6720	180	8570	230	11,600	311					
	20	1.4	750	51.7	5400	145	8850	237	9000	241							
			1000	69.0	5800	155	9500	255									
			1250	86.2	6300	169											
			1500	103	6600	177											
			1750	121	6800	182											
			2000	138	7600	204											
15 to 40 psig / 1.0 to 2.8 bar 10B3077X012 Green	40	2.8	30	2.1	350	9.4	600	16.1	1390	37.3	2580	69.1	4350	117	6290	169	
			60	4.1	640	17.2	1170	31.4	2630	70.5	4750	127	7800	209	10,600	284	
			100	6.9	990	26.5	1800	48.2	4070	109	7310	196	10,800	289	13,400	359	
			200	13.8	1850	49.6	3370	90.3	7050	189	10,500	281	14,000	375	14,400	386	
			500	34.5	4400	118	7830	210	11,800	316	13,300	356					
			750	51.7	6600	177	9000	241	12,000	322							
	60	4.1	1000	69.0	8700	233	9660	259									
			1250	86.2	10,000	268											
			1500	103	10,400	279											
			1750	121	12,000	322											
			2000	138	14,000	375											
			500	34.5	4400	118	8090	217	16,300	437	21,800	584					
35 to 80 psig / 2.4 to 5.5 bar 10B3078X012 Blue	60	4.1	75	5.2	700	18.8	1230	33.0	2760	74.0	4860	130	8600	230	12,800	343	
			100	6.9	970	26.0	1740	46.6	3910	105	7000	188	12,500	335	16,700	448	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	20,900	560	27,700	742	
			500	34.5	4400	118	8090	217	18,300	490	28,500	764					
			750	51.8	6600	177	12,000	322	22,800	611	29,500	791					
			1000	69.0	8700	233	16,000	429	26,800	718							
	80	5.5	1250	86.2	11,000	295	19,000	509									
			1500	103	13,000	348	22,000	590									
			1750	121	15,000	402	25,000	670									
			2000	138	17,000	456											
			100	6.9	900	24.1	1630	43.7	3570	95.7	6650	178	12,000	322	17,400	466	
			200	13.8	1850	49.6	3370	90.3	7630	204	13,700	367	25,100	673	31,800	852	
70 to 150 psig / 4.8 to 10.3 bar 10B3079X012 Red	100	6.9	500	34.5	4400	118	8090	217	18,300	490	30,300	812					
			750	51.8	6600	177	12,000	322	27,200	729	37,400	1002					
			1000	69.0	8700	233	16,000	429	33,300	892							
			1250	86.2	11,000	295											
			1500	103	13,000	348											
			1750	121	15,000	402											
	150	10.3	2000	138	17,000	456											
			200	13.8	1760	47.2	3200	85.8	7020	188	12,900	346	21,400	574	33,300	892	
			500	34.5	4400	118	8090	217	18,300	490							
			750	51.8	6600	177	12,000	322									
			1000	69.0	8700	233	16,000	429									
			1250	86.2	11,000	295											

1. Capacity is based on 20% droop unless otherwise noted below.  
 2. For pressure setting under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 / 6.9 bar so that setpoint adjustment can be obtained.  
 [ ] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

# 627 Series

## Pressure Reducing Regulator

FISHER™




Figure 4. NPT Dimensions




Figure 5. Long Body Dimensions

IN. / mm

Table 20. NPT Dimension

BODY SIZE, NPT	DIMENSION													
	A		B		D				E				G	
					Aluminum / Ductile iron		Steel / Stainless steel		Types 627, 627R, 627LR, 627M and 627MR		Types 627H and 627HM			
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
3/4 and 1	4.06	103	2.03	52	6.50	165	6.75	172	7.62	194	7.94	202	1.00	25
2	5.00	127	2.50	64	6.88	175	7.12	181					1.69	43

Table 21. Long Body Dimension

BODY SIZE		DIMENSION									
		A		B		D				G	
						Aluminum / Ductile iron		Steel / Stainless steel			
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	7.38	187	5.25	133	6.50	165	6.75	172	1.00	25
2	50	7.88	200	5.38	137	6.88	175	7.12	181	1.69	43




Figure 6. Flanged Dimensions

Table 22. Flanged Dimension																	
BODY SIZE		DIMENSION															
		A						B						D			
		CL150 RF		CL300 RF		CL600 RF		CL150 RF		CL300 RF		CL600 RF		Aluminum / Ductile iron		Steel / Stainless steel	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	7.25	184	7.75	197	8.25	210	3.62	92	3.88	99	4.12	105	6.50	165	6.75	171
2	50	10	254	10.5	267	11.25	286	5	127	5.25	133	5.62	143	6.88	175	7.12	181

Table 22. Flanged Dimension (continued)													
BODY SIZE		DIMENSION											
		E						G					
		Types 627, 627R, 627LR and 627MR				Types 627H and 627HM		CL150 RF		CL300 RF		CL600 RF	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	7.62	194	7.94	202	2.12	54	2.44	62	2.44	62		
2	50	7.62	194	7.94	202	3	76	3.25	83	3.25	83		

Table 23. Shipping Weight		
CASING MATERIAL	APPROXIMATE SHIPPING WEIGHT	
	lbs	kg
Ductile iron, Steel or Stainless steel	10	5
Aluminum	6.3	3

# 627 Series

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Type (Select One)

- 627 (basic construction)\*\*\*
- 627H (high-pressure version) (WCC steel / Stainless steel only)\*\*\*
- 627M (external pressure registration)\*\*\*
- 627HM\*\*\*
- 627R (internal relief)\*\*\*
- 627LR\*\*\*
- 627MR\*\*\*

### Body Sizes (Select One)

- 3/4 NPT\*\*\*
- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- 1 NPT Long Body\*\*
- 2 NPT Long Body\*\*

### Body Material and End Connection Style (Select One)

- Ductile Iron (not available for Types 627H and 627HM)**
- NPT\*\*\*
- WCC Steel (required for Types 627H and 627HM)**
- NPT (available end connection for Type 627 long body)\*\*\*
- CL150 RF\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- PN 16/25/40\*\*

### Stainless steel (available only for Types 627, 627R and 627H)

- NPT\*\*\*
- CL150 RF\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- PN 16/25/40\*\*

### Spring Case and Diaphragm Casing Material (Select One)

- Aluminum (Types 627, 627R and 627LR only)\*\*\*
- Ductile iron\*\*\*
- WCC steel\*\*\*
- Stainless steel (Types 627, 627R and 627H only)\*\*\*

### Diaphragm Material (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*\*
- Neoprene (CR) (for Types 627H and 627HM only)\*\*\*

### Trim Material (Select One)

- Aluminum (Types 627, 627R and 627LR only)\*\*\*
- Stainless steel\*\*\*

### Valve Disk Material (Select One)

- Nitrile (NBR)\*\*\*
- Nylon (PA) (not available to Type 627LR)\*\*\*
- Fluorocarbon (FKM) (not available to Types 627H and 627HM)\*\*

### Orifice Sizes (Select One)

- 3/32 in. / 2.4 mm\*\*\*
- 1/8 in. / 3.2 mm\*\*\*
- 3/16 in. / 4.8 mm\*\*\*
- 1/4 in. / 6.4 mm\*\*\*
- 3/8 in. / 9.5 mm (not available to Type 627LR)\*\*\*
- 1/2 in. / 13 mm (not available to Type 627LR)\*\*\*

### Outlet Pressure Ranges (Select One)

#### Types 627, 627M, 627R and 627MR

- 5 to 20 psig / 0.34 to 1.4 bar, Yellow\*\*\*
- 15 to 40 psig / 1.0 to 2.8 bar, Green\*\*\*
- 35 to 80 psig / 2.4 to 5.5 bar, Blue\*\*\*
- 70 to 150 psig / 4.8 to 10.3 bar, Red\*\*\*

#### Type 627LR

- 15 to 40 psig / 1.0 to 2.8 bar, Green\*\*\*

#### Types 627H and 627HM

- 140 to 250 psig / 9.7 to 17.2 bar, Blue\*\*\*
- 240 to 500 psig / 16.5 to 34.5 bar, Red\*\*\*

### Body Position (Select One)

- Position 1 (**standard** for NPT connections)\*\*\*
- Position 2\*\*
- Position 3 (**standard** for flanged bodies)\*\*
- Position 4\*\*

### Vent Position (Select One)

- Position C\*\*
- Position D (**standard**)\*\*\*
- Position E\*\*
- Position F\*\*

### DVGW Approval Required (Optional)

- Yes\*\*\*

### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.



## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Use control lines of equal or greater size than the control tap on the regulator. If a long control line is required, make it bigger. A rule of thumb is to use the next nominal pipe size for every 20 feet / 6.1 m of control line. Small control lines cause a delayed response of the regulator, leading to increased chance of instability. 3/8-inch / 9.5 mm OD tubing is the minimum recommended control line size.

# Type 627F

## Pressure Reducing Regulator

FISHER™

### Introduction

The Type 627F pilot-operated pressure reducing regulator provides superior performance when used in pressure-factor measurement (fixed-factor billing) applications. The Type 627F includes a factory-installed Type 6351F pilot and has external registration that requires a downstream control line.

### Body Sizes and End Connection Styles

See Table 1

### Maximum Inlet Pressures

See Table 2

### Maximum Outlet (Casing) Pressure

250 psig / 17.2 bar

### Outlet Pressure Ranges

5 to 100 psig / 0.34 to 6.9 bar in two ranges

See Table 9

### Temperature Capabilities

-20 to 180°F / -29 to 82°C

### Outlet Pressure Accuracy

±1% of absolute outlet pressure setting (psia or bar absolute) when inlet pressure is held within allowable variations; droop does not exceed 1% of absolute pressure setting for flow rates

### Flow Coefficients

See Table 3

### IEC Sizing Coefficients

See Table 4

### Pressure Registration

External

### Pilot Spring Case Vent Connection

1/4 NPT with removable screened vent assembly

### Approximate Weights

**NPT body with Ductile Iron or Steel Casings:** 10 lbs / 4.5 kg

**NPT body with Aluminum Casings:** 6.3 lbs / 2.9 kg

**Flanged body with Steel Casings:** 18 lbs / 8.2 kg

**Flanged body with Ductile Iron Casings:** 14 lbs / 6.4 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/13

### Features

- Fixed Factor Accuracy
- Wide Range of Flow Capabilities
- Tight Shutoff Capability
- Easy to Maintain
- Installation Adaptability
- Tamper-Resistant





Figure 1. Type 627F Pressure Reducing Regulators



A6558

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE
- LOADING PRESSURE

Figure 2. Type 627F Operational Schematic

**Table 1. Body Size and End Connection Style**

BODY SIZE		BODY MATERIAL	
In.	DN	Ductile Iron	WCC Steel
3/4		NPT	NPT
1 or 2	25 or 50	NPT	NPT, CL150 RF, CL300 RF, CL600 RF or PN 16/25/40 RF

**Table 2. Maximum Allowable Inlet and Differential Pressure**

ORIFICE SIZE		MAXIMUM INLET PRESSURE		MAXIMUM DIFFERENTIAL PRESSURE	
In.	mm	psig	bar	psi	bar
3/8 x 1/8	9.5 x 3.2	250	17.2	250	17.2
3/8 x 1/4	9.5 x 6.4	250	17.2	250	17.2
3/8	9.5	250	17.2	250	17.2
1/2	13	125	8.6	125	8.6

**Table 3. Flow Coefficient**

ORIFICE SIZE		3/4 NPT BODY			NPS 1 / DN 25 BODY			NPS 2 / DN 50 BODY		
		Wide-Open	Wide-Open	C <sub>t</sub>	Wide-Open	Wide-Open	C <sub>t</sub>	Wide-Open	Wide-Open	C <sub>t</sub>
In.	mm	C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>	
3/8 x 1/8	9.5 x 3.2	12.5	0.43	29.1	12.5	0.43	29.4	12.5	0.43	29.2
3/8 x 1/4	9.5 x 6.4	50	1.63	30.6	50	1.71	29.3	52	1.66	31.3
3/8	9.5	108	2.99	36.1	108	3.42	31.6	115	3.39	33.9
1/2	13	190	4.87	39.0	190	5.29	35.9	200	5.01	39.9

**Table 4. IEC Sizing Coefficient**

ORIFICE SIZE		X <sub>r</sub>			F <sub>0</sub>	F <sub>L</sub>
In.	mm	3/4 NPT body	NPS 1 / DN 25 body	NPS 2 / DN 50 body		
1/8	3.2	0.54	0.55	0.54	0.50	0.79
1/4	6.4	0.59	0.54	0.62		0.87
3/8	9.5	0.82	0.63	0.73		0.89
1/2	13	0.96	0.82	1.01		0.86

**Table 5. Additional Specification**

ORIFICE SIZE		ALLOWABLE INLET PRESSURE RANGE FOR MAINTAINING OUTLET PRESSURE WITHIN ±1% OF THE ABSOLUTE OUTLET PRESSURE SETTING <sup>(1)</sup>									
		5 psig / 0.34 bar		30 psig / 2.1 bar		40 psig / 2.8 bar		60 psig / 4.1 bar		100 psig / 6.9 bar	
In.	mm	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
3/8 x 1/8	9.5 x 3.2	30 to 250	2.1 to 17.2	55 to 250	3.8 to 17.2	65 to 250	4.5 to 17.2	85 to 250	5.9 to 17.2	125 to 250	8.6 to 17.2
3/8 x 1/4	9.5 x 6.4	30 to 250	2.1 to 17.2	55 to 250	3.8 to 17.2	65 to 250	4.5 to 17.2	85 to 250	5.9 to 17.2	125 to 250	8.6 to 17.2
3/8	9.5	30 to 250	2.1 to 17.2	55 to 250	3.8 to 17.2	65 to 250	4.5 to 17.2	85 to 250	5.9 to 17.2	125 to 250	8.6 to 17.2
1/2	13	25 to 125	1.7 to 8.6	50 to 125	3.4 to 8.6	60 to 125	4.1 to 8.6	80 to 125	5.5 to 8.6	120 to 125	8.3 to 8.6

1. For best performance, outlet pressure setting should be made using an inlet pressure that is midway between the highest and lowest expected inlet pressure.

**Table 6. Main Regulator Construction Material**

BODY	SPRING CASE AND DIAPHRAGM CASE	O-RING AND DIAPHRAGM	ORIFICE	DISK ASSEMBLY	TENSION SPRING
Ductile iron (standard) or WCC Steel	Die cast aluminum (standard), Ductile iron or Steel	Nitrile (NBR)	Aluminum (standard) or Stainless steel	Aluminum (standard) or Stainless steel with Nitrile (NBR) disk	Plated steel


**Table 7. Type 6351F Pilot Construction Material**

BODY	SPRING CASE	DIAPHRAGM	DIAPHRAGM PLATE, SPRING GUIDE AND ADJUSTING SCREW	INNER VALVE PLUG	VALVE SPRING
Stainless steel	Aluminum	Nylon (PA) fabric coated with Nitrile (NBR)	Zinc-plated steel	Stainless steel/Nitrile (NBR) or Stainless steel/Fluorocarbon (FKM)	Stainless steel

# Type 627F

## Pressure Reducing Regulator

FISHER™



12B2138\_E

12B7144\_C

Figure 3. Dimensions

In. / mm

Table 8. Dimension												
BODY SIZE		END CONNECTION STYLE	DIMENSION									
In.	dn		A		B		D		F		G	
			In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
3/4		NPT	4.06	103	1.94	49	6.75	171	----	----	2.00	51
1		NPT	4.06	103	1.94	49	6.75	171	----	----	2.00	51
1	25	CL150 RF	7.25	184	3.62	92	6.75	171	4.38	111	2.12	54
		CL300 RF	7.75	197	3.88	99					2.44	62
		CL600 RF	8.25	210	4.12	105					2.44	62
		PN 16/25/40	7.80	198	3.90	99					2.31	59
2	50	NPT	5.00	127	2.50	64	7.12	181	----	----	2.62	67
		CL150 RF	10.00	254	5.00	127	7.12	181	4.75	121	3.00	76
		CL300 RF	10.50	267	5.25	133					3.25	83
		CL600 RF	11.25	286	5.62	143					3.25	83
		PN 16/25/40	10.31	262	5.16	131					3.25	83

**Table 9. Capacities Based on 1% Droop in Absolute Outlet Pressure**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING, psig / bar	INLET PRESSURE, psig / bar	CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS (DOWNSTREAM CONTROL LINE IN BODY SIZE PIPING)											
			Orifice Size, In. / mm											
			3/4 NPT Body Size				1 In. / DN 25 Body Size				2 In. / DN 50 Body Size			
			3/8x1/8 / 9.5x3.2	3/8x1/4 / 9.5x6.4	3/8 / 9.5	1/2 / 13	3/8x1/8 / 9.5x3.2	3/8x1/4 / 9.5x6.4	3/8 / 9.5	1/2 / 13	3/8x1/8 / 9.5x3.2	3/8x1/4 / 9.5x6.4	3/8 / 9.5	1/2 / 13
5 to 35 psig / 0.34 to 2.4 bar 1B788327022 Silver	5 / 0.34	30 / 2.1	700 / 18.8	2840 / 76.1	5780 / 155	9730 / 261	700 / 18.8	2840 / 76.1	6040 / 162	10,100 / 271	700 / 18.8	2840 / 76.1	6150 / 165	10,100 / 271
		40 / 2.8	860 / 23.1	3500 / 93.8	7480 / 200	13,100 / 351	860 / 23.1	3500 / 93.8	7480 / 200	13,100 / 351	860 / 23.1	3500 / 93.8	7760 / 208	13,800 / 370
		60 / 4.1	1170 / 31.4	4780 / 128	10,200 / 273	15,500 / 415	1170 / 31.4	4780 / 128	10,200 / 273	17,800 / 477	1170 / 31.4	4780 / 128	10,600 / 284	18,800 / 504
		80 / 5.5	1490 / 39.9	6060 / 162	12,900 / 346	15,500 / 415	1490 / 39.9	6060 / 162	12,900 / 346	18,500 / 496	1490 / 39.9	6060 / 162	13,400 / 359	23,800 / 638
		100 / 6.9	1800 / 48.2	7340 / 197	15,500 / 415	15,500 / 415	1800 / 48.2	7340 / 197	15,700 / 421	18,500 / 496	1800 / 48.2	7340 / 197	16,300 / 437	28,900 / 775
		150 / 10.3	2580 / 69.1	10,500 / 281	15,500 / 415		2580 / 69.1	10,500 / 281	18,500 / 496		2580 / 69.1	10,500 / 281	23,400 / 627	
		200 / 13.8	3370 / 90.3	13,700 / 367	15,500 / 415		3370 / 90.3	13,700 / 367	18,500 / 496		3370 / 90.3	13,700 / 367	30,000 / 804	
		250 / 17.2	4170 / 112	15,500 / 415	15,500 / 415		4170 / 112	16,900 / 453	18,500 / 496		4170 / 112	16,900 / 453	30,000 / 804	
	10 / 0.69	30 / 2.1	690 / 18.5	2760 / 74.0	5480 / 147	8500 / 228	690 / 18.5	2760 / 74.0	5840 / 157	8930 / 239	690 / 18.5	2760 / 74.0	5870 / 157	9500 / 255
		40 / 2.8	860 / 23.1	3500 / 93.8	7480 / 200	13,100 / 351	860 / 23.1	3500 / 93.8	7480 / 200	13,100 / 351	860 / 23.1	3500 / 93.8	7760 / 208	13,800 / 370
		60 / 4.1	1170 / 31.4	4780 / 128	10,200 / 273	17,800 / 477	1170 / 31.4	4780 / 128	10,200 / 273	17,800 / 477	1170 / 31.4	4780 / 128	10,600 / 284	18,800 / 504
		80 / 5.5	1490 / 39.9	6060 / 162	12,900 / 346	19,500 / 523	1490 / 39.9	6060 / 162	12,900 / 346	22,600 / 606	1490 / 39.9	6060 / 162	13,400 / 359	23,800 / 638
		100 / 6.9	1800 / 48.2	7340 / 197	15,700 / 421	19,500 / 523	1800 / 48.2	7340 / 197	15,700 / 421	22,600 / 606	1800 / 48.2	7340 / 197	16,300 / 437	28,900 / 775
		150 / 10.3	2580 / 69.1	10,500 / 281	19,500 / 523		2580 / 69.1	10,500 / 281	22,500 / 603		2580 / 69.1	10,500 / 281	23,400 / 627	
		200 / 13.8	3370 / 90.3	13,700 / 367	19,500 / 523		3370 / 90.3	13,700 / 367	22,600 / 606		3370 / 90.3	13,700 / 367	30,500 / 817	
		250 / 17.2	4170 / 112	16,900 / 453	19,500 / 523		4170 / 112	16,900 / 453	22,600 / 606		4170 / 112	16,900 / 453	37,600 / 1008	
	20 / 1.4	30 / 2.1	590 / 15.8	2310 / 61.9	4360 / 117	6000 / 161	590 / 15.8	2310 / 61.9	4820 / 129	6400 / 172	590 / 15.8	2310 / 61.9	4750 / 127	7000 / 188
		40 / 2.8	820 / 22.0	3250 / 87.1	6320 / 169	10,000 / 268	820 / 22.0	3250 / 87.1	6830 / 183	10,500 / 281	820 / 22.0	3250 / 87.1	6820 / 183	10,900 / 292
		60 / 4.1	1170 / 31.4	4780 / 128	10,200 / 273	17,800 / 477	1170 / 31.4	4780 / 128	10,200 / 273	17,800 / 477	1170 / 31.4	4780 / 128	10,600 / 284	18,800 / 504
		80 / 5.5	1490 / 39.9	6060 / 162	12,900 / 346	22,600 / 606	1490 / 39.9	6060 / 162	12,900 / 346	22,600 / 606	1490 / 39.9	6060 / 162	13,400 / 359	23,800 / 638
		100 / 6.9	1800 / 48.2	7340 / 197	15,700 / 421	24,000 / 643	1800 / 48.2	7340 / 197	15,700 / 421	27,400 / 734	1800 / 48.2	7340 / 197	16,300 / 437	28,900 / 775
		150 / 10.3	2580 / 69.1	10,500 / 281	22,500 / 603		2580 / 69.1	10,500 / 281	22,500 / 603		2580 / 69.1	10,500 / 281	23,400 / 627	
		200 / 13.8	3370 / 90.3	13,700 / 367	28,000 / 750		3370 / 90.3	13,700 / 367	29,400 / 788		3370 / 90.3	13,700 / 367	30,500 / 817	
		250 / 17.2	4170 / 112	16,900 / 453	28,000 / 750		4170 / 112	16,900 / 453	33,300 / 892		4170 / 112	16,900 / 453	37,600 / 1008	
	30 / 2.1	50 / 3.4	930 / 24.9	3680 / 98.6	7090 / 190	11,000 / 295	930 / 24.9	3680 / 98.6	7720 / 207	11,700 / 314	930 / 24.9	3680 / 98.6	7670 / 206	12,100 / 324
		60 / 4.1	1140 / 30.6	4530 / 121	8880 / 238	14,800 / 397	1140 / 30.6	4530 / 121	9540 / 256	15,300 / 410	1140 / 30.6	4530 / 121	9540 / 256	15,300 / 410
		80 / 5.5	1490 / 39.9	6060 / 162	12,900 / 346	22,600 / 606	1490 / 39.9	6060 / 162	12,900 / 346	22,600 / 606	1490 / 39.9	6060 / 162	13,500 / 362	23,800 / 638
		100 / 6.9	1800 / 48.2	7340 / 197	15,700 / 421	27,400 / 734	1800 / 48.2	7340 / 197	15,700 / 421	27,400 / 734	1800 / 48.2	7340 / 197	16,300 / 437	28,900 / 775
150 / 10.3		2580 / 69.1	10,500 / 281	22,500 / 603		2580 / 69.1	10,500 / 281	22,500 / 603		2580 / 69.1	10,500 / 281	23,400 / 627		
200 / 13.8		3370 / 90.3	13,700 / 367	28,000 / 750		3370 / 90.3	13,700 / 367	29,400 / 788		3370 / 90.3	13,700 / 367	30,500 / 817		
250 / 17.2		4170 / 112	16,900 / 453	28,000 / 750		4170 / 112	16,900 / 453	36,200 / 970		4170 / 112	16,900 / 453	37,600 / 1008		

Shaded areas indicate maximum operating inlet pressure is exceeded.

- continued -

# Type 627F

## Pressure Reducing Regulator

FISHER™

**Table 9. Capacities Based on 1% Droop in Absolute Outlet Pressure (continued)**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING, psig / bar	INLET PRESSURE, psig / bar	CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS (DOWNSTREAM CONTROL LINE IN BODY SIZE PIPING)											
			Orifice Size, In. / mm											
			3/4 NPT Body Size				1 In. / DN 25 Body Size				2 In. / DN 50 Body Size			
			3/8 x 1/8 / 9.5 x 3.2	3/8 x 1/4 / 9.5 x 6.4	3/8 / 9.5	1/2 / 13	3/8 x 1/8 / 9.5 x 3.2	3/8 x 1/4 / 9.5 x 6.4	3/8 / 9.5	1/2 / 13	3/8 x 1/8 / 9.5 x 3.2	3/8 x 1/4 / 9.5 x 6.4	3/8 / 9.5	1/2 / 13
35 to 100 psig / 2.4 to 6.9 bar 1K748527202 Red	40 / 2.8	60 / 4.1	1030 / 27.6	4070 / 109	7770 / 208	10,400 / 279	1030 / 27.6	4070 / 109	8530 / 229	11,000 / 295	1030 / 27.6	4070 / 109	8440 / 226	12,000 / 322
		80 / 5.5	1450 / 38.9	5790 / 155	11,400 / 306	19,000 / 509	1450 / 38.9	5790 / 155	12,200 / 327	20,000 / 536	1450 / 38.9	5790 / 155	12,300 / 330	19,700 / 528
		100 / 6.9	1790 / 48.0	7340 / 197	15,700 / 421	27,400 / 734	1790 / 48.0	7340 / 197	15,700 / 421	27,400 / 734	1790 / 48.0	7340 / 197	16,300 / 437	28,900 / 775
		150 / 10.3	2580 / 69.1	10,400 / 279	20,000 / 536		2580 / 69.1	10,400 / 279	22,500 / 603		2580 / 69.1	10,400 / 279	23,400 / 627	
		200 / 13.8	3370 / 90.3	13,500 / 362	20,000 / 536		3370 / 90.3	13,500 / 362	29,400 / 788		3370 / 90.3	13,500 / 362	30,500 / 817	
		250 / 17.2	4170 / 112	16,900 / 453	20,000 / 536		4170 / 112	16,900 / 453	36,200 / 970		4170 / 112	16,900 / 453	37,600 / 1008	
	60 / 4.1	80 / 5.5	1220 / 32.7	4790 / 128	9050 / 243	12,000 / 322	1220 / 32.7	4790 / 128	9860 / 264	12,900 / 346	1220 / 32.7	4790 / 128	9860 / 264	14,000 / 375
		100 / 6.9	1700 / 45.6	6730 / 180	13,100 / 351	21,600 / 579	1700 / 45.6	6730 / 180	14,100 / 378	22,400 / 600	1700 / 45.6	6730 / 180	14,100 / 378	22,400 / 600
		150 / 10.3	2580 / 69.1	10,300 / 276	22,500 / 603		2580 / 69.1	10,300 / 276	22,500 / 603		2580 / 69.1	10,300 / 276	23,400 / 627	
		200 / 13.8	3370 / 90.3	13,500 / 362	29,400 / 788		3370 / 90.3	13,500 / 362	29,400 / 788		3370 / 90.3	13,500 / 362	30,500 / 817	
		250 / 17.2	4170 / 112	16,900 / 453	32,000 / 858		4170 / 112	16,900 / 453	36,200 / 970		4170 / 112	16,900 / 453	37,600 / 1008	
	100 / 6.9	125 / 8.6	1660 / 44.5	6680 / 179	12,500 / 335	18,000 / 482	1660 / 44.5	6680 / 179	13,900 / 373	19,400 / 520	1660 / 44.5	6680 / 179	13,700 / 367	21,200 / 568
		150 / 10.3	2360 / 63.2	9320 / 250	17,900 / 480		2360 / 63.2	9320 / 250	19,400 / 520		2360 / 63.2	9320 / 250	19,400 / 520	
		200 / 13.8	3330 / 89.2	13,400 / 359	26,600 / 713		3330 / 89.2	13,400 / 359	28,300 / 758		3330 / 89.2	13,400 / 359	28,500 / 764	
		250 / 17.2	4170 / 112	16,900 / 453	36,200 / 970		4170 / 112	16,900 / 453	36,200 / 970		4170 / 112	16,900 / 453	37,600 / 1008	

Shaded areas indicate maximum operating inlet pressure is exceeded.

## Ordering Guide

### Body Material, Body Size and End Connection Style (Select One)

#### Ductile Iron

- 3/4 NPT\*\*\*
- 1 NPT\*\*\*
- 2 NPT\*\*\*

#### WCC Steel

- 3/4 NPT\*\*\*
- 1 NPT\*\*\*
- NPS 1 / DN 25, CL150 RF\*\*
- NPS 1 / DN 25, CL300 RF\*\*
- NPS 1 / DN 25, CL600 RF\*\*
- NPS 1 / DN 25, PN 16/25/40\*\*
- 2 NPT\*\*\*
- NPS 2 / DN 50, CL150 RF\*\*
- NPS 2 / DN 50, CL300 RF\*\*
- NPS 2 / DN 50, CL600 RF\*\*
- NPS 2 / DN 50, PN 16/25/40\*\*

### Spring Case and Diaphragm Casing Material (Select One)

- Aluminum\*\*\*
- Ductile iron\*\*\*
- WCC steel\*\*\*

### Trim Material (Select One)

- Aluminum\*\*\*
- Stainless steel\*\*\*

- continued -

## Ordering Guide (continued)

<b>Orifice Size (Select One)</b>
<input type="checkbox"/> 3/8 x 1/8 in. / 9.5 x 3.2 mm**
<input type="checkbox"/> 3/8 x 1/4 in. / 9.5 x 6.4 mm**
<input type="checkbox"/> 3/8 in. / 9.5 mm***
<input type="checkbox"/> 1/2 in. / 13 mm***
<b>Outlet Pressure Range (Select One)</b>
<input type="checkbox"/> 5 to 35 psig / 0.34 to 2.4 bar, Unpainted***
<input type="checkbox"/> 35 to 100 psig / 2.4 to 6.9 bar, Red***
<b>Pilot Supply Filter (Optional)</b>
<input type="checkbox"/> Type P594-1
<b>Pilot Supply Steel Tubing (Optional)</b>
<input type="checkbox"/> With Type P594-1 Filter
<input type="checkbox"/> Without Filter
<b>Replacement Parts Kit (Optional)</b>
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Make control line connections in a straight run of pipe about 10 pipe diameters downstream of any area of turbulence, such as elbows, pipe swages or block valves.

# Type 627OSX

## Pressure Reducing Regulator

FISHER™

### Introduction

Type 627OSX direct-operated pressure reducing regulator is for low-pressure and high-pressure systems. Type 627OSX includes Type OSE slam-shut device for overpressure protection which is available with over and under pressure trip points.

Type 627OSX can be used as farm tap or small city gate regulators, monitoring regulators or high-pressure industrial gases.

### Body Sizes and End Connection Styles

See Table 2

### Temperature Capabilities

-20 to 180°F / -29 to 82°C  
See Table 3

### Flow Coefficients

See Table 4

### IEC Sizing Coefficients

See Table 5

### Maximum Inlet Pressure

1500 psig / 138 bar

### Maximum Body Outlet Pressure

1500 psig / 138 bar

### Outlet Pressure Ranges

5 to 500 psig / 0.34 to 34.5 bar  
See Table 7

### Regulator Capacities

See Tables 8 and 9

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

### Features

- Overpressure and underpressure protection
- High shock and vibration resistance
- Easy in-line maintenance
- Water tight
- Positive shutoff
- Remote alarm capability
- Remote shutoff capability




Figure 1. Type 627OSX Direct-Operated Pressure Reducing Regulator




Figure 2. Type 627OSX Operational Schematic



**Table 1. Construction Material**

BODY	SPRING AND DIAPHRAGM CASING	ORIFICE	DIAPHRAGM	DISK HOLDER	DISK
Ductile iron or WCC steel	Ductile iron, Aluminum or WCC steel	Aluminum ( <b>standard</b> ) or Stainless steel	Neoprene (CR)	Aluminum or Stainless steel	Nylon (PA) or Nitrile (NBR)

**Table 2. Body Size and End Connection Style**

BODY SIZE		END CONNECTION STYLE	CONSTRUCTION AVAILABLE
NPS	DN		
1	25	NPT <sup>(1)</sup> , CL150 RF, CL300 RF, CL600 RF and Long Body	All
2	50	NPT <sup>(1)</sup> , CL150 RF, CL300 RF, CL600 RF and Long Body	

1. Ductile iron bodies are only available with NPT end connection.

**Table 3. Elastomer Temperature Capabilities<sup>(1)(2)</sup>**

MATERIAL	DISK/ DIAPHRAGM	TEMPERATURE	
		°F	°C
Nitrile (NBR)	Disk	-40 to 180	-40 to 82
	Diaphragm		
Nylon (PA)	Disk	-40 to 180	-40 to 82
Neoprene (CR) for Types 627H and 627HM only	Diaphragm	-40 to 180	-40 to 82
Neoprene (CR) for Types 627HOSX and 627HMOSX only	Diaphragm	-20 to 180	-29 to 82
Nitrile (NBR) for Types 627OSX and 627MOSX only	Diaphragm	-20 to 180	-29 to 82

1. The pressure/temperature limits in this Application Guide or any applicable standard limitation should not be exceeded.  
 2. Stainless steel body is rated to -40°F / -40°C. Steel and Ductile iron bodies are rated to -20°F / -29°C.

**Table 4. Wide-Open Flow Coefficient for Relief Sizing**

ORIFICE SIZE		NPS 1 / DN 25 BODY			NPS 2 / DN 50 BODY		
In.	mm	Wide-Open		C <sub>i</sub>	Wide-Open		C <sub>i</sub>
		C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>	
3/32	2.4	6.9	0.24	28.5	6.9	0.23	29.7
1/8	3.2	12.5	0.43	29.4	12.5	0.42	29.5
3/16	4.8	29	0.93	31.2	29	1.02	28.5
1/4	6.4	50	1.71	29.3	52	1.66	31.3
3/8	9.5	108	3.42	31.6	115	3.39	33.9
1/2	13	190	5.29	35.9	200	5.01	39.9


**Table 5. IEC Sizing Coefficient**

ORIFICE SIZE		X <sub>r</sub>		F <sub>D</sub>	F <sub>L</sub>
In.	mm	NPS 1 / DN 25 Body	NPS 2 / DN 50 Body		
3/32	2.4	0.514	0.558	0.50	0.85
1/8	3.2	0.547	0.539		0.79
3/16	4.8	0.616	0.514		0.85
1/4	6.4	0.543	0.620		0.87
3/8	9.5	0.632	0.727		0.89
1/2	13	0.815	1.01		0.86

# Type 627OSX

## Pressure Reducing Regulator

FISHER™



A3726

Figure 3. Spring Case Orientation and Vent Location

Table 6. Maximum Cold Working Pressure of Body Inlet (Body Rating)<sup>(1)(2)</sup>

BODY SIZE		BODY MATERIAL	END CONNECTION	MAXIMUM INLET PRESSURE	
NPS	DN			psig	bar
1 and 2	25 and 50	Ductile iron	NPT	1000	69.0
			NPT	1500	103
		Steel	CL150 RF	290	20.0
			CL300 RF	750	51.7
			CL600 RF	1500	103
1 and 2	25 and 50	Stainless steel	PN 16/25/40	580	40.0
			CL150 RF	275	19.0
			CL300 RF	720	49.6
			CL600 RF	1440	99.3
			PN 16/25/40	580	40.0

1. The pressure/temperature limits in this Application Guide, and any applicable standard or code should not be exceeded.  
2. Temperature may decrease these maximum pressures.

Table 7. Type 627OSX Maximum Inlet and Outlet Pressure Range

TYPE	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	ORIFICE SIZE		MAXIMUM INLET PRESSURE <sup>(1)</sup>			
				Nylon (PA) Disk		Nitrile (NBR) Disk	
		In.	mm	psig	bar	psig	bar
627OSX	5 <sup>(2)</sup> to 20 psig / 0.34 to 1.4 bar 10B3076X012 Yellow	3/32	2.4	1500	103	1000	69.0
		1/8	3.2	1000	69.0	1000	69.0
		3/16	4.8	750	51.7	750	51.7
		1/4	6.4	500	34.5	500	34.5
		3/8	9.5	300	20.7	300	20.7
		1/2	13	250	17.2	250	17.2
	15 to 40 psig / 1.0 to 2.8 bar 10B3077X012 Green	3/32	2.4	1500	103	1000	69.0
		1/8	3.2	1500	103	1000	69.0
		3/16	4.8	1000	69.0	1000	69.0
		1/4	6.4	750	51.7	750	51.7
		3/8	9.5	500	34.5	500	34.5
		1/2	13	300	20.7	300	20.7
	35 to 80 psig / 2.4 to 5.5 bar 10B3078X012 Blue	3/32	2.4	1500	103	1000	69.0
		1/8	3.2	1500	103	1000	69.0
		3/16	4.8	1500	103	1000	69.0
		1/4	6.4	1500	103	1000	69.0
		3/8	9.5	1000	69.0	1000	69.0
		1/2	13	750	51.7	750	51.7
	70 to 150 psig / 4.8 to 10.3 bar 10B3079X012 Red	3/32	2.4	1500	103	1000	69.0
		1/8	3.2	1500	103	1000	69.0
3/16		4.8	1500	103	1000	69.0	
1/4		6.4	1500	121	1000	69.0	
3/8		9.5	1250	86.2	1000	69.0	
1/2		13	750	51.7	750	51.7	

1. For inlet pressure in excess of 1000 psig / 69.0 bar, refer to the maximum body and disk pressure ratings in the Specifications section.  
2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.

**Table 8. Types 627OSX Capacities for NPS 1 / DN 25 Body Size<sup>(1)</sup>**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	252	6.8	441	11.8	1035	27.7	1845	49.4	3042	81.5	3969	106	
			60	4.1	576	15.5	1053	28.3	2340	62.7	4239	113	7326	196	12,330	330	
			100	6.9	891	23.9	1620	43.4	3663	98.1	6579	176	11,250	302	14,400	386	
			200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	16,200	434	16,650	446	
			500	34.5	3960	106	7281	195	14,130	379	18,000	482					
			750	51.7	4860	131	10,800	290	16,200	434							
			1000	69.0	5220	140	12,600	338									
	1250	86.2	5670	152													
	1500	103	5940	159													
	1750	121	6120	164													
	2000	138	6840	184													
	20	1.4	30	2.1	315	8.5	558	14.9	1305	35.0	2322	62.2	3924	105	5661	152	
			60	4.1	576	15.5	1053	28.3	2376	63.7	4275	114	8721	234	13,050	350	
			100	6.9	891	23.9	1620	43.4	3663	98.1	6579	176	12,510	336	20,970	562	
200			13.8	1665	44.6	3033	81.3	6867	184	12,330	330	23,940	642	35,190	943		
500			34.5	3960	106	7281	195	16,470	441	29,610	794						
750			51.7	5940	159	10,800	290	21,240	569								
1000			69.0	8010	215	14,400	386										
1250	86.2	9000	241														
1500	103	9360	251														
1750	121	10,800	290														
2000	138	12,600	338														
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green	40	2.8	60	4.1	549	14.7	981	26.3	2277	61.0	4059	109	8361	224	8478	227	
			100	6.9	891	23.9	1611	43.2	3663	98.1	6579	176	13,230	355	19,710	528	
			200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	24,390	653	41,760	1120	
			500	34.5	3960	106	7281	195	16,470	441	29,610	794	57,510	1542			
			750	51.7	5940	159	10,800	290	24,480	656	35,460	950					
			1000	69.0	7830	210	14,400	386	32,490	870							
			1250	86.2	9900	266	17,100	458									
	1500	103	11,700	313	19,800	531											
	1750	121	13,500	362	22,500	603											
	2000	138	15,300	410	25,200	675											
	35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	60	4.1	100	6.9	873	23.4	1566	41.9	3609	96.3	6300	169	11,700	313	17,370	465
				200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	21,600	579	37,980	1018
				500	34.5	3960	106	7281	195	16,470	441	29,610	794	57,600	1544	84,870	2274
				750	51.8	5940	159	10,800	290	24,480	656	39,042	1047	59,400	1592	117,000	3136
1000				69.0	7830	210	14,400	386	32,490	870	45,270	1213	60,930	1633			
1250				86.2	9900	266	17,100	458	40,500	1085	51,300	1375					
1500				103	11,700	313	19,800	531	48,600	1302	56,700	1519					
1750		121	13,500	362	22,500	603	56,700	1519									
2000		138	15,300	410	25,200	675											
80		5.5	100	6.9	810	21.7	1440	38.6	3375	90.9	5985	160	10,980	294	16,740	448	
			200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	25,560	685	39,690	1064	
			500	34.5	3960	106	7281	195	16,470	441	29,610	794	64,440	1727	99,000	2653	
			750	51.8	5940	159	10,800	290	24,480	656	44,010	1180	94,950	2544	12,1500	3256	
			1000	69.0	7830	210	14,400	386	32,490	870	58,410	1565					
	1250		86.2	9900	266	17,100	458	40,500	1085	72,000	1930						
	1500		103	11,700	313	19,800	531	48,600	1302	86,400	2316						
1750	121	13,500	362	22,500	603	56,700	1519										
2000	138	15,300	410	25,200	675												
70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	100	6.9	200	13.8	1665	44.6	3033	81.3	6867	184	10,800	290	19,170	514	30,690	823	
			500	34.5	3960	106	7281	195	16,470	441	28,620	767	59,850	1604	75,510	2024	
			750	51.8	5940	159	10,800	290	24,480	656	42,570	1141	85,770	2299	105,300	2822	
			1000	69.0	7830	210	14,400	386	32,490	870	53,730	1440	90,000	2412			
			1250	86.2	9900	266	17,100	458	40,500	1085	64,800	1737	102,600	2750			
			1500	103	11,700	313	19,800	531	48,600	1302	77,400	2075					
			1750	121	13,500	362	22,500	603	56,700	1519	85,500	2291					
	2000	138	15,300	410	25,200	675	63,900	1713									
	150	10.3	200	13.8	1584	42.5	2880	77.2	6561	176	11,610	311	19,260	517	30,240	810	
			500	34.5	3960	106	7281	195	16,470	441	29,610	794	63,270	1696	99,900	2678	
			750	51.8	5940	159	10,800	290	24,480	656	44,010	1180	93,600	2508	144,000	3859	
			1000	69.0	7830	210	14,400	386	32,490	870	58,320	1563	124,200	3328	145,800	3908	
			1250	86.2	9900	266	17,100	458	40,500	1085	72,000	1930	135,000	3618			
			1500	103	11,700	313	19,800	531	48,600	1302	86,400	2316					
1750			121	13,500	362	22,500	603	56,700	1519	100,800	2702						
2000	138	15,300	410	25,200	675	63,900	1713										

1. Capacity is based on 20% droop unless otherwise noted below.  
 2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.

# Type 627OSX

## Pressure Reducing Regulator


FISHER™

Table 9. Type 627OSX Capacities for NPS 2 / DN 50 Body Size<sup>(1)</sup>

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS												
					Orifice Size, In. / mm												
	psig	bar	psig	bar	3/32 / 2.4		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
5 to 20 psig <sup>(2)</sup> / 0.34 to 1.4 bar  10B3076X012 Yellow	10	0.69	20	1.4	252	6.8	441	11.8	1035	27.7	1692	45.4	2349	62.9	3447	92.7	
			60	4.1	576	15.5	1053	28.3	2340	62.7	4275	114	6525	175	16,020	429	
			100	6.9	891	23.9	1611	43.2	3663	98.1	6579	176	14,580	391	25,830	692	
			200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	20,430	547	21,600	579	
			500	34.5	3960	106	7281	195	16,470	441	18,900	507					
			750	51.7	5940	159	10,800	290	24,480	656							
	1000	69.0	7830	210	14,400	386											
	1250	86.2	9900	266													
	1500	103	11,700	313													
	1750	121	13,500	362													
	2000	138	15,300	410													
	10B3077X012 Green	20	1.4	30	2.1	315	8.5	558	14.9	1305	35.0	2115	56.7	3870	104	5499	148
60				4.1	576	15.5	1053	28.3	2376	63.7	4275	114	7560	203	14,130	379	
100				6.9	891	23.9	1620	43.4	3663	98.1	6579	176	14,580	391	25,830	692	
200				13.8	1665	44.6	3033	81.3	6867	184	12,330	330	21,600	579	29,700	796	
500				34.5	3960	106	7281	195	16,470	441	29,610	794					
750				51.7	5940	159	10,800	290	24,480	656							
1000		69.0	7830	210	14,400	386											
1250		86.2	9900	266													
1500		103	11,700	313													
1750		121	13,500	362													
2000		138	15,300	410													
15 to 40 psig / 1.0 to 2.8 bar  10B3077X012 Green		40	2.8	60	4.1	549	14.7	981	26.3	2277	61.0	3933	105	7812	210	11,970	320
	100			6.9	891	23.9	1620	43.4	3663	98.1	6579	176	14,580	391	22,860	613	
	200			13.8	1665	44.6	3033	81.3	6867	184	12,330	330	27,360	734	48,510	1301	
	500			34.5	3960	106	7281	195	16,470	441	29,610	794	19,800	531			
	750			51.7	5940	159	10,800	290	24,480	656	25,200	675					
	1000			69.0	7830	210	14,400	386	32,490	870							
	1250	86.2	9900	266	17,100	458											
	1500	103	11,700	313	19,800	531											
	1750	121	13,500	362	22,500	603											
	2000	138	15,300	410	25,200	675											
	35 to 80 psig / 2.4 to 5.5 bar  10B3078X012 Blue	60	4.1	75	5.2	630	16.9	1134	30.4	2484	66.6	4410	118	8100	217	11,070	297
				100	6.9	873	23.4	1566	41.9	3609	96.3	6300	169	13,500	362	18,360	492
200				13.8	1665	44.6	3033	81.3	6867	184	12,330	330	27,360	734	48,510	1301	
500				34.5	3960	106	7281	195	16,470	441	29,610	794	65,700	1760	34,920	936	
750				51.8	5940	159	10,800	290	24,480	656	44,010	1180	47,700	1278	28,800	772	
1000				69.0	7830	210	14,400	386	32,490	870	38,700	1037	46,800	1255			
1250		86.2	9900	266	17,100	458	40,500	1085	63,000	1688							
1500		103	11,700	313	19,800	531	48,600	1302	38,700	1037							
1750		121	13,500	362	22,500	603	56,700	1519									
2000		138	15,300	410	25,200	675											
10B3079X012 Red		80	5.5	100	6.9	810	21.7	1467	39.3	3375	90.9	5760	155	11,520	309	18,360	492
				200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	27,360	734	48,510	1301
	500			34.5	3960	106	7281	195	16,470	441	29,610	794	65,700	1760	43,200	1157	
	750			51.8	5940	159	10,800	290	24,480	656	44,010	1180	78,300	2099	39,600	1061	
	1000			69.0	7830	210	14,400	386	32,490	870	58,500	1568	56,700	1519			
	1250			86.2	9900	266	17,100	458	40,500	1085	56,700	1519					
	1500	103	11,700	313	19,800	531	48,600	1302	77,400	2075							
	1750	121	13,500	362	22,500	603	56,700	1519									
	2000	138	15,300	410	25,200	675											
	70 to 150 psig / 4.8 to 10.3 bar  10B3079X012 Red	100	6.9	200	13.8	1665	44.6	3033	81.3	6867	184	12,330	330	19,800	531	29,700	796
				500	34.5	3960	106	7281	195	16,470	441	29,610	794	65,700	1760	116,100	3111
				750	51.8	5940	159	10,800	290	24,480	656	44,010	1180	97,200	2605	48,600	1302
1000				69.0	7830	210	14,400	386	32,490	870	58,320	1563	73,800	1978			
1250				86.2	9900	266	17,100	458	40,500	1085	72,000	1930	99,000	2653			
1500				103	11,700	313	19,800	531	48,600	1302	86,400	2316					
1750		121	13,500	362	22,500	603	56,700	1519	100,800	2702							
2000		138	15,300	410	25,200	675	63,900	1713									
150		10.3	200	13.8	1584	42.5	2880	77.2	6561	176	11,700	313	21,600	579	34,200	916	
			500	34.5	3960	106	7281	195	16,470	441	29,610	794	65,700	1760	116,100	3111	
			750	51.8	5940	159	10,800	290	24,480	656	44,010	1180	97,200	2605	55,800	1496	
			1000	69.0	7830	210	14,400	386	32,490	870	58,320	1563	129,600	3473			
	1250		86.2	9900	266	17,100	458	40,500	1085	72,000	1930	72,900	1954				
	1500		103	11,700	313	19,800	531	48,600	1302	86,400	2316						
1750	121	13,500	362	22,500	603	56,700	1519	100,800	2702								
2000	138	15,300	410	25,200	675												

1. Capacity is based on 20% droop unless otherwise noted below.  
 2. For pressure settings under 10 psig / 0.69 bar, inlet pressure should be limited to approximately 100 psig / 6.9 bar so the setpoint adjustment can be obtained.  
 [Blank] - Blank areas indicate where maximum operating inlet pressure for a given orifice is exceeded.





IN. /  
mm

Figure 4. Type 6270SX Dimension

# Type 627OSX

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Body Sizes (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- 1 NPT Long Body\*\*
- 2 NPT Long Body\*\*

### Body Material and End Connection Style (Select One)

#### Ductile Iron

- NPT\*\*\*

#### WCC Steel

- NPT (available end connection for Type 627OSX long body)\*\*\*
- CL150 RF\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- PN 16/25/40\*\*

### Spring Case and Diaphragm Casing Material (Select One)

- Aluminum\*\*\*
- Ductile iron\*\*\*
- WCC steel\*\*\*
- Stainless steel\*\*\*

### Diaphragm Material (Select One)

- Nitrile (NBR)\*\*\*
- Neoprene (CR)\*\*\*

### Trim Material (Select One)

- Aluminum\*\*\*
- Stainless steel\*\*\*

### Valve Disk Material (Select One)

- Nitrile (NBR)\*\*\*
- Nylon (PA)\*\*\*

### Orifice Sizes (Select One)

- 3/32 in. / 2.4 mm\*\*\*
- 1/8 in. / 3.2 mm\*\*\*
- 3/16 in. / 4.8 mm\*\*\*
- 1/4 in. / 6.4 mm\*\*\*
- 3/8 in. / 9.5 mm\*\*\*
- 1/2 in. / 13 mm\*\*\*

### Outlet Pressure Ranges (Select One)

#### Type 627OSX

- 5 to 20 psig / 0.34 to 1.4 bar, Yellow\*\*\*
- 15 to 40 psig / 1.0 to 2.8 bar, Green\*\*\*
- 35 to 80 psig / 2.4 to 5.5 bar, Blue\*\*\*
- 70 to 150 psig / 4.8 to 10.3 bar, Red\*\*\*

#### Type 627HOSX

- 140 to 250 psig / 9.7 to 17.2 bar, Blue\*\*\*
- 240 to 500 psig / 16.5 to 34.5 bar, Red\*\*\*

### Body Position (Select One)

- Position 1 (**standard** for NPT connections)\*\*\*
- Position 2\*\*
- Position 3 (**standard** for flanged bodies)\*\*
- Position 4\*\*

### Vent Position (Select One)

- Position C\*\*
- Position D (**standard**)\*\*\*
- Position E\*\*
- Position F\*\*

### DVGW Approval Required (Optional)

- Yes\*\*\*

### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Use control lines of equal or greater size than the control tap on the regulator. If a long control line is required, make it bigger. A rule of thumb is to use the next nominal pipe size for every 20 feet / 6.1 m of control line. Small control lines cause a delayed response of the regulator, leading to increased chance of instability. 3/8-inch / 9.5 mm OD tubing is the minimum recommended control line size.

# Type 630

## Pressure Reducing Regulator

FISHER™

### Introduction

Type 630 Big Joe™ regulators are spring-loaded, direct-operated regulators. Variations of the Type 630 can be used as first-stage farm tap regulators or high-pressure industrial regulators. These regulators are very durable and built to take rugged use.

### Body Sizes and End Connection Styles

See Table 1

### Flow and Sizing Coefficients

See Table 2

### Flow Capacities

See Tables 6 and 7

### Maximum Allowable Inlet Pressure and Pressure Drop

1500 psi / 103 bar

### Maximum Outlet Pressure

500 psig / 34.5 bar

### Outlet Pressure Ranges

3 to 500 psig / 0.21 to 34.5 bar

See Table 4

### Pressure Registration

Internal

### Temperature Capabilities

**Nitrile (NBR), Nylon (PA) and Neoprene (CR):**

-20 to 180°F / -29 to 82°C

**Fluorocarbon (FKM) and Polytetrafluoroethylene (PTFE):**  
0 to 300°F / -18 to 149°C

### Approximate Shipping Weight

**1 in. / DN 25 End Connection:**

25 lbs / 11.3 kg

**2 in. / DN 50 End Connection:**

30 lbs / 13.6 kg




Figure 1. Type 630 Big Joe High-Pressure Regulator

Figure 2. Type 630 Operational Schematic

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



12/12

### Features

- High-Pressure Capabilities
- Rugged Construction
- Better Low-Pressure Control

Table 1. Body Size and End Connection Style

BODY SIZE		BODY MATERIAL	
In.	DN	Cast Iron	Steel
1	25	NPT	NPT, CL150 RF, CL300 RF or CL600 RF
2	50		

Table 2. Flow and Sizing Coefficient

ORIFICE SIZE		WIDE-OPEN COEFFICIENT (FOR RELIEF SIZING)		C <sub>i</sub>	X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
In.	mm	C <sub>g</sub>	C <sub>v</sub>				
1/8	3.2	13.9	0.49	28.4	0.51	0.50	0.89
3/16	4.8	31.3	1.11	28.2	0.50		
1/4	6.4	55.1	2.03	27.2	0.47		
3/8	9.5	122.5	4.61	26.6	0.45		
1/2	13	216.0	8.18	26.4	0.44		



**Table 3. Maximum Inlet Pressure and Pressure Drop**

ORIFICE SIZE		MAXIMUM ALLOWABLE INLET PRESSURE <sup>(1)</sup>		MAXIMUM ALLOWABLE PRESSURE DROP					
				Nylon (PA) and PTFE Disk		Fluorocarbon (FKM) Disk		Nitrile (NBR) Disk	
In.	mm	psig	bar	psid	bar d	psid	bar d	psid	bar d
1/8 and 3/16	3.2 and 4.8	1500	103	1500	103	200	13.8	600	41.4
1/4	6.4	1500	103	1000	69.0			500	34.5
3/8	9.5	1000	69.0	500	34.5			250	17.2
1/2	13	750	51.7	250	17.2				

1. Inlet pressure must not exceed the sum of the actual outlet pressure setting and the maximum allowable pressure drop. For example, with an outlet pressure setting of 200 psig / 13.8 bar and a 3/8 in. / 9.5 mm orifice with a maximum allowable pressure drop of 500 psid / 34.5 bar d, the maximum allowable inlet pressure is 700 psig / 48.3 bar.

2. Nitrile (NBR) valve disks are normally furnished for pressure drops to 200 psi / 13.8 bar, differential. For better erosion resistance, Nylon (PA) valve disks are normally furnished for higher pressure drops. Some erosion of valve disks occurs at all pressure drops due to solid particles in the flow stream. The rate of erosion is higher with large amounts of impurities in the flow stream and with high pressure drops. Valve disks and other regulator parts must be inspected periodically for erosion and damage and must be replaced as necessary.

**Table 4. Outlet Pressure Range**

REGULATOR CONSTRUCTION	OUTLET PRESSURE RANGE		SPRING PART NUMBER	SPRING COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH		MAXIMUM OUTLET PRESSURE OVER SETPOINT <sup>(1)</sup>		MAXIMUM EMERGENCY OUTLET (CASING) PRESSURE <sup>(4)</sup>	
	psig	bar			In.	mm	In.	mm	psig	bar	psig	bar
Low pressure	3 to 10	0.21 to 0.69	0W019227022	Red Stripe	0.23	5.8	6.0	152	20 <sup>(2)</sup>	1.4 <sup>(2)</sup>	66	4.6
	8 to 20	0.55 to 1.4	0W019127022	Olive Drab	0.28	7.1						
	17 to 30	1.2 to 2.1	0W019027022	Unpainted	0.34	8.6			Limited by Maximum Emergency Outlet Pressure			
	27 to 40	1.9 to 2.8	0Y066427022	Green Stripe	0.36	9.1						
High pressure	27 to 50	1.9 to 3.5	0W019227022	Red Stripe	0.23	5.8	6.0	152	200	13.8	550	37.9
	46 to 95	3.2 to 6.6	0W019127022	Olive Drab	0.28	7.1						
	90 to 150	6.2 to 10.3	0W019027022	Unpainted	0.34	8.6						
	150 to 200	10.3 to 13.8	0Y066427022	Green Stripe	0.36	9.1	6.1	155				
	200 to 275	13.8 to 19.0	1J146927142	Blue Stripe	0.38	9.7						
275 to 500	19.0 to 34.5	1K370927082	Yellow Stripe	0.44	11	6.2	157	200 <sup>(3)</sup>	13.8 <sup>(3)</sup>			

1. Damage to internal parts of the regulator may occur if outlet pressure exceeds the actual pressure setting by amounts greater than those shown in this column.

2. For outlet pressure settings to 25 psig / 1.72 bar only. For pressure settings over 25 psig / 1.72 bar, outlet pressure is limited by maximum emergency outlet pressure of 45 psig / 3.10 bar.

3. For outlet pressure settings to 350 psig / 24.1 bar only. For pressure settings over 350 psig / 24.1 bar, outlet pressure is limited by maximum emergency outlet pressure of 550 psig / 37.9 bar.

4. Leakage or bursting of pressure-containing parts may occur if outlet pressure exceeds these values.

**Table 5. Construction Material**

BODY, SPRING CASE AND DIAPHRAGM ADAPTOR	VALVE DISK	DIAPHRAGM	ORIFICE	VALVE DISK HOLDER	GASKET
Cast iron or Steel	Nitrile (NBR), Nylon (PA), PTFE or Fluorocarbon (FKM)	Neoprene (CR) or Fluorocarbon (FKM)	Brass or Stainless steel	Brass or Stainless steel	<b>Inlet Body Gaskets:</b> Copper with brass trim or Stainless steel with Stainless steel trim <b>Other Gaskets:</b> Composition

# Type 630

## Pressure Reducing Regulator

FISHER™

**Table 6. Capacities for 1 in. / DN 25 Body Size Based on 20% Droop**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	INLET PRESSURE		OUTLET PRESSURE		1 IN. / DN 25 BODY CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
		psig	bar	psig	bar	Orifice Size, In. / mm									
						1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h		
LOW PRESSURE	3 to 10 psig / 0.21 to 0.69 bar  OW019227022  Red Stripe	10	0.69	5	0.34	200	5	510	14	990	27	1700	46	2200	59
		20	1.4			400	11	770	21	1200	32	2000	54	2700	72
		30	2.1			600	16	1100	29	1500	40	2200	59	3300	88
		50	3.4			950	25	1500	40	2100	56	2800	75	4200	113
		60	4.1			1100	29	1750	47	2400	64	3000	80	4100	110
		100	6.9			1700	46	2400	64	2900	78	4000	107	4900	131
		200	13.8	3000	80	3400	91	4200	113	5100	137	6100	163		
		400	27.6	3700	99	3900	105	4500	121	6400	172	----	----		
		500	34.5	4100	110	4300	115	4700	126	7400	198	----	----		
		600	41.4	4300	115	4600	123	5000	134	----	----	----	----		
		1000	69.0	4600	123	4900	131	5600	150	----	----	----	----		
		1500	103	5000	134	5400	145	----	----	----	----	----	----		
	20	1.4	10	0.69	500	13	1200	32	1800	48	4200	113	4900	131	
	30	2.1			700	19	1400	38	2800	75	4100	110	5300	142	
	50	3.4			1000	27	2300	62	4100	110	5100	137	6200	166	
	60	4.1			1150	31	2700	72	4200	113	5500	147	6500	174	
	100	6.9			1600	43	3800	102	5000	134	6400	172	7300	196	
	200	13.8			3300	88	5800	155	6900	185	7700	206	8200	220	
	400	27.6	5400	145	6900	185	7600	204	9000	241	----	----			
	500	34.5	6000	161	7100	190	7900	212	9700	260	----	----			
	600	41.4	6500	174	7300	196	8200	220	----	----	----	----			
	1000	69.0	7200	193	7700	206	8400	225	----	----	----	----			
	1500	103	7400	198	8400	225	----	----	----	----	----	----			
	8 to 20 psig / 0.55 to 1.4 bar  OW019127022  Olive Drab	20	1.4	10	0.69	500	13	700	19	1400	38	2200	59	3600	96
30		2.1	700			19	1300	35	2100	56	3100	83	4300	115	
50		3.4	900			24	1900	51	3200	86	4300	115	5400	145	
60		4.1	1050			28	2300	62	3500	94	4700	126	5800	155	
100		6.9	1600			43	3500	94	4600	123	5700	153	6900	185	
200		13.8	3300			88	4800	129	6200	166	7500	201	8200	220	
400		27.6	5400	145	6500	174	7600	204	8900	239	----	----			
500		34.5	6000	161	6900	185	7900	212	9400	252	----	----			
600		41.4	6500	174	7000	188	8200	220	----	----	----	----			
1000		69.0	7200	193	7700	206	8400	225	----	----	----	----			
1500		103	7400	198	8100	217	----	----	----	----	----	----			
20		1.4	15	1.0	470	13	1000	27	1700	46	3300	88	4900	131	
30	2.1	600			16	1500	40	2500	67	4600	123	5200	139		
50	3.4	1000			27	2300	62	3800	102	5500	147	5700	153		
60	4.1	1150			31	2700	72	4300	115	6100	163	6800	182		
100	6.9	1900			51	4300	115	6200	166	7600	204	9600	257		
200	13.8	3600			96	7500	201	8500	228	9600	257	10,000	268		
400	27.6	7100	190	8700	233	10,000	268	11,000	295	----	----				
500	34.5	8300	222	8800	236	10,500	281	12,000	322	----	----				
600	41.4	8600	230	9600	257	10,800	289	----	----	----	----				
1000	69.0	9600	257	10,000	268	11,000	295	----	----	----	----				
1500	103	10,000	268	11,000	295	----	----	----	----	----	----				

- continued -



**Table 6. Capacities for 1 in. / DN 25 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR		INLET PRESSURE		OUTLET PRESSURE		1 IN. / DN 25 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
							Orifice Size, In. / mm									
							1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
	psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h		
LOW PRESSURE	8 to 20 psig / 0.55 to 1.4 bar  OW019127022  Olive Drab		30	2.1	20	1.4	600	16	1500	40	2500	67	4600	123	6800	182
			40	2.8			800	21	2000	54	3400	91	5700	153	8100	217
			50	3.4			1000	27	2300	62	4200	113	6800	182	9000	241
			60	4.1			1150	31	2700	72	4900	131	7500	201	9800	263
			100	6.9			1800	48	4100	110	7400	198	9500	255	11,000	295
			200	13.8			3600	96	8000	214	10,000	268	12,000	322	13,000	348
	400	27.6	7200	193	10,000	268	13,000	348	14,000	375	----	----				
	500	34.5	8500	228	10,800	289	13,400	359	14,800	397	----	----				
	600	41.4	10,000	268	12,000	322	13,800	370	----	----	----	----				
	1000	69.0	11,000	295	12,300	330	15,000	402	----	----	----	----				
	1500	103	12,000	322	13,000	348	----	----	----	----	----	----				
	17 to 30 psig / 1.17 to 2.1 bar  OW019027022  Silver		30	2.1	20	1.4	590	16	900	24	1700	46	3300	88	4700	126
			40	2.8			790	21	1700	46	2400	64	4000	107	6100	163
			50	3.4			900	24	2200	59	3600	96	4900	131	6900	185
			60	4.1			1050	28	2500	67	4000	107	5500	147	7400	198
			100	6.9			1700	46	4000	107	5500	147	7600	204	9700	260
			200	13.8			3400	91	6400	172	9100	244	11,000	295	11,000	295
	400	27.6	7000	188	8700	233	11,000	295	13,000	348	----	----				
	500	34.5	8000	214	9800	263	11,800	316	13,700	367	----	----				
	600	41.4	9600	257	11,000	295	13,000	348	----	----	----	----				
	1000	69.0	10,000	268	12,000	322	14,000	375	----	----	----	----				
	1500	103	12,000	322	13,000	348	----	----	----	----	----	----				
	40	2.8	30	2.1	820	22	1700	46	2700	72	5100	137	7600	204		
	50	3.4			900	24	2200	59	3600	96	6400	172	8700	233		
60	4.1	1100			29	2600	70	4400	118	7500	201	9800	263			
100	6.9	1700			46	4100	110	6800	182	10,000	268	12,000	322			
200	13.8	3500			94	8000	214	11,000	295	14,000	375	16,000	429			
400	27.6	6900			185	13,000	348	15,000	402	17,000	456	----	----			
500	34.5	8800	236	14,000	375	15,600	418	18,500	496	----	----					
600	41.4	9700	260	15,000	402	16,000	429	----	----	----	----					
1000	69.0	15,500	415	17,800	477	17,900	480	----	----	----	----					
1500	103	16,400	440	18,500	496	----	----	----	----	----	----					
27 to 40 psig / 1.9 to 2.8 bar  OY066427022  Green Stripe		40	2.8	30	2.1	800	21	1500	40	2400	64	4400	118	6400	172	
		50	3.4			900	24	2000	54	3200	86	5600	150	7700	206	
		60	4.1			1100	29	2500	67	3900	105	6300	169	8900	239	
		100	6.9			1700	46	3900	105	6400	172	9400	252	11,000	295	
		200	13.8			3500	94	7000	188	9400	252	14,000	375	15,000	402	
		400	27.6			6900	185	12,000	322	15,000	402	17,000	456	----	----	
500	34.5	8800	236	12,500	335	15,600	418	17,800	477	----	----					
600	41.4	9700	260	13,400	359	16,000	429	----	----	----	----					
1000	69.0	15,600	418	15,800	423	17,900	480	----	----	----	----					
1500	103	16,400	440	18,000	482	----	----	----	----	----	----					
50	3.4	40	2.8	950	25	1800	48	3200	86	5500	147	8900	239			
60	4.1			1100	29	2300	67	4100	110	7500	201	10,000	268			
100	6.9			1800	48	4100	110	7000	188	11,000	295	14,000	375			
200	13.8			3500	94	7800	209	12,000	322	17,000	456	19,000	509			
400	27.6			7100	190	15,000	402	18,000	482	21,000	563	----	----			
500	34.5			8800	236	16,500	442	18,700	501	21,700	582	----	----			
600	41.4	9800	263	18,000	482	21,000	563	----	----	----	----					
1000	69.0	16,800	450	19,800	531	22,800	611	----	----	----	----					
1500	103	20,000	536	22,000	590	----	----	----	----	----	----					

- continued -

# Type 630

## Pressure Reducing Regulator

FISHER™

**Table 6. Capacities for 1 in. / DN 25 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR		INLET PRESSURE		OUTLET PRESSURE		1 IN. / DN 25 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS								
							Orifice Size, In. / mm								
							1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13
	psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
HIGH PRESSURE	27 to 50 psig / 1.9 to 3.4 bar  0W019227022  Red Stripe	60	4.1	50	3.4	900	24	2000	54	3100	83	5200	139	8100	217
		100	6.9			1700	46	3500	94	5700	153	10,500	281	13,000	348
		200	13.8			3500	94	7800	209	11,000	295	16,000	429	19,000	509
		300	20.7			5300	142	10,500	281	14,000	375	20,000	536	23,000	616
		400	27.6			6900	185	13,000	348	17,000	456	23,000	616	----	----
		500	34.5			8700	233	15,000	402	19,000	509	25,000	670	----	----
	46 to 95 psig / 3.2 to 6.6 bar  0W019127022  Olive Drab	600	41.4	50	3.4	9800	263	17,000	456	21,000	563	----	----	----	----
		1000	69.0			16,200	434	22,300	598	26,300	705	----	----	----	----
		1500	103			19,000	509	25,000	670	----	----	----	----	----	----
		300	20.7			5200	139	8900	239	11,000	295	16,000	429	20,000	536
		400	27.6			6800	182	11,000	295	15,000	402	20,000	536	----	----
		500	34.5			8600	230	12,300	330	16,300	437	22,000	590	----	----
	90 to 150 psig / 6.2 to 10.3 bar  0W019027022  Sliver	600	41.4	100	6.9	9800	263	14,000	375	19,000	509	----	----	----	----
		1000	69.0			13,500	362	18,400	493	21,700	582	----	----	----	----
		1500	103			18,000	482	24,000	643	----	----	----	----	----	----
		400	27.6			7100	190	14,000	375	19,000	509	27,000	724	----	----
		500	34.5			8600	230	16,300	437	21,300	571	28,700	769	----	----
		600	41.4			9900	265	19,000	509	25,000	670	----	----	----	----
	150 to 200 psig / 10.3 to 13.8 bar  0Y066427022  Green Stripe	1000	69.0	150	10.3	16,700	448	25,800	691	31,000	831	----	----	----	----
		1500	103			23,000	616	32,000	858	----	----	----	----	----	----
		200	13.8			3400	91	6800	182	10,000	268	16,000	429	26,000	697
		300	20.7			5300	142	10,000	268	15,000	402	24,000	643	35,000	938
		400	27.6			7100	190	14,000	375	22,000	590	34,000	911	42,000	1126
		500	34.5			8000	214	18,800	504	26,300	705	39,300	1053	----	----
90 to 150 psig / 6.2 to 10.3 bar  0W019027022  Sliver	800	55.2	125	8.62	13,000	348	29,000	777	38,000	1018	----	----	----	----	
	1000	69.0			17,000	456	34,000	911	44,300	1187	----	----	----	----	
	1500	103			26,000	697	43,000	1152	----	----	----	----	----	----	
	200	13.8			3400	91	6800	182	10,000	268	16,000	429	26,000	697	
	300	20.7			5300	142	10,000	268	15,000	402	24,000	643	35,000	938	
	400	27.6			7100	190	14,000	375	22,000	590	34,000	911	42,000	1126	
150 to 200 psig / 10.3 to 13.8 bar  0Y066427022  Green Stripe	500	34.5	150	10.3	8000	214	18,800	504	26,300	705	39,300	1053	----	----	
	800	55.2			13,000	348	29,000	777	38,000	1018	----	----	----	----	
	1000	69.0			17,000	456	34,000	911	44,300	1187	----	----	----	----	
	1500	103			26,000	697	47,000	1260	----	----	----	----	----	----	
	200	13.8			3400	91	6200	166	9300	249	16,000	429	26,000	697	
	300	20.7			5300	142	10,000	268	15,000	402	24,000	643	30,000	804	
90 to 150 psig / 6.2 to 10.3 bar  0W019027022  Sliver	400	27.6	150	10.3	7100	190	14,000	375	21,000	563	32,000	858	38,000	1018	
	500	34.5			8000	214	16,500	442	26,300	705	39,000	1045	----	----	
	800	55.2			13,000	348	27,000	724	37,000	992	----	----	----	----	
	1000	69.0			16,700	448	31,000	831	43,900	1177	----	----	----	----	
	1500	103			26,000	697	44,000	1179	----	----	----	----	----	----	
	200	13.8			3400	91	6200	166	9300	249	16,000	429	26,000	697	

- continued -



**Table 6. Capacities for 1 in. / DN 25 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	INLET PRESSURE		OUTLET PRESSURE		1 IN. / DN 25 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
						Orifice Size, In. / mm									
						1/8   3.2		3/16   4.8		1/4   6.4		3/8   9.5		1/2   13	
		psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
HIGH PRESSURE	150 to 200 psig / 10.3 to 13.8 bar  0Y066427022  Green Stripe	250	17.2	200	13.8	4200	113	8300	222	12,000	322	20,000	536	30,000	804
		300	20.7			5200	139	10,000	268	16,000	429	25,000	670	35,000	938
		600	41.4			9500	255	22,000	590	34,000	911	55,000	1474	----	----
		700	48.3			11,000	295	25,000	670	40,000	1072	61,500	1648	----	----
		800	55.2			13,000	348	30,000	804	43,000	1152	----	----	----	----
		1000	69.0			16,000	429	37,000	992	50,000	1340	----	----	----	----
	1200	82.7	20,000	536	41,000	1099	59,000	1581	----	----	----	----			
	1500	103	26,000	697	53,000	1420	----	----	----	----	----	----			
	200 to 275 psig / 13.8 to 19.0 bar  1J146927142  Blue Stripe	250	17.2	200	13.8	4200	113	8200	220	11,000	295	20,000	536	29,000	777
		300	20.7			5200	139	10,000	268	14,500	389	25,000	670	35,000	938
		600	41.4			9500	255	22,000	590	31,000	831	51,000	1367	----	----
		700	48.3			11,000	295	25,000	670	35,000	938	55,000	1474	----	----
800		55.2	13,000			348	29,000	777	42,000	1126	----	----	----	----	
1000		69.0	16,000			429	36,000	965	50,000	1340	----	----	----	----	
1200	82.7	19,000	509	41,000	1099	55,000	1474	----	----	----	----				
1500	103	26,000	697	51,000	1367	----	----	----	----	----	----				
275 to 500 psig / 19.0 to 34.5 bar  1K370927082  Yellow Stripe	300	20.7	275	19.0	4500	121	7500	201	10,000	268	20,000	536	31,000	831	
	400	27.6			6600	177	12,000	322	16,000	429	31,000	831	43,000	1152	
	600	41.4			9300	249	18,400	493	24,300	651	43,800	1174	----	----	
	1000	69.0			17,000	456	32,000	858	43,000	1152	----	----	----	----	
	1500	103			26,000	697	46,000	1233	----	----	----	----	----	----	
	400	27.6			300	20.7	6600	177	11,000	295	16,000	429	31,000	831	42,000
600	41.4	9900	265	19,000			509	26,000	697	48,000	1286	----	----		
700	48.3	11,000	295	23,000			616	30,000	804	54,000	1447	----	----		
800	55.2	13,000	348	26,000			697	35,000	938	61,000	1635	----	----		
1000	69.0	16,800	450	32,500			871	43,800	1174	----	----	----	----		
1300	89.6	22,000	590	43,000			1152	58,000	1554	----	----	----	----		
1500	103	26,000	697	49,000	1313	----	----	----	----	----	----				
500 to 700 psig / 34.5 to 48.3 bar  1K370927082  Yellow Stripe	500	34.5	400	27.6	8300	222	16,000	429	24,000	643	44,000	1179	62,000	1662	
	600	41.4			9400	252	21,300	571	30,000	804	55,300	1482	----	----	
	800	55.2			13,000	348	30,000	804	41,000	1099	76,000	2037	----	----	
	900	62.1			15,000	402	34,000	911	49,000	1313	85,000	2278	----	----	
	1000	69.0			17,000	456	38,000	1018	54,000	1447	----	----	----	----	
	1200	82.7			20,000	536	46,000	1233	63,000	1688	----	----	----	----	
1400	96.5	24,000	643	55,000	1474	76,000	2037	----	----	----	----				
1500	103	26,000	697	60,000	1608	----	----	----	----	----	----				
700 to 1000 psig / 48.3 to 68.9 bar  1K370927082  Yellow Stripe	550	37.9	500	34.5	8700	233	16,000	429	26,000	697	50,000	1340	77,000	2064	
	600	41.4			9500	255	19,000	509	36,800	986	57,000	1528	----	----	
	900	62.1			15,000	402	34,000	911	52,000	1394	92,000	2466	----	----	
	1000	69.0			17,000	456	39,000	1045	60,000	1608	100,000	2680	----	----	
	1500	103			26,000	697	59,000	1581	72,000	1930	----	----	----	----	

# Type 630

## Pressure Reducing Regulator



**Table 7. Capacities for 2 in. / DN 50 Body Size Based on 20% Droop**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	INLET PRESSURE		OUTLET PRESSURE		2 IN. / DN 50 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
		psig	bar	psig	bar	Orifice Size, In. / mm									
						1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
						SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
LOW PRESSURE	3 to 10 psig / 0.21 to 0.69 bar  0W019227022  Red Stripe	10	0.69	5	0.34	290	8	830	22	1300	35	3300	88	5900	158
		20	1.4			500	13	1200	32	2100	56	4800	129	9100	244
		30	2.1			760	20	1600	43	2700	72	7000	188	11,000	295
		50	3.4			1100	29	2200	59	3900	105	9800	263	17,000	456
		60	4.1			1250	34	2700	72	4500	121	11,100	297	19,500	523
		100	6.9			10	0.69	1900	51	4300	115	7000	188	17,000	456
		200	13.8	3700	99			8200	220	13,000	348	32,000	858	57,000	1528
		400	27.6	7200	193			16,000	429	28,000	750	64,000	1715	----	----
		500	34.5	9100	244			19,000	509	35,000	938	79,000	2117	----	----
		600	41.4	10,000	268			24,000	643	42,000	1126	----	----	----	----
		1000	69.0	18,000	482			39,000	1045	69,000	1849	----	----	----	----
		1500	103	22,000	590	60,000	1608	----	----	----	----	----	----		
	8 to 20 psig / 0.55 to 1.4 bar  0W019127022  Olive Drab	20	1.4	10	0.69	550	15	1200	32	1700	46	2500	67	4900	131
		30	2.1			760	20	1500	40	2500	67	4600	123	8800	236
		50	3.4			1000	27	2300	62	3800	102	7800	209	16,000	429
		60	4.1			1200	32	2700	72	4500	121	9900	265	18,500	496
		100	6.9			1900	51	4300	115	7400	198	17,000	456	30,000	804
		200	13.8			3600	96	8000	214	14,000	375	32,000	858	57,000	1528
		400	27.6	7200	193	15,000	402	28,000	750	60,000	1608	----	----		
		500	34.5	15	1.0	8800	236	19,000	509	35,000	938	74,000	1983	----	----
		600	41.4			10,000	268	23,000	616	42,000	1126	----	----	----	----
		1000	69.0			18,000	482	39,000	1045	72,000	1930	----	----	----	----
		1500	103			27,000	724	60,000	1608	----	----	----	----	----	----
		20	1.4			15	1.0	520	14	1100	29	1800	48	3500	94
30	2.1	740	20					1600	43	2800	75	5900	158	10,000	268
50	3.4	1100	29	2400	64			4300	115	9800	263	16,000	429		
60	4.1	1250	34	2800	75			5000	134	11,100	297	18,500	496		
100	6.9	1900	51	4400	118			7800	209	17,000	456	30,000	804		
200	13.8	3700	99	8300	222			14,000	375	31,000	831	57,000	1528		
400	27.6	7200	193	16,000	429	29,000	777	64,000	1715	----	----				
500	34.5	15	1.0	9200	247	20,000	536	37,000	992	82,000	2198	----	----		
600	41.4			11,000	295	23,000	616	42,000	1126	----	----	----	----		
1000	69.0			18,000	482	40,000	1072	71,000	1903	----	----	----	----		
1500	103			27,000	724	60,000	1608	----	----	----	----	----	----		

- continued -



**Table 7. Capacities for 2 in. / DN 50 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	INLET PRESSURE		OUTLET PRESSURE		2 IN. / DN 50 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS										
						Orifice Size, In. / mm										
						1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
		psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
LOW PRESSURE	8 to 20 psig / 0.55 to 1.4 bar  0W019127022  Olive Drab	30	2.1	20	1.4	700	19	1600	43	2600	70	5200	139	9200	247	
		40	2.8			900	24	2100	56	3500	94	7500	201	12,000	322	
		50	3.4			1100	29	2400	64	4300	115	9400	252	15,000	402	
		60	4.1			1250	34	2800	75	5100	137	11,000	295	18,000	482	
		100	6.9			1900	51	4300	115	7800	209	17,000	456	29,000	777	
		200	13.8			3700	99	8200	220	14,000	375	32,000	858	59,000	1581	
		400	27.6			7300	196	16,000	429	28,000	750	63,000	1688	----	----	
		500	34.5			9100	244	19,300	517	35,500	951	78,800	2112	----	----	
		600	41.4			11,000	295	24,000	643	43,000	1152	----	----	----	----	
		1000	69.0			17,700	474	39,200	1051	71,600	1919	----	----	----	----	
		1500	103			27,000	724	60,000	1608	----	----	----	----	----	----	
		17 to 30 psig / 1.17 to 2.1 bar  0W019027022  Silver	30			2.1	20	1.4	680	18	1300	35	2100	56	3500	94
	40		2.8	890	24	1800			48	2800	75	5100	137	8200	220	
	50		3.4	1000	27	2300			62	3700	99	6200	166	10,000	268	
	60		4.1	1200	32	2700			72	4300	115	7400	198	12,500	335	
	100		6.9	1900	51	4200			113	6900	185	12,000	322	24,000	643	
	200		13.8	3500	94	8000			214	13,000	348	32,000	858	56,000	1501	
	400		27.6	7100	190	15,000			402	28,000	750	63,000	1688	----	----	
	500		34.5	8900	239	19,200			515	35,500	951	78,800	2112	----	----	
	600		41.4	10,000	268	24,000			643	42,000	1126	----	----	----	----	
	1000		69.0	17,700	474	39,200			1051	70,600	1892	----	----	----	----	
	1500		103	27,000	724	60,000			1608	----	----	----	----	----	----	
	40		2.8	30	2.1	860			23	1800	48	2900	78	5300	142	8500
	50	3.4	1000			27	2300	62	3800	102	7300	196	11,000	295		
60	4.1	1200	32			2700	72	4700	126	8900	239	14,000	375			
100	6.9	1800	48			4200	113	7800	209	16,000	429	28,000	750			
200	13.8	3600	96			8100	217	14,000	375	24,000	643	58,000	1554			
400	27.6	7000	188			16,000	429	28,000	750	64,000	1715	----	----			
500	34.5	8900	239			19,100	512	34,900	935	80,900	2168	----	----			
600	41.4	10,000	268			23,000	616	42,000	1126	----	----	----	----			
1000	69.0	18,400	493			39,800	1067	70,900	1900	----	----	----	----			
1500	103	27,000	724			61,000	1635	----	----	----	----	----	----			
27 to 40 psig / 1.9 to 2.8 bar  0Y066427022  Green Stripe	40	2.8	30			2.1	850	23	1600	43	2600	70	4500	121	7200	193
	50	3.4					1000	27	2200	59	3500	94	5900	158	9700	260
	60	4.1		1200	32		2600	70	4200	113	7300	196	12,000	322		
	100	6.9		1800	48		4200	113	6900	185	12,000	322	23,000	616		
	200	13.8		3600	96		8100	217	13,000	348	24,000	643	57,000	1528		
	400	27.6		7000	188		15,000	402	28,000	750	64,000	1715	----	----		
	500	34.5		8900	239		18,800	504	34,900	935	80,200	2149	----	----		
	600	41.4		10,000	268		23,000	616	42,000	1126	----	----	----	----		
	1000	69.0		18,400	493		39,700	1064	70,800	1897	----	----	----	----		
	1500	103		27,000	724		61,000	1635	----	----	----	----	----	----		
	50	3.4		40	2.8		1000	27	2100	56	3400	91	5900	158	9900	265
	60	4.1					1200	32	2600	70	4300	115	7900	212	12,000	322
100	6.9	1900	51			4300	115	7200	193	13,000	348	24,000	643			
200	13.8	3600	96			8200	220	14,000	375	30,000	804	56,000	1501			
400	27.6	7200	193			16,000	429	28,000	750	63,000	1688	----	----			
500	34.5	8900	239			19,600	525	35,100	941	79,400	2128	----	----			
600	41.4	10,000	268			23,000	616	42,000	1126	----	----	----	----			
1000	69.0	17,300	464			39,400	1056	70,200	1881	----	----	----	----			
1500	103	27,000	724			61,000	1635	----	----	----	----	----	----			

- continued -

# Type 630

## Pressure Reducing Regulator

FISHER™

**Table 7. Capacities for 2 in. / DN 50 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR		INLET PRESSURE		OUTLET PRESSURE		2 IN. / DN 50 BODY CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
							Orifice Size, In. / mm									
							1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
							SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
HIGH PRESSURE	27 to 50 psig / 1.9 to 3.4 bar  0W019227022  Red Stripe	60	4.1	50	3.4	1000	27	2100	56	3200	86	5300	142	12,000	322	
		100	6.9			1800	48	3600	96	5800	155	10,000	268	21,000	563	
		200	13.8			3600	96	7900	212	12,000	322	21,000	563	55,000	1474	
		300	20.7			5500	147	11,000	295	19,000	509	48,000	1286	83,000	2224	
		400	27.6			7000	188	15,000	402	27,000	724	63,000	1688	----	----	
		500	34.5			8800	236	19,000	509	34,300	919	79,700	2136	----	----	
		600	41.4			10,000	268	23,000	616	42,000	1126	----	----	----	----	
		1000	69.0			18,000	482	39,900	1069	70,400	1887	----	----	----	----	
		1500	103			27,000	724	60,000	1608	----	----	----	----	----	----	----
		60	4.1	50	3.4	900	24	1600	43	2500	67	4400	118	7300	196	
		100	6.9			1600	43	3400	91	4300	115	7600	204	12,000	322	
		200	13.8			3500	94	6700	180	9600	257	16,000	429	27,000	724	
		300	20.7			5300	142	10,000	268	14,000	375	27,000	724	51,000	1367	
		400	27.6			6900	185	13,000	348	21,000	563	46,000	1233	----	----	
		500	34.5			8700	233	16,300	437	26,300	705	73,300	1964	----	----	
		600	41.4	10,000	268	20,000	536	35,000	938	----	----	----	----			
		1000	69.0	17,100	458	38,700	1037	68,800	1844	----	----	----	----			
		1500	103	26,000	697	59,000	1581	----	----	----	----	----	----			
		100	6.9	75	5.17	1800	48	3300	88	5200	139	9000	241	14,000	375	
		200	13.8			3600	96	7400	198	11,000	295	19,000	509	30,000	804	
	400	27.6	7200			193	15,000	402	24,000	643	----	----	----	----		
	500	34.5	8700			233	19,000	509	31,400	842	----	----	----	----		
	600	41.4	10,000			268	23,000	616	39,000	1045	----	----	----	----		
	1000	69.0	17,600			472	39,000	1045	69,300	1857	----	----	----	----		
	1500	103	24,000	643	60,000	1608	----	----	----	----	----	----				
	150	10.3	100	6.9	2600	70	4900	131	7400	198	12,000	322	18,000	482		
	200	13.8			3700	99	6900	185	10,000	268	17,000	456	27,000	724		
	300	20.7			5400	145	10,000	268	16,000	429	27,000	724	44,000	1179		
	400	27.6			7200	193	14,000	375	21,000	563	39,000	1045	----	----		
	500	34.5			8600	230	17,500	469	27,500	737	54,000	1447	----	----		
	1000	69.0			17,200	461	38,600	1034	66,000	1769	----	----	----	----		
	1500	103	27,000	724	59,000	1581	----	----	----	----	----	----				
	150	10.3	125	8.62	2500	67	5000	134	8100	217	12,000	322	20,000	536		
	200	13.8			3600	96	7400	198	11,000	295	19,000	509	30,000	804		
	300	20.7			5300	142	11,000	295	17,000	456	31,000	831	48,000	1286		
	400	27.6			7000	188	15,000	402	24,000	643	43,000	1152	65,000	1742		
	500	34.5			8800	236	19,000	509	30,000	804	59,000	1581	----	----		
	1000	69.0			17,000	456	39,000	1045	69,300	1857	----	----	----	----		
	1500	103	27,000	724	60,000	1608	----	----	----	----	----	----				
	200	13.8	150	10.3	3500	94	7300	196	11,000	295	18,000	482	30,000	804		
	300	20.7			5400	145	11,000	295	19,000	509	32,000	858	52,000	1394		
	400	27.6			7200	193	15,000	402	26,000	697	46,000	1233	77,000	2064		
	500	34.5			8600	230	19,800	531	32,800	879	62,500	1675	----	----		
	800	55.2			14,000	375	30,000	804	54,000	1447	----	----	----	----		
	1000	69.0			18,000	482	39,100	1048	67,700	1814	----	----	----	----		
	1500	103	27,000	724	60,000	1608	----	----	----	----	----	----				
	150 to 200 psig / 10.3 to 13.8 bar  0Y066427022  Green Stripe	200	13.8	150	10.3	3500	94	6900	185	10,000	268	17,000	456	28,000	750	
	300	20.7	5400			145	11,000	295	17,000	456	28,000	750	47,000	1260		
	400	27.6	7200			193	15,000	402	24,000	643	40,000	1072	66,000	1769		
	500	34.5	8500			228	18,300	490	30,250	811	53,000	1420	----	----		
	800	55.2	14,000			375	30,000	804	51,000	1367	----	----	----	----		
	1000	69.0	17,400			466	38,600	1034	66,400	1780	----	----	----	----		
	1500	103	27,000	724	60,000	1608	----	----	----	----	----	----				

- continued -





**Table 7. Capacities for 2 in. / DN 50 Body Size Based on 20% Droop (continued)**

	OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	INLET PRESSURE		OUTLET PRESSURE		2 IN. / DN 50 BODY CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY OF NATURAL GAS									
						Orifice Size, In. / mm									
						1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		psig	bar	psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
HIGH PRESSURE	150 to 200 psig / 10.3 to 13.8 bar  0Y066427022  Green Stripe	250	17.2	200	13.8	4300	115	9100	244	13,000	348	23,000	616	42,000	1126
		300	20.7			5300	142	11,000	295	18,000	482	33,000	884	52,000	1394
		600	41.4			10,000	268	23,000	616	40,000	1072	75,000	2010	----	----
		700	48.3			12,000	322	27,000	724	47,000	1260	90,000	2412	----	----
		800	55.2			14,000	375	31,000	831	54,000	1447	----	----	----	----
		1000	69.0			17,000	456	39,000	1045	69,000	1849	----	----	----	----
		1200	82.7			21,000	563	48,000	1286	83,000	2224	----	----	----	----
		1500	103			27,000	724	60,000	1608	----	----	----	----	----	----
	150 to 275 psig / 10.3 to 19.0 bar  1J146927142  Blue Stripe	250	17.2	200	13.8	4300	115	8900	239	12,000	322	23,000	616	35,000	938
		300	20.7			5300	142	11,000	295	18,000	482	31,000	831	46,000	1233
		600	41.4			10,000	268	23,000	616	38,000	1018	70,000	1876	----	----
		700	48.3			12,000	322	27,000	724	45,000	1206	83,000	2224	----	----
		800	55.2			14,000	375	31,000	831	52,000	1394	----	----	----	----
		1000	69.0			17,000	456	39,000	1045	68,000	1822	----	----	----	----
		1200	82.7			20,000	536	46,000	1233	83,000	2224	----	----	----	----
		1500	103			27,000	724	60,000	1608	----	----	----	----	----	----
		300	20.7	250	17.2	5000	134	10,000	268	17,000	456	30,000	804	52,000	1394
		400	27.6			7100	190	15,000	402	25,000	670	47,000	1260	76,000	2037
		500	34.5			8600	230	19,000	509	34,000	911	62,000	1662	103,000	2760
		600	41.4			10,000	268	23,000	616	41,000	1099	78,000	2090	----	----
	1000	69.0	275	19.0	17,000	456	40,000	1072	68,000	1822	----	----	----	----	
	1500	103			27,000	724	60,000	1608	----	----	----	----	----	----	
	300	20.7	275	19.0	4800	129	10,000	268	17,000	456	29,000	777	43,000	1152	
	400	27.6			7000	188	15,000	402	26,000	697	47,000	1260	73,000	1956	
600	41.4	10,000			268	23,000	616	40,800	1093	81,900	2195	----	----		
1000	69.0	17,000			456	40,000	1072	68,000	1822	----	----	----	----		
1500	103	26,000	697	61,000	1635	----	----	----	----	----	----	----			
275 to 500 psig / 19.0 to 34.5 bar  1K370927082  Yellow Stripe	300	20.7	275	19.0	4600	123	8400	225	13,000	348	23,000	616	37,000	992	
	400	27.6			7000	188	13,000	348	20,000	536	32,000	858	53,000	1420	
	600	41.4			10,000	268	23,000	616	40,800	1093	81,900	2195	----	----	
	1000	69.0			18,000	482	37,000	992	57,000	1528	----	----	----	----	
	1500	103			27,000	724	57,000	1528	----	----	----	----	----	----	
	400	27.6	300	20.7	7000	188	13,000	348	21,000	563	35,000	938	54,000	1447	
	600	41.4			10,000	268	21,000	563	34,000	911	59,000	1581	----	----	
	700	48.3			12,000	322	26,000	697	40,000	1072	72,000	1930	----	----	
	800	55.2			14,000	375	29,000	777	47,000	1260	81,000	2171	----	----	
	1000	69.0	400	27.6	15,800	423	33,200	890	53,600	1436	----	----	----	----	
	1300	89.6			23,000	616	50,000	1340	80,000	2144	----	----	----	----	
	1500	103			27,000	724	58,000	1554	----	----	----	----	----	----	
	500	34.5	400	27.6	8800	236	17,000	456	28,000	750	49,000	1313	77,000	2064	
	600	41.4			10,300	276	22,300	598	36,000	965	66,300	1777	100,300	2688	
800	55.2	14,000			375	31,000	831	51,000	1367	95,000	2546	----	----		
900	62.1	16,000			429	36,000	965	58,000	1554	110,000	2948	----	----		
1000	69.0	18,000			482	40,000	1072	66,000	1769	----	----	----	----		
1200	82.7	21,000			563	48,000	1286	80,000	2144	----	----	----	----		
1400	96.5	25,000	670	57,000	1528	96,000	2573	----	----	----	----				
1500	103	27,000	724	61,000	1635	----	----	----	----	----	----	----			
550	37.9	500	34.5	9000	241	18,000	482	30,000	804	53,000	1420	89,000	2385		
600	41.4			10,000	268	20,800	557	34,500	925	62,300	1670	102,000	2734		
900	62.1			16,000	429	35,000	938	60,000	1608	113,000	3028	----	----		
1000	69.0			18,000	482	40,000	1072	67,000	1796	130,000	3484	----	----		
1500	103			27,000	724	60,000	1608	82,000	2198	----	----	----	----		

# Type 630

## Pressure Reducing Regulator

FISHER™




Figure 3. NPT Dimensions




Figure 4. Flanged Dimensions

Table 8. NPT Dimension

BODY SIZE		NPT DIMENSION, IN. / mm											
		A		B		C		D		E		F	
Low-Pressure Regulator													
In.	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	7.38	187	3.69	94	7.19	183	10.31	262	1.38	35	15.88	403
2	50	7.88	200	3.94	100	7.19	183	10.94	278	2.00	51	16.38	416
High-Pressure Regulator													
1	25	7.38	187	3.69	94	4.69	119	7.81	198	1.38	35	15.88	403
2	50	7.88	200	3.94	100	4.69	119	8.44	214	2.00	51	16.38	416

Table 9. Flanged Dimension

BODY SIZE		FLANGED DIMENSION, IN. / mm															
		A		B		E		F				G				L	
								CL150 RF		CL300 RF and CL600 RF		CL150 RF		CL300 RF and CL600 RF			
Low-Pressure Regulator																	
In.	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	17.9	455	8	203	7.2	183	11.1	282	11.4	290	2.1	53	2.4	61	20.7	526
2	50	19.9	505	9	229	7.2	183	11.9	302	12.2	310	3	76	3.3	83.8	21.9	556
High-Pressure Regulator																	
1	25	17.9	455	8	203	4.7	119	8.6	218	8.9	226	2.1	53	2.4	61	21.2	538
2	50	19.9	505	11.2	284	4.7	119	9.4	238	9.7	246	3	76	3.3	84	21.4	544

## Ordering Guide

**Body Size (Select One)**

1 in. / DN 25\*\*\*

2 in. / DN 50\*\*\*

**Body Material and End Connection Style (Select One)**

**Cast Iron**

NPT\*\*\*

**Steel**

NPT\*\*\*

CL150 RF\*\*

CL300 RF\*\*

CL600 RF\*\*

**Trim Material (Select One)**

Brass\*\*\*

Stainless steel\*\*

**Disk and Holder Material (Select One)**

Nitrile (NBR) and Brass\*\*\*

Nitrile (NBR) and Stainless steel\*

Nylon (PA) and Brass\*\*

Nylon (PA) and Stainless steel\*

**Orifice Material (Select One)**

Brass\*\*\*

Stainless steel\*

**Orifice Size (Select One)**

1/8 in. / 3.2 mm\*\*

3/16 in. / 4.8 mm\*\*

1/4 in. / 6.4 mm\*\*

3/8 in. / 9.5 mm\*\*

1/2 in. / 13 mm\*\*

**Outlet Pressure Range (Select One)**

**Low Pressure**

3 to 10 psig / 0.21 to 0.69 bar, Red Stripe\*\*

8 to 20 psig / 0.55 to 1.4 bar, Olive Drab\*\*

17 to 30 psig / 1.2 to 2.1 bar, Unpainted\*\*

27 to 40 psig / 1.9 to 2.8 bar, Green Stripe\*\*

**High Pressure**

27 to 50 psig / 1.9 to 3.5 bar, Red Stripe\*\*

46 to 95 psig / 3.2 to 6.6 bar, Olive Drab\*\*

90 to 150 psig / 6.2 to 10.3 bar, Unpainted\*\*

150 to 200 psig / 10.3 to 13.8 bar, Green Stripe\*\*

200 to 275 psig / 13.8 to 19.0 bar, Blue Stripe\*\*

275 to 500 psig / 19.0 to 34.5 bar, Yellow Stripe\*\*

**Replacement Parts Kit (Optional)**

Yes, send one replacement parts kit to match this order.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**  
The recommended selection for orifice diameters is the smallest orifice that will handle the flow.

# Types 634 and 634M

## Shutoff Valve

FISHER™

### Introduction

The Types 634 and 634M high-pressure shutoff valves provide overpressure protection by containment. The Type 634 shutoff valve with internal registration is installed between a pressure-reducing regulator and a downstream system or equipment. The Type 634M shutoff valve with external registration requires a control line and is installed upstream of a pressure reducing regulator.

Regulator outlet pressure registers on the side of the diaphragm opposite the fracture disk. An excessive rise in outlet pressure provides enough force on the diaphragm to drive the stem through the fracture disk. This lets the plug close, and stay closed until upstream and downstream pressure are relieved and a new fracture disk is installed.

### Body Size and End Connection Style

3/4 or 1 NPT

### Wide-Open Flow Coefficients to Determine Capacities

NPS 3/4:  $C_g$ : 268,  $C_v$ : 7.37,  $C_i$ : 36.4

NPS 1:  $C_g$ : 319,  $C_v$ : 8.32,  $C_i$ : 38.3

### Maximum Inlet Pressure<sup>(1)</sup>

1500 psig / 103 bar

### Maximum Body Outlet Pressure<sup>(1)</sup>

Type 634: 150 psig / 10.3 bar

Type 634M: 1500 psig / 103 bar

### Maximum Diaphragm Pressure<sup>(1)</sup>

Operating: 150 psig / 10.3 bar

Emergency<sup>(2)</sup>: 225 psig / 15.5 bar

1. The pressure/temperature limits in this Datasheet or any applicable standard limitation should not be exceeded.

2. A pressure exceeding this value can cause failure of, or leakage from, pressure-containing components.

3. Low temperatures may stiffen elastomers and prevent normal shutoff.

### Pressure Registration

Type 634: Internal

Type 634M: External through 1/4 NPT control line connection in the diaphragm case

### Construction Materials

Body: WCC Steel

Casing and Fracture Disk: Cast Iron

Disk Retainer: Aluminum

Diaphragm: Neoprene (CR) and Nylon (PA) fabric

Plug Assembly: Aluminum and Nitrile (NBR)

O-rings: Nitrile (NBR)

Other Metal Parts: Steel and Stainless steel

### Temperature Capabilities<sup>(1)</sup>

-20<sup>(3)</sup> to 180°F / -29<sup>(3)</sup> to 82°C

### Approximate Weight

13 pounds / 6.0 kg

### Options

- One bleed valve in side tapping in upstream half of body
- Two bleed valves in side tappings in both upstream and downstream halves of body




Figure 1. Type 634 Shutoff Valve

Figure 2. Type 634M Shutoff Valve

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



12/18

### Features

- Overpressure Protection without Discharge of Gas or Liquid
- Positive Shutoff
- Application Versatility
- Easy Maintenance

Table 1. Fracture Disk Selection

SHATTER PRESSURE		FRACTURE DISK	
Type 634 Shutoff Valve	Type 634M Shutoff Valve	Color Code	Part Number
20 to 28 psig / 1.4 to 1.9 bar	20 to 28 psig / 1.4 to 1.9 bar at 0 psig / 0 bar inlet pressure; see curve A for other inlet pressures	Red	29A1936X012
50 to 60 psig / 3.4 to 4.1 bar	50 to 60 psig / 3.4 to 4.1 bar at 0 psig / 0 bar inlet pressure; see curve B for other inlet pressures	Yellow	29A1936X022
72 to 88 psig / 5.0 to 6.1 bar	72 to 88 psig / 4.9 to 6.1 bar at 0 psig / 0 bar inlet pressure; see curve C for other inlet pressures	White	29A1936X032




Figure 3. Types 634 and 634M Shutoff Valves Operational Schematic




Figure 4. Fracture Disk Selection




Figure 5. Dimensions

INLET PRESSURE TO SHUTOFF VALVE		WIDE-OPEN PRESSURE DROP THROUGH SHUTOFF VALVE		FLOW IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS			
psig	bar	psig	bar	3/4 NPT Body Size		1 NPT Body Size	
				SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
100	69.0	1	0.07	6000	161	7000	188
		5	0.34	13,000	348	15,000	402
		10	0.69	18,000	482	21,000	563
500	34.5	1	0.07	13,000	348	15,000	402
		5	0.34	29,000	777	34,000	911
		10	0.69	40,000	1072	46,000	1233
1000	69.0	1	0.07	18,000	482	21,000	563
		5	0.34	40,000	1072	46,000	1233
		10	0.69	56,000	1501	65,000	1741

# Types 634 and 634M

Shutoff Valve

FISHER™

## Ordering Guide

### Type (Select One)

- 634 (internal pressure registration)
- 634M (external pressure registration)

### Body Size and End Connection Style (Select One)

- 3/4 NPT
- 1 NPT

### Shatter Pressure (Select One)

- 20 to 28 psig / 1.4 to 1.9 bar, Red
- 50 to 60 psig / 3.4 to 4.1 bar, Yellow
- 72 to 88 psig / 5.0 to 6.1 bar, White

### Bleed Valve (Optional)

- Inlet
- Inlet and outlet

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

All regulators should be installed and used in accordance with federal, state and local codes and regulations.

### Introduction

The 912N Series direct-operated, spring-loaded regulators are used in a variety of service and industrial applications. These regulators have limited-capacity internal relief across the diaphragm (see Figure 2) to help minimize overpressure.

### Body Sizes and End Connection Style

**Inlet:** 1/4 NPT

**Outlet:** 1/4 or 3/8 NPT

### Flow Coefficients

**Wide-Open C<sub>g</sub> for Relief Sizing:** 4

### Maximum Allowable Inlet Pressure

250 psig / 17.2 bar

### Maximum Allowable Outlet Pressure

**Emergency Outlet Pressure:** 20 psig / 1.4 bar

### Recommended Outlet Pressure to

**Avoid Internal Part Damage:** 3 psid / 0.21 bar differential above outlet pressure setting; provide external relief if start-to-discharge point exceeds 3 psid / 0.21 bar differential

See Table 1

### Outlet Pressure Ranges

See Table 2

### Pressure Registration

Internal

### Temperature Capabilities

-20 to 160°F / -29 to 71°C

### Spring Case Vent

**Standard Construction:** 1/8 NPT tapped with removable screen

### Standard Location:

*Constructions Without Handwheel:* Over body outlet

*Handwheel Constructions:* Over body inlet

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/19

### Features

- Accurate, Sensitive Control
- Versatility
- Weather and Insect Protection
- Easy Maintenance



Figure 1. 912N Series Regulator




Figure 2. 912N Series Operational Schematic

Table 1. Construction Materials

BODY AND SPRING CASE	DISK AND LEVER ASSEMBLY	DIAPHRAGM	DIAPHRAGM PLATE	SPRING SEAT	RELIEF VALVE ASSEMBLY
Zinc	Fluorocarbon (FKM) disk with zinc lever, stainless steel lever pin and rod and plated carbon steel lever screws	Nitrile (NBR) or Nylon (PA)	Plated Steel	Plated Steel	Brass and Zinc

# 912N Series

## Pressure Reducing Regulator

FISHER™




Figure 3. Dimensions

Table 2. Outlet Pressure Ranges

AVAILABLE CONSTRUCTION	OUTLET PRESSURE RANGE		APPROXIMATE POINT ABOVE OUTLET PRESSURE SETTING AT WHICH INTERNAL RELIEF STARTS-TO-DISCHARGE		CONTROL SPRING SELECTION					
					Part Number	Color Code	Spring Free Length		Spring Wire Diameter	
	In. w.c.	mbar	In. w.c.	mbar			In.	mm	In.	mm
912N Series without handwheel	3 to 7	7 to 17	5 to 21	12 to 52	1B784327222	Red	1.09	27.7	0.035	0.89
	5 to 10	12 to 25	8 to 30	20 to 75	1B784427222	Orange	1.37	34.8	0.037	0.94
	9.25 to 13	23 to 32	16 to 39	40 to 97	1L507937022	Unpainted	1.78	45.2	0.038	0.97
	12 to 24	30 to 60	17 in. w.c. to 3 psig	42 mbar to 0.21 bar	1B784527222	Blue	1.34	34.0	0.047	1.19
912N Series with handwheel	0.5 to 2.7 psig	0.03 to 0.18 bar	0.70 to 6.80 psig	0.05 to 0.47 bar	1B784627222	Yellow	1.19	30.2	0.075	1.91
	2.7 to 5 psig	0.18 to 0.34 bar	3.80 to 12.5 psig	0.26 to 0.86 bar	1B784727222	Green	1.31	33.3	0.080	2.03
912N Series with handwheel	8 to 24	20 to 60	30.3 to 35.4	75 to 88	1B784527222	Blue	1.34	34.0	0.047	1.19
	2.7 to 5 psig	0.18 to 0.34 bar	5.4 to 6.7 psig	0.37 to 0.46 bar	1B784727222	Green	1.31	33.3	0.080	2.03

1. Internal Relief Performance is only adequate for relieving minor buildup situations. External relief is required if start-to-discharge point exceeds 3 psid / 0.21 bar differential.

Table 3. Capacities for Type 912N Regulators without Handwheel (Body Size 1/4 x 3/8 NPT)

OUTLET PRESSURE SETTING	OUTLET PRESSURE RANGE	SPRING PART NUMBER	OFFSET	ORIFICE SIZE	CAPACITY IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
					Inlet Pressure, psig / bar									
					5 / 0.34	10 / 0.69	25 / 1.7	50 / 3.4	75 / 5.2	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2	
5 in. w.c. / 12 mbar	3 to 7 in. w.c. / 7 to 17 mbar	1B784327222	1 in. w.c. / 2 mbar	0.073 in. / 1.9 mm	53 / 1.42	73 / 1.96	136 / 3.65	199 / 5.33	----	----	----	----	----	----
7 in. w.c. / 17 mbar	5 to 10 in. w.c. / 12 to 25 mbar	1B784427222	1 in. w.c. / 2 mbar		----	72 / 1.93	122 / 3.27	171 / 4.58	187 / 5.01	222 / 5.95	222 / 5.95	232 / 6.22	----	
11 in. w.c. / 27 mbar	9.25 to 13 in. w.c. / 23 to 32 mbar	1L507937022	1 in. w.c. / 2 mbar		----	61 / 1.64	100 / 2.68	144 / 3.86	163 / 4.37	180 / 4.82	210 / 5.63	234 / 6.27	259 / 6.94	
20 in. w.c. / 50 mbar	12 to 24 in. w.c. / 30 to 60 mbar	1B784527222	2 in. w.c. / 5 mbar		----	58 / 1.55	95 / 2.55	137 / 3.67	163 / 4.37	189 / 5.07	243 / 6.51	303 / 8.12	315 / 8.44	
1 psig / 69 mbar	0.5 to 2.7 psig / 0.03 to 0.18 bar	1B784627222	10%	0.094 in. / 2.4 mm	----	51 / 1.37	63 / 1.69	83 / 2.22	99 / 2.65	105 / 2.81	148 / 3.97	204 / 5.47	236 / 6.33	
			20%		----	70 / 1.88	100 / 2.68	140 / 3.75	177 / 4.74	201 / 5.39	302 / 8.09	377 / 10.1	440 / 11.8	
2 psig / 138 mbar	0.5 to 2.7 psig / 0.03 to 0.18 bar	1B784627222	10%		----	62 / 1.66	91 / 2.44	120 / 3.22	155 / 4.15	178 / 4.77	249 / 6.67	304 / 8.15	358 / 9.59	
			20%		----	85 / 2.28	146 / 3.91	220 / 5.90	300 / 8.04	348 / 9.33	480 / 12.9	576 / 15.4	683 / 18.3	
5 psig / 345 mbar	2.7 to 5 psig / 0.18 to 0.34 bar	1B784727222	10%		----	68 / 1.82	107 / 2.87	149 / 3.99	207 / 5.55	329 / 8.82	329 / 8.82	425 / 11.4	618 / 16.6	
			20%		----	94 / 2.52	169 / 4.53	283 / 7.58	386 / 10.3	486 / 13.0	711 / 19.1	860 / 23.0	1030 / 27.6	

---- Not recommended for the given pressure range.





**Table 4. Capacities for Type 912N Regulators with Handwheel (Body Size 1/4 x 3/8 NPT)**

OUTLET PRESSURE SETTING	OUTLET PRESSURE RANGE	SPRING PART NUMBER	OFFSET	ORIFICE SIZE, IN. / mm	CAPACITY IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS								
					Inlet Pressure, psig / bar								
					5 / 0.34	10 / 0.69	25 / 1.7	50 / 3.4	75 / 5.2	100 / 6.9	150 / 10.3	200 / 13.8	250 / 17.2
14 in. w.c. / 35 mbar	8 to 24 in. w.c. / 20 to 60 mbar	1B784527222	2 in. w.c. / 5 mbar	0.094 / 2.4	70 / 1.88	96 / 2.57	121 / 3.24	129 / 3.46	143 / 3.83	156 / 4.18	156 / 4.18	190 / 5.09	212 / 5.68
3 psig / 207 mbar	2.7 to 5 psig / 0.18 to 0.34 bar	1B784727222	10%		----	92 / 2.47	153 / 4.10	261 / 7.00	354 / 9.49	459 / 12.3	587 / 15.7	716 / 19.2	731 / 19.6

---- Not recommended for the given pressure range.

**Table 5. Shipping Weight**

END CONNECTION STYLE		APPROXIMATE SHIPPING WEIGHT	
Inlet	Outlet	Lb	kg
1/4 NPT	1/4 or 3/8 NPT	1.3	0.6

## Ordering Guide

### Body Size and End Connection Style (Select One)

- 1/4 x 3/8 NPT\*\*\*
- 1/4 x 1/4 NPT\*\*\*

### Outlet Pressure Range (Select One)

- 3 to 7 in. w.c. / 7 to 17 mbar, Red\*\*\*
- 5 to 10 in. w.c. / 12 to 25 mbar, Orange\*\*\*
- 9.25 to 13 in. w.c. / 23 to 32 mbar, Unpainted\*\*\*
- 12 to 24 in. w.c. / 30 to 60 mbar, Blue\*\*\*
- 0.5 to 2.7 psig / 0.03 to 0.18 bar, Yellow\*\*\*
- 2.7 to 5 psig / 0.18 to 0.34 bar, Green\*\*\*
- 8 to 24 in. w.c. / 20 to 60 mbar, Blue\*\*\*
- 2.7 to 5 psig / 0.18 to 0.34 bar, Green\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Downstream pressures significantly higher than the regulator's pressure setting may damage soft seats and other internal parts.

# 971 Series

## Pressure Reducing Regulator

TARTARINI™

### Introduction

The 971 Series regulators feature simple seat and counterbalanced valve. The “top entry” design allows to execute maintenance operations without disassembling the regulator from the line. They assure high accuracy of the regulated pressure even when the inlet pressure is extremely variable.

### Available Configurations

**Type 971:** Pilot-operated pressure reducing regulator for medium to high outlet pressures.

**Type 971-E:** Monitor version installed upstream or downstream of the working regulator for overpressure protection.

### Maximum Inlet (Casing) Pressure

1450 psig / 100 bar

### Maximum Outlet (Casing) Pressure

1015 psig / 70.0 bar

### Outlet Pressure Range

7.3 to 1015 psig / 0.50 to 70.0 bar

See Table 1

### Minimum Operating Differential Pressure

**Start Open:** 7.3 psid / 0.50 bar d

**Full Open:** 14.5 psid / 1.00 bar d

### Pressure Registration

External

### Flow Coefficients (Regulating and Wide-Open)

$C_g$ : 32,500

$C_v$ : 1048

$C_1$ : 31

### Body Size and End Connection Styles

NPS 10 / DN 250 body with CL300 or CL600 RF Flanges

### Pressure Ratings

**CL300 RF:** 740 psig / 51.0 bar

**CL600 RF:** 1450 psig / 100 bar

### Temperature Capabilities

#### Standard Version:

Working: 14 to 140°F / -10 to 60°C

#### Low Temperature Version:

Working: -4 to 140°F / -20 to 60°C

### Available Options

- Built-in silencer
- Prearrangement for remote alarms and controls

### Applications

- Non-corrosive gases (natural gas, compressed air, nitrogen, etc.)
- Sour gases (NACE standards)

### Approximate Weight (Including Pilot)

3748 lbs / 1700 kg




Figure 1. 971 Series with Type PS/79

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



05/15

### Features

- Accuracy Maintained with Variable Inlet Pressures
- Easy Setpoint Adjustment
- High Versatility for Different Applications
- Built-in Safety: Regulator Closes if Diaphragm Fails





Figure 2. Type 971 Operational Schematic



IN. /  
mm

Figure 3. Type 971 Dimensions

Table 1. Outlet Pressure Range of Service Regulator or Monitor Pilot

TYPE	USE	OUTLET PRESSURE RANGE		ALLOWABLE PRESSURE		BODY AND COVER MATERIAL
		psig	bar	psig	bar	
PS/79 <sup>(1)</sup>	Regulator or Monitor	7.3 to 580	0.50 to 40.0	1450	100	Steel
PSO/79 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/79 <sup>(1)</sup>	Operating Monitor - Monitor					
PS/80 <sup>(1)</sup>	Regulator or Monitor	22 to 580	1.5 to 40.0			
PSO/80 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/80 <sup>(1)</sup>	Operating Monitor - Monitor					
PRX/120 <sup>(2)</sup>	Regulator or Monitor	14.5 to 580	1.00 to 40.0			
PRX/125 <sup>(2)</sup>	Monitor					
PRX/120-AP <sup>(2)</sup>	Regulator or Monitor	435 to 1015	30.0 to 70.0			
PRX/125-AP <sup>(2)</sup>	Monitor					

1. All PS Series pilots are supplied with a filter (5-micron filtering degree) and built-in pressure stabilizer, with the exception of Types PSO/79 and PSO/80.  
2. The Type SA/2 pressure pre-reducer must be used with PRX Series pilots.

# 971 Series

Pressure Reducing Regulator

TARTARINI™

## Ordering Guide

Configuration	
<input type="checkbox"/>	Type 971**
<input type="checkbox"/>	Type 971-E**
Built-In Silencer - For Clean Gas Only (Select One)	
<input type="checkbox"/>	Type SR**
<input type="checkbox"/>	None
End Connection Style (Select One)	
<input type="checkbox"/>	CL300 RF**
<input type="checkbox"/>	CL600 RF**
Elastomer Part (Select One)	
<input type="checkbox"/>	Nitrile (NBR)***
<input type="checkbox"/>	Fluorocarbon (FKM)**
Working Temperature Range (Select One)	
<input type="checkbox"/>	Standard Version: 14 to 140°F / -10 to 60°C**
<input type="checkbox"/>	Low Temperature Version: -4 to 140°F / -20 to 60°C**
Pilot (Select One)	
<input type="checkbox"/>	Type PS/79**
<input type="checkbox"/>	Type REO/79**
<input type="checkbox"/>	Type PSO/80**
<input type="checkbox"/>	Type PRX/120**
<input type="checkbox"/>	Type PRX/120-AP**
<input type="checkbox"/>	Type PSO/79**
<input type="checkbox"/>	Type PS/80**
<input type="checkbox"/>	Type REO/80**
<input type="checkbox"/>	Type PRX125**
<input type="checkbox"/>	Type PRX125-AP**

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Outlet Pressure (See Table 1) (Specify)	
Monitor Booster Valve (Optional)	
<input type="checkbox"/>	Type PRX/131**
PED Certificate (Mandatory Only for CE Marker)	
<input type="checkbox"/>	Yes**
Replacement Parts Kit (Optional)	
<input type="checkbox"/>	Yes, send me one replacement parts kit to match this order.
Replacement Parts Kit (Optional)	
Horizontal Flow	
<input type="checkbox"/>	Left to Right
<input type="checkbox"/>	Right to Left

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Regulator body size should not be larger than the pipe size. In many cases, the regulator body is one size smaller than the pipe size.



### Introduction

Types 1098-EGR and 1098H-EGR regulators provide economical and accurate pressure control in a variety of applications: natural gas distribution systems; fuel gas supply to industrial boilers, furnaces, ovens and mixers; and commercial or industrial businesses such as steel mills, asphalt plants and shopping centers. This regulator is used with a Type 6351, 6352, 6353, 6354, Y600AM or 61 Series pilot.

The superior performance of this regulator is due to the amplifying effect of the pilot and the two-path control system. Changes in outlet pressure act quickly on the actuator diaphragm to provide fast response to system changes. The pilot amplifies small system changes to position the main valve for precise pressure control.

### Body Sizes and End Connection Styles

See Table 1

### Maximum Outlet (Casing) Pressure

See Table 2

### Flow and IEC Sizing Coefficients

See Table 4

### Outlet Pressure (Control) Ranges

4 in. w.c. to 300 psig / 10 mbar to 20.7 bar  
See Table 5

### Differential Pressures

See Table 6

### Flow Capacities

See Table 9

### Main Valve Maximum Inlet Pressure<sup>(1)</sup>

400 psig / 27.6 bar or body rating limit, whichever is lower

### Pressure Registration

External

### Temperature Capabilities

**Nitrile (NBR):** -20 to 180°F / -29 to 82°C

**Fluorocarbon (FKM):** 0 to 300°F / -18 to 149°C except water which is limited to 0 to 200°F / -18 to 93°C

**Ethylene propylene (EPR):** -20 to 275°F / -29 to 135°C

### Approximate Shipping Weight

See Table 12

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



09/19

### Features

- Differential as Low as 1 psid / 70 mbar d
- Quick Change Trim Package
- Optional Noise Abatement Trim (Up to 30 dBA reduction)
- No Atmospheric Bleed
- Easy Top Entry In-Line Maintenance
- Stainless steel Construction for Corrosive Environments and Oxygen Service
- Aqueous Trim Packages (Application Specific)
- In-Service Travel Inspection
- Materials of Construction Compatible with Below Grade Installations



Figure 1. Type 1098-EGR




Figure 2. Type 1098-EGR with 6350 Series Pilot Operational Schematic

# Types 1098-EGR and 1098H-EGR

## Pressure Reducing Regulators

FISHER™

**Table 1. Body Size and End Connection Style**

BODY SIZE		BODY MATERIAL	
NPS	DN	Cast Iron	Steel or Stainless steel
1 or 2	25 or 50	NPT, CL125 FF	NPT, CL150 RF, CL300 RF, CL600 RF, BWE, SWE or PN 16/25/40
3, 4 or 6	80, 100, 150	CL125 FF	CL150 RF, CL300 RF, CL600 RF, BWE or PN 16/25/40
8 x 6, 12 x 6	200 x 150, 300 x 150	----	CL150 RF, CL300 RF, CL600 RF, BWE

**Table 2. Actuator Size and Maximum Pressure**

ACTUATOR		OUTLET PRESSURE		EMERGENCY CASING PRESSURE	
Type	Size	psig	bar	psig	bar
1098	30	100	6.9	115	7.9
	40 (standard)	75	5.2	82	5.6
	70	50	3.4	65	4.5
1098H	30	350	24.1	400	27.6

**Table 3. Construction Material**

MAIN VALVE BODY	BONNET	VALVE PLUG AND SEAT RING	CAGE	PISTON RING	ACTUATOR DIAPHRAGM AND O-RING	MAIN VALVE PORT AND UPPER SEAL AND O-RING	ACTUATOR STEM	PILOT BODY AND CASING
Cast Iron, WCC Steel or CF8M Stainless steel	Zinc-plated steel or 304 Stainless steel	Hardened 416 Stainless steel or 316 Stainless steel	CF8M Stainless steel (linear), 416 or 316 Stainless steel (Whisper Trim™) or hardened ENC coated Cast Iron (quick opening)	Polytetrafluoroethylene (PTFE)	Nitrile (NBR) (standard), Fluorocarbon (FKM) or Ethylenepropylene (EPDM)	Nitrile (NBR) (standard), Fluorocarbon (FKM) or Ethylenepropylene (EPR)	17-4 PH Stainless steel (standard) or 316 Stainless steel	Aluminum or Stainless steel (for Type 6351, 6352, 6353, 6354L, 6354M or 6354H Pilot); or Cast Iron (for 61 Series and Type Y600AM Pilot)

**Table 4. Flow and Sizing Coefficient**

BODY SIZE		LINEAR CAGE											IEC Sizing Coefficient		
		1:1 Line Size to Body Size					2:1 Line Size to Body Size								
NPS	DN	C <sub>g</sub>		C <sub>v</sub>		C <sub>i</sub>	C <sub>g</sub>		C <sub>v</sub>		C <sub>i</sub>	X <sub>t</sub>	F <sub>d</sub>	F <sub>i</sub>	
		Regulating	Wide-Open	Regulating	Wide-Open		Regulating	Wide-Open	Regulating	Wide-Open					
1	25	600	632	16.8	17.7	35.7	568	598	17.2	18.1	33.0	0.806	0.43	0.84	
2	50	2280	2400	63.3	66.7	36.0	2050	2160	59.6	62.8	34.4	0.820	0.35		
3	80	4630	4880	132	139	35.1	4410	4650	128	135	34.4	0.779	0.30		
4	100	7320	7710	202	213	36.2	6940	7310	198	209	35.0	0.829	0.28		
6	150	12,900	13,600	397	418	32.5	12,100	12,800	381	404	31.7	0.668	0.28		
8 x 6	200 x 150	18,480	19,450	578	608	32.0	17,370	18,280	543	571	32.0	0.648	0.28		
12 x 6	300 x 150	21,180	22,290	662	697	32.0	19,900	20,950	622	655	32.0	0.648	0.28		
BODY SIZE		WHISPER TRIM™ CAGE											IEC Sizing Coefficient		
		1:1 Line Size to Body Size					2:1 Line Size to Body Size								
NPS	DN	C <sub>g</sub>		C <sub>v</sub>		C <sub>i</sub>	C <sub>g</sub>		C <sub>v</sub>		C <sub>i</sub>	X <sub>t</sub>	F <sub>d</sub>	F <sub>i</sub>	
		Regulating	Wide-Open	Regulating	Wide-Open		Regulating	Wide-Open	Regulating	Wide-Open					
1	25	576	607	16.7	17.6	34.5	529	557	15.6	16.4	34.0	0.753	0.10	0.89	
2	50	1970	2080	54.7	57.8	36.0	1830	1930	52.3	55.1	35.0	0.820	0.07		
3	80	3760	3960	107	113	35.0	3630	3830	106	110	34.2	0.775	0.05		
4	100	6280	6610	180	190	34.8	6020	6340	171	180	35.2	0.766	0.04		
6	150	9450	9950	295	310	32.0	9240	9730	291	306	31.7	0.648	0.03		
8 x 6	200 x 150	10,660	11,220	305	321	35.0	10,020	10,550	286	301	35.0	0.775	0.03		
12 x 6	300 x 150	11,050	11,630	316	332	35.0	10,380	10,930	297	312	35.0	0.775	0.03		



**Table 5. Outlet (Control) Pressure Range**

PILOT TYPE	OUTLET (CONTROL) PRESSURE RANGE		SPRING COLOR	SPRING PART NUMBER
6351	3 to 20 psig 5 to 35 psig 35 to 100 psig	0.21 to 1.4 bar 0.34 to 2.4 bar 2.4 to 6.9 bar	Green Unpainted Red	1B986027212 1B788327022 1K748527202
6352	14 in. w.c. to 2 psig 2 to 10 psig	35 mbar to 0.14 bar 0.14 to 0.69 bar	Yellow Black	14A9672X012 14A9673X012
6353	3 to 40 psig 35 to 125 psig	0.21 to 2.8 bar 2.4 to 8.6 bar	Yellow Red	1E392527022 1K748527202
6354L <sup>(1)</sup> 6354M <sup>(2)</sup> 6354H <sup>(2)</sup>	85 to 200 psig 175 to 220 psig 200 to 300 psig	5.9 to 13.8 bar <sup>(1)</sup> 12.1 to 15.2 bar <sup>(2)</sup> 13.8 to 20.7 bar <sup>(2)</sup>	Blue Blue Green	1L346127142 1L346127142 15A9258X012
61L 61LD 61LE	0.25 to 2 psig 1 to 5 psig 2 to 10 psig 5 to 15 psig 10 to 20 psig	0.02 to 0.14 bar 0.07 to 0.34 bar 0.14 to 0.69 bar 0.35 to 1.0 bar 0.7 to 1.4 bar	Red Yellow Blue Brown Green	1B886327022 1J857827022 1B886427022 1J857927142 1B886527022
61H	10 to 65 psig	0.7 to 4.5 bar	Green Stripe	0Y066427022
61HP	15 to 45 psig 35 to 100 psig 100 to 300 psig	1.0 to 3.1 bar 2.4 to 6.9 bar 6.9 to 20.7 bar	Yellow Blue Red	1E392527022 1D387227022 1D465127142
Y600AM	4 to 8 in. w.c. 7 to 16 in. w.c. 15 in w.c. to 1.2 psig 1.2 to 2.5 psig 2.5 to 4.5 psig 4.5 to 7 psig	10 to 20 mbar 17 to 40 mbar 37 mbar to 0.08 bar 0.08 to 0.17 bar 0.17 to 0.31 bar 0.31 to 0.48 bar	Red Unpainted Yellow Green Light Blue Black	1B653827052 1B653927022 1B537027052 1B537127022 1B537227022 1B537327052

1. Without diaphragm limiter.  
2. With diaphragm limiter.

**Table 6. Maximum and Minimum Differential Pressures for Main Valve Spring Selection**

BODY SIZE		SPRING PART NUMBER AND COLOR	MAXIMUM ALLOWABLE DIFFERENTIAL PRESSURE <sup>(1)</sup>		MINIMUM DIFFERENTIAL PRESSURE REQUIRED FOR FULL STROKE						
NPS	DN		psid	bar d	Size 30 Actuator		Size 40 Actuator		Size 70 Actuator		
				psid	bar d	psid	bar d	psid	bar d	psid	bar d
1	25	14A9687X012, Green	60	4.1	3.5	0.24	2.5	0.17	1	0.07	
		14A9680X012, Blue	125	8.6	5	0.34	3	0.21	1.5	0.10	
		14A9679X012, Red	400 / 27.6 or body rating limit, whichever is lower		7	0.48	5	0.34	2.5	0.17	
2	50	14A6768X012, Yellow	20	1.4	----	----	2	0.14	1	0.07	
		14A6626X012, Green	60	4.1	4	0.28	3	0.21	1.5	0.10	
		14A6627X012, Blue	125	8.6	6	0.41	5	0.34	2	0.14	
		14A6628X012, Red	400 / 27.6 or body rating limit, whichever is lower		11	0.76	10	0.69	3	0.21	
3	80	14A6771X012, Yellow	20	1.4	----	----	2.5	0.17	1	0.07	
		14A6629X012, Green	60	4.1	5	0.34	4	0.28	2	0.14	
		14A6630X012, Blue	125	8.6	8	0.55	6	0.41	2.5	0.17	
		14A6631X012, Red	400 / 27.6 or body rating limit, whichever is lower		14	0.97	11	0.76	4	0.28	
4	100	14A6770X012, Yellow	20	1.4	----	----	3.5	0.25	1.3	0.09	
		14A6632X012, Green	60	4.1	10	0.69	5	0.34	2.5	0.17	
		14A6633X012, Blue	125	8.6	13	0.90	8	0.55	3	0.21	
		14A6634X012, Red	400 / 27.6 or body rating limit, whichever is lower		22	1.5	13	0.90	5	0.34	
6, 8 x 6 and 12 x 6	150, 200 x 150 and 300 x 150	15A2253X012, Yellow	20	1.4	----	----	6	0.42	2.2	0.15	
		14A9686X012, Green	60	4.1	13	0.90	9.5	0.66	4	0.28	
		14A9685X012, Blue	125	8.6	19	1.3	14	0.97	6	0.41	
		15A2615X012, Red	400 / 27.6 or body rating limit, whichever is lower		28 <sup>(2)</sup>	1.9 <sup>(2)</sup>	19	1.3	8	0.55	

1. Maximum inlet pressure is equal to set pressure plus maximum differential.  
2. Requires special 6300 Series pilot construction without integral relief valve and with external Type 1806, 40 psid / 2.8 bar d relief valve.

# Types 1098-EGR and 1098H-EGR

## Pressure Reducing Regulators



**Table 7. Proportional Band (Standard Pilot Restriction and Size 40 Type 1098 Actuator<sup>(1)</sup>)**

BODY SIZE		PILOT		PROPORTIONAL BAND					
				Yellow or Green Main Valve Spring		Blue Main Valve Spring		Red Main Valve Spring	
NPS	DN	Type	Control Spring Color	psi	mbar	psi	mbar	psi	mbar
				1	25	6351	Green	0.1	7
Unpainted	0.2	14	0.4				28	0.8	55
Red	0.4	28	0.8				55	1.0	69
6352	Yellow	0.04	3			0.1	7	0.2	14
	Black	0.08	6			0.2	14	0.4	28
6353	Yellow	0.2	14			0.4	28	0.8	55
	Red	0.4	28			0.8	55	1.0	69
61L	All	0.09	6			0.16	11	0.3	21
61LD		0.04	3			0.08	6	0.2	14
61LE, 61H and 61HP		0.4	28			0.8	55	1.0	69
Y600AM <sup>(2)</sup>	Red	0.01	0.6			0.02	1	0.04	3
	Unpainted	0.01	0.6			0.02	1	0.04	3
	Yellow	0.05	3			0.1	7	0.15	10
	Green	0.10	7			0.15	10	0.2	14
	Light Blue	0.15	10			0.2	14	0.25	17
	Black	0.2	14	0.25	17	0.3	21		
	Black	0.2	14	0.25	17	0.3	21		
2	50	6351	Green	0.2	14	0.3	21	0.5	34
			Unpainted	0.3	21	0.5	34	1.0	69
			Red	0.5	34	1.0	69	1.4	97
		6352	Yellow	0.05	4	0.15	10	0.3	21
			Black	0.1	7	0.3	21	0.6	41
		6353	Yellow	0.3	21	0.5	34	1.0	69
			Red	0.5	34	1.0	69	1.4	97
		61L	All	0.1	7	0.2	14	0.6	41
		61LD		0.05	3	0.1	7	0.3	21
		61LE, 61H and 61HP		0.5	34	1.0	69	1.4	97
		Y600AM <sup>(2)</sup>	Red	0.01	0.6	0.02	1	0.04	3
			Unpainted	0.01	0.6	0.02	1	0.04	3
			Yellow	0.05	4	0.1	7	0.15	10
			Green	0.1	7	0.15	10	0.2	14
			Light Blue	0.15	10	0.2	14	0.25	17
Black	0.2		14	0.25	17	0.3	21		
Black	0.2		14	0.25	17	0.3	21		
3	80	6351	Green	0.3	21	0.4	28	0.6	41
			Unpainted	0.4	28	0.6	41	1.2	83
			Red	0.9	62	1.2	83	1.5	103
		6352	Yellow	0.1	7	0.2	14	0.4	28
			Black	0.2	14	0.4	28	0.8	55
		6353	Yellow	0.4	28	0.6	41	1.2	83
			Red	0.9	62	1.2	83	1.5	103
		61L	All	0.2	14	0.4	28	1.0	69
		61LD		0.1	7	0.2	14	0.5	34
		61LE, 61H and 61HP		0.9	62	1.2	83	1.5	103
		Y600AM <sup>(2)</sup>	Red	0.01	0.6	0.02	1	0.04	3
			Unpainted	0.01	0.6	0.02	1	0.04	3
			Yellow	0.05	3	0.1	7	0.15	10
			Light Green	0.1	7	0.15	10	0.2	14
			Light Blue	0.15	10	0.2	14	0.25	17
Black	0.2		14	0.25	17	0.3	21		
Black	0.2		14	0.25	17	0.3	21		

1. For other combinations, multiply table values by 1.6 for a size 30 actuator, 0.4 for a size 70 actuator, 2.0 for a low-gain Type 6352 or 6353 pilot restriction and 0.5 for a high-gain Type 6352 or 6353 pilot restriction. For instance, a standard NPS 2 / DN 50 Type 1098-EGR-6352 regulator with black pilot control spring and blue main valve spring has a proportional band of 0.3 psi / 21 mbar as given in the table, but this same regulator with low-gain restriction and size 70 actuator has a proportional band of 0.3 psi / 21 mbar x 2.0 x 0.4 = 0.24 psi / 17 mbar.

2. The configuration utilized in determining the proportional band of the Type Y600AM included the 95 Series pilot supplying the Type Y600AM for improved stability and a fixed restrictor, part number 1K9484X0022 or an optional Type 112 variable restrictor with a setting of 3.

- continued -





**Table 7. Proportional Band (Standard Pilot Restriction and Size 40 Type 1098 Actuator<sup>(1)</sup>) (continued)**

BODY SIZE		PILOT		PROPORTIONAL BAND					
		Type	Control Spring Color	Yellow or Green Main Valve Spring		Blue Main Valve Spring		Red Main Valve Spring	
NPS	DN			psi	mbar	psi	mbar	psi	mbar
4	100	6351	Green	0.4	28	0.5	34	0.8	55
			Unpainted	0.7	48	0.8	55	1.4	97
			Red	1.2	83	2.0	138	3.0	207
		6352	Yellow	0.15	10	0.3	21	0.6	41
			Black	0.3	21	0.6	41	1.2	83
		6353	Yellow	0.7	48	0.8	55	1.4	97
			Red	1.2	83	2.0	138	3.0	207
		61L	All	0.3	21	0.6	41	1.4	97
		61LD		0.15	10	0.3	21	0.7	48
		61LE, 61H and 61HP		1.2	83	2.0	138	3.0	207
		Y600AM <sup>(2)</sup>	Red	0.01	0.6	0.02	1	0.04	3
			Unpainted	0.01	0.6	0.02	1	0.04	3
			Yellow	0.05	3	0.1	7	0.15	10
			Green	0.1	7	0.15	10	0.2	14
Light Blue	0.15		10	0.2	14	0.25	17		
Black	0.2		14	0.25	17	0.3	21		
6, 8 x 6 and 12 x 6	150, 200 x 150 and 300 x 150	6351	Green	0.5	34	0.6	41	1.0	69
			Unpainted	0.9	62	1.5	103	2.0	138
			Red	1.5	103	2.5	172	3.5	241
		6352	Yellow	0.2	14	0.4	28	0.8	55
			Black	0.4	28	0.8	55	1.6	110
		6353	Yellow	0.9	62	1.5	103	2.0	138
			Red	1.5	103	2.5	172	3.5	241
		61L	All	0.6	41	1.2	83	2.0	138
		61LD		0.3	21	0.6	41	2.0	69
		61LE, 61H and 61HP		1.5	103	2.5	172	3.5	241
		Y600AM <sup>(2)</sup>	Red	0.01	0.6	0.02	1	0.04	3
			Unpainted	0.01	0.6	0.02	1	0.04	3
			Yellow	0.05	3	0.10	7	0.15	10
			Green	0.05	3	0.15	10	0.2	14
Light Blue	0.15		10	0.2	14	0.25	17		
Black	0.2		14	0.25	17	0.3	21		

1. For other combinations, multiply table values by 1.6 for a size 30 actuator, 0.4 for a size 70 actuator, 2.0 for a low-gain Type 6352 or 6353 pilot restriction and 0.5 for a high-gain Type 6352 or 6353 pilot restriction. For instance, a standard NPS 2 / DN 50 Type 1098-EGR-6352 regulator with black pilot control spring and blue main valve spring has a proportional band of 0.3 psi / 21 mbar as given in the table, but this same regulator with low-gain restriction and size 70 actuator has a proportional band of 0.3 psi / 21 mbar x 2.0 x 0.4 = 0.24 psi / 17 mbar.

2. The configuration utilized in determining the proportional band of the Type Y600AM included the 95 Series pilot supplying the Type Y600AM for improved stability and a fixed restrictor, part number 1K9484X0022 or an optional Type 112 variable restrictor with a setting of 3.

# Types 1098-EGR and 1098H-EGR

## Pressure Reducing Regulators



**Table 8. Approximate Proportional Band Range (Standard Pilot Restriction, Size 30 Type 1098H Actuator<sup>(1)</sup>)**

BODY SIZE		PILOT		APPROXIMATE PROPORTIONAL BAND RANGE					
				Green Main Valve Spring		Blue Main Valve Spring		Red Main Valve Spring	
		NPS	DN	Type	Control Spring Color	psi	bar	psi	bar
1	25	6354L, 6354M or 6354H	Blue or Green	1.0	0.07	1.5	0.10	2.5	0.17
2	50			1.5	0.10	2.0	0.14	3.0	0.21
3	80			2.5	0.17	3.0	0.21	4.0	0.28
4	100			3.5	0.24	4.0	0.28	5.0	0.34
6, 8 x 6 or 12 x 6	150, 200 x 150 or 300 x 150			4.0	0.28	5.0	0.34	Not Available	

1. For other restrictions, multiply table values by 2.0 for a low-gain restriction or by 0.5 for a high-gain restriction. For instance, a standard NPS 2 / DN 50 Type 1098H-EGR-6354L regulator with blue control spring and blue main valve spring has a proportional band of 2.0 psi / 0.14 bar as given in the table. But this same regulator with low-gain restriction has a proportional band of 2.0 psi / 0.14 bar x 2.0 = 4.0 psi / 0.28 bar.

**Table 9. Capacities**

INLET PRESSURE		OUTLET PRESSURE SETTING		CAPACITIES IN THOUSANDS OF SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS FOR REGULATORS WITH STANDARD LINEAR CAGE, STANDARD TRAVEL AND LINE SIZE EQUALS MAIN VALVE BODY SIZE													
				NPS 1 / DN 25 Body Size		NPS 2 / DN 50 Body Size		NPS 3 / DN 80 Body Size		NPS 4 / DN 100 Body Size		NPS 6 / DN 150 Body Size		NPS 8 x 6 / DN 200 x 150 Body Size		NPS 12 x 6 / DN 300 x 150 Body Size	
psig	bar	psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
3	0.21	7 in. w.c.	17 mbar	8	0.2	32	0.9	66	1.8	101	2.7	----	----	----	----	----	----
5	0.34	7 in. w.c.	17 mbar	11	0.3	42	1.1	87	2.3	135	3.6	257	6.9	372	10.0	427	11.4
		1	0.07	10	0.3	39	1.0	82	2.2	126	3.4	241	6.5	350	9.4	401	10.7
10	0.69	2	0.14	9	0.2	35	0.9	73	2.0	112	3.0	----	----	----	----	----	----
		7 in. w.c.	17 mbar	17	0.5	63	1.7	129	3.5	201	5.4	376	10.1	542	14.5	622	16.7
		3	0.21	15	0.4	56	1.5	116	3.1	180	4.8	341	9.1	493	13.2	565	15.1
15	1.0	5	0.35	13	0.3	49	1.3	102	2.7	158	4.2	302	8.1	438	11.7	502	13.5
		7	0.48	11	0.3	40	1.1	82	2.2	127	3.4	----	----	----	----	----	----
		4	0.07	21	0.6	79	2.1	163	4.4	254	6.8	471	12.6	678	18.2	777	20.8
20	1.4	4	0.28	20	0.5	74	2.0	153	4.1	237	6.4	445	11.9	642	17.2	735	19.7
		8	0.55	17	0.5	63	1.7	130	3.5	201	5.4	385	10.3	557	14.9	638	17.1
		12	0.83	12	0.3	44	1.2	91	2.4	140	3.8	----	----	----	----	----	----
30	2.1	1	0.07	27	0.7	102	2.7	207	5.5	328	8.8	577	15.5	827	22.1	948	25.4
		10	0.69	21	0.6	79	2.1	164	4.4	254	6.8	482	12.9	696	18.7	798	21.4
		15	1.0	16	0.4	60	1.6	125	3.4	192	5.1	371	9.9	538	14.4	616	16.5
40	2.8	17	1.2	13	0.3	48	1.3	99	2.7	153	4.1	----	----	----	----	----	----
		4 or less	0.28 or less	35	0.9	131	3.5	267	7.2	422	11.3	744	19.9	1066	28.6	1221	32.7
		15	1.0	29	0.8	108	2.9	223	6.0	345	9.2	651	17.5	940	25.2	1077	28.9
50	3.4	20	1.4	25	0.7	93	2.5	192	5.1	297	8.0	568	15.2	822	22.0	942	25.2
		25	1.7	18	0.5	69	1.8	144	3.9	221	5.9	429	11.5	622	16.7	713	19.1
		9 or less	0.62 or less	42	1.1	161	4.3	327	8.8	517	13.9	910	24.4	1304	34.9	1495	40.1
75	5.2	20	1.4	36	1.0	136	3.6	280	7.5	434	11.6	816	21.9	1178	31.6	1350	36.2
		30	2.1	28	0.8	105	2.8	217	5.8	335	9.0	644	17.3	933	25.0	1069	28.6
		35	2.4	21	0.6	77	2.1	161	4.3	247	6.6	480	12.9	697	18.7	798	21.4
100	6.9	13 or less	0.90 or less	50	1.3	190	5.1	386	10.3	611	16.4	1077	28.9	1542	41.3	1768	47.4
		20	1.4	45	1.2	172	4.6	354	9.5	551	14.8	1023	27.4	1473	39.5	1688	45.2
		30	2.1	40	1.1	152	4.1	313	8.4	485	13.0	919	24.6	1327	35.6	1521	40.8
125	8.6	40	2.8	31	0.8	115	3.1	240	6.4	369	9.9	712	19.1	1032	27.7	1182	31.7
		45	3.1	22	0.6	85	2.3	176	4.7	270	7.2	526	14.1	764	20.5	875	23.5
		24 or less	1.6 or less	69	1.8	264	7.1	536	14.4	847	22.7	1493	40.0	2138	57.3	2451	65.7
150	10.3	50	3.4	54	1.4	203	5.4	419	11.2	648	17.4	1232	33.0	1781	47.7	2041	54.7
		60	4.1	44	1.2	166	4.4	343	9.2	529	14.2	1019	27.3	1476	39.6	1692	45.3
		70	4.8	27	0.7	101	2.7	209	5.6	322	8.6	627	16.8	911	24.4	1044	28.0
175	12.1	35 or less	2.4 or less	89	2.4	337	9.0	685	18.4	1083	29.0	1909	51.2	2734	73.2	3134	84.0
		60	4.1	74	2.0	280	7.5	578	15.5	896	24.0	1689	45.3	2438	65.3	2794	74.9
		75	5.2	62	1.7	236	6.3	489	13.1	754	20.2	1444	38.7	2090	56.0	2396	64.2
200	13.8	46 or less	3.2 or less	108	2.9	411	11.0	834	22.4	1319	35.3	2325	62.3	3330	89.2	3817	102
		75	5.2	91	2.4	344	9.2	710	19.0	1101	29.5	2072	55.5	2990	80.1	3427	91.8
		57 or less	3.9 or less	127	3.4	484	13.0	984	26.4	1555	41.7	2741	73.5	3926	105	4500	121
250	17.2	75	5.2	115	3.1	436	11.7	897	24.0	1396	37.4	2593	69.5	3735	100	4281	115
		68 or less	4.7 or less	147	3.9	558	15.0	1133	30.4	1791	48.0	3157	84.6	4522	121	5183	139
		75 or less	5.2 or less	166	4.4	631	16.9	1282	34.4	2027	54.3	3573	95.8	5118	137	5866	157
300	20.7	75 or less	5.2 or less	205	5.5	779	20.9	1581	42.4	2500	67.0	4405	118	6310	169	7232	194
		244	6.5	926	24.8	1880	50.4	2972	79.6	5237	140	7502	201	8598	230		
		282	7.6	1073	28.8	2178	58.4	3444	92.3	6069	163	8694	234	9964	267		
350	24.1	75 or less	5.2 or less	321	8.6	1220	32.7	2477	66.4	3916	105	6901	185	9886	265	11,331	304
				400	27.6	400	11.3	1331	37.4	2644	70.4	4000	105	7150	201	8598	230






Figure 3. Dimensions

Table 10. Main Valve Dimension

BODY SIZE		DIMENSION																			
		A								D	G	R	Z				AR				
		NPT Cast Iron, CL600 RF, BWE or NPT Steel and Stainless steel		CL125 FF Cast Iron or CL150 RF Steel and Stainless steel		CL250 RF Cast Iron or CL300 RF Steel and Stainless steel		PN 16/25/40 Steel and Stainless steel					Cast Iron		Steel and Stainless steel						
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm		
1	25	8.25	210	7.25	184	7.75	197	7.62	194	3.88	99	8.62	219	4.06	103	12.00	305	13.75	349	3.00	76
2	50	11.25	286	10.00	254	10.50	267	10.19	259	4.56	116	9.12	232			13.31	338	15.06	383	3.12	79
3	80	13.25	337	11.75	298	12.50	317	11.81	300	5.31	135	11.31	287	5.06	129	16.50	419	18.25	464	3.88	99
4	100	15.50	394	13.88	353	14.50	368	13.56	344	6.56	167	12.69	322			19.12	486	21.12	536	5.12	130
6	150	20.00	508	17.75	451	18.62	473	17.48	444	8.06	205	13.62	346	8.00	203	20.25	514	23.25	591	6.62	168
8 x 6	200 x 150	24.0	610	21.4	544	22.4	569	----	9.76	248	15.02	382									
12 x 6	300 x 150	32.3	820	29.0	737	30.5	775		12.56	319	17.72	450									

Table 11. Actuator Dimension

TYPE AND ACTUATOR SIZE	DIMENSION										
	C (Diameter)		E		H		M				
	In.	mm	In.	mm	In.	mm	With Pilot Spring Case Vent		Without Pilot Spring Case Vent		
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1098 - 30		11.38	289	5.69	145	7.88	200	9.50	241	9.31	236
1098H - 30		11.38	289	6.06	154	7.88	200	9.50	241	9.31	236
1098 - 40		13.12	333	5.75	146	7.88	200	9.50	241	9.31	236
1098 - 70		21.12	536	7.44	189	14.19	360	15.81	402	15.62	397

Table 12. Shipping Weight

BODY SIZE		APPROXIMATE SHIPPING WEIGHT, LB / KG							
		Type 1098 Size 30 Actuator		Type 1098H Size 30 Actuator		Type 1098 Size 40 (Standard) Actuator		Type 1098 Size 70 Actuator	
NPS	DN	Lb	kg	Lb	kg	Lb	kg	Lb	kg
1	25	55	25	80	36	65	29	140	64
2	50	75	34	100	45	85	39	160	73
3	80	115	52	140	64	125	57	200	91
4	100	165	75	190	86	175	79	250	113
6	150	350	159	375	170	360	163	435	197
8 x 6	200 x 150	625	284	650	295	635	288	710	322
12 x 6	300 x 150	1102	500	1127	511	1112	504	1187	538

# Types 1098-EGR and 1098H-EGR

Pressure Reducing Regulators

FISHER™

## Ordering Guide

### Main Valve Body Size (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 x 6 / DN 200 x 150 (Not available in Cast Iron)\*\*
- NPS 12 x 6 / DN 300 x 150 (Not available in Cast Iron)\*\*

### Main Valve Body Material and End Connection Style (Select One)

#### Cast Iron Body

- 1 or 2 NPT only\*\*\*
- CL125 FF\*\*\*

#### WCC Steel Body

- 1 or 2 NPT only\*\*\*
- CL150 RF\*\*\*
- SWE (NPS 1 or 2 / DN 25 or 50 only)\*\*
- CL300 RF\*\*\*
- CL600 RF\*
- Sch 40 BWE
- PN 16/25/40\* (Not Available for NPS 8 x 6 or 12 x 6 / DN 200 x 150 or 300 x 150) Specify \_\_\_\_\_

#### CF8M Stainless steel

- NPT (1 or 2 NPT only)\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*
- SWE (NPS 1 or 2 / DN 25 or 50 only)\*\*
- Sch 40 BWE
- PN 16/25/40\* (Not Available for NPS 8 x 6 or 12 x 6 / DN 200 x 150 or 300 x 150) Specify \_\_\_\_\_

### Cage and Cage Material (Select One)

- Linear Cage, CF8M Stainless steel\*\*\*
- Whisper Trim™ Cage, 416 Stainless steel\*\*\*
- Whisper Trim Cage, 316 Stainless steel\*\*
- Quick Opening Cage, ENC Coated Cast Iron\*\*\*

### Main Valve Spring (Select One)

#### Maximum Differential and Spring Color

- 20 psi / 1.4 bar, Yellow\*\*
- 60 psi / 4.1 bar, Green\*\*\*
- 125 psi / 8.6 bar, Blue\*\*\*
- 400 psi / 27.6 bar, Red\*\*\*

### Spring Material (Select One)

- Steel\*\*\*
- Inconel® X-750

### Actuator Size (Select One)

- Type 1098 Size 70, maximum set pressure 50 psig / 3.4 bar
- Type 1098 Size 40, maximum set pressure 75 psig / 5.2 bar **(standard)**
- Type 1098 Size 30, maximum set pressure 100 psig / 6.9 bar
- Type 1098H Size 30H, maximum set pressure 350 psig / 24.1 bar

### Actuator and Bonnet Material (Select One)

- Steel casing with steel bonnet\*\*\*
- Stainless steel casing with stainless steel bonnet\*\*

### Body Flange Material (Select One)

- ENC Coated cast iron\*\*\*
- ENC Coated steel\*\*\*
- ENC Coated CF8M Stainless steel\*\*

### Valve Plug and Seat Ring (Select One)

- 416 Stainless steel\*\*\*
- 316 Stainless steel\*\*

### Diaphragms, O-rings and Other Elastomers (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*\*
- Ethylenepropylene (EPDM)\*\*

### Outlet Pressure Range (Select One)

#### Type 6351 Pilot

- 3 to 20 psig / 0.21 to 1.4 bar, Green\*\*
- 5 to 35 psig / 0.34 to 2.4 bar, Unpainted\*\*
- 35 to 100 psig / 2.4 to 6.9 bar, Red\*\*

#### Type 6352 Pilot

- 14 in. w.c. to 2 psig / 35 mbar to 0.14 bar, Yellow\*\*\*
- 2 to 10 psig / 0.14 to 0.69 bar, Black\*\*

#### Type 6353 Pilot

- 3 to 40 psig / 0.21 to 2.8 bar, Yellow\*\*
- 35 to 125 psig / 2.4 to 8.6 bar, Red\*\*

#### Type 6354L Pilot

- 85 to 200 psig / 5.9 to 13.8 bar\*\*

#### Type 6354M Pilot

- 175 to 220 psig / 12.1 to 15.2 bar\*\*

#### Type 6354H Pilot

- 200 to 300 psig / 13.8 to 20.7 bar\*\*

#### Type 61L, 61LD or 61LE Pilot; Specify Type \_\_\_\_\_

- 0.25 to 2 psig / 0.02 to 0.14 bar, Red\*\*
- 1 to 5 psig / 0.07 to 0.34 bar, Yellow\*\*
- 2 to 10 psig / 0.14 to 0.69 bar, Blue\*\*
- 5 to 15 psig / 0.34 to 1.0 bar, Brown\*\*
- 10 to 20 psig / 0.69 to 1.4 bar, Green\*\*

- continued -

Inconel® is a mark owned by Special Metals Corporation.



## Ordering Guide (continued)

Outlet Pressure Range (Select One) (continued)
<b>Type 61H Pilot</b> <input type="checkbox"/> 10 to 65 psig / 0.69 to 4.5 bar, Green Stripe**
<b>Type 61HP Pilot</b> <input type="checkbox"/> 15 to 45 psig / 1.0 to 3.1 bar, Yellow** <input type="checkbox"/> 35 to 100 psig / 2.4 to 6.9 bar, Blue** <input type="checkbox"/> 100 to 300 psig / 6.9 to 20.7 bar, Red**
<b>Type Y600AM</b> <input type="checkbox"/> 4 to 8 in. w.c. / 10 to 20 mbar, Red*** <input type="checkbox"/> 7 to 16 in. w.c. / 17 to 40 mbar, Unpainted** <input type="checkbox"/> 15 in. w.c. to 1.2 psig / 37 mbar to 0.08 bar, Yellow*** <input type="checkbox"/> 1.2 to 2.5 psig / 0.08 to 0.17 bar, Green*** <input type="checkbox"/> 2.5 to 4.5 psig / 0.17 to 0.31 bar, Light Blue*** <input type="checkbox"/> 4.5 to 7 psig / 0.31 to 0.48 bar, Black***

Liquid Service
<input type="checkbox"/> Low gain restriction

6350 Series Pilot Construction (Select One)
<input type="checkbox"/> Aluminum***
<input type="checkbox"/> Stainless steel**

Tubing and Fittings (Optional)
<input type="checkbox"/> Stainless steel tubing and steel plated fittings***
<input type="checkbox"/> Stainless steel tubing and fittings**

Main Valve Replacement Parts Kit (Optional)
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Actuator Replacement Parts Kit (Optional)
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.

Pilot Replacement Parts Kit (Optional)
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.

Wireless Position Monitor Mounting Kit (Optional)
<input type="checkbox"/> Yes, send one mounting kit for mounting the Topworx™ 4310 or the Fisher™ 4320 wireless position monitor.

NACE Construction (Optional)
<input type="checkbox"/> Yes

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**  
 Do not place control lines immediately downstream of rotary or turbine meters.

# 1301 Series

## High-Pressure Regulator

FISHER™

### Introduction

The proven reliability and accurate regulation of the 1301 Series regulators make them ideal for numerous high-pressure drop applications. These multi-purpose regulators can be used as pilot supply or pressure-loading regulators where high-pressure operating medium must be reduced for use by gas regulator pilots or pressure-loaded regulators. Their rugged design offers versatility for a wide variety of applications including air, gas, water and other liquids.

### Body Size and End Connection Style

1/4 NPT

### Spring Case Vents

#### Type 1301F Brass Spring Case:

Four 5/32 in. / 4.0 mm holes

#### Type 1301F Stainless Steel Spring Case:

One 1/4 NPT connection

**Type 1301G:** One 1/8 NPT connection with screen

### Pressure Registration

Internal

### Maximum Inlet Pressure

6000 psig / 414 bar at or below 200°F / 93°C and 1000 psig / 69.0 bar above 200°F / 93°C

### Maximum Emergency Outlet Pressures

**Type 1301F:** 250 psig / 17.2 bar

**Type 1301G:** 550 psig / 37.9 bar

### Outlet Pressure Ranges

10 to 500 psig / 0.69 to 34.5 bar in four ranges

See Table 2

### Material Temperature Capabilities

**Nylon (PA) Valve Disk and Neoprene (CR)**

**Gaskets:** -20 to 180°F / -29 to 82°C

**PTFE Valve Disk and Fluorocarbon (FKM)**

**Gaskets:** -20 to 400°F / -29 to 204°C not recommended for hot water use

**PTFE Valve Disk and Ethylenepropylene (EPDM) Gaskets:** -40 to 300°F / -40 to 149°C

### Flow Coefficients

**Wide-Open  $C_g$ :** 5.0

**Wide-Open  $C_v$ :** 0.13

$C_1$ : 38.5

$C_v$  Coefficients at 20% Droop

Type 1301F: See Table 5

Type 1301G: See Table 6

### IEC Sizing Coefficients

$X_T$ : 0.938

$F_D$ : 0.50

$F_L$ : 0.85

### Options

- Pipe plug in second outlet
- Handwheel adjusting screw (Type 1301F only)
- Panel mounting spring case with T-handle adjusting screw (Type 1301G only)
- Bracket for mounting regulator on yoke of control valve actuator
- NACE construction
- Stainless steel construction

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)




12/13

### Features

- Durable Stainless Steel Diaphragm
- Spare Valve Disk Provided
- Versatility
- ANSI Class VI Shutoff
- Sour Gas Service Capability



Figure 1. Type 1301F High Pressure Regulator



W0603

INLET PRESSURE

OUTLET PRESSURE

ATMOSPHERIC PRESSURE

Figure 2. Type 1301F Operational Schematic

**Table 1. Construction Materials**

BODY	BOTTOM CAP AND SPRING CASE	ORIFICE	ORIFICE YOKE	GASKET	VALVE SPRING	VALVE DISKS AND HOLDER	DIAPHRAGM
Brass	Brass	303 Stainless steel	Brass	Neoprene, Fluorocarbon (FKM) or Ethylenepropylene (EPDM)	302 Stainless steel	Nylon (PA) and Zinc-plated brass or PTFE and Zinc-plated brass	302 Stainless steel
CF8M Stainless steel	304 Stainless steel 316 Stainless steel	303 Stainless steel	316 Stainless steel	Neoprene, Fluorocarbon (FKM) or Ethylenepropylene (EPDM)	302 SST or Inconel®	Nylon (PA) and 316 Stainless steel or PTFE and 316 Stainless steel	302 Stainless steel or Monel®

**Table 2. Outlet Pressure Ranges**

TYPE	OUTLET PRESSURE RANGE <sup>(1)</sup>		SPRING PART NUMBER	SPRING COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	psig	bar			In.	mm	In.	mm
1301F	10 to 75	0.69 to 5.2	1D387227022	Blue	0.200	5.08	1.69	42.9
	50 to 150	3.4 to 10.3	1B788527022	Silver	0.225	5.72		
	100 to 225	6.9 to 15.5	1D465127142	Red	0.243	6.17		
1301G	200 to 500	13.8 to 34.5	1K156027142	Silver	0.331	8.41	1.88	47.8

1. All springs can be backed off to 0 psig / 0 bar.

**Table 3. Type 1301F Regulating Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
			Inlet Pressure, psig / bar													
			100 / 6.9		250 / 17.2		500 / 34.5		750 / 52		1000 / 69		1500 / 103		2000 / 138	
			Droop		Droop		Droop		Droop		Droop		Droop		Droop	
psig	bar	10%	20%	10%	20%	10%	20%	10%	20%	10%	20%	10%	20%	10%	20%	
10 to 75 psig / 0.69 to 5.2 bar 1D387227022 Blue	25	1.7	245 / 6.6	374 / 10.0	387 / 10.4	619 / 16.6	516 / 13.8	839 / 22.5	645 / 17.3	968 / 25.9	671 / 18.0	993 / 26.6	697 / 18.7	1032 / 27.7	722 / 19.3	1058 / 28.4
	50	3.4	361 / 9.7	516 / 13.8	619 / 16.6	1032 / 27.7	929 / 24.9	1290 / 34.6	1084 / 29.1	1548 / 41.5	1161 / 31.1	1677 / 44.9	1226 / 32.9	1806 / 48.4	1290 / 34.6	1935 / 51.9
	75	5.2	323 / 8.7	516 / 13.8	774 / 20.7	1161 / 31.1	1161 / 31.1	1806 / 48.4	1290 / 34.6	2064 / 55.3	1419 / 38.0	2193 / 58.8	1548 / 41.5	2322 / 62.2	1677 / 44.9	2451 / 65.7
50 to 150 psig / 3.4 to 10.3 bar 1B788527022 Silver	75	5.2	258 / 6.9	452 / 12.1	645 / 17.3	1032 / 27.7	1032 / 27.7	1677 / 44.9	1226 / 32.9	1935 / 51.9	1290 / 34.6	2064 / 55.3	1419 / 38.0	2193 / 58.8	1548 / 41.5	2322 / 62.2
	150	10.3	----	----	968 / 25.9	1290 / 34.6	1419 / 38.0	2322 / 62.2	1871 / 50.1	2967 / 79.5	2064 / 55.3	3354 / 89.9	2193 / 58.8	3612 / 96.8	2322 / 62.2	3870 / 104
100 to 225 psig / 6.9 to 15.5 bar 1D465127142 Red	150	10.3	----	----	839 / 22.5	1161 / 31.1	1290 / 34.6	2193 / 58.8	1742 / 46.7	2838 / 76.1	1935 / 51.9	2903 / 77.8	2129 / 57.1	3548 / 95.1	2322 / 62.2	3870 / 104
	225	15.5	----	----	645 / 17.3	1032 / 27.7	1806 / 48.4	2709 / 72.6	2451 / 65.7	3741 / 100	3096 / 83.0	4515 / 121	3483 / 93.3	5160 / 138	3870 / 104	5805 / 156

**Table 4. Type 1301G Regulating Capacities**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	OUTLET PRESSURE SETTING		OFFSET		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS										
					Inlet Pressure, psig / bar										
					300 / 20.7	500 / 34.5	750 / 52	1000 / 69	1500 / 103	2000 / 138	2250 / 155				
psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
200 to 500 psig / 13.8 to 34.5 bar 1K156027142 Silver	200	13.8	10	0.69	452 / 12.1	710 / 19.0	968 / 25.9	1226 / 32.9	1419 / 38.0	1613 / 43.2	1806 / 48.4				
			20	1.4	839 / 22.5	1161 / 31.1	1548 / 41.5	1935 / 51.9	2322 / 62.2	2580 / 69.1	2709 / 72.6				
			30	2.1	1161 / 31.1	1742 / 46.7	2193 / 58.8	2580 / 69.1	2967 / 79.5	3483 / 93.3	3870 / 104				
			40	2.8	1419 / 38.0	2129 / 57.1	2709 / 72.6	3225 / 86.4	3870 / 104	4515 / 121	4773 / 128				
500	34.5	15	1.0	----	----	1032 / 27.7	1290 / 34.6	1677 / 44.9	1935 / 51.9	2064 / 55.3					
		25	1.7	----	----	1806 / 48.4	2064 / 55.3	2580 / 69.1	3354 / 89.9	3612 / 96.8					
		50	3.4	----	----	2838 / 76.1	3612 / 96.8	4257 / 114	5160 / 138	5808 / 156					

**Table 5. Type 1301F C<sub>v</sub> Coefficients**

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR, psig / bar	OUTLET PRESSURE SETTING		TYPE 1301F C <sub>v</sub> COEFFICIENT BASED ON 20% DROOP								
			Inlet Pressure, psig / bar								
			100 / 6.90	250 / 17.2	500 / 34.5	750 / 51.7	1000 / 69.0	1500 / 103	2000 / 138		
psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
10 to 75 / 0.69 to 5.17 1D387227022 Blue	25	1.7	0.056	0.048	0.043	0.040	0.037	0.032	0.029		
	50	3.4	0.065	0.057	0.052	0.050	0.046	0.041	0.038		
	75	5.2	0.073	0.066	0.061	0.058	0.055	0.051	0.049		
50 to 150 / 3.45 to 10.3 1B788527022 Silver	75	5.2	0.068	0.064	0.059	0.057	0.054	0.050	0.047		
	150	10.3	----	0.089	0.084	0.080	0.078	0.075	0.074		
100 to 225 / 6.90 to 15.5 1D4651270142 Red	150	10.3	----	0.083	0.080	0.078	0.076	0.074	0.074		
	225	15.5	----	0.100	0.097	0.095	0.094	0.092	0.091		

# 1301 Series

## High-Pressure Regulator

FISHER™




Figure 3. 1301 Series Dimensions

Table 6. Type 1301G C<sub>v</sub> Coefficients

OUTLET PRESSURE RANGE, SPRING PART NUMBER AND COLOR, psig / bar	OUTLET PRESSURE SETTING		TYPE 1301G C <sub>v</sub> COEFFICIENT BASED ON 20% DROOP						
			Inlet Pressure, psig / bar						
	psig	bar	300 / 20.7	500 / 34.5	750 / 51.7	1000 / 69.0	1500 / 103	2000 / 138	2250 / 155
200 to 500 / 13.8 to 34.5 1K156027142 Silver	200	13.8	0.095	0.094	0.092	0.091	0.089	0.088	0.088
	500	34.5	----	----	0.106	0.105	0.104	0.103	0.103

Table 7. Dimension

TYPE	BODY MATERIAL	DIMENSION			
		A		B	
		In.	mm	In.	mm
1301F	Brass	3.38	86	1.69	43
	Stainless steel	3.62	92	1.75	44
1301G	Brass	3.38	86	1.69	43
	Stainless steel	3.62	92	1.75	44





## Ordering Guide

Type (Select One)	
<b>1301F</b>	<input type="checkbox"/> 10 to 75 psig / 0.69 to 5.2 bar, Blue*** <input type="checkbox"/> 50 to 150 psig / 3.4 to 10.3 bar, Silver*** <input type="checkbox"/> 100 to 225 psig / 6.9 to 15.5 bar, Red***
<b>1301G</b>	<input type="checkbox"/> 200 to 500 psig / 13.8 to 34.5 bar, Silver***

Dual Gauge Port Construction (Optional)	
<input type="checkbox"/> Yes	

Body and Spring Case Material (Select One)	
<input type="checkbox"/> Brass*** <input type="checkbox"/> CF8M Stainless steel**	

Valve Disk (Select One)	
<input type="checkbox"/> Nylon (PA) (standard)*** <input type="checkbox"/> PTFE**	

Gasket (Select One)	
<input type="checkbox"/> Neoprene (CR)*** <input type="checkbox"/> Fluorocarbon (FKM)** <input type="checkbox"/> Ethylenepropylene (EPDM)** <input type="checkbox"/> Fluorosilicone (FVMQ)**	

Replacement Parts Kit (Optional)	
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.	

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No	
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

A disk with a cookie cut appearance probably means you had an overpressure situation. Thus, investigate further.

# 1805 Series

## Relief Valve

FISHER™

### Introduction

The 1805 Series relief valves are designed for use in farm-tap applications where a relief valve is needed between the first and second-stage regulators. This relief valve is suitable for natural gas, air, propane or any medium compatible with the internal valve parts.

### Body Size and End Connection Style

3/4, 1, 1-1/2 or 2 NPT

### Flow Coefficients

C<sub>1</sub>: 35

### IEC Sizing Coefficients

#### 3/4 to 1 NPT Bodies:

X<sub>T</sub>: 0.73; F<sub>D</sub>: 0.39; F<sub>L</sub>: 0.89

1-1/2 to 2 NPT Bodies:

X<sub>T</sub>: 0.94; F<sub>D</sub>: 0.44; F<sub>L</sub>: 0.89

### Maximum Relief (Inlet) Pressure

150 psig / 10.3 bar, including build-up

### Relief Set Pressure Ranges

5 to 125 psig / 0.34 to 8.6 bar in three ranges for each body size  
See Table 3

### Temperature Capabilities

-20 to 150°F / -29 to 66°C

### Approximate Shipping Weights

3/4 to 1 NPT Bodies: 5 lbs / 2.3 kg

1-1/2 to 2 NPT Bodies: 13 lbs / 5.9 kg

### Options

- Cast iron spring case
- Cast iron spring case with closing cap and 1/4 NPT vent placed over adjusting screw

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/11

### Features

- Tight Shutoff
- Easy Maintenance
- Simple Adjustment
- Complete Venting
- Sour Gas Service Capability




Figure 1. Typical 1805 Series Relief Valves






Figure 2. Typical 1805 Series Operational Schematic



TYPE 1805-2, 1805-3 OR 1805-7 WITH CLOSING CAP



TYPE 1805-4 OR 1805-5 WITHOUT CLOSING CAP

Figure 3. Dimensions

Table 1. Type Number Description		
TYPE	SIZE	DISTINCTIVE CONSTRUCTION FEATURE
1805-2	3/4 or 1 NPT	Cast iron spring case, closing cap with 1/4 NPT vent placed over the adjusting screw
1805-3	1-1/2 or 2 NPT	Cast iron spring case, closing cap with 1/4 NPT vent placed over the adjusting screw
1805-4	3/4 or 1 NPT	Cast iron spring case
1805-5	1-1/2 or 2 NPT	Cast iron spring case
1805-7	3/4 or 1 NPT	Cast iron spring case, closing cap with 1/4 NPT vent placed over the adjusting screw and screen in outlet

Table 2. Construction Material			
BODY MATERIAL	UPPER SPRING SEAT	DIAPHRAGM AND O-RING	O-RING HOLDER AND VALVE GUIDE ORIFICE
Cast Iron (all sizes), Ductile Iron (3/4 or 1 NPT body) (NACE)	Plated Steel	Nitrile (NBR)	Aluminum

Table 3. Relief Set Pressure Range								
BODY SIZE	RELIEF PRESSURE RANGE		SPRING PART NUMBER	COLOR CODE	SPRING FREE LENGTH		SPRING WIRE DIAMETER	
	psig	bar			In.	mm	In.	mm
3/4 or 1 NPT	5 to 35	0.34 to 2.4	1B986027212	Green	2.25	57.2	0.12	3.05
	10 to 60	0.69 to 4.1	1B788327022	Silver	2.13	54.1	0.14	3.56
	20 to 125	1.4 to 8.6	1B788427022	Blue	1.94	49.3	0.18	4.57
1-1/2 or 2 NPT	5 to 20	0.34 to 1.4	1D892327022	Red	2.94	74.7	0.17	4.32
	10 to 50	0.69 to 3.4	1D665927022	Blue	2.50	63.5	0.22	5.59
	35 to 125	2.4 to 8.6	1E543627142	Yellow	2.31	58.7	0.28	7.11


Table 4. Dimension										
TYPE	BODY SIZE AND END CONNECTION STYLE	MATERIAL	DIMENSION							
			A		B		C		D (max)	
			In.	mm	In.	mm	In.	mm	In.	mm
1805-2 <sup>(1)</sup> , 1805-4 and 1805-7 <sup>(1)</sup>	3/4 NPT	Cast iron	3.62	92	1.81	46	1.00	25	6.44	164
		Ductile iron	3.88	99	1.94	49	1.38	35	6.44	164
	1 NPT	Cast iron	3.62	92	1.81	46	1.00	25	6.44	164
		Ductile iron	3.88	98	1.94	49	1.38	35	6.44	164
1805-3 <sup>(1)</sup> and 1805-5	1-1/2 NPT	Cast iron	5.88	149	2.94	75	1.69	43	9.12	232
	2 NPT	Cast iron	5.88	149	2.94	75	1.69	43	9.12	232

1. With closing cap.

# 1805 Series

## Relief Valve

FISHER™



- 0.6 SPECIFIC GRAVITY NATURAL GAS FLOW RATE-THOUSAND SCFH (AT 60°F AND 14.7 psia) AND Nm<sup>3</sup>/h (AT 0°C AND 1.01 bar).
- MAXIMUM PRESSURE INCLUDING BUILD-UP 150 psi / 10.3 bar AT 150°F / 66°C.
- SETPOINT IS TO BE INTERPRETED AS BUBBLE POINT.

Figure 4. Capacity Curves

## Ordering Guide

Type (Refer to Table 2 for Construction Features) (Select One)
<input type="checkbox"/> 1805-2***
<input type="checkbox"/> 1805-3***
<input type="checkbox"/> 1805-4**
<input type="checkbox"/> 1805-5***
<input type="checkbox"/> 1805-7***

Body Size and End Connection Style (Select One)
<input type="checkbox"/> 3/4 NPT***
<input type="checkbox"/> 1 NPT***
<input type="checkbox"/> 1-1/2 NPT**
<input type="checkbox"/> 2 NPT***

Body Material (Select One)
<input type="checkbox"/> Cast Iron (All sizes)**
<input type="checkbox"/> Ductile Iron (3/4 or 1 NPT body only)**

Relief Set Pressure Range (Select One)
<b>3/4 or 1 NPT Body</b>
<input type="checkbox"/> 5 to 35 psig / 0.34 to 2.4 bar, Green***
<input type="checkbox"/> 10 to 60 psig / 0.69 to 4.1 bar, Silver***
<input type="checkbox"/> 20 to 125 psig / 1.4 to 8.6 bar, Blue***

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Relief Set Pressure Range (Select One) (continued)
<b>1-1/2 or 2 NPT Body</b>
<input type="checkbox"/> 5 to 20 psig / 0.34 to 1.4 bar, Red***
<input type="checkbox"/> 10 to 50 psig / 0.69 to 3.4 bar, Blue***
<input type="checkbox"/> 35 to 125 psig / 2.4 to 8.6 bar, Yellow***

Replacement Parts Kit (Optional)
<input type="checkbox"/> Yes, send me one replacement parts kit to match this order.

Specification Worksheet
<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Adequate overpressure protection should be installed to protect the regulator from overpressure. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure.

# Type 1805P

## Pilot-Operated Relief Valve

FISHER™

### Introduction

Type 1805P Relief Valve is an accurate, economical, pilot-operated relief valve consisting of a Type 1805, 2 NPT main valve and a Type 6358B pilot. The relief pressure setting can be adjusted by rotating the pilot spring adjustment screw.

### Body Size and End Connection Style

2 NPT

### Wide-Open Flow Coefficients

$C_g$ : 900 (without outlet piping)

$C_v$ : 23.7

$C_1$ : 38

### IEC Sizing Coefficients

$X_T$ : 0.91

$F_D$ : 0.44

$F_L$ : 0.89

### Maximum Relief (Inlet) Pressures

50 psig / 3.4 bar over relief pressure setting or 150 psig / 10.3 bar, whichever is lower

### Relief Set Pressure Ranges

10 to 100 psig / 0.69 to 6.9 bar in three ranges

See Table 3

### Pressure Registration

External

### Pilot Control Line and Vent Connection

1/4 NPT

### Temperature Capabilities

**Nitrile (NBR):** -20 to 180°F / -29 to 82°C

**Fluorocarbon (FKM):** 0 to 300°F / -18 to 149°C

### Approximate Shipping Weight

13 lbs / 6 kg

### Features

- Fast Reseat After Operation
- Economical
- Accurate
- High Flow Capacity
- Low Build-Ups to Reach Wide-Open
- Tight Shutoff
- Rugged Construction
- Full Usable Capacity
- Powder Paint Coating



Figure 1. Type 1805P Pilot-Operated Relief Valve






Figure 2. Type 1805P Operational Schematic

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

07/09




Figure 3. Type 1805P-6358B Dimensions

Table 1. Main Valve Construction Material

BODY AND SPRING CASE	DIAPHRAGM, O-RING AND GASKET	VALVE GUIDE, ORIFICE AND O-RING HOLDER	DIAPHRAGM PLATE	SPRING	SPRING SEAT AND CAP SCREW
Cast iron	Nitrile (NBR) (standard) or Fluorocarbon (FKM) (high temperature)	Aluminum	Brass	Plated Steel	Steel

Table 2. Pilot Construction Material

BODY AND SPRING CASE	VALVE PLUG AND STEM	DIAPHRAGM	O-RING AND GASKET	STEM GUIDE	VALVE SPRING	PILOT SPRING	BODY PLUG
Aluminum	Nitrile (NBR) (standard) or Fluorocarbon (FKM) (high temperature) plug and Stainless steel stem	Nitrile (NBR) (standard) or Fluorocarbon (FKM) (high temperature)	Nitrile (NBR) (standard) or Fluorocarbon (FKM) (high temperature)	Stainless steel	Stainless steel	Steel	Stainless steel

Table 3. Type 6358B Set Pressure Range

RELIEF SET PRESSURE		PART NUMBER	COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
psig	bar			In.	mm	In.	mm
10 to 18	0.69 to 1.2	1B986027212	Green	0.120	3.05	2.12	53.8
18 to 30	1.2 to 2.1	1B788327022	Unpainted	0.142	3.61	2.12	53.8
30 to 100	2.1 to 6.9	1K748527202	Red	0.192	4.88	2.19	55.6

Table 4. Main Valve Capacities and Pilot Information

MAIN VALVE SPRING, PART NUMBER AND COLOR	RELIEF SET PRESSURE RANGE		SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE TO RESEAT PILOT		CAPACITIES OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(4)</sup>	
	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h
For set pressures up to 30 psig / 2.1 bar 1F826927052 Pink	10 to 8	0.69 to 1.2	10	0.69	0.8	0.06	1.1	0.08	1.0	0.69	26,000	697
			15	1.0							32,000	858
			18	1.2							36,000	965
	18 to 30	1.2 to 2.1	18	1.2	0.9	0.06	1.3	0.09			37,000	992
For set pressures over 30 psig / 2.1 bar 1D751527022 Unpainted	30 to 100	2.1 to 6.9	25	1.7	1.5	0.10	2.2	0.15	45,000	1206		
			30	2.1					53,000	1420		
			40	2.8					54,000	1447		
			50	3.4					66,000	1769		
	30 to 100	2.1 to 6.9	2.1 to 6.9	60	4.1	1.7	0.12	2.5	0.17	78,000	2090	
				60	4.1					89,000	2385	
				70	4.8					101,000	2707	
				80	5.5					113,000	3028	
30 to 100	2.1 to 6.9	2.1 to 6.9	90	6.2	2.0	0.14	2.5	0.17	124,000	3323		
			90	6.2					136,000	3645		
			100	6.9								
			100	6.9								

1. Set pressure is defined as the pressure at which the pilot exhaust starts-to-bubble (discharge).  
 2. Crack pressure is the inlet pressure at which the main valve starts audible flow.  
 3. Inlet pressure buildup over the set pressure to achieve wide-open capacity.  
 4. Capacities with inlet piping equal to body size and without outlet piping.

# Type 1805P

Pilot-Operated Relief Valve

FISHER™

## Ordering Guide

### Main Valve Diaphragm Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

### Main Valve O-ring Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

### Relief Set Pressure Range (Select One)

- 10 to 18 psig / 0.69 to 1.2 bar, Green\*\*\*
- 18 to 30 psig / 1.2 to 2.1 bar, Unpainted\*\*\*
- 30 to 100 psig / 2.1 to 6.9 bar, Red\*\*\*

### Pilot Diaphragm Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

### Pilot Valve Plug Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

### Pilot Gasket Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Tubing and Fittings (Select One)

- Stainless steel tubing and steel plated fittings\*\*\*
- Stainless steel tubing and stainless steel fittings\*\*\*

### Main Valve Replacement Parts Kit (Optional)

- Yes, send one parts kit to match this order.

### Pilot Replacement Parts Kit (Optional)

- Yes, send one parts kit to match this order.

### Specification Worksheet

<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Keep vents open. Do not use small diameter, long vent lines. Use the rule of thumb of the next nominal pipe size every 10 feet / 3.1 m of vent line and 3 feet / 0.9 m of vent line for every elbow in the line.



### Introduction

Types 1808 globe-style and 1808A angle-style pilot-operated backpressure regulators or relief valves are economical, compact devices used in gas or liquid service to maintain pressure on oil and gas separators and in pressure relief applications in gas distribution systems.

### Body Size and End Connection Style

2 NPT

### Available Configurations

Type 6358 for Backpressure Applications  
Type 6358B for Relief Applications

### Maximum Differential Pressures

125 psig / 8.6 bar

### Relief Set Pressure Range

See Table 3

### Flow and Sizing Coefficients

See Table 4

### Maximum Relief (Inlet) Pressure<sup>(1)</sup>

150 psig / 10.3 bar, including build-up

### Temperature Capabilities

-20 to 180°F / -29 to 82°C

### Pressure Registration

Internal (**standard**) or External (optional)

### Pilot Tubing and Connections

1/4 NPT with or without P590 Series filter

### Approximate Shipping Weights

**Type 1808:** 22 lbs / 10 kg  
**Type 1808A:** 25 lbs / 11 kg

### Options

- Upstream control line construction
- Pressure gauge (0 to 160 psig / 0 to 11 bar)
- P590 Series Pilot Supply Filter

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/17



W3716\_1

Figure 1. Type 1808 Relief Valve/Backpressure Regulator with P590 Series Filter



W3507\_1

Figure 2. Type 1808A without Filter

### Features

- Product Longevity
- Simple, In-line Field Maintenance
- Simple, Reliable Design
- Compact and Lightweight
- Versatility in Both Liquid and Gas Service
- Minimize Field Interference Fits and Complicated Piping
- Optional Upstream Registration for Reduced Buildup
- Self-Draining Body

Table 1. Main Valve Construction Material

BODY	DIAPHRAGM PLATE AND CASING	DIAPHRAGM	O-RING	GASKET	BACKUP RING	SPRING	VALVE PLUG GUIDE	TUBING AND FITTING
<b>Type 1808:</b> Cast iron or WCC Steel <b>Type 1808A:</b> Cast iron	Zinc-plated steel	Neoprene (CR) and Nitrile (NBR)	Nitrile (NBR)	Nitrile (NBR)	Polytetrafluoroethylene (PTFE)	Zinc-plated steel ( <b>standard</b> )	Stainless steel	Stainless steel

Table 2. 6358 Series Pilots Construction Material

BODY	BODY PLUG	SPRING CASE	VALVE PLUG	SPRING AND SPRING SEAT	DIAPHRAGM AND O-RING	STEM GUIDE	ADJUSTING SCREW	CLOSING CAP	CONNECTOR CAP
Aluminum or CF8M Stainless steel	Aluminum, Stainless steel or Brass	Aluminum or Stainless steel	Nitrile (NBR) or thermoplastic plug with Stainless steel stem	Zinc-plated steel	Nitrile (NBR) or Fluorocarbon (FKM)	Stainless steel	Zinc-plated steel	Plastic or Stainless steel	Stainless steel

1. The pressure or temperature limits in this Application Guide and any applicable standard or code limitations should not be exceeded.

# 1808 Series

Relief Valves/Backpressure Regulators

FISHER™




Figure 3. Type 1808 with 6358 Series Operational Schematic

Table 3. Relief Set Pressure Range

RELIEF SET PRESSURE RANGE		PART NUMBER	COLOR	WIRE DIAMETER		FREE LENGTH	
psig	bar			In.	mm	In.	mm
3 to 18	0.21 to 1.2	1B986027212	Green	0.120	3.05	2.12	54.0
15 to 40	1.0 to 2.8	1E392527022	Yellow	0.148	3.76	2.00	51.0
35 to 125	2.4 to 8.6	1K748527202	Red	0.192	4.88	2.19	55.6

Table 4. Flow and Sizing Coefficients

TYPE	FLOW COEFFICIENT (WIDE-OPEN)		C <sub>1</sub>	C <sub>1</sub>	IEC SIZING COEFFICIENT		
	C <sub>g</sub>	C <sub>v</sub>			X <sub>r</sub>	F <sub>L</sub>	F <sub>o</sub>
1808	1410	40.1	35.2	0.79	0.78	0.89	0.50
1808A	1800	51.4	35.0	0.76		0.87	






Figure 4a. Capacities for the Type 1808 Using Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction




Figure 4b. Capacities for the Type 1808A Using Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction





Figure 4c. Capacities for the Type 1808 Using Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction




Note: Capacities based on 0 psig / 0 bar outlet pressure. If outlet pressure is not 0 psig / 0 bar, shaded capacities may be recalculated using the wide-open  $C_v$  and the desired pressure drop.

Figure 4d. Capacities for the Type 1808A Using a Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction


# 1808 Series

## Relief Valves/Backpressure Regulators



Note: Capacities based on 0 psig / 0 bar outlet pressure. If outlet pressure is not 0 psig / 0 bar, shaded capacities may be recalculated using the wide-open Cg and the desired pressure drop.

**Figure 4e.** Capacities for the Type 1808 Using Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction



Note: Capacities based on 0 psig / 0 bar outlet pressure. If outlet pressure is not 0 psig / 0 bar, shaded capacities may be recalculated using the wide-open Cg and the desired pressure drop.

**Figure 4f.** Capacities for the Type 1808A Using Standard Internal Control Line and a Type 6358 or 6358B Pilot with High-Gain Restriction






Figure 5. Dimensions

Table 5. Capacities for Type 1808 Using Optional External Control Line and Type 6358B Pilot with High-Gain Restriction

SET PRESSURE RANGE		SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE TO RESEAT PILOT		CAPACITIES OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(4)(5)</sup>	
psig	bar	psig	bar	psig	bar	psig	bar	psi	bar	SCFH	Nm <sup>3</sup> /h
3 to 18	0.21 to 1.2	3	0.21	0.9	0.06	6.0	0.41	1.0	0.07	37,000	992
		5	0.35	0.7	0.05	4.0	0.28			37,000	992
		10	0.69	0.7	0.05	1.2	0.08			42,000	1126
		15	1.0	0.7	0.05	1.0	0.07			52,000	1394
15 to 40	1.0 to 2.8	15	1.0	0.8	0.05	1.1	0.08			53,000	1420
		20	1.4							63,000	1688
		30	2.1							82,000	2198
		40	2.8							101,000	2707
35 to 125	2.4 to 8.6	40	2.8	1.4	0.09	1.9	0.13			102,000	2734
		50	3.5							121,000	3243
		60	4.1							139,000	3725
		70	4.8							157,000	4208
		80	5.5	1.6	0.11	2.2	0.15	176,000	4717		
		90	6.2					194,000	5199		
		100	6.9					213,000	5708		
		110	7.6					231,000	6191		
		125	8.6					258,000	6914		

1. Set pressure is defined as the pressure at which the pilot exhaust starts-to-bubble (discharge).
2. Crack pressure is the inlet pressure at which the main valve starts audible flow.
3. Inlet pressure build-up over the set pressure to achieve wide-open capacity.
4. Capacities with inlet piping equal to body size and without outlet piping.
5. If capacities are desired for the Type 1808A, multiply by 1.27.

# 1808 Series

Relief Valves/Backpressure Regulators



## Ordering Guide

### Type (Select One)

- 1808 (globe body)\*\*\*
- 1808A (angle body)\*\*

### Body Material (Select One)

- Cast iron\*\*\*
- WCC Steel (Type 1808 only)\*

### Pilot (Select One)

- Type 6358 (for backpressure application)\*\*\*
- Type 6358b (for relief application)\*\*\*

### Set Pressure (Select One)

- 3 to 18 psig / 0.21 to 1.2 bar, Green\*\*\*
- 15 to 40 psig / 1.0 to 2.8 bar, Yellow\*\*\*
- 35 to 125 psig / 2.4 to 8.6 bar, Red\*\*\*

### O-ring Material (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*

### Tubing and Fittings (Select One)

- Stainless steel tubing and steel fittings\*\*\*
- Stainless steel tubing and stainless steel fittings\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Upstream Control Line Construction (Optional)

- Yes

### Gauge (Optional)

- Yes

### Pilot Supply Filter (Optional)

- Yes

### Main Valve Parts Kit (Optional)

- Yes, please send one parts kit to match this order.

### Pilot Parts Kit (Optional)

- Yes, please send one parts kit to match this order.

### Specification Worksheet

<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Vents should be pointed down to help avoid the accumulation of water condensation or other materials in the spring case.



### Introduction

A/100 Series regulators ensure precise stable operation even when the requirements of the plant cause exceptionally unfavorable condition such as rapid fluctuations in demand.

These regulators are commonly used on industrial burners, with starting controlled by solenoid valves (on-off).

### Configurations

**Types A/102 and A/102-AP:**  
without slam-shut valve  
**Types A/109 and A/109-AP:**  
with slam-shut valve

### Body Allowable Pressure

Up to 290 psig / 20.0 bar

### Highest Operating Pressure

4.35 psig / 300 mbar

### Maximum Inlet Pressure

116 psig / 8.0 bar

### Inlet Pressure Range

1.45 to 116 psig / 0.1 to 8 bar

### Set Range

0.14 to 4.35 psig / 10 to 300 mbar

### Accuracy Class

Up to ±5%

### Lock-up Pressure Class

Up to 10%

### Maximum Flow Rate

Up to 21,189 SCFH / 600 Sm<sup>3</sup>/h

### Built-in Slam-Shut Valve Independent Pneumatic Control

**Accuracy Class:** ±5%  
**Response Time:** ≤ 1 second

### Orifice

1/2, 5/8, 3/4 and 1 in. /  
13, 16, 19 and 25 mm

### Threaded Connections

2 in. BSP Inlet and Outlet

### Operating Temperature

**Standard version:**  
14 to 140°F / -10 to 60°C  
**Low-temperature version:**  
-4 to 140°F / -20 to 60°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Built-in Relief Valve
- Overpressure and Underpressure Slam-Shut Valve
- Manual Reset
- Inlet and Outlet In-Line




Figure 1. Type A/102 Spring-Loaded Regulator

Figure 2. Type A/109-AP Spring-Loaded Regulator





Figure 3. A/100 Series Dimensions

# A/100 Series

## Spring-Loaded Regulator

TARTARINI



IN. /  
mm

\* IN HIGH PRESSURE VERSIONS (AP), THIS DIMENSION MUST BE INCREASED BY 3.94 IN. / 100 mm.

Figure 3. A/100 Series Dimensions (continued)

Table 1. Construction Material			
BODY	SERVOMOTOR	VALVE SEAT	DIAPHRAGM
Cast Iron GS	Aluminum	Brass	Nitrile (NBR)

Table 2. A/100 Series Capacities														
OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											SEAT DIAMETER	
		Inlet Pressure, psig / bar												
	psig	mbar	0.435 / 0.03	1.02 / 0.07	4.35 / 0.30	7.25 / 0.50	14.5 / 1.00	21.76 / 1.5	29 / 2.0	43.5 / 3.0	58.02 / 4.0	116 / 8.0	In.	mm
STANDARD	0.14	10	----	1589 / 45.0	2295 / 65.0	3531 / 100	3884 / 110	4237 / 120	4590 / 130	4944 / 140	4944 / 140	----	1/2	12.7
			----	----	3178 / 90.0	3884 / 110	4237 / 120	4590 / 130	4944 / 140	4944 / 140	4944 / 140	----	5/8	15.8
			1765 / 50.0	3001 / 85.0	4414 / 125	5297 / 150	6003 / 170	6356 / 180	6356 / 180	----	----	----	----	3/4
	0.29	20	----	1412 / 40.0	3178 / 90.0	3531 / 100	4944 / 140	4944 / 140	5297 / 150	5650 / 160	5650 / 160	5650 / 160	1/2	12.7
			----	1765 / 50.0	2825 / 80.0	3884 / 110	5297 / 150	7062 / 200	8122 / 230	8122 / 230	8122 / 230	8122 / 230	5/8	15.8
			1236 / 35.0	2825 / 80.0	4237 / 120	6356 / 180	7062 / 200	7416 / 210	7416 / 210	----	----	----	----	3/4
0.73	50	----	1412 / 40.0	2825 / 80.0	3531 / 100	6356 / 180	7062 / 200	9181 / 260	12,360 / 350	14,832 / 420	16,950 / 480	1/2	12.7	
		----	----	3178 / 90.0	4590 / 130	7769 / 220	10,594 / 300	12,360 / 350	14,125 / 400	16,950 / 480	19,069 / 540	5/8	15.8	
		----	3178 / 90.0	6003 / 170	7062 / 200	8828 / 250	10,594 / 300	13,419 / 380	15,538 / 440	----	----	----	3/4	19.5
AP	1.45	100	----	----	1412 / 40.0	2825 / 80.0	4237 / 120	6709 / 190	8122 / 230	13,066 / 370	17,657 / 500	21,188 / 600	1/2	12.7
			----	----	3178 / 90.0	5297 / 150	7062 / 200	9181 / 260	12,360 / 350	19,069 / 540	21,188 / 600	21,188 / 600	5/8	15.8
			----	----	3178 / 90.0	6003 / 170	9181 / 260	11,300 / 320	18,363 / 520	21,188 / 600	21,188 / 600	----	----	3/4
	2.90	200	----	----	1765 / 50.0	2472 / 70.0	3884 / 110	6003 / 170	6709 / 190	11,653 / 330	16,597 / 470	21,188 / 600	1/2	12.7
			----	----	3178 / 90.0	4237 / 120	7062 / 200	8475 / 240	10,594 / 300	16,950 / 480	21,188 / 600	21,188 / 600	5/8	15.8
			----	----	3531 / 100	5650 / 160	8828 / 250	12,360 / 350	15,538 / 440	21,188 / 600	----	----	----	3/4
	4.35	300	----	----	----	1765 / 50.0	4237 / 120	5297 / 150	6356 / 180	8122 / 230	10,594 / 300	12,360 / 350	1/2	12.7
			----	----	----	2295 / 65.0	5297 / 150	7062 / 200	8828 / 250	10,594 / 300	12,360 / 350	14,125 / 400	5/8	15.8
			----	----	----	2825 / 80.0	6180 / 175	8828 / 250	10,594 / 300	----	----	----	----	3/4
----	----	----	3531 / 100	7062 / 200	10,594 / 300	14,125 / 400	----	----	----	----	1	25.4		

Note: To determine equivalent capacities for air, propane, butane or nitrogen, multiply the capacity by the following appropriate conversion factor: 0.775 for air, 0.625 for propane, 0.548 for butane or 0.787 for nitrogen.



# Ordering Guide

<b>Type (Select One)</b>
<input type="checkbox"/> A/102 or A/102-AP (without slam-shut valve)*** <input type="checkbox"/> A/109 or A/109-AP (with slam-shut valve)***
<b>Inlet Pressure</b>
_____ please specify
<b>Outlet Pressure</b>
_____ please specify
<b>Set Pressure</b>
_____ please specify
<b>Temperature Requirement (Select One)</b>
<input type="checkbox"/> Standard <input type="checkbox"/> Low Temperature
<b>Special Requirement (Optional)</b>
_____

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<input type="checkbox"/> Yes	<input type="checkbox"/> No
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**  
Downstream pressure always changes to some extent when inlet pressure changes.

# A/140 Series

## Spring-Loaded Regulator

TARTARINI™

### Introduction

A/140 Series regulators are spring controlled single seated, with counterbalanced valve disc. They are usually supplied with safety valve and built-in filter and can also be provided with shut-off device for minimum pressure, maximum pressure or minimum and maximum downstream pressure.

The regulators of the A/140 Series have been devised keeping in consideration the functionality of maintenance, in fact, it is possible to replace the seat or the seals without removing the body from the line.

### Configurations

**Types A/142 and A/142-AP:**  
without shut-off device

**Types A/149 and A/149-AP:**  
with shut-off device

### Body Allowable Pressure

Up to 290 psig / 20.0 bar

### Highest Operating Pressure

4.35 psig / 300 mbar

### Maximum Inlet Pressure

87 psig / 6.0 bar

### Inlet Pressure Range

1.45 to 87 psig / 0.10 to 6.0 bar

### Set Ranges

**Standard:** 0.22 to 1.09 psig / 15 to 75 mbar  
**AP:** 1.09 to 4.35 psig / 75 to 300 mbar  
**AP (QL Option):** 4.35 to 7.5 psig / 300 to 500 mbar

### Accuracy Class

Up to ±5%

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Counterbalanced Valve
- Available with or without Relief Valve
- AE/149 and AE/149-AP Monitor Version Available
- Overpressure and Underpressure Slam-Shut Valve
- Manual Reset

### Lockup Pressure Class

Up to ±10%

### Maximum Flow Rate

Up to 31,783 SCFH / 900 Sm<sup>3</sup>/h

### Built-in Slam-Shut Valve

**Built-in Pneumatic Control**

**Accuracy Class:** ±5%

**Response Time:** ≤1 second

### Orifice

1-3/16 in. / 30 mm

### Flanged Connection

2 in. / DN 50




Figure 1. Type A/142 Spring-Loaded Regulator




Figure 2. Type A/149-AP Spring-Loaded Regulator

### Flange Rating

PN 16 UNI/DIN

### Operating Temperature

**Standard Version:**

14 to 140°F / -10 to 60°C


**Low Temperature Version:**

-4 to 140°F / -20 to 60°C


Table 1. Construction Material

Table 1. Construction Material	
ACTUATOR CASING	Aluminum
COVER	Aluminum
VALVE CASING*	Ductile iron
VALVE SEAT	Brass
DIAPHRAGM	Nitrile (NBR)
SEAL	Nitrile (NBR)

\*Steel valve casing available on request.



TYPE A/142 OR A/142-AP



TYPE A/149 OR A/149-AP

IN. /  
mm

\*IN HIGH PRESSURE VERSIONS (AP), THIS DIMENSION MUST BE INCREASED BY 3.94 in. / 100 mm.

Figure 3. A/140 Series Dimensions

Table 2. A/140 Series Capacities																	
CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
OUTLET PRESSURE, psig / mbar		Inlet Pressure, psig / bar															
		0.44 / 0.03	0.73 / 0.05	1.09 / 0.08	1.45 / 0.10	2.18 / 0.15	2.9 / 0.20	4.35 / 0.30	5.8 / 0.40	7.25 / 0.50	10.9 / 0.75	14.5 / 1.00	21.8 / 1.5	29.0 / 2.0	43.51 / 3.0	58.01 / 4.0	72.52 / 5.0
STANDARD	0.22 / 15	1765 / 50.0	2825 / 80.0	3531 / 100	4237 / 120	5297 / 150	6003 / 170	7769 / 220	8828 / 250	9888 / 280	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900
	0.29 / 20	----	2648 / 75	3531 / 100	4237 / 120	5297 / 150	6003 / 170	7769 / 220	8828 / 250	9888 / 280	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900
	0.45 / 30	----	2118 / 60.0	3178 / 90.0	3884 / 110	5297 / 150	6003 / 170	7769 / 220	8828 / 250	9888 / 280	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900
	0.58 / 40	----	----	2825 / 80.0	3531 / 100	4944 / 140	6003 / 170	7416 / 210	8828 / 250	9888 / 280	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900
	0.73 / 50	----	----	2472 / 70.0	3178 / 90.0	4944 / 140	5650 / 160	7416 / 210	8475 / 240	9534 / 270	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900
AP	1.09 / 75	----	----	----	4237 / 120	5297 / 150	7062 / 200	8475 / 240	9534 / 270	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900	
	1.45 / 100	----	----	----	3531 / 100	4944 / 140	6709 / 190	8122 / 230	8828 / 250	12,006 / 340	14,125 / 400	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900	
	2.18 / 150	----	----	----	----	3531 / 100	6003 / 170	7769 / 220	8828 / 250	11,653 / 330	13,772 / 390	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900	
AP (QL Option)	2.90 / 200	----	----	----	----	----	4944 / 140	7062 / 200	8475 / 240	11,653 / 330	13,772 / 390	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900	
	4.35 / 300	----	----	----	----	----	----	5297 / 150	7416 / 210	10,947 / 310	13,419 / 380	17,657 / 500	21,188 / 600	22,954 / 650	26,485 / 750	31,783 / 900	
	4.35 / 300	----	----	----	----	----	----	3708 / 105	4944 / 140	7062 / 200	8828 / 250	11,124 / 315	14,479 / 410	16,597 / 470	18,363 / 520	25,426 / 720	
	5.08 / 350	----	----	----	----	----	----	----	4414 / 125	6533 / 185	8652 / 245	10,947 / 310	14,302 / 405	16,421 / 465	18,010 / 510	25,073 / 710	
	5.80 / 400	----	----	----	----	----	----	----	3708 / 105	6356 / 180	8475 / 240	10,770 / 305	14,125 / 460	16,244 / 500	17,657 / 500	24,720 / 700	
6.53 / 450	----	----	----	----	----	----	----	----	6003 / 170	8298 / 235	10,594 / 300	13,419 / 380	15,538 / 440	17,127 / 485	24,013 / 680		
7.25 / 500	----	----	----	----	----	----	----	----	5650 / 160	8122 / 230	10,241 / 290	12,713 / 360	15,185 / 430	16,597 / 470	23,660 / 670		

Note: To determine equivalent capacities for air, propane, butane or nitrogen, multiply the capacity by the following appropriate conversion factor: 0.775 for air, 0.625 for propane, 0.547 for butane or 0.789 for nitrogen.

## Ordering Guide

### Type (Select One)

- A/142 or A/142-AP (without slam-shut valve)\*\*\*
- A/149 or A/149-AP (with slam-shut valve)\*\*\*

### Inlet Pressure

\_\_\_\_\_ please specify

### Outlet Pressure

\_\_\_\_\_ please specify

### Set Pressure

\_\_\_\_\_ please specify

### Temperature Requirement (Select One)

- Standard**
- Low Temperature

### Special Requirement (Optional)

\_\_\_\_\_

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred?   <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve   <input type="checkbox"/> Monitor Regulator   <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?   <input type="checkbox"/> Yes   <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Differential Pressure Setting:
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

If two or more available springs have published pressure ranges that include the desired pressure setting, use the spring with the lower range for better accuracy.

### Introduction

The Type B regulator is a direct-operated, spring-loaded regulator providing economical, pressure reducing control in a variety of residential, commercial and industrial applications; and for a variety of gaseous fluids.

This compact regulator can be installed in a pressure reducing cabinet or a reducing and metering cabinet above ground or in underground modules.

### Body Sizes

3/4 x 1-1/4 in. / DN 20 x 32

### End Connections Styles

**Inlet:** Sphero-conical or flat joint connection

**Outlet:** Flat meter joint connection

### Flow Capacities

0 to 1791 SCFH / 0 to 48 Nm<sup>3</sup>/h  
See Table 2

### Pressure Registration

Internal

### Maximum Inlet Pressure

58 psig / 4.0 bar  
See Table 1

### Maximum Outlet Pressure

161 in. w.c. / 400 mbar

### Outlet Pressure Range

3.6 to 161 in. w.c. / 9 to 400 mbar  
See Table 1

### Accuracy

RG: 5

SG: 10

### Construction Materials

**Body and Castings:** Zinc/Aluminum Alloy

**Inlet and Outlet Connections:** Brass

**Inlet Filter:** Bronze

**Outlet Gasket:** Composition

**Plug:** Brass

**Disk Seat:** Nitrile (NBR)

**Diaphragm:** Reinforced Nitrile (NBR)

**Vent:** Plastic

### Temperature Capabilities

-4 to 140°F / -20 to 60°C

### Approximate Shipping Weight

4.4 lbs / 2 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/17

### Features

- Integral Slam-Shut Valve
- Compact Design
- Internal Relief
- Two Stages of Reduction for Constant Outlet Pressures
- Inlet Mesh Filter




Figure 1. Type B 25 Pressure Reducing Regulator




Figure 2. Type B 50 Pressure Reducing Regulator




Figure 3. Type BCH 30 Pressure Reducing Regulator







Figure 4. Type B Operational Schematic

# Type B

## Pressure Reducing Regulator

FRANCEL™



- C05
- P<sub>1</sub> = 58 psig / 4.0 bar
  - P<sub>1</sub> = 10 psig / 0.69 bar
  - P<sub>1</sub> = 7.3 psig / 0.50 bar
  - P<sub>1</sub> = 5.8 psig / 0.40 bar
  - P<sub>1</sub> = 4.4 psig / 0.30 bar
  - P<sub>1</sub> = 2.9 psig / 0.20 bar
  - P<sub>1</sub> = 1.5 psig / 0.10 bar
  - RG 5

Figure 5. Flow Curves

Table 1. Maximum Pressure

PRESSURE		TYPE B 25		TYPE B 40		TYPE BCH 30	
		psig	bar	psig	bar	psig	bar
Inlet	Minimum	7.3	0.50	10.2	0.70	11.6	0.80
	Maximum	58	4.0	58	4.0	58	4.0
Outlet	Minimum	3.6 in. w.c.	9 mbar	3.6 in. w.c.	9 mbar	18.5 in. w.c.	46 mbar
	Maximum	18.0 in. w.c.	45 mbar	18.0 in. w.c.	45 mbar	161 in. w.c.	400 mbar
	Standard	8.4 in. w.c.	21 mbar	8.4 in. w.c.	21 mbar	121 in. w.c.	300 mbar

Table 2. Flow Capacity

INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS		
psig	bar	Type B 25	Type B 40	Type BCH 30
1.4	0.10	485 / 13.0	----	----
2.9	0.20	672 / 18.0	----	----
4.4	0.30	932 / 25.0	----	----
5.8	0.40	1045 / 28.0	----	----
7.3	0.50	1120 / 30.0	1493 / 40.0	----
10.2	0.70	1120 / 30.0	1791 / 48.0	----
11.6 to 58	0.80 to 4.0	1120 / 30.0	1791 / 48.0	1343 / 36.0
73	5.0	1120 / 30.0	1791 / 48.0	1343 / 36.0






Figure 6. Dimensions




Figure 7. Installation

## Ordering Guide

### Type (Select One)

- B 25
- B 40
- B 50
- BCH 30

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

All regulators should be installed and used in accordance with federal, state and local codes and regulations.

# Type B NG

## Pressure Reducing Regulator

FISHER™

### Introduction

The new Type B NG residential regulator is a direct-action, spring-loaded regulator, with high performance and reinforced safety features. It provides pressure reducing control in a variety of residential, commercial and industrial applications for a variety of gaseous fluids. This regulator is used in a distribution network with inlet pressure of 7.25 to 72.5 psig / 0.50 to 5.0 bar. Standard outlet pressures can be set at 8.5, 10.8 and 14.8 in. w.c. / 21, 27 and 37 mbar with a flow capacity of 224 and 373 SCFH / 6.0 to 10.0 Nm<sup>3</sup>/h. Other outlet settings available on request: 4 to 20 in. w.c. / 10 to 50 mbar with a flow capacity of 933 SCFH / 25.0 Nm<sup>3</sup>/h under specific conditions.

A shutoff valve cuts off the gas flow in the case of excessive flow, or when the outlet pressure drops below the setpoint (high gas demand or broken line) or in the case of inlet pressure dropping below the setpoint (network pressure drop or pipe damage).

The regulator can be manually reset after the safety function trips. The regulator is factory preset.

The new Type B6 NG is interchangeable with the current angle-shaped Type B6 N (same key dimensions).

### Body Size

3/4 x 1-1/4 in. / DN 20 x 32

### Flow Capacity

0 to 373 SCFH / 0 to 10.0 Nm<sup>3</sup>/h

See flow curves in Figure 3

### Pressure Registration

Internal

### Maximum Inlet Pressure

72.5 psig / 5.0 bar

### Inlet Pressure Range

7.25 to 72.5 psig / 0.5 to 5 bar  
(1.45 to 102 psig / 0.1 to 6 bar)  
- on request

### Maximum Outlet Pressure

20 in. w.c. / 50 mbar

### Outlet Pressure Range

3.6 to 20 in. w.c. / 9 to 50 mbar

### Accuracy Class

SG: Up to 20

AC: Up to 5

### Temperature Capabilities

-4 to 140°F / -20 to 60°C  
-22 to 140°F / -30 to 60°C (on request)

### Approximate Shipping Weight

2.16 to 2.21 lbs / 0.98 to 1 kg




Figure 1. Type B NG Pressure Reducing Regulator

### Features

- Reinforced Integration
- Two Stages of Reduction for Constant Outlet Pressures
- Compact Design
- Internal Relief
- Inlet Strainer

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



04/10




Figure 2. Type B NG Operational Schematic




Figure 3. Types B6 NG and B10 NG Flow Curve








Figure 3. Types B6 NG and B10 NG Flow Curve (continued)




Figure 4. Type B NG Installation




Figure 5. Dimensions

# Type B NG

## Pressure Reducing Regulator

FISHER™

**Table 1. Construction Materials**

<b>BODY</b>	Zinc/Aluminum Alloy	<b>1ST STAGE DISK ORIFICE</b>	Aluminum
<b>CASING</b>	Zinc/Aluminum Alloy	<b>2ND STAGE PLUG</b>	Nitrile (NBR)
<b>INLET CONNECTION</b>	Brass	<b>2ND STAGE DISK ORIFICE</b>	Brass
<b>INLET FILTER</b>	Bronze or Plastic	<b>DIAPHRAGM</b>	Nitrile (NBR)
<b>OUTLET CONNECTION</b>	Brass	<b>VENT SCREEN</b>	Stainless Steel
<b>1ST STAGE PLUG</b>	Nitrile (NBR)	<b>VENT</b>	Plastic (option)

**Table 2. Capacities**

INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS			
		Type B6 NG		Type B10 NG	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
1.4	0.10	131	3.5	224	6
2.9	0.20	224	6.0	373	10
4.4	0.30	246	6.6	410	11
5.8	0.40	246	6.6	410	11
7.3	0.50	246	6.6	410	11
10.2	0.70	246	6.6	410	11
11.6 to 58	0.80 to 4.0	246	6.6	410	11
72.5	5.0	246	6.6	410	11

## Ordering Guide

### Type (Select One)

- B6 NG  
 B10 NG

### Installation Orientation (Select One)

- Direct Line  
 Angle Line

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

When a regulator appears unable to pass the published flow rate, be sure to check the inlet pressure measured at the regulator body inlet connection. Piping up to and away from regulators can cause significant flowing pressure losses.



### Introduction

Construction and performance features make the B/240 Series spring-loaded regulators the ideal choice in applications involving sudden changes in capacity or where the gas shutoff is solenoid-controlled as with domestic or industrial burners.

These regulators can be employed with natural, manufactured, propane, air and other gases so long as they are duly filtered and do not contain high percentages of benzol.

### Available Configurations

**Types B/242 and B/242-AP:**

Without safety shut-off device

**Types B/249 and B/249-AP:**

With safety shut-off device

### Body Sizes and End Connection Styles

**B/240 Series:** NPS 1-1/2 / DN 40 BSP inlet and outlet

**B/240-FS Series:** NPS 1-1/2 / DN 40 PN 16 flanged

### Body Allowable Pressure

Up to 290 psig / 20.0 bar

### Highest Operating Pressure

7.25 psig / 0.50 bar

### Maximum Inlet Pressure

87 psig / 6.0 bar

### Inlet Pressure Range

1.45 to 87 psig / 0.10 to 6.0 bar

### Outlet Pressure Ranges

**Types B/242 and B/249:**

0.22 to 1.1 psig / 15 to 75 mbar

**Types B/242-AP and B/249-AP:**

1.1 to 4.35 psig / 75 to 300 mbar

**Types B/242-AP and B/249-AP**

**(QL Option):** 4.35 to 7.25 psig / 300 to 500 mbar

### Accuracy Class

Up to ±5%

### Lock-up Pressure Class


Up to 10%

### Built-in Slam-Shut Valve

Independent pneumatic control

**Accuracy class:** ±5%

Response time: ≤1 second



**Figure 1.** Type B/242 Spring-loaded Regulator Balanced Plug

**Figure 2.** Type B/249 Spring-loaded Regulator Balanced Plug

### Maximum Flow Rate

Up to 10,594 SCFH / 300 Stm<sup>3</sup>/h

### Orifice

0.67 in. / 17 mm

### Operating Temperature

**Standard version:**

14 to 140°F / -10 to 60°C

**Low-temperature version:**

-4 to 140°F / -20 to 60°C

### Weights

**Types B/242 and B/242-AP:**

7.7 lbs / 3.5 kg

**Types B/242-FS and B/242-AP-FS:**

16.5 lbs / 7.5 kg

**Types B/249 and B/249-AP:**

9.9 lbs / 4.5 kg

**Types B/249-FS and B/249-AP-FS:**

18.7 lbs / 8.5 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



07/15

### Features

- Counterbalanced Valve
- Built-in Relief Valve
- Overpressure and Underpressure Slam-Shut Valve
- Manual Reset
- Inlet and Outlet In-line

**Table 1. Construction Material**

Component	Material
ACTUATOR CASING	Aluminum
COVER	Aluminum
VALVE CASING	Ductile iron
VALVE DISK	Brass
VALVE SEAT	Brass
DIAPHRAGM	Nitrile (NBR)
SEAL	Nitrile (NBR)

# B/240 Series

## Spring-Loaded Regulator

TARTARINI




Figure 3. Outline Dimensions

OUTLET PRESSURE, In. w.c. / mbar		CAPACITIES IN SCFH / Stm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
		Inlet Pressure, psig / bar															
		0.4 / 28 mbar	0.7 / 48 mbar	1.09 / 75 mbar	1.45 / 0.10	2.17 / 0.15	2.9 / 0.20	4.35 / 0.30	5.8 / 0.40	7.2 / 0.50	10.9 / 0.75	14.5 / 1.0	21.7 / 1.5	29 / 2.0	43.5 / 3.0	58 / 4.0	72.5 and 87 / 5.0 and 6.0
STANDARD	6 / 15	424 / 12	530 / 15	706 / 20	1059 / 30	1413 / 40	1766 / 50	2295 / 65	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
	8 / 20	----	530 / 15	706 / 20	1059 / 30	1413 / 40	1766 / 50	2295 / 65	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
	12 / 30	----	424 / 12	706 / 20	1059 / 30	1413 / 40	1766 / 50	2295 / 65	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
	16 / 40	----	----	530 / 15	883 / 25	1413 / 40	1766 / 50	2295 / 65	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
	20 / 50	----	----	530 / 15	706 / 20	1413 / 40	1766 / 50	2295 / 65	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
	30 / 75	----	----	----	530 / 15	1059 / 30	1589 / 45	2119 / 60	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	8829 / 250	8829 / 250
AP	40 / 100	----	----	----	----	706 / 20	1413 / 40	1766 / 50	2825 / 80	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	9888 / 280	10,594 / 300
	60 / 150	----	----	----	----	----	1059 / 30	1413 / 40	2472 / 70	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	9888 / 280	10,594 / 300
	80 / 200	----	----	----	----	----	----	1059 / 30	2119 / 60	3531 / 100	4238 / 120	4238 / 120	6003 / 170	7063 / 200	8829 / 250	9888 / 280	10,594 / 300
	120 / 300	----	----	----	----	----	----	----	1766 / 50	2825 / 80	3885 / 110	3885 / 110	6003 / 170	7063 / 200	8829 / 250	9888 / 280	10,594 / 300

Note: To determine equivalent capacities for air, propane, butane or nitrogen, multiply the capacity by the following appropriate conversion factor: 0.78 for air, 0.63 for propane, 0.55 for butane or 0.79 for nitrogen.

- continued -



**Table 2. B/240 Series Capacities (continued)**

OUTLET PRESSURE, In. w.c. / mbar		CAPACITIES IN SCFH / Stm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS														
		Inlet Pressure, psig / bar														
		0.4 / 28 mbar	0.7 / 48 mbar	1.09 / 75 mbar	1.45 / 0.10	2.17 / 0.15	2.9 / 0.20	4.35 / 0.30	5.8 / 0.40	7.2 / 0.50	10.9 / 0.75	14.5 / 1.0	21.7 / 1.5	29 / 2.0	43.5 / 3.0	58 / 4.0
AP	4.35 / 300							1059 / 30	1413 / 40	2119 / 60	2825 / 80	4591 / 130	6003 / 170	7063 / 200	8122 / 230	8829 / 250
	5.08 / 350								1413 / 40	2119 / 60	2825 / 80	4591 / 130	6003 / 170	7063 / 200	8122 / 230	8829 / 250
	5.80 / 400								1236 / 35	2119 / 60	2825 / 80	4591 / 130	6003 / 170	7063 / 200	8122 / 230	8829 / 250
	6.52 / 450									2119 / 60	2825 / 80	4591 / 130	6003 / 170	7063 / 200	8122 / 230	8829 / 250
	7.25 / 500									1766 / 50	2649 / 75	4238 / 120	5650 / 160	6710 / 190	7769 / 220	8476 / 240

— QL Option.  
 Note: To determine equivalent capacities for air, propane, butane or nitrogen, multiply the capacity by the following appropriate conversion factor: 0.78 for air, 0.63 for propane, 0.55 for butane or 0.79 for nitrogen.

## Ordering Guide

**Main Valve Diaphragm Material (Select One)**

Type B/242 or B/242-AP (without safety shut-off device)\*\*\*

Type B/249 or B/249-AP (with safety shut-off device)\*\*\*

**End Connection Style (Select One)**

NPS 1-1/2 / DN 40 BSP

NPS 1-1/2 / DN 40 PN 16

**Inlet Pressure (Specify)**

**Outlet Pressure (Specify)**

**Set Pressure (Select One)**

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.

Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.

**Temperature Requirement (Select One)**

Standard

Low Temperature

**Special Requirements (Optional)**

**Specification Worksheet**

**Application**

Specific Use:

Line Size:

Gas Type and Specific Gravity:

Gas Temperature:

Does the application require overpressure protection?

Yes, which is preferred?  No

Relief Valve  Monitor Regulator  Shutoff Device

Is overpressure protection equipment selection assistance desired?  Yes  No

**Pressure**

Maximum Inlet Pressure (P<sub>1max</sub>):

Minimum Inlet Pressure (P<sub>1min</sub>):

Downstream Pressure Setting(s) (P<sub>2</sub>):

Maximum Flow (Q<sub>max</sub>):

**Performance Required**

Accuracy requirements?

Need for extremely fast response?

**Other Requirements:**

**Regulator Tip:**

When adjusting setpoint, the regulator should be flowing at least five percent of the normal operating flow.

# Types BLE and BLX

## Throttle Valve

FRANCEL™

### Introduction

The Types BLE and BLX throttle valves functions as a bypass on transmission stations reducing pressure up to 1450 psig / 100 bar.

The Type BLX version is equipped with a Type OSE valve plug and a Type OS2 release relay to cut off pressure flow in case of outlet over pressure.

The Type BLE version consists of:

- A body (type E body) with removable orifice, closed with a cap which can also be used as a valve guide
- A balanced valve plug, opened by fluid flow, with linear characteristics
- A valve plug/orifice Nitrile (NBR) disk plug, removable and tight shutoff
- A valve plug guide with plastic rings and manual handwheel
- A button used as an opening indicator

The Type BLX version consists of:

- A body (type X body) including an inferior opening for lodging the slam-shut

The slam-shut includes:

- A valve plug/orifice assembly with connecting part
- A release relay Type OS2 including a mechanism box (Type BM) and a safety manometric box (Type BMS)

The Types BLE and BLX are in conformity with the Pressure Equipment Directive (PED) 2014/68/EU and are classified in Category IV.

### Maximum Operating Pressures

**LCC Body:** 1450 psig / 100 bar

**WCB-20 Body:** 1402 psig / 96.7 bar

### Operating Temperatures

**LCC Body:** -22 to 160°F / -30 to 71°C

**WCB-20 Body:** -4 to 160°F / -20 to 71°C

### Slam-Shut (Type BLX only)

**Response time:** <1 second

**Accuracy:** 2.5; 5 (piston)

Setpoint range: 0.14 to 1450 psig / 0.01 to 100 bar

Resetting:

Manually after fault rectification

Position indicator:

On the mechanism box

### Connections

**Inlet/Outlet:**

DN 25, 50, 80

ISO PN 100 B (CL600 RF)

ISO PN 50 B (CL300 RF)

ISO PN 20 B (CL150 RF)


Other connections available (contact factory)

ISO PN 16 B, 25 B, 40 B

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)




12/13

### Features

- Robust
- High Precision
- Progressive Opening



Figure 1. Type BLX Throttle Valve



■ INLET PRESSURE  
■ ATMOSPHERIC PRESSURE

Figure 2. Type BLX Operational Schematic

Table 1. Construction Material

BODY	BONNET	SCREW HOLDER	ORIFICE	VALVE PLUG	DISK PLUG
Steel	Steel	Bronze	Stainless steel	Steel	Nitrile (NBR)

Table 2. Flow Coefficient

BODY SIZE		Q <sub>r</sub>	C <sub>g</sub>	C <sub>t</sub>
In.	DN			
1	25	230	450	35
2	50	970	1880	
3	80	2150	4170	




Figure 3. Dimensions

BODY SIZE		PN	DIMENSION FOR TYPES BLE (WITHOUT SLAM-SHUT) AND BLX (WITH SLAM-SHUT)										APPROXIMATE SHIPPING WEIGHT					
			A		Type BLE		Type BLX		Type BLE		Type BLX		REMOVAL		Type BLE		Type BLX	
In.	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lbs	kg	lbs	kg	
1	25	20	7.28	185	2.13	54	12.4	315	7.21	183	7.72	196	2.17	55	26.4	12	44.1	20
		50	7.77	197	2.44	62									28.6	13	46.3	21
		100	8.27	210	3.00	76									30.8	14	48.5	22
2	50	20	10.0	254			13.0	331	7.72	196	8.39	213	2.95	75	49.6	22	79.4	36
		50	10.5	267											3.27	83	54.0	24
		100	11.3	286	3.74	95									58.4	26.5	88.2	40
3	80	20	11.73	298	14.2	366	8.78	223	9.49	241	3.74	95	94.8	43	126	57		
		50	12.52	318									4.13	105	108	49	139	63
		100	13.3	337									112	51	143	65		

## Ordering Guide

**Type (Select One)**

**BLE (without slam-shut)**

- 1 in. / DN 25
- 2 in. / DN 50
- 3 in. / DN 80

**BLX (with slam-shut)**

- 1 in. / DN 25
- 2 in. / DN 50
- 3 in. / DN 80

**Inlet/Outlet Connections**

- ISO PN 100 B (CL600 RF)
- ISO PN 50 B (CL300 RF)
- ISO PN 20 B (CL150 RF)
- ISO PN 16 B
- ISO PN 25 B
- ISO PN 40 B

**Slam-Shut Valve (Optional, Select Range)**

**Maximum Only**

**Lowest**

- 0.22 to 17.4 psig / 0.01 to 1.2 bar
- 29 to 116 psig / 2.0 to 8.0 bar
- 232 to 319 psig / 16.0 to 22.0 bar
- 580 to 798 psig / 40.0 to 55.0 bar
- 160 to 232 psig / 11.0 to 16.0 bar
- 507 psig / 35.0 bar

**Highest**

- 0.51 to 33 psig / 0.03 to 2.3 bar
- 74 to 232 psig / 5.1 to 16.0 bar
- 319 to 580 psig / 22.0 to 40.0 bar
- 798 to 1450 psig / 55.0 to 100 bar
- 319 to 507 psig / 22.0 to 35.0 bar
- 1044 psig / 72.0 bar

- continued -

## Ordering Guide (continued)

### Slam-Shut Valve (Optional, Select Range) (continued)

#### Minimum Only

##### Lowest

- 0.22 to 16 psig / 0.01 to 1.1 bar
- 29 to 116 psig / 2.0 to 8.0 bar
- 232 to 276 psig / 16.0 to 19.0 bar
- 551 to 725 psig / 38.0 to 50.0 bar
- 160 to 232 psig / 11.0 to 16.0 bar
- 406 psig / 28.0 bar

##### Highest

- 0.51 to 29 psig / 0.03 to 2.0 bar
- 68.2 to 209 psig / 4.7 to 14.4 bar
- 275 to 551 psig / 19.0 to 38.0 bar
- 725 to 1305 psig / 50.0 to 90.0 bar
- 232 to 406 psig / 16.0 to 28.0 bar
- 942 psig / 65.0 bar

### Slam-Shut Valve (Optional, Select Range) (continued)

#### Minimum and Maximum

##### Lowest

- 0.145 to 6.53 psig / 0.01 to 0.45 bar
- 14.5 to 58 psig / 1.00 to 4.0 bar
- 79.8 to 120 psig / 5.5 to 8.3 bar
- 254 psig / 17.5 bar

##### Highest

- 0.51 to 33.4 psig / 0.03 to 2.3 bar
- 74 to 232 psig / 5.1 to 16.0 bar
- 319 to 507 psig / 22.0 to 35.0 bar
- 1044 psig / 72.0 bar

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

#### Regulator Tip:

The full advertised range of a spring can be utilized without sacrificing performance or spring life.



**Introduction**

The BM5 Series slam-shut valve is an automatic shut-off appliance suitable for installation as a safety device in regulating stations and gas distribution piping.

The slam-shut valve has the task to quickly shut off the gas flow when the pressure in control point(s) reaches a fixed set value.

The valve is a sleeve-type, as a consequence, does not need any external bypass to facilitate the opening of the valve itself.

The valve re-opening can be made only through a manual operation.

The BM5 Series slam-shut valves are used in natural gas regulating installations and air, propane, butane, LPG, city gas, nitrogen, carbon dioxide, hydrogen regulating or distribution installations.

**Allowable Pressure**

Up to 1450 psig / 100 bar

**Inlet Pressure Range**

0 to 1450 psig / 0 to 100 bar

**Maximum Capacity**

9,627,000 SCFH / 258,000 Nm<sup>3</sup>/h

**Overpressure Set Range**

0.44 to 1160 psig / 0.03 to 80.0 bar

**Underpressure Set Range**

0.15 to 1160 psig / 0.01 to 80.0 bar

**Accuracy Class**

Up to ±1%

**Response Time**

≤ 1 second

**Flow Coefficients**

C<sub>g</sub>: Up to 18,600

See Table 2

**Flanged Connections**


**Same Inlet and Outlet:**

NPS 1, 1-1/2, 2, 2-1/2, 3, 4 and 6 / DN 25, 40, 50, 65, 80, 100 and 150

**Flange Ratings**

PN 16/25


CL150 RF, CL300 RF and CL600 RF




**Figure 1.** Type BM5 with Type OS/80X-APA-D



**Figure 2.** Type BM5 with Type OS/84



**Figure 3.** Type BM5 with Type OS/80X-BP



**Figure 4.** BM5 Series Sectional View

**Temperature Capabilities**

**Standard Version:**

Working: 14 to 140°F / -10 to 60°C

**Low Temperature Version:**

Working: -4 to 140°F / -20 to 60°C

**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

**Features**

- Axial Flow
- Flanged Connections
- Protected Seal Pad
- Possible to Fit in all Positions
- Pressure Control in One or More Points of the Installation
- Starting up Following Overpressure and/or Underpressure
- Push-Button Manual Emergency Release
- Manual Reset through Rotation of the Reset Shaft Only

**Table 1. Construction Material**

BODY	SHUTTER	O-RING	PAD	PAD HOLDER
Steel	Steel	Nitrile (NBR) or Fluorocarbon (FKM)	Nitrile (NBR) or Fluorocarbon (FKM)	Steel

**Table 2. Flow Coefficient**

BODY SIZE		C <sub>g</sub>	C <sub>i</sub>
NPS	DN		
1	25	525	29
1-1/2	40	1420	28
2	50	2250	26
2-1/2	65	3600	28
3	80	5400	30
4	100	8700	26
6	150	18,600	28

**Table 3. Pressure Rating**

FLANGE RATING	PN 16		PN 25		CL150 RF		CL300 RF		CL600 RF	
	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
ALLOWABLE PRESSURE	232	16.0	363	25.0	290	20.0	725	50.0	1450	100
INLET PRESSURE RANGE	0 to 232	0 to 16.0	0 to 363	0 to 25.0	0 to 290	0 to 20.0	0 to 725	0 to 50.0	0 to 1450	0 to 100
OVERPRESSURE SET RANGE	0.44 to 232	0.03 to 16.0	0.44 to 363	0.03 to 25.0	0.44 to 290	0.03 to 20.0	0.44 to 725	0.03 to 50.0	0.44 to 1160	0.03 to 80.0
UNDERPRESSURE SET RANGE	0.15 to 232	0.01 to 16.0	0.15 to 363	0.01 to 25.0	0.15 to 290	0.01 to 20.0	0.15 to 725	0.01 to 50.0	0.15 to 1160	0.01 to 80.0

**Table 4. Construction and Functional Specifications of OS/80X and OS/80X-PN Series Pilots**

TYPE	SERVOMOTOR BODY RESISTANCE		OVERPRESSURE SET RANGE		UNDERPRESSURE SET RANGE	
	psig	bar	psig	bar	psig	bar
OS/80X-BP	72.5	5.00	0.44 to 29	0.03 to 2.00	0.15 to 8.7	0.01 to 0.60
OS/80X-BPA-D	290	20.0	0.44 to 29	0.03 to 2.00	0.15 to 8.7	0.01 to 0.60
OS/80X-MPA-D	1450	100	7.3 to 72.5	0.50 to 5.00	3.6 to 58	0.25 to 4.00
OS/80X-APA-D			29 to 145	2.0 to 10.00	4.4 to 102	0.30 to 7.00
OS/84X			72.5 to 595	5.0 to 41.0	58 to 232	4.0 to 16.0
OS/88X			261 to 1160	18.0 to 80.0	116 to 1015	8.0 to 70.0
OS/80X-PN			7.3 to 580	0.50 to 40.0	7.3 to 580	0.50 to 40.0
OS/84X-PN			435 to 1160	30.0 to 80.0	435 to 1160	30.0 to 80.0

**Type OS/80X-PN:**

Appliance made of Type OS/80X-APA-D set at about 5.8 psig / 0.4 bar and a variable number of Type PRX/182 pilots for overpressure and Type PRX/181 for underpressure, as many as necessary to control different points of the installation.

**Type OS/84X-PN:**

Appliance made of Type OS/84X set at about 290 psig / 20 bar and a variable number of Type PRX-AP/182 pilots for overpressure and Type PRX-AP/181 for underpressure, as many as necessary to control different points of the installation.

**Table 5. OS/80X Series Pilot Material**

SERVOMOTOR BODY	Type OS/80X-BP	Aluminum
	Type OS/80X-BPA-D	Aluminum
	Type OS/80X-MPA-D	Steel
	Type OS/80X-APA-D	Steel
DIAPHRAGM	----	Fabric-finished Nitrile (NBR)
O-RING	----	Nitrile (NBR)




Figure 5. Dimensions

Table 6. Types OS/84X and OS/88X Pilot Material

SERVOMOTOR BODY	Brass
LIP SEAL	Polytetrafluoroethylene (PTFE)
O-RING	Nitrile (NBR)

Table 7. PRX Series Pilot Material

BODY	Steel
DIAPHRAGM	Fabric-finished Nitrile (NBR)
O-RING	Nitrile (NBR)

Table 8. Dimension

DIMENSION DESIGNATION	BODY SIZE														
	NPS 1 / DN 25		NPS 1-1/2 / DN 40		NPS 2 / DN 50		NPS 2-1/2 / DN 65		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	
A	3.93	100	4.92	125	5.71	145	6.10	155	6.50	165	7.68	195	9.84	250	
B	8.66	220	9.25	235	9.65	245	10.04	255	10.83	275	11.61	295	14.37	365	
C	7.87	200	8.07	205	8.47	215	8.86	225	9.65	245	10.63	270	14.96	380	
D	4.92	125	6.10	155	6.50	165	7.48	190	9.06	230	10.83	275	16.14	410	
E	10.24	260	11.02	280	11.81	300	12.60	320	14.17	360	16.14	410	23.03	585	
I	PN 16	7.24	184	8.74	222	10	254	10.87	276	11.75	298.5	13.88	352.5	17.76	451
I	PN 25	7.24	184	----	----	10	254	----	----	11.75	298.5	13.88	352.5	17.76	451
I	CL150 RF	7.24	184	8.74	222	10	254	10.87	276	11.75	298.5	13.88	352.5	17.76	451
I	CL300 RF	7.76	197	9.25	235	10.49	266.5	11.50	292	12.50	317.5	14.51	368.5	18.62	473
I	CL600 RF	8.27	210	9.88	251	11.26	286	12.24	311	13.25	336.5	15.51	394	20	508

Note: Dimensions C are indicative and refer to models with larger dimensions. The threaded hole for the control piping connection is 1/4 NPT (internal).

Table 9. Shipping Weight

END CONNECTION STYLE	APPROXIMATE SHIPPING WEIGHT													
	BODY SIZE													
	NPS 1 / DN 25		NPS 1-1/2 / DN 40		NPS 2 / DN 50		NPS 2-1/2 / DN 65		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150	
	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg
PN 16/25 - CL150 RF	33.07	15	46.30	21	57.32	26	83.77	38	119	54	183	83	375	170
CL300 RF/CL600 RF	37.48	17	55.12	25	66.14	30	90.39	41	137	62	231	105	617	280

Note: Weight of the valve complete with pilot.

# BM5 Series

Slam-Shut Valve

TARTARINI™

## Ordering Guide

### Size (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 1-1/2 / DN 40\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 2-1/2 / DN 65\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*

### End Connection Style (Select One)

- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- PN 16\*\*\*
- PN 25\*\*\*

### Elastomer Part (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*

### Orientation - Indicates Flow Direction (Select One)

- SD, Left-Hand - Right-Hand
- DS, Right-Hand - Left-Hand
- AB, Up-Down
- BA, Down-Up

### Pilot Type (Select One)

- OS/80X-BP\*\*\*
- OS/80X-BPA-D\*\*\*
- OS/80X-MPA-D\*\*\*
- OS/80X-APA-D\*\*\*
- OS/84X\*\*\*
- OS/88X\*\*\*
- OS/80X-PN\*\*\*
- OS/84X-PN\*\*\*

### Required Overpressure Setpoint (Specify)

### Required Underpressure Setpoint (Specify)

### Temperature Construction (Select One)

- Standard\*\*\*
- Low Temperature\*\*

### Accessories (Select All that Apply)

- Proximity Switch
- Electrovalve for Remote Controlled Closure
- IT/3V Three-Way Valve for Setting Control (Pu max 50 bar)

### Special Requirements

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Looking for a specific product? When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.

# BM6X Series

## Axial Flow Slam-Shut Valve - Disk Closing, Manual Reset

TARTARINI™

### Introduction

The BM6X Series axial flow slam-shut valves are an automatic shutoff appliance suitable for installation as a safety device in regulating stations and on gas transfer and distribution lines.

The reduced face-to-face dimension, which is typical of wafer valves, facilitates installation even in existing regulating stations that are not equipped with shutoff devices. The slam-shut valve rapidly interrupts the gas flow in cases in which the pressure at the control point or points reaches the set level.

The BM6X Series slam-shut valves are of the "wafer" type with an off-center butterfly disk that is mounted eccentrically. The gas flow favors closure of the valve. The valve can only be re-opened manually.

The BM6X Series slam-shut valves use gas from the gas line for operation and therefore it does not require outside sources to operate.

### Body Sizes

NPS 3, 4, 6, 8, 10 and 12 /  
DN 80, 100, 150, 200, 250 and 300

### End Connection Style

CL150 RF, CL300 RF or CL600 RF

### Pressure Ratings

See Table 2

### Flow Coefficients

See Table 4

### Accuracy Class

Up to ± 1%

### Response Time

< 1 second

### Type IT/2V By-Pass Valve Features

**Material:** Brass

**Allowable Pressure:**

1450 psig / 100 bar

Maximum Operating Pressure:

1450 psig / 100 bar

Threaded Pipe Fitting:

1/4 FNPT

### Maximum Capacity

63,433,000 SCFH / 1,700,000 Nm<sup>3</sup>/h



Figure 1. BM6X Series Slam-Shut Valve



Figure 2. BM6X Series Axial Flow Slam-Shut Valve



Figure 3. Type IT/2V By-Pass Valve




Figure 4. Sectional View

### Temperature Capabilities

**Standard Version:**

14 to 140°F / -10 to 60°C

**Low Temperature Version:**

-4 to 140°F / -20 to 60°C

### Approximate Shipping Weight

See Table 9

### Additional Technical Data

Scan or Click the QR code for more information on this product.


[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Axial Flow
- "Wafer" Type Valve
- Off-Center Butterfly Disc
- Pressure Control at One or More Points in the System
- Activation Due to Pressure Increase or Decrease
- Emergency Slam-Shut Push Button
- Button By-Pass with Automatic Return
- Manual Reset by the Sole Rotation of the Reset Shaft
- Easy Maintenance



“A” ZONE INDICATES THE RANGE IN WHICH THE NACE VERSION MUST BE USED.  
 “B” ZONE INDICATES THE RANGE IN WHICH THAT VERSION IS NOT REQUIRED.

Figure 5. Application Graph Based on the Amount of Hydrogen Sulfide (H<sub>2</sub>S) Present in the Gas

Table 1. Construction Material	
BODY	Steel
BUTTERFLY DISK	Cast iron or Steel
SHAFT	Steel
SPRING	Stainless steel
LIP SEAL	Fluorocarbon (FKM)
O-RING	Nitrile (NBR) or Fluorocarbon (FKM)

Table 2. Additional Specification						
SPECIFICATION	PRESSURE RATING					
	End Connection					
	CL150 RF		CL300 RF		CL600 RF	
	psig	bar	psig	bar	psig	bar
Allowable Pressure	290	20.0	725	50.0	1450	100
Inlet Pressure Range	0 to 290	0 to 20.0	0 to 725	0 to 50.0	0 to 1450	0 to 100
Overpressure Set Range	0.44 to 290	0.03 to 20.0	0.44 to 725	0.03 to 50.0	0.44 to 1160	0.03 to 80.0
Underpressure Set Range	0.15 to 290	0.01 to 20.0	0.15 to 725	0.01 to 50.0	0.15 to 1160	0.01 to 80.0

Table 3. Construction and Functional Specifications of OS/80X-R and OS/80X-R-PN Series Pilots							
VALVE FLOW FROM RIGHT TO LEFT	VALVE FLOW FROM LEFT TO RIGHT	BODY RESISTANCE		OVERPRESSURE SET RANGE		UNDERPRESSURE SET RANGE	
		psig	bar	psig	bar	psig	bar
Type OS/80X-BP-R	Type OS/80X-BP-S-R	72.5	5.0	0.44 to 29	0.03 to 2.0	0.15 to 8.7	0.01 to 0.60
Type OS/80X-BPA-D-R	Type OS/80X-BPA-D-S-R	290	20.0				
Type OS/80X-MPA-D-R	Type OS/80X-MPA-D-S-R	1450	100	7.25 to 72.5	0.50 to 5.0	3.63 to 58	0.25 to 4.0
Type OS/80X-APA-D-R	Type OS/80X-APA-D-S-R			29 to 145	2.0 to 10.0	4.35 to 102	0.30 to 7.0
Type OS/84X-R	Type OS/84X-S-R			72.5 to 595	5.0 to 41.0	58 to 232	4.0 to 16.0
Type OS/88X-R	Type OS/88X-S-R			261 to 1160	18.0 to 80.0	116 to 1015	8.0 to 70.0
Type OS/80X-R-PN	Type OS/80X-S-R-PN			7.25 to 580	0.50 to 40.0	7.25 to 580	0.50 to 40.0
Type OS/84X-R-PN	Type OS/84X-S-R-PN			435 to 1160	30.0 to 80.0	435 to 1160	30.0 to 80.0

Table 4. Flow Coefficient for BM6X Series						
COEFFICIENT	NPS 3 / DN 80	NPS 4 / DN 100	NPS 6 / DN 150	NPS 8 / DN 200	NPS 10 / DN 250	NPS 12 / DN 300
C <sub>G</sub>	4500	9000	20,250	36,000	55,800	81,000
C <sub>I</sub>	24					

# BM6X Series

Axial Flow Slam-Shut Valve - Disk Closing, Manual Reset

TARTARINI




Figure 6. Dimensions

Table 5. OS/80X-R Series Pilot Material

SERVOMOTOR BODY	Types OS/80X-BP-R and OS/80X-BPA-D-R: Aluminum Types OS/80X-MPA-D-R and OS/80X-APA-D-R: Steel
DIAPHRAGM	Fabric-finished Nitrile (NBR)
O-RING	Nitrile (NBR)

Table 6. Types OS/84X-R and OS/88X-R Material

SERVOMOTOR BODY	Brass
LIP SEAL	Polytetrafluoroethylene (PTFE)
O-RING	Nitrile (NBR)

Table 7. PRX Series Pilot Material

BODY	Steel
DIAPHRAGM	Fabric-finished Nitrile (NBR)
O-RING	Nitrile (NBR)

Table 8. Dimension

DESIGNATION	DIMENSION												
	Body Size												
	NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 10 / DN 250		NPS 12 / DN 300		
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	
A	6.10	155	6.69	170	8.66	220	8.66	220	8.66	220	8.66	220	
B	9.84	250	11.4	290	16.3	415	17.5	445	18.9	480	20.1	510	
C	2.13	54	2.76	70	4.02	102	5.32	135	6.61	168	8	203	
CL150 RF	D	7.48	190	9.06	230	11	279	13.5	343	16	406	19	482
	E	3.74	95	4.53	115	5.51	140	6.77	172	8	203	9.5	241
	I	7.76	197	8.94	227	11.2	284	13.5	342	14.8	375	17.2	436
CL300 RF	D	8.27	210	10.0	254	12.5	318	15	381	17.5	445	20.5	521
	E	4.13	105	5.0	127	6.26	159	7.52	191	8.78	223	10.3	261
	I	8.54	217	9.65	245	11.9	303	14.2	361	16	407	18.4	468
CL600 RF	D	8.27	210	10.8	274	14.1	357	16.5	419	20	508	22	559
	E	4.13	105	5.39	137	7.05	179	8.66	220	10.0	254	11	280
	I	9.25	235	10.4	264	13.9	354	16.5	419	19.3	490	20.9	531

Note: Dimensions B are indicative and refer to the models with larger dimensions. The threaded opening for the connection of the control line is 1/4 NPT female.

Table 9. Shipping Weight

END CONNECTION STYLE	APPROXIMATE SHIPPING WEIGHT											
	Body Size											
	NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 10 / DN 250		NPS 12 / DN 300	
	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg
CL150 RF	22.0	10	28.7	13	48.5	22	72.8	33	104	47	179	81
CL300 RF	22.0	10	28.7	13	57.3	26	92.6	42	123	56	198	90
CL600 RF	22.0	10	33.1	15	72.8	33	112	51	187	85	276	125





## Ordering Guide (continued)

**Body Size (Select One)**

NPS 3 / DN 80\*\*\*

NPS 4 / DN 100\*\*\*

NPS 6 / DN 150\*\*\*

NPS 8 / DN 200\*\*\*

NPS 10 / DN 250\*\*\*

NPS 12 / DN 300\*\*\*

**End Connection Style (Select One)**

CL150 RF\*\*\*

CL300 RF\*\*\*

CL600 RF\*\*\*

**Elastomer Part (Select One)**

Nitrile (NBR)\*\*

Fluorocarbon (FKM)\*\*

**Pilot (Select One)**

Type OS/80X-BP-R\*\*\*

Type OS/80X-BPA-D-R\*\*\*

Type OS/80X-MPA-D-R\*\*\*

Type OS/80X-APA-D-R\*\*\*

Type OS/84X-R\*\*\*

Type OS/88X-R\*\*\*

Type OS/80X-R-PN\*\*\*

Type OS/84X-R-PN\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

**Orientation - Indicates Flow Direction (Select One)**

Flow from Left to Right (Clockwise Resetting)

Flow from Right to Left (Counterclockwise Resetting)

**Required Overpressure Setpoint (Specify)**

\_\_\_\_\_

**Required Underpressure Setpoint (Specify)**

\_\_\_\_\_

**Sour Gas Construction (Optional)**

Yes\*\*

No\*\*\*

**Accessories (Select All That Apply)**

Proximity Switch

Electrovalve

Type IT/3V 3-way valve

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**

Four easy ways to find the products you need . . .

1. Section headers at the top of each page are grouped by application of product (i.e., Natural Gas).
2. The Product Index at the back of this Application Guide contains a detailed list of products arranged by type and application.
3. If you know the application and product number, turn to the Application Map of that section and locate the Section Outline which indexes all of the products found in that section.
4. Look for the product type number in the Quick Reference Chart in the Table of Contents.

# BM7 Series

## Disk Slam-Shut Valve Manual Reset

TARTARINI™

### Introduction

The BM7 Series slam-shut valves are automatic isolating elements suitable for installation as safety devices in regulating stations. They assure easy installation and maintenance together with high accuracy.

### Body Sizes and End Connection Styles

See Table 1

### Flow Coefficients

See Table 4

### Allowable Inlet Pressure

Up to 203 psig / 14.0 bar

### Inlet Pressure Range

0 to 203 psig / 0 to 14.0 bar

### Slam-Shut Pressure Ranges

#### Versions with Type OS/66:

Minimum Pressure Set Range:

0.10 to 6.5 psig / 0.007 to 0.45 bar

Maximum Pressure Set Range:

0.36 to 8.7 psig / 0.022 to 0.60 bar

#### Versions with Type OS/66-AP:

Minimum Pressure Set Range:

1.45 to 36.3 psig / 0.10 to 2.5 bar

Maximum Pressure Set Range:

2.90 to 72.5 psig / 0.20 to 5.0 bar

### Maximum Capacity

36,194 SCFH / 970 Nm<sup>3</sup>/h

### Accuracy Class

Up to ±1%

### Response Time

≤ 1 second

### Temperature Capabilities

#### Standard Version:

Working: 14 to 140°F / -10 to 60°C

#### Low-Temperature Version:

Working: -4 to 140°F / -20 to 60°C

### Approximate Weights

See Table 5

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



### Features

- Ease of Installation
- Ease of Maintenance
- High Operation Accuracy




Figure 1. BM7 Series with Threaded Connection




Figure 2. BM7 Series with Flanged Connection

Table 1. Body Size and End Connection Style

TYPE	BODY SIZE		END CONNECTION STYLE
	NPS	DN	
BM7/1-1/2 in.	1-1/2	40	GAS
BM7/40-FS	1-1/2	40	PN 16 (with sliding flanges)
BM7/2 in.	2	50	GAS
BM7/50-F	2	50	PN 16

Table 2. Main Valve Construction Material

BODY	TYPE		CONSTRUCTION MATERIAL
		Type BM7/1-1/2-inch	Type BM7/40-FS
	Type BM7/2-inch	Type BM7/50-F	Cast iron
			Cast iron or Steel
SEAT			Brass

Table 3. Slam-Shut Device Construction Material

TYPE	DIAPHRAGM	COVER	BODY
OS/66 and OS/66-AP	Nitrile (NBR)	Steel	Aluminum

Table 4. Flow Coefficient

TYPE	C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>
BM7/1-1/2-inch	170	5.86	29
BM7/40-FS	170	5.86	29
BM7/2-inch	500	17.2	29
BM7/50-F	650	22.4	29




Figure 3. Dimensions

IN. /  
mm

Table 5. Dimension and Approximate Weight

TYPE	DIMENSION								APPROXIMATE WEIGHT	
	A		B		C		I		LBS	kg
	In.	mm	In.	mm	In.	mm	In.	mm		
<b>Threaded Connection</b>										
BM7/1-1/2 in.	6.50	165	2.24	57	3.54	90	5.12	130	6.6	3
BM7/2 in.	7.48	190	3.35	85	4.72	120	6.30	160	15.4	7
<b>Flanged Connection</b>										
BM7/40-FS	6.50	165	2.24	57	3.54	90	7.24	184	11	5
BM7/50-F	7.68	195	3.54	90	4.92	125	7.48	190	28.7	13

### Ordering Guide

**Type (Select One)**

- BM7/1-1/2 in.\*\*\*
- BM7/40-FS\*\*\*
- BM7/2 in.\*\*\*
- BM7/50-F\*\*\*

**Elastomer Part (Select One)**

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*

**Required Overpressure Setpoint**

\_\_\_\_\_ please specify

**Required Underpressure Setpoint**

\_\_\_\_\_ please specify

**Temperature Construction (Select One)**

- Standard\*\*\*
- Low Temperature\*\*

**Sour Gas Construction (Optional)**

- Yes\*\*
- No\*\*\*

**Accessory (Optional)**

- Proximity Switch

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**  
All regulators should be installed and used in accordance with federal, state and local codes and regulations.

### Introduction

In the gas pressure reduction process by the “Joule-Thomson” effect, temperature drops considerably about 33°F / 0.5°C per reduction bar are estimated.

This fall in gas temperature can damage equipment due to formation of dangerous ice crystals produced by water vapor in the gas.

In first stage stations in particular, gas must be heated before pressure is reduced, since high pressure changes are usually involved.

It is recommended that, after reduction, gas temperature should not be below 41°F / 5°C.

One of the best established methods of heating gas in reduction stations is to use heat exchangers employing hot water or steam as their thermal carrier fluid.

The heat exchangers we produce are sized and designed to meet a very wide range of system requirements, and include all connections for accessories.

### Available Configurations

**Water as Thermal Carrier Fluid:**  
CNF, CN and CF Series  
**Steam as Thermal Carrier Fluid:**  
SV Series

### Applications

- For pre-heating natural gas in first reception and reduction stations and for all gas heating requirements
- Non-Corrosive Gases
- Maximum Water Temperature: 194°F / 90°C (CNF, CN and CF Series)
- Maximum Steam Temperature: 248°F / 120°C (SV Series)

### Installation and Assembly

- Heat Exchangers designed for installation with vertical tube bundle
- Can be supplied with different tube bundle configurations upon request

### End Connections

See Table 1

### Features

- Tube Bundle Heat Exchangers Using U-tubes (BEU)
- Tube Bundle with Inspection Facility
- Gas in Tubes Section, Thermal Carrier Fluid in Shell Section
- Axial Connections in Gas Section
- Designed for Installation of Automatic Air Escape
- Designed for Installation of Relief Valve



Figure 1. Tube Bundle Heat Exchangers

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

Table 1. CNF, CN, CF and SV Series End Connections and Thermal Characteristics

RATING	DESIGN PRESSURE		HYDROSTATIC TEST		PNEUMATIC TEST	
	psig	bar	psig	bar	psig	bar
Gas Side						
CL300 RF	653	45.0	827	57.0	102	7.0
CL600 RF	1305	90.0	1639	113	102	7.0
Water or Steam Side						
UNI/DIN PN 6	73	5.0	----	----	109	7.5

Table 2. CNF, CN, CF and SV Series Construction Materials

SHELL ON GAS SECTION	FLANGE	BUILT-IN FLANGE	TUBE PLATE	STUD BOLT	NUT	CONNECTION	SEAL
Steel	Steel	Steel	Steel	Steel	Steel	Steel	Nitrile (NBR)

# CNF, CN, CF and SV Series

## Tube Bundle Heat Exchanger

TARTARINI™




Figure 2. Tube Bundle Heat Exchangers Operational Schematic




Figure 3. CNF, CN and CF Series Dimensions

Table 3. Types of Thermal Carrier Fluid

HOT WATER NATURAL CONVECTION <sup>(1)</sup>	HOT WATER FORCED CONVECTION <sup>(2)</sup>	STEAM <sup>(3)</sup>
Type CNF-05-AP Type CNF-1-AP Type CN2-AP	Type CNF-05-AP Type CNF-1-AP Type CF2-AP Type CF3-AP Type CF1-AP/5000 Type CF1-AP/8000 Type CF1-AP/12500 Type CF1-AP/17500	Type SV3-AP Type SV-AP/5000 Type SV-AP/8000 Type SV-AP/12500

1. Recommended for medium capacities up to a maximum of 45,000 Kcal/h.  
 2. Recommended for medium and large capacities up to a maximum of 75,000 Kcal/h.  
 3. Make sure steam pressure and temperature does not exceed 29 psia / 2.0 bar a and 248°F / 120°C respectively. If these values are exceeded, reduce them adequately before use. For these exchangers, it is normal practice to assume the same capacity as for those using forced circulation water.

Table 4. CNF, CN and CF Series Optional Connections

POSITION	QUANTITY	DESCRIPTION
1	1	Coupling 3/8 in. GAS-F
2	3	Thredolet 1/2 NPT
3	3	Coupling 1/2 in. GAS-M
4	2	Thredolet 1/4 NPT

Table 5. CNF, CN and CF Series Dimensions and Shipping Weights

TYPE	DIMENSION, in. / mm											APPROXIMATE SHIPPING WEIGHT, Lb / kg
	Gas Side		Water Side		A	B	C	D <sup>(1)</sup>	Ø E	F	L	
	Inlet (Maximum)	Outlet (Maximum)	Inlet (Maximum)	Outlet (Maximum)								
CNF-05-AP	1.97 / 50	1.97 / 50	1.97 / 50	1.97 / 50	74.0 / 1880	27.6 / 700	8.66 / 220	31.5 / 800	5.55 / 141	13.8 / 350	19.7 / 500	198 / 90
CNF-1-AP	3.94 / 100	3.94 / 100	2.56 / 65	2.56 / 65	76.0 / 1930	27.9 / 710	9.72 / 247	31.5 / 800	7.64 / 194	15.75 / 400	21.65 / 550	441 / 200
CN2-AP	4.92 / 125	4.92 / 125	3.15 / 80	3.15 / 80	97.2 / 2470	45.3 / 1150	12.6 / 320	31.5 / 800	8.62 / 219	16.54 / 420	25.6 / 650	562 / 255
CF2-AP	4.92 / 125	4.92 / 125	3.15 / 80	3.15 / 80	97.2 / 2470	45.3 / 1150	12.6 / 320	31.5 / 800	8.62 / 219	16.54 / 420	25.6 / 650	562 / 255
CF3-AP	5.91 / 150	5.91 / 150	3.15 / 80	3.15 / 80	102.2 / 2595	43.3 / 1100	16.9 / 430	31.5 / 800	10.75 / 273	23.6 / 600	31.5 / 800	683 / 310
CF1-AP/5000	7.87 / 200	7.87 / 200	3.15 / 80	3.15 / 80	100 / 2540	39.4 / 1000	16.7 / 425	31.5 / 800	12.75 / 324	23.6 / 600	31.5 / 800	1323 / 600
CF1-AP/8000	9.84 / 250	9.84 / 250	3.15 / 80	3.15 / 80	117.9 / 2995	41.3 / 1050	22.8 / 580	39.4 / 1000	18.0 / 457	31.5 / 800	43.3 / 1100	1984 / 900
CF1-AP/12500	11.8 / 300	11.8 / 300	5.91 / 150	5.91 / 150	120.1 / 3050	37.4 / 950	26.0 / 660	39.4 / 1000	20.0 / 508	31.5 / 800	47.2 / 1200	2866 / 1300
CF1-AP/17500	13.8 / 350	13.8 / 350	7.87 / 200	7.87 / 200	130.5 / 3315	37.4 / 950	32.3 / 820	39.4 / 1000	22.04 / 560	31.5 / 800	49.2 / 1250	2976 / 1350

1. Proposed height, variable according to installation needs.




Figure 4. SV Series Dimensions

Table 6. CNF, CN and CF Series Thermal Features

TYPE	EXCHANGE SURFACE		WATER SIDE VOLUME		GAS SIDE VOLUME		REFERENCE THERMAL CAPACITY Kcal/h
	ft <sup>2</sup>	m <sup>2</sup>	Gallon	Liter	Gallon	Liter	
CNF-05-AP	7.0	0.6	2.91	11.0	1.0	3.8	14,500
CNF-1-AP	14.7	1.4	6.08	23.0	3.17	12.0	29,000
CN2-AP	21.2	2.0	7.93	30.0	6.74	25.5	48,500
CF2-AP	21.2	2.0	7.93	30.0	6.74	25.5	64,500
CF3-AP	36.6	3.5	14.5	55.0	11.1	42.0	100,000
CF1-AP/5000	54	5.0	18.0	68.0	19.8	75.0	161,000
CF1-AP/8000	124	11.5	31.7	120	42.3	160	340,000
CF1-AP/12500	161	15.0	52.8	200	66.0	250	485,000
CF1-AP/17500	194	18.0	74.2	281	88.8	336	750,000

Notes: Thermal capacities are calculated with the following conditions:  
 • Gas inlet pressure: 73 to 1088 psig / 5.0 to 75.0 bar  
 • Gas reduced pressure: 58 psig / 4.0 bar  
 • Inlet gas temperature: 41°F / 5°C  
 • After reduction gas temperature: 41°F / 5°C  
 For different conditions contact your local Sales Office.

Table 7. SV Series Optional Connections

POSITION	QUANTITY	DESCRIPTION
1	1	Coupling 3/8 in. GAS-F
2	3	Thredolet 1/2 NPT
3	3	Coupling 1/2 in. GAS-M
4	2	Thredolet 1/4 NPT

Table 8. SV Series Dimensions and Shipping Weights (See Figure 4)

TYPE	DIMENSION, In. / mm											APPROXIMATE SHIPPING WEIGHT, Lb / kg
	Gas Side		Steam Side		A	B	C	D <sup>(1)</sup>	Ø E	F	L	
	Inlet (Maximum)	Outlet (Maximum)	Inlet (Maximum)	Outlet (Maximum)								
SV3-AP	4.92 / 125	4.92 / 125	3.15 / 80.0	3.15 / 80.0	98.34 / 2498	43.3 / 1100	16.9 / 430	31.5 / 800	10.75 / 273	23.6 / 600	31.5 / 800	683 / 310
SV-AP/5000	5.91 / 150	5.91 / 150	3.15 / 80.0	3.15 / 80.0	97.84 / 2485	39.4 / 1000	15.7 / 400	31.5 / 800	12.75 / 324	23.6 / 600	31.5 / 800	1323 / 600
SV-AP/8000	7.87 / 200	7.87 / 200	3.15 / 80.0	3.15 / 80.0	118 / 3000	41.3 / 1050	22.8 / 580	39.4 / 1000	18.0 / 457	31.5 / 800	43.3 / 1100	2425 / 1100
SV-AP/12500	9.84 / 250	9.84 / 250	4.92 / 125	4.92 / 125	118.9 / 3019	37.4 / 950	26.0 / 660	39.4 / 1000	20.0 / 508	31.5 / 800	47.2 / 1200	2535 / 1150

1. Proposed height, variable according to installation needs.

## Ordering Guide (continued)

**Table 9. SV Series Thermal Features**

TYPE	EXCHANGE SURFACE		WATER SIDE VOLUME		GAS SIDE VOLUME		REFERENCE THERMAL CAPACITY
	ft <sup>2</sup>	m <sup>2</sup>	Gallon	Liter	Gallon	Liter	Kcal/h
SV3-AP	37.6	3.5	6.60	25.0	10.6	40.0	100,000
SV-AP/5000	53.8	5.0	18.0	68.0	19.8	75.0	161,000
SV-AP/8000	124	11.5	31.7	120	42.3	160	340,000
SV-AP/12500	161	15.0	52.8	200	66.0	250	485,000

Notes: Thermal capacities are calculated with the following conditions:

- Gas inlet pressure: 73 to 1088 psig / 5.0 to 75.0 bar
- Gas reduced pressure: 58 psig / 4.0 bar
- Inlet gas temperature: 41°F / 5°C
- After reduction gas temperature: 41°F / 5°C

For different conditions contact your local Sales Office.

## Ordering Guide

### Type (Select One)

- CNF\*\*\*
- CN\*\*\*
- CF\*\*\*
- SV\*\*\*

### Elastomer Part (Select One)

- Nitrile (NBR)\*\*\*
- Fluorocarbon (FKM)\*\*

### Thermal Capacity

\_\_\_\_\_ please specify

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

For every 15 psid / 1.0 bar d pressure differential across the regulator, expect approximately a one degree drop in gas temperature due to the natural refrigeration effect. Freezing is often a problem when the ambient temperature is between 30 and 45°F / -1 and 7°C.



**Introduction**

The CP200 Series pressure loaded regulators have been engineered to fit a multitude of pressure-reducing applications including commercial and industrial installations. This flexibility is provided by the various body end connection sizes, outlet pressure settings and orifice sizes. The CP200 Series provides accurate control for use in pressure-factor measurement (fixed factor billing) applications.

**Available Configurations**

See Table 1

**Body Size and End Connection Style**

See Table 2

**Inlet Pressure Ratings**

See Table 5

**Maximum Outlet Pressure**

**Emergency Casing:** 25 psig / 1.7 bar  
**Operating:** 20 psig / 1.4 bar

**Outlet Pressure Ranges**

1 to 20 psig / 69 mbar to 1.4 bar  
See Table 6

**Flow and Sizing Coefficients**

See Table 7

**Pressure Loading Regulator (Type 67CP) Spring Case Connection**

1/4 NPT

**Temperature Capabilities**

-20 to 150°F / -29 to 66°C

**Pressure Registration**



Internal

**Approximate Shipping Weight**

10 lbs / 5 kg

**Features**

- **Fixed Factor / Pressure Factor Measurement (PFM) Accuracy Capabilities**
- **Easy to Install and Maintain**
- **Only Standard Tools Required for Pressure Adjustment and Orifice Removal**
- **Wide Range of NPT Body Sizes**
- **Highly Configurable**
- **Secondary Seat™ Protection**



**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



12/13

# CP200 Series

## Pressure Reducing Regulator

FISHER™

**Table 1. Available Configuration**

TYPE NUMBER				OPTION	
C	P	2	0		
					<b>OVERPRESSURE PROTECTION MODULE</b>
			0		Without Overpressure Protection Module
			5		With Secondary Seat™ Protection
			6		With Secondary Seat Protection with bleed to indicate Secondary Seat is functioning
					<b>PRESSURE REGISTRATION</b>
				I	Internal Registration
					<b>RELIEF</b>
				N	Non-Relief
				T	Token Internal Relief

**Table 2. Body Size, Material, End Connection Style and Pressure Rating**

SERIES	BODY SIZE	END CONNECTION STYLE	BODY MATERIAL	FACE-TO-FACE DIMENSION		PRESSURE RATING	
				In.	mm	psig	bar
CP200	3/4	NPT	Gray Cast Iron	4	102	175	12,1
	3/4 x 1						
	3/4 x 1-1/4						
	1						
	1 x 1-1/4						
1-1/4							

**Table 3. Main Valve and Actuator Construction Material**

BODY	BODY O-RING, DIAPHRAGM AND DISK	CLOSING CAP, ADJUSTING SCREW, DIAPHRAGM CASE, SPRING CASE AND ORIFICE	DIAPHRAGM PLATE	LEVER	PUSHER POST	LEVER PIN
Gray Cast Iron	Nitrile (NBR)	Aluminum	Steel	Zinc-plated Steel	Aluminum	18-8 Stainless steel

**Table 4. Type 67CP Pressure Loading Regulator Construction Material**

BODY	SPRING	VALVE STEM	O-RING, SOFT SEAT	ADJUSTING SCREW AND SPRING SEAT
Aluminum	302 Stainless steel	316 Stainless steel	Nitrile (NBR)	Steel

**Table 5. Orifice Size and Inlet Pressure Rating**

SERIES	ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE	
	In.	mm	psig	bar
CP200	1/8	3.2	125	8.6
	3/16	4.8	125	8.6
	1/4	6.4	125	8.6
	3/8	9.5	60	4.1
	1/2	13	40	2.8

**Table 6. Outlet Pressure Range**

SPRING RANGE <sup>(1)</sup>		PART NUMBER	COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
psig	bar			In.	mm	In.	mm
1 to 2	69 mbar to 0.14 bar	GE30199X012	Yellow Stripe	0.078	2.0	1.35	34.3
2 to 5	0.14 to 0.34	GE27213X012	Orange Stripe	0.100	2.5	1.47	37.3
5 to 10	0.34 to 0.69	GE39890X012	Black Stripe	0.114	2.9	1.47	37.3
10 to 20	0.69 to 1.4	GE30200X012	Purple Stripe	0.137	3.5	1.42	36.1

1. Spring range is controlled by Type 67CP pressure loading regulator.

**Table 7. Flow and Sizing Coefficient**

SERIES	ORIFICE SIZE		FLOW COEFFICIENT (WIDE-OPEN)			IEC SIZING COEFFICIENT		
	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	X <sub>r</sub>	F <sub>0</sub>	F <sub>L</sub>
CP200	1/8	3.2	12	0.40	30	0.53	0.87	0.89
	3/16	4.8	24	0.80	30	0.58	0.82	
	1/4	6.4	44	1.52	29	0.53	0.85	
	3/8	9.5	102	3.30	31	0.60	0.83	
	1/2	13	172	4.40	39	0.97	0.72	



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
1 psig	-0.16 psi	0.16 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
69 mbar	-11 mbar	11 mbar	69 mbar to 0.14 bar	

**Table 8. CP200 Series Flow Capacities for 1 psig / 69 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 3/4 and 1 NPT									
3	0.21	160	4.2	310	8.3	460	12.3	850	22.8	1300	34.8
5	0.34	210	5.6	440	11.8	760	20.4	1200	32.2	1500	40.2
10	0.69	320	8.5	730	19.5	1100	29.5	2100	56.3	2100	56.3
15	1.0	410	11.0	890	23.8	1500	40.2	2500	67.1	2500	67.1
20	1.4	490	13.1	1000	26.8	1800	48.3	2800	75.1	2700	72.4
30	2.1	630	16.9	1400	37.5	2400	64.4	3000	80.5	2800	75.1
40	2.8	740	19.8	1700	45.6	2800	75.1	3000	80.5		
50	3.4	920	24.6	2000	53.6	3100	83.2	3100	83.2		
60	4.1	1000	26.8	2300	61.7	3300	88.5	3100	83.2		
80	5.5	1300	34.8	3000	80.5	3300	88.5				
100	6.9	1600	42.9	3100	83.2	3300	88.5				
125	8.6	2000	53.6	3100	83.2	1300	34.8				
psig	bar	Body Size: 1-1/4 NPT									
3	0.21	160	4.2	310	8.3	460	12.3	850	22.8	1400	37.5
5	0.34	210	5.6	440	11.8	800	21.4	1600	42.9	2100	56.3
10	0.69	320	8.5	730	19.5	1300	34.8	2500	67.1	2800	75.1
15	1.0	410	11.0	890	23.8	1600	42.9	3000	80.5	3000	80.5
20	1.4	490	13.1	1000	26.8	1900	51.0	3000	80.5	3000	80.5
30	2.1	630	16.9	1400	37.5	2500	67.1	3000	80.5	3000	80.5
40	2.8	740	19.8	1700	45.6	3000	80.5	3000	80.5		
50	3.4	920	24.6	2000	53.6	3200	85.9	3200	85.9		
60	4.1	1000	26.8	2300	61.7	3200	85.9	3200	85.9		
80	5.5	1300	34.8	3000	80.5	4200	113				
100	6.9	1600	42.9	3300	88.5	4200	113				
125	8.6	2000	53.6	3300	88.5	4200	113				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
Shaded areas indicate values that are limited due to boost effects.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.14 bar	-12 mbar	12 mbar	69 mbar to 0.14 bar	

**Table 9. CP200IN Series Flow Capacities for 2 psig / 0.14 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 3/4 and 1 NPT									
5	0.34	190	5.1	410	11.0	780	20.9	1400	37.5	1900	51.0
10	0.69	330	8.8	580	15.5	1200	32.2	2600	69.7	2900	77.8
15	1.0	420	11.2	770	20.6	1600	42.9	3200	85.9	3200	85.9
20	1.4	500	13.4	1000	26.8	1900	51.0	3200	85.9	3200	85.9
30	2.1	630	16.9	1300	34.8	2500	67.1	3200	85.9	3200	85.9
40	2.8	790	21.2	1600	42.9	3100	83.2	4200	113		
50	3.4	930	24.9	1800	48.3	3700	99.3	4200	113		
60	4.1	1000	26.8	1800	48.3	4200	113	4200	113		
80	5.5	1300	34.8	1800	48.3	4200	113				
100	6.9	1600	42.9	1800	48.3	4200	113				
125	8.6	1800	48.3	1800	48.3						
psig	bar	Body Size: 1-1/4 NPT									
5	0.34	190	5.1	420	11.2	780	20.9	1400	37.5	1900	51.0
10	0.69	330	8.8	580	15.5	1200	32.2	2600	69.7	2900	77.8
15	1.0	420	11.2	770	20.6	1600	42.9	3200	85.9	3200	85.9
20	1.4	500	13.4	1000	26.8	1900	51.0	3200	85.9	3200	85.9
30	2.1	630	16.9	1300	34.8	2500	67.1	3200	85.9	3200	85.9
40	2.8	790	21.2	1600	42.9	3100	83.2	4200	113		
50	3.4	930	24.9	1800	48.3	3700	99.3	4200	113		
60	4.1	1000	26.8	1800	48.3	4200	113	4200	113		
80	5.5	1300	34.8	1800	48.3	4200	113				
100	6.9	1600	42.9	1800	48.3	4200	113				
125	8.6	1800	48.3	1800	48.3						

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CP200 Series

## Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
5 psig	-0.2 psi	0.2 psi	2 to 5 psig	GE27213X012 / Orange Stripe
0.34 bar	-14 mbar	14 mbar	0.14 to 0.34 bar	

**Table 10. CP200 Series Flow Capacities for 5 psig / 0.34 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		Body Size: 3/4 and 1 NPT									
psig	bar										
10	0.69	270	7.2	560	15.0	960	25.7	2000	53.6	2900	77.8
15	1.0	370	9.9	870	23.3	1500	40.2	3100	83.2	3800	102
20	1.4	470	12.6	1000	26.8	1900	51.0	3900	105	3900	105
30	2.1	620	16.6	1400	37.5	2400	64.4	4300	115	4300	115
40	2.8	770	20.6	1700	45.6	3000	80.5	4300	115		
50	3.4	940	25.2	1900	51.0	3600	96.6	4300	115		
60	4.1	1000	26.8	2000	53.6	4300	115	4300	115		
80	5.5	1300	34.8	2000	53.6	4300	115				
100	6.9	1600	42.9	2000	53.6	4300	115				
125	8.6	2000	53.6	2000	53.6						
		Body Size: 1-1/4 NPT									
psig	bar										
10	0.69	270	7.2	560	15.0	1000	26.8	2000	53.6	3000	80.5
15	1.0	370	9.9	870	23.3	1500	40.2	3200	85.9	3800	102
20	1.4	470	12.6	1000	26.8	1900	51.0	4000	107	3900	105
30	2.1	620	16.6	1400	37.5	2600	69.7	4300	115	4300	115
40	2.8	770	20.6	1700	45.6	3000	80.5	5300	142		
50	3.4	940	25.2	1900	51.0	3700	99.3	5300	142		
60	4.1	1000	26.8	2000	53.6	4300	115	5300	142		
80	5.5	1300	34.8	2000	53.6	4300	115				
100	6.9	1600	42.9	2000	53.6	4300	115				
125	8.6	2000	53.6	2000	53.6						

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
10 psig	-0.25 psi	0.25 psi	5 to 10 psig	GE39890X012 / Black Stripe
0.69 bar	-17 mbar	17 mbar	0.34 to 0.69 bar	

**Table 11. CP200 Series Flow Capacities for 10 psig / 0.69 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		Body Size: 3/4 and 1 NPT									
psig	bar										
15	1.0	260	6.9	580	15.5	1000	26.8	1600	42.9	2500	67.1
20	1.4	410	11.0	880	23.6	1500	40.2	2900	77.8	3100	83.2
30	2.1	590	15.8	1200	32.2	2200	59.0	3800	102	4100	110
40	2.8	760	20.4	1500	40.2	2900	77.8	4200	113		
50	3.4	900	24.1	1900	51.0	3600	96.6	4700	126		
60	4.1	990	26.5	2300	61.7	4000	107	4700	126		
80	5.5	1300	34.8	2900	77.8	5200	139				
100	6.9	1600	42.9	3500	93.9	5200	139				
125	8.6	1900	51.0	4500	121	5200	139				
		Body Size: 1-1/4 NPT									
psig	bar										
15	1.0	260	6.9	580	15.5	1000	26.8	2500	67.1	3400	91.2
20	1.4	410	11.0	880	23.6	1700	45.6	3200	85.9	4400	118
30	2.1	590	15.8	1200	32.2	2200	59.0	5000	134	5000	134
40	2.8	760	20.4	1500	40.2	3100	83.2	6100	164		
50	3.4	900	24.1	1900	51.0	3700	99.3	6900	185		
60	4.1	990	26.5	2300	61.7	4300	115	8000	215		
80	5.5	1300	34.8	2900	77.8	5200	139				
100	6.9	1600	42.9	3500	93.9	5200	139				
125	8.6	1900	51.0	4500	121	5200	139				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
15 psig	-0.3 psi	0.3 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.0 bar	-20 mbar	20 mbar	0.69 to 1.4 bar	

**Table 12. CP200 Series Flow Capacities for 15 psig / 1.0 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 3/4 and 1 NPT									
20	1.4	360	9.6	460	12.3	1200	32.2	2300	61.7	2800	75.1
30	2.1	580	15.5	1200	32.2	2200	59.0	4000	107	4200	113
40	2.8	690	18.5	1600	42.9	2900	77.8	4900	131		
50	3.4	890	23.8	2000	53.6	3500	93.9	5100	137		
60	4.1	1000	26.8	2300	61.7	4000	107	5900	158		
80	5.5	1300	34.8	2900	77.8	5100	137				
100	6.9	1500	40.2	3600	96.6	6200	166				
125	8.6	1800	48.3	4400	118	7500	201				
psig	bar	Body Size: 1-1/4 NPT									
20	1.4	360	9.6	460	12.3	1200	32.2	2700	72.4	4100	110
30	2.1	580	15.5	1200	32.2	2200	59.0	4900	131	6000	161
40	2.8	690	18.5	1600	42.9	2900	77.8	6300	169		
50	3.4	890	23.8	2000	53.6	3500	93.9	7500	201		
60	4.1	1000	26.8	2300	61.7	4000	107	8200	220		
80	5.5	1300	34.8	2900	77.8	5100	137				
100	6.9	1500	40.2	3600	96.6	6200	166				
125	8.6	1800	48.3	4400	118	7500	201				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
20 psig	-0.35 psi	0.35 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.4 bar	-24 mbar	24 mbar	0.69 to 1.4 bar	

**Table 13. CP200 Series Flow Capacities for 20 psig / 1.4 bar Setpoint**


CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 3/4 and 1 NPT									
30	2.1	560	15.0	1100	29.5	1900	51.0	3800	102	4100	110
40	2.8	740	19.8	1600	42.9	2700	72.4	4800	129		
50	3.4	840	22.5	1900	51.0	3300	88.5	5900	158		
60	4.1	1000	26.8	2300	61.7	4000	107	6700	180		
80	5.5	1300	34.8	2900	77.8	5200	139				
100	6.9	1600	42.9	3600	96.6	6300	169				
125	8.6	2000	53.6	4400	118	7700	207				
psig	bar	Body Size: 1-1/4 NPT									
30	2.1	560	15.0	1100	29.5	1900	51.0	4100	110	5600	150
40	2.8	740	19.8	1600	42.9	2700	72.4	6400	172		
50	3.4	840	22.5	1900	51.0	3300	88.5	7300	196		
60	4.1	1000	26.8	2300	61.7	4000	107	8800	236		
80	5.5	1300	34.8	2900	77.8	5200	139				
100	6.9	1600	42.9	3600	96.6	6300	169				
125	8.6	2000	53.6	4400	118	7700	207				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CP200 Series

## Pressure Reducing Regulator

FISHER™



GE34260

Figure 3. Dimensions

Table 14. Dimension

BODY SIZE, NPT		DIMENSION			
Inlet	Outlet	B		C	
		In.	mm	In.	mm
3/4	3/4	5.84	148	9.89	251
3/4	1				
1					
3/4	1-1/4	6.02	153	10.1	257
1					
1-1/4					

## Ordering Guide

Type (Select One)
<input type="checkbox"/> CP200IN (without token relief)***
<input type="checkbox"/> CP200IT (with token relief)
<input type="checkbox"/> CP205IN (without token relief and with Secondary Seat™ Protection)
<input type="checkbox"/> CP205IT (with token relief and Secondary Seat Protection)
<input type="checkbox"/> CP206IT (with token relief and Secondary Seat Protection with bleed to indicate Secondary Seat is functioning)

Body Size and End Connection Style (Select One)
<input type="checkbox"/> 3/4 NPT***
<input type="checkbox"/> 3/4 x 1 NPT***
<input type="checkbox"/> 3/4 x 1-1/4 NPT***
<input type="checkbox"/> 1 NPT***
<input type="checkbox"/> 1 x 1-1/4 NPT***
<input type="checkbox"/> 1-1/4 NPT***

Outlet Pressure Range (Select One)
<b>Type 67CP (without token relief)</b>
<input type="checkbox"/> 1 to 2 psig / 69 mbar to 0.14 bar, Yellow Stripe***
<input type="checkbox"/> 2 to 5 psig / 0.14 bar to 0.34 bar, Orange Stripe***
<input type="checkbox"/> 5 to 10 psig / 0.34 to 0.69 bar, Black Stripe***
<input type="checkbox"/> 10 to 20 psig / 0.69 to 1.4 bar, Purple Stripe***

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Orifice Size (Select One)
<input type="checkbox"/> 1/8 in. / 3.2 mm***
<input type="checkbox"/> 3/16 in. / 4.8 mm***
<input type="checkbox"/> 1/4 in. / 6.4 mm***
<input type="checkbox"/> 3/8 in. / 9.5 mm***
<input type="checkbox"/> 1/2 in. / 13 mm***

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Fixed factor measurement (or PFM) requires the regulator to maintain outlet pressure within ±1% of absolute pressure. For example: Setpoint of 2 psig + 14.7 psia = 16.7 psia x 0.01 = ±0.167 psi. (Setpoint of 0.14 bar + 1.01 bar = 1.15 bar x 0.01 = ±0.0115 bar.) Regulating Cg (coefficient of flow) can only be used for calculating flow capacities on pilot-operated regulators. Use capacity tables or flow charts for determining a direct-operated regulator's capacity.

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

### Introduction

The CP400 Series pressure loaded regulators have been engineered to fit a multitude of pressure-reducing applications including commercial and light industrial installations. This flexibility is provided by the numerous body end connection sizes, body materials, outlet pressure settings and orifice sizes. The CP400 Series provides accurate control for use in pressure-factor measurement (fixed factor billing) applications.

### Body Size, End Connection Style and Pressure Rating

See Table 2

### Flow Capacities

#### Type CP400:

See Tables 12 through 17, 20 through 25

#### Types CP403 and CP404:

See Tables 18, 19, 26 and 27

### Flow and Sizing Coefficients

See Table 7

### Inlet Pressure Ratings

See Table 5

### Maximum Outlet Pressure

**Emergency (Casing):** 25 psig / 1.7 bar

#### Operating:

Types CP400 and CP404: 20 psig / 1.4 bar

Type CP403: 7.5 psig / 0.52 bar

#### To Avoid Internal Parts Damage:

Types CP400 and CP404: 25 psig / 1.7 bar

Type CP403: 5 psig / 0.34 bar

over setpoint

### Outlet Pressure Range

1 to 20 psig / 0.07 to 1.4 bar

See Table 6

### Pressure Loading Regulator (Type 67CP) Spring Case Connection

1/4 NPT

### Pressure Registrations

Types CP400IN and CP400IT: Internal

Types CP400EN and CP400ET: External

### Temperature Capabilities

-20 to 150°F / -29 to 66°C

### Approximate Shipping Weight With Threaded Body

Type CP400: 11 lbs / 5 kg

Type CP403: 20.5 lbs / 9 kg


Type CP404: 13.2 lbs / 6 kg

#### With Flanged Body:

Add 8.6 lbs / 3.9 kg to above listed weights

### Additional Technical Data

Scan or Click the QR code for more information on this product.




[www.Emerson.com](http://www.Emerson.com)

09/14


### Features

- Fixed Factor / Pressure Factor Measurement (PFM) Accuracy Capabilities
- Easy to Install and Maintain
- Only Standard Tools Required for Pressure Adjustment and Orifice Removal
- Wide Variety of Body Sizes and End Connections



P1182

Figure 1. Typical Type CP400 Pressure Loaded Pressure Reducing Regulator



P1562

Figure 2. Typical Type CP400 Regulator Cut-Away View






Figure 3. Type CP400EN External Registration for Downstream Control Line

Table 1. Available Configurations

TYPE NUMBER					OPTION
C	P	4	0		
					<b>OVERPRESSURE PROTECTION MODULE</b>
			0		Without Overpressure Protection Module
			3		With Integral Monitor Module <sup>(1)</sup>
			4		With Slam-Shut Module <sup>(2)</sup>
					<b>PRESSURE REGISTRATION</b>
				E	External Registration
				I	Internal Registration
					<b>RELIEF</b>
				N	Non-Relief
				T	Token Internal Relief
Example: Type number <b>CP404IT</b> : CP400 regulator constructed with Type VSX4 Slam-Shut module, with Internal pressure registration and with Token relief.					
1. Reference Instruction Manual D103126X012 for information regarding the Integral Monitor module.					
2. Reference Instruction Manual D103127X012 for information regarding the Type VSX4 safety shutoff module.					

Table 2. Body Sizes, Materials, End Connections and Pressure Ratings

TYPE	BODY MATERIAL	BODY SIZE, IN.	END CONNECTION STYLE	FACE-TO-FACE DIMENSION		PRESSURE RATING			
				In.	mm	psig	bar		
CP400	Gray Cast Iron	1-1/4	NPT	4.5	114	175	12.1		
		1-1/2							
		2	NPT	5	127				
		NPS 2 / DN 50						CL125 FF	10
CP400, CP403 and CP404	Ductile Iron	1-1/4	NPT	4.5	114	290	20.0		
		1-1/2							
		2	NPT	5	127				
		1-1/4						Rp	4.5
		1-1/2							
		2	5	127					
		NPS 2 / DN 50	CL125 FF / CL150 FF	10	254			290	20.0
		NPS 2 / DN 50	PN 10/16	10	254			232	16.0
	Steel	NPT	1-1/4	4.5	114	290	20.0		
			1-1/2						
		Rp	1-1/4	7.5	191				
			1-1/2					10	254

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

**Table 3. Main Valve and Actuator Construction Material**

BODY	Gray Cast Iron, Ductile Iron and Steel
BODY O-RING	Nitrile (NBR)
CLOSING CAP	Aluminum
ADJUSTING SCREW	Aluminum
DIAPHRAGM CASE, SPRING CASE, DIAPHRAGM PLATE AND VALVE STEM	Aluminum
ORIFICE	Aluminum
PUSHER POST	Aluminum
DIAPHRAGM AND DISK	Nitrile (NBR)
CONTROL SPRING	Stainless Steel
LEVER	Steel

**Table 4. 67CP Series Construction Material**

BODY	Aluminum
SPRING	Music Wire or Stainless Steel
VALVE STEM	Aluminum
O-RING, SOFT SEAT AND DIAPHRAGM	Nitrile (NBR)

**Table 5. Orifice Size and Inlet Pressure Rating**

ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE <sup>(1)</sup>	
In.	mm	psig	bar
3/16	4.8	125	8.6
1/4	6.4	125	8.6
3/8	9.5	80	5.5
1/2	13	60	4.1
5/8	16	50	3.4
3/4	19	40	2.8

1. The pressure/temperature limits in this Application Guide or any applicable standard limitation should not be exceeded.

**Table 6. Outlet Pressure Range**

TYPE	OUTLET PRESSURE RANGE <sup>(1)</sup>		PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	psig	bar			In.	mm	In.	mm
CP400, CP403 <sup>(2)</sup> and CP404	1 to 2	0.07 to 0.14	GE30199X012	Yellow Stripe	0.085	2.16	1.47	37.3
	2 to 5	0.14 to 0.34	GE27213X012	Orange Stripe	0.096	2.44	1.47	37.3
CP400 and CP404	5 to 10	0.34 to 0.69	GE39890X012	Black Stripe	0.114	2.90	1.47	37.3
	10 to 20	0.69 to 1.4	GE30200X012	Purple Stripe	0.137	3.48	1.43	36.3

1. Outlet pressure range is controlled by Type 67CP loading pressure regulator spring.

2. Maximum operating outlet pressure for the integral True-Monitor™ installed on the Type CP403 is 7.5 psig / 0.52 bar.

**Table 7. Flow and Sizing Coefficients**

ORIFICE SIZE		WIDE-OPEN FLOW COEFFICIENT			IEC SIZING COEFFICIENT		
In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	X <sub>r</sub>	F <sub>L</sub>	F <sub>D</sub>
3/16	4.8	27	0.97	27.7	0.50	0.89	0.91
1/4	6.4	50	1.77	28.2	0.50		0.92
3/8	9.5	113	3.72	30.4	0.58		0.89
1/2	13	182	5.61	32.4	0.66		0.82
5/8	16	284	7.26	39.1	0.97		0.74
3/4	19	356	9.83	36.2	0.83		0.72



**Table 8. CP404 Series Regulator and Slam-Shut Spring Ranges Overpressure Shutoff (OPSO) Only**

TYPE	REGULATOR				SLAM-SHUT						
	Typical Setpoint		Spring Range <sup>(1)</sup>		Overpressure Shutoff (OPSO)						
					Typical Setpoint		Spring Range		Spring Part Number		
	psig	bar	psig	bar	psig	bar	psig	bar			
CP404IN, CP404IT, CP404EN and CP404ET	1	0.07	1 to 2	0.07 to 0.14	5	0.34	2 to 7.3	0.14 to 0.50	GF02172X012		
	2	0.14			5.5	0.38					
	3	0.21	2 to 5	0.14 to 0.34	8.5	0.59	3.2 to 11	0.22 to 0.76		GF02173X012	
	4	0.28			9.5	0.66					
	5	0.34			10.5	0.72					
	CP404IN and CP404EN	6	0.41	5 to 10	0.34 to 0.69	11.5	0.79	5.8 to 21		0.40 to 1.4	GF04353X012
		7	0.48			14	0.97				
10		0.69	17			1.2					
12		0.83	18			1.2					
15		1.0	20			1.4					
	20	1.4	10 to 20	0.69 to 1.4	25	1.7	13.1 to 43.5	0.90 to 3.0	GF02173X012		

1. Token Relief is not available with the 10 to 20 psig / 0.69 to 1.4 bar spring range.

**Table 9. CP404 Series Regulator and Slam-Shut Spring Ranges Overpressure and Underpressure Shutoff (OPSO and UPSO)**

TYPE	REGULATOR				SLAM-SHUT												
	Typical Setpoint		Spring Range <sup>(1)</sup>		Overpressure Shutoff (OPSO)					Underpressure Shutoff (UPSO)							
					Typical Setpoint		Spring Range		Spring Part Number	Typical Setpoint		Spring Range		Spring Part Number			
	psig	bar	psig	bar	psig	bar	psig	bar		psig	bar	psig	bar				
CP404IN, CP404IT, CP404EN and CP404ET	1	0.07	1 to 2	0.07 to 0.14	5	0.34	2.2 to 5.5	0.15 to 0.38	GF02170X012	0.5	0.03	0.36 to 2.3	0.03 to 0.16	T14170T0012			
	2	0.14			5.5	0.38				1	0.07						
	3	0.21	2 to 5	0.14 to 0.34	8.5	0.59	5.8 to 16	0.40 to 1.1		GF02172X012	2	0.14	1.5 to 7.3		0.10 to 0.50	FA142869X12	
	4	0.28			9.5	0.66					3	0.21					
	5	0.34			10.5	0.72					4	0.28					
	CP404IN and CP404EN	6	0.41	5 to 10	0.34 to 0.69	11.5	0.79	11.6 to 3.2		0.80 to 1.6	GF02173X012	4.5	0.31		1.5 to 10.9	0.10 to 0.75	T14171T0012
		7	0.48			14	0.97					5.5	0.38				
10		0.69	17			1.2	8		0.55								
12		0.83	18			1.2	9		0.62								
15		1.0	10 to 20			0.69 to 1.4	20		1.4			10	0.69				
	20	1.4	16 to 29	1.1 to 2.0	25	1.7	GF02171X012	14	0.96	7.3 to 29	0.50 to 2.0	FA142869X12					

1. Token Relief is not available with the 10 to 20 psig / 0.69 to 1.4 bar spring range.

**Table 10. CP403 Series Spring Ranges (Without Token Relief)**

TYPE	PRIMARY REGULATOR					INTEGRAL MONITOR				
	Typical Setpoint		Spring Range		Spring Color	Minimum Setpoint		Spring Range		Spring Color
	psig	bar	psig	bar		psig	bar	psig	bar	
CP403IN and CP403EN	1	0.07	1 to 2	0.07 to 0.14	Yellow Stripe	2	0.14	1.4 to 2.9	0.10 to 0.20	Black
	2	0.14				3	0.21	2.6 to 3.7	0.18 to 0.26	Purple
	3	0.21	2 to 5	0.14 to 0.34	Orange Stripe	5	0.34	3.6 to 6	0.25 to 0.40	Dark Blue
	4	0.28				6	0.41	5.1 to 7.5	0.35 to 0.52	Red
	5	0.34				7	0.48			

**Table 11. CP403 Series Spring Ranges (With Token Relief)**

TYPE	PRIMARY REGULATOR					INTEGRAL MONITOR				
	Typical Setpoint		Spring Range		Spring Color	Minimum Setpoint		Spring Range		Spring Color
	psig	bar	psig	bar		psig	bar	psig	bar	
CP403IT and CP403ET	1	0.07	1 to 2	0.07 to 0.14	Yellow Stripe	5	0.34	3.6 to 6	0.25 to 0.40	Dark Blue
	2	0.14				5.5	0.38	5.1 to 7.5	0.35 to 0.52	Red

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
1 psig	-0.16 psi	0.16 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.07 bar	-11 mbar	11 mbar	0.07 to 0.14 bar	

**Table 12. CP400 Series Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4 / DN 32											
3	0.21	310	8.31	500	13.4	940	25.2	1400	37.5	2300	61.6	2400	64.3
5	0.34	520	13.9	970	26.0	1900	50.9	2200	59.0	3500	93.8	3800	102
10	0.69	850	22.8	1500	40.2	2800	75.0	4100	110	5800	155	6000	161
15	1.0	1000	26.8	1800	48.2	3900	105	5700	153	6000	161	6000	161
20	1.3	1200	32.2	2000	53.6	4700	126	6000	161	6000	161	6000	161
30	2.0	1500	40.2	2800	75.0	6000	161	6000	161	5100	137	5500	147
40	2.7	1900	50.9	3300	88.4	6000	161	5200	139	5100	137	5500	147
50	3.4	2200	59.0	3900	105	6000	161	3200	85.8	5100	137		
60	4.1	2400	64.3	4500	121	3200	85.8	3200	85.8				
80	5.5	3300	88.4	5500	147	3200	85.8						
100	6.8	4000	107	7300	196								
125	8.6	4800	129	8400	225								
psig	bar	Body Size: NPS 1-1/2 / DN 40											
3	0.21	390	10.5	590	15.8	1300	34.8	1600	42.9	1600	42.9	2100	56.3
5	0.34	520	13.9	930	24.9	1900	50.9	2900	77.7	3300	88.4	3300	88.4
10	0.69	840	22.5	1300	34.8	2900	77.7	4900	131	5200	139	5200	139
15	1.0	1000	26.8	1600	42.9	3600	96.5	4600	123	6400	172	6400	172
20	1.3	1200	32.2	1900	50.9	4600	123	4600	123	7600	204	8200	220
30	2.0	1600	42.9	2700	72.4	4600	123	4600	123	3700	99.2	10,100	271
40	2.7	1800	48.2	3400	91.1	4600	123	3100	83.1	3500	93.8	12,000	322
50	3.4	2200	59.0	4000	107	4000	107	3100	83.1	3500	93.8		
60	4.1	2500	67.0	4300	115	3800	102	3000	80.4				
80	5.5	3300	88.4	5400	145	3800	102						
100	6.8	4000	107	5600	150								
125	8.6	4900	131	7900	212								
psig	bar	Body Size: NPS 2 / DN 50											
3	0.21	410	11.0	570	15.3	1100	29.5	1700	45.6	1700	45.6	2400	64.3
5	0.34	550	14.7	890	23.9	1900	50.9	2900	77.7	3100	83.1	4200	113
10	0.69	820	22.0	1400	37.5	3100	83.1	4700	126	6300	169	4200	113
15	1.0	1000	26.8	1800	48.2	4000	107	5600	150	10,700	287	5600	150
20	1.3	1200	32.2	2100	56.3	4800	129	5600	150	10,700	287	9700	260
30	2.0	1500	40.2	2800	75.0	5600	150	5600	150	10,700	287	7300	196
40	2.7	1900	50.9	3400	91.1	5600	150	5600	150	8500	228	5400	145
50	3.4	2300	61.6	4000	107	5600	150	5600	150	5700	153		
60	4.1	2600	69.7	4600	123	5600	150	5600	150				
80	5.5	3300	88.4	5600	150	5600	150						
100	6.8	4100	110	6500	174								
125	8.6	5000	134	7000	188								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.14 bar	-12 mbar	12 mbar	0.07 to 0.14 bar	

**Table 13. CP400 Series Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4 / DN 32											
5	0.34	470	12.6	970	26.0	1400	37.5	1900	50.9	2700	72.4	3800	102
10	0.69	800	21.4	1300	34.8	2800	75.0	4100	110	5200	139	7100	190
15	1.0	1000	26.8	1800	48.2	3800	102	5000	134	5700	153	7200	193
20	1.3	1200	32.2	2100	56.3	4700	126	5000	134	5700	153	7200	193
30	2.0	1500	40.2	2700	72.4	6000	161	3200	85.8	5700	153	7200	193
40	2.7	1900	50.9	3300	88.4	6000	161	3200	85.8	5700	153	7200	193
50	3.4	2200	59.0	3900	105	6000	161	3200	85.8	5700	153		
60	4.1	2500	67.0	4200	113	4500	121	3200	85.8				
80	5.5	3300	88.4	4200	113	2900	77.7						
100	6.8	3300	88.4	4200	113								
125	8.6	3300	88.4	4200	113								
psig	bar	Body Size: NPS 1-1/2 / DN 40											
5	0.34	420	11.3	820	22.0	1900	50.9	350	9.38	2700	72.4	2800	75.0
10	0.69	810	21.7	1400	37.5	3200	85.8	3900	105	5300	142	6400	172
15	1.0	1000	26.8	1500	40.2	4000	107	5600	150	7000	188	9000	241
20	1.3	1100	29.5	2100	56.3	4700	126	7100	190	8400	225	9700	260
30	2.0	1500	40.2	2600	69.7	6000	161	7400	198	8400	225	10,200	273
40	2.7	1900	50.9	3200	85.8	7400	198	3700	99.2	8400	225	12,100	324
50	3.4	2100	56.3	3900	105	7400	198	3200	85.8	4200	113		
60	4.1	2400	64.3	4700	126	7400	198	3200	85.8				
80	5.5	3300	88.4	6000	161	7400	198						
100	6.8	4100	110	6500	174								
125	8.6	4900	131	6500	174								
psig	bar	Body Size: NPS 2 / DN 50											
5	0.34	530	14.2	850	22.8	1400	37.5	2100	56.3	3000	80.4	3400	91.1
10	0.69	820	22.0	1500	40.2	3100	83.1	4400	118	5700	153	9500	255
15	1.0	1000	26.8	1800	48.2	4000	107	6100	163	10,100	271	10,100	271
20	1.3	1200	32.2	2100	56.3	4600	123	7100	190	10,100	271	10,100	271
30	2.0	1500	40.2	2700	72.4	6000	161	7100	190	10,100	271	8600	230
40	2.7	1900	50.9	3300	88.4	6000	161	7100	190	6200	166	6700	180
50	3.4	2200	59.0	4000	107	6000	161	7100	190	4900	131		
60	4.1	2600	69.7	4700	126	6000	161	7100	190				
80	5.5	3400	91.1	6000	161	6000	161						
100	6.8	4100	110	6000	161								
125	8.6	5000	134	6000	161								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
5 psig	-0.2 psi	0.2 psi	2 to 5 psig	GE27213X012 / Orange Stripe
0.34 bar	-14 mbar	14 mbar	0.14 to 0.34 bar	

**Table 14. CP400 Series Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4 / DN 32											
10	0.69	650	17.4	1200	32.2	2500	67.0	3100	83.1	3400	91.1	6000	161
15	1.0	1000	26.8	1700	45.6	3200	85.8	4300	115	6000	161	6000	161
20	1.3	1200	32.2	2100	56.3	4100	110	6000	161	6000	161	6000	161
30	2.0	1500	40.2	2600	69.7	6000	161	6000	161	6000	161	6000	161
40	2.7	1900	50.9	3000	80.4	6000	161	6000	161	5700	153	5200	139
50	3.4	2200	59.0	4100	110	6000	161	4300	115	3500	93.8		
60	4.1	2600	69.7	4700	126	6000	161	4300	115				
80	5.5	3300	88.4	5000	134	5500	147						
100	6.8	3900	105	5000	134								
125	8.6	5000	134	5000	134								
psig	bar	Body Size: NPS 1-1/2 / DN 40											
10	0.69	740	19.8	1000	26.8	2500	67.0	3800	102	5900	158	6500	174
15	1.0	980	26.3	1500	40.2	3500	93.8	5900	158	8700	233	8700	233
20	1.3	1200	32.2	2000	53.6	4300	115	6600	177	8700	233	8700	233
30	2.0	1500	40.2	2700	72.4	5500	147	6600	177	5700	153	5200	139
40	2.7	1800	48.2	3200	85.8	6600	177	6600	177	5700	153	5200	139
50	3.4	2400	64.3	3700	99.2	8800	236	5000	134	5300	142		
60	4.1	2600	69.7	4700	126	10,400	279	4700	126				
80	5.5	3200	85.8	5700	153	12,000	322						
100	6.8	4000	107	6300	169								
125	8.6	4700	126	6300	169								
psig	bar	Body Size: NPS 2 / DN 50											
10	0.69	680	18.2	1100	29.5	2600	69.7	3300	88.4	3800	102	5400	145
15	1.0	1000	26.8	1700	45.6	3800	102	5000	134	5900	158	11,000	295
20	1.3	1200	32.2	2100	56.3	4600	123	6400	172	12,400	332	12,900	346
30	2.0	1500	40.2	2700	72.4	6400	172	8700	233	12,900	346	12,900	346
40	2.7	1900	50.9	3400	91.1	7700	206	8700	233	6100	163	5400	145
50	3.4	2200	59.0	3900	105	7800	209	8700	233	5900	158		
60	4.1	2600	69.7	4500	121	7800	209	8800	236				
80	5.5	3300	88.4	5700	153	6700	180						
100	6.8	4000	107	6900	185								
125	8.6	4800	129	8900	239								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
10 psig	-0.25 psi	0.25 psi	5 to 10 psig	GE39890X012 / Black Stripe
0.69 bar	-17 mbar	17 mbar	0.34 to 0.69 bar	

**Table 15. CP400 Series Internal Registration Flow Capacities for 10 psig / 0.69 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4 / DN 32											
15	1.0	820	22.0	1300	34.8	2700	72.4	3900	105	5200	139	5200	139
20	1.3	1100	29.5	1900	50.9	3200	85.8	5500	147	5800	155	7400	198
30	2.0	1300	34.8	2700	72.4	5700	153	7100	190	7100	190	7400	198
40	2.7	1700	45.6	3100	83.1	7100	190	7100	190	7100	190	7400	198
50	3.4	2300	61.6	3900	105	7100	190	7100	190	7100	190		
60	4.1	2500	67.0	4500	121	7500	201	7500	201				
80	5.5	3200	85.8	5200	139	7500	201						
100	6.8	4100	110	5200	139								
125	8.6	4600	123	5200	139								
psig	bar	Body Size: NPS 1-1/2 / DN 40											
15	1.0	770	20.6	1300	34.8	2500	67.0	3900	105	5900	158	7800	209
20	1.3	1100	29.5	1500	40.2	4100	110	4200	113	7700	206	9700	260
30	2.0	1500	40.2	2700	72.4	6100	163	6700	180	9700	260	9700	260
40	2.7	1900	50.9	3400	91.1	6700	180	6700	180	6700	180	9700	260
50	3.4	2200	59.0	4000	107	6800	182	6800	182	5200	139		
60	4.1	2600	69.7	4700	126	7200	193	5100	137				
80	5.5	3300	88.4	5400	145	5400	145						
100	6.8	4000	107	5600	150								
125	8.6	5000	134	5600	150								
psig	bar	Body Size: NPS 2 / DN 50											
15	1.0	590	15.8	1200	32.2	3000	80.4	3600	96.5	4800	129	4800	129
20	1.3	1100	29.5	1600	42.9	3100	83.1	5100	137	7800	209	9500	255
30	2.0	1500	40.2	2800	75.0	5900	158	8800	236	7800	209	11,900	319
40	2.7	1800	48.2	2800	75.0	7600	204	9900	265	7800	209	11,900	319
50	3.4	2200	59.0	4000	107	9200	247	9900	265	7800	209		
60	4.1	2600	69.7	4700	126	9200	247	9900	265				
80	5.5	3300	88.4	5600	150	9200	247						
100	6.8	4100	110	7100	190								
125	8.6	5000	134	8600	230								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
15 psig	-0.30 psi	0.30 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.0 bar	-20 mbar	-20 mbar	0.69 to 1.4 bar	

**Table 16. CP400 Series Internal Registration Flow Capacities for 15 psig / 1.0 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4 / DN 32											
20	1.3	460	12.3	1500	40.2	2800	75.0	4200	113	4700	126	5400	145
30	2.0	1500	40.2	2600	69.7	5100	137	7200	193	10,400	279	15,400	413
40	2.7	1900	50.9	3300	88.4	7300	196	9400	252	11,100	297	15,400	413
50	3.4	2200	59.0	4000	107	7500	201	11,000	295	11,100	297		
60	4.1	2600	69.7	4600	123	9800	263	11,000	295				
80	5.5	3300	88.4	5900	158	11,000	295						
100	6.8	4000	107	7200	193								
125	8.6	4900	131	7500	201								
psig	bar	Body Size: NPS 1-1/2 / DN 40											
20	1.3	700	18.8	1400	37.5	2800	75.0	4200	113	6400	172	7100	190
30	2.0	1500	40.2	2500	67.0	5800	155	8600	230	11,800	316	12,200	327
40	2.7	1900	50.9	3400	91.1	7300	196	10,000	268	11,800	316	12,200	327
50	3.4	2300	61.6	4000	107	7500	201	10,300	276	7600	204		
60	4.1	2600	69.7	4600	123	7500	201	6700	180				
80	5.5	3300	88.4	5900	158	7500	201						
100	6.8	4100	110	6500	174								
125	8.6	5000	134	6500	174								
psig	bar	Body Size: NPS 2 / DN 50											
20	1.3	670	18.0	1500	40.2	2700	72.4	3500	93.8	6600	177	7700	206
30	2.0	1400	37.5	2500	67.0	5600	150	8300	222	13,900	373	17,100	458
40	2.7	1800	48.2	3400	91.1	7600	204	12,300	330	15,600	418	17,200	461
50	3.4	2200	59.0	4000	107	9100	244	14,700	394	15,600	418		
60	4.1	2600	69.7	4600	123	10,500	281	15,600	418				
80	5.5	3300	88.4	5900	158	13,600	364						
100	6.8	3900	105	7100	190								
125	8.6	4800	129	8900	239								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
20 psig	-0.35 psi	0.35 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.4 bar	-24 mbar	24 mbar	0.69 bar to 1.4 bar	

Table 17. CP400 Series Internal Registration Flow Capacities for 20 psig / 1.4 bar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		Body Size: NPS 1-1/4 / DN 32											
psig	bar												
30	2.0	1300	34.8	2300	61.6	4100	110	7100	190	8800	236	8800	236
40	2.7	1800	48.2	3400	91.1	6800	182	10,900	292	11,200	300	15,800	423
50	3.4	2200	59.0	4000	107	7300	196	13,000	348	15,800	423		
60	4.1	2600	69.7	4700	126	10,300	276	15,800	423				
80	5.5	3300	88.4	5900	158	11,100	297						
100	6.8	4100	110	7200	193								
125	8.6	4500	121	8800	236								
		Body Size: NPS 1-1/2 / DN 40											
psig	bar												
30	2.0	1300	34.8	2000	53.6	4800	129	6100	163	11,600	311	13,700	367
40	2.7	1700	45.6	3300	88.4	7000	188	10,200	273	15,600	418	15,600	418
50	3.4	2300	61.6	3900	105	8400	225	11,000	295	15,800	423		
60	4.1	2500	67.0	4700	126	9800	263	14,600	391				
80	5.5	3300	88.4	6100	163	12,200	327						
100	6.8	4100	110	7200	193								
125	8.6	5000	134	8100	217								
		Body Size: NPS 2 / DN 50											
psig	bar												
30	2.0	1300	34.8	2500	67.0	5100	137	6700	180	8400	225	13,300	356
40	2.7	1900	50.9	3300	88.4	7500	201	10,600	284	11,400	306	15,600	418
50	3.4	2200	59.0	4000	107	9200	247	13,900	373	14,300	383		
60	4.1	2600	69.7	4600	123	10,300	276	15,800	423				
80	5.5	3400	91.1	5900	158	13,700	367						
100	6.8	4100	110	7300	196								
125	8.6	4900	131	8800	236								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.14 bar	-12 mbar	12 mbar	0.07 to 0.14 bar	

Table 18. Types CP403 and CP404 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50											
psig	bar												
3	0.21	240	6.43	450	12.1	840	22.5	880	23.6	1400	37.5	1300	34.8
5	0.34	450	12.1	740	19.8	1400	37.5	2500	67.0	2500	67.0	3200	85.8
10	0.69	810	21.7	1300	34.8	3000	80.4	4400	118	5600	150	6500	174
15	1.0	980	26.3	1800	48.2	4000	107	6000	161	8200	220	9800	263
20	1.4	1200	32.2	2100	56.3	4700	126	7500	201	8200	220	9800	263
30	2.1	1500	40.2	2700	72.4	6300	169	7500	201	5100	137	5600	150
40	2.8	1900	50.9	3400	91.1	7900	212	4900	131	4400	118	4700	126
50	3.4	2200	59.0	4200	113	7900	212	4400	118	4000	107		
60	4.1	2600	69.7	4700	126	4700	126	4400	118				
80	5.5	3300	88.4	4700	126	4700	126						
100	6.9	4000	107	5100	137								
125	8.6	4900	131	5100	137								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Shaded areas indicate limited capacities due to boost effects.

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
5 psig	-0.2 psi	0.2 psi	2 to 5 psig	GE27213X012 / Orange Stripe
0.34 bar	-14 mbar	14 mbar	0.14 to 0.34 bar	

**Table 19. Types CP403 and CP404 Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50													
10	0.69	630	16.9	1000	26.8	1600	42.9	2700	72.4	3500	93.8	3700	99.2
15	1.0	910	24.4	1400	37.5	3000	80.4	4400	118	5400	145	7400	198
20	1.4	1100	29.5	2000	53.6	4000	107	6000	161	6800	182	7400	198
30	2.1	1500	40.2	2700	72.4	6000	161	6000	161	6800	182	7400	198
40	2.8	1900	50.9	3300	88.4	6000	161	5200	139	6800	182	6300	169
50	3.4	2200	59.0	4000	107	6000	161	4400	118	7200	193		
60	4.1	2600	69.7	4700	126	5100	137	4400	118				
80	5.5	3300	88.4	6000	161	3700	99.2						
100	6.9	4000	107	6700	180								
125	8.6	4500	121	8400	225								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
Shaded areas indicate limited capacities due to boost effects.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
1 psig	-0.16 psi	0.16 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.07 bar	-11 mbar	11 mbar	0.07 to 0.14 bar	

**Table 20. CP400 Series External Registration Flow Capacities for 1 psig / 0.07 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50													
3	0.21	330	8.84	330	8.84	890	23.9	1700	45.6	1700	45.6	1700	45.6
5	0.34	400	10.7	690	18.5	1800	48.2	2500	67.0	2500	67.0	2900	77.7
10	0.69	820	22.0	1400	37.5	2500	67.0	3600	96.5	3600	96.5	5700	153
15	1.0	1000	26.8	1800	48.2	3300	88.4	5100	137	5100	137	8700	233
20	1.3	1200	32.2	2200	59.0	4100	110	6300	169	6400	172	8700	233
30	2.0	1500	40.2	2700	72.4	5800	155	8500	228	11,200	300	8700	233
40	2.7	1900	50.9	3200	85.8	6900	185	11,100	297	14,300	383	8700	233
50	3.4	2300	61.6	3900	105	6900	185	13,800	370	15,200	407		
60	4.1	2700	72.4	4600	123	6900	185	15,200	407				
80	5.5	3300	88.4	5800	155	6900	185						
100	6.8	4100	110	7000	188								
125	8.6	5000	134	7000	188								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.14 bar	-12 mbar	12 mbar	0.07 to 0.14 bar	

**Table 21. CP400 Series External Registration Flow Capacities for 2 psig / 0.14 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50													
5	0.34	500	13.4	800	21.4	1300	34.8	1600	42.9	1600	42.9	2200	59.0
10	0.69	800	21.4	1000	26.8	2400	64.3	3700	99.2	3700	99.2	5300	142
15	1.0	1000	26.8	1600	42.9	3100	83.1	5600	150	6300	169	7300	196
20	1.3	1200	32.2	2100	56.3	4100	110	6100	163	8500	228	13,800	370
30	2.0	1600	42.9	2400	64.3	5600	150	6300	169	13,000	348	15,200	407
40	2.7	1900	50.9	3200	85.8	6500	174	9300	249	13,000	348	15,200	407
50	3.4	2300	61.6	3500	93.8	6500	174	12,300	330	13,000	348		
60	4.1	2600	69.7	4500	121	6500	174	13,000	348				
80	5.5	3400	91.1	5800	155	6500	174						
100	6.8	3800	102	7100	190								
125	8.6	4900	131	8700	233								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
5 psig	-0.2 psi	0.2 psi	2 to 5 psig	GE27213X012 / Orange Stripe
0.34 bar	-14 mbar	14 mbar		

**Table 22. CP400 Series External Registration Flow Capacities for 5 psig / 0.34 bar Setpoint**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
<b>psig</b>	<b>bar</b>	<b>Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50</b>											
10	0.69	520	13.9	980	26.3	1300	34.8	2200	59.0	3300	88.4	3300	88.4
15	1.0	770	20.6	1500	40.2	2900	77.7	4400	118	6600	177	6800	182
20	1.3	1100	29.5	2000	53.6	3800	102	6000	161	11,700	314	12,800	343
30	2.0	1300	34.8	2400	64.3	5300	142	8400	225	12,800	343	13,900	373
40	2.7	1700	45.6	3200	85.8	6500	174	10,800	289	17,200	461	17,200	461
50	3.4	1900	50.9	3800	102	9000	241	13,100	351	17,200	461		
60	4.1	2200	59.0	4400	118	9500	255	14,500	389				
80	5.5	3100	83.1	5900	158	13,300	356						
100	6.8	3900	105	7000	188								
125	8.6	4800	129	8700	233								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
10 psig	-0.25 psi	0.25 psi	5 to 10 psig	GE39890X012 / Black Stripe
0.69 bar	-17 mbar	17 mbar		

**Table 23. CP400 Series External Registration Flow Capacities for 10 psig / 0.69 bar Setpoint**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
<b>psig</b>	<b>bar</b>	<b>Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50</b>											
15	1.0	650	17.4	1300	34.8	2000	53.6	3100	83.1	3800	102	6300	169
20	1.3	990	26.5	1700	45.6	2700	72.4	6200	166	9800	263	10,300	276
30	2.0	1400	37.5	2400	64.3	5800	155	9500	255	14,500	389	15,800	423
40	2.7	1700	45.6	3100	83.1	6400	172	10,000	268	15,800	423	17,200	461
50	3.4	2000	53.6	3900	105	8700	233	12,300	330	16,700	448		
60	4.1	2500	67.0	4500	121	9200	247	13,300	356				
80	5.5	3100	83.1	5800	155	10,300	276						
100	6.8	3500	93.8	7000	188								
125	8.6	4400	118	8500	228								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
15 psig	-0.30 psi	0.30 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.0 bar	-20 mbar	20 mbar		

**Table 24. CP400 Series External Registration Flow Capacities for 15 psig / 1.0 bar Setpoint**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
<b>psig</b>	<b>bar</b>	<b>Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50</b>											
20	1.3	680	18.2	1300	34.8	2500	67.0	2800	75.0	4000	107	8500	228
30	2.0	1300	34.8	2200	59.0	5300	142	6300	169	8500	228	15,000	402
40	2.7	1500	40.2	3300	88.4	6100	163	11,800	316	14,300	383	17,600	472
50	3.4	2200	59.0	3600	96.5	7600	204	12,800	343	16,700	448		
60	4.1	2400	64.3	4500	121	10,500	281	14,400	386				
80	5.5	3000	80.4	5800	155	11,700	314						
100	6.8	3600	96.5	6700	180								
125	8.6	4300	115	8500	228								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CP400 Series

## Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
20 psig	-0.35 psi	0.35 psi	10 to 20 psig	GE30200X012 / Purple Stripe
1.4 bar	-24 mbar	24 mbar	0.69 to 1.4 bar	

**Table 25. CP400 Series External Registration Flow Capacities for 20 psig / 1.4 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50											
30	2.0	960	25.7	2500	67.0	3400	91.1	6600	177	11,800	316	14,200	381
40	2.7	1400	37.5	2900	77.7	5500	147	9500	255	12,800	343	17,600	472
50	3.4	1900	50.9	3700	99.2	7500	201	13,600	364	14,400	386		
60	4.1	2600	69.7	4000	107	8600	230	13,600	364				
80	5.5	3000	80.4	5800	155	11,700	314						
100	6.8	3900	105	6500	174								
125	8.6	4900	131	8200	220								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30199X012 / Yellow Stripe
0.14 bar	-12 mbar	12 mbar	0.07 to 0.14 bar	

**Table 26. Types CP403 and CP404 External Registration Flow Capacities for 2 psig / 0.14 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50											
3	0.20	280	7.50	380	10.2	740	19.8	1200	32.2	1400	37.5	1400	37.5
5	0.34	450	12.1	770	20.6	1400	37.5	1800	48.2	2200	59.0	2800	75.0
10	0.69	740	19.8	1300	34.8	2400	64.3	3300	88.4	3700	99.2	5400	145
15	1.0	1000	26.8	1600	42.9	3000	80.4	4700	126	6800	182	7900	212
20	1.4	1100	29.5	2100	56.3	4200	113	6100	163	9300	249	11,400	306
30	2.1	1500	40.2	2600	69.7	6000	161	9300	249	13,700	367	16,900	453
40	2.8	1900	50.9	3400	91.1	7400	198	11,800	316	18,700	501	21,000	563
50	3.4	2200	59.0	4000	107	9000	241	15,500	415	23,300	624		
60	4.1	2600	69.7	4700	126	10,700	287	17,300	464				
80	5.5	3300	88.4	6000	161	13,700	367						
100	6.9	4000	107	7400	198								
125	8.6	4900	131	9000	241								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 1% ABS			
5 psig	-0.2 psi	0.2 psi	2 to 5 psig	GE27213X012 / Orange Stripe
0.34 bar	-14 mbar	14 mbar	0.14 to 0.34 bar	

**Table 27. Types CP403 and CP404 External Registration Flow Capacities for 5 psig / 0.34 bar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
Inlet Pressure		Orifice Size											
		3/16 In. / 4.8 mm		1/4 In. / 6.4 mm		3/8 In. / 9.5 mm		1/2 In. / 13 mm		5/8 In. / 16 mm		3/4 In. / 19 mm	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: NPS 1-1/4, 1-1/2 and 2 / DN 32, 40 and 50											
10	0.69	520	13.9	1000	26.8	1500	40.2	2400	64.3	2800	75.0	3100	83.1
15	1.0	810	21.7	1300	34.8	2700	72.4	3700	99.2	4500	121	5600	150
20	1.4	1000	26.8	1800	48.2	3200	85.8	5200	139	6300	169	8100	217
30	2.1	1400	37.5	2700	72.4	4900	131	7700	206	10,500	281	13,200	354
40	2.8	1800	48.2	3200	85.8	6800	182	10,200	273	15,300	410	18,500	496
50	3.4	2100	56.3	4000	107	9100	244	13,000	348	19,900	533		
60	4.1	2500	67.0	4500	121	10,000	268	16,700	448				
80	5.5	3200	85.8	5800	155	13,000	348						
100	6.9	4000	107	7000	188								
125	8.6	4700	126	8200	220								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.







Figure 4. CP400 Series Vent and Body Orientation

Table 28. Type CP400 Inlet Set Pressure for Pressure Factor Measurement (PFM) Service

BODY SIZE, NPS / DN	SETPOINT		ORIFICE SIZE, IN. / mm									
			3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		3/4 / 19	
			Inlet Set Pressure		Inlet Set Pressure		Inlet Set Pressure		Inlet Set Pressure		Inlet Set Pressure	
	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
1-1/4 / 32	2	0.14	60	4.1	60	4.1	40	2.8	25	1.7	10	0.69
	5	0.34	40	2.8	60	4.1	25	1.7	25	1.7	15	1.0
	7	0.48	80	5.5	40	2.8	50	3.4	25	1.7	25	1.7
	10	0.69	80	5.5	80	5.5	25	1.7	25	1.7	20	1.4
	15	1.0	60	4.1	40	2.8	25	1.7	25	1.7	25	1.7
1-1/2 / 40	2	0.14	60	4.1	40	2.8	40	2.8	30	2.1	25	1.7
	5	0.34	80	5.5	60	4.1	25	1.7	25	1.7	10	0.69
	7	0.48	60	4.1	60	4.1	25	1.7	25	1.7	15	1.0
	10	0.69	80	5.5	60	4.1	25	1.7	25	1.7	25	1.7
	15	1.0	60	4.1	60	4.1	60	4.1	25	1.7	25	1.7
2 / 50	2	0.14	60	4.1	40	2.8	40	2.8	30	2.1	30	2.1
	5	0.34	60	4.1	60	4.1	30	2.1	25	1.7	20	1.4
	7	0.48	60	4.1	50	3.4	25	1.7	25	1.7	20	1.4
	10	0.69	80	5.5	60	4.1	25	1.7	25	1.7	25	1.7
	15	1.0	60	4.1	40	2.8	25	1.7	25	1.7	25	1.7
	20	1.4	60	4.1	60	4.1	25	1.7	25	1.7	30	2.1
			60	4.1	40	2.8	30	2.1	30	2.1	25	1.7

# CP400 Series

Commercial/Industrial Pressure Loaded-Pressure Reducing Regulator

FISHER™




Figure 5. Dimensions

Table 29. Dimensions

BODY SIZE, IN.	END CONNECTION STYLE			
	A			
	NPT / Rp		CL125 FF / CL150 FF / PN 16	
	In.	mm	In.	mm
1-1/4	4.49	114	----	----
1-1/2			----	----
1	3.94	100	----	----
NPS 2 / DN 50	5	127	10	254

## Ordering Guide

Type (Select One)
<b>Regulator with Internal Registration</b> <input type="checkbox"/> CP400IN*** <input type="checkbox"/> CP400IT (with token relief)***
<b>Regulator with External Registration</b> <input type="checkbox"/> CP400EN*** <input type="checkbox"/> CP400ET (with token relief)***
<b>Regulator with Internal Registration and Integral True-Monitor™ Protection</b> <input type="checkbox"/> CP403IN*** <input type="checkbox"/> CP403IT (with token relief)***
<b>Regulator with External Registration and Integral True-Monitor™ Protection</b> <input type="checkbox"/> CP403EN*** <input type="checkbox"/> CP403ET (with token relief)***
<b>Regulator with Internal Registration and Integral Type VSX4 Slam-Shut module</b> <input type="checkbox"/> CP404IN*** <input type="checkbox"/> CP404IT (with token relief)***
<b>Regulator with External Registration and Integral Type VSX4 Slam-Shut module</b> <input type="checkbox"/> CP404EN*** <input type="checkbox"/> CP404ET (with token relief)***

Body Size, Material and End Connection (Select One)
<b>Gray Cast Iron (Type CP400 only)</b> <input type="checkbox"/> 1-1/4 NPT*** <input type="checkbox"/> 1-1/2 NPT*** <input type="checkbox"/> 2 NPT*** <input type="checkbox"/> NPS 2 / DN 50, CL125 FF (10 in. / 254 mm Face-to-Face)***
<b>Ductile Iron (All Types)</b> <input type="checkbox"/> 1-1/4 NPT*** <input type="checkbox"/> 1-1/2 NPT*** <input type="checkbox"/> 2 NPT*** <input type="checkbox"/> Rp 1-1/4*** <input type="checkbox"/> Rp 1-1/2*** <input type="checkbox"/> Rp 2*** <input type="checkbox"/> NPS 2 / DN 50, CL125 FF (10 in. / 254 mm Face-to-Face)*** <input type="checkbox"/> NPS 2 / DN 50, CL150 FF (10 in. / 254 mm Face-to-Face)*** <input type="checkbox"/> NPS 2 / DN 50, PN 10/16 (10 in. / 254 mm Face-to-Face)***
<b>Steel (All Types)</b> <input type="checkbox"/> 1-1/4 NPT*** <input type="checkbox"/> 1-1/2 NPT*** <input type="checkbox"/> Rp 1-1/4*** <input type="checkbox"/> Rp 1-1/2***

Outlet Pressure Range (Select One)
<input type="checkbox"/> 1 to 2 psig / 0.07 to 0.14 bar*** <input type="checkbox"/> 2 to 5 psig / 0.14 to 0.34 bar*** <input type="checkbox"/> 5 to 10 psig / 0.34 to 0.69 bar*** <input type="checkbox"/> 10 to 20 psig / 0.69 to 1.4 bar***

Orifice Size (Select One)
<input type="checkbox"/> 3/16 in. / 4.8 mm*** <input type="checkbox"/> 1/4 in. / 6.4 mm*** <input type="checkbox"/> 3/8 in. / 9.5 mm*** <input type="checkbox"/> 1/2 in. / 13 mm*** <input type="checkbox"/> 5/8 in. / 16 mm*** <input type="checkbox"/> 3/4 in. / 19 mm***

Body Orientation (Select One)
<b>Type CP400</b> <input type="checkbox"/> Position 3 (standard)*** <input type="checkbox"/> Position 4 (only available on Type CP400 with Gray Cast Iron Body)***

Vent Orientation of Types 67CP/67CPR and CP400 with Gray Cast Iron Body (Select One)
<input type="checkbox"/> Position 1 (standard)*** <input type="checkbox"/> Position 2***

Vent Orientation of Types CP403/CP404 and CP400 with Ductile or Steel Body (Select One)
<input type="checkbox"/> Position 2*** <input type="checkbox"/> Position 5 (standard)***

Certification
(Available only on CP400 Series Construction) <input type="checkbox"/> Pressure Factor Measurement (PFM)

True-Monitor™ Control Pressure Range (Select One)
<b>CP403 Series</b> <input type="checkbox"/> 1.4 to 2.9 psig / 97 to 200 mbar, Black <sup>(1)</sup> <input type="checkbox"/> 2.6 to 3.7 psig / 179 to 255 mbar, Purple <sup>(1)</sup> <input type="checkbox"/> 3.6 to 6 psig / 248 to 414 mbar, Dark Blue <input type="checkbox"/> 5.1 to 7.5 psig / 352 to 517 mbar, Red

Slam-Shut Trip Pressure Setting Types VSX4L and VSX4H
<input type="checkbox"/> Overpressure (OPSO) trip only (supply high-pressure trip pressure) Indicate trip pressure <b>See Table 8</b>
<input type="checkbox"/> Over and Underpressure (OPSO / UPSO) trip (supply high and low pressure trip pressure) Indicate trip points <b>See Table 9</b> Over _____ Under _____

1. Available with CP403 Series without Token relief only.

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Do not use needle valves in control lines; use full-open valves. Needle valves can cause instability.



### Introduction

The Cronos Series regulators are accurate pilot-operated, pressure balanced, soft seated regulators designed for high pressure transmission/city gate, large capacity distribution systems and power plant feeds. They provide smooth, quiet operation, tight shutoff and long life. The regulator utilizes a main valve actuator, Type PRX pressure reducing pilot, and Type SA/2 pilot supply regulator or Type PS compact pressure reducing pilot.

The superior performance of this regulator is due to the amplifying effect of the pilot and the two-path control system. Changes in outlet pressure act quickly on the actuator diaphragm to provide fast response to system change. Then the pilot amplifies any small system changes to position the main valve for precise pressure control.

### Available Configurations

See Table 1

### Flange Rating PN 16 - CL150 RF

**Allowable Pressure:**

Up to 290 psig / 20.0 bar

**Inlet Pressure Range:**

2.9 to 290 psig / 0.20 to 20.0 bar

**Set Range:** 0.15 to 116 psig / 0.01 to 8.0 bar

**Minimum Operating Differential**

**Pressure:** 2.9 psi / 0.20 bar

### Flange Rating PN 25/40 - CL300 RF, CL600 RF

**Allowable Pressure:**

Up to 1450 psig / 100 bar

**Inlet Pressure Range:**

14.5 to 1450 psig / 1.00 to 100 bar

**Set Range:** 7.25 to 1160 psig / 0.50 to 80.0 bar

**Minimum Operating Differential**

**Pressure:** 7.25 psi / 0.50 bar

### Accuracy Class

Up to  $\pm 1\%$

### Lockup Pressure Class

Up to 5%

### Class of Lockup Pressure Zone

Up to 5%

### Outlet Pressure Ranges

See Tables 3 and 4

### Flow Coefficients

See Table 5

### Shutoff Device

**Accuracy Class:** Up to  $\pm 1\%$

**Response Time:**  $\leq 1$  second

### Flanged Connections

**Same Inlet and Outlet:**

NPS 1, 2 or 3 / DN 25, 50 or 80

**Different Inlet and Outlet:**

NPS 1 x 4, 2 x 6 or 3 x 10 /

DN 25 x 100, 50 x 150 or 80 x 250

### Operating Temperature

**Standard Version:**

Working: 14 to 140°F / -10 to 60°C

**Low Temperature Version:**

Working: -4 to 140°F / -20 to 60°C

### Approximate Weights (Including Pilot)

See Tables 7 and 9

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)




02/15

### Features

- Control Accuracy
- Versatility
- Tight Shutoff
- No Atmospheric Bleed
- High Capacity
- Quiet Operation
- In-Service Travel Indicator
- Silencer Options



**Figure 1.** Type Cronos C Pressure Reducing Regulator



**Figure 2.** Type Cronos CCB - SRS Pressure Reducing Regulator with Slam-Shut and Type SRS Silencer



**Figure 3.** Type Cronos CCBS Pressure Reducing Regulator and Monitor with Slam-Shut




Figure 4. Type Cronos with Type PRX Pilot Operational Schematic




Figure 5. Monitor Operational Schematic

Table 1. Available Configurations

CONFIGURATION	TYPE					
	Horizontal Flow			90° Flow		
	Standard	Silenced		Standard	Silenced	
		with SR	with SRS		with SR	with SRS
Pressure Reducing Regulator	C	C-SR	C-SRS	----	----	----
Pressure Reducing Regulator with Slam-Shut	CB	CB-SR	CB-SRS	CBS	CBS-SR	CBS-SRS
Pressure Reducing Regulator and Monitor	CC	CC-SR	CC-SRS	CCS	CCS-SR	CCS-SRS
Pressure Reducing Regulator and Monitor with Slam-Shut	CCB	CCB-SR	CCB-SRS	CCBS	CCBS-SR	CCBS-SRS

**Table 2. Construction Material**

MAIN BODY, FLANGE, DIAPHRAGM CASING AND DIAPHRAGM PLATE	SEAT	DIAPHRAGM	O-RING AND SEAT
Steel	Stainless steel	Nitrile (NBR) with PVC Coating	Nitrile (NBR) or Fluorocarbon (FKM)

**Table 3. Outlet Pressure Ranges of Service Regulator or Monitor Pilot**

PILOT TYPE	USE	OUTLET PRESSURE RANGE		ALLOWABLE PRESSURE		BODY AND COVER MATERIAL
		psig	bar	psig	bar	
PS/79-1 <sup>(1)</sup>	Regulator or Monitor	0.15 to 7.3	0.01 to 0.50	363	25.0	Aluminum
PS/79-2 <sup>(1)</sup>		7.3 to 43.5	0.50 to 3.0			
PS/79 <sup>(1)</sup>	Regulator or Monitor	7.3 to 580	0.50 to 40.0	1450	100	Steel
PSO/79 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/79 <sup>(1)</sup>	Operating Monitor - Monitor					
PS/80 <sup>(1)</sup>	Regulator or Monitor	22 to 580	1.5 to 40.0	1450	100	Steel
PSO/80 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/80 <sup>(1)</sup>	Operating Monitor - Monitor					
PRX/120 <sup>(2)</sup>	Regulator or Monitor	14.5 to 26 23 to 44 41 to 80 73 to 123 116 to 210 203 to 334 319 to 435	1.00 to 1.8 1.6 to 3.0 2.8 to 5.5 5.0 to 8.5 8.0 to 14.5 14.0 to 23.0 22.0 to 30.0	1450	100	Steel
PRX/125 <sup>(2)</sup>	Monitor					
PRX-AP/120 <sup>(2)</sup>	Regulator or Monitor	435 to 1160	30.0 to 80.0	1450	100	Steel
PRX-AP/125 <sup>(2)</sup>	Monitor					

1. All PS/ Series pilots are supplied with a filter (5 micron filtering degree) and built-in pressure stabilizer, with the exception of Types PSO/79 and PSO/80.  
2. The Type SA/2 pressure pre-reducer must be used with PRX Series pilots.

**Table 4. Outlet Pressure Ranges of Shutoff Device Pilots**

TYPE	SERVOMOTOR BODY RESISTANCE		OVERPRESSURE SET RANGE				UNDERPRESSURE SET RANGE			
			Minimum		Maximum		Minimum		Maximum	
			psig	bar	psig	bar	psig	bar	psig	bar
OS/80X-BP	73	5.0	0.4	0.03	29	2.0	0.15	0.01	8.7	0.60
OS/80X-BPA-D	290	20.0	0.4	0.03	29	2.0	0.15	0.01	8.7	0.60
OS/80X-MPA-D	1450	100	7.25	0.50	73	5.0	3.6	0.25	58	4.0
OS/80X-APA-D	1450	100	29	2.0	145	10.0	4.4	0.30	102	7.0
OS/84X	1450	100	73	5.0	595	41.0	58	4.0	232	16.0
OS/88X	1450	100	261	18.0	1160	80.0	116	8.0	1015	70.0


**Table 5. Flow Coefficients**

BODY SIZE		FLOW COEFFICIENT	TYPE															
			Regulating and Wide-Open for Relief Sizing															
			Standard				With SR				With SRS				With Wide Outlet			
In.	DN	C	CB	CC	CCB	C	CB	CC	CCB	C	CB	CC	CCB	C	CB	CC	CCB	
<b>Horizontal Flow</b>																		
1	25	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	550	510	510	500	540	500	500	490	500	460	460	450	580	550	550	540
			18.3	16.7	16.7	16.1	18	16.4	16.4	15.8	15.2	13.7	13.7	13.2	19.3	17.7	17.7	17.4
			30	30.5	30.5	31	30	30.5	30.5	31	33	33.5	33.5	34	30	31	31	31
2	50	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	2250	2080	2080	2050	2200	2030	2030	2000	1900	1780	1780	1750	2300	2100	2100	2050
			77.6	69.3	69.3	67.2	75.9	67.7	67.7	64.5	59.4	53.9	53.9	52.2	79.3	70	70	67.2
			29	30	30	30.5	29	30	30	31	32	33	33	33.5	29	30	30	30.5
3	80	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	5100	4800	4800	4700	5000	4700	4700	4600	4200	4000	4000	3900	5200	4850	4850	4800
			176	160	160	152	172	157	157	148	131	121	121	114	179	162	162	155
			29	30	30	31	29	30	30	31	32	33	33	34	29	30	30	31
<b>90° Flow</b>																		
1	25	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	----	450	450	440	----	440	440	430	----	400	400	390	----	475	475	470
				15	15	14.2		14.7	14.7	13.9		12.1	12.1	11.5		15.8	15.8	15.2
				30	30	31		30	30	31		33	33	34		30	30	31
2	50	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	----	1850	1850	1800	----	1800	1800	1750	----	1650	1650	1600	----	1900	1900	1850
				61.7	61.7	58.1		60	60	56.5		51.6	51.6	48.5		63.3	63.3	59.7
				30	30	31		30	30	31		32	32	33		30	30	31
3	80	C <sub>1</sub> C <sub>2</sub> C <sub>3</sub>	----	4300	4300	4200	----	4200	4200	4100	----	3500	3500	3400	----	4400	4400	4300
				143	143	135		140	140	132		106	106	100		147	147	139
				30	30	31		30	30	31		33	33	34		30	30	31



# Cronos Series

Pressure Reducing Regulator



TARTARINI




TYPE CRONOS C WITH TYPE SR SILENCER



TYPE CRONOS C WITH TYPE SRS SILENCER



TYPE CRONOS CCB WITH TYPE SR SILENCER



TYPE CRONOS CCB WITH TYPE SRS SILENCER

IN. /  
mm


Figure 6. Horizontal Flow Dimensions

Table 6. Horizontal Flow Dimensions

BODY SIZE		OVERALL DIMENSIONS, IN. / mm										FACE-TO-FACE DIMENSIONS, IN. / mm					
		CL150 RF Flanged PN 16					CL300 RF or CL600 RF Flanged PN 25 or 40					CL150 RF Flanged PN 16		CL300 RF Flanged PN 25 or 40		CL600 RF Flanged	
NPS	DN	A	B	C	D	E	A	B	C	D	E	I	I1	I	I1	I	I1
1	25	8.5 / 215	7.1 / 180	11.2 / 285	10.2 / 260	6.7 / 170	8.7 / 220	7.1 / 180	8.9 / 225	10.2 / 260	6.7 / 170	7.2 / 184	13.8 / 350	7.8 / 197	13.9 / 353.5	8.3 / 210	14.2 / 360
2	50	9.6 / 245	7.7 / 195	13.2 / 335	11.2 / 285	6.9 / 175	10.2 / 260	7.7 / 195	11.3 / 287	11.2 / 285	6.9 / 175	10.0 / 254	18.3 / 465	10.5 / 267	18.6 / 472	11.3 / 286	19.0 / 482
3	80	13.0 / 330	10.2 / 260	15.7 / 400	12.8 / 325	7.3 / 185	13.8 / 350	10.2 / 260	15.7 / 400	12.8 / 325	7.3 / 185	11.7 / 298	22.4 / 570	12.5 / 317	23.2 / 590	13.3 / 337	23.6 / 600

Table 7. Horizontal Flow Weights

BODY SIZE		TYPE															
		Standard and SR, LBS / kg								Widened Outlet and SRS, LBS / kg							
		CL150 RF Flanged PN 16				CL300 RF or CL600 RF Flanged PN 25 or 40				CL150 RF Flanged PN 16				CL300 RF or CL600 RF Flanged PN 25 or 40			
NPS	DN	C	CB	CC	CCB	C	CB	CC	CCB	C	CB	CC	CCB	C	CB	CC	CCB
1	25	79 / 36	84 / 38	123 / 56	128 / 58	82 / 37	86 / 39	134 / 61	139 / 63	108 / 49	112 / 51	152 / 69	157 / 71	123 / 56	128 / 58	172 / 78	176 / 80
2	50	137 / 62	146 / 66	212 / 96	220 / 100	163 / 74	172 / 78	260 / 118	269 / 122	192 / 87	201 / 91	267 / 121	276 / 125	240 / 109	249 / 113	337 / 153	346 / 157
3	80	282 / 128	313 / 142	421 / 191	434 / 197	377 / 171	408 / 185	597 / 271	611 / 277	419 / 190	450 / 204	558 / 253	571 / 259	602 / 273	615 / 279	822 / 373	836 / 379



IN. /  
mm

Figure 7. 90° Flow Dimensions

Table 8. 90° Flow Dimensions

BODY SIZE		OVERALL DIMENSIONS, IN. / mm										FACE-TO-FACE DIMENSIONS, IN. / mm								
		CL150 RF Flanged PN 16					CL300 RF or CL600 RF Flanged PN 25 or 40					CL150 RF Flanged PN 16			CL300 RF Flanged PN 25 or 40			CL600 RF Flanged PN 40		
NPS	DN	A	B	C	D	E	A	B	C	D	E	I	I1	I2	I	I1	I2	I	I1	I2
1	25	8.5 / 215	7.1 / 180	11.2 / 285	10.2 / 260	6.7 / 170	8.7 / 220	7.1 / 180	8.9 / 225	10.2 / 260	6.7 / 170	3.6 / 92	11.0 / 280	15.2 / 386	3.88 / 98.5	11.6 / 295	15.2 / 385	4.13 / 105	11.6 / 295	15.2 / 385
2	50	9.6 / 245	7.7 / 195	13.2 / 335	11.2 / 285	6.9 / 175	10.2 / 260	7.7 / 195	11.3 / 287	11.2 / 285	6.9 / 175	5.0 / 127	13.7 / 347	18.6 / 473	5.26 / 133.5	14.6 / 370	19.1 / 484	5.63 / 143	14.6 / 370	19.1 / 484
3	80	13.0 / 330	10.2 / 260	15.7 / 400	12.8 / 325	7.3 / 185	13.8 / 350	10.2 / 260	15.7 / 400	12.8 / 325	7.3 / 185	5.9 / 149	17.7 / 450	24.5 / 622	6.24 / 158.5	19.1 / 485	25.5 / 648.5	6.63 / 168.5	19.1 / 485	25.5 / 648.5

Table 9. 90° Flow Weights

BODY SIZE		TYPE											
		Standard and SR, LBS / kg						Widened Outlet and SRS, LBS / kg					
		CL150 RF Flanged PN 16			CL300 RF or CL600 RF Flanged PN 25 or 40			CL150 RF Flanged PN 16			CL300 RF or CL600 RF Flanged PN 25 or 40		
NPS	DN	CBS	CCS	CCBS	CBS	CCS	CCBS	CBS	CCS	CCBS	CBS	CCS	CCBS
1	25	88 / 40	123 / 56	128 / 58	95 / 43	139 / 63	143 / 65	117 / 53	152 / 69	157 / 71	132 / 60	176 / 80	181 / 82
2	50	159 / 72	225 / 102	234 / 106	203 / 92	291 / 132	300 / 136	214 / 97	280 / 127	289 / 131	280 / 127	368 / 167	377 / 171
3	80	351 / 159	459 / 208	472 / 214	496 / 225	703 / 319	716 / 325	487 / 221	595 / 270	631 / 286	721 / 327	928 / 421	941 / 427

### Ordering Guide

#### Configuration (Fill in — See Table 1)

#### Body Size (Select One)

- NPS 1 / DN 25\*\*
- NPS 2 / DN 50\*\*
- NPS 3 / DN 80\*\*

#### Built-In Silencer - For Clean Gas Only

- Type SR\*\*
- Type SRS\*\*
- None

#### End Connection Style (Select One)

- PN 16\*\*       CL150\*\*
- PN 25\*\*       CL300\*\*
- PN 40\*\*       CL600\*\*

#### Elastomer Part (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*

#### Working Temperature Range (Select One)

- Standard Version: 14 to 140°F / -10 to 60°C\*\*
- Low Temperature Version: -4 to 140°F / -20° to 60°C\*\*

#### Pilot Type (Fill in — See Table 3)

- PS/79-1\*\*
- PS/79-2\*\*
- PS/79\*\*
- PS/80\*\*
- PSO/79
- PSO/80
- REO/79
- REO/80
- PRX/120 and SA/2\*\*
- PRX-AP/120 and SA/2\*\*
- PRX/125 and SA/2\*\*
- PRX-AP/125 and SA/2\*\*

#### Setpoint (Fill in - see Tables 3 and 4)

- Regulator Outlet Pressure: \_\_\_\_\_
- Built-in Monitor Outlet Pressure: \_\_\_\_\_
- Built-in Safety Shutoff Device Minimum Pressure: \_\_\_\_\_
- Built-in Safety Shutoff Device Maximum Pressure: \_\_\_\_\_

#### Monitor Booster Valve

- Type V/31-2\*\*
- Type PRX/131\*\*
- Type PRX-AP/131\*\*

#### PED Certificate (Optional)

- Yes\*\*

#### Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

#### Installation (Select One)

##### Horizontal Flow

- Left to Right
- Right to Left

##### Vertical Flow

- Downward
- Upward

##### 90° Flow

- Left Downward
- Right Downward
- Left Upward
- Right Upward

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Do not make the setpoints of the regulator/monitor too close together. The monitor can try to take over if the setpoints are too close, causing instability and reduction of capacity. Set them at least one proportional band apart.

# CS200 Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The CS200 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of pressure-reducing applications including commercial and industrial installations. This flexibility is provided by the numerous body sizes, outlet pressure settings and orifice sizes. Ease of maintenance and installation are also strengths of the CS200 Series, which offers a full 360° of rotation of the actuator via the union ring connection between the body and casing. The combination of 360° rotatable union ring along with a rotatable upper casing provide simplified vent position, especially in tight spaces or awkward installations.

The CS200 Series also offers Overpressure Protection in the form of Internal Relief and Secondary Seat™ Protection.

### Body Sizes, End Connection Style and Pressure Rating

See Table 2

### Inlet Pressure Ratings

See Table 4

### Maximum Outlet Pressures

Casing: 25 psig / 1.7 bar

To Avoid Internal Parts Damage:

5 psi / 0.34 bar differential above outlet pressure setting

Operating: 2 psig / 138 mbar

### Outlet Pressure Range

3.5 in. w.c. to 2 psig / 9 mbar to 138 mbar

See Table 5

### Spring Case Vent Connection

1 NPT

### Temperature Capabilities

-20 to 150°F / -29 to 66°C

### Pressure Registration

Internal

### Approximate Shipping Weight

8 lbs / 4 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



11/13

### Features

- Wide Range of NPT Body Sizes
- Easy to Install and Maintain
- Only Standard Tools Required for Pressure Adjustment and Orifice Removal
- Fixed Factor Accuracy (PFM Approved)
- Application Flexibility
- Secondary Seat Protection




Figure 1. Typical CS200 Pressure Reducing Regulator




Figure 2. Type CS200IR Pressure Reducing Regulator Operational Schematic



**Table 1. Available Configuration**

TYPE NUMBER				OPTION	
C	S	2	0		
					<b>OVERPRESSURE PROTECTION MODULE</b>
			0		Without Overpressure Protection Module
			5		With Secondary Seat™ Protection
			6		With Secondary Seat Protection with bleed to indicate Secondary Seat is functioning
					<b>PRESSURE REGISTRATION</b>
				I	Internal Registration
					<b>RELIEF</b>
				N	Non-Relief
				R	Internal Relief

**Table 2. Body Size, Material, End Connection Style and Pressure Rating**

SERIES	BODY SIZE	END CONNECTION STYLE	BODY MATERIAL	PRESSURE RATING	
				psig	bar
CS200	3/4 3/4 x 1 3/4 x 1-1/4 1 1 x 1-1/4 1-1/4	NPT	Gray Cast Iron	175	12.1

**Table 3. Construction Material**

BODY	BODY O-RING	CLOSING CAP	ADJUSTING SCREW	DIAPHRAGM CASE, SPRING CASE AND VALVE STEM	DIAPHRAGM HEAD	ORIFICE	PUSHER POST	DIAPHRAGM AND DISK	LEVER PIN
Gray Cast Iron	Nitrile (NBR)	Aluminum	Aluminum	Aluminum	Steel	Aluminum	Aluminum	Nitrile (NBR)	18-8 Stainless steel

**Table 4. Orifice Size and Inlet Pressure Rating**

SERIES	ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE <sup>(1)(2)</sup>		MAXIMUM EMERGENCY INLET PRESSURE	
	In.	mm	psig	bar	psig	bar
CS200	1/8	3.2	125	8.6	175	12.1
	3/16	4.8	125	8.6		
	1/4	6.4	125	8.6		
	3/8	9.5	60	4.1		
	1/2	13	40	2.8		

1. Inlet pressures based on lockup performance. For maximum inlet pressure values with optimum regulating performance refer to the applicable Flow Capacity table.  
2. To comply with ANSI B109.4 relief requirements the maximum inlet pressure may need to be reduced. Reference the Relief Performance Tables 8 and 11.

**Table 5. Outlet Pressure Range**

SERIES	OUTLET PRESSURE RANGE		PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	In. w.c.	mbar			In.	mm	In.	mm
CS200	3.5 to 5	9 to 12	GE30198X012	Red	0.102	2.59	3.95	100
	4.5 to 6.5	11 to 16	GE30195X012	Purple	0.090	2.28	4.32	110
	6 to 8	15 to 20	GE30188x012	Gold	0.111	2.82	4.48	114
	7.5 to 11	19 to 27	GE30189X012	Blue	0.112	2.84	4.40	112
	10 to 14	25 to 35	GE30224X012	Unpainted	0.102	2.59	4.78	121
	12 to 19	30 to 47	GE30196X012	Green	0.112	2.84	4.70	119
	18 to 1 psig	45 to 0.07 bar	GE30225X012	Orange	0.120	3.04	4.94	125
	1 to 2 psig	0.07 to 0.14 bar	GE30190X012	Black	0.145	3.68	4.66	118

**Table 6. Flow and Sizing Coefficient**

SERIES	ORIFICE SIZE		FLOW COEFFICIENT (WIDE-OPEN)			IEC SIZING COEFFICIENT		
	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	X <sub>r</sub>	F <sub>d</sub>	F <sub>L</sub>
CS200	1/8	3.2	12	0.40	30	0.53	0.87	0.89
	3/16	4.8	24	0.80	30	0.58	0.82	
	1/4	6.4	44	1.52	29	0.53	0.85	
	3/8	9.5	102	3.30	31	0.60	0.83	
	1/2	13	172	4.40	39	0.97	0.72	

# CS200 Series

## Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	Droop	Boost		
7 in. w.c.	-1 in. w.c.	2 in. w.c.	6 to 8 in. w.c.	GE30188X012 / Gold
17 mbar	-2 mbar	5 mbar	15 to 20 mbar	

**Table 7. Types CS200IN and CS200IR Series Flow Capacities for 7 in. w.c. / 17 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
0.5	34 mbar	60	1.6	120	3.2	170	4.6	225	6.0	300	8.1
1	69 mbar	100	2.7	175	4.7	300	8.1	350	9.4	425	11.4
2	138 mbar	130	3.5	250	6.7	325	8.7	525	14.1	625	16.8
3	0.21	160	4.3	325	8.7	400	10.7	600	16.1	825	22.1
5	0.34	220	5.9	425	11.4	675	18.1	925	24.8	1050	28.2
10	0.69	300	8.1	700	18.8	1025	27.5	1400	37.6	1400	37.6
15	1.0	375	10.1	900	24.2	1400	37.6	1675	45.0	1550	41.6
20	1.4	475	12.8	1050	28.2	1625	43.6	1825	49.0	1725	46.3
30	2.1	600	16.1	1375	36.9	1975	53.0	2000	53.7		
40	2.8	750	20.1	1700	45.6	2075	55.7	2000	53.7		
50	3.4	900	24.2	2025	54.4	2150	57.7	2000	53.7		
60	4.1	1050	28.2	2350	63.1	2200	59.1				
80	5.5	1350	36.2	2350	63.1	2250	60.4				
100	6.9	1650	44.3	2350	63.1						
125	8.6	2000	53.7								
psig	bar	Body Size: NPS 1									
0.5	34 mbar	60	1.6	120	3.2	170	4.6	240	6.4	300	8.1
1	69 mbar	100	2.7	175	4.7	300	8.1	400	10.7	425	11.4
2	138 mbar	130	3.5	250	6.7	400	10.7	575	15.4	775	20.8
3	0.21	160	4.3	325	8.7	475	12.8	750	20.1	1025	27.5
5	0.34	220	5.9	425	11.4	700	18.8	1100	29.5	1375	36.9
10	0.69	300	8.1	700	18.8	1150	30.9	1775	47.7	2075	55.7
15	1.0	375	10.1	900	24.2	1600	43.0	2300	61.7	2525	67.8
20	1.4	475	12.8	1050	28.2	1950	52.3	2650	71.1	2675	71.8
30	2.1	600	16.1	1375	36.9	2550	68.5	3325	89.3	3250	87.2
40	2.8	750	20.1	1375	36.9	3100	83.2	3775	101	3400	91.3
50	3.4	900	24.2	1375	36.9	1350	36.2	3775	101		
60	4.1	1050	28.2	1375	36.9	1250	33.6	3775	101		
80	5.5	1350	36.2	1375	36.9	1250	33.6				
100	6.9	1350	36.2	1375	36.9	1250	33.6				
125	8.6	1350	36.2	1250	33.6	1250	33.6				
psig	bar	Body Size: NPS 1-1/4									
0.5	34 mbar	60	1.6	100	2.6	160	4.2	240	6.4	300	8.1
1	69 mbar	100	2.7	170	4.5	250	6.7	400	10.7	425	11.4
2	138 mbar	130	3.5	250	6.7	400	10.7	575	15.4	775	20.8
3	0.21	160	4.3	270	7.2	475	12.8	775	20.8	1050	28.2
5	0.34	220	5.9	425	11.4	700	18.8	1175	31.5	1475	39.6
10	0.69	300	8.1	700	18.8	1150	30.9	2150	57.7	2450	65.8
15	1.0	375	10.1	870	23.4	1600	43.0	3000	80.5	3300	88.6
20	1.4	500	13.4	1050	28.2	1900	51.0	3200	85.9	2750	73.8
30	2.1	625	16.8	1320	35.4	2550	68.5	2200	59.1	2000	53.7
40	2.8	775	20.8	1725	46.3	2800	75.2	1825	49.0	1700	45.6
50	3.4	950	25.5	2025	54.4	2350	63.1	1600	42.9		
60	4.1	1075	28.9	2375	63.8	1900	51.0	1600	42.9		
80	5.5	1375	36.9	2875	77.2	1900	51.0				
100	6.9	1700	45.6	3150	84.6	1900	51.0				
125	8.6	1700	53.0	3175	85.2	1900	51.0				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Gray areas indicate limited capacities due to boost effects.






Figure 3. Type CS200IR Relief Curves (Linkage Disconnect) at 7 in. w.c. / 17 mbar Set Pressure

Table 8. Type CS200IR Internal Relief Performance Table for 7 in. w.c. / 17 mbar Setpoint

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT OR BELOW <sup>(1)(2)</sup>			
				1 psig / 0.07 bar		2 psig / 0.14 bar	
In.	mm	In. w.c.	mbar	psig	bar	psig	bar
1/8	3.2	7	17	36	2.5	>125	>8.6
3/16	4.8			15	1.0	74	5.1
1/4	6.4			6	0.41	36	2.5
3/8	9.5			3	0.21	12	0.83

1. Relief value obtained by disconnecting the lever.  
 2. 2 psig / 138 mbar is the maximum outlet pressure allowed per ANSI B109.4.

# CS200 Series

## Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	Droop	Boost		
11 in. w.c.	-2 in. w.c.	2 in. w.c.	7.5 to 11 in. w.c.	GE30189X012 / Blue
27 mbar	-5 mbar	5 mbar	19 to 27 mbar	

**Table 9. Types CS200IN and CS200IR Series Flow Capacities for 11 in. w.c. / 27 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
1	69 mbar	85	2.3	185	5.0	300	8.1	425	11.4	575	15.4
2	138 mbar	130	3.5	285	7.7	425	11.4	600	16.1	825	22.1
3	0.21	170	4.6	350	9.4	525	14.1	775	20.8	1050	28.2
5	0.34	225	6.0	480	12.9	775	20.8	1150	30.9	1300	34.9
10	0.69	325	8.7	700	18.8	1200	32.2	1550	41.6	1625	43.6
15	1.0	400	10.7	900	24.2	1500	40.3	1850	49.7	1775	47.7
20	1.4	480	12.9	1075	28.9	1750	47.0	2025	54.4	2200	59.1
30	2.1	625	16.8	1400	37.6	2125	57.0	2200	59.1	2200	59.1
40	2.8	775	20.8	1700	45.6	2300	61.7	2200	59.1	2200	59.1
50	3.4	925	24.8	2025	54.4	2375	63.8	2200	59.1		
60	4.1	1050	28.2	2350	63.1	2450	65.8	2200	59.1		
80	5.5	1350	36.2	2500	67.1	2500	67.1				
100	6.9	1650	44.3	2500	67.1	2500	67.1				
125	8.6	1950	52.3	2500	67.1	2500	67.1				
psig	bar	Body Size: NPS 1									
1	69 mbar	85	2.3	185	5.0	300	8.1	500	13.4	650	17.4
2	138 mbar	130	3.5	285	7.7	425	11.4	725	19.5	975	26.2
3	0.21	170	4.6	350	9.4	525	14.1	925	24.8	1250	33.6
5	0.34	225	6.0	480	12.9	775	20.8	1325	35.6	1750	47.0
10	0.69	325	8.7	700	18.8	1250	33.6	1950	52.3	2400	64.4
15	1.0	400	10.7	900	24.2	1625	43.6	2500	67.1	2850	76.5
20	1.4	480	12.9	1075	28.9	1950	52.3	2925	78.5	2900	77.9
30	2.1	625	16.8	1400	37.6	2550	68.5	3550	95.3		
40	2.8	775	20.8	1725	46.3	3125	83.9	3900	105		
50	3.4	925	24.8	2050	55.0	1475	39.6	3900	105		
60	4.1	1050	28.2	1350	36.2	1475	39.6				
80	5.5	1350	36.2	1350	36.2	1475	39.6				
100	6.9	1475	39.6	1350	36.2						
125	8.6	1600	43.0								
psig	bar	Body Size: NPS 1-1/4									
1	69 mbar	85	2.3	170	4.6	300	8.1	500	13.4	650	17.4
2	138 mbar	130	3.5	270	7.2	425	11.4	725	19.5	1100	29.5
3	0.21	170	4.6	350	9.4	525	14.1	1000	26.8	1475	39.6
5	0.34	225	6.0	480	12.9	775	20.8	1375	36.9	2000	53.7
10	0.69	325	8.7	700	18.8	1250	33.6	2225	59.7	2450	65.8
15	1.0	400	10.7	900	24.2	1625	43.6	2850	76.5	2875	77.2
20	1.4	480	12.9	1075	28.9	1950	52.3	3400	91.3	3525	94.5
30	2.1	625	16.8	1400	37.6	2500	67.1	3400	91.3	1800	48.3
40	2.8	775	20.8	1725	46.3	2500	67.1	2400	64.4	1800	48.3
50	3.4	925	24.8	2050	55.0	2500	67.1	1700	45.6		
60	4.1	1050	28.2	2350	63.1	2500	67.1	1700	45.6		
80	5.5	1350	36.2	2975	79.9	2000	53.6				
100	6.9	1650	44.3	1700	45.6	1900	51.0				
125	8.6	2000	53.7	1700	45.6	1900	51.0				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Gray areas indicate limited capacities due to boost effects.



SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	Drop	Boost		
14 in. w.c.	-2 in. w.c.	2 in. w.c.	10 to 14 in. w.c.	GE30224X012 / Unpainted
35 mbar	-5 mbar	5 mbar	25 to 35 mbar	

**Table 10. Types CS200IN and CS200IR Series Flow Capacities for 14 in. w.c. / 35 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
1	69 mbar	85	2.3	185	5.0	300	8.1	425	11.4	575	15.4
2	138 mbar	130	3.5	285	7.7	425	11.4	600	16.1	825	22.1
3	0.21	170	4.6	350	9.4	525	14.1	775	20.8	1050	28.2
5	0.34	225	6.0	480	12.9	775	20.8	1150	30.9	1300	34.9
10	0.69	325	8.7	700	18.8	1200	32.2	1550	41.6	1625	43.6
15	1.0	400	10.7	900	24.2	1500	40.3	1850	49.7	1775	47.7
20	1.4	480	12.9	1075	28.9	1750	47.0	2025	54.4	2200	59.1
30	2.1	625	16.8	1400	37.6	2125	57.0	2200	59.1		
40	2.8	775	20.8	1700	45.6	2300	61.7	2200	59.1		
50	3.4	925	24.8	2025	54.4	2375	63.8	2200	59.1		
60	4.1	1050	28.2	2350	63.1	2450	65.8				
80	5.5	1350	36.2	2500	67.1	2500	67.1				
100	6.9	1650	44.3	2500	67.1						
125	8.6	1950	52.3								
psig	bar	Body Size: NPS 1									
1	69 mbar	85	2.3	185	5.0	300	8.1	500	13.4	650	17.4
2	138 mbar	130	3.5	285	7.7	425	11.4	725	19.5	975	26.2
3	0.21	170	4.6	350	9.4	525	14.1	925	24.8	1250	33.6
5	0.34	225	6.0	480	12.9	775	20.8	1325	35.6	1750	47.0
10	0.69	325	8.7	700	18.8	1250	33.6	1950	52.3	2400	64.4
15	1.0	400	10.7	900	24.2	1625	43.6	2500	67.1	2850	76.5
20	1.4	480	12.9	1075	28.9	1950	52.3	2925	78.5	2900	77.9
30	2.1	625	16.8	1400	37.6	2550	68.5	3550	95.3	3400	91.3
40	2.8	775	20.8	1725	46.3	3125	83.9	3900	105		
50	3.4	925	24.8	2050	55.0	1475	39.6	3900	105		
60	4.1	1050	28.2	1350	36.2	1475	39.6				
80	5.5	1350	36.2	1350	36.2	1475	39.6				
100	6.9	1475	39.6	1350	36.2						
125	8.6	1600	43.0								
psig	bar	Body Size: NPS 1-1/4									
1	69 mbar	85	2.3	185	5.0	280	7.5	500	13.4	650	17.4
2	138 mbar	130	3.5	245	6.6	425	11.4	725	19.5	1100	29.5
3	0.21	170	4.6	350	9.4	525	14.1	1000	26.8	1475	39.6
5	0.34	225	6.0	480	12.9	775	20.8	1375	36.9	2000	53.7
10	0.69	325	8.7	700	18.8	1250	33.6	2225	59.7	2450	65.8
15	1.0	400	10.7	900	24.2	1625	43.6	2850	76.5	2875	77.2
20	1.4	480	12.9	1075	28.9	1950	52.3	3400	91.1	3525	94.6
30	2.1	625	16.8	1400	37.6	2300	61.7	3400	91.1	1850	49.7
40	2.8	775	20.8	1725	46.3	2300	61.7	2300	61.7	1850	49.7
50	3.4	925	24.8	2050	55.0	2300	61.7	2150	57.7		
60	4.1	1050	28.2	2350	63.1	2300	61.7	2150	57.7		
80	5.5	1350	36.2	2975	79.9	2000	53.6				
100	6.9	1650	44.3	2975	79.9	1900	51.0				
125	8.6	2000	53.7	2975	79.9	1900	51.0				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Gray areas indicate limited capacities due to boost effects.

# CS200 Series

## Pressure Reducing Regulator

FISHER™




Figure 4. Type CS200IR Relief Curves (Linkage Disconnect) at 14 in. w.c. / 35 mbar Set Pressure

Table 11. Type CS200IR Internal Relief Performance Table for 14 in. w.c. / 35 mbar Setpoint

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT OR BELOW <sup>(1)(2)</sup>			
				2 psig / 0.14 bar		2.5 psig / 0.17 bar	
In.	mm	In. w.c.	mbar	psig	bar	psig	bar
1/8	3.2	14	35	>125	>8.6	>125	>8.6
3/16	4.8			59	4.1	82	5.7
1/4	6.4			28	1.9	40	2.8
3/8	9.5			10	0.69	14	0.97

1. Relief value obtained by disconnecting the lever.  
 2. 2 psig / 138 mbar is the maximum outlet pressure allowed per ANSI B109.4.

SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	+ / - 1% ABS			
1 psig	-0.16 psi	0.16 psi	18 in. w.c. to 1 psig	GE30225X012 / Orange
69 mbar	-11 mbar	11 mbar	45 to 69 mbar	

**Table 12. Types CS200IN and CS200IR Series Flow Capacities for 1 psig / 69 mbar Setpoint at 1% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
2	138 mbar	115	3.1	240	6.4	375	10.1	625	16.8	875	23.5
3	0.21	150	4.0	325	8.7	500	13.4	800	21.5	1175	31.5
5	0.34	225	6.0	450	12.1	725	19.5	1200	32.2	1475	39.6
10	0.69	325	8.7	725	19.5	1150	30.9	1750	47.0	1950	52.3
15	1.0	400	10.7	850	22.8	1500	40.3	2100	56.4	2225	59.7
20	1.4	475	12.8	1025	27.5	1725	46.3	2300	61.7	2350	63.1
30	2.1	625	16.8	1400	37.6	2175	58.4	2675	71.8	2700	72.5
40	2.8	750	20.1	1700	45.6	2550	68.5	2675	71.8	2700	72.5
50	3.4	900	24.2	2000	53.7	2650	71.1	2675	71.8		
60	4.1	1050	28.2	2350	63.1	2750	73.8	2675	71.8		
80	5.5	1350	36.2	2850	76.5	2850	76.5				
100	6.9	1600	43.0	2850	76.5	2850	76.5				
125	8.6	1975	53.0	2850	76.5						
psig	bar	Body Size: NPS 1									
2	138 mbar	115	3.1	240	6.4	400	10.7	675	18.1	950	25.5
3	0.21	150	4.0	325	8.7	550	14.8	975	26.2	1325	35.6
5	0.34	225	6.0	450	12.1	775	20.8	1400	37.6	1850	49.7
10	0.69	325	8.7	725	19.5	1200	32.2	2100	56.4	2600	69.8
15	1.0	400	10.7	850	22.8	1600	43.0	2750	73.8	3100	83.2
20	1.4	475	12.8	1025	27.5	1900	51.0	3200	85.9	3450	92.6
30	2.1	625	16.8	1400	37.6	2425	65.1	3750	101	4000	107
40	2.8	750	20.1	1700	45.6	3150	84.6	4375	117	4000	107
50	3.4	900	24.2	2000	53.7	3700	99.3	4550	122		
60	4.1	1050	28.2	2350	63.1	4150	111	4550	122		
80	5.5	1350	36.2	2975	79.9	4150	111				
100	6.9	1600	43.0	3650	98.0	4150	111				
125	8.6	1975	53.0	4400	118	4150	111				
psig	bar	Body Size: NPS 1-1/4									
2	138 mbar	115	3.1	240	6.4	425	11.4	750	20.1	1000	26.8
3	0.21	150	4.0	325	8.7	575	15.4	1050	28.2	1450	38.9
5	0.34	225	6.0	450	12.1	825	22.1	1500	40.2	2100	56.4
10	0.69	325	8.7	725	19.5	1300	34.9	2475	66.4	3250	87.2
15	1.0	400	10.7	850	22.8	1600	42.9	3325	89.3	4100	110
20	1.4	475	12.8	1025	27.5	1925	51.7	4095	110	4900	131
30	2.1	625	16.8	1400	37.6	2500	67.1	4400	118	4900	131
40	2.8	750	20.1	1700	45.6	3025	81.2	4400	118	4900	131
50	3.4	900	24.2	2000	53.7	3175	85.2	4400	118		
60	4.1	1050	28.2	2350	63.1	4275	115	4400	118		
80	5.5	1350	36.2	2975	79.9	4600	123				
100	6.9	1600	43.0	3650	98.0	4600	123				
125	8.6	1975	53.0	4400	118	4600	123				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS200 Series

## Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	+ / - 2% ABS			
1 psig	-0.31 psi	0.31 psi	18 in. w.c. to 1 psig	GE30225X012 / Orange
69 mbar	-21 mbar	21 mbar	45 to 69 mbar	

**Table 13. Types CS200IN and CS200IR Series Flow Capacities for 1 psig / 69 mbar Setpoint at 2% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
2	138 mbar	115	3.1	275	7.4	450	12.1	875	23.5	1300	34.9
3	0.21	150	4.0	350	9.4	600	16.1	1150	30.9	1675	45.0
5	0.34	225	6.0	500	13.4	850	22.8	1625	43.6	2150	57.7
10	0.69	325	8.7	775	20.8	1300	34.9	2425	65.1	2550	68.5
15	1.0	400	10.7	925	24.8	1650	44.3	2775	74.5	2875	77.2
20	1.4	475	12.8	1050	28.2	1925	51.7	3000	80.5	2975	79.9
30	2.1	625	16.8	1425	38.3	2500	67.1	3325	89.3	3400	91.3
40	2.8	750	20.1	1725	46.3	3025	81.2	3500	94.0	3500	94.0
50	3.4	900	24.2	2050	55.0	3425	91.9	3500	94.0		
60	4.1	1050	28.2	2375	63.8	3500	94.0	3500	94.0		
80	5.5	1350	36.2	3000	80.5	3500	94.0				
100	6.9	1600	43.0	3600	96.6	3500	94.0				
125	8.6	1975	53.0	3700	99.3						
psig	bar	Body Size: NPS 1									
2	138 mbar	115	3.1	275	7.4	450	12.1	950	25.5	1450	38.9
3	0.21	150	4.0	350	9.4	600	16.1	1275	34.2	1850	49.7
5	0.34	225	6.0	500	13.4	850	22.8	1775	47.7	2525	67.8
10	0.69	325	8.7	775	20.8	1300	34.9	2700	72.5	3400	91.3
15	1.0	400	10.7	925	24.8	1650	44.3	3425	91.9	4025	108
20	1.4	475	12.8	1050	28.2	1925	51.7	4000	107	4450	120
30	2.1	625	16.8	1425	38.3	2500	67.1	4800	129	4875	131
40	2.8	750	20.1	1725	46.3	3100	83.2	5450	146	5425	146
50	3.4	900	24.2	2050	55.0	3675	98.7	5950	160		
60	4.1	1050	28.2	2375	63.8	4275	115	6000	161		
80	5.5	1350	36.2	3000	80.5	5425	146				
100	6.9	1600	43.0	3600	96.6	5825	156				
125	8.6	1975	53.0	4400	118	5825	156				
psig	bar	Body Size: NPS 1-1/4									
2	138 mbar	115	3.1	275	7.4	450	12.1	1000	26.8	1450	38.9
3	0.21	150	4.0	350	9.4	600	16.1	1325	35.6	1950	52.3
5	0.34	225	6.0	500	13.4	850	22.8	1875	50.3	2800	75.2
10	0.69	325	8.7	775	20.8	1300	34.9	2825	75.8	4250	114
15	1.0	400	10.7	925	24.8	1650	44.3	3600	96.6	5250	141
20	1.4	475	12.8	1050	28.2	1925	51.7	4200	113	6200	166
30	2.1	625	16.8	1425	38.3	2500	67.1	5625	151	7400	199
40	2.8	750	20.1	1725	46.3	3100	83.2	6825	183	7600	204
50	3.4	900	24.2	2050	55.0	3675	98.7	7000	188		
60	4.1	1050	28.2	2375	63.8	4275	115	7000	188		
80	5.5	1350	36.2	3000	80.5	5425	146				
100	6.9	1600	43.0	3600	96.6	5825	156				
125	8.6	1975	53.0	4400	118	5825	156				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.








Figure 5. Type CS200IR Relief Curves (Linkage Disconnect) at 1 psig / 69 mbar Set Pressure

Table 14. Type CS200IR Internal Relief Performance Table for 1 psig / 69 mbar Setpoint

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT OR BELOW <sup>(1)</sup>			
				2.5 psig / 0.17 bar		3 psig / 0.21 bar	
In.	mm	psig	mbar	psig	bar	psig	bar
1/8	3.2	1	69	121	8.3	>125	>8.6
3/16	4.8			49	3.4	74	5.1
1/4	6.4			24	1.7	38	2.6
3/8	9.5			8	0.55	12	0.83

1. Relief value obtained by disconnecting the lever.

# CS200 Series

## Pressure Reducing Regulator

FISHER™

SETPPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	+ / - 1% ABS			
2 psig	-0.17 psi	0.17 psi	1 to 2 psig	GE30190X012 / Black
138 mbar	-12 mbar	12 mbar	69 to 138 mbar	

**Table 15. Types CS200IN and CS200IR Series Flow Capacities for 2 psig / 138 mbar Setpoint at 1% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
3	0.21	120	3.2	250	6.7	250	6.7	425	11.4	550	14.8
5	0.34	150	4.0	350	9.4	445	11.9	700	18.8	1000	26.8
10	0.69	250	6.7	550	14.8	720	19.3	1125	30.2	1550	41.6
15	1.0	330	8.9	750	20.1	1100	29.5	1575	42.3	1900	51.0
20	1.4	425	11.4	950	25.5	1375	36.9	1800	48.3	2125	57.0
30	2.1	550	14.8	1300	34.9	1850	49.7	2150	57.7	2475	66.4
40	2.8	750	20.1	1425	38.3	2175	58.4	2450	65.8	2575	69.1
50	3.4	875	23.5	1900	51.0	2475	66.4	2575	69.1		
60	4.1	1025	27.5	2100	56.4	2600	69.8	2675	71.8		
80	5.5	1300	34.9	2475	66.4	2850	76.5				
100	6.9	1600	43.0	2725	73.2	2850	76.5				
125	8.6	1975	53.0	2850	76.5						
psig	bar	Body Size: NPS 1									
3	0.21	120	3.2	250	6.7	300	8.1	475	12.8	675	18.1
5	0.34	150	4.0	350	9.4	445	11.9	800	21.5	1000	26.8
10	0.69	250	6.7	550	14.8	720	19.3	1400	37.6	1850	49.7
15	1.0	330	8.9	800	21.5	1120	30.1	1900	51.0	2500	67.1
20	1.4	425	11.4	1000	26.8	1445	38.8	2325	62.4	2800	75.2
30	2.1	550	14.8	1350	36.2	2045	54.9	3000	80.5	3300	88.6
40	2.8	750	20.1	1600	43.0	2750	73.8	3500	94.0	4100	110
50	3.4	875	23.5	1950	52.3	3300	88.6	3900	105		
60	4.1	1025	27.5	2300	61.7	3825	103	4100	110		
80	5.5	1300	34.9	3000	80.5	4200	113				
100	6.9	1600	43.0	3550	95.3	4200	113				
125	8.6	1975	53.0	4200	113	4200	113				
psig	bar	Body Size: NPS 1-1/4									
3	0.21	120	3.2	250	6.7	290	7.7	475	12.8	675	18.1
5	0.34	150	4.0	350	9.4	445	11.9	825	22.1	1000	26.8
10	0.69	250	6.7	550	14.8	720	19.3	1500	40.3	1850	49.7
15	1.0	330	8.9	800	21.5	1120	30.1	2175	58.4	2800	75.2
20	1.4	425	11.4	1000	26.8	1495	40.1	2675	71.8	3675	98.7
30	2.1	550	14.8	1350	36.2	2220	59.6	3950	106	5400	145
40	2.8	750	20.1	1600	43.0	3000	80.5	5400	145	5400	145
50	3.4	875	23.5	1950	52.3	3475	93.3	5400	145		
60	4.1	1025	27.5	2300	61.7	4075	109	5400	145		
80	5.5	1300	34.9	3000	80.5	4400	118				
100	6.9	1600	43.0	3550	95.3	4400	118				
125	8.6	1975	53.0	4200	113	4400	118				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY		SET RANGE	SPRING PART NUMBER / COLOR
	+ / - 2% ABS			
2 psig	-0.33 psi	0.33 psi	1 to 2 psig	GE30190X012 / Black
138 mbar	-23 mbar	23 mbar	69 to 138 mbar	

**Table 16. Types CS200IN and CS200IR Series Flow Capacities for 2 psig / 138 mbar Setpoint at 2% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 3/4									
3	0.21	120	3.2	275	7.4	450	12.1	700	18.8	1100	29.5
5	0.34	150	4.0	425	11.4	675	18.1	1050	28.2	1550	41.6
10	0.69	250	6.7	675	18.1	1150	30.9	1850	49.7	2225	59.7
15	1.0	330	8.9	875	23.5	1450	38.9	2175	58.4	2650	71.1
20	1.4	425	11.4	1050	28.2	1725	46.3	2500	67.1	2825	75.8
30	2.1	550	14.8	1400	37.6	2150	57.7	2975	79.9	3300	88.6
40	2.8	750	20.1	1650	44.3	2800	75.2	3275	87.9	3300	88.6
50	3.4	875	23.5	2050	55.0	3000	80.5	3400	91.3		
60	4.1	1025	27.5	2275	61.1	3300	88.6	3400	91.3		
80	5.5	1300	34.9	3000	80.5	3500	94.0				
100	6.9	1600	43.0	3400	91.3	3500	94.0				
125	8.6	1975	53.0	3400	91.3						
psig	bar	Body Size: NPS 1									
3	0.21	120	3.2	275	7.4	450	12.1	700	18.8	1100	29.5
5	0.34	150	4.0	425	11.4	675	18.1	1250	33.6	1725	46.3
10	0.69	250	6.7	675	18.1	1175	31.5	2075	55.7	2750	73.8
15	1.0	330	8.9	875	23.5	1550	41.6	2675	71.8	3425	91.9
20	1.4	425	11.4	1050	28.2	1900	51.0	3250	87.2	3900	105
30	2.1	550	14.8	1400	37.6	2500	67.1	4025	108	4475	120
40	2.8	750	20.1	1650	44.3	3050	81.9	4550	122	5100	137
50	3.4	875	23.5	2050	55.0	3650	98.0	5000	134		
60	4.1	1025	27.5	2275	61.1	4250	114	5200	140		
80	5.5	1300	34.9	3000	80.5	5450	146				
100	6.9	1600	43.0	3600	96.6	5700	153				
125	8.6	1975	53.0	4450	120	5700	153				
psig	bar	Body Size: NPS 1-1/4									
3	0.21	120	3.2	275	7.4	430	11.5	750	20.1	1150	30.9
5	0.34	150	4.0	425	11.4	675	18.1	1300	34.9	1700	45.6
10	0.69	250	6.7	675	18.1	1175	31.5	2225	59.7	3090	83.0
15	1.0	330	8.9	875	23.5	1550	41.6	2975	79.9	4090	110
20	1.4	425	11.4	1050	28.2	1900	51.0	3800	102	5025	135
30	2.1	550	14.8	1400	37.6	2500	67.1	5250	141	5900	158
40	2.8	750	20.1	1650	44.3	3050	81.9	5800	155	5900	158
50	3.4	875	23.5	2050	55.0	3650	98.0	5800	155		
60	4.1	1025	27.5	2275	61.1	4250	114	5800	155		
80	5.5	1300	34.9	3000	80.5	4900	131				
100	6.9	1600	43.0	3600	96.6	4900	131				
125	8.6	1975	53.0	4450	120	4900	131				

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS200 Series

## Pressure Reducing Regulator

FISHER™




Figure 6. Type CS200IR Relief Curves (Linkage Disconnect) at 2 psig / 0.14 bar Set Pressure

Table 17. Type CS200IR Internal Relief Performance Table for 2 psig / 138 mbar Setpoint

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT OR BELOW <sup>(1)</sup>			
				4 psig / 0.28 bar		5 psig / 0.34 bar	
In.	mm	psig	mbar	psig	bar	psig	bar
1/8	3.2	2	138	122	8.4	>125	>8.6
3/16	4.8			47	3.2	96	6.6
1/4	6.4			23	1.6	49	3.4
3/8	9.5			9	0.62	17	1.17

1. Relief value obtained by disconnecting the lever.






Figure 7. Body Positions and Spring Case Vent Locations





GE34192



IN. /  
mm

Figure 8. Dimension

Table 18. Dimension					
BODY SIZE, NPT		DIMENSION			
Inlet	Outlet	B		C	
		In.	mm	In.	mm
3/4	3/4	5.84	148	9.93	252
3/4	1				
1	1				
3/4	1-1/4	6.02	153	10.1	257
1					
1-1/4					

# CS200 Series

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Type (Select One)

- CS200IN\*\*\*
- CS200IR\*\*\*
- CS205IN\*\*\*
- CS205IR\*\*\*
- CS206IR\*\*\*

### Body Size, Material and End Connection (Select One)

#### Gray Cast Iron

- 3/4 NPT\*\*\*
- 3/4 x 1 NPT\*\*\*
- 3/4 x 1-1/4 NPT\*\*\*
- 1 NPT\*\*\*
- 1 x 1-1/4 NPT\*\*\*
- 1-1/4 NPT\*\*\*

### Outlet Pressure Range (Select One)

- 3.5 to 5 in. w.c. / 9 to 12 mbar, Red\*\*\*
- 4.5 to 6.5 in. w.c. / 11 to 16 mbar, Purple\*\*\*
- 6 to 8 in. w.c. / 15 to 20 mbar, Gold\*\*\*
- 7.5 to 11 in. w.c. / 19 to 27 mbar, Blue\*\*\*
- 10 to 14 in. w.c. / 25 to 35 mbar, Unpainted\*\*\*
- 12 to 19 in. w.c. / 30 to 47 mbar, Green\*\*\*
- 18 in. w.c. to 1 psig / 45 to 69 mbar, Orange\*\*\*
- 1 to 2 psig / 69 to 138 mbar, Black\*\*\*

### Orifice Size (Select One)

- 1/8 in. / 3.2 mm\*\*\*
- 3/16 in. / 4.8 mm\*\*\*
- 1/4 in. / 6.4 mm\*\*\*
- 3/8 in. / 9.5 mm\*\*\*
- 1/2 in. / 13 mm\*\*\*

### Body Orientation (Select One)

- Position 1\*\*\*
- Position 2\*\*\*
- Position 3 (standard)\*\*\*
- Position 4\*\*\*

### Vent Orientation (Select One)

- Position C\*\*\*
- Position D\*\*\*
- Position E\*\*\*
- Position F (standard)\*\*\*

### Certification (available only on CS200 Series constructions)

- Pressure Factor Measurement (PFM)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Do not oversize regulators. Pick the smallest orifice size or regulator that will work. Keep in mind when sizing a station that most restricted trims that do not reduce the main port size do not help with improved low flow control.



**Introduction**

The CS400 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of pressure-reducing applications including commercial and industrial installations. This flexibility is provided by the numerous body sizes and end connections, outlet pressure settings orifice sizes, as well as the option for internal or external pressure registration.

In addition to application flexibility, the CS400 Series offers multiple overpressure protection options to meet demands on application requirements.

**Body Sizes, Materials, End Connections and Pressure Rating**  
See Table 2

**Flow Capacities**

See Tables 10, 12, 13, 15, 17, 19 and 21 through 28

**Flow and Sizing Coefficients**  
See Table 9

**Maximum Inlet Pressure**

**Emergency:** 175 psig / 12.1 bar  
**Operating:** See Table 9

**Maximum Outlet Pressure**

**Casing:** 25 psig / 1.7 bar  
**To Avoid Internal Parts Damage:**  
5 psig / 0.34 bar over set pressure  
**Operating:** 5.5 psig / 0.38 bar

**Outlet Pressure Ranges**

3.5 in. w.c. to 5.5 psig / 9 mbar to 0.38 bar  
See Table 4

**Spring Case Vent Connection**  
1 NPT

**Pressure Registration**  
Internal or External

**Operating Temperature (TS)<sup>(1)</sup>**  
**According to PED Standards**  
All Types: -4 to 150°F / -20 to 66°C  
**Non-PED**  
All Types: -20 to 150°F / -29 to 66°C

**Approximate Shipping Weight**  
**With Threaded Body**  
Type CS400: 9 lb / 4.1 kg  
Type CS403: 18.5 lb / 8.4 kg  
Type CS404: 11.2 lb / 5.1 kg  
**With Flanged Body**  
Add 8.6 lbs / 4.0 kg to weights listed in the previous section.

1. Product has passed Fisher™ testing for lockup, relief start-to-discharge and reseal down to -40°.




Figure 1. Typical Type CS400 Pressure Reducing Regulator

Figure 2. Typical Type CS400 Pressure Reducing Regulator Internal View

**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/14

**Features**

- Wide Variety of Body Sizes and End Connections
- Fixed Factor/PFM Accuracy Capabilities
- Only Standard Tools Required for Pressure Adjustment and Orifice Removal
- Easy to Maintain

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator



**Table 1. Available Configurations**

TYPE NUMBER				OPTION			
C	S	4	0				
							<b>OVERPRESSURE PROTECTION MODULE</b>
				0			Without Overpressure Protection Module
				3			With Integral Monitor Module <sup>(1)(3)</sup>
				4			With Slam-Shut Module <sup>(2)</sup>
							<b>PRESSURE REGISTRATION</b>
				E			External Registration <sup>(3)</sup>
				I			Internal Registration
							<b>RELIEF</b>
				N			Non-Relief
				T			Token Internal Relief
				R			Internal Relief
Example: Type number CS404IT: A Type CS400 regulator constructed with Type VSX4 Slam-Shut module, with Internal pressure registration and with Token relief.							
1. Reference Instruction Manual D103126X012 for information regarding the Integral Monitor module. 2. Reference Instruction Manual D103127X012 for information regarding the Type VSX4 safety shut-off module. 3. Available only with Non-Relieving or Token Relief options, not Internal Relief.							

**Table 2. Body Size, Material, End Connection and Pressure Rating**

BODY MATERIAL	BODY SIZE, IN.		END CONNECTION	FACE-TO-FACE DIMENSION		BODY PRESSURE RATING	
	Inlet	Outlet		in.	mm	psig	bar
Gray Cast iron	1-1/4	1-1/4	NPT	4.5	114	175	12.1
	1-1/4	1-1/2					
	1-1/2	1-1/2					
	2	2	NPT	5	127		
	NPS 2 / DN 50	NPS 2 / DN 50	CL125 FF	10	254		
Ductile Cast iron	1-1/4	1-1/4	NPT	4.5	114	290	20.0
	1-1/2	1-1/2					
	2	2					
	1-1/4	1-1/4	Rp	4.5	114		
	1-1/2	1-1/2					
	2	2					
	NPS 2 / DN 50	NPS 2 / DN 50	CL125 FF / CL150 FF	10	254		
PN 10/16			10	254	232	16.0	
Steel	1-1/4	1-1/4	NPT	4.5	114	290	20.0
	1-1/2	1-1/2					
	1-1/4	1-1/4	Rp	4.5	114		
	1-1/2	1-1/2					

**Table 3. CS400 Series Main Valve and Actuator Construction Material**

BODY	CONTROL SPRING	RELIEF VALVE SPRING	LEVER PIN	DIAPHRAGM PLATE	O-RING, DIAPHRAGM AND DISK	CLOSING CAP, ADJUSTING SCREW, VALVE STEM, ORIFICE AND RELIEF VALVE SPRING RETAINER
Gray Cast iron, Ductile iron and Steel	Stainless steel or Music Wire	Stainless steel	Stainless steel	Zinc-plated steel	Nitrile (NBR)	Aluminum








Figure 3. Type CS400IR Internally Registered Regulator with Internal Relief Operational Schematic




Figure 4. Type CS403, Internally Registered Primary Regulator with Internally Registered Integral Monitor Operational Schematic




Figure 5. Type CS404ET with Slam-Shut Module, External Pressure Registration and Token Relief Operational Schematic

# CS400 Series

## Commercial / Industrial – Pressure Reducing Regulator



**Table 4. Outlet Pressure Range**

TYPE	OUTLET PRESSURE RANGE		PART NUMBER	COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	In. w.c.	mbar			In.	mm	In.	mm
CS400, CS403 and CS404	3.5 to 5	9 to 12	GE30198X012	Red	0.098	2.49	4.18	106
	4.5 to 6.5	11 to 16	GE30195X012	Purple	0.080	2.03	4.32	110
	6 to 8	15 to 20	GE30188X012	Gold	0.108	2.74	4.18	106
	7.5 to 11	19 to 27	GE30189X012	Blue	0.110	2.80	4.40	112
	10 to 14	25 to 35	GE30224X012	Unpainted	0.110	2.80	4.40	112
	12 to 19	30 to 47	GE30196X012	Green	0.112	2.85	4.70	119
	18 in. w.c. to 1 psig	45 mbar to 0.07 bar	GE30225X012	Orange	0.120	3.05	4.94	125
	1 to 2 psig	0.07 to 0.14 bar	GE30190X012	Black	0.140	3.56	4.66	118
	2 to 5.5 psig	0.14 to 0.38 bar	GE30197X012	Yellow	0.172	4.37	4.42	112

**Table 5. Approximate Internal Relief Valve Start-to-Discharge Pressure Above Setpoint**

SETPOINT	SPRING COLOR	SPRING PART NUMBER	START-TO-DISCHARGE PRESSURE RANGE ABOVE SETPOINT	
			Internal Relief	Token Relief
7 in. w.c. / 17 mbar	Gold	GE30188X012	6 to 12 in. w.c. / 15 to 30 mbar	6 to 12 in. w.c. / 15 to 30 mbar
11 in. w.c. / 27 mbar	Blue	GE30189X012	6 to 12 in. w.c. / 15 to 30 mbar	6 to 12 in. w.c. / 15 to 30 mbar
14 in. w.c. / 35 mbar	Unpainted	GE30224X012	6 to 12 in. w.c. / 15 to 30 mbar	6 to 12 in. w.c. / 15 to 30 mbar
1 psig / 0.07 bar	Orange	GE30225X012	0.5 to 1.5 psi / 35 to 103 mbar	0.5 to 1 psi / 35 mbar to 0.07 bar
2 psig / 0.14 bar	Black	GE30190X012	0.5 to 1.5 psi / 35 to 103 mbar	0.5 to 1 psi / 35 mbar to 0.07 bar
5 psig / 0.34 bar	Yellow	GE30197X012	0.5 to 3.3 psi / 35 to 228 mbar	0.5 to 2 psi / 35 mbar to 0.14 bar

**Table 6. Type CS403 Regulator and Integral Monitor Outlet Pressure Range**

TYPE	PRIMARY REGULATOR				INTEGRAL MONITOR					
	Setpoint		SPRING PART NUMBER	Spring Color	Setpoint <sup>(1)</sup>		Spring Part Number	Spring Range		Spring Color
	In. w.c.	mbar			In. w.c.	mbar		In. w.c.	mbar	
CS403	4	10	GE30198X012	Red	14	35	GE30189X012	12 to 21	30 to 52	Blue
	5	12	GE30195X012	Purple						
	7	17	GE30188X012	Gold						
	11	27	GE30189X012	Blue	21	52	GE30196X012	18 to 30	45 to 75	Green
	14	35	GE30224X012	Unpainted						
	18	45	GE30196X012	Green	1 psig	0.07 bar	GE30225X012	26 to 40	65 to 99	Orange
	1 psig	0.07 bar	GE30225X012	Orange	1.5 psig	0.10 bar	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
	2 psig	0.14 bar	GE30190X012	Black	2.5 psig	0.17 bar	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
	3 psig	0.21 bar	GE30197X012	Yellow	3.5 psig	0.24 bar	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple
	4 psig	0.28 bar			5 psig	0.34 bar	GE30192X012	3.6 to 6 psig	248 to 414	Dark Blue
	5 psig	0.34 bar			6 psig	0.41 bar	GE33121X012	5.1 to 7.5 psig	352 to 517	Red

1. Integral Monitor setpoints shown represent the minimum setpoint difference between the Integral Monitor and the Primary regulator. Higher monitor setpoints can be chosen, e.g., for a Primary regulator setpoint of 7 in. w.c. / 17 mbar, the Integral Monitor can also be set at 14 and 21 in. w.c. / 35 and 52 mbar; 1 psig / 0.07 bar or higher.



**Table 7. Type CS404 Regulator and Slam-Shut OPSO Pressure Range**

REGULATOR		SLAM-SHUT DEVICE			
Type	Setpoint, In. w.c. / mbar	Spring Range, In. w.c. / mbar	Overpressure Shutoff (OPSO)		
			Factory Setpoint, In. w.c. / mbar <sup>(1)</sup>	Spring Range, In. w.c. / mbar	Spring Part Number
CS404	4 / 10	3.5 to 5 / 9 to 12	18 / 45	12 to 25 / 30 to 60	GF02168X012
	5 / 12	4.5 to 6.5 / 11 to 16	19 / 47		
	7 / 17	6 to 8 / 15 to 20	21 / 52		
	11 / 27	7.5 to 11 / 19 to 27	0.9 psig / 62	0.58 to 1.6 psig / 40 to 110	GF02169X012
	14 / 35	10 to 14 / 25 to 35	1.1 psig / 75		
	0.65 psig / 45	0.45 to 0.7 psig / 30 to 47	1.4 psig / 96	0.87 to 2.8 psig / 60 to 190	GF02170X012
	0.72 psig / 50		1.6 psig / 112		
	1 psig / 69	0.65 to 1 psig / 45 to 69	2.5 psig / 172	1.4 to 4.1 psig / 95 to 280	GF02171X012
	1.5 psig / 103		1 to 2 psig / 69 to 138		
	2 psig / 138	3.5 psig / 241			
	3 psig / 207	2 to 5.5 psig / 138 to 380	6.3 psig / 434	3.2 to 11 psig / 220 to 760	GF02173X012
	4 psig / 276		7.3 psig / 503		
	5 psig / 345		8.3 psig / 572		
5.5 psig / 380	8.8 psig / 606				

1. For Types CS404IT and CS404ET equipped with Token Relief, if Non-Factory slam-shut OPSO setpoints are specified, they must not encroach on the Token Relief Start-to-Discharge values provided in Table 5.

**Table 8. Type CS404 Regulator and Slam-shut OPSO and UPSO Pressure Range**

REGULATOR			SLAM-SHUT DEVICE					
Type	Setpoint, psig / mbar	Spring Range, psig / mbar	Overpressure Shutoff (OPSO)			Underpressure Shutoff (UPSO)		
			Typical Setpoint, psig / mbar <sup>(1)</sup>	Range, psig / mbar	Spring Part Number	Typical Setpoint, psig / mbar <sup>(1)</sup>	Range, psig / mbar	Spring Part Number
CS404	0.51 / 35	0.36 to 0.51 / 25 to 35	1.1 / 75	0.73 to 1.9 / 50 to 130	GF02168X012	0.32 / 22	0.14 to 1.1 / 10 to 75	T14169T0012
	0.65 / 45	0.45 to 0.7 / 30 to 48	1.4 / 95			0.4 / 30		
	0.72 / 50	0.65 to 1 / 45 to 69	1.6 / 110			0.4 / 30		
	1 / 69		2.5 / 172	0.58 / 40				
	1.5 / 103	1 to 2 psig / 69 to 138	3.0 / 207	2.2 to 5.5 / 150 to 380	GF02170X012	0.73 / 50	0.36 to 2.3 / 25 to 160	T14170T0012
	2 / 138		3.5 / 241			1 / 69		
	3 / 207	2 to 5.5 psig / 138 to 380	6.3 / 434	3.8 to 8.7 / 260 to 600	GF02171X012	1.75 / 121	1.5 to 7.3 / 100 to 500	FA142869X12
	4 / 276		7.3 / 503			2 / 140		
	5 / 345		8.3 / 572			2.9 / 200		
	5.5 / 380		8.8 / 606	5.8 to 16 / 400 to 1100	GF02172X012	3.6 / 250		

1. For Types CS404IT and CS404ET equipped with Token Relief, if Non-Factory slam-shut OPSO setpoints are specified, they must not encroach on the Token Relief Start-to-Discharge values provided in Table 5.

**Table 9. Inlet Pressure Rating and Flow and Sizing Coefficient**

TYPE	ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE TO OBTAIN OPTIMUM PERFORMANCE		FLOW COEFFICIENT (WIDE-OPEN)		C <sub>i</sub>	IEC SIZING COEFFICIENT		
	In.	mm	psig	bar	C <sub>0</sub>	C <sub>v</sub>		X <sub>r</sub>	F <sub>0</sub>	F <sub>L</sub>
CS400, CS403 and CS404	3/16	4.8	125	8.6	27	0.97	27.7	0.50	0.89	0.91
	1/4	6.4	125	8.6	50	1.77	28.2	0.50		0.92
	5/16	7.9	100	6.9	82	2.90	28.3	0.50		0.94
	3/8 <sup>(1)</sup>	9.5 <sup>(1)</sup>	60	4.1	113	3.72	30.4	0.58		0.89
	1/2	12	40	2.8	182	5.61	32.4	0.66		0.82
	5/8	16	30	2.1	284	7.26	39.1	0.97		0.74
	3/4	19	20	1.4	356	9.83	36.2	0.83		0.72

1. 80 psig / 5.5 bar maximum operating inlet pressure available at special request for setpoints 1 psig / 0.07 bar or greater.

# CS400 Series

## Commercial / Industrial – Pressure Reducing Regulator



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
7 in. w.c.	-1 in. w.c.	2 in. w.c.	6 to 8 in. w.c.	GE30188X012 / Gold
17 mbar	-2 mbar	5 mbar	15 to 20 mbar	

**Table 10. Type CS400 Internal Registration Flow Capacities for 7 in. w.c. / 17 mbar Setpoint**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4													
0.5	0.03	100	2.6	160	4.2	200	5.3	290	7.7	370	9.9	630	16.9	560	15.0
1	0.07	170	4.5	250	6.7	330	8.8	630	16.9	650	17.4	660	17.7	730	19.5
2	0.14	260	6.9	510	13.6	770	20.6	660	17.7	880	23.6	1100	29.5	1200	32.2
3	0.21	390	10.4	690	18.5	710	19.0	860	23.0	1100	29.5	1700	45.6	1800	48.3
5	0.34	500	13.4	800	21.4	970	26.0	1300	34.8	1600	42.9	2700	72.4	3200	85.9
10	0.69	750	20.1	1200	32.2	1900	51.0	2500	67.1	3300	88.5	3300	88.5	3900	105
15	1.0	1000	26.8	1700	45.6	2800	75.1	3200	85.9	3300	88.5	3300	88.5	3900	105
20	1.4	1100	29.5	1900	51.0	3200	85.9	3200	85.9	3300	88.5	3300	88.5	3900	105
30	2.1	1500	40.2	2700	72.4	3300	88.5	2400	64.4	2700	72.4	3300	88.5		
40	2.8	1900	51.0	2800	75.1	2000	53.6	2100	56.3	1700	45.6				
50	3.4	2200	59.0	2800	75.1	2000	53.6	1600	42.9						
60	4.1	2600	69.7	1900	51.0	1500	40.2	1600	42.9						
80	5.5	3100	83.2	1900	51.0	1500	40.2								
100	6.9	1700	45.6	1900	51.0	1500	40.2								
125	8.6	1700	45.6	1900	51.0										
psig	bar	Body Size: NPS 1-1/2													
0.5	0.03	120	3.2	210	5.6	220	5.9	280	7.5	340	9.1	470	12.6	720	19.3
1	0.07	170	4.5	260	6.9	330	8.8	620	16.6	840	22.5	620	16.6	740	19.8
2	0.14	260	6.9	500	13.4	770	20.6	730	19.5	850	22.8	1100	29.5	1300	34.8
3	0.21	310	8.3	680	18.2	780	20.9	980	26.3	1200	32.2	1400	37.5	1800	48.3
5	0.34	540	14.4	940	25.2	950	25.5	1300	34.8	2300	61.7	3300	88.5	4400	118
10	0.69	770	20.6	1200	32.2	2000	53.6	3000	80.5	3300	88.5	4300	115	4400	118
15	1.0	990	26.5	1800	48.3	2900	77.8	3300	88.5	3300	88.5	4300	115	4400	118
20	1.4	1100	29.5	2100	56.3	3300	88.5	3300	88.5	3300	88.5	4300	115	4400	118
30	2.1	1500	40.2	2300	61.7	3300	88.5	3300	88.5	2500	67.1	2800	75.1		
40	2.8	1900	51.0	2500	67.1	3300	88.5	2500	67.1	2500	67.1				
50	3.4	2200	59.0	1900	51.0	2900	77.8	2200	59.0						
60	4.1	2200	59.0	1800	48.3	2500	67.1	2000	53.6						
80	5.5	2200	59.0	1800	48.3	2200	59.0								
100	6.9	1800	48.3	1800	48.3	2200	59.0								
125	8.6	1600	42.9	1800	48.3										
psig	bar	Body Size: NPS 2													
0.5	0.03	130	3.4	200	5.3	260	6.9	260	6.9	420	11.2	380	10.2	750	20.1
1	0.07	160	4.2	280	7.5	330	8.8	590	15.8	610	16.3	660	17.7	760	20.4
2	0.14	240	6.4	400	10.7	700	18.7	700	18.7	840	22.5	1100	29.5	1100	29.5
3	0.21	320	8.5	660	17.7	610	16.3	850	22.8	1100	29.5	1500	40.2	1700	45.6
5	0.34	540	14.4	730	19.5	790	21.2	1100	29.5	1900	51.0	2400	64.4	2700	72.4
10	0.69	700	18.7	1200	32.2	1500	40.2	2400	64.4	4000	107	4400	118	4400	118
15	1.0	980	26.3	1700	45.6	2500	67.1	3500	93.9	4200	113	4400	118	4400	118
20	1.4	1100	29.5	2100	56.3	3300	88.5	3500	93.9	4400	118	4400	118	4400	118
30	2.1	1500	40.2	2600	69.7	3300	88.5	3500	93.9	4400	118	3200	85.9		
40	2.8	1900	51.0	3200	85.9	3300	88.5	3100	83.2	3200	85.9				
50	3.4	2200	59.0	3200	85.9	3200	85.9	2800	75.1						
60	4.1	2600	69.7	3200	85.9	3000	80.5	2500	67.1						
80	5.5	3100	83.2	3000	80.5	2900	77.8								
100	6.9	3100	83.2	3000	80.5	2900	77.8								
125	8.6	3100	83.2	2800	75.1										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Gray areas indicate limited capacities due to boost effects.






Figure 6. Type CS400IR Relief Curves (Blocked per Orifice Size) at 7 in. w.c. / 17 mbar Set Pressure

Table 11. Type CS400 Relief Table, 7 in. w.c. / 17 mbar Setpoint, Internal Registration							
ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT/OR BELOW <sup>(1)</sup>			
				1 psig / 69 mbar		2 psig / 138 mbar	
In.	mm	In. w.c.	mbar	psig	bar	psig	bar
3/16	4.8	7	17	46	3.2	100	6.9
1/4	6.4			23	1.6	54	3.7
5/16	7.9			15	1.0	31	2.1
3/8	9.5			9	0.62	20	1.4

1. Relief values obtained by blocking regulator open per orifice.

# CS400 Series

## Commercial / Industrial – Pressure Reducing Regulator



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
11 in. w.c.	-2 in. w.c.	2 in. w.c.	7.5 to 11 in. w.c.	GE30189X012 / Blue
27 mbar	-5 mbar	5 mbar	19 to 27 mbar	

**Table 12. Type CS400 Internal Registration Flow Capacities for 11 in. w.c. / 27 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4													
0.5	0.03	150	4.0	220	5.9	300	8.0	320	8.5	530	14.2	710	19.0	550	14.7
1	0.07	210	5.6	320	8.5	680	18.2	700	18.7	840	22.5	810	21.7	1000	26.8
2	0.14	320	8.5	600	16.1	940	25.2	920	24.6	1100	29.5	1500	40.2	1600	42.9
3	0.21	450	12.0	700	18.7	1100	29.5	1100	29.5	1500	40.2	2000	53.6	2300	61.7
5	0.34	540	14.4	920	24.6	1200	32.2	1500	40.2	2100	56.3	2900	77.8	3200	85.9
10	0.69	780	20.9	1300	34.8	2100	56.3	2600	69.7	3500	93.9	3900	105	4300	115
15	1.0	980	26.3	1700	45.6	2800	75.1	3400	91.2	3500	93.9	3900	105	4300	115
20	1.4	1100	29.5	2000	53.6	3400	91.2	3400	91.2	3500	93.9	2200	59.0	4300	115
30	2.1	1500	40.2	2800	75.1	3400	91.2	3400	91.2	3500	93.9	2200	59.0		
40	2.8	1800	48.3	2800	75.1	2700	72.4	2400	64.4	1800	48.3				
50	3.4	2200	59.0	2800	75.1	2500	67.1	1700	45.6						
60	4.1	2500	67.1	2600	69.7	2400	64.4	1700	45.6						
80	5.5	2500	67.1	2000	53.6	2400	64.4								
100	6.9	1700	45.6	1900	51.0	1600	42.9								
125	8.6	1700	45.6	1900	51.0										
psig	bar	Body Size: NPS 1-1/2													
0.5	0.03	100	2.6	160	4.2	240	6.4	340	9.1	410	11.0	530	14.2	690	18.5
1	0.07	170	4.5	320	8.5	440	11.8	700	18.7	970	26.0	880	23.6	970	26.0
2	0.14	280	7.5	550	14.7	840	22.5	970	26.0	1200	32.2	1500	40.2	2000	53.6
3	0.21	410	11.0	710	19.0	930	24.9	1100	29.5	1600	42.9	2200	59.0	2600	69.7
5	0.34	560	15.0	970	26.0	1200	32.2	1700	45.6	2700	72.4	3500	93.9	3500	93.9
10	0.69	800	21.4	1400	37.5	2100	56.3	3000	80.5	3500	93.9	3500	93.9	4800	129
15	1.0	990	26.5	1800	48.3	2900	77.8	3300	88.5	3500	93.9	3500	93.9	4800	129
20	1.4	1100	29.5	2100	56.3	3300	88.5	3300	88.5	3500	93.9	3500	93.9	4900	134
30	2.1	1500	40.2	2800	75.1	3300	88.5	3300	88.5	2500	67.1	1900	51.0		
40	2.8	1800	48.3	3200	85.9	3300	88.5	3000	80.5	2500	67.1				
50	3.4	2200	59.0	3200	85.9	3300	88.5	1800	48.3						
60	4.1	2600	69.7	2000	53.6	3200	85.9	1700	45.6						
80	5.5	2800	75.1	2000	53.6	1900	51.0								
100	6.9	2800	75.1	2000	53.6	1900	51.0								
125	8.6	2800	75.1	2000	53.6										
psig	bar	Body Size: NPS 2													
0.5	0.03	110	2.9	200	5.3	270	7.2	340	9.1	420	11.2	620	16.6	870	23.3
1	0.07	190	5.1	270	7.2	430	11.5	690	18.5	990	26.5	820	22.0	1000	26.8
2	0.14	290	7.7	530	14.2	800	21.4	940	25.2	1100	29.5	1400	37.5	1700	45.6
3	0.21	410	11.0	730	19.5	870	23.3	1200	32.2	1400	37.5	1900	51.0	2400	64.4
5	0.34	550	14.7	920	24.6	1100	29.5	1500	40.2	2200	59.0	3100	83.2	3500	93.9
10	0.69	790	21.2	1300	34.8	1900	51.0	2800	75.1	4000	107	4200	113	4800	129
15	1.0	1000	26.8	1800	48.3	2800	75.1	3700	99.3	4000	107	4200	113	4800	129
20	1.4	1100	29.5	2000	53.6	3400	91.2	3700	99.3	4100	110	4200	113	4800	129
30	2.1	1500	40.2	2700	72.4	3400	91.2	3700	99.3	4100	110	2600	69.7		
40	2.8	1900	51.0	3200	85.9	3400	91.2	3200	85.9	3000	80.5				
50	3.4	2200	59.0	3200	85.9	3400	91.2	3200	85.9						
60	4.1	2500	67.1	3200	85.9	3400	91.2	3200	85.9						
80	5.5	3200	85.9	3200	85.9	3400	91.2								
100	6.9	3300	88.5	3200	85.9	3000	80.5								
125	8.6	3300	88.5	3200	85.9										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 Gray areas indicate limited capacities due to boost effects.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Drop	Boost		
14 in. w.c.	-2 in. w.c.	2 in. w.c.	10 to 14 in. w.c.	GE30224X012 / Unpainted
35 mbar	-5 mbar	5 mbar	25 to 35 mbar	

Table 13. Type CS400 Internal Registration Flow Capacities for 14 in. w.c. / 35 mbar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4															
psig	bar	190	5.1	280	7.5	380	10.2	680	18.2	860	23.0	890	23.8	1000	26.8
2	0.14	320	8.5	540	14.4	770	20.6	910	24.4	1100	29.5	1300	34.8	1700	45.6
3	0.21	390	10.4	700	18.7	840	22.5	1100	29.5	1500	40.2	2000	53.6	2200	59.0
5	0.34	530	14.2	880	23.6	1100	29.5	1500	40.2	2100	56.3	2700	72.4	3100	83.2
10	0.69	770	20.6	1300	34.8	2000	53.6	2600	69.7	3300	88.5	3600	96.6	4100	110
15	1.0	970	26.0	1700	45.6	2600	69.7	3400	91.2	3600	96.6	3600	96.6	4300	115
20	1.4	1100	29.5	2000	53.6	3200	85.9	3400	91.2	3600	96.6	3600	96.6	4300	115
30	2.1	1500	40.2	2300	61.7	3200	85.9	3400	91.2	3600	96.6	3300	88.5		
40	2.8	1800	48.3	2300	61.7	1900	51.0	2300	61.7	2000	53.6				
50	3.4	2200	59.0	2300	61.7	1900	51.0	2300	61.7						
60	4.1	2500	67.1	2300	61.7	1900	51.0	2300	61.7						
80	5.5	2500	67.1	2000	53.6	1900	51.0								
100	6.9	2500	67.1	1900	51.0	1900	51.0								
125	8.6	1600	42.9	1900	51.0										
Body Size: NPS 1-1/2															
psig	bar	180	4.8	260	6.9	420	11.2	680	18.2	870	23.3	840	22.5	840	22.5
2	0.14	280	7.5	530	14.2	760	20.4	860	23.0	1000	26.8	1300	34.8	1600	42.9
3	0.21	370	9.9	740	19.8	870	23.3	980	26.3	1500	40.2	2100	56.3	2200	59.0
5	0.34	560	15.0	930	24.9	1100	29.5	1500	40.2	2300	61.7	3500	93.9	3500	93.9
10	0.69	760	20.4	1300	34.8	1900	51.0	2700	72.4	3500	93.9	3800	102	4500	121
15	1.0	980	26.3	1800	48.3	2600	69.7	3400	91.2	3500	93.9	3800	102	4500	121
20	1.4	1100	29.5	2100	56.3	3200	85.9	3400	91.2	3500	93.9	3800	102	4500	121
30	2.1	1500	40.2	2800	75.1	3400	91.2	3400	91.2	3300	88.5	3000	80.5		
40	2.8	1900	51.0	2900	77.8	3400	91.2	3100	83.2	2800	75.1				
50	3.4	2200	59.0	2900	77.8	3400	91.2	2900	77.8						
60	4.1	2600	69.7	2900	77.8	3400	91.2	2800	75.1						
80	5.5	3300	88.5	2900	77.8	3400	91.2								
100	6.9	3500	93.9	2900	77.8	3400	91.2								
125	8.6	3600	96.6	2900	77.8										
Body Size: NPS 2															
psig	bar	170	4.5	230	6.1	350	9.3	530	14.2	890	23.8	790	21.2	960	25.7
2	0.14	310	8.3	450	12.0	760	20.4	940	25.2	1000	26.8	1400	37.5	1600	42.9
3	0.21	360	9.6	700	18.7	860	23.0	1100	29.5	1400	37.5	1700	45.6	2200	59.0
5	0.34	560	15.0	890	23.8	1100	29.5	1600	42.9	2200	59.0	2800	75.1	3500	93.9
10	0.69	760	20.4	1300	34.8	1900	51.0	2600	69.7	3300	88.5	3400	91.2	4500	121
15	1.0	980	26.3	1800	48.3	2600	69.7	3400	91.2	3500	93.9	3500	93.9	4800	129
20	1.4	1100	29.5	2100	56.3	3200	85.9	3500	93.9	3600	96.6	3600	96.6	4800	129
30	2.1	1500	40.2	2700	72.4	3400	91.2	3600	96.6	4000	107	2400	64.4		
40	2.8	1900	51.0	3200	85.9	3500	93.9	3600	96.6	2700	72.4				
50	3.4	2200	59.0	3200	85.9	3700	99.3	2900	77.8						
60	4.1	2600	69.7	3200	85.9	3700	99.3	2800	75.1						
80	5.5	3100	83.2	2800	75.1	3700	99.3								
100	6.9	3100	83.2	2600	69.7	3700	99.3								
125	8.6	3100	83.2	2600	69.7										

- Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 - Gray areas indicate limited capacities due to boost effects.

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator




Figure 7. Type CS400IR Relief Curves (Blocked per Orifice Size) at 14 in. w.c. / 35 mbar Set Pressure

Table 14. Type CS400 Relief Table, 14 in. w.c. / 35 mbar Setpoint, Internal Registration

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT/OR BELOW <sup>(1)</sup>			
				2 psig / 138 mbar		2.5 psig / 172 mbar	
In.	mm	In. w.c.	mbar	psig	bar	psig	bar
3/16	4.8	14	35	87	6.0	107	7.4
1/4	6.4			45	3.1	56	3.9
5/16	7.9			30	2.1	37	2.6
3/8	9.5			18	1.2	23	1.6

1. Relief values obtained by blocking regulator open per orifice.





SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 20%			
1 psig	-0.2 psi	0.2 psi	18 in. w.c. to 1 psig	GE30225X012 / Orange
69 mbar	-14 mbar	14 mbar	45 to 69 mbar	

**Table 15. Type CS400 Internal Registration Flow Capacities for 1 psig / 69 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4													
2	0.14	270	7.2	510	13.6	840	22.5	1000	26.8	1200	32.2	1700	45.6	2000	53.6
3	0.21	370	9.9	700	18.7	1000	26.8	1200	32.2	1700	45.6	2200	59.0	2700	72.4
5	0.34	530	14.2	940	25.2	1300	34.8	1700	45.6	2400	64.4	3400	91.2	4100	110
10	0.69	790	21.2	1400	37.5	2200	59.0	2800	75.1	3900	105	5600	150	6700	180
15	1.0	1000	26.8	1700	45.6	2900	77.8	3800	102	5300	142	7000	188	7800	209
20	1.4	1100	29.5	2100	56.3	3500	93.9	4200	113	6800	183	7600	204	7800	209
30	2.1	1500	40.2	2700	72.4	4700	126	6200	166	7600	204	7600	204		
40	2.8	1800	48.3	3400	91.2	5800	156	7600	204	7600	204				
50	3.4	2200	59.0	4000	107	6200	166	7600	204						
60	4.1	2500	67.1	4700	126	7600	204	7600	204						
80	5.5	3200	85.9	5800	156	7600	204								
100	6.9	3800	102	6500	174	7600	204								
125	8.6	4700	126	6500	174										
psig	bar	Body Size: NPS 1-1/2													
2	0.14	290	7.7	530	14.2	810	21.7	1000	26.8	1300	34.8	1500	40.2	1900	51.0
3	0.21	390	10.4	700	18.7	1000	26.8	1200	32.2	1700	45.6	2400	64.4	2700	72.4
5	0.34	550	14.7	960	25.7	1300	34.8	1800	48.3	2700	72.4	3800	102	4900	132
10	0.69	840	22.5	1400	37.5	2100	56.3	2800	75.1	4600	123	5600	150	6000	161
15	1.0	1000	26.8	1800	48.3	2700	72.4	3900	105	5600	150	5600	150	6000	161
20	1.4	1200	32.2	2100	56.3	3400	91.2	4700	126	5600	150	5600	150	6000	161
30	2.1	1500	40.2	2800	75.1	4700	126	6300	169	5600	150	5600	150		
40	2.8	1900	51.0	3300	88.5	5500	148	5600	150	5600	150				
50	3.4	2300	61.7	3900	105	5500	148	5600	150						
60	4.1	2600	69.7	4500	121	5500	148	5600	150						
80	5.5	3300	88.5	5400	145	5500	148								
100	6.9	4000	107	5500	148	5500	148								
125	8.6	4000	107	5500	148										
psig	bar	Body Size: NPS 2													
2	0.14	290	7.7	450	12.0	750	20.1	1000	26.8	1300	34.8	1700	45.6	1800	48.3
3	0.21	380	10.2	670	17.9	1000	26.8	1100	29.5	1700	45.6	2100	56.3	2600	69.7
5	0.34	540	14.4	950	25.5	1200	32.2	1700	45.6	2400	64.4	3100	83.2	4300	115
10	0.69	820	22.0	1400	37.5	2100	56.3	2800	75.1	4500	121	6000	161	8200	220
15	1.0	1000	26.8	1800	48.3	2700	72.4	3900	105	5700	153	6600	177	8200	220
20	1.4	1100	29.5	2100	56.3	3400	91.2	4800	129	6000	161	6600	177	8200	220
30	2.1	1500	40.2	2600	69.7	4200	113	6300	169	6000	161	6600	177		
40	2.8	1900	51.0	3300	88.5	5700	153	6300	169	6000	161				
50	3.4	2200	59.0	4000	107	5700	153	6300	169						
60	4.1	2600	69.7	4500	121	5700	153	6300	169						
80	5.5	3300	88.5	5500	148	5700	153								
100	6.9	4000	107	5500	148	5700	153								
125	8.6	4000	107	5500	148										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator




Figure 8. Type CS400IR Relief Curves (Blocked per Orifice Size) at 1 psig / 69 mbar Set Pressure

Table 16. Type CS400 Relief Table, 1 psig / 69 mbar Setpoint, Internal Registration

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT/OR BELOW <sup>(1)</sup>			
				2.5 psig / 172 mbar		3 psig / 207 mbar	
In.	mm	psig	mbar	psig	bar	psig	bar
3/16	4.8	1	69	84	5.8	105	7.2
1/4	6.4			46	3.2	56	3.9
5/16	7.9			29	2.0	37	2.6
3/8	9.5			19	1.3	24	1.7

1. Relief values obtained by blocking regulator open per orifice.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 20%			
2 psig	-0.4 psi	0.4 psi	1 to 2 psig	GE30190X012 / Black
138 mbar	-28 mbar	28 mbar	69 to 138 mbar	

**Table 17. Type CS400 Internal Registration Flow Capacities for 2 psig / 138 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4													
3	0.21	350	9.3	460	12.3	820	22.0	1100	29.5	1300	34.8	1600	42.9	1900	51.0
5	0.34	550	14.7	850	22.8	1100	29.5	1500	40.2	1900	51.0	2600	69.7	3400	91.2
10	0.69	850	22.8	1300	34.8	1900	51.0	2600	69.7	3400	91.2	4700	126	6200	166
15	1.0	1000	26.8	1700	45.6	2500	67.1	3600	96.6	4400	118	6200	166	6200	166
20	1.4	1200	32.2	2100	56.3	3100	83.2	4100	110	6200	166	6200	166	6200	166
30	2.1	1500	40.2	2700	72.4	4400	118	6000	161	6200	166	6200	166		
40	2.8	1800	48.3	3400	91.2	5400	145	6000	161	6200	166				
50	3.4	2200	59.0	4000	107	6000	161	6000	161						
60	4.1	2600	69.7	4600	123	6000	161	6000	161						
80	5.5	3300	88.5	5800	156	6000	161								
100	6.9	3900	105	5800	156	6000	161								
125	8.6	3900	105	5800	156										
psig	bar	Body Size: NPS 1-1/2													
3	0.21	310	8.3	570	15.3	900	24.1	1100	29.5	1300	34.8	1700	45.6	1900	51.0
5	0.34	520	13.9	880	23.6	1100	29.5	1500	40.2	2000	53.6	2600	69.7	3300	88.5
10	0.69	800	21.4	1300	34.8	1900	51.0	2500	67.1	3400	91.2	5300	142	6700	180
15	1.0	1000	26.8	1800	48.3	2500	67.1	3600	96.6	5400	145	6400	172	6700	180
20	1.4	1100	29.5	2100	56.3	3100	83.2	4500	121	6200	166	6400	172	6700	180
30	2.1	1600	42.9	2800	75.1	4600	123	6200	166	6200	166	6400	172		
40	2.8	1900	51.0	3300	88.5	5700	153	6200	166	6200	166				
50	3.4	2200	59.0	3900	105	6000	161	6200	166						
60	4.1	2500	67.1	4500	121	6000	161	6200	166						
80	5.5	3300	88.5	5800	156	6000	161								
100	6.9	3900	105	5800	156	6000	161								
125	8.6	3900	105	5800	156										
psig	bar	Body Size: NPS 2													
3	0.21	300	8.0	560	15.0	850	22.8	1100	29.5	1300	34.8	1700	45.6	1900	51.0
5	0.34	500	13.4	890	23.8	1000	26.8	1500	40.2	2100	56.3	2700	72.4	3200	85.9
10	0.69	780	20.9	1300	34.8	1800	48.3	2600	69.7	3600	96.6	4900	131	5600	150
15	1.0	1000	26.8	1700	45.6	2400	64.4	3300	88.5	5100	137	6000	161	6000	161
20	1.4	1100	29.5	2000	53.6	3000	80.5	4200	113	6000	161	6000	161	6000	161
30	2.1	1500	40.2	2700	72.4	3900	105	6000	161	6000	161	6000	161		
40	2.8	1900	51.0	3300	88.5	5400	145	6000	161	6000	161				
50	3.4	2200	59.0	4000	107	5800	156	6000	161						
60	4.1	2600	69.7	4600	123	5800	156	6000	161						
80	5.5	3300	88.5	5800	156	5800	156								
100	6.9	4100	110	5800	156	5800	156								
125	8.6	4100	110	5800	156										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator

FISHER™




Figure 9. Type CS400IR Relief Curves (Blocked per Orifice Size) at 2 psig / 138 mbar Set Pressure

Table 18. Type CS400 Relief Table, 2 psig / 138 mbar Setpoint, Internal Registration							
ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT/OR BELOW <sup>(1)</sup>			
				3 psig / 207 mbar		4 psig / 276 mbar	
In.	mm	psig	mbar	psig	bar	psig	bar
3/16	4.8	2	138	64	4.4	105	7.2
1/4	6.4			32	2.2	58	4.0
5/16	7.9			23	1.6	37	2.6
3/8	9.5			14	0.97	24	1.7

1. Relief values obtained by blocking regulator open per orifice.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 20%			
5 psig	-1 psig	1 psig	2 to 5.5 psig	GE30197X012 / Yellow
345 mbar	-69 mbar	69 mbar	138 to 380 mbar	

**Table 19. Type CS400 Internal Registration Flow Capacities for 5 psig / 345 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: NPS 1-1/4													
10	0.69	720	19.3	1200	32.2	1700	45.6	2200	59.0	3000	80.5	3900	105	4700	126
15	1.0	960	25.7	1700	45.6	2400	64.4	3100	83.2	4700	126	6200	166	7000	188
20	1.4	1100	29.5	2000	53.6	3000	80.5	4000	107	6000	161	6500	174	7000	188
30	2.1	1400	37.5	2700	72.4	4500	121	5800	156	6500	174	6500	174		
40	2.8	1900	51.0	3400	91.2	5500	148	6500	174	6500	174				
50	3.4	2200	59.0	4100	110	6500	174	6500	174						
60	4.1	2600	69.7	4600	123	6500	174	6500	174						
80	5.5	3200	85.9	5700	153	6500	174								
100	6.9	4000	107	5700	153	6500	174								
125	8.6	4200	113	5700	153										
psig	bar	Body Size: NPS 1-1/2													
10	0.69	750	20.1	1200	32.2	1600	42.9	2300	61.7	2900	77.8	3900	105	4400	118
15	1.0	990	26.5	1500	40.2	2300	61.7	3200	85.9	4200	113	6100	164	7200	193
20	1.4	1100	29.5	2000	53.6	2800	75.1	4000	107	5900	158	6600	177	7200	193
30	2.1	1600	42.9	2600	69.7	4200	113	5900	158	6500	174	6600	177		
40	2.8	1900	51.0	3300	88.5	5200	140	6500	174	6500	174				
50	3.4	2200	59.0	3800	102	6200	166	6500	174						
60	4.1	2600	69.7	4500	121	6200	166	6500	174						
80	5.5	3300	88.5	5700	153	6200	166								
100	6.9	4100	110	5700	153	6200	166								
125	8.6	4500	121	5700	153										
psig	bar	Body Size: NPS 2													
10	0.69	720	19.3	1200	32.2	1500	40.2	2200	59.0	3000	80.5	3800	102	4700	126
15	1.0	970	26.0	1600	42.9	2200	59.0	3200	85.9	4400	118	5700	153	6600	177
20	1.4	1100	29.5	2000	53.6	2900	77.8	3900	105	5200	140	6800	183	7200	193
30	2.1	1500	40.2	2700	72.4	4000	107	5400	145	6500	174	6800	183		
40	2.8	1900	51.0	3200	85.9	5000	134	6500	174	6500	174				
50	3.4	2200	59.0	3800	102	5900	158	6500	174						
60	4.1	2600	69.7	4300	115	6200	166	6500	174						
80	5.5	3300	88.5	5900	158	6200	166								
100	6.9	4000	107	5900	158	6200	166								
125	8.6	4900	132	5900	158										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator




Figure 10. Type CS400IR Relief Curves (Blocked per Orifice Size) at 5 psig / 345 mbar Set Pressure

Table 20. Type CS400 Relief Table, 5 psig / 345 mbar Setpoint, Internal Registration

ORIFICE SIZE		REGULATOR SET PRESSURE		MAXIMUM INLET PRESSURE TO KEEP OUTLET PRESSURE AT/OR BELOW <sup>(1)</sup>			
				6 psig / 414 mbar		7 psig / 483 mbar	
In.	mm	psig	mbar	psig	bar	psig	bar
3/16	4.8	5	345	63	4.3	106	7.3
1/4	6.4			36	2.5	61	4.2
5/16	7.9			31	2.1	53	3.7
3/8	9.5			20	1.4	29	2.0

1. Relief values obtained by blocking regulator open per orifice.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
7 in. w.c.	-1 in. w.c.	2 in. w.c.	6 to 8 in. w.c.	GE30188X012 / Gold
17 mbar	-2 mbar	5 mbar	15 to 20 mbar	

Table 21. Type CS400 External Registration Flow Capacities for 7 in. w.c. / 17 mbar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4, 1-1/2 and 2															
0.5	0.03	140	3.7	200	5.3	230	6.1	280	7.5	360	9.6	410	11.0	430	11.5
1	0.07	180	4.8	260	6.9	300	8.0	360	9.6	360	9.6	610	16.3	760	20.4
2	0.14	210	5.6	350	9.3	360	9.6	360	9.6	360	9.6	910	24.4	980	26.3
3	0.21	210	5.6	450	12.0	510	13.6	510	13.6	510	13.6	990	26.5	1060	28.4
5	0.34	210	5.6	590	15.8	610	16.3	870	23.3	1120	30.0	1360	36.5	1920	51.5
10	0.69	210	5.6	680	18.2	970	26.0	1180	31.6	1430	38.3	2000	53.6	2500	67.1
15	1.0	210	5.6	1060	28.4	1150	30.8	1440	38.6	1720	46.1	2100	56.3	2700	72.4
20	1.4	980	26.3	1220	32.7	1390	37.3	1550	41.6	1550	41.6	2500	67.1	3300	88.5
30	2.1	1230	33.0	1450	38.9	1700	45.6	1800	48.3	1880	50.4	2600	69.7		
40	2.8	1400	37.5	1450	38.9	1730	46.4	1880	50.4	2300	61.7				
50	3.4	1450	38.9	1450	38.9	1860	49.9	2000	53.6						
60	4.1	1450	38.9	1450	38.9	2000	53.6	2300	61.7						
80	5.5	1450	38.9	1450	38.9	2500	67.1								
100	6.9	1450	38.9	1450	38.9	2900	77.8								
125	8.6	1450	38.9	1450	38.9										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
11 in. w.c. 27 mbar	-2 in. w.c. -5 mbar	2 in. w.c. 5 mbar	7.5 to 11 in. w.c. 19 to 27 mbar	GE30189X012 / Blue

**Table 22. Type CS400 External Registration Flow Capacities for 11 in. w.c. / 27 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4, 1-1/2 and 2															
0.5	0.03	130	3.4	170	4.5	240	6.4	290	7.7	350	9.3	350	9.3	350	9.3
1	0.07	160	4.2	350	9.3	380	10.2	520	13.9	690	18.5	890	23.8	1040	27.9
2	0.14	280	7.5	470	12.6	600	16.1	840	22.5	1050	28.1	1330	35.7	1530	41.0
3	0.21	370	9.9	600	16.1	760	20.4	1060	28.4	1380	37.0	1390	37.3	1950	52.3
5	0.34	500	13.4	810	21.7	1380	37.0	1900	51.0	1950	52.3	2000	53.6	2400	64.4
10	0.69	760	20.4	1330	35.7	1480	39.7	2100	56.3	2700	72.4	3600	96.6	3800	102
15	1.0	840	22.5	1790	48.0	1960	52.6	2700	72.4	3500	93.9	4900	132	6600	177
20	1.4	1180	31.6	1990	53.4	2500	67.1	3800	102	4900	132	7100	191	7300	196
30	2.1	1500	40.2	2400	64.4	3300	88.5	5100	137	7900	212	10,700	287		
40	2.8	1880	50.4	3100	83.2	4700	126	6200	166	9700	260				
50	3.4	2200	59.0	3900	105	5700	153	8200	220						
60	4.1	2500	67.1	4600	123	6500	174	9900	266						
80	5.5	3300	88.5	6000	161	7000	188								
100	6.9	4000	107	7000	188	7000	188								
125	8.6	4700	126	8600	231										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
14 in. w.c. 35 mbar	-2 in. w.c. -5 mbar	2 in. w.c. 5 mbar	10 to 14 in. w.c. 25 to 35 mbar	GE30224X012 / Unpainted

**Table 23. Type CS400 External Registration Flow Capacities for 14 in. w.c. / 35 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4, 1-1/2 and 2															
1	0.07	170	4.5	260	6.9	370	9.9	490	13.1	610	16.3	820	22.0	840	22.5
2	0.14	270	7.2	450	12.0	600	16.1	810	21.7	1040	27.9	1180	31.6	1520	40.8
3	0.21	350	9.3	570	15.3	750	20.1	970	26.0	1610	43.2	1650	44.2	1730	46.4
5	0.34	480	12.8	760	20.4	1310	35.1	1330	35.7	1630	43.7	2300	61.7	2300	61.7
10	0.69	760	20.4	1380	37.0	1670	44.8	2100	56.3	2600	69.7	3500	93.9	3900	105
15	1.0	970	26.0	1650	44.2	1940	52.0	2500	67.1	3900	105	5000	134	5100	137
20	1.4	1170	31.4	1760	47.2	2300	61.7	3200	85.9	4200	113	6100	164	6500	174
30	2.1	1500	40.2	2400	64.4	3300	88.5	4200	113	6400	172	10,300	277		
40	2.8	1830	49.1	3200	85.9	4000	107	5900	158	10,900	293				
50	3.4	2200	59.0	3700	99.3	5200	140	8200	220						
60	4.1	2500	67.1	4500	121	6200	166	8700	234						
80	5.5	3300	88.5	5400	145	9100	244								
100	6.9	4000	107	6700	180	11,200	301								
125	8.6	4600	123	8100	217										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 20%			
1 psig 69 mbar	-0.2 psi -14 mbar	0.2 psi 14 mbar	18 in. w.c. to 1 psig 45 to 69 mbar	GE30225X012 / Orange

**Table 24. Type CS400 External Registration Flow Capacities for 1 psig / 69 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		ORIFICE SIZE, IN. / MM													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4, 1-1/2 and 2															
2	0.14	270	7.2	360	9.6	430	11.5	430	11.5	430	11.5	430	11.5	430	11.5
3	0.21	350	9.3	410	11.0	470	12.6	470	12.6	470	12.6	1200	32.2	1350	36.2
5	0.34	410	11.0	410	11.0	840	22.5	1070	28.7	1330	35.7	1780	47.7	1790	48.0
10	0.69	410	11.0	410	11.0	1310	35.1	1650	44.2	2200	59.0	2600	69.7	2900	77.8
15	1.0	490	13.1	1250	33.5	1670	44.8	2100	56.3	2800	75.1	3500	93.9	3700	99.3
20	1.4	1090	29.2	1480	39.7	2000	53.6	2500	67.1	3500	93.9	4000	107	4100	110
30	2.1	1490	40.0	1940	52.0	2600	69.7	3300	88.5	4400	118	5400	145		
40	2.8	1790	48.0	2500	67.1	3300	88.5	4300	115	5700	153				
50	3.4	2100	56.3	2300	61.7	3900	105	4900	132						
60	4.1	2400	64.4	3300	88.5	4500	121	5200	140						
80	5.5	3100	83.2	3300	88.5	5400	145								
100	6.9	3600	96.6	3700	99.3	6400	172								
125	8.6	4500	121	4500	121										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS400 Series

## Commercial / Industrial – Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY + / - 20%		SET RANGE	PART NUMBER / COLOR
	-0.4 psi 138 mbar	0.4 psi 28 mbar		
2 psig	-0.4 psi	0.4 psi	1 to 2 psig	GE30190X012 / Black
138 mbar	-28 mbar	28 mbar	69 to 138 mbar	

**Table 25. Type CS400 External Registration Flow Capacities for 2 psig / 138 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16 SCFH	4.8 Nm³/h	1/4 SCFH	6.4 Nm³/h	5/16 SCFH	7.9 Nm³/h	3/8 SCFH	9.5 Nm³/h	1/2 SCFH	13 Nm³/h	5/8 SCFH	16 Nm³/h	3/4 SCFH	19 Nm³/h
psig	bar	Body Size: NPS 1-1/4, 1-1/2 and 2													
3	0.21	330	8.8	540	14.4	720	19.3	990	26.5	1360	36.5	2200	59.0	2600	69.7
5	0.34	500	13.4	800	21.4	1100	29.5	1500	40.2	2500	67.1	2500	67.1	3000	80.5
10	0.69	790	21.2	1270	34.0	1960	52.6	2500	67.1	3400	91.2	4200	113	5400	145
15	1.0	1020	27.3	1760	47.2	2300	61.7	3200	85.9	4500	121	6000	161	6800	183
20	1.4	1180	31.6	2100	56.3	2800	75.1	3900	105	5800	156	7000	188	8000	215
30	2.1	1550	41.6	2600	69.7	4000	107	5500	148	7900	212	9500	255		
40	2.8	1900	51.0	3300	88.5	5000	134	6900	185	9800	263				
50	3.4	2200	59.0	4100	110	5800	156	8200	220						
60	4.1	2600	69.7	4500	121	6800	183	9600	258						
80	5.5	3300	88.5	5800	156	8900	239								
100	6.9	3900	105	7000	188	10,500	282								
125	8.6	4900	132	8700	234										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY + / - 20%		SET RANGE	PART NUMBER / COLOR
	-1 psig 345 mbar	1 psig 69 mbar		
5 psig	-1 psig	1 psig	2 to 5.5 psig	GE30190X012 / Black
345 mbar	-69 mbar	69 mbar	138 to 380 mbar	

**Table 26. Type CS400 External Registration Flow Capacities for 5 psig / 345 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16 SCFH	4.8 Nm³/h	1/4 SCFH	6.4 Nm³/h	5/16 SCFH	7.9 Nm³/h	3/8 SCFH	9.5 Nm³/h	1/2 SCFH	13 Nm³/h	5/8 SCFH	16 Nm³/h	3/4 SCFH	19 Nm³/h
psig	bar	Body Size: NPS 1-1/4, 1-1/2 and 2													
10	0.69	670	17.9	1320	35.4	1600	42.9	1700	45.6	3000	80.5	3600	97	4200	113
15	1.0	950	25.5	1770	47.5	2700	72.4	3100	83.2	4400	118	5500	148	6300	169
20	1.4	1160	31.1	2000	53.6	2900	77.8	3700	99.3	5300	142	7000	188	8200	220
30	2.1	1570	42.1	2600	69.7	4100	110	5200	140	7700	207	9000	247		
40	2.8	1860	49.9	3300	88.5	4800	129	6700	180	9000	242				
50	3.4	2000	53.6	3900	105	5800	156	8100	217						
60	4.1	2500	67.1	4300	115	7000	188	9600	258						
80	5.5	3300	88.5	5600	150	8900	239								
100	6.9	3900	105	6600	177	10,200	274								
125	8.6	4900	132	8800	236										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	Droop	Boost		
7 in. w.c.	-1 in. w.c.	2 in. w.c.	6 to 8 in. w.c.	GE30188X012 / Gold
17 mbar	-2 mbar	5 mbar	15 to 20 mbar	

**Table 27. Types CS403 and CS404 Internal Registration Flow Capacities for 7 in. w.c. / 17 mbar Setpoint**

CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16 SCFH	4.8 Nm³/h	1/4 SCFH	6.4 Nm³/h	5/16 SCFH	7.9 Nm³/h	3/8 SCFH	9.5 Nm³/h	1/2 SCFH	13 Nm³/h	5/8 SCFH	16 Nm³/h	3/4 SCFH	19 Nm³/h
psig	bar	Body Size: NPS 1-1/4													
0.5	0.03	80	2.1	160	4.3	210	5.6	250	6.7	520	13.9	420	11.3	410	11.0
1	0.07	160	4.3	290	7.8	440	11.8	340	9.1	520	13.9	560	15.0	730	19.6
2	0.14	280	7.5	350	9.4	480	12.9	590	15.8	830	22.2	1050	28.1	1210	32.4
3	0.21	310	8.3	460	12.3	650	17.4	740	19.8	1270	34.0	1440	38.6	1790	48.0
5	0.34	420	11.3	660	17.7	960	25.7	1180	31.6	2070	55.5	2460	65.9	2730	73.2
10	0.69	720	19.3	1280	34.3	1840	49.3	2390	64.1	3640	97.6	4830	129	4850	130.0
15	1.0	970	26.0	1800	48.2	2700	72.4	3580	95.9	5130	138	3910	105	6700	180
20	1.4	1150	30.8	2170	58.2	3390	90.9	4530	121	3170	85.0	2540	68.1	3330	89.2
30	2.1	1530	41.0	2780	74.5	4450	119	2410	64.6	2260	60.6	2280	61.1		
40	2.8	1890	50.7	2800	75.0	2980	79.9	2120	56.8	2260	60.6				
50	3.4	2260	60.6	2800	75.0	2690	72.1	2080	55.7						
60	4.1	2400	64.3	2730	73.2	2590	69.4	2040	54.7						
80	5.5	2400	64.3	2590	69.4	2590	69.4								
100	6.9	2400	64.3	2590	69.4	2590	69.4								
125	8.6	2540	68.1	2590	69.4										

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

Gray areas indicate limited capacities due to boost effects.








Figure 11. Spring Case Vent Orientation

CHOOSE VENT AND BODY POSITION FOR THE TYPES CS403 AND CS404 IN THE SAME MANNER AS FOR THE BASE TYPE CS400 REGULATOR. THE VENT OF THE INTEGRAL MONITOR OR SLAM-SHUT WILL BE ORIENTED IN THE SAME DIRECTION AS THE PRIMARY REGULATOR. BODY POSITION WILL ALSO BE BASED ON PRIMARY REGULATOR AS THE SPRING BARREL OF THE INTEGRAL MONITOR OR SLAM-SHUT WILL POINT THE SAME DIRECTION AS THE PRIMARY REGULATOR.

SETPOINT	ACCURACY		SET RANGE	PART NUMBER / COLOR
	+ / - 20%			
1 psig	-0.2 psig	0.2 psig	18 in. w.c. to 1 psig	GE30225X012 / Orange
69 mbar	-14 bar	14 mbar	45 to 69 mbar	

Table 28. Types CS403 and CS404 Internal Registration Flow Capacities for 1 psig / 69 mbar Setpoint at 20% Accuracy

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS															
Inlet Pressure		Orifice Size, In. / mm													
		3/16	4.8	1/4	6.4	5/16	7.9	3/8	9.5	1/2	13	5/8	16	3/4	19
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: NPS 1-1/4															
2	0.14	220	5.9	370	9.9	700	18.8	560	15.0	760	20.4	840	22.5	960	25.7
3	0.21	380	10.2	450	12.1	950	25.5	740	19.8	1000	26.8	1200	32.2	1390	37.3
5	0.34	450	12.1	640	17.2	1350	36.2	1080	28.9	1460	39.1	1860	49.8	2270	60.8
10	0.69	740	19.8	1050	28.1	2100	56.3	1890	50.7	2610	69.9	3230	86.6	3850	103
15	1.0	950	25.5	1460	39.1	2750	73.7	2530	67.8	3630	97.3	4980	134	5800	155
20	1.4	1180	31.6	1860	49.8	3390	90.9	3290	88.2	4890	131	6610	177	7370	198
30	2.1	1530	41.0	2680	71.8	4470	120	4710	126	7650	205	9180	246		
40	2.8	1900	50.9	3320	89.0	5620	151	6760	181	10,380	278				
50	3.4	2250	60.3	4000	107	6680	179	8530	229						
60	4.1	2650	71.0	4650	125	7770	208	10,030	269						
80	5.5	3360	90.0	5980	160	9900	265								
100	6.9	4090	110	7230	194	12,010	322								
125	8.6	3890	104	7840	210										

- Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 - Gray areas indicate limited capacities due to boost effects.

# CS400 Series

Commercial / Industrial – Pressure Reducing Regulator

FISHER™




Figure 12. Body Orientation

CHOOSE VENT AND BODY POSITION FOR THE TYPES CS403 AND CS404 IN THE SAME MANNER AS FOR THE BASE TYPE CS400 REGULATOR. THE VENT OF THE INTEGRAL MONITOR OR SLAM-SHUT WILL BE ORIENTED IN THE SAME DIRECTION AS THE PRIMARY REGULATOR. BODY POSITION WILL ALSO BE BASED ON PRIMARY REGULATOR AS THE SPRING BARREL OF THE INTEGRAL MONITOR OR SLAM-SHUT WILL POINT THE SAME DIRECTION AS THE PRIMARY REGULATOR.




Figure 13. Dimensions

Table 29. Dimension

BODY SIZE	END CONNECTION STYLE					
	A					
	NPT / Rp		CL125 FF/CL150 FF		PN 16	
	In.	mm	In.	mm	In.	mm
1-1/4	4.49	114	----	----	----	----
1-1/2	4.49	114	----	----	----	----
1	3.94	100	----	----	----	----
2	5	127	----	----	----	----
NPS 2 / DN 50	----	----	10	254	10	254

## Ordering Guide

### Type (See Table 1 for Construction Features) (Select One)

#### Stand-Alone Regulator

- CS400IN
- CS400IR
- CS400IT
- CS400EN
- CS400ET

#### With Integral True-Monitor™ Module

- CS403IN
- CS403IT
- CS403EN
- CS403ET

#### With Type VSX4 Slam-Shut Module

- CS404IN
- CS404IR
- CS404IT
- CS404EN
- CS404ET

### Body Sizes, Materials and End Connection (Select One)

#### Cast Iron (Type CS400 Only)

- 1-1/4 NPT\*\*\*
- 1-1/4 x 1-1/2 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- NPS 2 / DN 50, CL125 FF\*\*\*

#### Ductile Cast Iron (All Types)

- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL125 FF / CL150 FF\*\*\*
- NPS 2 / DN 50, PN 10/16

#### Steel (All Types)

- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*

### Outlet Pressure Range (Select One)

- 3.5 to 5 in. w.c. / 9 to 12 mbar, Red\*\*\*
- 4.5 to 6.5 in. w.c. / 11 to 16 mbar, Purple\*\*\*
- 6 to 8 in. w.c. / 15 to 20 mbar, Gold\*\*\*
- 7.5 to 11 in. w.c. / 19 to 27 mbar, Blue\*\*\*
- 10 to 14 in. w.c. / 25 to 35 mbar, Unpainted\*\*\*
- 12 to 19 in. w.c. / 30 to 47 mbar, Green\*\*\*
- 18 to 28 in. w.c. / 45 to 69 mbar, Orange\*\*\*
- 1 to 2 psig / 69 to 138 mbar, Black\*\*\*
- 2 to 5.5 psig / 138 to 380 mbar, Yellow\*\*\*

### Orifice Size (Select One)

- 3/16 in. / 4.8 mm
- 1/4 in. / 6.4 mm
- 5/16 in. / 7.9 mm
- 3/8 in. / 9.5 mm
- 1/2 in. / 13 mm
- 5/8 in. / 16 mm
- 3/4 in. / 19 mm

### Body Orientation (Select One)

- Position 1\*\*\*
- Position 2\*\*\*
- Position 3 (standard)\*\*\*
- Position 4\*\*\*

### Vent Orientation (Select One)

- Position C\*\*\*
- Position D\*\*\*
- Position E\*\*\*
- Position F (standard)\*\*\*

### Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### Regulator Tip:

Droop is the reduction of outlet pressure experienced by pressure-reducing regulators as the flow rate increases. It is stated as a percent, in inches of water column (mbar) or in pounds per square inch (bar) and indicates the difference between the outlet pressure setting made at low flow rates and the actual outlet pressure at the published maximum flow rate. Droop is also called offset or proportional band.

**Introduction**

The CS800 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of commercial and industrial pressure-reducing applications. This flexibility is provided by the numerous body sizes and end connections, outlet pressure settings orifice sizes, as well as the option for internal or external pressure registration.

**Body Sizes, Material, End Connection and Pressure Rating<sup>(1)</sup>**  
See Table 2

**Outlet Pressure Ranges<sup>(1)</sup>**  
3.5 in. w.c. to 10 psig / 9 mbar to 0.69 bar  
See Table 4

**Maximum Inlet Pressures<sup>(1)</sup>**  
Emergency: 175 psig / 12.1 bar  
Operating: See Table 8

**Maximum Outlet Pressure<sup>(1)</sup>**  
Emergency (Casing): 15 psig / 1.0 bar  
To Avoid Internal Parts Damage:  
3 psig / 0.21 bar, differential above outlet pressure setting

**Flow and Sizing Coefficients**  
See Table 8

**Flow Capacities**  
See Tables 12 to 42

**Flow and Sizing Coefficients**  
See Table 8

**Maximum Inlet Pressure**  
Emergency: 175 psig / 12.1 bar  
Operating: See Table 8

**Maximum Outlet Pressure**  
Emergency (Casing):  
15 psig / 1.0 bar  
To Avoid Internal Parts Damage:  
3 psig / 0.21 bar differential above outlet pressure setting

**Outlet Pressure Ranges**  
3.5 in. w.c. to 10 psig /  
9 mbar to 0.69 bar  
See Table 4

**Spring Case Vent Connection**

**Internal Relief:** 1 NPT  
**High Capacity Relief:** 2-1/2 NPT

**Pressure Registration**  
Internal or External

**Temperature Capabilities<sup>(1)(2)</sup>**  
-20 to 150°F / -29 to 66°C

**Approximate Weights**  
**With Threaded Body**

Type CS800/CS820: 25 lbs / 11 kg  
Type CS803/CS823: 34 lbs / 15 kg  
Type CS804/CS824: 31 lbs / 14 kg  
Type CS805/CS825: 26 lbs / 12 kg  
Type CS806/CS826: 26 lbs / 12 kg

**High-Pressure Types:**  
For CS85x add 2 lbs / 0.9 kg to types listed with threaded body  
**With Flanged Body:**  
Add 11 lbs / 5.0 kg to weights listed above

**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)




07/19

**Features**


- Flow Optimized Disks Provide the Maximum Flow for Your Application
- Wide Variety of Body Sizes and End Connections
- Fixed Factor / Pressure Factor Measurement (PFM) Accuracy Capabilities
- Only Standard Tools Required for Pressure Adjustment and Orifice Removal
- Simplified Maintenance




P1235  
**Figure 1.** Type CS800 Regulator



P1234  
**Figure 2.** Type CS800IQ with High Capacity Relief



P1521  
**Figure 3.** Type CS803 Regulator with True-Monitor™ Protection




P1692  
**Figure 4.** Type CS804IT Regulator with Integral Type VSX8 Slam-shut Module

1. The pressure/temperature limits in this Datasheet or any applicable standard or code limitation should not be exceeded.  
2. Product has passed Emerson Process Management Regulator Technologies, Inc. testing for lockup, relief start-to-discharge and reseal down to -40 degrees.

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™



P1287

Figure 5. Internal View of CS800 Series with High Capacity Relief

Table 1. Available Configuration

TYPE NUMBER				OPTION
C	S	8		
				<b>OUTLET PRESSURE CONSTRUCTION</b>
			0	Low Pressure Applications (Outlet Pressure: 3.5 to 30 in. w.c. / 9 to 75 mbar)
			2	Medium Pressure Applications (Outlet Pressure: 1 to 5.5 psig / 69 mbar to 0.38 bar)
			5	High Pressure Applications (Outlet Pressure: 5 to 10 psig / 0.34 to 0.69 bar) <sup>(1)</sup>
				<b>OVERPRESSURE PROTECTION MODULE</b>
			0	Without Overpressure Protection Module
			3	With Integral True-Monitor Module <sup>(4)</sup>
			4	With Slam-shut Module <sup>(4)</sup>
			5	With Secondary Seat™ Protection
			6	With Secondary Seat Protection with controlled bleed to indicate Secondary Seat is functioning <sup>(2)</sup>
				<b>PRESSURE REGISTRATION</b>
			I	Internal Registration
			E	External Registration <sup>(3)</sup>
				<b>RELIEF</b>
			N	Non-Relieving
			R	Internal Relief
			Q	High-Capacity Relief
			T	Token Relief
			L	Low Flow Token Relief
			SC	Stabilizer Cartridge
Example: Type Number CS800IR: Type CS800 regulator without Overpressure Protection Module with Internal Pressure Registration and with Internal Relief. 1. High-pressure Construction is not available with True-Monitor Protection, Secondary Seat Protection or Relief. 2. Available only with Internal Relief or High-Capacity Relief Constructions. 3. Available only with Non-Relieving or Token Relief Constructions. 4. Reference Instruction Manual D103126X012 for information regarding the Type TM600 Integral True-Monitor or Instruction Manual D103127X012 for Type VSX8 safety Slam-shut module.				




Figure 6. Type CS800IR Internally Registered Regulator with Internal Relief Operational Schematic





Figure 7. Type CS803IT Internally Registered Primary Regulator with Internally Registered Integral Monitor Operational Schematic

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™



**SECONDARY SEAT DETAILED VIEW**  
 Figure 8. CS800 Series with Secondary Seat Protection

**Table 2. Body Sizes, Materials, End Connections and Maximum Cold Working Pressure Ratings<sup>(5)</sup>**

TYPE	BODY MATERIAL	END CONNECTION	BODY SIZE		FACE-TO-FACE DIMENSION		BODY INLET PRESSURE RATING	
			In.	DN	In.	mm	psig	bar
CS800, CS805, CS806, CS820, CS825, CS826 and CS850	Gray Cast Iron	NPT	1-1/4	----	6.12	155	175	12.1
			1-1/2	----	6.12	155		
			2 <sup>(1)</sup>	----	6.12	155		
		CL125 FF	2	----	6.12	155	175	12.1
			2	50	7.5	191		
			2	50	10	254		
CS800 <sup>(3)</sup> , CS820 <sup>(3)</sup> , CS850 <sup>(3)</sup> , CS803, CS823, CS804, CS824 and CS854	Gray Cast Iron	NPT	2 <sup>(2)</sup>	----	6.12	155	175	12.1
			1-1/4 <sup>(4)</sup>	----	6.12	155		
	Ductile Iron	NPT	1-1/2	----	6.12	155	250	17.2
			2	----	6.12	155		
			2	----	6.12	155		
		Rp	2	----	6.12	155	250	17.2
			2	50	7.5 <sup>(4)</sup>	191 <sup>(4)</sup>		
			2	50	10	254		
		PN 10/16	2	50	10.5	267	250	17.2
			2	50	7.5 <sup>(4)</sup>	191 <sup>(4)</sup>		
	2		50	10	254			
	2		50	10	254			
	WCC Steel	NPT	1-1/4 <sup>(4)</sup>	----	6.12	155	290	20
			1-1/2	----	6.12	155		
2			----	6.12	155			
Rp		2	----	6.12	155	290	20	
		2	50	10	254			
		2	50	10	254			
CL150 RF	2	50	10	254	290	20		
	2	50	10	254				
PN 10/16	2	50	10	254	232	16		
	2	50	10	254				

1. Standard on Types CS800, CS820 and CS850.  
 2. Standard on Types CS803, CS804, CS823, CS824 and CS854.  
 3. If a ductile iron or steel body material is selected without an Integral True-Monitor™ or Slam-shut Overpressure Protection (OPP) device, the port located at the bottom of the body will receive an aluminum plug.  
 4. Not available on Types CS804, CS824 and CS854.  
 5. The pressure/temperature limits in this Datasheet or any applicable standard or code limitation should not be exceeded.



**Table 3. CS800 Series Main Valve and Actuator Construction Material**

BODY	LEVER PIN AND RELIEF VALVE SPRING	DIAPHRAGM, DISK AND BODY O-RING	CLOSING CAP, ADJUSTING SCREW, PUSHER POST, UPPER AND LOWER CASE	LEVER
Gray Cast iron, Ductile iron or Steel	Stainless steel	Nitrile (NBR)	Aluminum	Steel

**Table 4. Outlet Pressure Range**

TYPE	OUTLET PRESSURE RANGE		COLOR CODE	PART NUMBER	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	In. w.c.	mbar			In.	mm	In.	mm
CS800, CS803, CS804, CS805 and CS806	3.5 to 6 <sup>(1)</sup>	9 to 15 <sup>(1)</sup>	Red	GE30337X012	0.15	3.8	6.8	173
	5.5 to 8.5	13 to 21	Black	GE30338X012	0.17	4.3	6.8	173
	5.5 to 8.5	13 to 21	Brown [Use with Low Inlet (LIN) Option]	GE49043X012	0.16	4.1	8.3	211
	8 to 12	20 to 30	Purple	GE30339X012	0.17	4.3	7.4	188
	10 to 16	25 to 40	White	GE30340X012	0.18	4.6	7.4	188
	14 to 30	35 to 75	Dark Green	GE30341X012	0.2	5.2	7.5	191
CS820, CS823, CS824, CS825 and CS826	1 to 2.5 psig	69 to 170	Dark Blue	GE30342X012	0.25	6.4	7.5	191
	1.5 to 3.5 psig	100 to 241	Orange	GE46922X012	0.26	6.6	7.1	180
	2.5 to 5.5 psig	170 to 380	Yellow	GE30343X012	0.29	7.5	6.7	170
CS850 and CS854	5 to 10 psig	345 to 690	Green with White Stripe	GE30344X012	0.39	9.9	7.6	192

1. In order to achieve the complete spring range listed, in some applications it may be required to re-orient the actuator/spring case to point downward to utilize the weight of the internal components.

**Table 5. Secondary Seat™ Outlet Pressure**

CONTROL SPRING		SPRING RANGE		SETPOINT		TYPES CS805 AND CS825				TYPES CS806 AND CS826			
						Secondary Seat Shutoff Pressure <sup>(2)</sup>				Downstream Build-up Pressure <sup>(1)(2)(3)</sup>			
						Orifice Size							
						In.		mm		In.		mm	
Color	Spring Part Number	In. w.c.	mbar	In. w.c.	mbar	Up to 1/2	Up to 13	Up to 7/8	Up to 22	Up to 1/2	Up to 13	Up to 7/8	Up to 22
		In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar
Black	GE30338X012	5.5 to 8.5	13 to 21	7	17	11	27	12	30	25	62	23	57
Brown (LIN)	GE49043X012	5.5 to 8.5	13 to 21	7	17	11	27	12	30	25	62	23	57
White Stripe	GE30340X012	10 to 16	25 to 40	14	35	19	47	20	50	36	89	33	81
Dark Green	GE30341X012	14 to 30	35 to 75	1 psig	69	1.2 psig	83	1.3 psig	90	2.1 psig	145	2 psig	138
Dark Blue	GE30342X012	1 to 2.5 psig	69 to 170	2 psig	140	2.6 psig	179	2.6 psig	179	3.8 psig	262	3.7 psig	255
Yellow	GE30343X012	2.5 to 5.5 psig	170 to 380	5 psig	345	6.3 psig	434	6.3 psig	434	7.4 psig	510	8.2 psig	565

1. Downstream pressure buildup with Secondary Seat fixed bleed in operation and regulator relief valve relieving to atmosphere.

2. Outlet pressure values listed are at maximum operating inlet pressure rating per orifice.

3. If the outlet pressure rises above setpoint exceeding the pressure rating of the regulator, the internal parts must be inspected and replaced if damaged.

**Table 6. Types CS803 and CS823 Regulator and Integral True-Monitor™ Outlet Pressure Ranges without Token Relief**

Type	PRIMARY REGULATOR						INTEGRAL TRUE MONITOR					
	Setpoint		Spring Part Number	Spring Range		Spring Color	Setpoint		Spring Part Number	Spring Range		Spring Color
	In. w.c.	mbar		In. w.c.	mbar		In. w.c.	mbar		In. w.c.	mbar	
CS803IN and CS803EN	4	10	GE30337X012	3.5 to 6	9 to 15	Red	14	35	GE30189X012	12 to 21	30 to 52	Blue
							21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	7	17	GE30338X012	5.5 to 8.5	13 to 21	Black	14	35	GE30189X012	12 to 21	30 to 52	Blue
							21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	7	17	GE49043X012	5.5 to 8.5	13 to 21	Brown (LIN)	14	35	GE30189X012	12 to 21	30 to 52	Blue
							21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	11	27	GE30339X012	8 to 12	20 to 30	Purple	21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
							1.5 psig	103	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
	14	35	GE30340X012	10 to 16	25 to 40	White	21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
1.5 psig							103	GE30190X012	1.4 to 2.9 psig	97 to 200	Black	
1 psig	69	GE30341X012	14 to 30	35 to 75	Dark Green	1.5 psig	103	GE30190X012	1.4 to 2.9 psig	97 to 200	Black	
						2 psig	138	GE30190X012	1.4 to 2.9 psig	97 to 200	Black	
						3.5 psig	241	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple	
CS823IN and CS823EN	2 psig	138	GE30342X012	1 to 2.5 psig	69 to 170	Dark Blue	2.5 psig	172	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
							3 psig	207	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple
							5 psig	345	GE30192X012	3.6 to 6 psig	248 to 414	Dark Blue
	3 psig	207	GE46922X012	1.5 to 3.5 psig	100 to 241	Orange	3.5 psig	241	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple
							4 psig	276	GE30192X012	3.6 to 6 psig	248 to 414	Dark Blue
							6 psig	414				
	5 psig	345	GE30343X012	2.5 to 5.5 psig	170 to 380	Yellow	6 psig	414				
							7 psig	483	GE33121X012	5.1 to 7.5 psig	352 to 517	Red
						7.5 psig	517					

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator



**Table 7. Types CS803 and CS823 Regulator and Integral True-Monitor™ Outlet Pressure Range with Token Relief**

Type	PRIMARY REGULATOR						INTEGRAL TRUE MONITOR					
	Setpoint		Spring Part Number	Spring Range		Spring Color	Setpoint		Spring Part Number	Spring Range		Spring Color
	In. w.c.	mbar		In. w.c.	mbar		In. w.c.	mbar		In. w.c.	mbar	
CS803IL, CS803ET and CS803EL	4	10	GE30337X012	3.5 to 6	9 to 15	Red	21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	7	17	GE30338X012	5.5 to 8.5	13 to 21	Black	21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	7	17	GE30338X012	5.5 to 8.5	13 to 21	Brown (LIN)	21	52	GE30196X012	18 to 30	45 to 75	Green
							1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
	11	27	GE30339X012	8 to 12	20 to 30	Purple	1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
							1.5 psig	103	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
	14	35	GE30340X012	10 to 16	25 to 40	White	1 psig	69	GE30225X012	26 to 40	65 to 99	Orange
							1.5 psig	103	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
	1 psig	69	GE30341X012	14 to 30	35 to 75	Dark Green	2 psig	138	GE30190X012	1.4 to 2.9 psig	97 to 200	Black
							3 psig	207	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple
CS823IT, CS823IL, CS823ET and CS823EL	2 psig	138	GE30342X012	1 to 2.5 psig	69 to 170	Dark Blue	3 psig	207	GE35081X012	2.6 to 3.7 psig	179 to 255	Purple
							4 psig	276	GE30192X012	3.6 to 6 psig	248 to 414	Dark Blue
	3 psig	207	GE46922X012	1.5 to 3.5 psig	100 to 241	Orange	5 psig	345	GE30192X012	3.6 to 6 psig	248 to 414	Dark Blue
							6 psig	414	GE33121X012	5.1 to 7.5 psig	352 to 517	Red
	5 psig	345	GE30343X012	2.5 to 5.5 psig	170 to 380	Yellow	7 psig	483	GE33121X012	5.1 to 7.5 psig	352 to 517	Red
							7.5 psig	517	GE33121X012	5.1 to 7.5 psig	352 to 517	Red

**Table 8. Inlet Pressure Rating and Flow and Sizing Coefficient**

ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE TO OBTAIN OPTIMUM PERFORMANCE				MAXIMUM EMERGENCY INLET PRESSURE		WIDE-OPEN FLOW COEFFICIENT			IEC SIZING COEFFICIENT		
		psig Setpoint		In. w.c. Setpoint									
In.	mm	psig	bar	psig	bar	psig	bar	C <sub>q</sub>	C <sub>v</sub>	C <sub>i</sub>	X <sub>r</sub>	F <sub>l</sub>	F <sub>o</sub>
1/4 <sup>(1)</sup>	6.4 <sup>(1)</sup>	125	8.6	125	8.6	175	12.1	50	2.1	24.6	0.38	0.89	0.99
3/8	9.5	125	8.6	125	8.6	175	12.1	110	3.8	29.5	0.55	0.89	0.90
1/2	13	100	6.9	100	6.9	175	12.1	210	7.2	29.5	0.55	0.89	0.93
5/8	16	80	6.5	60	4.1	175	12.1	320	10.1	31.8	0.64	0.89	0.88
3/4	19	80	6.5	60	4.1	175	12.1	450	13.3	34	0.73	0.89	0.84
7/8	22	60	4.1	50	3.4	175	12.1	600	16.7	36	0.82	0.89	0.81
1 <sup>(1)</sup>	25 <sup>(1)</sup>	30	2.1	25	1.7	175	12.1	765	20.1	38.1	0.92	0.89	0.77
1-3/8 <sup>(1)(2)</sup>	35 <sup>(1)(2)</sup>	15	1.0	15	1.0	175	12.1	1125	29.8	37.7	0.90	0.89	0.76

1. Not available on the Types CS805, CS806, CS825 and CS826.  
2. Not available on the Types CS803 and CS823.

**Table 9. Approximate Internal Relief Valve Start-to-Discharge Pressure Above Setpoint**

CONTROL SPRING	SETPOINT		SET RANGE		INTERNAL RELIEF AND HIGH CAPACITY RELIEF				TOKEN RELIEF	
					Start-to-Discharge Pressure Range above Setpoint		Low Start-to-Discharge Option <sup>(1)</sup>		Start-to-Discharge Pressure Range above Setpoint	
	In. w.c.	mbar	In. w.c.	mbar			In. w.c.	mbar		
GE30337X012	4	10	3.5 to 6	9 to 15	11 to 18	27 to 42	7 to 14	17 to 35	6 to 14	15 to 35
GE30338X012	7	17	5.5 to 8.5	13 to 21	11 to 18	27 to 42	7 to 14	17 to 35	6 to 14	15 to 35
GE49043X012 (LIN)	7	17	5.5 to 8.5	13 to 21	11 to 18	27 to 42	7 to 14	17 to 35	6 to 14	15 to 35
GE30339X012	11	27	8 to 12	20 to 30	11 to 18	27 to 42	7 to 14	17 to 35	6 to 14	15 to 35
GE30340X012	14	35	10 to 16	25 to 40	11 to 18	27 to 42	7 to 14	17 to 35	6 to 14	15 to 35
GE30341X012	1 psig	69	14 to 30	35 to 75	7 in. w.c. to 1 psig	17 to 69	----	----	8 to 16	20 to 40
GE30342X012	2 psig	138	1 to 2.5 psig	70 to 170	7 in. w.c. to 2 psig	17 to 138	----	----	7 in. w.c. to 1 psig	17 to 69
GE46922X012	3 psig	207	1.5 to 3.5 psig	100 to 240	7 in. w.c. to 2 psig	17 to 138	----	----	0.5 to 1.5 psig	35 to 100
GE30343X012	5 psig	345	2.5 to 5.5 psig	170 to 380	7 in. w.c. to 2.5 psig	17 to 170	----	----	1 to 2 psig	69 to 138

1. Low start-to-discharge option is only available on the main control spring ranges up to 10 to 16 in. w.c. / 25 to 40 mbar.



**Table 10. Regulator and Slam-Shut Overpressure Shutoff (OPSO) Pressure Ranges**

REGULATOR					SLAM-SHUT DEVICE				
					Over Pressure Shut-off (OPSO)				
Type	Factory Setpoint		Spring Range		Factory Setpoint <sup>(1)</sup>		Spring Range <sup>(2)</sup>		Spring Part Number and Color
	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	
CS804	4	10	3.5 to 6	9 to 15	19	47	12 to 25	30 to 60	GF02168X012 / Brown
	7	17	5.5 to 8.5	14 to 21	22	55			
	7 (optional)	17 (optional)	5.5 to 8.5	14 to 21	25	62	16 to 44	40 to 110	GF02169X012 / Red
	11	27	8 to 12	20 to 30					
	14	35	10 to 16	25 to 40	30	75	24 to 78	60 to 190	GF02170X012 / Orange
	14 (optional)	35 (optional)	10 to 16	25 to 40	2 psig	138	1.4 to 4.1 psig	97 to 283	GF02171X012 / Pink
1 psig	69	14 to 30	35 to 75	2 psig	138				
CS824	2 psig	138	1 to 2.5 psig	69 to 170	3.5 psig	241	2 to 7.3 psig	138 to 503	GF02172X012 / Green
	3 psig	207	1.5 to 3.5 psig	100 to 241	5 psig	345			
	5 psig	345	2.5 to 5.5 psig	170 to 380	7 psig	483	3.2 to 8.5 psig	221 to 586	GF02173X012 / Silver
CS854	7 psig	483	5 to 10 psig	345 to 690	9 psig	621	5.8 to 13 psig	400 to 896	GF04353X012 / Yellow

1. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 9.  
2. If Non-Factory OPSO setpoints are specified, the allowable OPSO setpoint cannot exceed the maximum of 3 psig / 207 mbar above the regulator setpoint in order to ensure no internal parts damage from overpressure.

**Table 11. Regulator and Slam-Shut Underpressure Shutoff (UPSO) Pressure and Overpressure Shutoff (OPSO) Ranges**

REGULATOR					SLAM-SHUT DEVICE									
					Under Pressure Shut-off (UPSO)				Over Pressure Shut-off (OPSO)					
Type	Factory Setpoint		Spring Range		Factory Setpoint <sup>(1)</sup>		Spring Range		Spring Part Number and Color	Factory Setpoint <sup>(2)</sup>		Spring Range Over UPSO Setpoint <sup>(3)</sup>		Spring Part Number and Color
	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar	In. w.c.	mbar		In. w.c.	mbar	In. w.c.	mbar	
CS804	7	17	5.5 to 8.5	14 to 21	3	7	2 to 12	5 to 30	T14168T0012 / White	22	55	17 to 28	42 to 69	GF02168X012 / Brown
	11	27	8 to 12	20 to 30	6	15				25	62			
	14	35	10 to 16	25 to 40	9	22	0.36 to 2.3 psig	25 to 160	T14170T0012 / Silver	30	75	1.3 to 3.1 psig	90 to 214	GF02170X012 / Orange
	1 psig	69	14 to 30	35 to 75	0.5 psig	35								
CS824	2 psig	138	1 to 2.5 psig	69 to 170	1 psig	69	0.36 to 2.3 psig	25 to 160	T14170T0012 / Silver	3.5 psig	241	1.3 to 3.1 psig	90 to 214	GF02170X012 / Orange
	3 psig	207	1.5 to 3.5 psig	100 to 241	1.75 psig	121	1.5 to 7.3 psig	100 to 500	FA142869X12 / Orange Stripe	5 psig	345	2.7 to 5.5 psig	186 to 379	GF02171X012 / Pink
	5 psig	345	2.5 to 5.5 psig	170 to 380	3 psig	207				7 psig	483			
CS854	7 psig	483	5 to 10 psig	345 to 690	3.5 psig	241	1.5 to 7.3 psig	100 to 500	FA142869X12 / Orange Stripe	9 psig	621	2.7 to 5.5 psig	186 to 379	GF02171X012 / Pink

1. If Non-Factory UPSO setpoints are specified, a minimum differential of 4 in. w.c. / 10 mbar between UPSO setpoint and regulator setpoint must be maintained in order to ensure a secure latch of the Slam-Shut.  
2. For units equipped with Token Relief, if Non-Factory Slam-shut OPSO setpoints are specified, they must be higher than the Token Relief Start-to-Discharge values provided in Table 9.  
3. If Non-Factory OPSO setpoints are specified, the allowable OPSO setpoint cannot exceed the maximum of 3 psig / 207 mbar above the regulator setpoint in order to ensure no internal parts damage from overpressure.

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator



SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
4 in. w.c.	-1 in. w.c.	2 in. w.c.	3.5 to 6 in. w.c.	GE30337X012 / Red
10 mbar	-2.5 mbar	5 mbar	9 to 15 mbar	

**Table 12. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 4 in. w.c. / 10 mbar Setpoint for 1-1/2 in. / DN 40 Body Size**

Capacities in SCFH / Nm <sup>3</sup> /h of 0.6 Specific Gravity Natural Gas																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 1-1/2 in. / DN 40																	
psig	bar																
0.4	0.03			300	8.1	300	8.1	300	8.1	1000	26.8	1400	37.6	1400	37.6	1600	43.0
0.51	0.04			300	8.1	500	13.4	850	22.8	1400	37.6	1590	42.7	1600	43.0	1710	45.9
1	0.07	400	10.7	800	21.5	1200	32.2	1540	41.3	2100	56.4	2300	61.7	2500	67.1	2700	72.5
2	0.14	600	16.1	1300	34.9	2000	53.7	2400	64.4	2800	75.2	3100	83.2	3470	93.2	3470	93.2
3	0.21	780	20.9	1600	43.0	2470	66.3	2860	76.8	3360	90.2	3620	97.2	4100	110	4190	113
5	0.34	1150	30.9	2170	58.3	2940	78.9	3800	102	4500	121	4580	123	5190	139	5190	139
10	0.69	1370	36.8	2900	77.9	4750	128	5200	140	5650	152	5650	152	5650	152	5930	159
15	1.0	1600	43.0	3600	96.6	6200	166	6500	175	6500	175	6500	175	6000	161	6710	180
20	1.4	2070	55.6	4300	115	6620	178	7250	195	7250	195	7400	199	7500	201		
25	1.7	2550	68.5	5000	134	7050	189	7250	195	7250	195	7500	201	9000	242		
30	2.1	2860	76.8	5010	135	7050	189	7250	195	7250	195	7500	201				
40	2.8	3170	85.1	5020	135	7050	189	7250	195	7250	195	7500	201				
50	3.4	4120	111	5070	136	7050	189	7250	195	7250	195	7500	201				
60	4.1	4750	128	5100	137	7050	189	7250	195	7250	195						
80	5.5	5700	153	6200	166	7170	193										
100	6.9	6650	179	7300	196	7300	196										
125	8.6	6950	187	8300	223												

     - Black areas show where indicated droop/boost would be exceeded regardless of capacity.  
     - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on Type CS803.

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
4 in. w.c.	-1 in. w.c.	2 in. w.c.	3.5 to 6 in. w.c.	GE30337X012 / Red
10 mbar	-2.5 mbar	5 mbar	9 to 15 mbar	

**Table 13. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 4 in. w.c. / 10 mbar Setpoint for 2 in. / DN 50 Body Size**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 2 in. / DN 50																	
psig	bar																
0.4	0.03			300	8.1	300	8.1	300	8.1	1170	31.4	1400	37.6	1600	43.0	1800	48.3
0.51	0.04			300	8.1	500	13.4	1000	26.8	1550	41.6	1900	51.0	2070	55.6	2400	64.4
1	0.07	400	10.7	900	24.2	1300	34.9	1760	47.2	1950	52.3	3000	80.5	2710	72.8	3800	102
2	0.14	600	16.1	1240	33.3	2070	55.6	2620	70.3	3930	106	5000	134	3450	92.6	5620	151
3	0.21	730	19.6	1530	41.1	2580	69.3	3540	95.0	4980	134	6200	166	6830	183	8010	215
5	0.34	1000	26.8	2090	56.1	3700	99.3	5500	148	7800	209	8600	231	9500	255	10,620	285
10	0.69	1320	35.4	3000	80.5	5100	137	7450	200	10,400	279	10,900	293	11,750	315	12,580	338
15	1.0	1650	44.3	3700	99.3	6500	175	9400	252	13,000	349	13,200	354	14,000	376	13,150	353
20	1.4	2020	54.2	4450	120	7850	211	10,150	273	13,000	349	13,200	354	16,000	430		
25	1.7	2400	64.4	5200	140	9200	247	10,900	293	13,000	349	13,200	354	18,000	483		
30	2.1	2720	73.0	5560	149	9460	254	10,980	295	13,400	360	13,560	364				
40	2.8	3040	81.6	5920	159	9720	261	11,060	297	13,800	371	13,920	374				
50	3.4	4000	107	7000	188	10,500	282	11,300	303	15,000	403	12,510	336				
60	4.1	4450	120	9000	242	12,800	344	13,800	371	11,140	299						
80	5.5	4970	133	9250	248	12,850	345										
100	6.9	5500	148	9500	255	11,770	316										
125	8.6	7250	195	9500	255												

     - Black areas show where indicated droop/boost would be exceeded regardless of capacity.  
     - Gray areas indicate limited capacities due to boost effects.  
     - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on the Type CS803.



SETPOINT	ACCURACY		SPRING	
	Drop	Boost	Set Range	Part Number / Color
7 in. w.c.	-1 in. w.c.	2 in. w.c.	5.5 to 8.5 in. w.c.	GE30338X012 / Black
17 mbar	-2.5 mbar	5 mbar	13 to 21 mbar	

**Table 14. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 7 in. w.c. / 17 mbar Setpoint for 1-1/2 in. / DN 40 Body Size**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40															
0.4	0.03			430	11.5	740	19.9	550	14.8	800	21.5	800	21.5	1060	28.5	1420	38.1
0.51	0.04			520	14.0	800	21.5	890	23.9	1100	29.5	1150	30.9	1300	34.9	1630	43.8
1	0.07	570	15.3	770	20.7	1140	30.6	1360	36.5	1510	40.5	1830	49.1	1960	52.6	2640	70.9
2	0.14	780	20.9	980	26.3	1570	42.1	1790	48.1	2220	59.6	2510	67.4	2790	74.9	3550	95.3
3	0.21	990	26.6	1230	33.0	1960	52.6	2380	63.9	2810	75.4	3310	88.9	3680	98.8	4380	118
5	0.34	1220	32.8	1920	51.5	2940	78.9	3390	91.0	4130	111	4130	111	4850	130	5510	148
10	0.69	1600	43.0	3160	84.8	4900	132	5130	138	5950	160	6270	168	6650	179	7200	193
15	1.0	1980	53.2	4150	111	6310	169	6040	162	7110	191	7240	194	7520	202	7650	205
20	1.4	2330	62.6	4910	132	7300	196	7130	191	7770	209	7770	209	8010	215		
25	1.7	2620	70.3	5680	153	7550	203	7550	203	8220	221	8330	224	8330	224		
30	2.1	2990	80.3	6370	171	8310	223	8140	219	8560	230	8560	230				
40	2.8	3650	98.0	7830	210	8990	241	8690	233	8770	235	8770	235				
50	3.4	4320	116	9010	242	9010	242	8880	238	9000	242	9210	247				
60	4.1	5010	135	9040	243	9040	243	9040	243	9070	244						
80	5.5	6290	169	9620	258	9620	258										
100	6.9	7550	202	9510	255	9510	255										
125	8.6	7820	210	9600	258												

     - Black areas show where indicated droop/boost would be exceeded regardless of capacity.  
     - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on Type CS803.

SETPOINT	ACCURACY		SPRING	
	Drop	Boost	Set Range	Part Number / Color
7 in. w.c.	-1 in. w.c.	2 in. w.c.	5.5 to 8.5 in. w.c.	GE30338X012 / Black
17 mbar	-2.5 mbar	5 mbar	13 to 21 mbar	

**Table 15. Types CS800<sup>(1)</sup>, CS803<sup>(2)</sup> and CS804<sup>(2)</sup> Internal Registration Flow Capacities for 7 in. w.c. / 17 mbar Setpoint for 2 in. / DN 50 Body Size**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25 <sup>(1)(2)</sup>		1-3/8 / 35 <sup>(3)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 2 in. / DN 50															
5	0.34	1120	30.1	1120	30.1	2600	69.8	3670	98.5	4630	124	8130	218	9590	257	5510	148
10	0.69	1480	39.7	2520	67.7	4840	130	9100	244	12,450	334	13,250	356	16,280	437	7200	193
15	1.0	1870	50.2	3130	84.0	7760	208	12,000	322	16,170	434	16,630	446	20,380	547	7650	205
20	1.4	2130	57.2	4230	114	9200	247	14,550	391	19,090	513	17,370	466	22,860	614		
25	1.7	2500	67.1	5530	149	10,510	282	15,920	427	20,180	542	17,370	466	22,860	614		
30	2.1	2850	76.5	6290	169	11,850	318	18,720	503	23,010	618	17,380	467				
40	2.8	3590	96.4	7850	211	14,100	379	22,910	615	25,910	696	16,180	434				
50	3.4	4200	113	9280	249	16,740	449	24,340	653	27,340	734	12,050	324				
60	4.1	4910	132	10,810	290	19,390	521	24,360	654	19,730	530						
80	5.5	6220	167	13,740	369	25,530	685										
100	6.9	7440	200	16,630	446	25,530	685										
125	8.6	8730	234	20,320	546												

     - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
     - Gray areas indicate limited capacities due to boost effects.  
 1. Type CS800 with Ductile iron or Steel Bodies exhibit a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.  
 2. Types CS803 and CS804 exhibit a 30% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.7.  
 3. Not available on the Type CS803.




Figure 9. Type CS800IR Relief Curves (Blocked Open per Orifice Size) at 7 in. w.c. / 17 mbar Set Pressure




Figure 10. Type CS800IQ High Capacity Relief Curves (Blocked Open per Orifice Size) at 7 in. w.c. / 17 mbar Set Pressure

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
14 in. w.c.	-2 in. w.c.	2 in. w.c.	10 to 16 in. w.c.	GE30340X012 / White
35 mbar	-5 mbar	5 mbar	25 to 40 mbar	

**Table 16. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 14 in. w.c. / 35 mbar Setpoint for 1-1/2 in. / DN 40 Body Size**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, in. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40															
1	0.07	450	12.1	670	18.0	1000	26.8	1100	29.5	1250	33.6	1400	37.6	1500	40.3	1950	52.3
2	0.14	550	14.8	1070	28.7	1400	37.6	1600	43.0	1750	47.0	2000	53.7	2300	61.7	2500	67.1
3	0.21	700	18.8	1160	31.1	1610	43.2	1900	51.0	2160	58.0	2500	67.1	2960	79.5	3250	87.2
5	0.34	1000	26.8	1200	32.2	2050	55.0	2500	67.1	3000	80.5	3600	96.6	4300	115	4750	128
10	0.69	1370	36.8	2120	56.9	3150	84.6	3800	102	4550	122	5100	137	5800	156	6300	169
15	1.0	1750	47.0	3050	81.9	4250	114	5100	137	6100	164	6700	180	7300	196	7850	211
20	1.4	2120	56.9	3900	105	4950	133	6000	161	7250	195	7600	204	8000	215		
25	1.7	2500	67.1	4750	128	5650	152	7000	188	8700	234	8700	234	8600	231		
30	2.1	2820	75.7	5420	146	6260	168	7500	201	8960	241	8960	241				
40	2.8	3140	84.3	6090	164	6870	184	7900	212	9220	248	9220	248				
50	3.4	4100	110	8100	217	8720	234	9300	250	9870	265	9870	265				
60	4.1	4750	128	9450	254	9730	261	9730	261	10,240	275						
80	5.5	6100	164	9920	266	10,270	276										
100	6.9	7450	200	10,400	279	10,430	280										
125	8.6	9050	243	10,400	279												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on Type CS803.

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
14 in. w.c.	-2 in. w.c.	2 in. w.c.	10 to 16 in. w.c.	GE30340X012 / White
35 mbar	-5 mbar	5 mbar	25 to 40 mbar	

**Table 17. Types CS800, CS803 and CS804 Series Internal Registration Flow Capacities for 14 in. w.c. / 35 mbar Setpoint for 2 in. / DN 50 Body Size**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, in. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 2 in. / DN 50															
1	0.07	450	12.1	630	16.9	770	20.7	1300	34.9	1500	40.3	1600	43.0	1700	45.6	2700	72.5
2	0.14	600	16.1	1000	26.8	1800	48.3	2240	60.1	2800	75.2	3260	87.5	3800	102	3800	102
3	0.21	750	20.1	1210	32.5	2200	59.1	2700	72.5	3200	85.9	3700	99.3	4300	115	6060	163
5	0.34	1050	28.2	1750	47.0	2800	75.2	3300	88.6	4000	107	4600	124	5300	142	10,200	274
10	0.69	1400	37.6	2720	73.0	4250	114	6500	175	9200	247	10,300	277	11,650	313	14,550	391
15	1.0	1750	47.0	3700	99.3	5700	153	9600	258	14,400	387	16,100	431	17,910	481	17,110	459
20	1.4	2170	58.3	4700	126	7950	213	11,700	314	16,200	435	18,800	504	20,290	544		
25	1.7	2560	68.7	5700	153	10,200	274	12,400	333	18,000	483	21,400	574	22,000	590		
30	2.1	2910	78.1	6440	173	10,310	277	12,400	333	18,220	489	21,400	574				
40	2.8	3540	95.0	7770	209	10,540	283	13,020	350	18,680	501	21,400	574				
50	3.4	4170	112	9190	247	10,770	289	14,500	389	19,140	513	21,400	574				
60	4.1	4800	129	10,900	293	11,000	295	14,900	400	19,600	525						
80	5.5	6100	164	12,550	337	12,550	337										
100	6.9	7400	199	14,100	379	14,100	379										
125	8.6	9100	244	16,120	433												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on Type CS803.

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™




Figure 11. Type CS800IR Relief Curves (Blocked Open per Orifice Size) at 14 In. w.c. / 35 mbar Set Pressure




Figure 12. Types CS800IQ High Capacity Relief Curves (Blocked Open per Orifice Size) at 14 In. w.c. / 35 mbar Set Pressure



SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-2.8 in. w.c.	2.8 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
0.07 bar	-7 mbar	7 mbar	35 to 75 mbar	

**Table 18. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint for 1-1/2 in. / DN 40 Body Size at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)(2)</sup>	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 1-1/2 in. / DN 40																	
2	0.14	530	14.2	710	19.1	940	25.2	1220	32.8	1430	38.4	1430	38.4	1330	35.7	1930	51.8
3	0.21	620	16.6	1070	28.7	1150	30.9	1490	40.0	1770	47.5	1700	45.6	1700	45.6	2530	67.9
5	0.34	810	21.7	1560	41.9	1650	44.3	2050	55.0	2530	67.9	2450	65.8	2450	65.8	3750	101
10	0.69	1360	36.5	2080	55.8	3100	83.2	3840	103	4680	126	4840	130	4950	133	5330	143
15	1.0	1650	44.3	2920	78.4	3860	104	4670	125	5570	150	6290	169	7000	188	7500	201
20	1.4	1960	52.6	3650	98.0	4560	122	5040	135	5570	150	6680	179	8120	218		
25	1.7	2400	64.4	4400	118	5550	149	6700	180	7900	212	7900	212	8650	232		
30	2.1	2570	69.0	5270	142	5650	152	7080	190	8220	221	9300	250	9990	268		
40	2.8	3360	90.2	3960	106	7300	196	7790	209	8470	227	8510	229				
50	3.4	3960	106	7920	213	7970	214	8590	231	8920	240	8920	240				
60	4.1	4660	125	7820	210	8020	215	8520	229	9020	242	9020	242				
80	5.5	5860	157	8740	235	9020	242	9020	242	9020	242						
100	6.9	7350	197	8960	241	10,150	273										
125	8.6	9050	243	10,020	269												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on the Type CS803.  
 2. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.

SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-2.8 in. w.c.	2.8 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
0.07 bar	-7 mbar	7 mbar	35 to 75 mbar	

**Table 19. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint for 2 in. / DN 50 Body Size at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 2 in. / DN 50																	
2	0.14	500	13.4	860	23.1	1420	38.1	1450	38.9	1450	38.9	1450	38.9	1450	38.9	1450	38.9
3	0.21	610	16.4	1030	27.7	1420	38.1	1660	44.6	2000	53.7	2300	61.7	2700	72.5	3260	87.5
5	0.34	850	22.8	1640	44.0	1800	48.3	2130	57.2	2570	69.0	3320	89.1	4190	113	5140	138
10	0.69	1350	36.2	1750	47.0	2380	63.9	4000	107	5920	159	6540	176	7110	191	8470	227
15	1.0	1610	43.2	2690	72.2	3540	95.0	5290	142	7470	201	7680	206	8050	216	9580	257
20	1.4	2000	53.7	3760	101	5350	144	7430	200	9760	262	9760	262	9800	263		
25	1.7	2400	64.4	4340	117	7000	188	9770	262	13,100	352	13,410	360	13,890	373		
30	2.1	2470	66.3	5120	137	7500	201	11,420	307	16,250	436	17,320	465	18,520	497		
40	2.8	3490	93.7	7300	196	13,100	352	15,510	416	18,410	494	20,910	561				
50	3.4	3900	105	8020	215	16,110	433	17,090	459	18,410	494	22,290	598				
60	4.1	4600	124	10,700	287	18,800	505	19,700	529	20,700	556	22,410	602				
80	5.5	5700	153	13,000	349	18,800	505	19,700	529	20,700	556						
100	6.9	7190	193	15,720	422	19,070	512										
125	8.6	9190	247	19,600	526												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on the Type CS803.

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator



SETPOINT	ACCURACY: +/- 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-5.5 in. w.c.	5.5 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
0.07 bar	-14 mbar	14 mbar	35 to 75 mbar	

**Table 20. Types CS800, CS803<sup>(1)</sup> and CS804<sup>(2)</sup> Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint for 1-1/2 in. / DN 40 Body Size at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, Inch / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)(2)</sup>	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 1-1/2 in. / DN 40																	
2	0.14	500	13.4	750	20.1	1750	47.0	2000	53.7	2250	60.4	2300	61.7	2400	64.4	2850	76.5
3	0.21	700	18.8	1100	29.5	1930	51.8	2200	59.1	2630	70.6	2900	77.9	3210	86.2	3680	98.8
5	0.34	1100	29.5	1800	48.3	2300	61.7	2800	75.2	3400	91.3	4100	110	4850	130	5350	144
10	0.69	1600	43.0	3200	85.9	4600	124	5800	156	7250	195	8000	215	8800	236	8800	236
15	1.0	1900	51.0	3970	107	5400	145	6600	177	8030	216	8700	234	9410	253	10,020	269
20	1.4	2200	59.1	4750	128	6200	166	7400	199	8820	237	9400	252	10,020	269		
25	1.7	2500	67.1	5520	148	7000	188	8200	220	9610	258	10,100	271	10,630	285		
30	2.1	2800	75.2	6300	169	7800	209	9000	242	10,400	279	10,800	290	11,250	302		
40	2.8	3500	94.0	7400	199	8410	226	9400	252	10,600	285	10,600	285				
50	3.4	4200	113	8500	228	9030	242	9800	263	10,800	290	10,800	290				
60	4.1	4900	132	9600	258	9650	259	10,300	277	11,000	295	11,000	295				
80	5.5	6100	164	10,070	270	10,800	290	10,900	293	11,000	295						
100	6.9	7300	196	10,550	283		321										
125	8.6	9100	244	10,550	283												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on the Type CS803.  
 2. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.

SETPOINT	ACCURACY: +/- 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-5.5 in. w.c.	5.5 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
0.07 bar	-14 mbar	14 mbar	35 to 75 mbar	

**Table 21. Types CS800, CS803 and CS804 Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint for 2 in. / DN 50 Body Size at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
Body Size: 2 in. / DN 50																	
2	0.14	650	17.4	1040	27.9	2200	59.1	2570	69.0	3200	85.9	3400	91.3	3600	96.6	4500	121
3	0.21	800	21.5	1560	41.9	2530	67.9	3100	83.2	3730	100	4300	115	4960	133	6330	170
5	0.34	1100	29.5	2300	61.7	3200	85.9	3900	105	4800	129	6100	164	7700	207	10,000	269
10	0.69	1600	43.0	3000	80.5	4300	115	7500	201	11,400	306	13,200	354	15,200	408	16,300	438
15	1.0	1900	51.0	4000	107	6900	185	10,800	290	14,560	391	18,000	483	19,930	535	20,170	542
20	1.4	2300	61.7	4900	132	9100	244	13,600	365	18,520	497	21,300	572	22,680	609		
25	1.7	2600	69.8	5600	150	10,500	282	15,500	416	21,700	583	24,300	652	24,410	655		
30	2.1	2900	77.9	6500	175	11,800	317	17,900	481	24,020	645	25,320	680	25,580	687		
40	2.8	3700	99.3	8000	215	14,500	389	20,100	540	27,000	725	27,810	747				
50	3.4	4300	115	9300	250	16,600	446	21,700	583	27,810	747	27,810	747				
60	4.1	4900	132	10,940	294	19,500	524	24,900	669	29,050	780	29,050	780				
80	5.5	6300	169	13,830	371	24,000	644	27,400	736	29,070	780						
100	6.9	7700	207	16,680	448	29,500	792										
125	8.6	9600	258	20,200	542												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on the Type CS803.






Figure 13. Type CS800IR Relief Curves (Blocked Open per Orifice Size) at 1 psig / 0.07 bar Set Pressure




Figure 14. Type CS800IQ High Capacity Relief Curves (Blocked Open per Orifice Size) at 1 psig / 0.07 bar Set Pressure

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.20 psig	0.20 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-14 mbar	14 mbar	0.07 to 0.17 bar	

**Table 22. Types CS820, CS823 and CS824 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint for 1-1/2 in. / DN 40 Body Size at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40															
3	0.21	740	19.9	1170	31.4	1170	31.4	1560	41.9	1730	46.4	2240	60.1	2240	60.1	3080	82.7
5	0.34	960	25.8	1410	37.9	1980	53.2	2510	67.4	2850	76.5	3640	97.7	3980	107	4830	130
10	0.69	1450	38.9	2260	60.7	3360	90.2	4320	116	5040	135	5510	148	6030	162	7410	199
15	1.0	1940	52.1	3080	82.7	4640	125	5830	157	6480	174	6980	187	7740	208	8440	227
20	1.4	2310	62.0	3880	104	5920	159	7090	190	7720	207	8020	215	8860	238		
25	1.7	2610	70.1	4660	125	6830	183	8210	220	8470	227	8600	231	9180	246		
30	2.1	2960	79.5	5430	146	7750	208	8810	237	9450	254	9120	245	9860	265		
40	2.8	3570	95.8	6830	183	9110	245	10,220	274	10,230	275	10,230	275				
50	3.4	4340	117	8310	223	10,060	270	10,520	282	10,800	290	10,800	290				
60	4.1	4970	133	9680	260	10,850	291	11,100	298	11,100	298	11,100	298				
80	5.5	6370	171	11,390	306	11,810	317	11,810	317	11,810	317						
100	6.9	7590	204	12,070	324	12,090	325										
125	8.6	9340	251	12,080	324												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on the Type CS823.

SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.20 psig	0.20 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-14 mbar	14 mbar	0.07 to 0.17 bar	

**Table 23. Types CS820, CS823<sup>(1)</sup> and CS824 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint for 2 in. / DN 50 Body Size at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(2)(3)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 2 in. / DN 50															
3	0.21	670	18.0	910	24.4	1280	34.4	1760	47.2	1920 <sup>(1)</sup>	51.5 <sup>(1)</sup>	2310	62.0	2770	74.4	3490	93.7
5	0.34	1080	29.0	1430	38.4	2230	59.9	3110	83.5	3440 <sup>(1)</sup>	92.3 <sup>(1)</sup>	4830	130	4970	133	6390	172
10	0.69	1510	40.5	2580 <sup>(1)</sup>	69.3 <sup>(1)</sup>	4040	109	5470	147	6680	179	8670	233	10,060	270	12,100	325
15	1.0	1900	51.0	3610	96.9	6220	167	8610	231	9800	263	12,320	331	13,570	364	17,260	463
20	1.4	2310	62.0	4520	121	7980	214	10,990	295	13,000	349	14,630	393	16,230	436		
25	1.7	2620	70.3	5380	144	9690	260	13,480	362	16,010	430	17,180	461	18,510	497		
30	2.1	2940	78.9	5910	159	11,080	297	15,240	409	18,190	488	19,450	522	19,930	535		
40	2.8	3530	94.8	7770	209	14,390	386	18,740	503	21,510	577	22,830	613				
50	3.4	4250	114	8860	238	17,160	461	22,320	599	23,060	619	23,060	619				
60	4.1	4980	134	10,710	288	20,160	541	23,740	637	23,740	637	23,740	637				
80	5.5	6310	169	13,640	366	25,290	679	26,330	707	26,330	707						
100	6.9	7640	205	16,380	440	29,370	789										
125	8.6	9370	252	19,980	536												

1. Due to droop, the Type CS823 exhibits a 10% reduction in capacity for indicated conditions. Multiply listed values by a factor of 0.9.  
2. Not available on the Type CS823.  
3. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.



SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.40 psig	0.40 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-28 mbar	28 mbar	0.07 to 0.17 bar	

**Table 24. Types CS820, CS823 and CS824 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint for 1-1/2 in. / DN 40 Body Size at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40															
3	0.21	820	22.0	1420	38.1	1960	52.6	2830	76.0	3200	85.9	3950	106	4160	112	4620	124
5	0.34	1060	28.5	1860	49.9	3220	86.4	4200	113	5020	135	5920	159	6570	176	8000	215
10	0.69	1590	42.7	3120	83.8	5230	140	6870	184	7600	204	8410	226	9580	257	11,220	301
15	1.0	1990	53.4	4090	110	6970	187	8880	238	9820	264	10,200	274	11,520	309	11,790	317
20	1.4	2310	62.0	4880	131	8440	227	10,380	279	11,160	300	11,490	309	12,630	339		
25	1.7	2680	71.9	5640	151	9630	259	11,480	308	12,480	335	12,130	326	13,570	364		
30	2.1	2980	80.0	6340	170	10,670	286	12,360	332	12,960	348	12,990	349	13,920	374		
40	2.8	3660	98.3	7850	211	12,140	326	14,150	380	14,240	382	13,470	362				
50	3.4	4360	117	9260	249	13,460	361	14,190	381	14,920	401	14,280	383				
60	4.1	5000	134	10,860	292	14,740	396	14,910	400	15,260	410	14,620	393				
80	5.5	6400	172	13,710	368	15,440	415	15,440	415	15,440	415						
100	6.9	7670	206	15,900	427	16,200	435										
125	8.6	9410	253	16,080	432												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on the Type CS823.

SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.40 psig	0.40 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-28 mbar	28 mbar	0.07 to 0.17 bar	

**Table 25. Types CS820, CS823<sup>(1)(2)</sup> and CS824 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint for 2 in. / DN 50 Body Size at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25 <sup>(1)</sup>		1-3/8 / 35 <sup>(3)(4)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 2 in. / DN 50															
3	0.21	730	19.6	1280	34.4	2140	57.4	2890	77.6	3400 <sup>(2)</sup>	91.3 <sup>(2)</sup>	4190	113	4800	129	6490	174
5	0.34	1150	30.9	1960	52.6	3440	92.3	4380	118	5700 <sup>(2)</sup>	153 <sup>(2)</sup>	6770	182	7960	214	11,840	318
10	0.69	1610	43.2	3260	87.5	5790	155	7870	211	9930	267	11,840	318	13,680	367	18,160	488
15	1.0	1980	53.2	4200	113	7760	208	10,520	282	13,510	363	16,080	432	18,220	489	20,810	559
20	1.4	2330	62.6	4950	133	9250	248	12,990	349	16,570	445	19,760	531	20,610	553		
25	1.7	2660	71.4	5710	153	10,560	284	15,060	404	19,630	527	22,340	600	23,530	632		
30	2.1	2940	78.9	6300	169	11,890	319	17,290	464	21,870	587	24,500	658	25,180	676		
40	2.8	3600	96.6	7950	213	14,880	400	21,370	574	24,710	663	28,610	768				
50	3.4	4280	115	9200	247	17,600	473	24,860	667	27,290	733	29,870	802				
60	4.1	4980	134	10,890	292	20,430	549	29,670	797	29,670	797	30,930	830				
80	5.5	6310	169	13,710	368	25,880	695	32,240	866	32,240	866						
100	6.9	7650	205	16,620	446	31,200	838										
125	8.6	9360	251	20,220	543												

1. Type CS823 exhibits a 10% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.9.  
2. Due to droop, the Type CS823 exhibits a 15% reduction in capacity for indicated conditions. Multiply listed values by a factor of 0.85.  
3. Not available on the Type CS823.  
4. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™




Figure 15. Type CS8201R Relief Curves (Blocked Open per Orifice Size) at 2 psig / 0.14 bar Set Pressure




Figure 16. Types CS8201Q High Capacity Relief Curves (Blocked Open per Orifice Size) at 2 psig / 0.14 bar Set Pressure



SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
5 psig	-0.50 psig	0.50 psig	2.5 to 5.5 psig	GE30343X012 / Yellow
0.34 bar	-34 mbar	34 mbar	0.17 to 0.38 bar	

**Table 26. Types CS820, CS823 and CS824 Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint at 10% Accuracy**

CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
<b>Body Size: 1-1/2 in. / DN 40</b>																	
10	0.69	1450	38.9	1870	50.2	2650	71.1	3640	97.7	4170	112	5190	139	5760	155	7240	194
15	1.0	1910	51.3	2640	70.9	3920	105	5070	136	6050	162	6970	187	7960	214	9410	253
20	1.4	2260	60.7	3440	92.3	4910	132	6530	175	7520	202	8800	236	9670	260		
25	1.7	2640	70.9	4060	109	5920	159	7510	202	8570	230	9620	258	11,320	304		
30	2.1	2710	72.8	4700	126	6690	180	8750	235	9900	266	10,670	286	12,160	326		
40	2.8	3410	91.5	6000	161	8000	215	10,100	271	11,330	304	13,220	355				
50	3.4	4100	110	7260	195	10,070	270	11,540	310	13,030	350	14,920	401				
60	4.1	4950	133	8610	231	11,250	302	12,880	346	14,220	382	15,630	420				
80	5.5	6260	168	10,690	287	13,890	373	15,400	413	16,290	437						
100	6.9	7660	206	12,590	338	15,980	429										
125	8.6	9300	250	14,860	399												
<b>Body Size: 2 in. / DN 50</b>																	
10	0.69	1280	34.4	1880	50.5	2940	78.9	3530	94.8	4830	130	4970	133	6060	163	7680 <sup>(2)</sup>	206 <sup>(2)</sup>
15	1.0	1880	50.5	2410	64.7	4310	116	5160	139	7240	194	7610	204	9790	263	12,150 <sup>(2)</sup>	326 <sup>(2)</sup>
20	1.4	2300	61.7	3310	88.9	5610	151	6900	185	9230	248	10,390	279	12,770	343		
25	1.7	2660	71.4	4200	113	7040	189	8220	221	10,950	294	12,690	341	15,480	416		
30	2.1	2950	79.2	4990	134	8220	221	10,580	284	13,060	351	14,810	398	19,260	517		
40	2.8	3640	97.7	6360	171	11,080	297	14,630	393	17,710	475	20,120	540				
50	3.4	4280	115	8000	215	14,370	386	18,760	504	21,200	569	23,760	638				
60	4.1	4940	133	9900	266	17,590	472	21,760	584	23,760	638	27,480	738				
80	5.5	6290	169	13,260	356	22,900	615	27,200	730	27,200	730						
100	6.9	7650	205	16,380	440	28,030	753										
125	8.6	9390	252	20,030	538												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

1. Not available on the Type CS823.

2. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.

SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
5 psig	-1.0 psig	1.0 psig	2.5 to 5.5 psig	GE30343X012 / Yellow
0.34 bar	-69 mbar	69 mbar	0.17 to 0.38 bar	

**Table 27. Types CS820, CS823 and CS824 Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
<b>Body Size: 1-1/2 in. / DN 40</b>																	
10	0.69	1530	41.1	2710	72.8	4370	117	5880	158	6680	179	8470	227	9740	262	12,040	323
15	1.0	1960	52.6	3750	101	6250	168	7870	211	9620	258	11,330	304	12,580	338	15,210	408
20	1.4	2310	62.0	4720	127	7850	211	10,140	272	11,480	308	13,870	372	14,580	391		
25	1.7	2640	70.9	5520	148	9360	251	10,840	291	13,070	351	15,030	404	16,530	444		
30	2.1	2880	77.3	6390	172	10,570	284	12,760	343	14,620	393	16,620	446	16,990	456		
40	2.8	3560	95.6	7870	211	12,500	336	15,170	407	16,890	453	19,270	517				
50	3.4	4240	114	9360	251	14,840	398	16,650	447	18,310	492	21,270	571				
60	4.1	4950	133	11,000	295	16,380	440	17,530	471	19,970	536	22,640	608				
80	5.5	6310	169	13,840	372	19,090	513	20,400	548	22,710	610						
100	6.9	7690	206	16,280	437	21,380	574										
125	8.6	9390	252	19,280	518												
<b>Body Size: 2 in. / DN 50</b>																	
10	0.69	1500	40.3	2840	76.2	4780	128	5970	160	8000	215	9400	252	10,550	283	13,590 <sup>(2)</sup>	365 <sup>(2)</sup>
15	1.0	1970	52.9	3870	104	6960	187	8540	229	11,770	316	12,740	342	15,830	425	19,260 <sup>(2)</sup>	517 <sup>(2)</sup>
20	1.4	2330	62.6	4700	126	8600	231	10,760	289	14,810	398	16,600	446	19,810	532		
25	1.7	2660	71.4	5700	153	10,060	270	13,260	356	17,350	466	19,690	529	21,840	586		
30	2.1	2970	79.7	6500	175	11,660	313	15,530	417	20,540	551	20,950	562	24,770	665		
40	2.8	3670	98.5	7910	212	14,470	389	20,460	549	24,480	657	25,870	695				
50	3.4	4320	116	9340	251	17,690	475	23,180	622	29,880	802	30,750	826				
60	4.1	5010	135	11,120	299	20,100	540	27,820	747	31,780	853	33,840	909				
80	5.5	6340	170	13,740	369	25,800	693	34,910	937	36,270	974						
100	6.9	7710	207	16,900	454	31,450	844										
125	8.6	9410	253	20,580	553												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

1. Not available on the Type CS823.

2. Type CS824 exhibits a 20% reduction in capacity for indicated orifice size. Multiply listed values by a factor of 0.8.

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™




Figure 17. Type CS820IR Relief Curves (Blocked Open per Orifice Size) at 5 psig / 0.34 bar Set Pressure




Figure 18. Type CS820IQ High Capacity Relief Curves (Blocked Open per Orifice Size) at 5 psig / 0.34 bar Set Pressure





SETPOINT	ACCURACY: +/- 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
10 psig	-1 psig	1 psig	5 to 10 psig	GE30344X012 / Green with White Stripe
0.69 bar	-69 mbar	69 mbar	345 to 690 bar	

**Table 28. Types CS850 and CS854 Internal Registration Flow Capacities for 10 psig / 0.69 bar Setpoint at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
15	1.0	1300	34.9	1780	47.9	2460	66.1	2780	74.7	3140	84.2	4040	108	4040	108	6010	161
20	1.4	1960	52.6	2240	60.1	2980	80.0	3640	97.5	4370	117	5230	140	6060	163		
25	1.7	2430	65.2	2860	76.9	4020	108	4780	128	5180	139	6530	175	7210	193		
30	2.1	2910	78.1	3210	86.2	4470	120	5720	153	6540	175	7400	198	8420	226		
40	2.8	3560	95.4	4080	109	6090	163	7150	192	8680	233	9860	264				
50	3.4	4230	113	5020	135	7760	208	9730	261	10,750	288	11,210	300				
60	4.1	4790	129	6360	170	8900	238	10,530	282	12,960	347	13,720	368				
80	5.5	6110	164	7950	213	10,840	290	13,920	373	15,610	418						
100	6.9	7610	204	9730	261	12,780	343										
125	8.6	8960	240	11,890	319												

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
10 psig	-2 psig	2 psig	5 to 10 psig	GE30344X012 / Green with White Stripe
0.69 bar	-1.4 bar	1.4 bar	345 to 690 bar	

**Table 29. Type CS850 Internal Registration Flow Capacities for 10 psig / 0.69 bar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
15	1.0	1820	48.8	3160	84.8	4670	125	6050	162	6650	178	8250	221	9420	252	11,730	314
20	1.4	2190	58.8	3850	103	6450	173	7820	210	9380	251	11,000	295	12,560	336		
25	1.7	2570	69.0	4920	132	8110	217	9780	262	11,240	301	14,080	377	14,750	395		
30	2.1	2950	79.2	5780	155	9090	244	11,710	314	14,110	378	15,450	414	17,370	465		
40	2.8	3620	97.0	7330	197	11,740	315	14,830	398	16,820	451	19,590	525				
50	3.4	4310	116	8910	239	14,510	389	17,600	472	19,840	532	22,180	594				
60	4.1	4940	133	10,410	279	16,430	440	19,720	528	23,450	628	23,920	641				
80	5.5	6260	168	13,140	352	20,040	537	23,940	641	28,110	753						
100	6.9	7660	205	16,210	434	23,050	618										
125	8.6	9290	249	19,320	517.8												

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator



SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
7 in. w.c.	-2 in. w.c.	2 in. w.c.	5.5 to 8.5 in. w.c.	GE30338X012 / Black
17 mbar	-5 mbar	5 mbar	13 to 21 mbar	

### Table 30. Types CS800, CS803 and CS804 External Registration Flow Capacities for 7 In. w.c. / 17 mbar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
0.4	0.03			550	14.8	780	20.9	1090	29.3	1000	26.8	1390	37.3	1640	44.0	1780	47.8
0.51	0.04	360	9.7	630	16.9	930	25.0	1100	29.5	1530	41.1	1530	41.1	1940	52.1	2400	64.4
1	0.07	500	13.4	830	22.3	1290	34.6	1730	46.4	1980	53.2	2320	62.3	2860	76.8	3780	102
2	0.14	720	19.3	1330	35.7	2010	54.0	2550	68.5	3260	87.5	3740	100	4360	117	5930	159
3	0.21	870	23.4	1650	44.3	2500	67.1	3180	85.4	4130	111	4760	128	5250	141	7110	191
5	0.34	1120	30.1	2070	55.6	3410	91.5	4380	118	5620	151	6400	172	7500	201	9370	252
10	0.69	1480	39.7	2990	80.3	5010	135	6480	174	8420	226	9820	264	11,600	311	14,600	392
15	1.0	1810	48.6	3710	99.6	6410	172	8320	223	10,800	290	12,770	343	15,130	406	19,610	526
20	1.4	2170	58.3	4560	122	7720	207	10,750	289	13,660	367	15,080	405	18,520	497		
25	1.7	2520	67.7	5320	143	9030	242	12,220	328	16,340	439	18,630	500	21,950	589		
30	2.1	2770	74.4	5990	161	10,440	280	13,770	370	17,790	478	20,350	546				
40	2.8	3400	91.3	7360	198	12,490	335	16,720	449	20,320	546	25,650	689				
50	3.4	4010	108	8700	234	14,510	390	18,750	503	24,220	650	26,390	709				
60	4.1	4630	124	10,110	271	16,810	451	22,130	594	26,490	711						
80	5.5	5960	160	12,550	337	19,580	526										
100	6.9	7280	195	15,030	404	22,540	605										
125	8.6	8150	219	16,990	456												

■ - Black areas show where indicated droop/boost would be exceeded regardless of capacity.  
 □ - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on Type CS803.

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
14 in. w.c.	-2 in. w.c.	2 in. w.c.	10 to 16 in. w.c.	GE30340X012 / White
35 mbar	-5 mbar	5 mbar	25 to 40 mbar	

### Table 31. Types CS800, CS803 and CS804 External Registration Flow Capacities for 14 in. w.c. / 35 mbar Setpoint

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
1	0.07	430	11.5	520	14.0	1210	32.5	1210	32.5	1290	34.6	1540	41.3	1790	48.1	2510	67.4
2	0.14	630	16.9	990	26.6	1690	45.4	2010	54.0	2440	65.5	2900	77.9	3350	89.9	4500	121
3	0.21	770	20.7	1350	36.2	1870	50.2	2540	68.2	2890	77.6	3730	100	4230	114	5660	152
5	0.34	1030	27.7	1800	48.3	2760	74.1	3280	88.1	4020	108	5320	143	5730	154	7160	192
10	0.69	1380	37.0	2560	68.7	4000	107	5110	137	6320	170	7700	207	8530	229	13,160	353
15	1.0	1700	45.6	3220	86.4	4980	134	6400	172	8180	220	10,270	276	11,690	314	19,100	513
20	1.4	1970	52.9	4040	109	6270	168	8110	218	10,620	285	15,320	411	17,550	471		
25	1.7	2340	62.8	4890	131	7810	210	9570	257	12,530	336	18,870	507	20,710	556		
30	2.1	2710	72.8	5320	143	8280	222	10,890	292	13,070	351	19,710	529				
40	2.8	3300	88.6	6900	185	10,980	295	13,280	357	16,560	444	26,440	710				
50	3.4	3890	104	8290	223	12,990	349	16,060	431	18,020	484	30,650	823				
60	4.1	4490	121	9710	261	15,400	413	18,340	492	21,170	568						
80	5.5	5770	155	12,450	334	18,900	507										
100	6.9	7000	188	15,030	404	21,320	572										
125	8.6	7900	212	16,680	448												

□ - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
 1. Not available on Type CS803.



SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-5.5 in. w.c.	5.5 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
69 mbar	-14 mbar	14 mbar	35 to 75 mbar	

**Table 32. Types CS800, CS803 and CS804 External Registration Flow Capacities for 1 psig / 69 mbar Setpoint**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
2	0.14	680	18.3	1090	29.3	1830	49.1	2540	68.2	2950	79.2	3390	91.0	4140	111	6030	162
3	0.21	870	23.4	1500	40.3	2530	67.9	3360	90.2	4300	115	4870	131	5700	153	7310	196
5	0.34	1170	31.4	2050	55.0	3430	92.1	4690	126	6110	164	7000	188	8210	220	9760	262
10	0.69	1490	40.0	2960	79.5	4840	130	6550	176	8320	223	9480	255	11,380	306	14,700	395
15	1.0	1810	48.6	3790	102	6610	177	8740	235	10,590	284	11,840	318	13,980	375	20,000	537
20	1.4	2130	57.2	4920	132	7750	208	10,220	274	12,360	332	14,930	401	16,240	436		
25	1.7	2580	69.3	5590	150	9070	244	11,790	317	14,230	382	17,970	482	18,370	493		
30	2.1	2900	77.9	6570	176	10,070	270	13,200	354	16,450	442	19,880	534	22,620	607		
40	2.8	3640	97.7	7830	210	12,890	346	15,860	426	19,200	515	20,760	557				
50	3.4	4420	119	9360	251	15,480	416	18,380	493	22,670	609	24,280	652				
60	4.1	5100	137	10,910	293	18,120	486	21,070	566	24,680	663	26,750	718				
80	5.5	6460	173	13,140	353	20,770	558	23,970	644	27,780	746						
100	6.9	7930	213	16,420	441	23,090	620										
125	8.6	8730	234	19,710	529												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on Type CS803.

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.40 psig	0.40 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
138 mbar	-28 mbar	28 mbar	69 to 170 mbar	

**Table 33. Types CS820, CS823 and CS824 External Registration Flow Capacities for 2 psig / 138 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
3	0.21	760	20.4	1220	32.8	1820	48.9	2780	74.6	2780	74.6	4180	112	5360	144	5540	149
5	0.34	1080	29.0	1770	47.5	2880	77.3	3710	99.6	4840	130	5570	150	6950	187	8570	230
10	0.69	1460	39.2	2560	68.7	4400	118	6330	170	7400	197	8750	235	9180	246	12,710	341
15	1.0	1760	47.2	3560	95.6	5540	149	7870	211	9590	257	11,280	303	11,890	319	15,220	409
20	1.4	2090	56.1	4310	116	6680	179	9610	258	11,940	321	13,420	360	14,300	384		
25	1.7	2350	63.1	5100	137	7600	204	10,780	289	13,440	361	14,020	376	15,510	416		
30	2.1	2710	72.8	5760	155	8980	241	12,410	333	15,040	404	15,770	423	17,220	462		
40	2.8	3390	91.0	7290	196	10,560	284	14,810	398	16,840	452	18,260	490				
50	3.4	3970	107	8530	229	12,490	335	16,790	451	18,370	493	19,490	523				
60	4.1	4570	123	9930	267	14,050	377	18,570	499	19,310	518	21,120	567				
80	5.5	5880	158	12,420	333	16,150	434	20,330	546	21,450	576						
100	6.9	7250	195	14,670	394	18,850	506										
125	8.6	8960	241	16,450	442												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on Type CS823.

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator

FISHER™

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
5 psig	-1 psig	1 psig	2.5 to 5.5 psig	GE30343X012 / Yellow
345 mbar	-69 mbar	69 mbar	170 to 380 mbar	

**Table 34. Types CS820, CS823 and CS824 External Registration Flow Capacities for 5 psig / 345 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35 <sup>(1)</sup>	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
10	0.69	1430	38.4	2320	62.3	4370	117	4780	128	5920	159	7360	198	8670	233	10,820	291
15	1.0	1800	48.3	3370	90.5	5370	144	7030	189	8520	229	11,130	299	11,870	319	15,610	419
20	1.4	2120	56.9	4510	121	6640	178	8920	240	11,730	315	13,420	360	15,360	412		
25	1.7	2430	65.2	5340	143	7770	209	11,420	307	14,150	380	15,880	426	18,530	497		
30	2.1	2730	73.3	5960	160	9120	245	13,180	354	15,890	427	17,100	459	20,070	539		
40	2.8	3410	91.5	7210	194	11,410	306	16,620	446	18,800	505	19,890	534				
50	3.4	4040	109	8640	232	13,540	364	17,940	482	21,260	571	24,110	647				
60	4.1	4560	122	10,140	272	15,530	417	21,730	583	24,520	658	26,500	711				
80	5.5	5880	158	12,840	345	20,480	550	25,360	681	29,700	797						
100	6.9	7230	194	15,560	418	23,710	637										
125	8.6	8910	239	20,320	546												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.  
1. Not available on Type CS823.

SETPOINT	ACCURACY		SPRING	
	Droop	Boost	Set Range	Part Number / Color
7 psig	-1.4 psig	1.4 psig	5 to 10 psig	GE30344X012 / Green with White Stripe
483 mbar	-96 mbar	96 mbar	345 to 690 mbar	

**Table 35. Types CS850 and CS854 External Registration Flow Capacities for 7 psig / 483 mbar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
Inlet Pressure		Orifice Size, In. / mm															
		1/4 / 6.4		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22		1 / 25		1-3/8 / 35	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Sizes: 1-1/2 and 2 in. / DN 40 and 50															
10	0.69	1410	37.9	1750	47.0	2030	54.5	3630	97.4	4130	111	4770	128	5390	145	7360	198
15	1.0	1880	50.5	2840	76.2	4040	109	5350	144	6970	187	7280	195	9050	243	12,240	329
20	1.4	2230	59.9	3710	99.6	5200	140	6840	184	8520	229	9550	256	11,390	306		
25	1.7	2590	69.5	3710	99.6	6250	168	8580	230	10,630	285	11,740	315	13,260	356		
30	2.1	2860	76.8	5140	138	7120	191	9970	268	12,780	343	14,020	376	14,890	400		
40	2.8	3540	95.0	6440	173	9050	243	12,630	339	14,690	394	16,690	448				
50	3.4	4290	115	7710	207	11,610	312	14,930	401	18,140	487	21,190	569				
60	4.1	4980	134	8920	240	13,370	359	16,650	447	20,110	540	23,550	632				
80	5.5	6010	161	11,490	309	17,230	463	19,220	516	24,430	656						
100	6.9	7360	198	15,110	406	20,130	540										
125	8.6	9090	244	17,490	470												

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY		SPRING	
	Drop	Boost	Set Range	Part Number / Color
7 in. w.c.	-1 in. w.c.	2 in. w.c.	5.5 to 8.5 in. w.c.	GE30338X012 / Black
17 mbar	-2.5 mbar	5 mbar	13 to 21 mbar	

**Table 36. Types CS805 and CS806 Internal Registration Flow Capacities for 7 In. w.c. / 17 mbar Setpoint**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40									
0.51	0.04					730	19.6	850	22.8	910	24.4
1	0.07	580	15.6	800	21.5	880	23.6	1050	28.2	1060	28.5
2	0.14	900	24.2	1140	30.6	1520	40.8	1610	43.2	1610	43.2
3	0.21	1080	29.0	1480	39.7	1920	51.5	2250	60.4	2260	60.7
5	0.34	1620	43.5	2120	56.9	2560	68.7	3370	90.5	3470	93.2
10	0.69	2520	67.7	3100	83.2	5200	140	5620	151	5680	153
15	1.0	3150	84.6	5350	144	6400	172	7500	201	7140	192
20	1.4	3910	105	6500	175	7200	193	7500	201	8610	231
25	1.7	4680	126	7600	204	7600	204	7600	204	8610	231
30	2.1	5160	139	7700	207	7700	207	7700	207	9550	256
40	2.8	6140	165	7800	209	7900	212	7900	212	9550	256
50	3.4	7120	191	7900	212	8000	215	8000	215	9550	256
60	4.1	7500	201	8000	215	8000	215	8000	215		
80	5.5	8500	228	8500	228						
100	6.9	8500	228	8500	228						
125	8.6	8500	228								

     - Black areas show where indicated droop/boost would be exceeded regardless of capacity.  
 - Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Drop	Boost	Set Range	Part Number / Color
1 psig	-2.8 in. w.c.	2.8 in. w.c.	14 to 30 in. w.c.	GE30341X012 / Dark Green
0.07 bar	-7 mbar	7 mbar	35 to 75 mbar	

**Table 37. Types CS805 and CS806 Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint at 10% Accuracy**

CAPACITIES IN SCFH / Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40									
2	0.14	840	22.6	1200	32.2	1310	35.2	1820	48.9	1610	43.2
3	0.21	1100	29.5	1520	40.8	1760	47.2	2430	65.2	2700	72.5
5	0.34	1680	45.1	2280	61.2	2820	75.7	3490	93.7	3710	99.6
10	0.69	2410	64.7	3430	92.1	4480	120	5630	151	6480	174
15	1.0	3080	82.7	4770	128	6910	186	7850	211	8520	229
20	1.4	4080	110	5970	160	8540	229	9100	244	9670	260
25	1.7	4690	126	7400	199	9030	242	9700	260	10,190	274
30	2.1	5790	155	8680	233	10,380	279	10,240	275	10,790	290
40	2.8	7310	196	10,290	276	11,660	313	11,470	308	11,930	320
50	3.4	9270	249	11,010	296	12,140	326	11,740	315	12,550	337
60	4.1	10,320	277	11,200	301	12,490	335	12,220	328		
80	5.5	11,810	317	11,610	312						
100	6.9	12,180	327	12,030	323						
125	8.6	11,730	315								

- Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator



SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
1 psig	-5.5 In. w.c.	5.5 In. w.c.	14 to 30 In. w.c.	GE30341X012 / Dark Green
0.07 bar	-14 mbar	14 mbar	35 to 75 mbar	

**Table 38. Types CS805 and CS806 Internal Registration Flow Capacities for 1 psig / 0.07 bar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40									
2	0.14	1120	30.1	1710	45.9	2130	57.2	2600	69.8	2910	78.1
3	0.21	1620	43.5	2320	62.3	2510	67.4	3590	96.4	3750	101
5	0.34	2250	60.4	3090	83.0	3650	98.0	5190	139	5230	140
10	0.69	3150	84.6	4610	124	6320	170	7720	207	8330	224
15	1.0	3990	107	6310	169	8480	228	9390	252	10,000	269
20	1.4	4970	133	7600	204	9950	267	10,710	288	11,480	308
25	1.7	5490	147	8860	238	11,100	298	11,880	319	12,340	331
30	2.1	6590	177	9910	266	12,110	325	12,120	325	13,160	353
40	2.8	7890	212	11,640	313	13,000	349	13,590	365	13,920	374
50	3.4	9350	251	12,680	340	14,120	379	13,940	374	14,440	388
60	4.1	10,860	292	13,000	349	14,540	390	14,080	378		
80	5.5	13,310	357	13,780	370						
100	6.9	13,750	369	14,360	386						
125	8.6	13,750	369								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
2 psig	-0.20 psig	0.20 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-14 mbar	14 mbar	0.07 to 0.17 bar	

**Table 39. Types CS825 and CS826 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40									
3	0.21	740	19.9	1580	42.4	1230	33.0	1620	43.5	1860	49.9
5	0.34	990	26.6	1720	46.2	2020	54.2	2730	73.3	2870	77.0
10	0.69	2040	54.8	2970	79.7	3490	93.7	4820	129	5290	142
15	1.0	2890	77.6	4170	112	5000	134	6510	175	7010	188
20	1.4	3600	96.6	5350	144	6580	177	8620	231	8690	233
25	1.7	4370	117	6430	173	7950	213	9240	248	9530	256
30	2.1	4960	133	7690	206	9030	242	10,240	275	11,060	297
40	2.8	6800	183	9790	263	11,040	296	11,890	319	12,590	338
50	3.4	8140	219	11,460	308	12,760	343	13,290	357	14,450	388
60	4.1	9850	264	12,100	325	13,760	369	14,020	376		
80	5.5	12,110	325	13,830	371						
100	6.9	13,720	368	14,800	397						
125	8.6	13,880	373								
psig	bar	Body Size: 2 in. / DN 50									
3	0.21	810	21.7	1080	29.0	1340	36.0	1560	41.9	1780	47.8
5	0.34	1240	33.3	1760	47.2	2170	58.3	2750	73.8	3170	85.1
10	0.69	2100	56.4	2670	71.7	4130	111	4910	132	6300	169
15	1.0	2900	77.9	4220	113	6230	167	7920	213	9310	250
20	1.4	3640	97.7	5770	155	8400	226	10,470	281	12,460	335
25	1.7	4530	122	7180	193	10,660	286	13,300	357	14,970	402
30	2.1	5190	139	8840	237	12,270	330	15,280	410	17,900	481
40	2.8	7140	192	12,040	323	16,610	446	19,630	527	22,700	609
50	3.4	9020	242	14,530	390	20,410	548	23,830	640	26,840	721
60	4.1	10,720	288	17,070	458	24,980	671	27,450	737		
80	5.5	13,660	367	22,220	597						
100	6.9	16,760	450	27,350	734						
125	8.6	20,350	546								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.



SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Drop	Boost	Set Range	Part Number / Color
2 psig	-0.40 psig	0.40 psig	1 to 2.5 psig	GE30342X012 / Dark Blue
0.14 bar	-28 mbar	28 mbar	0.07 to 0.17 bar	

**Table 40. Types CS825 and CS826 Internal Registration Flow Capacities for 2 psig / 0.14 bar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
psig	bar	Body Size: 1-1/2 in. / DN 40									
3	0.21	1170	31.4	2020	54.2	2150	57.7	2570	69.0	3110	83.5
5	0.34	1770	47.5	2540	68.2	3130	84.0	4100	110	4520	121
10	0.69	3080	82.7	4420	119	5370	144	6800	183	7330	197
15	1.0	3880	104	5600	150	7180	193	8730	234	9850	264
20	1.4	4830	130	6970	187	9130	245	10,390	279	11,410	306
25	1.7	5740	154	8500	228	10,630	285	12,150	326	12,640	339
30	2.1	6180	166	9670	260	11,650	313	13,330	358	14,210	382
40	2.8	7810	210	12,190	327	13,870	372	15,330	412	15,860	426
50	3.4	9250	248	13,800	371	15,660	420	16,330	438	17,440	468
60	4.1	10,570	284	14,780	397	16,310	438	17,480	469		
80	5.5	13,170	354	16,800	451						
100	6.9	15,740	423	18,200	489						
125	8.6	17,430	468								
psig	bar	Body Size: 2 in. / DN 50									
3	0.21	1070	28.7	1470	39.5	2080	55.8	2540	68.2	2710	72.8
5	0.34	1760	47.2	2660	71.4	3420	91.8	4130	111	4660	125
10	0.69	2860	76.8	4260	114	5930	159	7190	193	8360	224
15	1.0	3880	104	5950	160	8200	220	9920	266	11,340	304
20	1.4	4740	127	7360	198	10,200	274	12,310	331	14,410	387
25	1.7	5590	150	8830	237	12,560	337	15,100	405	16,980	456
30	2.1	6310	169	10,150	273	14,290	384	17,140	460	19,320	519
40	2.8	7820	210	12,990	349	18,360	493	21,510	577	23,500	631
50	3.4	9370	252	15,320	411	22,350	600	25,450	683	28,260	759
60	4.1	10,860	292	17,710	475	26,420	709	29,670	797		
80	5.5	13,750	369	22,830	613						
100	6.9	16,800	451	27,610	741						
125	8.6	20,510	551								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

# CS800 Series

## Commercial/Industrial - Pressure Reducing Regulator



SETPOINT	ACCURACY: + / - 10% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
5 psig	-0.50 psig	0.50 psig	2.5 to 5.5 psig	GE30343X012 / Yellow
0.34 bar	-34 mbar	34 mbar	0.17 to 0.38 bar	

**Table 41. Types CS825 and CS826 Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint at 10% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		<b>Body Size: 1-1/2 in. / DN 40</b>									
psig	bar										
10	0.69	1750	47.0	2360	63.4	2860	76.8	3630	97.4	4290	115
15	1.0	2400	64.4	3530	94.8	4370	117	5400	145	5960	160
20	1.4	3110	83.5	4270	115	5660	152	6630	178	7540	202
25	1.7	3640	97.7	5320	143	6910	186	7870	211	8920	240
30	2.1	4350	117	6240	168	7950	213	9530	256	10,490	282
40	2.8	5490	147	7730	208	9760	262	11,740	315	12,770	343
50	3.4	6850	184	9270	249	11,900	320	13,230	355	14,360	386
60	4.1	7970	214	11,280	303	13,470	362	15,070	405		
80	5.5	10,650	286	13,750	369						
100	6.9	12,440	334	15,460	415						
125	8.6	14,500	389								
		<b>Body Size: 2 in. / DN 50</b>									
psig	bar										
10	0.69	1730	46.4	2400	64.4	2840	76.2	3620	97.2	4060	109
15	1.0	2500	67.1	3410	91.5	4300	115	5360	144	6490	174
20	1.4	3230	86.7	4360	117	5610	151	6950	187	8760	235
25	1.7	3810	102	5280	142	6860	184	8960	241	11,030	296
30	2.1	4410	118	6340	170	8430	226	10,780	289	13,080	351
40	2.8	5550	149	8640	232	11,810	317	15,280	410	17,290	464
50	3.4	6980	187	11,120	299	15,070	405	19,630	527	21,680	582
60	4.1	8750	235	13,630	366	18,300	491	23,260	624		
80	5.5	11,970	321	18,590	499						
100	6.9	15,030	404	23,560	633						
125	8.6	19,350	520								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.

SETPOINT	ACCURACY: + / - 20% GAUGE		SPRING	
	Droop	Boost	Set Range	Part Number / Color
5 psig	-1.0 psig	1.0 psig	2.5 to 5.5 psig	GE30343X012 / Yellow
0.34 bar	-69 mbar	69 mbar	0.17 to 0.38 bar	

**Table 42. Types CS825 and CS826 Internal Registration Flow Capacities for 5 psig / 0.34 bar Setpoint at 20% Accuracy**

CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
Inlet Pressure		Orifice Size, In. / mm									
		3/8 / 9.5		1/2 / 13		5/8 / 16		3/4 / 19		7/8 / 22	
		SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
		<b>Body Size: 1-1/2 in. / DN 40</b>									
psig	bar										
10	0.69	2460	66.0	3650	98.0	4680	126	5880	158	6610	177
15	1.0	3460	92.9	5200	140	6520	175	8240	221	9120	245
20	1.4	4370	117	6650	179	8300	223	10,120	272	11,110	298
25	1.7	5220	140	7700	207	10,020	269	12,050	324	13,400	360
30	2.1	6060	163	8980	241	11,440	307	13,520	363	15,180	408
40	2.8	7580	204	11,060	297	14,160	380	16,400	440	17,610	473
50	3.4	9150	246	12,850	345	16,250	436	17,880	480	19,590	526
60	4.1	10,490	282	15,370	413	18,130	487	20,170	542		
80	5.5	13,270	356	18,410	494						
100	6.9	15,310	411	20,820	559						
125	8.6	18,730	503								
		<b>Body Size: 2 in. / DN 50</b>									
psig	bar										
10	0.69	2440	65.5	3650	98.0	4660	125	5740	154	6660	179
15	1.0	3540	95.0	5220	140	6790	182	8260	222	9740	262
20	1.4	4480	120	6650	179	8720	234	10,670	286	12,370	332
25	1.7	5260	141	7950	213	10,580	284	13,090	351	15,060	404
30	2.1	6100	164	9370	252	12,540	337	15,440	415	17,410	467
40	2.8	7650	205	11,860	318	16,150	434	19,860	533	22,580	606
50	3.4	9230	248	14,510	390	19,730	530	24,260	651	27,210	731
60	4.1	10,710	288	16,820	452	23,710	637	28,650	769		
80	5.5	13,670	367	21,930	589						
100	6.9	16,630	446	27,000	725						
125	8.6	20,310	545								

Blank areas indicate where maximum operating inlet pressure for a given orifice size is exceeded.








Figure 19. Spring Case Vent and Body Orientation

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™






Figure 19. Spring Case Vent and Body Orientation (continued)




### TYPE CS800 REGULATOR MAIN VALVE




In. / mm


Figure 20. Dimensions



TYPE CS850 REGULATOR MAIN VALVE



SLAM-SHUT MODULE



TRUE-MONITOR™ MODULE

In. /  
mm

ERSA00347

Figure 20. Dimensions (continued)

BODY SIZE		END CONNECTION STYLE	DIMENSION A			
In.	DN		in.		mm	
1-1/4 to 2	----	NPT or Rp	6.12		155	
2 <sup>(1)</sup>	50 <sup>(1)</sup>	CL125 FF Flange	7.5	10	191	254
2 <sup>(2)</sup>	50 <sup>(2)</sup>	CL125 FF, CL150 FF or PN 10/16 Flange				
2 <sup>(2)</sup>	50 <sup>(2)</sup>	CL125 FF or CL150 FF Flange	10.5		267	
2 <sup>(3)</sup>	50 <sup>(3)</sup>	CL150 RF or PN 16 Flange	10		254	

1. For Cast iron.  
2. For Ductile iron.  
3. For Steel.

# CS800 Series

Commercial/Industrial - Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Type (See Table 1 for Construction Features) (Select One)

#### Stand-Alone Regulator

- |                                  |                                  |
|----------------------------------|----------------------------------|
| <input type="checkbox"/> CS800IN | <input type="checkbox"/> CS820IR |
| <input type="checkbox"/> CS800IR | <input type="checkbox"/> CS820IT |
| <input type="checkbox"/> CS800IT | <input type="checkbox"/> CS820IQ |
| <input type="checkbox"/> CS800IQ | <input type="checkbox"/> CS820IL |
| <input type="checkbox"/> CS800IL | <input type="checkbox"/> CS820EN |
| <input type="checkbox"/> CS800EN | <input type="checkbox"/> CS820ET |
| <input type="checkbox"/> CS800ET | <input type="checkbox"/> CS820EL |
| <input type="checkbox"/> CS800EL | <input type="checkbox"/> CS850IN |
| <input type="checkbox"/> CS820IN | <input type="checkbox"/> CS850EN |

#### With Integral True-Monitor™ Module

- |                                  |                                  |
|----------------------------------|----------------------------------|
| <input type="checkbox"/> CS803IN | <input type="checkbox"/> CS823IN |
| <input type="checkbox"/> CS803IT | <input type="checkbox"/> CS823IT |
| <input type="checkbox"/> CS803IL | <input type="checkbox"/> CS823IL |
| <input type="checkbox"/> CS803EN | <input type="checkbox"/> CS823EN |
| <input type="checkbox"/> CS803ET | <input type="checkbox"/> CS823ET |
| <input type="checkbox"/> CS803EL | <input type="checkbox"/> CS823EL |

#### With Type Secondary Seat™ Protection Without Vent

- |                                  |                                  |
|----------------------------------|----------------------------------|
| <input type="checkbox"/> CS805IN | <input type="checkbox"/> CS825IN |
| <input type="checkbox"/> CS805IR | <input type="checkbox"/> CS825IR |
| <input type="checkbox"/> CS805IT | <input type="checkbox"/> CS825IT |
| <input type="checkbox"/> CS805IQ | <input type="checkbox"/> CS825IQ |

#### With Type Secondary Seat Protection with Vent

- |                                  |                                  |
|----------------------------------|----------------------------------|
| <input type="checkbox"/> CS806IR | <input type="checkbox"/> CS826IR |
| <input type="checkbox"/> CS806IQ | <input type="checkbox"/> CS826IQ |

#### With Slam Shut

- |                                  |                                  |
|----------------------------------|----------------------------------|
| <input type="checkbox"/> CS804IN | <input type="checkbox"/> CS824IT |
| <input type="checkbox"/> CS804IT | <input type="checkbox"/> CS824IL |
| <input type="checkbox"/> CS804IL | <input type="checkbox"/> CS824EN |
| <input type="checkbox"/> CS804EN | <input type="checkbox"/> CS824ET |
| <input type="checkbox"/> CS804ET | <input type="checkbox"/> CS824EL |
| <input type="checkbox"/> CS804EL | <input type="checkbox"/> CS854IN |
| <input type="checkbox"/> CS824IN | <input type="checkbox"/> CS854EN |

### Body Material, Body Size and End Connection (Select One)

#### Gray Cast Iron (Types CS800, CS805, CS806, CS820, CS825, CS826 and CS850)

- 1-1/4 NPT\*\*\*
  - 1-1/2 NPT\*\*\*
  - 2 NPT\*\*\*
  - NPS 2 / DN 50, CL125 FF\*\*\*
- Face-to-face dimension:
- 7.5 in. / 191 mm
  - 10 in. / 254 mm

### Body Material, Body Size and End Connection (Select One) (continued)

#### Gray Cast Iron (Types CS803, CS823, CS804, CS824 and CS854)

- 2 NPT\*\*\*

#### Ductile Iron (Types CS800, CS803, CS820, CS823 and CS850)

- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL125 FF / CL150 FF\*\*\*

Face-to-face dimension:

- 7.5 in. / 191 mm
- 10 in. / 254 mm
- 10.5 in. / 267 mm

- NPS 2 / DN 50, PN 10/16\*\*\*

Face-to-face dimension:

- 7.5 in. / 191 mm
- 10 in. / 254 mm

#### Ductile Iron (Types CS804, CS824 and CS854)

- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL125 FF / CL150 FF\*\*\*

Face-to-face dimension:

- 10 in. / 254 mm
- 10.5 in. / 267 mm

- NPS 2 / DN 50, PN 10/16\*\*\*<sup>(1)</sup>

#### WCC Steel (Types CS800, CS803, CS820, CS823 and CS850)

- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL150 RF\*\*\*<sup>(1)</sup>
- NPS 2 / DN 50, PN 10/16\*\*\*<sup>(1)</sup>

#### WCC Steel (Types CS804, CS824 and CS854)

- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL150 RF\*\*\*<sup>(1)</sup>
- NPS 2 / DN 50, PN 10/16\*\*\*<sup>(1)</sup>

- continued -

1. 10 in. / 254 mm face-to-face dimension

## Ordering Guide (continued)

### Outlet Pressure Range (See Table 4) (Select One)

- 3.5 to 6 in. w.c. / 9 to 15 mbar, Red
- 5.5 to 8.5 in. w.c. / 13 to 21 mbar, Black
- 5.5 to 8.5 in. w.c. / 13 to 21 mbar, Brown
- 8 to 12 in. w.c. / 20 to 30 mbar, Purple
- 10 to 16 in. w.c. / 25 to 40 mbar, White
- 14 to 30 in. w.c. / 35 to 75 mbar, Dark Green
- 1 to 2.5 psig / 69 to 170 mbar, Dark Blue
- 1.5 to 3.5 psig / 100 to 241 mbar, Orange
- 2.5 to 5.5 psig / 170 to 380 mbar, Yellow
- 5 to 10 psig / 345 to 690 mbar, Green with White Stripe

### Orifice Size (Select One)

#### Types CS800, CS804, CS820, CS824, CS850 and CS854

- 1/4 in. / 6.4 mm
- 3/8 in. / 9.5 mm
- 1/2 in. / 13 mm
- 5/8 in. / 16 mm
- 3/4 in. / 19 mm
- 7/8 in. / 22 mm
- 1 in. / 25 mm
- 1-3/8 in. / 34.9 mm

#### Types CS803 and CS823

- 1/4 in. / 6.4 mm
- 3/8 in. / 9.5 mm
- 1/2 in. / 13 mm
- 5/8 in. / 16 mm
- 3/4 in. / 19 mm
- 7/8 in. / 22 mm
- 1 in. / 25 mm

#### Types CS805, CS825, CS855, CS806, CS826 and CS856

- 3/8 in. / 9.5 mm
- 1/2 in. / 13 mm
- 5/8 in. / 16 mm
- 3/4 in. / 19 mm
- 7/8 in. / 22 mm

### Body Orientation (Select One, see Figure 19)

- Position 1 (standard)\*\*\*
- Position 2\*\*\*
- Position 3\*\*\*
- Position 4\*\*\*

### Vent Orientation (Select One, see Figure 19)

- Position C\*\*\*
- Position D (standard)\*\*\*
- Position E\*\*\*
- Position F\*\*\*

### True-Monitor™ Control Pressure Range (See Tables 6 and 7) (Select One)

#### CS803 and C823 Series

- 12 to 21 in. w.c. / 30 to 52 mbar, Blue
- 18 to 30 in. w.c. / 45 to 75 mbar, Green
- 26 to 40 in. w.c. / 65 to 99 mbar, Orange
- 1.4 to 2.9 psig / 97 to 200 mbar, Black
- 2.6 to 3.7 psig / 179 to 255 mbar, Purple
- 3.6 to 6 psig / 248 to 414 mbar, Dark Blue
- 5.1 to 7.5 psig / 352 to 517 mbar, Red

### Slam-Shut Trip Pressure Setting

#### CS804, CS824 and CS854 Series

(Select one if applicable and specify setpoint/s, see Tables 10 and 11)

- Overpressure Protection Only (OPSO)**  
Supply setpoint required \_\_\_\_\_
- Overpressure and Underpressure Protection (OPSO/UPS0)**  
Supply overpressure setpoint required \_\_\_\_\_  
Supply underpressure setpoint required \_\_\_\_\_

### Options (Select all that apply)

- Enhanced Low Inlet Pressure Flow Performance**  
Choose this option for enhanced flow performance for low inlet pressure systems, up to 25 psig / 1.7 bar. This option applies to the 5.5 to 8.5 in. w.c. / 13 to 21 mbar spring range when combined with 2 in. threaded or flanged bodies only.
- Low Relief Start-to-Discharge (STD) Spring**  
This option provides a relief start-to-discharge range of 7 to 14 in. w.c. / 17 to 35 mbar above setpoint for the Type CS800IR or CS800IQ with a spring range of up to 10 to 16 in. w.c. / 25 to 40 mbar.
- Closing Cap and Setpoint Seal Wire**
- Stabilizer Cartridge**

- continued -

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

- Speed of regulator response, in order: • Direct-operated • Two-path pilot-operated • Unloading pilot-operated  
• Control valve Note: Although direct-operated regulators give the fastest response, all types provide quick response.

**Introduction**

The CSB400 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of pressure-reducing applications including commercial and industrial installations. This flexibility is provided by the numerous body sizes and end connections, outlet pressure settings, as well as the option for internal, external or dual pressure registration. In addition to application flexibility, the CSB400 Series offers multiple overpressure protection options to meet your demands on application requirements.

**Available Configurations**

See Table 1

**Body Sizes, Materials, End Connections and Pressure Ratings<sup>(1)</sup>**

See Table 3

**Pressure Registrations**

Internal, External or Dual (Internal and External)

**Operating Pressure Ranges<sup>(1)</sup>**

See Table 4

**Regulator Type**

Differential Strength (DS)

**Operating Temperatures (TS)<sup>(1)(2)</sup>**

**According to PED Standards:**

All Types: -4 to 150°F / -20 to 66°C

**Non-PED with Standard Construction:**

Types CSB400/CSB404 and CSB420/CSB424: -4 to 150°F / -20 to 66°C

Types CSB450/CSB454<sup>(3)</sup>: -20 to -150°F / -30 to 66°C

**Non-PED with Low**

**Temperature Construction:**

Types CSB400F/CSB404F<sup>(3)</sup> and CSB420F/CSB424F<sup>(3)</sup>: -22 to 150°F / -30 to 66°C

**Orifice Size**

11/16 in. / 17.5 mm

**Maximum Inlet Pressure Ratings**

Regulator: See Table 6

Integral Monitor Module: See Table 7

Slam-Shut Module: See Table 8

**Maximum Outlet Pressures<sup>(1)</sup>**

Emergency Casing: 58 psig / 4.0 bar

To Avoid Internal Parts Damage:

All other Types: 5.0 psig / 0.34 bar above outlet pressure setting

Type CSB450: 14.5 psig / 1 bar above outlet pressure setting

Operating: 43.5 psig / 3.0 bar

1. The pressure/temperature limits in this Datasheet or any applicable standard limitation should not be exceeded.  
 2. Standard token relief set values listed in Table 8 are based on -4 to 140°F / -20 to 60°C.  
 3. Product has passed Fisher™ testing for lockup, relief start-to-discharge and reseal down to -40°.

**Accuracy Class**

Up to AC5

**Lockup Class**

Up to SG10

**Spring Case Vent Connection**

1 NPT

**Failure Mode**

Fail Open (FO)

**PED Information**

See Table 5

**Approximate Shipping Weight**

**With Threaded Body:**

Type CSB400: 9 lbs / 4 kg

Type CSB403: 20 lbs / 9 kg

Type CSB404: 11 lbs / 5 kg

**With Flanged Body:**

Add 9 lbs / 4 kg to weights listed

**Additional Technical Data**

Scan or Click the QR code for more information on this product.


[www.Emerson.com](http://www.Emerson.com)



10/15

**Features**

- Integral True Monitor™ Option
- Slam-Shut Option
- Ductile Cast Iron and WCC Steel Bodies Available
- Wide Variety of Body Sizes and End Connections
- No Special Tools for Pressure Adjustment and Orifice Removal



# CSB400 Series

## Commercial/Industrial Pressure Reducing Regulator

FISHER™




Figure 3. Type CSB403IT Internally Registered Primary Regulator with Externally registered Integral Monitor Operational Schematic




Figure 4. Type CSB404ET Externally Registered Regulator and Slam-Shut Operational Schematic

Table 1. Available Configurations

TYPE NUMBER					OPTION
C	S	B	4		
					<b>PRESSURE CONSTRUCTION AND UPSTREAM MONITOR APPLICATION</b>
0					Low Pressure Applications (Outlet Pressure: 7 to 40 in. w.c. / 17 to 100 mbar)
1					Low Pressure, Upstream Monitoring Applications <sup>(1)(3)</sup> (Outlet Pressure: 7 to 40 in. w.c. / 17 to 100 mbar)
2					Medium Pressure Applications (Outlet Pressure: 40 to 208 in. w.c. / 100 to 517 mbar)
3					Medium Pressure, Upstream Monitoring Applications <sup>(1)(3)</sup> (Outlet Pressure: 40 to 208 in. w.c. / 100 to 517 mbar)
5					High Pressure Applications <sup>(2)</sup> (Outlet Pressure: 7 to 43.5 psig / 0.50 to 3.0 bar)
					<b>OVERPRESSURE PROTECTION</b>
0					Without Overpressure Protection Module
0F					Low Temperature Capability, Without Overpressure Protection Module
3					With Integral True-Monitor™ Module <sup>(4)</sup>
3F					Low Temperature Capability, With Integral True-Monitor Module <sup>(4)</sup>
4					With Type VSX4 Slam-shut Module <sup>(5)</sup>
4F					Low Temperature Capability, With Type VSX4 Slam-shut Module <sup>(5)</sup>
					<b>PRESSURE REGISTRATION</b>
D					Dual Registration (Best Solution for Quick Changing Loads)
E					External Registration
I					Internal Registration
					<b>RELIEF</b>
N					No Relief
T					Internal Token Relief
					Example: Type number <b>CSB424DT</b> : CSB400 Series regulator constructed for medium pressure applications, with Type VSX4 slam-shut module, Dual pressure registration and Internal Token relief.
					1. Not available with Integral True-Monitor option.
					2. Not available with Integral True-Monitor or Token Relief option.
					3. Available with External Pressure Registration only.
					4. Reference Instruction Manual D103126X012 for information regarding the Type TM600 Integral True-Monitor module.
					5. Reference Instruction Manual D103127X012 for information regarding the Type VSX4 Slam-shut module.



**Table 2. Construction Material**

CSB400 SERIES MAIN VALVE ACTUATOR							
Body	Body O-ring	Closing Cap	Adjusting Screw	Relief Valve Seat	Diaphragm and Disk	Control Spring	Relief Valve Spring
Ductile Cast Iron and WCC Steel	Nitrile (NBR)	Aluminum	Aluminum	Aluminum	Nitrile (NBR)	302 Stainless steel	302 Stainless steel
TM600 SERIES TRUE MONITOR ACTUATOR							
Diaphragm Case, Spring Case, Diaphragm Plate and Valve Stem		Diaphragm and Disk	Control Spring	Vent Screen	Vent Screen Retainer	Closing Cap	Adjusting Screw
Aluminum		Nitrile (NBR)	302 Stainless steel	18-8 Stainless steel	Stainless steel	Aluminum	Aluminum
TYPE VSX-4 SLAM-SHUT DEVICE							
Diaphragm Case, Spring Case, Diaphragm Plate and Valve Stem			Control Spring	Vent Screen	Vent Screen Retainer	Closing Cap	Adjusting Screw
Aluminum			Music Wire or 302 Stainless steel	18-8 Stainless steel	Zinc-plated steel	Aluminum	Aluminum

**Table 3. Body Sizes, Material, End Connections and Pressure Rating**

BODY MATERIAL	INLET SIZE		OUTLET SIZE		END CONNECTION	FACE-TO-FACE DIMENSION		BODY PRESSURE RATING	
	NPS	DN	NPS	DN		In.	mm	psig	bar
Ductile Iron	1	25	1	25	NPT	4	100	290	20
	1-1/4	32	1-1/4	32		4.5	114		
	1-1/2	40	1-1/2	40		4.5	114		
	2	50	2	50		5	127		
	1	25	1	25	Rp	4	100		
	1	25	1-1/4	32		4.5	114		
	1-1/4	32	1-1/4	32		4.5	114		
	1-1/2	40	1-1/2	40		4.5	114		
	2	50	2	50		5	127		
	2	50	2	50		CL150 FF	10		
				PN 10/16	10	254	232	16	
	1-1/2 <sup>(1)</sup>	40 <sup>(1)</sup>	1-1/2 <sup>(1)</sup>	40 <sup>(1)</sup>	PN 16 Slip-On	7.24	184	232	16
Steel	1	25	2-1/4	57	Rp x GAZ	4.1	105	290	20
	1	25	1	25	NPT	4	100		
	1-1/4	32	1-1/4	32		4.5	114		
	1-1/2	40	1-1/2	40		4.5	114		
	1	25	1	25	Rp	4	100		
	1-1/4	32	1-1/4	32		4.5	114		
	1-1/2	40	1-1/2	40		4.5	114		

1. Uses Rp 1-1/2 x 1-1/2 threaded body with PN 16 slip-on flanges.

**Table 4. CSB400 Series Primary Regulator Outlet Pressure Range**

TYPE	OPERATING PRESSURE RANGES, W <sub>b</sub>		PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	In. w.c.	mbar			In.	mm	In.	mm
CBS400, CSB400F, CSB403, CSB403F, CSB404, CSB404F, CSB410 and CSB414	6.8 to 9.6	17 to 24	GE30191X012	Pink	0.080	2.03	6.00	152
	9.6 to 14	24 to 35	GE43955X012	Orange Stripe	0.086	2.19	4.35	110
	14 to 24.1	35 to 60	GE30201X012	Dark Green	0.127	3.23	4.35	110
	21.7 to 40	54 to 100	GE30202X012	Tan	0.112	2.85	5.00	127
CSB420, CSB420F, CSB423, CSB423F, CSB424, CSB424F, CSB430 and CSB434	1.45 to 2.3 psig	100 to 160	GE35081X012	Purple Stripe	0.152	3.86	4.90	124
	2.0 to 4.4 psig	138 to 300	GE30192X012	Dark Blue	0.168	4.27	4.65	118
	4 to 7.5 psig	276 to 517	GE33121X012	Red	0.194	4.93	4.65	118
CSB450 and CSB454	7.3 to 14.5 psig	0.50 to 1.00 bar	GE30203X012	Light Blue	0.220	5.59	4.00	102
	14.5 to 43.5 psig	1.00 to 3.0 bar	GE30204X012	Light Green	0.265	6.73	3.95	100


**Table 5. PED Information**

TYPE	DESCRIPTION	PED CATEGORY	FLUID GROUP
CSB400, CSB400F, CSB410, CSB420, CSB420F, CSB430 and CSB450	Base regulator	I	Groups 1 and 2 according to PED 2014/68/EU, 1st and 2nd family gas according to EN 437 or other gases (compressed air, nitrogen). The gas must be non-corrosive, clean (filtration on inlet side necessary) and dry.
CSB404, CSB404F, CSB414, CSB424, CSB424F, CSB434 and CSB454	Regulator with Slam-Shut Module	IV	
<b>European EN Reference Standards</b>		<b>EN 334, EN 14382</b>	

# CSB400 Series

Commercial/Industrial Pressure Reducing Regulator

FISHER™



GE27692

Figure 5. CSB400 Series Spring Case Vent and Body Orientation

Table 6. Maximum Inlet Pressure Ratings and Flow Coefficients

TYPE	MAXIMUM ALLOWABLE PRESSURE <sup>(1)</sup> / MAXIMUM EMERGENCY INLET PRESSURE		MAXIMUM OPERATING INLET PRESSURE <sup>(1)</sup>	
	P <sub>s</sub>		P <sub>umax</sub>	
	psig	bar	psig	bar
CSB400, CSB400F, CSB404 and CSB404F	58	4.0	58	4.0
CSB420, CSB420F, CSB424 and CSB424F				
CSB450 and CSB454				
CSB410 and CSB414				
CSB403, CSB403F, CSB423 and CSB423F				
CSB403 and CSB423				

1. For the Integral Strength (IS) version, the maximum value of P<sub>s</sub> and P<sub>umax</sub> should be similar to the PSD used for the Differential Strength (DS) version.

**Table 7. Primary Regulator and Integral Monitor Outlet Pressure Ranges**

TYPE	PRIMARY REGULATOR						INTEGRAL TRUE-MONITOR™								
	Factory Setpoint		Set Pressure Range		Color	Part Number	Factory Token Relief Set <sup>(1)</sup>			Factory Setpoint <sup>(1)</sup>		Spring Range		Color	Part Number
	psig	mbar	psig	mbar			% of Reg. Set	psig	mbar	psig	mbar	psig	mbar		
CSB403 and CB403F	8 in. w.c.	20	6.8 to 9.6 in. w.c.	17 to 24	Pink	GE30191X012	No Token Relief			15 in. w.c.	37	12 to 21 in. w.c.	30 to 52	Blue	GE30189X012
							170%	14 in. w.c.	35						
	12 in. w.c.	30	9.6 to 14 in. w.c.	24 to 35	Orange Stripe	GE43955X012	No Token Relief			21 in. w.c.	52	18 to 30 in. w.c.	45 to 75	Green	GE30196X012
							150%	18 in. w.c.	45						
	20 in. w.c.	50	14 to 24 in. w.c.	35 to 60	Dark Green	GE30201X012	No Token Relief			1	70	26 to 40 in. w.c.	65 to 99	Orange	GE30225X012
							140%	1	70						
	1	69	0.78 to 1.45	54 to 100	Tan	GE30202X012	No Token Relief			1.5	103	1.4 to 2.9	97 to 200	Black	GE30190X012
							130%	1.3	90						
CSB423 and CB423F	2	138	1.45 to 2.3	100 to 160	Purple Stripe	GE35081X012	No Token Relief			2.5	172	1.4 to 2.9	97 to 200	Black	GE30190X012
							130%	2.6	180						
	3	207	2.0 to 4.4	138 to 300	Dark Blue	GE30192X012	No Token Relief			4	276	3.6 to 6	248 to 414	Dark Blue	GE30192X012
							125%	3.8	260						
	5	345	4 to 7.5	276 to 517	Red	GE33121X012	No Token Relief			6	414	5.1 to 7.5	352 to 517	Red	GE33121X012
							125%	6.25	430						

1. Recommended minimum Integral True-Monitor setpoints shown.

**Table 8. Regulator and Slam-Shut OPSO and UPSO Pressure Ranges**

TYPE	REGULATOR								SLAM-SHUT MODULE									
	Set Pressure Range		Standard Setpoints		Token Relief Set <sup>(1)(2)</sup>		Available Token Relief Range Shown as a % of Regulator Setpoint		Overpressure Shutoff (OPSO)				Underpressure Shutoff (UPSO)					
	psig	mbar	psig	mbar	psig	mbar	Min <sup>(2)</sup>	Max	psig	mbar	psig	mbar	Min	Max	psig	mbar	Min	Max
CSB404, CSB404F and CSB414	0.25 to 0.35	17 to 24	0.29	20	0.49	34	170	215	0.12	8	0.62	43	215%	270%	0.15	10	50	56
			0.30	21	0.52	36					0.65	45			0.16	11		
	0.35 to 0.51	24 to 35	0.39	27	0.59	41	150	160	0.12	10	0.74	51	190%	200%	0.20	14	50	60
			0.44	30	0.65	45					0.83	57			0.22	15		
			0.50	35	0.76	53					0.96	67			0.26	18		
	0.51 to 0.87	35 to 60	0.70	50	1.0	70	140	158	0.23	16	1.3	90	180%	200%	0.36	25	50	70
			0.87	60	1.2	84					1.57	108			0.44	30		
	0.78 to 1.5	54 to 100	1.10	75	1.4	98	130	140	0.29	20	1.85	128	170%	190%	0.54	38	50	70
1.5			100	1.9	130	2.47					170	0.73			50			
CSB424, CSB424F and CSB434	1.5 to 2.3	100 to 160	2.2	150	2.8	195	130	140	0.58	40	3.59	248	165%	175%	1.1	75	50	70
			2.3	160	3.0	208					3.83	264			1.2	80		
	2.0 to 4.4	138 to 300	4.4	300	5.4	375	125	140	0.73	50	6.53	450	150%	165%	2.2	150		
CSB454 <sup>(3)</sup>	4.0 to 7.5	276 to 517	7.3	500	9.1	625	125	140	0.87	60	10.2	700	140%	180%	3.6	250	50	70
	7.3 to 14.5	500 to 1000	14.5	1000	----	----	----	----	----	----	19.2	1320	112%	140%	7.3	500		
			17.4	1200	----	----	----	----	----	----	23.2	1600	112%	133%	8.7	600		
			21.6	1500	----	----	----	----	----	----	27.6	1900	112%	127%	10.9	750		
14.5 to 43.5	1000 to 3000	29.0	2000	----	----	----	----	----	----	34.8	2400	112%	120%	14.5	1000			
		43.5	3000	----	----	----	----	----	----	49.3	3400	112%	113%	21.8	1500			

1. Standard factory set shown. Factory set is at the Minimum value of the range indicated. Range indicated is a percentage of Setpoint. Percentage indicated is based on the Set Pressure Range in which that setpoint resides. If non-standard sets are required, adherence must be made to constraints shown in Table 7, including Token Relief Set Range, OPSO and UPSO set range and Minimum Required Difference between Token Relief and OPSO Set.


2. Minimum Token Relief values apply to -4 to 140°F / -20 to 60°C service temperatures. For service below -4°F / -20°C, add 0.12 psig / 8 mbar to the minimum Token Relief value listed.

3. Token Relief is not available for the Type CSB454.

# CSB400 Series

## Commercial/Industrial Pressure Reducing Regulator

FISHER™



GE34270

Figure 6. CSB400 Series Dimensions

Table 9. CSB400 Series Dimensions

BODY SIZE		BODY END CONNECTION STYLE	FACE-TO-FACE DIAMETER (A)		PITOT TUBE (B)	
NPS	DN		In.	mm	In.	mm
1	25	NPT or Rp	4	100	3.8	97
1-1/4	32		4.5	114		
1-1/2	40		4.5	114		
2	50		5	127		
2	50	CL150 FF or PN 10/16	10	254		
1 x 1-1/4	25 x 32	Rp	4.5	114		
1 x 2-1/4	25 x 57	Rp x GAZ	4.1	105	0.8	20
1-1/2	40	PN 16 Slip-On	7.2	184	3.8	97

## Ordering Guide

### Type (See Table 1 for Construction details) (Select One)

#### Stand-alone Regulator

- CSB400IN
- CSB400IT
- CSB400DT
- CSB400DN
- CSB400ET
- CSB400EN
- CSB410EN
- CSB420IN
- CSB420IT
- CSB420DN
- CSB420DT
- CSB420EN
- CSB420ET
- CSB430EN
- CSB450IN
- CSB450DN
- CSB450EN

#### With Integral True-Monitor™ Module

- CSB403IN
- CSB403IT
- CSB403DT
- CSB403DN
- CSB403ET
- CSB403EN
- CSB423IN
- CSB423IT
- CSB423DN
- CSB423DT
- CSB423EN
- CSB423ET

#### With Type VSX4 Slam-Shut Module

- CSB404IN
- CSB404IT
- CSB404DT
- CSB404DN
- CSB404ET
- CSB404EN
- CSB414EN
- CSB424IN
- CSB424IT
- CSB424DN
- CSB424DT
- CSB424EN
- CSB424ET
- CSB434EN
- CSB454IN
- CSB454DN
- CSB454EN

### Body Size, Material and End Connection (Select One)

#### Ductile Cast Iron (Types CSB400, CSB420 and CSB450)

- 1 NPT\*\*\*
- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp1\*\*\*
- Rp 1 x 1-1/4\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL150 FF\*\*\*
- NPS 2 / DN 50, PN 10/16\*\*\*
- RP 1 x G 2-1/4 Gaz\*\*\*
- NPS 1-1/2 / DN 40, PN 16 slip-on flanged body

#### Steel (Types CSB400, CSB420 and CSB450)

- 1 NPT\*\*\*
- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- Rp1\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*

### Outlet Pressure Range (Select One)

- 6.8 to 9.6 in. w.c. / 17 to 24 mbar, Pink\*\*\*
- 9.6 to 14 in. w.c. / 24 to 35 mbar, Orange Stripe\*\*\*
- 14.5 to 24 in. w.c. / 35 to 60 mbar, Dark Green\*\*\*
- 21.7 to 40 in. w.c. / 54 to 100 mbar, Tan\*\*\*
- 1.45 to 2.3 psig / 100 to 160 mbar, Purple Stripe\*\*\*
- 2.0 to 4.4 psig / 138 to 300 mbar, Dark Blue\*\*\*
- 4 to 7.5 psig / 276 to 517 mbar, Red\*\*\*
- 7.3 to 14.5 psig / 0.50 to 1.00 bar, Light Blue\*\*\*
- 14.5 to 43.5 psig / 1.00 to 3.0 bar, Light Green\*\*\*

### Body Orientation (For the Types CSB403 and CSB404, choose the body orientation of the primary regulator only. The Integral Monitor and Slam-Shut spring barrel will be oriented in the same direction as the Primary Regulator spring barrel) (Select One)

- Position 1\*\*\*
- Position 2\*\*\*
- Position 3 (standard)\*\*\*
- Position 4\*\*\*

- continued -

### Ordering Guide (continued)

**Vent Orientation** (For the Types CSB403 and CSB404, choose the vent orientation of the primary regulator only. The Integral Monitor and Slam-Shut vent will be oriented to point in the same direction as the Primary Regulator) (Select One)

- Position C\*\*\*
- Position D\*\*\*
- Position E\*\*\*
- Position F (standard)\*\*\*

**Slam-Shut Trip Pressure Setting**  
(Select One if applicable)

- Overpressure (OPSO) trip only (supply high pressure trip pressure) Indicate trip pressure \_\_\_\_\_
- Over and Underpressure (OPSO / UPSO) trip (supply high and low trip pressure) Indicate trip points \_\_\_\_\_

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

A disk with a cookie cut appearance probably means you had an overpressure situation. Thus, investigate further.

## Introduction

The CSB600 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of pressure reducing applications including commercial and industrial installations. This flexibility is provided by the numerous body sizes and end connections, outlet pressure settings. In addition to application flexibility, the CSB600 Series offers multiple overpressure protection options to meet your application requirements.

## Available Configurations

See Table 1

## Body Sizes, Materials, End Connections and Pressure Ratings<sup>(1)</sup>

See Table 3

## Inlet Pressure Ratings<sup>(1)</sup>

See Tables 4 and 5

## Maximum Outlet Pressure<sup>(1)</sup>

### Emergency Casing:

Type CSB600/CSB620/CSB620F: 58 psig / 4.0 bar

Type CSB650: 72.5 psig / 5.0 bar

### To Avoid Internal Metallic Parts

#### Damage:

Type CSB600/CSB620/CSB620F: 5 psig / 0.34 bar over set pressure

Type CSB650: 21.8 psig / 1.5 bar over set pressure —not to exceed maximum emergency outlet

### Operating Casing:

Types CSB600 and CSB620: 16 psig / 1.1 bar

Type CSB650: 72.5 psig / 5.0 bar

## Flow and IEC Sizing Coefficients

See Table 5

## Outlet Pressure Ranges<sup>(1)</sup>

0.13 to 58.0 psig / 9.0 mbar to 4.0 bar

See Table 6

## Orifice Size

1 in. / 25 mm

## Temperature Capabilities<sup>(1)(2)(3)</sup>

### According to PED Standards:

-4 to 151°F / -20 to 66°C

Non-PED: -22 to 151°F / -30 to 66°C

## Spring Case Vent Connection

1 NPT: Types CSB600 and CSB620

1/2 NPT: Type CSB650

## Spring Case Vent and Body Orientation

See Figure 4

## Type VSX8 Slam-Shut Device

### Maximum Inlet Pressure ( $P_{umax}$ )<sup>(1)</sup>

Differential Strength (DS):

232 psig / 16 bar

Integral Strength (IS): 87 psig / 6.0 bar

## Approximated Weights

### With Threaded Body

Type CSB600/CSB620: 29 lbs / 13 kg

Type CSB650: 31 lbs / 14 kg

Type CSB604/CSB624: 31 lbs / 14 kg

Type CSB654: 33 lbs / 15 kg

### With Flanged Body

Add 11 lbs / 5.2 kg weights listed

## Designed, Tested and Evaluated Consistent With:

ANSI B16, ASME BPVC Section VIII Division I, ASTM B117 (Corrosion Resistance), EN 334 and EN 14382




Figure 1. Typical CSB600 Series Pressure Reducing Regulator

## Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

10/18

## Features

- Ductile Iron and WCC Steel Bodies Available
- Wide Variety of Body Sizes and End Connections
- With Type VSX8 Slam-Shut Option
- No Special Tools for Pressure Adjustment and Orifice Removal

1. The pressure/temperature limits in this Datasheet or any applicable standard limitation should not be exceeded.

2. Standard token relief set values listed in Tables 7a and 7b are based on -20 to 60°C / -4 to 140°F.

3. Product has passed Emerson Process Management Regulator Technologies, Inc. testing for lockup, relief start-to-discharge and reseat down to -40°.

# CSB600 Series

Commercial/Industrial Pressure Reducing Regulators

FISHER™




Figure 2. CSB600 Series External Registration Operational Schematic




Figure 3. Type CSB604ET Externally Registered Regulator and Slam-Shut Operational Schematic



**Table 1. Available Configurations**

TYPE NUMBER					OPTION
C	S	B	6		
					<b>PRESSURE CONSTRUCTION</b>
0					Low Pressure Applications (Outlet Pressure: 3.6 in.w.c. to 1.6 psig / 9.0 to 110 mbar) <sup>(2)</sup>
2					Medium Pressure Applications (Outlet Pressure: 0.9 to 11.3 psig / 61 to 780 mbar) <sup>(2)</sup>
5					High Pressure Applications (Outlet Pressure: 10.2 to 58.0 psig / 0.70 to 4.0 bar) <sup>(2)</sup>
					<b>OVERPRESSURE PROTECTION</b>
0					Without Overpressure Protection Module
0F					Without Overpressure Protection Module (Outlet Pressure: 3.6 in.w.c. to 1.6 psig / 9.0 to 110 mbar and 3.9 to 4.7 psig / 270 to 325 mbar only) <sup>(2)</sup>
4					With Type VSX8 Slam-Shut Module <sup>(1)</sup>
4F					With Type VSX8 Slam-shut Module <sup>(1)</sup> (Outlet Pressure: 3.6 in.w.c. to 1.6 psig / 9.0 to 110 mbar and 3.9 to 4.7 psig / 270 to 325 mbar only) <sup>(2)</sup>
					<b>PRESSURE REGISTRATION</b>
E					External
					<b>RELIEF</b>
N					None
T					Token Internal Relief <sup>(3)</sup>
<p>Example: Type number <b>CSB624ET</b>: CSB600 Series regulator constructed for medium pressure applications, with Type VSX8 slam-shut module, with External pressure registration and with Token relief.</p> <p>1. Reference Instruction Manual D103127X012 for information regarding the Type VSX8 Slam-Shut Module.</p> <p>2. The pressure/temperature limits in this document and any applicable standard or code limitation should not be exceeded.</p> <p>3. Token relief is not available for outlet pressure above 8 psig / 500 mbar.</p>					

**Table 2. Construction Materials**

CSB600 SERIES MAIN VALVE ACTUATOR				
Body	Body O-ring, Diaphragm and Disk	Closing Cap, Adjusting Screw, Casing, Valve Stem, Orifice, Pusher Post and Relief Valve Seat	Control Spring	Relief Valve Spring
Ductile Iron or WCC Steel	Nitrile (NBR)	Aluminum	Music Wire or Stainless steel	Stainless steel
TYPE VSX8 SLAM-SHUT DEVICE				
Casing, Valve Stem and Closing Cap	Diaphragm and Disk	Vent Screen	Vent Screen Retainer	Control Spring
Aluminum	Nitrile (NBR)	Stainless steel	Zinc-plated steel	Steel

**Table 3. CSB600 Series Body Sizes, Material, End Connections and Pressure Ratings**

BODY MATERIAL	BODY SIZE		END CONNECTION	FACE-TO-FACE DIMENSION		BODY PRESSURE RATING	
	NPS	DN		In.	mm	psig	bar
Ductile Iron	1-1/4	32	NPT	6.10	155	250	17.2
	1-1/2	40					
	2	50					
	2	50					
	1-1/4	32	Rp	6.10	155	250	17.2
	1-1/2	40					
	2	50					
	2	50					
	1-1/4	32	CL125 FF / CL150 FF	6.10	155	250	17.2
	1-1/2	40					
	2	50					
	2	50					
	1-1/4	32	PN 10/16	6.10	155	250	17.2
	1-1/2	40					
2	50						
2	50						
WCC Steel	1-1/4	32	NPT	6.10	155	290	20
	1-1/2	40					
	2	50					
	2	50					
	1-1/4	32	Rp	6.10	155	290	20
	1-1/2	40					
	2	50					
	2	50					
	1-1/4	32	PN 16 Slip-On	10	254	290	20
	1-1/2	40					
1-1/4	32	PN 10/16	10	254	232	16	
1-1/2	40						

# CSB600 Series

## Commercial/Industrial Pressure Reducing Regulators

FISHER™

**Table 4. Integral Strength (IS) Pressure Ratings<sup>(1)</sup>**

TYPE	MAXIMUM ALLOWABLE PRESSURE <sup>(2)</sup> / MAXIMUM EMERGENCY INLET PRESSURE		MAXIMUM OPERATING INLET PRESSURE <sup>(2)</sup>	
	P <sub>s</sub>		P <sub>umax</sub>	
	psig	bar	psig	bar
CSB600, CSB604, CSB600F and CSB604F	58	4	58	4
CSB620F and CSB624F				
CSB620 and CSB624				
CSB650 and CSB654	72.5	5	72.5	5

1. Applicable only to applications where the inlet rating cannot exceed the outlet rating.

2. For the Integral Strength (IS version), the maximum value of P<sub>s</sub> and P<sub>umax</sub> should be similar to the PSD used for the Differential Strength (DS) version.

**Table 5. Differential Strength (DS) Pressure Ratings and Flow and Sizing Coefficients**

TYPE	SPECIFIC MAXIMUM ALLOWABLE PRESSURE / MAXIMUM EMERGENCY OUTLET PRESSURE <sup>(1)</sup>		MAXIMUM EMERGENCY INLET PRESSURE <sup>(1)</sup>		MAXIMUM OPERATING INLET PRESSURE <sup>(1)</sup>		ORIFICE SIZE		FLOW COEFFICIENTS WIDE OPEN			IEC SIZING COEFFICIENT		
	P <sub>SD</sub>		P <sub>s</sub>		P <sub>umax</sub>									
	psig	bar	psig	bar	psig	bar	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>
CSB600 and CSB604	58	4	174	12	145	10	1	25	675	17.9	37.8	0.91	0.89	0.73
CSB600F and CSB604F					87	6								
CSB620F and CSB624F					87	6								
CSB620 and CSB624					232	16								
CSB650 and CSB654	72.5	5	290	20	232	16								

1. The pressure/temperature limits in this document and any applicable standard or code limitation should not be exceeded.

**Table 6. CSB600 Series Primary Regulator Outlet Pressure Ranges**

TYPE	OPERATING PRESSURE RANGE, W <sub>d</sub>		PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	psig	mbar			In.	mm	In.	mm
CSB600, CSB604 CSB600F and CSB604F	3.6 to 5.6 in. w.c.	9 to 14	GE30336X012	Silver	0.118	3.00	8.82	224
	5.2 to 9.6 in. w.c.	13 to 24	ERSA01138A0	Red	0.138	3.50	9.25	235
	8.8 to 15.7 in. w.c.	22 to 39	GE30338X012	Black Stripe	0.156	4.00	6.78	172
	12.8 to 20.1 in. w.c.	32 to 50	GE30339X012	Purple	0.171	4.30	7.35	187
	16.9 to 28.1 in. w.c.	42 to 70	GE30340X012	White Stripe	0.182	4.62	7.40	188
CSB620 and CSB624	0.9 to 1.6	61 to 110	ERSA03656A0	Dark Green	0.192	4.88	8.82	224
	0.9 to 1.6	61 to 110	ERSA03656A0	Dark Green	0.192	4.88	8.82	224
	1.5 to 3.2	105 to 220	ERSA03657A0	Blue	0.234	5.94	8.54	217
	3.1 to 5.5	210 to 380	GG06247X012	Black	0.315	8.00	8.11	206
	4.6 to 8.3	320 to 570	ERSA01582A0	Red with White Stripe	0.343	8.71	6.97	177
	7.4 to 11.3	510 to 780	ERSA05055A0	Blue with White Stripe	0.394	10.0	7.13	181
CSB620F and CSB624F	3.9 to 4.7	270 to 325	ERAA11747A0	Black with White Stripe	0.250	6.35	8.94	227
CSB650 and CSB654	10.2 to 17.3	0.7 to 1.19 bar	GE30345X012	Purple Stripe	0.354	9.00	8.86	225
	15.2 to 39.2	1.05 to 2.7 bar	GE30346X012	Brown	0.433	11.0	8.88	226
	33.4 to 47.1	2.3 to 3.25 bar	ERSA01125A0	Grey with Red Stripe	0.496	12.6	8.86	225
	45 to 58.0	3.1 to 4.0 bar	ERSA01126A0	Grey with Orange Stripe	0.539	13.7	8.88	226



**Table 7a. North American Overpressure and Underpressure Shut-off UPSO/OPSO Ranges**

REGULATOR				SLAM SHUT DEVICE										
Type	Typical Setpoint	Spring Range	Type (Maximum Operating Inlet)	Token Relief Set	Relief Range Shown as a % of Regulator Setpoint		Required Difference Between Token Relief and OPSO	USPO	OPSO	Factory Set				
					Set Range	Shut-off (OPSO) Set Range Over UPSO Setpoint		USPO	Adjusted OPSO Range	OPSO				
	psig	psig		psig	min	max	psig	psig	psig	psig	psig	psig		
CSB604F	7 in. w.c.	5.2 to 9.6 in. w.c.	VSX8L (125 psi)	12 in. w.c.	170	215	3.2 in. w.c.	3 to 12 in. w.c.	16 to 29 in. w.c.	3 in. w.c.	19 in. w.c. to 1.2 psig	22 in. w.c.		
	11 in. w.c.	8.8 to 15.7 in. w.c.		17 in. w.c.	150	160	4 in. w.c.			6 in. w.c.			22 in. w.c. to 1.3 psig	25 in. w.c.
	14 in. w.c.	12.8 to 20.0 in. w.c.		21 in. w.c.	150	160	4 in. w.c.	4 in. w.c. to 1.1 psig	20 in. w.c. to 1.8 psig	9 in. w.c.	1 to 2.1 psig	1.1		
	1	24.0 in. w.c. to 1.6 psig		1.4	140	150	6.4 in. w.c.	10 in. w.c. to 2.3 psig	1.2 to 3.2	14 in. w.c.	1.7 to 3.7	2		
CSB624F	2	1.5 to 3.2		VSX8L (232 psi)	2.6	130	140	0.6	1.5 to 7.3	2.6 to 5.6	1	2.2 to 4.2	3.5	
	3				3.8	125	140	0.6			2	4.6 to 7.6	5	
	5	3.1 to 5.5			6.2	125	140	0.7	1.5 to 7.3	3.5 to 8.2	3	5.6 to 8.6	7	
	10	7.4 to 11.3			1.5 to 7.3	3.5 to 8.2	5	8.5 to 13.2	12					
CSB604	7 in. w.c.	5.2 to 9.6 in. w.c.			VSX8L (232 psi)	12 in. w.c.	170	215	3.2 in. w.c.	3 to 12 in. w.c.	18 to 30 in. w.c.	3 in. w.c.	21 in. w.c. to 1.2 psig	22 in. w.c.
	11 in. w.c.	8.8 to 15.7 in. w.c.				17 in. w.c.	150	160	4 in. w.c.			6 in. w.c.		
	14 in. w.c.	12.8 to 20.0 in. w.c.				21 in. w.c.	150	160	4 in. w.c.	4 in. w.c. to 1.1 psig	25 in. w.c. to 1.9 psig	9 in. w.c.	1.2 to 2.2	1.1
	1	24.0 in. w.c. to 1.6 psig				1.4	140	150	6.4 in. w.c.	10 in. w.c. to 2.3 psig	1.2 to 3.2	14 in. w.c.	1.7 to 3.7	2
CSB624	2	1.5 to 3.2	VSX8H (232 psi)			2.6	130	140	0.6	1.5 to 7.3	2.6 to 5.6	1	2.2 to 4.2	3.5
	3					3.8	125	140	0.6			2	4.6 to 7.6	5
	5	3.1 to 5.5				6.2	125	140	0.7	1.5 to 7.3	3.5 to 8.2	3	5.6 to 8.6	7
	10	7.4 to 11.3				1.5 to 7.3	3.5 to 8.2	5	8.5 to 13.2	12				
CSB654	15	10.2 to 17.3		VSX8H (232 psi)		1.5 to 10.9	6.7 to 13.5	7	13.7 to 20.5	19				
	20	15.2 to 39.2				15.2 to 22.8	10	25.2 to 32.8	25					
	30					18.1 to 33.4	15	33.1 to 48.4	35					
	40	33.4 to 55.1				20	38.1 to 53.4	45						

- Grey areas indicate that token relief is not available above 8 psig setpoint.

**Table 7b. European Overpressure and Underpressure Shut-off UPSO/OPSO Ranges**

REGULATOR				SLAM SHUT DEVICE								
Type	Typical Setpoint	Spring Range	Type (Maximum Operating Inlet)	Token Relief Set	Relief Range Shown as a % of Regulator Setpoint		Required Difference Between Token Relief and OPSO	USPO	OPSO	Factory Set		
					Set Range	Shut-off (OPSO) Set Range Over UPSO Setpoint		USPO	Adjusted OPSO Range	OPSO		
	mbar	mbar		mbar	min	max	mbar	mbar	mbar	mbar	mbar	mbar
CSB604F	15	13 to 24	VSX8L (8.6 bar)	26	170	215	6	7 to 11	30 to 44	8	38 to 52	40
	20	13 to 24		34	170	215	6	7 to 11	30 to 44	10	40 to 54	40
	21	13 to 24		36	170	215	4	7 to 11	30 to 44	10	40 to 54	40
	27	22 to 39		41	150	160	5	7 to 15	32 to 44	14	46 to 58	46
	30	22 to 39		45	150	160	10	7 to 30	40 to 72	15	55 to 87	60
	35	22 to 39		53	150	160	10	7 to 30	40 to 72	18	58 to 90	70
	50	42 to 70		70	140	158	16	10 to 75	48 to 74	25	73 to 99	90
	60			84	140	158	16	10 to 75	48 to 74	30	78 to 104	100
	75	61 to 110		98	130	140	20	25 to 160	83 to 221	38	121 to 259	130
	CSB604	15		13 to 24	VSX8L (16 bar)	26	170	215	6	7 to 30	40 to 55	8
20		13 to 24	34	170		215	6	7 to 30	40 to 55	10	50 to 65	55
21		13 to 24	36	170		215	4	7 to 30	40 to 55	10	50 to 65	55
27		22 to 39	41	150		160	5	7 to 30	40 to 55	14	54 to 69	55
30			45	150		160	10	7 to 30	45 to 76	15	60 to 91	60
35		42 to 70	53	150		160	10	7 to 30	45 to 76	18	63 to 94	70
50			70	140		158	16	10 to 75	50 to 80	25	75 to 105	90
60		61 to 110	84	140		158	16	10 to 75	50 to 80	30	80 to 110	100
75	98		130	140		20	25 to 160	83 to 221	38	121 to 259	130	
100	105 to 220	130	130	140		20	25 to 160	83 to 221	50	133 to 271	170	
120		156	130	140	40	25 to 160	83 to 221	60	143 to 281	205		
150		210 to 380	195	130	140	40	25 to 160	83 to 221	75	158 to 296	250	
160			208	130	140	40	25 to 160	83 to 221	80	163 to 301	265	
200		320 to 570	250	125	140	50	100 to 500	114 to 261	100	214 to 361	330	
300			375	125	140	50	100 to 500	179 to 386	150	329 to 536	450	
500		510 to 780	625	125	140	60	100 to 500	241 to 565	250	491 to 815	700	
600			100 to 500	241 to 565	300	541 to 865	840					
750		100 to 750	460 to 932	375	835 to 1120 <sup>(1)</sup>	1050						
CSB624F		300	270 to 325	VSX8L (8.6 bar)	100 to 500	179 to 386	200	379 to 586	400			
CSB654 GrDF	1 bar	0.7 to 1.19 bar	VSX8L (16 bar)	100 to 500	460 to 932	750	1210 to 1682	1210				
CSB654	1 bar	0.7 to 1.19 bar	VSX8H (16 bar)	100 to 500	460 to 932	500	960 to 1432	1320				
	1.2 bar			1050 to 1570	600	1650 to 2170	1650					
	1.5 bar	1250 to 2300			750	1800 to 2320	1900					
	2 bar			1000	2250 to 3300	2400						
	3 bar	2.3 to 3.25 bar		1500	2750 to 3800	3400						
4 bar	3.1 to 4 bar	500 to 2800	2100 to 3750	2000	4100 to 5000 <sup>(1)</sup>	4400						


- Grey areas indicate that token relief is not available above 500 mbar setpoint.  
 1. Max OPSO setpoint truncated to reflect maximum outlet pressure for spring range.

**Example:** If a non-standard setpoint is needed, see the following example for the proper use of Tables 7a and 7b. In this example, the non-standard regulator setpoint is 2.0 psig / 140 mbar. The minimum factory token relief set pressure is 130% of the non-standard setpoint. The resulting token relief set pressure is 2.6 psig / 183 mbar. The minimum factory OPSO and USPO set pressures are 165% and 50% of the non-standard setpoint, respectively. The resulting minimum settings are: OPSO = 3.4 psig / 231 mbar and USPO = 1.0 psig / 70 mbar.


# CSB600 Series

Commercial/Industrial Pressure Reducing Regulators

FISHER™




TYPE CSB600/620



TYPE CSB650

Figure 4. Types CSB600 and CSB604 Spring Case Vent and Body Orientation



IN. / mm

1. Maximum spring removal clearance for the primary regulator is 6.2 in. / 158 mm.
2. Maximum spring removal clearance for the slam shut is 3.1 in. / 80 mm.

Figure 5. CSB600 Series Dimensions

BODY SIZE		BODY END CONNECTION STYLE	FACE-TO-FACE DIAMETER (A)	
NPS	DN		In.	mm
1-1/4	32	NPT or Rp	6.10	155
1-1/2	40			
2	50			
2	50	CL125 FF / CL150 FF or PN 10/16	7.52	191
		CL125 FF / CL150 FF	10	254
			10.5	267
1-1/4	32	PN 16 Slip-On	7.87	200
1-1/2	40		8.74	222
2	50	CL150 RF	10	254

# CSB600 Series

Commercial/Industrial Pressure Reducing Regulators



## Ordering Guide

### Type (See Table 1, Select One)

#### Stand-Alone Regulator

- CSB600EN
- CSB600ET
- CSB600FEN
- CSB600FET
- CSB620FEN
- CSB620EN
- CSB620ET
- CSB650EN

#### With Type VSX8 Slam-shut Module

- CSB604ET
- CSB604EN
- CSB604FEN
- CSB604FET
- CSB624FEN
- CSB624EN
- CSB624ET
- CSB654EN

### Body Size and End Connection Style (Select One)

#### Ductile Iron

- 1-1/4 NPT
- 1-1/2 NPT
- 2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL150 FF\*\*\*
- NPS 2 / DN 50, CL125 FF\*\*\*
- NPS 2 / DN 50, PN 10/16\*\*\*
- NPS 1-1/4 / DN 32, PN 16 slip-on flanged body
- NPS 1-1/2 / DN 40, PN 16 slip-on flanged body

#### WCC Steel

- 1-1/4 NPT\*\*\*
- 1-1/2 NPT\*\*\*
- 2 NPT\*\*\*
- Rp 1-1/4\*\*\*
- Rp 1-1/2\*\*\*
- Rp 2\*\*\*
- NPS 2 / DN 50, CL150 RF
- NPS 2 / DN 50, PN 10/16

### Outlet Pressure Range (Select One)

#### Type CSB600/CSB604/CSB600F/CSB604F

- 3.6 to 5.6 in.w.c. / 9 to 14 mbar, Silver\*\*\*
- 5.2 to 9.6 in.w.c. / 13 to 24 mbar, Red\*\*\*
- 8.8 to 15.7 in.w.c. / 22 to 39 mbar, Black Stripe\*\*\*
- 12.8 to 20.1 in.w.c. / 32 to 50 mbar, Purple\*\*\*
- 16.9 to 28.1 in.w.c. / 42 to 70 mbar, White Stripe\*\*\*
- 0.9 to 1.6 psig / 61 to 110 mbar, Dark Green\*\*\*

#### Type CSB620/CSB624

- 0.9 to 1.6 psig / 61 to 110 mbar, Dark Green\*\*\*
- 1.5 to 3.2 psig / 105 to 220 mbar, Blue\*\*\*
- 3.1 to 5.5 psig / 210 to 380 mbar, Black\*\*\*
- 4.6 to 8.3 psig / 320 to 570 mbar, Red with White Stripe\*\*\*
- 7.4 to 11.3 psig / 510 to 780 mbar, Blue with White Stripe\*\*\*

#### Type CSB620F/CSB624F

- 3.9 to 4.7 psig / 270 to 325 mbar, Black and White Stripe\*\*\*

#### Type CSB650/CSB654

- 10.2 to 17.3 psig / 0.7 to 1.19 bar, Purple Stripe\*\*\*
- 15.2 to 39.2 psig / 1.05 to 2.7 bar, Brown\*\*\*
- 33.4 to 47.1 psig / 2.3 to 3.25 bar, Grey with Red Stripe\*\*\*
- 45 to 58 psig / 3.1 to 4.0 bar, Grey with Orange Stripe\*\*\*

### Body Orientation<sup>(1)</sup> (See Figure 4, Select One)

- Position 1\*\*\*
- Position 2\*\*\*
- Position 3 (standard)\*\*\*
- Position 4\*\*\*

### Vent Orientation<sup>(2)</sup> (See Figure 4, Select One)

- Position C\*\*\*
- Position D\*\*\*
- Position E\*\*\*
- Position F (standard)\*\*\*

### Slam-Shut Trip Pressure Setting

(Select One if applicable)

- Overpressure (OPSO) trip only  
Indicate Overpressure Trip Point \_\_\_\_\_
- Over and Underpressure (OPSO/UPSO) trip  
Indicate Overpressure Trip Point \_\_\_\_\_  
Indicate Underpressure Trip Point \_\_\_\_\_

1. For the Type CSB604, choose the body orientation of the primary regulator only. The Slam-Shut spring barrel will be oriented in the same direction as the primary regulator spring barrel.  
2. For the Type CSB604, choose the vent orientation of the primary regulator only. The Slam-Shut vent will be oriented to point in the same direction as the primary regulator.



## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

If two or more available springs have published pressure ranges that include the desired pressure setting, use the spring with the lower range for better accuracy.

# CSB700 Series

Commercial / Industrial – Pressure Reducing Regulator

FISHER™

## Introduction

The CSB700 Series direct-operated, spring-loaded regulators have been engineered to fit a multitude of pressure reducing applications including commercial and industrial installations. This flexibility is provided by the numerous body sizes and end connections and outlet pressure settings. In addition to application flexibility, CSB700 Series offers multiple overpressure protection options to meet your application requirements.

## Available Configurations

See Table 1

## Body Sizes, Materials, End Connections and Pressure Ratings<sup>(1)</sup>

See Table 2

## Inlet Pressure Ratings<sup>(1)</sup>

See Tables 3 and 4

## Maximum Outlet Pressure<sup>(1)</sup>

### Emergency Casing:

Type CSB700/CSB700F/  
CSB720/CSB720F: 58 psig / 4.0 bar

Type CSB750: 72.5 psig / 5.0 bar

### To Avoid Internal Metallic Parts Damage:

Type CSB700/CSB700F/CSB720/CSB720F:  
5 psig / 0.34 bar over set pressure

Type CSB750:  
21.8 psig / 1.5 bar over set pressure — not to exceed maximum emergency outlet

### Operating Casing:

Type CSB700/CSB720: 16 psig / 1.1 bar

Type CSB750: 72.5 psig / 5.0 bar

## Flow and IEC Sizing Coefficients

See Table 4

## Outlet Pressure Ranges<sup>(1)</sup>

0.13 to 58.0 psig / 9.0 mbar to 4.0 bar

See Table 5

## Orifice Size

1-3/8 in. / 35 mm

## Temperature Capabilities<sup>(1)(2)(3)</sup>

### According to PED Standards:

-4 to 151°F / -20 to 66°C

### Non-PED:

-22 to 151°F / -30 to 66°C

## Spring Case Vent Connection

1 NPT: Types CSB700 and CSB720

1/2 NPT: Type CSB750

## Spring Case Vent and Body Orientation

See Figure 4

## Type VSX8 Slam-Shut Device Maximum Inlet Pressure ( $P_{umax}$ )<sup>(1)</sup>

### Differential Strength (DS):

232 psig / 16 bar

### Integral Strength (IS):

87 psig / 6.0 bar

## Approximate Weights with Threaded body

Type CSB700/CSB720: 29 lbs / 13 kg

Type CSB750: 31 lbs / 14 kg

Type CSB704/CSB724: 31 lbs / 14 kg

Type CSB754: 33 lbs / 15 kg

## with Flanged body

Add 11 lbs / 5.2 kg to weights listed

## Designed, Tested and Evaluated Consistent With:

ANSI B16, ASME BPVC Section VIII  
Division I, ASTM B117 (Corrosion  
Resistance), EN334 and EN 14382




Figure 1. Type CSB704 with  
Type VSX8 Slam-Shut

## Additional Technical Data

Scan or Click the  
QR code for more  
information on  
this product.



[www.Emerson.com](http://www.Emerson.com)

10/18

## Features


- Ductile iron and WCC Steel Bodies Available
- Wide Variety of Body Sizes and End Connections
- With Type VSX8 Slam-Shut Option
- No Special Tools for Pressure Adjustment and Orifice Removal

1. The pressure/temperature limits in this Datasheet or any applicable standard limitation should not be exceeded.

2. Standard token relief set values listed in Tables 6a and 6b are based on -4 to 140°F / -20 to 60°C.

3. Product has passed Emerson Process Management Regulator Technologies, Inc. testing for lockup, relief start-to-discharge and reseal down to -40°.






ERSA01618\_02

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

Figure 2. CSB700 Series with External Registration Operational Schematic



ERSA01618\_06

- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

Figure 3. Type CSB704ET, Externally Registered Regulator and Slam-Shut Operational Schematic

# CSB700 Series

## Commercial / Industrial – Pressure Reducing Regulator

FISHER™

**Table 1. Available Configurations**

TYPE NUMBER					OPTION
C	S	B	7		
					<b>PRESSURE CONSTRUCTION</b>
	0				Low Pressure Applications (Outlet Pressure: 3.6 in. w.c. to 1.6 psig / 9.0 to 110 mbar) <sup>(2)</sup>
	2				Medium Pressure Applications (Outlet Pressure: 0.9 to 11.3 psig / 61 to 780 mbar) <sup>(2)</sup>
	5				High Pressure Applications (Outlet Pressure: 10.2 to 58.0 psig / 0.70 to 4.0 bar) <sup>(2)</sup>
					<b>OVERPRESSURE PROTECTION</b>
	0				Without Overpressure Protection Module
	0F				Without Overpressure Protection Module (Outlet Pressure: 3.6 in. w.c. to 1.6 psig / 9.0 to 110 mbar and 3.9 to 4.7 psig / 270 to 325 mbar only) <sup>(2)</sup>
	4				With Type VSX8 Slam-shut Module <sup>(1)</sup>
	4F				With Type VSX8 Slam-shut Module <sup>(1)</sup> (Outlet Pressure: 3.6 in. w.c. to 1.6 psig / 9.0 to 110 mbar and 3.9 to 4.7 psig / 270 to 325 mbar only) <sup>(2)</sup>
					<b>PRESSURE REGISTRATION</b>
				E	External
					<b>RELIEF</b>
				N	None
				T	Token Internal Relief <sup>(3)</sup>
Example: Type number CSB724ET: Type CSB700 regulator constructed for medium pressure applications, with Type VSX8 Slam-shut Module, with External pressure registration and with Token relief.					
1. Reference Instruction Manual D103127X012 for information regarding the Type VSX8 Slam-shut Module. 2. The pressure/temperature limits in this Bulletin and any applicable standard or code limitation should not be exceeded. 3. Token relief not available for outlet pressure above 8 psig / 500 mbar.					

**Table 2. Body Sizes, Material, End Connections and Pressure Ratings**

BODY MATERIAL	BODY SIZE		END CONNECTION	FACE-TO-FACE DIMENSION		BODY PRESSURE RATING	
	NPS	DN		In.	mm	psig	bar
Ductile iron	1-1/2	40	NPT	6.1	155	250	17.2
	2	50					
	1-1/2	40	Rp	7.52	191		
	2	50					
	2	50	CL125 FF/CL150 FF	10	254		
	2	50					
	2	50					
	2	50	PN 10/16	7.52	191	232	16
	2	50					
	2	50					
2	50	PN 16 Slip-On	8.74	222			
WCC Steel	1-1/2	40	NPT	6.1	155	290	20
	2	50					
	1-1/2	40	Rp	10	254		
	2	50					
	2	50	CL150 RF	7.5	191	232	16
	2	50	PN 10/16				
2	50	PN 10/16					



**Table 3. Integral Strength (IS) Pressure Ratings<sup>(1)</sup>**

TYPE	MAXIMUM ALLOWABLE PRESSURE / MAXIMUM EMERGENCY INLET PRESSURE		MAXIMUM OPERATING INLET PRESSURE <sup>(2)</sup>	
	P <sub>s</sub>		P <sub>umax</sub>	
	psig	bar	psig	bar
CSB700 and CSB704	58	4	58	4
CSB700F and CSB704F				
CSB720 and CSB724				
CSB720F and CSB724F				
CSB750 and CSB754	72.5	5	72.5	5

1. Applicable only to applications where the inlet rating cannot exceed the outlet rating.  
 2. For the Integral Strength (IS version), the maximum value of P<sub>s</sub> and P<sub>umax</sub> should be similar to the PSD used for the Differential Strength (DS) version.

**Table 4. Differential Strength (DS) Pressure Ratings and Flow and Sizing Coefficients**

TYPE	SPECIFIC MAXIMUM ALLOWABLE PRESSURE / MAXIMUM EMERGENCY OUTLET PRESSURE <sup>(1)</sup>		MAXIMUM ALLOWABLE PRESSURE / MAXIMUM EMERGENCY INLET PRESSURE <sup>(1)</sup>		MAXIMUM OPERATING INLET PRESSURE <sup>(1)</sup>		ORIFICE SIZE		WIDE-OPEN FLOW COEFFICIENT			IEC SIZING COEFFICIENT		
	P <sub>sd</sub>		P <sub>s</sub>		P <sub>umax</sub>									
	psig	bar	psig	bar	psig	bar	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>
CSB700 and CSB704	58	4	174	12	145	10	1-3/8	35	1080	27.7	39	0.96	0.89	0.66
CSB700F and CSB704F			174	12	87	6								
CSB720F and CSB724F			174	12	87	6								
CSB720 and CSB724			290	20	232	16								
CSB750 and CSB754			72.5	5	290	20								

1. The pressure/temperature limits in this document and any applicable standard or code limitation should not be exceeded.

**Table 5. CSB700 Series Primary Regulator Outlet Pressure Ranges**

TYPE	OPERATING PRESSURE RANGES, W <sub>d</sub>		PART NUMBER	SPRING COLOR	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
	psig	mbar			In.	mm	In.	mm
CSB700, CSB704, CSB700F and CSB704F	3.6 to 5.6 in. w.c.	9 to 14	GE30336X012	Silver	0.118	3.00	8.82	224
	5.2 to 9.6 in. w.c.	13 to 24	ERSA01138A0	Red	0.138	3.50	10.4	264
	8.8 to 15.7 in. w.c.	22 to 39	GE30338X012	Black Stripe	0.170	4.32	6.78	172
	12.8 to 20.1 in. w.c.	32 to 50	GE30339X012	Purple	0.171	4.34	7.35	187
	16.9 to 28.1 in. w.c.	42 to 70	GE30340X012	White Stripe	0.182	4.62	7.40	188
CSB720 and CSB724	0.9 to 1.6	61 to 110	ERSA03656A0	Dark Green	0.192	4.88	8.82	224
	0.9 to 1.6	61 to 110	ERSA03656A0	Dark Green	0.192	4.88	8.82	224
	1.5 to 3.2	105 to 220	ERSA03657A0	Blue	0.234	5.94	8.53	217
	3.1 to 5.5	210 to 380	GG06247X012	Black	0.315	8.00	8.13	206
	4.6 to 8.3	320 to 570	ERSA01582A0	Red with White Stripe	0.343	8.71	6.97	177
CSB720F and CSB724F	7.4 to 11.3	510 to 780	ERSA05055A0	Blue with White Stripe	0.394	10	7.13	181
	3.9 to 4.7	270 to 325	ERAA11747A0	Black with White Stripe	0.256	6.5	9.25	235
CSB750 and CSB754	10.2 to 17.3	0.7 to 1.19 bar	GE30345X012	Purple Stripe	0.354	9.00	8.87	225
	15.2 to 39.2	1.05 to 2.7 bar	GE30346X012	Brown	0.433	11.0	8.88	226
	33.4 to 47.1	2.3 to 3.25 bar	ERSA01125A0	Grey with Red Stripe	0.496	12.6	8.87	225
	45 to 58	3.1 to 4 bar	ERSA01126A0	Grey with Orange Stripe	0.539	13.7	8.89	226

# CSB700 Series

Commercial / Industrial – Pressure Reducing Regulator



**Table 6a. North American Overpressure and Underpressure Shut-off UPSO/OPSO Ranges**

REGULATOR			SLAM SHUT DEVICE										
Type	Typical Setpoint	Spring Range	Type (Maximum Operating Inlet)	Token Relief Set	Relief Range Shown as a % of Regulator Setpoint		Required Difference Between Token Relief and OPSO	UPSO	OPSO	Factory Set			
					min	max		Set Range	Shut-off (OPSO) Set Range Over UPSO Setpoint	UPSO	Adjusted OPSO Range	OPSO	
		psig	psig	psig	min	max	psig	psig	psig	psig	psig	psig	
CSB704F	7 in. w.c.	5.2 to 9.6 in. w.c.	VSX8L (125 psi)	12 in. w.c.	170	215	3.2 in. w.c.	3 to 12 in. w.c.	16 to 29 in. w.c.	3 in. w.c.	19 in. w.c. to 1.2 psig	22 in. w.c.	
	11 in. w.c.	8.8 to 15.7 in. w.c.		17 in. w.c.	150	160	4 in. w.c.			6 in. w.c.	22 in. w.c. to 1.3 psig	25 in. w.c.	
	14 in. w.c.	12.8 to 20.0 in. w.c.		21 in. w.c.	150	160	4 in. w.c.	4 in. w.c. to 1.1 psig	20 in. w.c. to 1.8 psig	9 in. w.c.	1 to 2.1 psig	1.1	
CSB724F	1	24.0 in. w.c. to 1.6 psig		1.4	140	150	6.4 in. w.c.	10 in. w.c. to 2.3 psig	1.2 to 3.2	14 in. w.c.	1.7 to 3.7	2	
	2			2.6	130	140	0.6			1	2.2 to 4.2	3.5	
	3	1.5 to 3.2		3.8	125	140	0.6	1.5 to 7.3	2.6 to 5.6	2	4.6 to 7.6	5	
	5	3.1 to 5.5		6.2	125	140	0.7	1.5 to 7.3	2.6 to 5.6	3	5.6 to 8.6	7	
	10	7.4 to 11.3						1.5 to 7.3	3.5 to 8.2	5	8.5 to 13.2	12	
CSB704	7 in. w.c.	5.2 to 9.6 in. w.c.		VSX8L (232 psi)	12 in. w.c.	170	215	3.2 in. w.c.	3 to 12 in. w.c.	18 to 30 in. w.c.	3 in. w.c.	21 in. w.c. to 1.2 psig	22 in. w.c.
	11 in. w.c.	8.8 to 15.7 in. w.c.			17 in. w.c.	150	160	4 in. w.c.			6 in. w.c.	24 in. w.c. to 1.3 psig	25 in. w.c.
	14 in. w.c.	12.8 to 20.0 in. w.c.	21 in. w.c.		150	160	4 in. w.c.	4 in. w.c. to 1.1 psig	25 in. w.c. to 1.9 psig	9 in. w.c.	1.2 to 2.2 psig	1.1	
CSB724	1	24.0 in. w.c. to 1.6 psig	1.4		140	150	6.4 in. w.c.	10 in. w.c. to 2.3 psig	1.2 to 3.2	14 in. w.c.	1.7 to 3.7	2	
	2		2.6		130	140	0.6			1	2.2 to 4.2	3.5	
	3	1.5 to 3.2	3.8		125	140	0.6	1.5 to 7.3	2.6 to 5.6	2	4.6 to 7.6	5	
	5	3.1 to 5.5	6.2		125	140	0.7	1.5 to 7.3	2.6 to 5.6	3	5.6 to 8.6	7	
	10	7.4 to 11.3						1.5 to 7.3	3.5 to 8.2	5	8.5 to 13.2	12	
CSB754	15	10.2 to 17.3	VSX8H (232 psi)						1.5 to 10.9	6.7 to 13.5	7	13.7 to 20.5	19
	20	15.2 to 39.2							7.3 to 29.0	15.2 to 22.8	10	25.2 to 32.8	25
30								18.1 to 33.4	15	33.1 to 48.4	35		
40	33.4 to 55.1								20	38.1 to 53.4	45		

Grey areas indicate that token relief is not available above 8 psig setpoint.


**Table 6b. European Overpressure and Underpressure Shut-off UPSO/OPSO Ranges**

REGULATOR			SLAM SHUT DEVICE												
Type	Typical Setpoint	Spring Range	Type (Maximum Operating Inlet)	Token Relief Set	Relief Range Shown as a % of Regulator Setpoint		Required Difference Between Token Relief and OPSO	UPSO	OPSO	Factory Set					
					min	max		Set Range	Shut-off (OPSO) Set Range Over UPSO Setpoint	UPSO	Adjusted OPSO Range	OPSO			
		mbar	mbar	mbar	min	max	mbar	mbar	mbar	mbar	mbar	mbar			
CSB704F	15	13 to 24	VSX8L (8.6 bar)	26	170	215	6	7 to 11	30 to 44	8	38 to 52	40			
	20	13 to 24		34	170	215	6	7 to 11	30 to 44	10	40 to 54	40			
	21	13 to 24		36	170	215	4	7 to 11	30 to 44	10	40 to 54	40			
	27	22 to 39		41	150	160	5	7 to 15	32 to 44	14	46 to 58	46			
	30	22 to 39		45	150	160	10	7 to 30	40 to 72	15	55 to 87	60			
	35	22 to 39		53	150	160	10	7 to 30	40 to 72	18	58 to 90	70			
	50	42 to 70		70	140	158	16	10 to 75	48 to 74	25	73 to 99	90			
	60			84	140	158	16		48 to 74	30	78 to 104	100			
	75	61 to 110		98	130	140	20	25 to 160	83 to 221	38	121 to 259	130			
	CSB704	15		13 to 24	VSX8L (16 bar)	26	170	215	6	7 to 30	40 to 55	8	48 to 63	50	
20		13 to 24	34	170		215	6	7 to 30	40 to 55	10	50 to 65	55			
21		13 to 24	36	170		215	4	7 to 30	40 to 55	10	50 to 65	55			
27		22 to 39	41	150		160	5	7 to 30	40 to 55	14	54 to 69	55			
30		22 to 39	45	150		160	10	7 to 30	45 to 76	15	60 to 91	60			
35			53	150		160	10	7 to 30	45 to 76	18	63 to 94	70			
50		42 to 70	70	140		158	16	10 to 75	50 to 80	25	75 to 105	90			
60			84	140		158	16		50 to 80	30	80 to 110	100			
75		61 to 110	98	130		140	20	25 to 160	83 to 221	38	121 to 259	130			
CSB724		100	61 to 110	VSX8L (16 bar)		130	130	140	20	25 to 160	83 to 221	50	133 to 271	170	
	120	156			130	140	40	60	143 to 281			205			
	150	105 to 220	195		130	140	40	75	158 to 296			250			
	160		208		130	140	40	80	163 to 301			265			
	200		250		125	140	50	100 to 500	114 to 261			100	214 to 361	330	
	300		210 to 380		375	125	140	50	179 to 386			150	329 to 536	450	
	500		320 to 570		625	125	140	60	241 to 565			250	491 to 815	700	
	600		510 to 780						100 to 500			241 to 565	300	541 to 865	840
	750								100 to 750			460 to 932	375	835 to 1120 <sup>(1)</sup>	1050
CSB724F	300	270 to 325	VSX8L (8.6 bar)				100 to 500	179 to 386	200	379 to 586	400				
CSB754 GrDF	1000	0.7 to 1.19 bar	VSX8L (16 bar)				100 to 500	460 to 932	750	1210 to 1682	1210				
CSB754	1000	0.7 to 1.19 bar	VSX8H (16 bar)					100 to 500	460 to 932	500	960 to 1432	1320			
	1200							500 to 2000	1050 to 1570	600	1650 to 2170	1650			
	1500	1.05 to 2.7 bar						1250 to 2300	1000	1800 to 2320	1900				
	2000							1500	2250 to 3300	2400					
	3000			2.3 to 3.25 bar					1500	2750 to 3800	3400				
4000	3.1 to 4 bar					500 to 2800	2100 to 3750	2000	4100 to 5000 <sup>(1)</sup>	4400					

Grey areas indicate that token relief is not available above 500 mbar setpoint.  
 1. Max OPSO setpoint truncated to reflect maximum outlet pressure for spring range.

**Example:** If a non-standard setpoint is needed, see the following example for the proper use of Tables 6a and 6b. In this example, the non-standard regulator setpoint is 2.0 psig / 140 mbar. The minimum factory token relief set pressure is 130% of the non-standard setpoint. The resulting token relief set pressure is 2.6 psig / 183 mbar. The minimum factory OPSO and UPSO set pressures are 165% and 50% of the non-standard setpoint, respectively. The resulting minimum settings are: OPSO = 3.4 psig / 231 mbar and UPSO = 1.0 psig / 70 mbar.






GE32407\_DF

Figure 4. CSB700 Series Vent and Body Positions

# CSB700 Series

Commercial / Industrial – Pressure Reducing Regulator

FISHER™



ERSA01617\_AB

TYPES CSB700, CSB700F, CSB720F AND CSB720

1. Maximum spring removal clearance for the primary regulator is 6.2 in. / 158 mm.
2. Maximum spring removal clearance for the slam shut is 3.1 in. / 80 mm.

Figure 5. CSB700 Series Dimensions

Table 7. CSB700 Series Dimensions

BODY SIZE		BODY END CONNECTION STYLE	FACE-TO-FACE DIAMETER (A)	
NPS	DN		In.	mm
1-1/2	40	NPT or Rp	6.1	155
2	50	NPT or Rp	6.1	155
2	50	CL125 FF/CL150 FF	7.50	191
			10.0	254
			10.5	267
		CL150 RF	10	254
		PN 10/16	7.5	191
1-1/2	40	PN 16 Slip-on	7.87	200
			10	254
			8.74	222

## Ordering Guide

<b>Type (See Table 1 for Construction details) (Select One)</b>	<b>Outlet Pressure Range (Select One)</b>																
<p><b>Stand-Alone Regulator</b></p> <table style="width: 100%; border: none;"> <tr> <td><input type="checkbox"/> CSB700EN</td> <td><input type="checkbox"/> CSB720FEN</td> </tr> <tr> <td><input type="checkbox"/> CSB700ET</td> <td><input type="checkbox"/> CSB720EN</td> </tr> <tr> <td><input type="checkbox"/> CSB700FEN</td> <td><input type="checkbox"/> CSB720ET</td> </tr> <tr> <td><input type="checkbox"/> CSB700FET</td> <td><input type="checkbox"/> CSB750EN</td> </tr> </table> <p><b>With Type VSX8 Slam-Shut Module</b></p> <table style="width: 100%; border: none;"> <tr> <td><input type="checkbox"/> CSB704EN</td> <td><input type="checkbox"/> CSB724FEN</td> </tr> <tr> <td><input type="checkbox"/> CSB704ET</td> <td><input type="checkbox"/> CSB724EN</td> </tr> <tr> <td><input type="checkbox"/> CSB704FEN</td> <td><input type="checkbox"/> CSB724ET</td> </tr> <tr> <td><input type="checkbox"/> CSB704FET</td> <td><input type="checkbox"/> CSB754EN</td> </tr> </table>	<input type="checkbox"/> CSB700EN	<input type="checkbox"/> CSB720FEN	<input type="checkbox"/> CSB700ET	<input type="checkbox"/> CSB720EN	<input type="checkbox"/> CSB700FEN	<input type="checkbox"/> CSB720ET	<input type="checkbox"/> CSB700FET	<input type="checkbox"/> CSB750EN	<input type="checkbox"/> CSB704EN	<input type="checkbox"/> CSB724FEN	<input type="checkbox"/> CSB704ET	<input type="checkbox"/> CSB724EN	<input type="checkbox"/> CSB704FEN	<input type="checkbox"/> CSB724ET	<input type="checkbox"/> CSB704FET	<input type="checkbox"/> CSB754EN	<p><b>Type CSB700/CSB704</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 3.6 to 5.6 in. w.c. / 9 to 14 mbar, Silver***</li> <li><input type="checkbox"/> 5.2 to 9.6 in. w.c. / 13 to 24 mbar, Red***</li> <li><input type="checkbox"/> 8.8 to 15.7 in. w.c. / 22 to 39 mbar, Black Stripe***</li> <li><input type="checkbox"/> 12.8 to 20.1 in. w.c. / 32 to 50 mbar, Purple***</li> <li><input type="checkbox"/> 16.9 to 28.1 in. w.c. / 42 to 71 mbar, White Stripe***</li> <li><input type="checkbox"/> 0.9 to 1.6 psig / 61 to 110 mbar, Dark Green***</li> </ul> <p><b>Type CSB700F/CSB704F</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 5.2 to 9.6 in. w.c. / 13 to 24 mbar, Red***</li> <li><input type="checkbox"/> 8.8 to 15.7 in. w.c. / 22 to 39 mbar, Black Stripe***</li> </ul> <p><b>Type CSB720/CSB724</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 0.9 to 1.6 psig / 61 to 110 mbar, Dark Green***</li> <li><input type="checkbox"/> 1.5 to 3.2 psig / 105 to 220 mbar, Blue***</li> <li><input type="checkbox"/> 3.1 to 5.5 psig / 210 to 380 mbar, Black***</li> <li><input type="checkbox"/> 4.6 to 8.3 psig / 320 to 570 bar, Red with White Stripe***</li> <li><input type="checkbox"/> 7.40 to 11.3 psig / 510 to 780 bar, Blue with White Stripe***</li> </ul> <p><b>Type CSB720F/CSB724F</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 3.9 to 4.7 psig / 270 to 325 mbar, Black with White Stripe</li> </ul> <p><b>Type CSB750/CSB754</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 10.2 to 17.3 psig / 0.7 to 1.19 bar, Purple Stripe***</li> <li><input type="checkbox"/> 15.2 to 39.2 psig / 1.05 to 2.7 bar, Brown***</li> <li><input type="checkbox"/> 33.4 to 47.1 psig / 2.3 to 3.25 bar, Grey with Red Stripe***</li> <li><input type="checkbox"/> 45 to 58 psig / 3.1 to 4 bar, Grey with Orange Stripe***</li> </ul>
<input type="checkbox"/> CSB700EN	<input type="checkbox"/> CSB720FEN																
<input type="checkbox"/> CSB700ET	<input type="checkbox"/> CSB720EN																
<input type="checkbox"/> CSB700FEN	<input type="checkbox"/> CSB720ET																
<input type="checkbox"/> CSB700FET	<input type="checkbox"/> CSB750EN																
<input type="checkbox"/> CSB704EN	<input type="checkbox"/> CSB724FEN																
<input type="checkbox"/> CSB704ET	<input type="checkbox"/> CSB724EN																
<input type="checkbox"/> CSB704FEN	<input type="checkbox"/> CSB724ET																
<input type="checkbox"/> CSB704FET	<input type="checkbox"/> CSB754EN																
<b>Body Size and End Connection Style (Select One)</b>																	
<p><b>Ductile Iron</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 1-1/2 NPT</li> <li><input type="checkbox"/> 2 NPT***</li> <li><input type="checkbox"/> Rp 1-1/2***</li> <li><input type="checkbox"/> Rp 2***</li> <li><input type="checkbox"/> NPS 2 / DN 50, CL125 FF***</li> <li><input type="checkbox"/> NPS 2 / DN 50, CL150 FF***</li> <li><input type="checkbox"/> NPS 2 / DN 50, PN 10/16***</li> <li><input type="checkbox"/> NPS 1-1/2 / DN 40, PN 16 slip-on flanged body</li> </ul> <p><b>WCC Steel</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> 1-1/2 NPT***</li> <li><input type="checkbox"/> 2 NPT***</li> <li><input type="checkbox"/> Rp 1-1/2***</li> <li><input type="checkbox"/> Rp 2***</li> <li><input type="checkbox"/> NPS 2 / DN 50, CL150 RF</li> <li><input type="checkbox"/> NPS 2 / DN 50, PN 10/16</li> </ul>																	
	<b>Body Orientation<sup>(1)</sup> (Select One)</b>																
	<ul style="list-style-type: none"> <li><input type="checkbox"/> Position 1***</li> <li><input type="checkbox"/> Position 2***</li> <li><input type="checkbox"/> Position 3 <b>(standard)</b>***</li> <li><input type="checkbox"/> Position 4***</li> </ul>																

- continued -

1. For the Type CSB704, choose the body orientation of the primary regulator only. The slam-shut spring barrel will be oriented in the same direction as the primary regulator spring barrel.

# CSB700 Series

Commercial / Industrial – Pressure Reducing Regulator



## Ordering Guide (continued)

### Vent Orientation<sup>(1)</sup> (Select One)

- Position C\*\*\*
- Position D\*\*\*
- Position E\*\*\*
- Position F (**standard**)\*\*\*

### Slam-Shut Trip Pressure Setting (Select One if applicable)

- Overpressure (OPSO) trip only  
Indicate Overpressure Trip Point \_\_\_\_\_
- Over and Underpressure (OPSO/UPS) trip  
Indicate Overpressure Trip Point \_\_\_\_\_  
Indicate Underpressure Trip Point \_\_\_\_\_

1. For the Type CSB704, choose the vent orientation of the primary regulator only. The slam-shut vent will be oriented to point in the same direction as the primary regulator.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Regulators with high flows and large pressure drops generate noise. Noise can wear parts which can cause failure and/or inaccurate control. Keep regulator noise below 110 dBA.





### Introduction

Type Dosaodor-D is a computerized odorant injection system for natural gas that uses patented solenoid injector technology that eliminates the need for plunger pumps.

The solenoid injectors permit odorant injection accuracy to be maintained over the entire range of the system, approaching infinite turndown.

Automatic calibration during operation adjusts for any changes in mechanical components and detects failures for report by exception alarming. The system can also be configured to use two solenoid injection valves and/or an emergency backup absorption system.

The system can be configured and operation data can be viewed using an integrated push button panel and display. A printer option is also available for local hard copy documentation of system operations (gas flow rates, injection rates, configuration changes, and alarms).

Type Dosaodor-D has standard modbus registers for real-time data and archiving history. This data can be read locally by a laptop computer or remotely using third party SCADA products.

Dosalink mini-SCADA software is available for local or remote configuration and operation of the system including: automatic polling and display of real time and historical data, monitoring for report by exception alarming and relational data base archival of historical data. The historical data can be exported in ODBC format for analysis and reports using commercially available relational data base software products.

Type Dosaodor-D controlled by Type Electronic Control Unit is available in Asia Pacific, Europe, Middle East and Africa only.

### Software Specifications

#### Modes of Operation:

*System:* Automatic, Manual, Wash and Disabled

*Injector:* Injector 1, Injector 2, Injector 1-2 (dual injector solenoid valve option only)

### Pneumatic Panel Specifications

**Material:** 20/10 mm Stainless steel plate  
Installation: Wall mount

Weight: 55 to 100 lbs / 25 to 45 kg (based on configuration type)

#### Overpressure Relief Valve:

Stainless steel with following rating options:

203 psi / 14 bar

551 psi / 38 bar

870 psi / 60 bar

**Electrical Protection:** Explosion proof and intrinsically safe

**Material Electrical Protection:** Available for European and North American standards

#### Mechanical Connections:

**Odorant Inlet and Discharge:**  
1/4 in. / 6.4 mm double ferrule fitting for 6 x 1 in. / 15 x 2.5 mm pipe

**Gas Inlet and Discharge:**  
1/4 in. / 6.4 mm single ferrule fitting for 8 x 1 in. / 20 x 2.5 mm pipe

#### Maximum Working Pressure:

**Supply:** 1450 psi / 100 bar

**Injection:**

203 psi / 14 bar

551 psi / 38 bar

870 psi / 60 bar

**Odorant Flow Rate:** 0.89 to 24.97 lbs/h / 0.5 to 14.0 l/h at 6.75 lbs/gal

### Electronic Control Unit Specifications

**Material:** 10/10 mm steel plate

Installation: Wall mounted

Weight: 49 lbs / 22 kg

(medium complexity configuration)

**Power Supply Options:**

12 Vdc +/-15%

115 Vac 60Hz

230 Vac 50Hz

**Electrical Protection:**

Explosion proof/intrinsically safe

**Communication Ports Included:** One

RS-232 serial port is available for local configuration or connected to an GSM modem.

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Consistent Odorization Proportional to Entire Range of Gas Flow Rate
- Significantly Reduced Maintenance
- Variety of Redundancy Options for Odorization
- User Friendly Configuration Software
- Automatic Calibration During Operation
- Standard and Scalable Hardware Platform



Figure 1. Type Dosaodor-D Pneumatic Panel



Figure 2. Type Electronic Control Unit



Figure 3. Standard Wick Insert (Pipeline Injection)

# Type Dosaodor-D

Odorant Injection System Controlled by Type Electronic Control Unit

TARTARINI




Figure 4. Typical Type Dosaodor-D Installation Schematic

Table 1. Maximum Odorant Injection Rate

MAXIMUM INJECTION RATE, l/h	MAXIMUM GAS VOLUME IN Sm <sup>3</sup> /h		MAXIMUM INJECTION RATE, Lbs/h (AT 6.75 Lbs/h)	MAXIMUM GAS VOLUME MSCF/h	
	40 mg/Sm <sup>3</sup> (THT)	10 mg/Sm <sup>3</sup> (Mercaptan)		1.0 lbs/MMSCF (THT)	0.5 lbs/MMSCF (Mercaptan)
0.5	12,500	50,000	0.89	892	1783
1.0	25,500	100,000	1.78	1783	3567
2.0	50,000	200,000	3.57	3567	7133
4.0	100,000	400,000	7.13	7133	14,267
6.0	150,000	600,000	10.68	10,698	21,400
8.0	200,000	800,000	14.27	14,267	28,534
10.0	250,000	1,000,000	17.83	17,834	35,667
12.0	300,000	1,200,000	21.40	21,400	42,800
14.0	350,000	1,400,000	24.97	24,967	49,934




Figure 5. Pneumatic Panel and Electronic Control Unit Overall Dimensions

# Type Dosaodor-D

Odorant Injection System Controlled by Type Electronic Control Unit

TARTARINI™

## Ordering Guide

### Base Unit (Select One)

- A1:** Type Dosaodor-D odorant injection system completed with:
  - Pneumatic Panel*
    - Stainless steel panel
    - Installation kit (bracket, pipe connection, injector, valves, etc.)
    - EEx element certificate for installation in hazardous area zone 1 according to EN 60079 -10
  - Electronic Control Unit*
    - Steel cabinet IP55 for non hazardous locations
    - Display LCD (4X40)
    - Membrane keyboard 26 keys
    - Memory lithium battery for data retain
- A4:** Type Dosaodor-D odorant injection system completed with:
  - Pneumatic Panel*
    - Stainless steel panel
    - Installation kit (bracket, pipe connection, injector, valves, etc.)
    - EEx element certificate for installation in hazardous area zone 1 according to EN 60079 -10 (Junction box and cable glands Elcon). According to Polish market requirements.
  - Electronic Control Unit*
    - Steel cabinet IP55 for non hazardous locations
    - Display LCD (4X40)
    - Membrane Keyboard 26 keys
    - Memory Lithium battery for data retain

### Model (Select One)

- B1:** Single Injector
- B2:** Dual Injector

### Maximum Odorant Injection Rate (Select One)

- C1:** 0.89 lbs/h / 0.5 l/h
- C2:** 1.78 lbs/h / 1.0 l/h
- C3:** 3.57 lbs/h / 2.0 l/h
- C4:** 7.13 lbs/h / 4.0 l/h
- C5:** 10.68 lbs/h / 6.0 l/h
- C6:** 14.27 lbs/h / 8.0 l/h
- C7:** 17.83 lbs/h / 10.0 l/h
- C8:** 21.40 lbs/h / 12.0 l/h
- C9:** 24.97 lbs/h / 14.0 l/h

1. Options are not available with I1 option.

### Options (Select One, None, or More Options)

- D1:** Printer (1)
- D2:** 6 Ampere/h (Ah) UPS (Uninterruptible Power Supply)
- D3:** 18 Ampere/h (Ah) UPS (Uninterruptible Power Supply)
- D4:** Accessory Kit for Emergence Absorption System with Injection Pressure  $\leq$  6 bar (tanks not included)
- D5:** Accessory Kit for Emergence Absorption System with Injection Pressure 6 to 14 bar (tanks not included)
- D6:** Accessory Kit for Emergence Absorption System with Injection Pressure  $>$  14 bar (tanks not included)

### Main Power Supply (Select One or More Options)

- E1:** 230 V to 50 Hz, 12 Vcc
- E2:** 115 V to 60 Hz, 12 Vcc

### Front Panel Language (Select One)

- F1:** Italian / English
- F2:** Byelorussian / English
- F3:** English

### Display and Printer Language (Select One)

- G1:** Italian
- G2:** Byelorussian
- G3:** Spanish
- G4:** Polish
- G5:** English I.S. Units - International System
- G6:** English Imperial U.S. Units - Imperial System
- G7:** French
- G8:** Ukraine

### Communication (Select One)

- H2:** Dial-up modem for electronic control unit
- H3:** GSM Modem for Electronic control unit
- H6:** Telealarm and warning messaging  
Available with DosaLink software - DSL  
Available for Italian market only  
For other markets please ask for availability.

- continued -

## Ordering Guide (continued)

### Maximum Working Pressure (Select One)

- I1:** 203 psig / 14 bar (odorant SG>=0.7)
- I2:** 551 psig / 38 bar (odorant SG>=0.55)
- I3:** 870 psig / 60 bar (odorant SG>=0.7)

### Special Versions

(Select One, Both or None Options)

- L1:** Skid Mounted
- L2:** Low Temperature

### Installation Options - Injector (Select One)

- M1:** DN 3/4 in. long injector  
(for downstream size >= 10 in. / DN 250)
- M2:** DN 3/4 in. short injector  
(for downstream size < 10 in. / DN 250)
- M3:** DN 1/2 in. long injector  
(for downstream size >= 10 in. / DN 250)
- M4:** DN 1/2 in. short injector  
(for downstream size < 10 in. / DN 250)

### Installation Options - Emergency Absorption System Valve (Select One or None Options)

**Standard: Pneumatic Valve (normally open) - Threaded 1 in. / DN 25 NPT-F PN 16**

- N0:** Pneumatic Valve (normally open) - Threaded 1-1/2 in. / DN 40 NPT-F - Max operating pressure 64 bar
- N1<sup>2</sup>:** Valve + Pneumatic Actuator (normally open) - 2-1/2 in. / DN 65, CL150 Flanged
- N2<sup>2</sup>:** Valve + Pneumatic Actuator (normally open) - 1-1/2 in. / DN 40 CL150 Flanged
- N3:** Valve + Pneumatic Actuator (normally open) - 1-1/2 in. / DN 40 PN 64 Flanged
- N4:** Valve + Pneumatic Actuator (normally open) - Threaded 1 in. / DN 25 NPT-F - Max operating pressure 64 bar
- N5<sup>2</sup>:** Pneumatic Valve (normally open) - 3/4 in. / DN 20 PN 16 Flanged
- N6<sup>2</sup>:** Pneumatic Valve (normally open) - 1 in. / DN 25 PN 16 Flanged
- N7<sup>2</sup>:** Pneumatic Valve (normally open) - 1-1/4 in. / DN 32 PN 16 Flanged
- N8<sup>2</sup>:** Pneumatic Valve (normally open) - 1-1/2 in. / DN 40 PN 16 Flanged
- N9<sup>2</sup>:** Pneumatic Valve (normally open) - 2 in. / DN 50 PN 16 Flanged

2. Options can not be ordered if the D6 option is selected.

### Optional Components

#### Containing Tank

- VASC:** Stainless steel containing tank, installed under the pneumatic panel, to collect eventual odorant liquid loss

### Remote Control Center Components

#### Software for Management and Programming

- DSL:** DosaLink mini-SCADA Software

### External Modem for Personal Computer

(Select One or More Options)

- DUP:** External dial-up modem for Personal Computer, to be used with DosaLink software - DSL
- GSM:** External GSM modem for Personal Computer, to be used with DosaLink software - DSL Necessary in presence of telealarm - H6

# Type Dosaodor-D

Odorant Injection System Controlled by Type Electronic Control Unit

TARTARINI™

## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

Looking for a specific product? When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.

### Introduction

Type Dosaodor-D is a computerized odorant injection system for natural gas that uses patented solenoid injector technology that eliminates the need for plunger pumps.

The solenoid injectors permit odorant injection accuracy to be maintained over the entire flow range of the system, approaching infinite turn down.

Automatic calibration during operation adjusts for any changes in mechanical components and detects failures for alarming. Report by exception alarming is a configurable option.

The system can also be configured to use redundant injectors and/or an emergency backup or bypass absorption system.

Real time and historical data can be read locally by a laptop computer using ROCLINK 800 configuration software or remotely using third party SCADA products utilizing modbus or ROC protocol.

ROCLINK 800 software is available for complete configuration and operation of the system including: display of real time and historical data, configuration of alarms and archival of historical data.

Type Dosaodor-D controlled by Type ROC809 is available in North America only.

### Remote Telemetry Unit

**For Technical Specifications please refer to the Type ROC800 Series pages**

*Required Equipment Includes:*

- Type ROC809E Controller
- ROC800 Series Power Supply
- ROC800 Series Discrete Relay Output Card
- ROC800 Series Discrete Input Card
- DS800 Runtime License

*Input Card Options for Flow Rate Input:*

- ROC800 Series Analog Input Card
- ROC800 Series Pulse Input Card

### Optional Equipment:

- Type ROCLINK800 Software (at least 1 license required)
- Type ROC800 LOI Cable
- Type ROC800 Ethernet Crossover Cable
- Type ROC800 RS232 Comm Module
- Type ROC800 RS485 Comm Module
- Type ROC800 14.4 Dial-up Modem Comm
- Type ROC800 Analog Output Card
- Power Supply Charger 12 Vdc

### Software Specifications

#### Modes of Operation:

- Auto, Manual, Minimal, Refill, Purge/Wash and Disabled
- ROC and/or modbus protocol
- Event, Alarm and History archive
- RBX and SRBX alarms

### Pneumatic Panel Specifications

#### Material:

Stainless steel plate

#### Installation:

Wall mount

#### Weight:

55 to 100 lbs / 25 to 45 kg  
(based on configuration)

#### Overpressure Relief Valve:

Stainless steel with following rating options:

200 psi / 13.8 bar

550 psi / 37.9 bar

870 psi / 60 bar

#### Electrical Protection:

Explosion proof

Class I, Division 1 and 2 - Groups B, C, D

Class I, Zone 1 and 2 - Groups IIB+H2, IIA

#### Material Electrical Protection:

Available for European and North American standards

#### Mechanical Connections:

Odorant Inlet and Discharge:

1/4-in. / 6.4 mm OD Tube Fitting  
(double Ferrule)

Gas Inlet and Discharge:

3/8-in. / 10 mm OD Tube fitting  
(single Ferrule)

#### Maximum Working Pressure:

Supply: 1450 psi / 100 bar

Injection: 870 psi / 60 bar

#### Odorant Flow Rate:

0.13 to 3.70 gallons per hour / 0.5 to 14.0 L/hr  
(0.89 to 24.97 lbs/hr at 6.75 lbs/gal)

#### Temperature Range:

14 to 140°F / -10 to 60°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



01/10

### Features

- **Consistent Odorization Proportionate to Entire Range of Gas Flow Rate**
- **Significantly Reduced Maintenance**
- **Variety of Redundancy Options for Odorization**
- **User Friendly Configuration Software**
- **Automatic Calibration During Operation**
- **Standard and Scalable Hardware Platform**




Figure 1. Type Dosaodor-D Pneumatic Panel



Figure 2. Type ROC809 Remote Telemetry Unit



Figure 3. Standard Wick Insert (Pipeline Injection)

# Type Dosaodor-D

Odorant Injection System Controlled by Type ROC809

TARTARINI





Figure 4. Typical Type Dosaodor-D Installation Schematic

Table 1. Maximum Odorant Injection Rate

ORDER FROM CONFIGURATION	MAXIMUM INJECTION RATE		MAXIMUM GAS VOLUME IN Sm <sup>3</sup> /h		MAXIMUM INJECTION RATE, lbs/h (at 6.75 lbs/h)	MAXIMUM GAS VOLUME, MMSCF/h	
	gal/hr	L/h	40 mg/Sm <sup>3</sup> (THT)	10 mg/Sm <sup>3</sup> (Mercaptan)		1.0 lbs/MMSCF (THT)	0.5 lbs/MMSCF (Mercaptan)
C1	0.13	0.5	12,500	50,000	0.89	0.89	1.78
C2	0.26	1.0	25,500	100,000	1.78	1.78	3.57
C3	0.53	2.0	50,000	200,000	3.57	3.57	7.13
C4	1.06	4.0	100,000	400,000	7.13	7.13	14.27
C5	1.58	6.0	150,000	600,000	10.70	10.70	21.40
C6	2.11	8.0	200,000	800,000	14.27	14.27	28.53
C7	2.64	10.0	250,000	1,000,000	17.83	17.83	35.67
C8	3.17	12.0	300,000	1,200,000	21.40	21.40	42.80
C9	3.70	14.0	350,000	1,400,000	24.97	24.97	49.93





**OPTIONAL STAINLESS STEEL CABINET**

DIMENSIONS: 37 X 18.2 X 78.4 IN. / 940 X 460 X 1990 MM

Figure 5. Pneumatic Panel Overall Dimensions

## Ordering Guide

**Base Unit (Select One)**

- A6:** Type Dosaodor-D odorant injection system completed with:
  - Pneumatic Panel*
  - Stainless steel panel
  - Installation kit (bracket, pipe connection, injector, valves, etc.)
  - Explosion proof Class I, Division 1 and 2 - Groups B, C, D - Class I, Zone 1 and 2 - Groups IIB+H2, IIA
  - Included 1/4-in. NPT fitting connectors for 3/8-in. / 9.5 mm and 1/4-in. / 6.4 mm OD tubing

**Model (Select One)**

- B1:** Single Injector
- B2:** Dual Injector

**Maximum Odorant Injection Rate (Select One, See Table 1)**

- |  |  |
|--|--|
| <input type="checkbox"/> <b>C1:</b> 0.13 gal/h / 0.5 l/h | <input type="checkbox"/> <b>C6:</b> 2.11 gal/h / 8.0 l/h   |
| <input type="checkbox"/> <b>C2:</b> 0.26 gal/h / 1.0 l/h | <input type="checkbox"/> <b>C7:</b> 2.64 gal/hr / 10.0 l/h |
| <input type="checkbox"/> <b>C3:</b> 0.53 gal/h / 2.0 l/h | <input type="checkbox"/> <b>C8:</b> 3.17 gal/hr / 12.0 l/h |
| <input type="checkbox"/> <b>C4:</b> 1.06 gal/h / 4.0 l/h | <input type="checkbox"/> <b>C9:</b> 3.70 gal/hr / 14.0 l/h |
| <input type="checkbox"/> <b>C5:</b> 1.58 gal/h / 6.0 l/h |  |

**Maximum Working Pressure (Select One)**

- I1:** 200 psi / 13.6 bar (odorant  $\rho \geq 5.8$  lbs/gallon / 0.70 kg/dm<sup>3</sup>)
- I2:** 550 psi / 37.9 bar (odorant  $\rho \geq 4.6$  lbs/gallon / 0.55 kg/dm<sup>3</sup>)
- I3:** 870 psi / 60 bar (odorant  $\rho \geq 5.8$  lbs/gallon / 0.70 kg/dm<sup>3</sup>)

- continued -

# Type Dosaodor-D

Odorant Injection System Controlled by Type ROC809

TARTARINI™

## Ordering Guide (continued)

### Installation Options - Wick Insert (Select One)

- Standard Wick Insert (for downstream size < 10-in. / DN 250)
- Long Wick Insert (for downstream size ≥ 10-in. / DN 250)

### Installation Options - Fittings (Bulk Brand as Standard)

- Swagelok fittings

### Cabinet for Pneumatic Panel (Optional Component)

- Stainless steel Cabinet for Pneumatic Panel

### Automation Software and License Key

- Software for Pneumatic Panel Control, available with Type ROC809 plus Type Dosaodor-D License Key

### Type ROC809 Configurations and Options

#### Required Components

- | Quantity                   | Description                            |
|----------------------------|--|
| <input type="checkbox"/> 1 | Type ROC809E Controller                |
| <input type="checkbox"/> 1 | Type ROC800 12 Vdc Power Supply        |
| <input type="checkbox"/> 2 | Type ROC800 Discrete Relay Output Card |
| <input type="checkbox"/> 1 | Type ROC800 Discrete Input Card        |
| <input type="checkbox"/> 1 | Type DS800 Runtime License             |

### Select Input Card Type for Flow Rate Input (Choose Only One for Configuration)

- | Quantity                   | Description                   |
|----------------------------|-------------------------------|
| <input type="checkbox"/> 1 | Type ROC800 Analog Input Card |
| <input type="checkbox"/> 1 | Type ROC800 Pulse Input Card  |
- #### Optional Equipment
- | Quantity                   | Description  |
|----------------------------|--|
| <input type="checkbox"/> 1 | Type ROCLINK800 Software (at least 1 license required) |
| <input type="checkbox"/> 1 | Type ROC800 LOI Cable                                  |
| <input type="checkbox"/> 1 | Type ROC800 Ethernet Crossover Cable                   |
| <input type="checkbox"/> 1 | Type ROC800 RS232 Comm Module                          |
| <input type="checkbox"/> 1 | Type ROC800 RS485 Comm Module                          |
| <input type="checkbox"/> 1 | Type ROC800 14.4 Dial-up Modem Comm                    |
| <input type="checkbox"/> 1 | Type ROC800 Analog Output Card                         |
| <input type="checkbox"/> 1 | Power Supply Charger 12 Vdc                            |

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### Regulator Tip:

If you don't see what you're looking for in this Application Guide. . . ask us about it. Space in this Application Guide does not always permit us to list all of the options or products available to you. If you don't see the product you're looking for, just pick up the phone and ask your local Sales Office to help you find the item you need. To locate your local Sales Office, log on to Emerson.com/ContactUs.



## Introduction

The Type DO200 system consists of the pneumatic injection panel installed in the classified area, a control panel installed in the safe area and an appropriate diffuser installed in the gas piping.

The pneumatic panel injects the odorant liquid into the main gas pipe through the diffuser.

The control panel controls the pneumatic injection panel through a logic based PLC and automatically manages the dosage of the odorant liquid proportionately to the gas flow rate.

The backup odorant system is installed in the classified area and consists of an absorption tank which also serves as the service tank of the main injection unit.

Type DO200 provides two back up options: the absorption system or the double injection with two panels in master/ slave configuration.

## Control Panel Specifications

**Cabinet Material:** Resin IP65-IP55

Installation: Wall mount

Feeding: 24 V DC, 100-240 V AC and 50/60 Hz

Consumption: 120 W at 24 V DC

Electromagnetic Interferences:

Compliant to 89/336/CE

Operating Temperature: -10 to 40°C / 14 to 104°F

Humidity: 10% - 90% not condensate

Installation Area: Safe Area (not classified)

## Input Signals

**Level measurement:** Analogic 4 to 20 mA (Exd)

**Analogic instant flow rate:** Analogic 4 to 20 mA

**Impulsive instant flow rate:** Impulsive

Cylinders pressure measurement:  
Analogic 4 to 20 mA (Exd)

## Output Signals

**Solenoid Valve:** 24 V DC (Exe)

## Communication Ports

1 RS485 port with internal unit

1 RS485 RJ11 port

1 Ethernet RJ11 port

## Display

Display touch screen 7 in. / 178 mm  
Default/Programmable password

## Operating Mode

Off-Automatic-Manual

## Remote Communication

Gateway 3G (optional)

## Pneumatic Panel Specifications

**Material:** Stainless steel

Liquid Odorants: THT/Mercaptans

Installation: Wall or floor (optional)

Maximum Feeding Pressure:

100 barg /1450 psig

## Features

- Operational Safety
- Extreme Reliability
- Very Low Maintenance
- Ease of Use
- Results Certainty

## Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



Figure 1. Pneumatic Injection Panel



Figure 2. Control Panel

# Type DO200

Odorant Injection System Controlled by Type Electronic Control Unit

TARTARINI




Figure 3. System Connections Schematic with Absorption and Inlet Pressure Supply




Figure 4. Type DO200 Overall Dimensions

# Type DO200

Odorant Injection System Controlled by Type Electronic Control Unit

TARTARINI™

## **Regulator Tip:**

Looking for a specific product? When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.

### Introduction

Types EZH (Spring-to-Close version) and EZHSO (Spring-to-Open version) regulators are accurate pilot-operated, pressure balanced, soft-seated regulators. They are designed for use in high pressure natural gas transmission, city gate stations, large capacity distribution systems and power plant feeds. They provide smooth, reliable operation, tight shutoff and long life.

For underpressure or overpressure protection, the Types EZHOSX (Spring-to-Close) and EZHSO-OSX (Spring-to-Open) are available with an integral slam-shut device to completely shutoff the flow of gas to the downstream system.

### Available Configurations

**Type EZH:** Spring-to-close pilot-operated pressure reducing regulator for low to high outlet pressure

**Type EZHSO:** Spring-to-open pilot-operated pressure reducing regulator for low to high outlet pressure

**Type EZHOSX:** Type EZH with a Type OS2 slam-shut device for overpressure (OPSO) or overpressure and underpressure (OPSO/UPSO) protection

### Body Sizes, End Connection

#### Styles and Pressure Ratings<sup>(1)</sup>

See Table 1

#### Outlet Pressure Ranges

See Table 2

#### Minimum Differential Pressures

See Table 3

### Flow and Sizing Coefficients

See Tables 5 to 11

### Flow Capacities

See Tables 12 to 13

### Maximum Allowable Pressures<sup>(1)</sup>

**Inlet Pressure:** 1500 psig / 103 bar

**Outlet (Casing) Pressure:**

1500 psig / 103 bar

**Emergency Casing Pressure:**

1500 psig / 103 bar

### Maximum Operating Differential Pressures<sup>(1)(3)</sup>

**Main Valve:** 1500 psid / 103 bar d

**Pilot:**  
Between Loading Pressure in Pilot and Loading Sense Pressure:  
1233 psid / 85.0 bar d

### Pressure Registration

External

### Type PRX Pilot Flow Coefficients

**C<sub>g</sub>:** 10.5; **C<sub>v</sub>:** 0.36; **C<sub>i</sub>:** 29

### Type SA/2 Flow Coefficient

**C<sub>g</sub>:** 4.9

### Temperature Capabilities<sup>(1)</sup>

**Nitrile (NBR) Version:**

-20 to 180°F / -29 to 82°C

**Fluorocarbon (FKM) Version:**

0 to 180°F / -18 to 82°C<sup>(2)</sup>

**Polyurethane (PU) Version:**

NPS 1, 2, 6, 8, 12 x 6 /

DN 25, 50, 150, 200, 300 x 150 Sizes:

-22 to 180°F / -30 to 82°C

NPS 3 to 4 / DN 80 to 100 Sizes:

-4 to 180°F / -20 to 82°C




Figure 1. Type EZH Pressure Reducing Regulator



Figure 2. Type EZHOSX Pressure Reducing Regulator with Type OS2 Slam-Shut Device

## Features

- No Gas Emissions
- Common Body Platform
- Bubble Tight Shutoff
- Full Pressure Rating
- Full Usable Capacity
- Easy In-Line Maintenance
- Long Life in Severe Service Applications
- Precise Pressure Control
- High Turn Down Capability
- Quiet Operation
- Failure Mode Options
- Integral Slam-Shut for Overpressure and Underpressure Protection

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



11/19

1. The pressure/temperature limits in this Datasheet and any applicable standard or code limitation should not be exceeded.  
2. Types PRX and SA/2 Fluorocarbon (FKM) elastomer is limited to 0°F / -18°C.  
3. Maximum Operating Differential Pressure is 1400 psid / 96.5 bar d for NPS 1 / DN 25 Type EZHSO.

# EZH and EZHSO Series

Pressure Reducing Regulator

FISHER™




Figure 3. Type EZH (Spring-to-Close Version) Operational Schematic




Figure 4. Type EZHSO (Spring-to-Open Version) Operational Schematic






Figure 5. Type EZHOSX Operational Schematic

Table 1. Main Valve Body Size, End Connection Style and Body Rating

MAIN VALVE BODY SIZE		MAIN VALVE BODY MATERIAL	END CONNECTION STYLE	STRUCTURAL DESIGN RATING	
NPS	DN			psig	bar
1 and 2	25 and 50	LCC or WCC Steel	NPT or SWE	1500	103
1, 2, 3, 4, 6, 8 12 X 6	25, 50, 80, 100, 150, 200, 300 X 150		CL150 RF	290	20.0
			CL300 RF	750	51.7
			CL600 RF or BWE	1500	103

Table 2. Outlet Pressure Range

TYPE	OUTLET PRESSURE RANGE		AC (ACCURACY CLASS)		PILOT CONTROL SPRING INFORMATION					
	psig	bar	EZH Series	EZHSO Series	Spring Color	Part Number	Wire Diameter		Free Length	
							In.	cm	In.	cm
PRX/120 PRX/125 PRX/131	14.5 to 26 23 to 44 41 to 80 73 to 123	1.00 to 1.8 1.6 to 3.0 2.8 to 5.5 5.0 to 8.5	2.5%	2.5%	Yellow Green Blue Black	M0255240X12 M0255230X12 M0255180X12 M0255220X12	0.110	0.28	2.16	5.49
	0.126	0.32								
PRX/120-AP PRX/125-AP PRX/131-AP	435 to 1160	30.0 to 80.0	1%	2.5%	Silver Gold Aluminum	M0255210X12 M0255200X12 M0255860X12	0.177	0.45	2.16	5.49
							0.197	0.50	2.00	5.10
							0.236	0.60	2.00	5.10
PRX/120-AP PRX/125-AP PRX/131-AP	435 to 1160	30.0 to 80.0	1%	2.5%	Clear	M0273790X12	0.335	0.85	3.93	10.0

# EZH and EZHSO Series

## Pressure Reducing Regulator

FISHER™

**Table 3. Minimum Differential Pressure**

TYPE	MAIN VALVE BODY SIZE		MINIMUM DIFFERENTIAL			
	NPS	DN	For 90% Capacity		For 100% Capacity	
			psid	bar d	psid	bar d
EZH	1	25	15.2	1.1	15.7	1.1
	2	50	12.0	0.83	13.8	0.95
	3	80	10.6	0.73	12.8	0.88
	4	100	15.8	1.1	16.4	1.1
	6, 8 and 12 X 6	150, 200 and 300 X 600	----	----	14.0	0.98
EZHSO	1	25	55	3.8	55	3.8
	2	50	55	3.8	55	3.8
	3	80	55	3.8	55	3.8
	4	100	----	----	25.6	1.8
	6, 8 and 12 X 6	150, 200 and 300 X 600	----	----	14.0	0.98

**Table 4. Construction Material**

TYPES EZH AND EZHSO MAIN VALVE	
Main Body	WCC Steel or LCC Steel (for EMA Market Only)
Intermediate Flange and Actuator Casing	Steel, ASTM A350 LF2
Diaphragm Plate	Steel, ASTM A105
Diaphragm	Nitrile (NBR) with PVC coating
Main Valve O-ring	Nitrile (NBR) or Fluorocarbon (FKM)
Actuator O-ring	Fluorocarbon (FKM)
Disk	Nitrile (NBR), Fluorocarbon (FKM) or Polyurethane (PU)
PRX SERIES PILOTS	
Body	Steel, ASTM A105
Trim	Stainless steel
Elastomer	Nitrile (NBR) or Fluorocarbon (FKM)
Disk	Polyurethane (PU) or Fluorocarbon (FKM)
TYPE SA/2 PILOT SUPPLY FILTER REGULATOR	
Body	Steel
Diaphragm	Nitrile (NBR) with PVC coating
O-ring/Disk	Nitrile (NBR) or Fluorocarbon (FKM)
TYPE OS2 SLAM-SHUT DEVICE	
Mechanism Box	Aluminum alloy
First and Second Stage Mechanism	WCC Steel
Diaphragm	Nitrile (NBR)
Bellow	316 Stainless steel

**Table 5. Types EZH and EZHSO Main Valve with Standard Cage Regulating Flow Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
1	25	100	564	16.3	34.6	544	15.3	35.5
		80	436	12.3	35.4	423	10.9	38.7
		50	284	8.4	33.7	249	6.3	39.7
		30	172	5.3	32.5	157	4.0	39.1
2	50	100	2278	58.5	38.9	2110	62.9	33.5
		80	1719	47.1	36.5	1609	50.5	31.9
		50	1213	31.0	39.1	1177	33.0	35.6
		30	707	16.9	41.7	718	18.8	38.2
3	80	100	4960	133	37.3	4396	143	30.8
		80	3950	109	36.2	3294	97.2	33.9
		50	2550	63.6	40.1	2069	54.7	37.80
		30	1530	36.7	41.7	1339	39.8	33.6
4	100	100	7250	227	31.9	7170	229	31.3
		80	5750	165	34.8	5630	165	34.1
		50	3510	95.9	36.6	3460	95.5	36.2
		30	2130	56.7	37.6	2080	56.2	37.0
6	150	100	14,430	462	31.2	13,600	433	31.4
		80	11,270	344	32.8	11,260	313	35.9
		50	7150	206	34.7	7120	181	39.3
		30	4100	132	31.1	4070	132	30.8
8	200	100	26,540	720	36.9	25,270	722	35.0
		50	13,990	375	37.3	13,600	374	36.4
		30	7720	202	38.1	7860	205	38.3
		12 X 6	300 X 150	100	30,490	815	37.4	29,270
		50	14,040	359	39.1	13,620	348	39.1
		30	8050	202	39.7	7890	198	39.7

**Table 6. Types EZHOSX and EZHSO-OSX Main Valve with Standard Cage Flow and Sizing Coefficient**

MAIN VALVE BODY SIZE	TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE					2:1 LINE SIZE TO BODY SIZE PIPING						
		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	IEC Sizing Coefficient			C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	IEC Sizing Coefficient		
					X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>				X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
<b>Regulating</b>													
NPS 1 / DN 25	100	560	16.3	34.4	0.75	0.61	0.89	550	17.6	31.3	0.94	0.63	0.89
	80	428	12.0	35.7	0.81	0.52		408	11.9	34.3	0.68	0.53	
	50	282	8.3	33.9	0.73	0.44		245	7.3	33.6	0.26	0.44	
	30	171	5.3	32.3	0.65	0.35		154	4.8	32.1	0.87	0.35	
NPS 2 / DN 50	100	2259	53.5	42.3	0.78	0.61		2092	54.6	38.3	0.86	0.60	
	80	1837	52.0	35.4	0.79	0.55		1762	50.0	35.3	0.92	0.54	
	50	1297	32.9	39.4	0.98	0.45		1301	33.5	38.80	0.95	0.44	
	30	746	17.9	41.7	0.99	0.35		746	18.3	40.80	1.05	0.31	
NPS 3 / DN 80	100	4620	125	37.0	0.87	0.56		4359	142	30.8	0.59	0.56	
	80	3920	106	37.0	0.87	0.52		3266	96.4	33.9	0.72	0.51	
	50	2560	64.9	39.4	0.98	0.41		2052	54.3	37.8	0.90	0.40	
	30	1540	36.8	41.8	0.99	0.31		1328	39.5	33.6	0.71	0.31	
NPS 4 / DN 100	100	7120	209	34.1	0.73	0.61		6920	213	32.5	0.66	0.61	
	80	5920	162	36.5	0.84	0.74		5760	163	35.3	0.78	0.74	
	50	3550	93.3	38.0	0.91	0.76	3420	91.7	37.3	0.88	0.75		
	30	2080	56.4	36.9	0.86	0.78	2060	55.6	37.1	0.87	0.77		
NPS 6 / DN 150	100	13,930	412	33.8	0.72	0.69	13,280	405	32.8	0.68	0.69		
	80	11,230	305	36.8	0.86	0.78	10,600	303	35.0	0.77	0.78		
	50	7150	185	38.7	0.95	0.61	7150	185	38.8	0.95	0.61		
	30	4020	101	39.8	1.00	0.95	4050	102	39.7	1.00	0.95		

- continued -

# EZH and EZHSO Series

## Pressure Reducing Regulator

FISHER™

**Table 6. Types EZHOSX and EZHSO-OSX Main Valve with Standard Cage Flow and Sizing Coefficient (continued)**

MAIN VALVE BODY SIZE	TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE					2:1 LINE SIZE TO BODY SIZE PIPING											
		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	IEC Sizing Coefficient			C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	IEC Sizing Coefficient							
					X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>				X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>					
Wide-Open																		
NPS 1 / DN 25	100	582	16.95	34.34	0.75	0.61	0.89	572	18.3	31.26	0.94	0.63	0.89					
	80	445	12.48	35.66	0.81	0.52		424	12.38	34.25	0.68	0.53						
	50	293	8.66	33.83	0.73	0.44		255	7.59	33.60	0.26	0.44						
	30	178	5.51	32.30	0.65	0.35		160	4.99	32.06	0.87	0.35						
NPS 2 / DN 50	100	2349	55.59	42.26	0.78	0.61		2176	56.75	38.34	0.86	0.60		1832	51.97	35.25	0.92	0.54
	80	1911	54.04	35.36	0.79	0.55		1352	34.87	38.77	0.95	0.44		775	19.01	40.77	1.05	0.31
	50	1348	34.21	39.40	0.98	0.45		4533	147	30.77	0.59	0.56		3397	100	33.89	0.72	0.51
	30	776	18.62	41.68	0.99	0.35		2134	56.46	37.80	0.90	0.40		1381	41.05	33.64	0.71	0.31
NPS 3 / DN 80	100	4805	130	36.96	0.87	0.56		7130	219	32.4	0.66	0.61		5930	168	35.2	0.78	0.74
	80	4077	110	36.98	0.87	0.52		3520	94.5	37.4	0.88	0.75		2120	57.3	37.1	0.87	0.77
	50	2662	67.50	39.44	0.98	0.41		13,678	417	32.8	0.68	0.69		10,918	312	35.0	0.77	0.78
	30	1602	38.27	41.86	0.99	0.31		7365	191	38.8	0.95	0.61		4172	105	39.7	1.00	0.95
NPS 4 / DN 100	100	7330	215	34.0	0.73	0.61	13,678	417	32.8	0.68	0.69	10,918	312	35.0	0.77	0.78		
	80	6100	167	36.5	0.84	0.74	7365	191	38.8	0.95	0.61	4172	105	39.7	1.00	0.95		
	50	3660	96.1	38.0	0.91	0.76												
	30	2140	58.1	36.9	0.86	0.78												
NPS 6 / DN 150	100	14,348	424	33.8	0.72	0.69												
	80	11,567	314	36.8	0.86	0.78												
	50	7365	191	38.7	0.95	0.61												
	30	4141	104	39.8	1.00	0.95												

**Table 7. Types EZH and EZHSO with Standard Cage Wide-Open Flow Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
1	25	100	587	16.95	34.63	566	15.94	35.51
		80	453	12.79	35.42	440	11.37	38.70
		50	295	8.76	33.68	259	6.52	39.72
		30	179	5.51	32.49	163	4.16	39.18
2	50	100	2369	60.89	38.91	2194	65.44	33.53
		80	1788	48.94	36.53	1673	52.52	31.85
		50	1261	32.26	39.09	1224	34.35	35.63
		30	735	17.62	41.71	747	19.57	38.17
3	80	100	5158	138	37.29	4571	149	30.77
		80	4108	113	36.24	3426	101	33.89
		50	2652	66.14	40.10	2152	56.94	37.79
		30	1591	38.17	41.68	1393	41.40	33.65
4	100	100	7470	234	31.6	7390	236	31.4
		80	5920	170	34.8	5800	170	34.2
		50	3620	98.8	36.7	3560	98.4	36.3
		30	2190	58.4	37.3	2140	57.9	37.3
6	150	100	14,870	476	31.2	14,010	446	31.4
		80	11,610	354	32.8	11,600	323	35.9
		50	7370	212	34.7	7340	187	39.3
		30	4230	136	31.1	4200	136	30.8
8	200	100	27,340	742	36.9	26,040	744	35.0
		50	14,410	386	37.3	14,000	385	36.3
		30	7950	209	38.1	8100	212	38.3
12 X 6	300 X 150	100	31,400	839	37.4	30,160	806	37.4
		50	14,460	370	39.1	14,030	359	39.1
		30	8290	208	39.7	8130	204	39.7



**Table 8. Types EZH and EZHSO Main Valve with Standard Cage IEC Sizing Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		Xr	F <sub>D</sub>	F <sub>L</sub>	Xr	F <sub>D</sub>	F <sub>L</sub>
1	25	100	0.61	0.61	0.89	0.80	0.59	0.89
		80	0.72	0.67		0.95	0.63	
		50	0.69	0.80		0.99	0.69	
		30	0.66	0.81		0.97	0.71	
2	50	100	0.73	0.59		0.69	0.61	
		80	0.84	0.68		0.72	0.70	
		50	0.97	0.69		0.84	0.72	
		30	0.99	0.70		0.92	0.74	
3	80	100	0.88	0.58		0.60	0.60	
		80	0.83	0.71		0.73	0.67	
		50	0.99	0.73		0.90	0.68	
		30	0.99	0.72		0.72	0.75	
4	100	100	0.63	0.63	0.62	0.63		
		80	0.76	0.74	0.74	0.74		
		50	0.85	0.77	0.83	0.77		
		30	0.88	0.78	0.88	0.77		
6	150	100	0.62	0.69	0.62	0.69		
		80	0.68	0.78	0.82	0.78		
		50	0.76	0.61	0.98	0.61		
		30	0.61	0.95	0.60	0.95		
8	200	100	0.86	0.69	0.77	0.69		
		50	0.88	0.78	0.83	0.78		
		30	0.92	0.61	0.93	0.61		
12 X 6	300 X 150	100	0.88	0.69	0.88	0.69		
		50	0.96	0.78	0.96	0.78		
		30	1.00	0.61	1.00	0.61		

**Table 9. Whisper Trim™ Cage Regulating Flow and Sizing Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING			IEC SIZING COEFFICIENTS				
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	1:1 Line to Body Size		2:1 Line to Body Size		F <sub>L</sub>
				Xr	F <sub>D</sub>	Xr	F <sub>D</sub>						
2	50	100	1627	42.5	38.3	1539	45.9	33.5	0.82	0.03	0.71	0.03	0.89
		80	1466	37.6	39.0	1389	40.7	34.1	0.90	0.03	0.74	0.03	
		50	1114	28.0	39.8	1099	30.8	35.7	0.99	0.02	0.81	0.02	
		30	689	16.6	41.6	695	18.4	37.7	0.99	0.02	0.90	0.02	
3	80	100	3502	103	34.1	3313	108	30.8	0.59	0.02	0.60	0.02	
		80	2928	81.4	36.0	2774	82.6	33.6	0.72	0.02	0.71	0.02	
		50	1934	49.3	39.2	1908	51.4	37.1	0.95	0.01	0.87	0.01	
		30	1355	32.9	41.2	1366	35.0	39.0	0.99	0.01	0.96	0.01	
4	100	100	5570	179	31.1	5410	178	30.4	0.61	0.02	0.59	0.02	
		80	4860	148	32.8	4730	146	32.4	0.67	0.02	0.66	0.02	
		50	3340	93.4	35.8	3320	93.0	35.7	0.80	0.01	0.79	0.01	
		30	2080	54.3	38.3	2050	55.0	37.3	0.92	0.01	0.88	0.01	
6	150	100	12,860	375	34.3	12,410	373	33.3	0.74	0.01	0.70	0.01	
		80	10,610	295	35.9	10,290	293	35.1	0.82	0.01	0.78	0.01	
		50	7140	191	37.4	7080	191	37.1	0.88	0.01	0.87	0.01	
		30	4040	102	39.8	4020	102	39.6	1.00	0.01	0.99	0.01	
8	200	100	20,620	518	39.8	19,570	598	32.8	1.00	0.01	0.68	0.01	
		50	13,180	333	39.6	12,850	327	39.3	0.99	0.01	0.98	0.01	
		30	7590	193	39.4	7550	191	39.6	0.98	0.01	0.99	0.01	
12 X 6	300 X 150	100	20,000	648	30.9	19,200	622	30.9	0.60	0.01	0.60	0.01	
		50	13,110	330	39.8	12,720	320	39.8	1.00	0.01	1.00	0.01	
		30	7570	190	39.8	7420	186	39.8	1.00	0.01	1.00	0.01	

# EZH and EZHSO Series

Pressure Reducing Regulator

FISHER™

**Table 10. Whisper Trim™ Cage Wide-Open Flow and Sizing Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING			IEC SIZING COEFFICIENTS				F <sub>L</sub>
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	1:1 LINE TO BODY SIZE		2:1 LINE TO BODY SIZE		
								X <sub>T</sub>	F <sub>D</sub>	X <sub>T</sub>	F <sub>D</sub>		
2	50	100	1692	44.2	38.2	1600	47.7	33.5	0.82	0.03	0.71	0.03	0.89
		80	1524	39.1	39.0	1444	42.3	34.1	0.90	0.03	0.74	0.03	
		50	1159	29.1	39.8	1143	31.9	35.8	0.99	0.02	0.81	0.02	
		30	718	17.2	41.7	722	19.2	37.6	0.99	0.02	0.90	0.02	
3	80	100	3642	107	34.1	3445	112	30.7	0.59	0.02	0.60	0.02	
		80	3045	84.7	35.9	2885	85.8	33.6	0.72	0.02	0.71	0.02	
		50	2011	51.3	39.2	1985	53.4	37.1	0.95	0.01	0.87	0.01	
		30	1409	34.2	41.2	1421	36.3	39.1	0.99	0.01	0.96	0.01	
4	100	100	5740	184	31.0	5570	183	30.5	0.61	0.02	0.59	0.02	
		80	5010	152	32.7	4870	150	32.4	0.67	0.02	0.66	0.02	
		50	3440	96.2	35.6	3420	95.8	35.3	0.80	0.01	0.79	0.01	
		30	2140	55.9	38.1	2110	56.7	37.3	0.92	0.01	0.88	0.01	
6	150	100	13,240	386	34.3	12,790	384	33.3	0.74	0.01	0.70	0.01	
		80	10,930	304	35.9	10,600	302	35.1	0.82	0.01	0.78	0.01	
		50	7350	197	37.4	7290	197	37.0	0.88	0.01	0.87	0.01	
		30	4160	105	39.7	4140	105	39.5	1.00	0.01	0.99	0.01	
8	200	100	21,230	534	39.8	20,160	615	32.8	1.00	0.01	0.68	0.01	
		50	13,580	343	39.6	13,240	337	39.3	0.99	0.01	0.98	0.01	
		30	7820	198	39.4	7770	196	39.6	0.98	0.01	0.99	0.01	
12 X 6	300 X 150	100	20,600	668	30.9	19,780	641	30.9	0.60	0.01	0.60	0.01	
		50	13,500	340	39.8	13,100	329	39.8	1.00	0.01	1.00	0.01	
		30	7800	196	39.8	7640	192	39.8	1.00	0.01	1.00	0.01	

**Table 11. Types EZHOSX and EZHSO-OSX Main Valve with Whisper Trim Cage Flow and Sizing Coefficient**

MAIN VALVE BODY SIZE		TRIM, % OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING			IEC SIZING COEFFICIENT				F <sub>L</sub>
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>t</sub>	1:1 Line to Body Size		2:1 Line to Body Size		
								X <sub>T</sub>	F <sub>D</sub>	X <sub>T</sub>	F <sub>D</sub>		
<b>Regulating</b>													
2	50	100	1494	39.9	37.4	1516	41.0	37.0	0.89	0.03	0.87	0.03	0.89
		80	1473	39.3	37.5	1482	39.5	37.5	0.89	0.03	0.89	0.03	
		50	1171	30.0	39.0	1169	29.6	39.5	0.96	0.02	0.99	0.02	
		30	721	17.0	42.4	718	18.2	39.4	0.99	0.02	0.98	0.02	
3	80	100	3472	102	34.1	3285	107	30.8	0.73	0.02	0.59	0.02	
		80	2903	80.7	36.0	2751	81.9	33.6	0.82	0.02	0.71	0.02	
		50	1918	48.9	39.2	1892	51.0	37.1	0.97	0.01	0.86	0.01	
		30	1344	32.6	41.2	1354	34.7	39.0	0.99	0.01	0.96	0.01	
4	100	100	5490	167	32.9	5320	168	31.7	0.68	0.02	0.63	0.02	
		80	4960	144	34.4	4810	141	34.1	0.74	0.02	0.73	0.02	
		50	3270	89.9	36.4	3190	87.7	36.4	0.83	0.01	0.86	0.01	
		30	2040	54.4	37.5	2020	53.7	37.6	0.89	0.01	0.90	0.01	
6	150	100	12,240	353	34.7	11,840	348	34.0	0.76	0.01	0.73	0.01	
		80	9970	275	36.3	9650	275	35.0	0.83	0.01	0.78	0.01	
		50	6970	181	38.6	6780	180	37.6	0.94	0.01	0.89	0.01	
		30	3990	100	39.8	3950	99.9	39.6	1.00	0.01	0.99	0.01	
<b>Wide-Open</b>													
2	50	100	1554	41.5	37.4	1577	42.6	37.1	0.89	0.03	0.87	0.03	0.89
		80	1532	40.9	37.5	1542	41.1	37.5	0.89	0.03	0.89	0.03	
		50	1218	31.2	39.0	1216	30.8	39.4	0.96	0.02	0.99	0.02	
		30	750	17.7	42.3	747	19.0	39.3	0.99	0.02	0.98	0.02	
3	80	100	3611	106	34.1	3416	111	30.7	0.73	0.03	0.59	0.03	
		80	3020	84.0	35.9	2861	85.2	33.6	0.82	0.03	0.71	0.03	
		50	1994	50.9	39.1	1968	53.0	37.1	0.97	0.02	0.86	0.02	
		30	1397	33.9	41.2	1409	36.1	39.0	0.99	0.02	0.96	0.02	
4	100	100	5650	172	32.9	5480	173	31.6	0.68	0.02	0.63	0.02	
		80	5110	148	34.2	4950	145	34.1	0.74	0.02	0.73	0.02	
		50	3370	92.6	36.3	3290	89.7	36.8	0.83	0.01	0.86	0.01	
		30	2100	56.0	37.6	2080	55.3	37.6	0.89	0.01	0.90	0.01	
6	150	100	12,610	363	34.7	12,200	359	34.0	0.76	0.01	0.73	0.01	
		80	10,270	283	36.3	9940	284	35.0	0.83	0.01	0.78	0.01	
		50	7190	186	38.6	6990	186	37.6	0.94	0.01	0.89	0.01	
		30	4120	104	39.8	4080	103	39.8	1.00	0.01	0.99	0.01	



**Table 12. Capacities for Types EZH and EZHSO with PRX Series Pilot and Type SA/2 Pilot Supply Filter Regulator**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING													
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 12 X 6 / DN 300 X 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
30	2.1	15	1.0	27	0.7	112	3.0	229	6.1	365	9.8	745	19.9	1233	33.0	1403	37.6
40	2.8	15 25	1.0 1.7	37 31	0.9 0.8	149 128	4.0 3.4	309 260	8.2 6.9	483 420	13.0 11.3	980 858	26.2 23.0	1663 1403	44.6 37.6	1896 1596	50.8 42.7
50	3.4	15 25 35	1.0 1.7 2.4	45 41 35	1.2 1.1 0.9	183 169 142	4.9 4.5 3.8	382 347 288	10.2 9.3 7.7	588 550 469	15.8 14.8 12.6	1189 1118 959	31.8 29.9 25.7	2056 1870 1556	55.1 50.1 41.7	2347 2130 1768	62.9 57.1 47.4
60	4.1	16 20 30 45	1.1 1.3 2.0 3.1	53 52 48 38	1.4 1.3 1.3 1.0	214 211 197 156	5.7 5.6 5.3 4.2	450 440 406 314	12.0 11.8 10.8 8.4	687 678 641 513	18.4 18.2 17.2 13.8	1384 1371 1302 1051	37.1 36.7 34.9 28.2	2420 2368 2186 1695	64.8 63.5 58.6 45.4	2765 2703 2490 1926	74.1 72.4 66.7 51.6
75	5.2	22 30 40 60	1.5 2.0 2.7 4.1	63 61 58 42	1.7 1.6 1.5 1.1	257 250 235 174	6.9 6.7 6.3 4.6	541 520 483 349	14.5 13.9 12.9 9.3	825 806 764 574	22.1 21.6 20.5 15.4	1662 1632 1553 1177	44.5 43.7 41.6 31.5	2908 2798 2601 1886	77.9 75.0 69.7 50.5	3322 3192 2963 2142	89.0 85.5 79.4 57.4
100	6.9	32 40 50 85	2.2 2.7 3.4 5.8	81 79 76 49	2.2 2.1 2.0 1.3	329 322 309 200	8.8 8.6 8.3 5.3	692 672 639 401	18.5 18.0 17.1 10.7	1055 1038 1003 663	28.3 27.9 26.9 17.8	2126 2099 2035 1362	57.0 56.2 54.5 36.5	3722 3616 3441 2167	99.7 96.9 92.2 58.1	4251 4126 3921 2460	114 111 105 65.9
125	8.6	43 50 75 110	2.9 3.4 5.2 7.5	99 97 88 55	2.7 2.6 2.4 1.4	400 394 356 224	10.7 10.6 9.5 6.0	841 824 730 447	22.6 22.1 19.6 12.0	1283 1269 1163 742	34.4 34.1 31.2 19.9	2588 2565 2368 1525	69.3 68.7 63.4 40.9	4523 4432 3939 2417	121 119 106 64.8	5166 5058 4484 2743	138 136 120 73.5
150	10.3	52 75 95 130	3.5 5.2 6.5 8.9	117 110 101 68	3.1 2.9 2.7 1.8	473 449 411 278	12.7 12.0 11.0 7.5	994 929 841 557	26.6 24.9 22.5 14.9	1515 1453 1345 923	40.7 39.0 36.1 24.8	3054 2947 2740 1895	81.8 79.0 73.4 50.8	5348 5004 4535 3011	143 134 122 80.7	6109 5704 5162 3418	164 153 138 91.6
200	13.8	73 100 125 185	5.0 6.9 8.6 12.8	152 145 133 69	4.1 3.9 3.6 1.8	616 588 544 283	16.5 15.8 14.6 7.6	1295 1219 1113 563	34.7 32.7 29.8 15.1	1974 1903 1775 940	53.0 51.1 47.7 25.2	3979 3858 3616 1935	107 103 96.9 51.8	6963 6564 6004 3046	187 176 161 81.6	7953 7484 6835 3456	213 200 183 92.6
300	20.7	115 150 200 275	7.9 10.3 13.8 19.0	222 213 190 107	6.0 5.7 5.1 2.9	902 866 773 440	24.2 23.2 20.7 11.8	1895 1798 1579 877	50.8 48.2 42.3 23.5	2892 2802 2532 1462	77.6 75.2 67.9 39.2	5830 5678 5162 3007	156 152 138 80.5	10,193 9683 8517 4741	273 259 228 127	11,641 11,042 9691 5379	312 296 260 144
400	27.6	155 200 250 300 350	10.7 13.8 17.2 20.7 24.1	293 282 261 227 171	7.9 7.6 7.0 6.1 4.6	1189 1145 1061 926 698	31.9 30.7 28.4 24.8 18.7	2500 2377 2176 1876 1399	67.0 63.7 58.3 50.3 37.5	3813 3701 3463 3047 2316	102 99.3 92.9 81.8 62.2	7685 7497 7048 6230 4757	206 201 189 167 127	13,446 12,801 11,733 10,126 7559	360 343 314 271 202	15,357 14,598 13,358 11,511 8580	411 391 358 308 230
500	34.5	196 250 300 400	13.5 17.2 20.7 27.6	364 350 330 259	9.8 9.4 8.8 7	1476 1423 1345 1058	39.6 38.1 36 28.4	3103 2956 2765 2134	83.2 79.2 74.1 57.2	4732 4600 4379 3492	127 123 117 93.6	9538 9315 8905 7153	256 250 239 192	16,687 15,918 14,905 11,522	447 426 399 309	19,060 18,154 16,977 13,091	511 486 455 351
600	41.4	250 300 350 450 500	17.2 20.7 24.1 31 34.5	432 419 400 338 288	11.6 11.2 10.7 9.1 7.7	1752 1701 1626 1378 1176	47 45.6 43.6 37 31.5	3675 3535 3351 2793 2364	98.5 94.7 89.8 74.9 63.4	5628 5498 5289 4535 3889	151 147 142 122 104	11,356 11,134 10,748 9273 7976	304 298 288 248 214	19,771 19,035 18,058 15,079 12,772	530 510 484 404 342	22,575 21,709 20,572 17,142 14,505	605 582 551 459 389
700	48.3	250 300 350 400 550 600	17.2 20.7 24.1 27.6 37.9 41.4	510 501 487 469 371 314	13.7 13.4 13.1 12.6 10 8.4	2068 2032 1979 1907 1514 1283	55.4 54.5 53 51.1 40.6 34.4	4366 4256 4114 3934 3058 2575	117 114 110 105 82 69	6607 6530 6397 6196 4992 4251	177 175 171 166 134 114	13,294 13,181 12,952 12,583 10,221 8725	356 353 347 337 274 234	23,472 22,898 22,152 21,200 16,513 13,913	629 613 593 568 442 373	26,824 26,142 25,264 24,155 18,764 15,796	719 700 677 647 503 423

- continued -

# EZH and EZHSO Series

Pressure Reducing Regulator

FISHER™

**Table 12. Capacities for Types EZH and EZHSO with PRX Series Pilot and Type SA/2 Pilot Supply Filter Regulator (continued)**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING													
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 12 X 6 / DN 300 X 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
800	55.2	300	20.7	579	15.5	2349	63	4951	133	7517	202	15,135	405	26,623	713	30,418	815
		350	24.1	569	15.2	2311	62	4836	130	7431	199	15,005	402	26,023	697	29,706	796
		400	27.6	556	14.9	2257	60.5	4693	126	7295	196	14,770	396	25,268	677	28,820	772
		450	31	538	14.4	2187	58.6	4517	121	7100	190	14,413	386	24,334	652	27,731	743
		500	34.5	515	13.8	2096	56.2	4301	115	6835	184	13,910	373	23,186	621	26,401	707
		609	42	441	11.8	1800	48.2	3644	97.7	5926	159	12,121	325	19,674	527	22,363	599
		650	44.8	401	10.7	1639	44	3302	88.5	5414	145	11,094	297	17,836	478	20,261	543
900	62.1	350	24.1	649	17.4	2630	70.5	5535	148	8424	226	16,972	455	29,767	797	34,004	911
		400	27.6	638	17.1	2589	69.4	5416	145	8331	224	16,827	451	29,145	781	33,268	891
		500	34.5	606	16.2	2466	66.1	5098	137	8003	214	16,241	435	27,465	736	31,302	839
		600	41.4	557	15	2271	60.9	4641	124	7428	199	15,141	406	25,031	671	28,487	763
		800	55.2	361	9.7	1475	39.5	2952	79.1	4897	131	10,062	270	15,955	427	18,108	485
1000	69	350	24.1	726	19.5	2942	79	6219	167	9391	252	18,886	506	33,433	896	38,214	1024
		400	27.6	718	19.2	2910	78	6118	164	9330	250	18,805	504	32,906	882	37,584	1007
		500	34.5	693	18.6	2814	75.4	5851	157	9092	244	18,406	493	31,502	844	35,930	963
		600	41.4	654	17.5	2662	71.3	5477	147	8665	232	17,615	472	29,519	791	33,624	901
		800	55.2	514	13.8	2097	56.2	4231	113	6922	186	14,179	380	22,851	612	25,962	696
1100	75.8	350	24.1	802	21.5	3248	87	6894	185	10,342	277	20,766	556	37,045	992	42,363	1135
		450	31	786	21.1	3190	85.5	6700	180	10,234	275	20,636	553	36,041	966	41,160	1103
		500	34.5	775	20.8	3147	84.3	6576	176	10,131	272	20,470	548	35,388	948	40,388	1082
		600	41.4	744	20	3025	81.1	6259	168	9807	263	19,891	533	33,718	903	38,435	1030
		800	55.2	635	17	2589	69.4	5261	141	8504	228	17,374	465	28,390	761	32,284	865
		1000	68.9	402	10.8	1646	44.1	3287	88.1	5469	147	11,245	301	17,766	476	20,159	540
		1200	82.7	350	24.1	877	24	3551	95.2	7562	203	11,281	302	22,620	606	40,621	1088
500	34.5	855	23	3470	93	7282	195	11,137	298	11,137	298	22,465	602	39,174	1049	44,733	1198
600	41.4	829	22.2	3370	90.3	7008	188	10,888	292	10,888	292	22,043	591	37,735	1011	43,040	1153
800	55.2	741	19.9	3020	80.9	6172	165	9876	265	20,129	539	33,288	892	37,883	892	37,883	1015
1100	75.8	422	11.3	1724	46.2	3442	92.2	3442	92.2	5734	154	11,792	316	18,607	498	21,111	566
1300	89.6	350	24.1	952	26	3852	103	8224	220	12,211	327	24,457	655	44,169	1183	50,547	1354
		500	34.5	934	25	3786	101	7976	214	12,121	325	24,412	654	42,889	1149	48,999	1313
		600	41.4	912	24.4	3704	99.3	7735	207	11,930	320	24,110	646	41,627	1115	47,505	1273
		800	55.2	839	22.5	3414	91.5	7014	188	11,125	298	22,628	606	37,812	1013	43,061	1154
		1160	80	513	13.7	2096	56.2	4193	112	6958	187	14,299	383	22,661	607	25,718	689
1400	96.5	350	24.1	1026	27.5	4151	111	8883	238	13,140	352	26,280	704	47,696	1278	54,601	1463
		500	34.5	1011	27.1	4098	110	8660	232	13,088	351	26,325	705	46,552	1247	53,206	1425
		600	41.4	993	26.6	4029	108	8444	226	12,942	347	26,118	700	45,432	1217	51,872	1390
		800	55.2	930	25	3785	101	7812	209	12,294	330	24,961	669	42,094	1128	47,966	1285
		1160	80	674	18.1	2753	73.8	5540	148	9102	244	18,663	500	29,923	802	33,986	910
1480	102	350	24.1	1085	29.1	4388	118	9408	252	13,883	372	27,731	743	50,507	1353	57,831	1549
		500	34.5	1072	28.7	4344	116	9201	247	13,852	371	27,837	746	49,455	1325	56,539	1515
		600	41.4	1056	28.3	4284	115	9004	241	13,737	369	27,692	742	48,428	1297	55,311	1482
		800	55.2	1001	26.8	4070	109	8428	226	13,188	354	26,744	716	45,396	1216	51,751	1386
		1160	80	782	21	3191	85.5	6447	173	10,518	282	21,532	577	34,812	933	39,561	1060





**Table 13. Capacities for Types EZHOSX and EZHSO-OSX with PRX Series Pilot and Type SA/2 Pilot Supply Filter Regulator**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING									
				NPS 1 / DN 25 Body		NPS 2 / DN 50 Body		NPS 3 / DN 80 Body		NPS 4 / DN 100 Body		NPS 6 / DN 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
30	2.1	15	1.0	27	0.7	108	2.9	214	5.7	351	9.4	686	18.4
40	2.8	15	1.0	36	0.9	145	3.9	289	7.7	467	12.5	914	24.5
		25	1.7	31	0.8	124	3.3	244	6.5	401	10.8	785	21.0
50	3.5	15	1.0	45	1.2	179	4.8	357	9.5	572	15.4	1120	30.0
		25	1.7	41	1.1	164	4.4	325	8.7	529	14.2	1035	27.7
		35	2.4	35	0.9	138	3.6	270	7.2	447	12.0	873	23.4
60	4.1	16	1.1	52	1.4	210	5.6	421	11.2	669	18.0	1312	35.1
		20	1.3	52	1.4	206	5.5	412	11.0	659	17.7	1291	34.6
		30	2.0	48	1.2	192	5.1	380	10.1	617	16.6	1208	32.4
		45	3.1	38	1.0	150	4.0	294	7.9	489	13.1	955	25.6
75	5.8	22	1.5	63	1.7	252	6.7	505	13.5	804	21.6	1576	42.2
		30	2.0	61	1.6	244	6.5	486	13.0	781	21.0	1530	41.0
		40	2.7	57	1.5	228	6.1	452	12.1	735	19.7	1439	38.5
		60	4.1	42	1.1	167	4.4	327	8.7	545	14.6	1065	28.5
100	6.9	32	2.2	81	2.2	323	8.6	647	17.3	1029	27.6	2016	54.0
		40	2.7	79	2.1	315	8.4	628	16.8	1008	27.0	1973	52.9
		50	3.4	75	2.0	301	8.0	598	16.0	968	26.0	1895	50.8
		85	5.8	49	1.3	193	5.1	376	10.1	629	16.9	1228	32.9
125	8.6	43	2.9	98	2.6	392	10.5	786	21.1	1251	33.5	2452	65.7
		50	3.4	96	2.5	386	10.3	770	20.6	1233	33.0	2415	64.7
		75	5.1	87	2.3	346	9.2	684	18.3	1117	30.0	2186	58.5
		110	7.5	54	1.4	215	5.7	420	11.2	703	18.8	1372	36.8
150	10.3	52	3.5	116	3.1	464	12.4	929	24.9	1478	39.6	2897	77.6
		75	5.1	110	2.9	437	11.7	869	23.3	1405	37.7	2750	73.7
		95	6.5	100	2.7	399	10.7	788	21.1	1290	34.6	2522	67.6
		130	8.9	68	1.8	268	7.2	523	14.0	875	23.5	1708	45.8
200	13.8	73	5.0	151	4.0	604	16.2	1210	32.4	1925	51.6	3773	101
		100	6.9	144	3.9	573	15.4	1140	30.6	1841	49.3	3604	96.5
		125	8.6	133	3.6	528	14.2	1043	28.0	1705	45.7	3334	89.3
		185	12.8	69	1.8	272	7.3	529	14.1	889	23.8	1735	46.5
300	20.7	115	7.9	221	5.9	884	23.7	1771	47.5	2819	75.7	5525	148
		150	10.3	212	5.7	845	22.6	1682	45.1	2712	72.8	5310	142
		200	13.8	188	5.0	750	20.1	1479	39.6	2426	65.1	4744	127
		275	19.0	107	2.9	422	11.3	823	22.1	1383	37.1	2699	72.3
400	27.6	155	10.7	291	7.8	1166	31.2	2337	62.6	3718	99.8	7286	195
		200	13.8	280	7.5	1117	30.0	2224	59.6	3583	96.2	7016	188
		250	17.2	259	6.9	1031	27.6	2038	54.6	3327	89.3	6508	174
		300	20.7	225	6.0	895	24.0	1758	47.1	2907	78.0	5681	152
		350	24.1	170	4.6	672	18.0	1312	35.2	2196	58.9	4287	115
500	34.5	196	13.5	361	9.7	1447	38.8	2900	77.7	4614	124	9042	242
		250	17.2	348	9.3	1389	37.2	2766	74.1	4454	119	8721	234
		300	20.7	328	8.8	1308	35.1	2589	69.4	4215	113	8246	221
		400	27.6	257	6.9	1021	27.4	2001	53.6	3323	89.2	6492	174
600	41.4	250	17.2	429	11.5	1717	46	3436	92.1	5480	147	10,737	288
		300	20.7	416	11.1	1661	44.5	3307	88.6	5325	143	10,426	279
		350	24.1	397	10.6	1583	42.4	3137	84.1	5097	137	9973	267
		450	31	335	9	1333	35.7	2618	70.2	4328	116	8458	227
		500	34.5	286	7.7	1133	30.4	2217	59.4	3695	99	7217	193
700	48.3	250	17.2	507	13.6	2031	54.4	4079	109	6460	173	12,664	339
		300	20.7	497	13.3	1990	53.4	3979	107	6354	170	12,449	333
		350	24.1	484	13	1933	51.8	3849	103	6196	166	12,131	325
		400	27.6	465	12.5	1857	49.8	3683	98.7	5975	160	11,692	313
		550	37.4	368	9.9	1462	39.2	2867	77	4755	127	9291	249
		600	41.4	312	8.4	1236	33.1	2415	64.7	4034	108	7877	211
800	55.2	300	20.7	575	15.4	2306	61.8	4627	124	7341	197	14,390	385
		350	24.1	565	15.1	2262	60.6	4522	121	7227	194	14,158	379
		400	27.6	552	14.8	2204	59.1	4390	118	7066	189	13,836	371
		450	31	534	14.3	2130	57.1	4227	113	6851	184	13,408	359
		500	34.5	511	13.7	2036	54.6	4027	108	6571	176	12,853	344
		609	42	438	11.7	1740	46.6	3416	91.5	5652	151	11,045	296
		650	44.8	399	10.7	1581	42.4	3097	83	5149	138	10,059	269
900	62.1	350	24.1	644	17.3	2580	69.1	5173	139	8220	220	16,111	432
		400	27.6	633	17	2534	68	5064	136	8099	217	15,867	425
		500	34.5	602	16.1	2403	64.4	4771	128	7726	207	15,121	405
		600	41.4	553	14.8	2203	59	4347	117	7123	191	13,930	373
		800	55.2	358	9.6	1420	38.1	2770	74.2	4639	124	9057	243

# EZH and EZHSO Series


## Pressure Reducing Regulator




**Table 13. Capacities for Types EZHOSX and EZHSO-OSX with PRX Series Pilot and Type SA/2 Pilot Supply Filter Regulator (continued)**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING									
				NPS 1 / DN 25 Body		NPS 2 / DN 50 Body		NPS 3 / DN 80 Body		NPS 4 / DN 100 Body		NPS 6 / DN 150	
psig	bar	psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
1000	69	350	24.1	721	19.3	2891	77.5	5811	156	9189	246	18,017	483
		400	27.6	712	19.1	2854	76.5	5719	153	9097	244	17,829	478
		500	34.5	688	18.4	2748	73.6	5473	146	8808	236	17,246	462
		600	41.4	649	17.4	2589	69.4	5128	137	8343	224	16,322	437
		800	55.2	510	13.7	2025	54.3	3968	106	6589	177	12,872	345
1100	75.8	350	24.1	796	21.3	3197	85.7	6439	173	10,142	272	19,892	533
		450	31	781	20.9	3127	83.8	6263	168	9974	267	19,545	524
		500	34.5	770	20.6	3079	82.5	6149	165	9844	264	19,282	517
		600	41.4	739	19.8	2948	79	5858	157	9474	254	18,543	497
		800	55.2	630	16.9	2506	67.2	4930	132	8128	218	15,887	426
1000	69	400	10.7	1582	42.4	3084	82.7	5176	139	10,103	271		
1200	82.7	350	24.1	871	23.3	3500	93.8	7061	189	11,084	297	21,745	583
		500	34.5	849	22.8	3401	91.1	6807	182	10,894	292	21,259	570
		600	41.4	824	22.1	3291	88.2	6556	176	10,549	283	20,656	553
		800	55.2	736	19.7	2929	78.5	5781	155	9472	254	18,522	496
		1100	75.8	419	11.2	1658	44.4	3230	86.6	5424	145	10,588	284
1300	89.6	350	24.1	945	25.3	3800	102	7678	206	12,018	322	23,582	632
		500	34.5	927	24.8	3716	99.6	7454	200	11,833	317	23,194	621
		600	41.4	906	24.3	3623	97.1	7233	194	11,587	311	22,696	608
		800	55.2	833	22.3	3319	88.9	6568	176	10,702	287	20,936	561
		1160	80	509	13.6	2017	54.1	3934	105	6591	177	12,868	345
1400	96.5	350	24.1	1019	27.3	4099	110	8292	222	12,946	347	25,408	681
		500	34.5	1004	26.9	4027	108	8091	217	12,802	343	25,099	672
		600	41.4	986	26.4	3946	106	7895	212	12,598	338	24,684	661
		800	55.2	924	24.8	3686	98.8	7312	196	11,858	318	23,206	622
		1160	80	669	18	2655	71.2	5195	139	8651	232	16,897	453
1480	102	350	24.1	1078	28.9	4337	116	8781	235	13,685	367	26,861	720
		500	34.5	1065	28.5	4273	115	8596	230	13,568	364	26,606	713
		600	41.4	1049	28.1	4201	113	8416	226	13,392	359	26,246	703
		800	55.2	994	26.6	3968	106	7887	211	12,746	342	24,950	668
		1160	80	776	20.8	3082	82.6	6045	162	10,021	269	19,579	525
1000	69	350	24.1	721	19.3	2891	77.5	5811	156	9189	246	18,017	483
		400	27.6	712	19.1	2854	76.5	5719	153	9097	244	17,829	478
		500	34.5	688	18.4	2748	73.6	5473	146	8808	236	17,246	462
		600	41.4	649	17.4	2589	69.4	5128	137	8343	224	16,322	437
		800	55.2	510	13.7	2025	54.3	3968	106	6589	177	12,872	345
1100	75.8	350	24.1	796	21.3	3197	85.7	6439	173	10,142	272	19,892	533
		450	31	781	20.9	3127	83.8	6263	168	9974	267	19,545	524
		500	34.5	770	20.6	3079	82.5	6149	165	9844	264	19,282	517
		600	41.4	739	19.8	2948	79	5858	157	9474	254	18,543	497
		800	55.2	630	16.9	2506	67.2	4930	132	8128	218	15,887	426
1000	69	400	10.7	1582	42.4	3084	82.7	5176	139	10,103	271		
1200	82.7	350	24.1	871	23.3	3500	93.8	7061	189	11,084	297	21,745	583
		500	34.5	849	22.8	3401	91.1	6807	182	10,894	292	21,259	570
		600	41.4	824	22.1	3291	88.2	6556	176	10,549	283	20,656	553
		800	55.2	736	19.7	2929	78.5	5781	155	9472	254	18,522	496
		1100	75.8	419	11.2	1658	44.4	3230	86.6	5424	145	10,588	284
1300	89.6	350	24.1	945	25.3	3800	102	7678	206	12,018	322	23,582	632
		500	34.5	927	24.8	3716	99.6	7454	200	11,833	317	23,194	621
		600	41.4	906	24.3	3623	97.1	7233	194	11,587	311	22,696	608
		800	55.2	833	22.3	3319	88.9	6568	176	10,702	287	20,936	561
		1160	80	509	13.6	2017	54.1	3934	105	6591	177	12,868	345
1400	96.5	350	24.1	1019	27.3	4099	110	8292	222	12,946	347	25,408	681
		500	34.5	1004	26.9	4027	108	8091	217	12,802	343	25,099	672
		600	41.4	986	26.4	3946	106	7895	212	12,598	338	24,684	661
		800	55.2	924	24.8	3686	98.8	7312	196	11,858	318	23,206	622
		1160	80	669	18	2655	71.2	5195	139	8651	232	16,897	453
1480	102	350	24.1	1078	28.9	4337	116	8781	235	13,685	367	26,861	720
		500	34.5	1065	28.5	4273	115	8596	230	13,568	364	26,606	713
		600	41.4	1049	28.1	4201	113	8416	226	13,392	359	26,246	703
		800	55.2	994	26.6	3968	106	7887	211	12,746	342	24,950	668
		1160	80	776	20.8	3082	82.6	6045	162	10,021	269	19,579	525





TYPES EZH AND EZHSO



TYPE EZHSOX

Figure 6. Dimensions

Table 14. Type EZH/EZHSO Dimension

BODY SIZE, NPS / DN	DIMENSION, In. / mm											
	A				C	D (Maximum)	E	F	G	H	J	R
	NPT or SWE	CL150 RF	CL300 RF	CL600 RF or BWE								
1 / 25	8.25 / 210	7.25 / 184	7.75 / 197	8.25 / 210	1.50 / 38.1	2.10 / 53	12.3 / 311	13.05 / 331	11.10 / 282	5.10 / 130	8.25 / 210	3.5 / 88.9
2 / 50	11.25 / 286	10.0 / 254	10.50 / 267	11.25 / 286	1.50 / 38.1	3.10 / 79	14 / 356	14.75 / 375	11.30 / 287	6.50 / 165	7.75 / 197	4.5 / 114
3 / 80	----	11.75 / 298	12.50 / 317	13.25 / 337	2.00 / 50.8	3.81 / 97	16 / 406	15.36 / 390	16.75 / 425	8.00 / 203	13.25 / 337	6.0 / 152
4 / 100	----	13.9 / 353	14.5 / 368	15.5 / 394	2.00 / 50.8	5.06 / 129	18.3 / 464	15.85 / 403	16.8 / 427	10.03 / 255	5.5 / 140	7.5 / 191
6 / 150	----	17.75 / 451	18.62 / 473	20 / 508	2.75 / 70	5.31 / 135	17 / 432	19.25 / 489	25 / 635	13 / 330	18 / 457	8.7 / 221
8 / 200	----	21.38 / 543	22.38 / 568	24 / 610	2.75 / 70	8.25 / 210	17 / 432	19.25 / 489	28.5 / 724	13 / 330	18 / 457	8.7 / 221
12 X 6 / 300 X 150	----	29 / 737	30.5 / 775	32.25 / 819	2.75 / 70	10 / 254	17 / 432	19.25 / 489	28.5 / 724	13 / 330	18 / 457	8.7 / 221

Table 15. Type EZHSOX/EZHSO-OSX Dimension

BODY SIZE		DIMENSION WITH SLAM-SHUT													
		D		H		M <sup>(1)</sup>				N					
						Diaphragm		Piston		Diaphragm		Piston		Bellow	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	25	12.0	305	9.8	249	6.4	163	2.8	71	6.9	175	8.0	203	8.8	224
2	50	13.0	330	10.4	264										
3	80	14.4	366	11.8	300										
4	100	16.8	427	13.6	346										
6	150	15.6	359	13.0	330										

1. Type 71 BMS with a diaphragm has an M dimension of 2.80 in. / 71 mm.

# EZH and EZHSO Series

Pressure Reducing Regulator

FISHER™

Table 16. Approximate Weight

BODY SIZE		APPROXIMATE SHIPPING WEIGHTS					
		Flanged		NPT, SWE and BWE		For Type OSX	
NPS	DN	lbs	kg	lbs	kg	lbs	kg
1	25	87	39	77	35	Add 17	Add 8
2	50	150	68	136	62	Add 30	Add 14
3	80	410	186	390	177	Add 41	Add 19
4	100	514	234	433	197	Add 57	Add 26
6	150	1460	662	1400	635	Add 74	Add 34
8	200	1875	850	1805	819	----	----
12 X 6	300 X 150	2050	930	1970	894	----	----

## Ordering Guide

### Type and Body Material (Select One)

#### WCC Steel

- Type EZH (Spring-to-Close Version)\*\*\*
- Type EZHSO (Spring-to-Open Version)\*\*\*

#### LCC Steel

- Type EZHOSX (Spring-to-Close Version with Slam shut)\*\*\*
- Type EZHSO-OSX (Spring-to-Open Version with Slam shut)\*\*\*

### Body Size (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 / DN 200\*\*\*
- NPS 12 x 6 / DN 300 x 150\*\*\*

### Body Material and End Connection Style (Select One)

#### WCC Steel (Types EZH and EZHSO Only)

- NPT (1 or 2 NPT only)\*\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- SWE (Available for NPS 1 and 2 / DN 25 and 50 Body Sizes only)\*\*
- BWE\*\*
- PN 16/40 (For NPS 1 and 2 / DN 25 and 50 Body Sizes Only)\*\*
- PN 25/40 (For NPS 3 / DN 80 Body Size only)\*\*

#### LCC Steel (Types EZHOSX and EZHSO-OSX Only)

- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*

### Main Valve Disk and O-ring Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*
- Polyurethane (PU)\*\*\*

### Pilot Type (Select One)

- Type PRX/120\*\*\*
- Type PRX/120-AP\*\*\*
- Type PRX/125 (monitor override pilot)\*\*\*
- Type PRX/125-AP (monitor override pilot)\*\*\*

### Outlet Pressure Range (Select One)

#### Type PRX/120 or PRX/125 Pilot

- 14.5 to 26 psig / 1.00 to 1.8 bar, Yellow\*\*\*
- 23 to 44 psig / 1.6 to 3.0 bar, Green\*\*\*
- 41 to 80 psig / 2.8 to 5.5 bar, Blue\*\*\*
- 73 to 123 psig / 5.0 to 8.5 bar, Black\*\*\*
- 116 to 210 psig / 8.0 to 14.5 bar, Silver\*\*\*
- 203 to 334 psig / 14.0 to 23.0 bar, Gold\*\*\*
- 319 to 435 psig / 22.0 to 30.0 bar, Aluminum\*\*\*

#### Type PRX/120-AP or PRX/125-AP Pilot

- 435 to 1160 psig / 30.0 to 80.0 bar, Clear\*\*\*

### Type SA/2 Elastomer Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Pilot Elastomer Material (Select One)

- Nitrile (NBR)/Polyurethane (PU) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Whisper Trim™ Cage Construction (Optional) (Not available to NPS 1 / DN 25 Body Size)

- Yes\*\*\*

- continued -

## Ordering Guide (continued)

Travel Indicator (Optional)	
<input type="checkbox"/> Yes***	
<input type="checkbox"/> No***	

Pre-piped Pilot Supply (Optional)	
<input type="checkbox"/> Yes***	

Slam-Shut Trip Pressure Setting (Select One)	
<b>Overpressure Protection Only</b>	
<input type="checkbox"/> Supply setpoint required _____	
<b>Underpressure Protection Only</b>	
<input type="checkbox"/> Supply setpoint required _____	
<b>Overpressure Protection and Underpressure Protection</b>	
<input type="checkbox"/> Supply overpressure setpoint required _____	
<input type="checkbox"/> Supply underpressure setpoint required _____	
<b>Overpressure Protection, Overpressure Protection and Underpressure Protection</b>	
<input type="checkbox"/> Supply overpressure setpoint required _____	
<input type="checkbox"/> Supply overpressure setpoint required _____	
<input type="checkbox"/> Supply underpressure setpoint required _____	

Explosion-Proof Limit Switch (Optional)	
<input type="checkbox"/> Yes***	

Main Valve Spare Parts Kit (Optional)	
<input type="checkbox"/> Yes, send one disk parts kit to match this order.	
<input type="checkbox"/> Yes, send one full parts kit to match this order.	

Pilot Spare Parts Kit (Optional)	
<input type="checkbox"/> Yes, send one spare parts kit to match this order.	

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Cutting the supply pressure to a pilot-operated regulator reduces the regulator gain or sensitivity and, thus, may improve regulator stability. (This can only be used with two path control.)

# Type EZH Relief

## Relief Valve or Backpressure Regulator

FISHER™

### Introduction

Type EZH is an accurate pilot-operated, pressure-balanced, soft-seated relief valve or backpressure regulator. It is designed for use in high pressure natural gas transmission/city gate stations, large capacity distribution systems and power plant feeds. It provides smooth and reliable operation, tight shutoff and long life.

The Type EZH relief valve or backpressure regulator includes a Type PRX/182 pilot mounted on the EZH Series main valves for relief valve or backpressure regulator applications.

### Body Sizes, End Connection Styles and Pressure Ratings<sup>(1)</sup>

See Table 1

### Maximum Allowable Pressures<sup>(1)</sup>

#### Inlet Pressure:

1500 psig / 103 bar

Outlet (Casing) Pressure:

1500 psig / 103 bar

Emergency Casing Pressure:

1500 psig / 103 bar

### Minimum Buildup Pressure

**Main Valve:** 1500 psid / 103 bar d

**Pilot (Between loading pressure in pilot and loading sense pressure):**

1233 psid / 85.0 bar d

### Minimum Differential Pressures

See Table 3

### Relief Set Pressure Ranges

See Table 2

### Flow and Sizing Coefficients

See Tables 5 and 6

1. The pressure/temperature limits in this Bulletin and any applicable standard or code limitation should not be exceeded.

2. Type PRX Fluorocarbon (FKM) elastomer is limited to 0°F / -18°C.

### Flow Capacities

See Table 7

### Pilot and Filter-Regulator

#### Flow Coefficients

**Type PRX Pilot:** C<sub>g</sub>: 10.5; C<sub>v</sub>: 0.36; C<sub>t</sub>: 29

### Pressure Registration

External

### Pilot Connection

1/4 NPT

### Temperature Capabilities<sup>(1)</sup>

#### Nitrile (NBR) Version:

-20 to 180°F / -29 to 82°C

Fluorocarbon (FKM) Version:

0 to 180°F / -18 to 82°C<sup>(2)</sup>

Polyurethane (PU) Version:

NPS 1, 2, 6, 8, 12 x 6 /

DN 25, 50, 150, 200, 300 x 150 Sizes:

-22 to 180°F / -30 to 82°C

NPS 3 to 4 / DN 80 to 100 Sizes:

-4 to 180°F / -20 to 82°C

### Option

- Travel Indicator
- Whisper Trim™ Cage

### Construction Materials

#### Main Valve

**Main Valve Body:** WCC Steel

Intermediate Flange and Actuator

Casings: Steel, ASTM A350 LF2

Diaphragm Plates: Steel, ASTM 105

Diaphragm: Nitrile (NBR) with PVC coating

O-rings: Fluorocarbon (FKM)

Disk: Nitrile (NBR), Fluorocarbon (FKM) or Polyurethane (PU)

#### PRX Series Pilots

**Body:** Steel, ASTM 105

**Trim:** Stainless steel

**Elastomers:**

Nitrile (NBR) or Fluorocarbon (FKM)

Disk: Polyurethane (PU) or

Fluorocarbon (FKM)

### Approximate Weights

See Table 9




Figure 1. Type EZH Relief Valve or Backpressure Regulator

### Features

- Full Pressure Rating
- Quiet Operation
- Bubble Tight Shutoff
- Full Usable Capacity
- Versatility
- Travel Indicator
- Precise Pressure Control

### Additional Technical Data

Scan or Click the QR code for more information on this product.




[www.Emerson.com](http://www.Emerson.com)

12/17

Table 1. Main Valve Body Sizes, End Connection Styles and Body Ratings

MAIN VALVE BODY SIZE		MAIN VALVE BODY MATERIAL	END CONNECTION STYLE	STRUCTURAL DESIGN RATING	
NPS	DN			psig	bar
1 and 2	25 and 50	LCC or WCC Steel	NPT or SWE  CL150 RF CL300 RF CL600 RF or BWE	1500	103
1, 2, 3, 4, 6, 8 and 12 x 6	25, 50, 80, 100, 150, 200 and 300 x 150	WCC Steel		290	20.0
				750	51.7
				1500	103



M1055

Figure 2. Type EZH with Type PRX-182 Pilot

Table 2. Relief Set Pressure Ranges

PILOT TYPE	RELIEF SET PRESSURE RANGE		PILOT CONTROL INFORMATION							
	psig	bar	Part Number	Color	Wire Diameter		Free Length		Maximum Emergency Pressure	
					In.	mm	In.	mm	psig	bar
PRX/182	29 to 116	2.0 to 8.0	M0255220X12	Black	0.157	4.00	2.16	55	1480	102
	73 to 290	5.0 to 20.0	M0255200X12	Gold	0.217	5.50	2.01	51		
	217 to 609	15.0 to 42.0	M0255190X12	Red	0.256	6.50	1.97	50		

Table 3. Minimum Differential Pressures

TYPE	MAIN VALVE BODY SIZE		MINIMUM DIFFERENTIAL			
	NPS	DN	For 90% Capacity		For 100% Capacity	
			psid	bar d	psid	bar d
EZH	1	25	15.2	1.1	15.7	1.1
	2	50	12.0	0.83	13.8	0.95
	3	80	10.6	0.73	12.8	0.88
	4	100	15.8	1.1	16.4	1.1
	6, 8, 12 x 6	150, 200, 300 x 150	----	----	14.0	0.98

# Type EZH Relief

## Relief Valve or Backpressure Regulator



**Table 4. Relief Set Pressure Build-Up Table**

PILOT TYPE	SET PRESSURE CONTROL RANGE, SPRING PART NUMBER AND COLOR, psig / bar	SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESEAT PILOT	
		psig	bar	psig	bar	psig	bar	psig	bar
PRX/182	29 to 116 / 2 to 8 M0255220X12 Black	30	2.1	1.7	0.12	3.4	0.23	0.9	0.06
		60	4.1	2.7	0.19	4.7	0.32	0.9	0.06
		80	5.5	2.8	0.19	5.3	0.36	0.9	0.06
		100	6.9	3.8	0.26	6.3	0.43	0.9	0.06
	73 to 290 / 5 to 20 M0255200X12 Gold	75	5.2	3.7	0.25	7.7	0.53	1.9	0.13
		100	6.9	3.7	0.25	9.2	0.63	1.9	0.13
		150	10.3	4.7	0.32	9.8	0.68	1.9	0.13
		200	13.8	5.0	0.34	10.9	0.75	1.9	0.13
		250	17.2	5.0	0.34	11.5	0.79	1.9	0.13
	217 to 609 / 14.9 to 41.7 M0255190X12 Red	225	15.5	5.0	0.34	13.7	0.95	2.5	0.17
		300	20.7	5.1	0.35	14.0	0.97	2.5	0.17
		400	27.6	5.2	0.36	14.5	1.00	2.5	0.17
450		31.0	5.4	0.37	14.5	1.00	2.5	0.17	
450		31.0	5.4	0.37	14.9	1.03	2.9	0.20	
PRX-AP/182	435 to 1160 / 30 to 80 M0273790X12 Clear	500	34.5	5.4	0.37	14.9	1.03	3.2	0.22
		600	41.4	6.2	0.43	14.9	1.03	3.2	0.22
		1050	72.4	6.2	0.43	15.6	1.08	3.2	0.22
		1050	72.4	6.2	0.43	15.6	1.08	3.2	0.22

1. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
2. Crack point pressure of the main valve of the inlet pressure build-up over the set pressure at which the main valve starts audible flow.
3. Inlet pressure build-up over the set pressure for the main valve to achieve wide-open flow capacity.

**Table 5. Type EZH Main Valve with Standard Cage Regulating Flow Coefficients**


MAIN VALVE BODY SIZE		LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN	C <sub>g</sub>	C <sub>v</sub>	C <sub>l</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>l</sub>
1	25	564	16.3	34.6	544	15.3	35.5
2	50	2278	58.5	38.9	2110	62.9	33.5
3	80	4960	133	37.3	4396	143	30.8
4	100	7250	227	31.9	7170	229	31.3
6	150	14,430	462	31.2	13,600	433	31.4
8	200	26,540	720	36.9	25,270	722	35.0
12 x 6	300 x 150	30,490	815	37.4	----	----	----

**Table 6. Type EZH Main Valve with Standard Cage IEC Sizing Coefficients**

MAIN VALVE BODY SIZE		LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN	X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>	X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
1	25	0.61	0.61	0.89	0.80	0.59	0.89
2	50	0.73	0.59		0.69	0.61	
3	80	0.88	0.58		0.60	0.60	
4	100	0.63	0.63		0.62	0.63	
6	150	0.62	----		0.62	----	
8	200	0.86	0.69		0.77	0.69	
12 x 6	300 x 150	0.88	----		----	----	







ERCA04507

Figure 3. Type EZH Dimensions (See Table 8)

Table 7. Capacities for Type EZH with PRX Series Pilot

SET PRESSURE RANGE, PILOT SPRING PART NUMBER AND COLOR, psig / bar	SET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / NM <sup>3</sup> /H OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
			NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 12 X 6 / DN 300 X 150	
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
29 to 116 / 2 to 8 M0255220X12 Black	30	2.1	36	0.96	139	3.73	307	8.23	458	12.27	891	23.9	1638	43.9	1881	50.4
	60	4.1	59	1.58	235	6.30	518	13.88	756	20.26	1486	39.8	2732	73.2	3138	84.1
	80	5.5	75	2.01	298	7.99	654	17.53	952	25.51	1872	50.1	3441	92.2	3952	105.9
	100	6.9	91	2.44	363	9.73	795	21.31	1154	30.93	2275	60.9	4183	112.1	4804	128.7
73 to 290 / 5 to 20 M0255200X12 Gold	75	5.2	72	1.93	286	7.66	628	16.83	914	24.50	1793	48.0	3297	88.3	3786	101.4
	100	6.9	91	2.44	366	9.81	801	21.47	1163	31.17	2273	60.9	4179	112.0	4800	128.6
	150	10.3	130	3.48	522	13.99	1141	30.58	1654	44.33	3252	87.1	5979	160.2	6867	184.0
	200	13.8	169	4.53	678	18.17	1482	39.72	2148	57.57	4218	113.0	7754	207.7	8906	238.6
	250	17.2	207	5.55	834	22.35	1822	48.83	2639	70.73	5177	138.7	9519	255.0	10,933	292.9
217 to 609 / 14.9 to 41.7 M0255190X12 Red	225	15.5	189	5.07	762	20.42	1664	44.60	2410	64.59	4698	125.8	8637	231.4	9919	265.7
	300	20.7	246	6.59	992	26.59	2165	58.02	3136	84.04	6139	164.5	11,288	302.4	12,964	347.3
	400	27.6	322	8.63	1298	34.79	2833	75.92	4102	109.93	8061	215.9	14,821	397.0	17,022	456.0
	450	31.0	360	9.65	1452	38.91	3168	84.90	4588	122.96	9025	241.8	16,592	444.5	19,056	510.5
435 to 1160 / 30 to 80 M0273790X12 Clear	450	31.0	360	9.65	1452	38.91	3168	84.90	4588	122.96	9025	241.8	16,592	444.5	19,056	510.5
	500	34.4	398	10.67	1605	43.01	3501	93.83	5071	135.90	9984	267.5	18,357	491.8	21,083	565
	600	41.4	474	12.70	1911	51.21	4167	111.68	6035	161.74	11,919	319.3	21,915	587.1	25,169	674
	1050	72.4	815	21.84	3286	88.06	7164	192.00	10,375	278.05	20,558	550.8	37,798	1012.6	43,411	1163

Table 8. Type EZH Dimensions (See Figure 3)

BODY SIZE, NPS / DN	DIMENSION, IN. / mm											
	A				C	D (Maximum)	E	F	G	H	J	R
	NPT or SWE	CL150 RF	CL300 RF	CL600 RF or BWE								
1 / 25	8.25 / 210	7.25 / 184	7.75 / 197	8.25 / 210	1.50 / 38.1	2.10 / 53	12.3 / 311	13.05 / 331	11.10 / 282	5.10 / 130	8.25 / 210	3.5 / 88.9
2 / 50	11.25 / 286	10.0 / 254	10.50 / 267	11.25 / 286	1.50 / 38.1	3.10 / 79	14 / 356	14.75 / 375	11.30 / 287	6.50 / 165	7.75 / 197	4.5 / 114
3 / 80	----	11.75 / 298	12.50 / 317	13.25 / 337	2.00 / 50.8	3.81 / 97	16 / 406	15.36 / 390	16.75 / 425	8.00 / 203	13.25 / 337	6.0 / 152
4 / 100	----	13.9 / 353	14.5 / 368	15.5 / 394	2.00 / 50.8	5.06 / 129	18.3 / 464	15.85 / 403	16.8 / 427	10.03 / 255	5.5 / 140	7.5 / 191
6 / 150	----	17.75 / 451	18.62 / 473	20 / 508	2.75 / 70	5.31 / 135	17 / 432	19.25 / 489	25 / 635	13 / 330	18 / 457	8.7 / 221
8 / 200	----	21.38 / 543	22.38 / 568	24 / 610	2.75 / 70	8.25 / 210	17 / 432	19.25 / 489	28.5 / 724	13 / 330	18 / 457	8.7 / 221
12 x 6 / 300 x 150	----	29 / 737	30.5 / 775	32.25 / 819	2.75 / 70	10 / 254	17 / 432	19.25 / 489	28.5 / 724	13 / 330	18 / 457	8.7 / 221

# Type EZH Relief

Relief Valve or Backpressure Regulator

FISHER™

Table 9. Approximate Weights

BODY SIZE, NPS / DN	APPROXIMATE SHIPPING WEIGHT, LBS / kg	
	Flanged	NPT, SWE and BWE
1 / 25	87 / 39	77 / 35
2 / 50	150 / 68	136 / 62
3 / 80	410 / 186	390 / 177
4 / 100	514 / 234	433 / 197
6 / 150	1460 / 662	1400 / 635
8 / 200	1875 / 850	1805 / 819
12 x 6 / 300 x 150	2050 / 930	1970 / 894

## Ordering Guide

### Body Sizes (Select One)

- NPS 1 / DN 25\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 / DN 200\*\*\*
- NPS 12 x 6 / DN 300 x 150\*\*\*

### End Connection Styles (Select One)

#### WCC Steel

- NPT (available for NPS 1 and 2 / DN 25 and 50 Body Sizes only)\*\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- SWE (Available for NPS 1 and 2 / DN 25 and 50 Body Sizes only)\*\*
- BWE\*\*
- PN 16/40 (For NPS 1 and 2 / DN 25 and 50 Body Sizes only)\*\*
- PN 25/40 (For NPS 3 / DN 80 Body Size only)\*\*

### Main Valve Disk Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Pilot Type and Outlet Pressure Range (Select One)

#### Type PRX/182 Pilot

- 29 to 116 psig / 2.0 to 8.0 bar, Black\*\*\*
- 73 to 290 psig / 5.0 to 20.0 bar, Gold\*\*\*
- 217 to 609 psig / 14.9 to 41.7 bar, Red\*\*\*

#### Type PRX-AP/182 Pilot

- 435 to 1160 psig / 30.0 to 80.0 bar, Clear\*\*\*

### Pilot Elastomer Material (Select One)

- Nitrile (NBR)/Polyurethane (PU) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Travel Indicator (Optional)

- Yes\*\*\*
- No\*\*\*

### Main Valve Spare Parts Kit (Optional)

- Yes, send one disk parts kit to match this order.
- Yes, send one full parts kit to match this order.

### Pilot Spare Parts Kit (Optional)

- Yes, send one spare parts kit to match this order.

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>	<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
<b>Relief Valve Size</b>	
Brand of upstream regulator?	
Orifice size of the upstream regulator?	
Wide-open coefficient of the upstream regulator?	
<b>Pressure</b>	
Maximum Inlet Pressure:	
Downstream Pressure:	
Differential Pressure:	
Relief (Inlet) Set Pressure:	
Maximum Flow:	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Introduction**

Type EZL regulators are accurate pilot-operated, pressure balanced and soft-seated regulators. They are designed for use in natural gas distribution applications such as district regulating stations and commercial/industrial meter sets. They provide low differential, smooth, reliable operation, tight shutoff and long life. For underpressure and/or overpressure protection, the Type EZL is available with an integral slam-shut device.

**Body Sizes, End Connection Styles and Pressure Ratings<sup>(1)</sup>**

See Table 1

**Maximum Inlet and Outlet (Casing) Pressures<sup>(1)</sup>**

290 psig / 20.0 bar

**Maximum Emergency (Design Casing Pressure)<sup>(1)</sup>**

290 psig / 20.0 bar

**Maximum Operating Differential Pressure<sup>(1)</sup>**

290 psid / 20.0 bar d

**Outlet Pressure Ranges**

See Table 3

**Flow Coefficients**

See Tables 5, 6, 7 and 8

**IEC Sizing Coefficients**

See Table 9

**Flow Capacities**

See Tables 10 and 11

**Temperature Capabilities<sup>(1)</sup>**

**Nitrile (NBR) Version:**

-20 to 180°F / -29 to 82°C

**Fluorocarbon (FKM) Version:**

0 to 180°F / -18 to 82°C

**Approximate Shipping Weights**

See Table 15

**Features**

- **Bubble Tight Shutoff**
- **Precise Pressure Control**
- **Corrosion Resistant Anodized Aluminum Casing**
- **Common E-Body Platform**
- **Low Differential**
- **No Atmospheric Bleed**
- **Full Pressure Rating**
- **High Capacity**
- **Easy In-Line Maintenance**
- **High Turn Down Capability**
- **Optional Slam-Shut Device**




Figure 1. Type EZL Pressure Reducing Regulator

**Table 1. Main Valve Body Size, End Connection Style and Body Rating**

MAIN VALVE BODY SIZE		MAIN VALVE BODY MATERIAL	END CONNECTION STYLE	STRUCTURAL DESIGN RATING <sup>(1)</sup>	
NPS	DN			psig	bar
2, 3 and 4	50, 80 and 100	WCC steel	NPT <sup>(2)</sup> or SWE <sup>(2)</sup>	1500	103
			CL150 RF	290	20.0
			CL300 RF	750	51.7
			CL600 RF or BWE	1500	103
		Cast iron	NPT <sup>(2)</sup>	400	27.6
			CL125 FF	200	13.8
			CL250 RF	500	34.5

1. Structural Design Rating is the rating for the main valve body. The Type EZL complete assembly is limited to 290 psig / 20.0 bar.  
2. Only available in NPS 2 / DN 50 body size.

**Table 2. Minimum Differential Pressure<sup>(1)</sup>**

TRIM, PERCENT OF CAPACITY	MINIMUM DIFFERENTIAL FOR FULL STROKE					
	NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100	
	psid	bar d	psid	bar d	psid	bar d
100	2.9	0.204	2.9	0.204	2.9	0.204
80	2.9	0.204	3.1	0.214	3.2	0.221
50	3.0	0.207	3.2	0.221	3.7	0.255
30	3.4	0.234	3.5	0.241	3.9	0.269

**Additional Technical Data**

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)


12/19

1. The pressure/temperature limits in this Datasheet and any applicable standard or code limitation should not be exceeded.

# Type EZL

Pressure Reducing Regulator for Low Differential Pressure Application


FISHER™



E0944

- █ INLET PRESSURE
- █ OUTLET PRESSURE
- █ ATMOSPHERIC PRESSURE
- █ LOADING PRESSURE

Figure 2. Type EZL with Type 6352 Pilot and Type P590 Pilot Supply Filter Operational Schematic



E0959

- █ INLET PRESSURE
- █ OUTLET PRESSURE
- █ ATMOSPHERIC PRESSURE
- █ LOADING PRESSURE

Figure 3. Type EZL with Type 61L Pilot and Type P590 Pilot Supply Filter Operational Schematic




Figure 4. Type EZL Operational Schematic

Table 3. Outlet (Control) Pressure Range						
PILOT TYPE	OUTLET (CONTROL) PRESSURE RANGE		SPRING COLOR	SPRING PART NUMBER	APPROXIMATE PROPORTIONAL BAND	
	psig	bar			psig	bar
6352	2 to 10	0.14 to 0.69	Black	14A9673X012	0.3	0.02
6353	3 to 40	0.21 to 2.8	Yellow	1E392527022	0.5	0.03
	35 to 125	2.41 to 8.6	Red	1K748527202	1.0	0.07
6354L <sup>(1)</sup> , 6354M <sup>(2)</sup> and 6354H <sup>(2)</sup>	85 to 200	5.9 to 13.8	Blue	1L346127142	3.0	0.2
	175 to 220	12.1 to 15.2	Blue	1L346127142	3.0	0.2
	200 to 300 <sup>(4)</sup>	13.8 to 20.7 <sup>(4)</sup>	Green	15A9258X012	5.0	0.34
61L	0.25 to 2	0.017 to 0.14	Red	1B886327022	0.15	0.01
	1 to 5	0.069 to 0.35	Yellow	1J857827022	0.2	0.01
	2 to 10	0.14 to 0.69	Blue	1B886427022	0.3	0.02
	5 to 15	0.35 to 1.03	Brown	1J857927142	0.5	0.03
	10 to 20	0.69 to 1.38	Green	1B886527022	0.7	0.05
61HP	15 to 45	1.03 to 3.10	Yellow	1E392527022	1.0	0.07
	35 to 100	2.41 to 6.90	Blue	1D387227022	1.5	0.1
	100 to 300 <sup>(4)</sup>	6.90 to 20.7 <sup>(4)</sup>	Red	1D465127142	3.0	0.2
161EBM <sup>(3)</sup>	5 to 15	0.34 to 1.03	White	17B1260X012	0.3	0.02
	10 to 40	0.69 to 2.8	Yellow	17B1262X012	0.5	0.03
	30 to 75	2.07 to 5.17	Black	17B1259X012	1.0	0.07
	70 to 140	4.83 to 9.65	Green	17B1261X012	2.0	0.14
	130 to 200	8.96 to 13.8	Blue	17B1263X012	4.0	0.28
	200 to 350 <sup>(4)</sup>	13.8 to 24.1 <sup>(4)</sup>	Red	17B1264X012	5.0	0.34

1. Without diaphragm limiter.  
 2. With diaphragm limiter.  
 3. Monitoring pilot for working monitors.  
 4. Operating range is limited to maximum pressure.

# Type EZL

Pressure Reducing Regulator for Low Differential Pressure Application

FISHER™

**Table 4. Construction Material**

TYPE EZL MAIN VALVE		
Main Body	WCC Steel or Cast iron	
Intermediate Flange	Steel	
Actuator Casing	Anodized Forged Aluminum	
Inlet and Outlet Plate	Steel	
Diaphragm	Nitrile (NBR) with PVC coating	
O-ring	Nitrile (NBR) or Fluorocarbon (FKM)	
Seat	Nitrile (NBR) or Fluorocarbon (FKM)	
TYPE 6352, 6353, 6354L, 6354M OR 6354H PILOT (FOR PRESSURE REDUCING APPLICATION)		
Body, Body Plug, Spring Case and Closing Cap	Aluminum ( <b>standard</b> ) or Stainless steel	
Control Spring	Zinc-plated steel	
Bellows Assembly	Nickel and Stainless steel	
Body Plug and Closing Cap Gasket	Composition	
Other Metal Trim Part	Steel, Aluminum and/or Stainless steel	
Diaphragm	Nitrile (NBR) or Fluorocarbon (FKM)	
O-ring and Soft Part	Nitrile (NBR) ( <b>standard</b> ) or Fluorocarbon (FKM)	
61 SERIES PILOT (FOR PRESSURE REDUCING APPLICATION)		
Body and Spring Case	Cast iron	
Upper and Lower Diaphragm	Type 61L	Nitrile (NBR) or Fluorocarbon (FKM)
	Type 61HP	Neoprene (CR) or Fluorocarbon (FKM)
Metal Trim Part	Steel, Stainless steel, Cast iron, Aluminum, Brass or Zinc	
Gasketing	Neoprene (CR)	
Elastomer Seat and O-ring	Nitrile (NBR) or Fluorocarbon (FKM)	
TYPE 161EBM PILOT (FOR MONITORING APPLICATION ONLY)		
Body	Stainless steel	
Spring Case	Stainless steel	
Body Plug and Diaphragm Limiter	Stainless steel	
Control Spring	Plated steel	
Adjusting Screw	Plated steel	
Valve Plug, Diaphragm and O-ring	Nitrile (NBR) or Fluorocarbon (FKM)	
PILOT AND ACTUATOR VENT		
Type Y602 vent assembly		
TYPE 252 PILOT SUPPLY FILTER		
Body	Aluminum or Stainless steel	
Filter Cartridge	Polyethylene	
O-ring	Nitrile (NBR)	
Drain Valve or Pipe Plug	Stainless steel	
TYPE P590 PILOT SUPPLY FILTER		
Body and Filter Head	Aluminum or Brass	
Filter Element	Cellulose	

**Table 5. Type EZL Main Valve Regulating Flow Coefficient**

MAIN VALVE BODY SIZE		TRIM, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
2	50	100	2290	63.2	36.2	2140	61.5	34.8
		80	1914	56.7	33.8	1760	51.5	34.2
		50	1290	41.4	31.2	1230	36.4	33.8
		30	858	25.5	33.6	800	24.9	32.1
3	80	100	4800	144	33.5	4580	142	32.3
		80	3950	120	32.9	3930	120	32.7
		50	2440	69.2	35.3	2420	72.5	33.4
		30	1560	44.8	34.9	1570	48.7	32.3
4	100	100	6560	200	32.6	6440	192	33.6
		80	4550	129	35.2	4500	146	30.8
		50	2740	78.2	35.1	2750	80.7	34.1
		30	1760	50.5	34.9	1760	47.4	37.1



Table 6. Type EZL Main Valve Wide-Open Flow Coefficient

MAIN VALVE BODY SIZE		TRIM, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
2	50	100	2360	65.0	37.3	2200	63.3	35.8
		80	1970	58.4	34.8	1810	53.0	35.2
		50	1330	42.6	32.1	1270	37.5	34.8
		30	884	26.3	34.7	820	25.7	33.1
3	80	100	4940	148	34.5	4710	146	33.3
		80	4060	123	33.9	4050	124	33.7
		50	2510	71.3	36.3	2500	74.7	34.5
		30	1610	46.1	35.9	1620	50.1	33.3
4	100	100	6760	208	33.5	6630	198	34.6
		80	4690	133	36.3	4630	151	31.7
		50	2830	80.5	35.2	2830	83.1	35.1
		30	1820	52.0	36.0	1810	48.7	38.2

Table 7. Type EZLOSX Main Valve Regulating Flow Coefficients

MAIN VALVE BODY SIZE		TRIM, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
2	50	100	2210	65.7	33.6	2058	64.6	31.9
		80	1890	58.6	32.3	1790	56.6	31.6
		50	1270	43.2	29.5	1250	40.3	31.1
		30	855	26.6	32.1	872	28.5	30.6
3	80	100	4610	134	34.5	4390	134	32.9
		80	4060	117	34.5	3900	118	33.1
		50	2600	75.3	34.5	2420	72.1	33.6
		30	1610	46.5	34.6	1580	49.2	32.1
4	100	100	6280	194	32.4	6160	194	31.7
		80	4470	145	30.9	4380	141	31.1
		50	2740	88.3	31.0	2700	86.3	31.2
		30	1770	61.0	29.0	1780	65.8	27.1

Table 8. Type EZLOSX Main Valve Wide-Open Flow Coefficients

MAIN VALVE BODY SIZE		TRIM, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE			2:1 LINE SIZE TO BODY SIZE PIPING		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
2	50	100	2280	67.7	34.6	2120	66.5	32.8
		80	1950	60.4	33.2	1840	58.3	32.6
		50	1310	44.5	30.4	1290	41.5	32.0
		30	881	27.4	33.1	898	29.4	31.5
3	80	100	4750	138	35.5	4520	138	33.9
		80	4180	121	35.6	4020	121	34.1
		50	2680	77.6	35.5	2490	74.2	34.6
		30	1660	47.9	35.7	1620	50.6	33.0
4	100	100	6470	200	33.4	6340	200	32.7
		80	4600	149	31.8	4500	145	32.1
		50	2820	91.0	31.9	2780	88.9	32.2
		30	1820	62.8	29.8	1840	67.8	27.9

Table 9. IEC Sizing Coefficient

MAIN VALVE BODY SIZE		TRIM, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE		2:1 LINE SIZE TO BODY SIZE PIPING		F <sub>L</sub>
NPS	DN		X <sub>r</sub>	F <sub>D</sub>	X <sub>r</sub>	F <sub>D</sub>	
2	50	100	0.829	0.61	0.766	0.60	0.89
		80	0.723	0.58	0.740	0.55	
		50	0.616	0.50	0.723	0.46	
		30	0.714	0.39	0.652	0.38	
3	80	100	0.710	0.61	0.660	0.60	
		80	0.685	0.55	0.676	0.55	
		50	0.788	0.42	0.706	0.43	
		30	0.770	0.34	0.660	0.35	
4	100	100	0.672	0.72	0.714	0.70	
		80	0.784	0.57	0.600	0.61	
		50	0.779	0.45	0.736	0.45	
		30	0.770	0.36	0.871	0.35	

# Type EZL

Pressure Reducing Regulator for Low Differential Pressure Application



**Table 10. Capacities for Type EZL**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING					
psig	bar	psig	bar	NPS 2 / DN 50 BODY		NPS 3 / DN 80 BODY		NPS 4 / DN 100 BODY	
				SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
4	0.28	0.25	0.02	37	1.00	83	2.22	116	3.10
5	0.34	0.25	0.02	42	1.13	94	2.51	130	3.50
		1	0.07	39	1.06	88	2.35	122	3.28
		2	0.14	35	0.94	78	2.10	109	2.93
10	0.69	0.25	0.02	63	1.68	138	3.69	191	5.12
		3	0.21	56	1.51	124	3.33	173	4.64
		5	0.34	49	1.32	110	2.95	153	4.11
		7	0.48	40	1.06	89	2.39	124	3.34
15	1.0	1	0.07	79	2.13	173	4.64	239	6.41
		4	0.28	74	1.98	162	4.36	225	6.05
		8	0.55	63	1.69	140	3.75	195	5.23
		12	0.83	44	1.18	99	2.65	138	3.71
20	1.4	1	0.07	96	2.58	208	5.58	287	7.70
		10	0.69	79	2.13	175	4.71	244	6.55
		15	1.03	60	1.61	134	3.61	188	5.04
		17	1.17	48	1.28	107	2.88	150	4.04
30	2.1	4	0.28	126	3.37	271	7.26	372	10.0
		15	1.03	108	2.89	237	6.37	330	8.86
		20	1.38	93	2.49	206	5.54	288	7.73
		25	1.72	69	1.86	155	4.17	217	5.83
40	2.8	9	0.62	153	4.10	330	8.85	454	12.2
		20	1.38	136	3.64	298	8.00	414	11.1
		30	2.07	105	2.81	234	6.27	326	8.76
		35	2.41	77	2.07	174	4.66	243	6.53
50	3.4	13	0.90	181	4.86	391	10.5	538	14.4
		20	1.38	172	4.62	375	10.1	519	13.9
		30	2.07	152	4.07	335	8.99	466	12.5
		40	2.76	115	3.10	258	6.93	361	9.68
		45	3.10	85	2.27	190	5.11	267	7.16
60	4.1	17	1.17	209	5.62	451	12.1	622	16.7
		25	1.72	199	5.35	434	11.7	600	16.1
		35	2.41	180	4.83	397	10.6	551	14.8
		45	3.10	149	3.99	331	8.89	462	12.4
		55	3.79	91	2.45	206	5.52	288	7.73
75	5.2	24	1.65	251	6.73	541	14.5	745	20.0
		50	3.45	202	5.44	448	12.0	624	16.8
		60	4.14	165	4.44	370	9.92	516	13.9
		70	4.83	100	2.70	227	6.08	318	8.53
100	6.9	35	2.41	320	8.60	691	18.6	953	25.6
		60	4.14	280	7.52	617	16.6	856	23.0
		75	5.17	236	6.33	525	14.1	732	19.6
125	8.6	46	3.17	390	10.5	842	22.6	1160	31.1
		75	5.17	344	9.23	757	20.3	1051	28.2
150	10.3	57	3.93	460	12.3	992	26.6	1367	36.7
		75	5.17	436	11.7	951	25.5	1316	35.3
		100	6.89	383	10.3	847	22.8	1179	31.6
		125	8.62	291	7.82	652	17.5	911	24.5
175	12.1	68	4.69	530	14.2	1143	30.7	1574	42.3
		75	5.17	522	14.0	1129	30.3	1558	41.8
		100	6.89	482	12.9	1057	28.4	1465	39.3
		125	8.62	419	11.3	930	25.0	1296	34.8
		150	10.3	316	8.47	707	19.0	989	26.6
200	13.8	75	5.17	603	16.2	1300	34.9	1789	48.0
		100	6.89	572	15.4	1246	33.5	1723	46.3
		125	8.62	525	14.1	1155	31.0	1603	43.0
		150	10.3	453	12.2	1007	27.0	1404	37.7
		175	12.1	338	9.07	759	20.4	1062	28.5
225	15.5	75	5.17	683	18.3	1465	39.3	2013	54.0
		100	6.89	657	17.6	1424	38.2	1966	52.8
		125	8.62	619	16.6	1355	36.4	1877	50.4
		150	10.3	564	15.1	1246	33.4	1732	46.5
		175	12.1	484	13.0	1078	28.9	1504	40.4
		200	13.8	359	9.64	807	21.7	1130	30.3
250	17.0	75	5.17	761	20.4	1627	43.7	2232	59.9
		125	8.62	708	19.0	1541	41.4	2131	57.2
		150	10.3	663	17.8	1456	39.1	2021	54.2
		175	12.1	601	16.1	1331	35.7	1853	49.7
		200	13.8	513	13.8	1145	30.7	1599	42.9
		225	15.5	379	10.2	853	22.9	1194	32.1
285	20.0	75	5.17	869	23.3	1850	49.7	2534	68.0
		125	8.62	826	22.2	1789	48.0	2467	66.2
		150	10.3	791	21.2	1726	46.3	2388	64.1
		175	12.1	744	20.0	1635	43.9	2270	60.9
		200	13.8	681	18.3	1507	40.5	2098	56.3
225	15.5	595	16.0	1327	35.6	1852	49.7		






**Table 11. Capacities for Type EZLOSX**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING					
				NPS 2 / DN 50 BODY		NPS 3 / DN 80 BODY		NPS 4 / DN 100 BODY	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
4	0.3	0.25	0.02	38	1.02	78	2.09	111	2.98
		1	0.07	43	1.15	88	2.36	125	3.37
		2	0.14	40	1.08	82	2.21	118	3.16
5	0.3	3	0.21	36	0.96	73	1.96	105	2.82
		5	0.34	63	1.70	130	3.49	183	4.92
		7	0.48	57	1.53	117	3.14	166	4.46
10	0.7	8	0.55	50	1.35	103	2.77	147	3.96
		12	0.83	41	1.10	83	2.23	120	3.21
		1	0.07	79	2.13	164	4.40	229	6.16
15	1.0	4	0.28	75	2.00	153	4.12	217	5.81
		8	0.55	64	1.72	131	3.53	188	5.03
		12	0.83	45	1.22	92	2.48	133	3.57
20	1.4	1	0.07	96	2.57	198	5.30	275	7.38
		10	0.69	81	2.16	165	4.43	235	6.30
		15	1.03	62	1.66	126	3.38	181	4.85
30	2.1	17	1.17	49	1.32	100	2.70	145	3.89
		4	0.28	124	3.34	257	6.91	357	9.58
		15	1.03	109	2.93	224	6.01	317	8.51
40	2.8	20	1.38	95	2.55	194	5.21	277	7.43
		25	1.72	71	1.91	145	3.90	209	5.61
		9	0.62	152	4.07	314	8.42	436	11.7
50	3.4	20	1.38	137	3.68	281	7.55	398	10.7
		30	2.07	107	2.88	219	5.88	314	8.42
		35	2.41	80	2.14	162	4.36	234	6.28
60	4.1	13	0.90	180	4.82	371	9.97	516	13.8
		20	1.38	172	4.63	355	9.54	498	13.4
		30	2.07	154	4.13	315	8.47	448	12.0
75	5.2	40	2.76	119	3.18	242	6.49	347	9.32
		45	3.10	87	2.35	178	4.77	257	6.89
		17	1.17	208	5.57	429	11.5	596	16.0
100	6.9	25	1.72	200	5.36	411	11.0	576	15.5
		35	2.41	182	4.89	374	10.0	529	14.2
		45	3.10	152	4.08	311	8.34	444	11.9
125	8.6	55	3.79	94	2.53	192	5.16	277	7.45
		24	1.65	249	6.68	514	13.8	715	19.2
		50	3.45	206	5.53	422	11.3	600	16.1
150	10	60	4.14	170	4.56	346	9.30	497	13.3
		70	4.83	104	2.79	212	5.68	306	8.21
		35	2.41	318	8.54	657	17.7	913	24.5
175	12	60	4.14	283	7.61	582	15.6	823	22.1
		75	5.17	241	6.47	493	13.2	704	18.9
		46	3.17	387	10.4	801	21.5	1112	29.9
200	14	75	5.17	348	9.34	714	19.2	1009	27.1
		57	3.93	456	12.3	944	25.3	1311	35.2
		75	5.17	437	11.7	901	24.2	1263	33.9
225	16	100	6.89	389	10.5	798	21.4	1133	30.4
		125	8.62	299	8.04	611	16.4	877	23.5
		68	4.69	526	14.1	1087	29.2	1510	40.5
250	17	75	5.17	519	13.9	1072	28.8	1495	40.1
		100	6.89	486	13.0	999	26.8	1407	37.8
		125	8.62	427	11.5	875	23.5	1246	33.4
285	20	150	10.3	325	8.72	662	17.8	952	25.6
		75	5.17	598	16.1	1237	33.2	1715	46.0
		100	6.89	573	15.4	1180	31.7	1654	44.4
300	20	125	8.62	531	14.2	1089	29.2	1540	41.4
		150	10.3	462	12.4	946	25.4	1350	36.2
		175	12.1	348	9.35	710	19.1	1022	27.4
325	20	75	5.17	674	18.1	1396	37.5	1929	51.8
		100	6.89	655	17.6	1352	36.3	1885	50.6
		125	8.62	623	16.7	1281	34.4	1802	48.4
350	20	150	10.3	572	15.4	1173	31.5	1664	44.7
		175	12.1	495	13.3	1012	27.2	1447	38.8
		200	13.8	371	10.0	755	20.3	1088	29.2
375	20	75	5.17	749	20.1	1553	41.7	2139	57.4
		125	8.62	709	19.0	1460	39.2	2045	54.9
		150	10.3	669	18.0	1375	36.9	1941	52.1
400	20	175	12.1	612	16.4	1253	33.6	1781	47.8
		200	13.8	526	14.1	1075	28.8	1538	41.3
		225	15.5	392	10.5	798	21.4	1149	30.9
425	20	75	5.17	851	22.9	1769	47.5	2427	65.2
		125	8.62	823	22.1	1699	45.6	2366	63.5
		150	10.3	794	21.3	1634	43.9	2293	61.5
450	20	175	12.1	752	20.2	1544	41.4	2180	58.5
		200	13.8	693	18.6	1419	38.1	2017	54.1
		225	15.5	609	16.4	1245	33.4	1781	47.8

# Type EZL

Pressure Reducing Regulator for Low Differential Pressure Application

FISHER™



GE11539-1

Figure 5. Type EZL Dimensions

Table 12. Type EZL with Type 61L Pilot Dimension

BODY SIZE		DIMENSION											
		A						B					
		CL125 FF, CL150 RF		CL250 RF, CL300 RF		CL600 RF		CL125 FF, CL150 RF		CL250 RF, CL300 RF		CL600 RF	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
2	50	10.00	254	10.50	267	11.25	286	5.00	127	5.25	133	5.63	143
3	80	11.75	298	12.50	317	13.25	337	5.88	149	6.25	159	6.63	168
4	100	13.90	353	14.50	368	15.50	394	6.95	177	7.25	184	7.75	197


Table 12. Type EZL with Type 61L Pilot Dimension (continued)

BODY SIZE		DIMENSION									
		D		G		M		N			
		In.	mm	In.	mm	In.	mm	In.	mm		
2	50	12.50	318	3.06	78	16.25	413	8.66	220		
3	80	15.49	393	3.81	97	17.58	447	9.99	254		
4	100	16.67	423	5.10	130	17.58	447	9.99	254		

Table 13. Type EZL with Type 6352, 6353 or 161EBM Pilot Dimension


BODY SIZE		DIMENSION											
		E						F					
		CL125 FF, CL150 RF		CL250 RF, CL300 RF		CL600 RF		CL125 FF, CL150 RF		CL250 RF, CL300 RF		CL600 RF	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
2	50	10.00	254	10.50	267	11.25	286	5.00	127	5.25	133	5.63	143
3	80	11.75	298	12.50	317	13.25	337	5.88	149	6.25	159	6.63	168
4	100	13.88	353	14.50	368	15.50	394	6.94	176	7.25	184	7.75	197





GE12413-1

Figure 5. Type EZL Dimensions (continued)



GE24229\_A

Figure 6. Type EZLOSX Dimensions

# Type EZL

Pressure Reducing Regulator for Low Differential Pressure Application

FISHER™

**Table 13. Type EZL with Type 6352, 6353 or 161EBM Pilot Dimension (continued)**

BODY SIZE		DIMENSION							
		J		K		O		P	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm
2	50	13.53	344	3.06	78	10.50	267	12.50	318
3	80	16.52	420	3.81	97	11.83	300	14.13	359
4	100	19.03	483	5.10	130	11.83	300	14.13	359

**Table 14. Type EZLOSX Dimensions**

BODY SIZE		DIMENSION WITH SLAM-SHUT													
		D		H		M <sup>(1)</sup>				N					
						Diaphragm		Piston		Diaphragm		Piston		Bellow	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
2	50	13.0	330	10.4	264	6.38	162	2.80	71	6.89	175	8.03	204	8.78	223
3	80	14.34	364	11.78	299	6.38	162	2.80	71	6.89	175	8.03	204	8.78	223
4	100	15.64	397	13.09	332	6.38	162	2.80	71	6.89	175	8.03	204	8.78	223

1. Type 71 BMS with a diaphragm has an M dimension of 2.80 in. / 71 mm.

**Table 15. Shipping Weight**

BODY SIZE		APPROXIMATE SHIPPING WEIGHT													
		NPT		SWE		CL150 RF		CL300 RF		CL600 RF		SCH 40		ACTUATOR ONLY	
NPS	DN	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg	lb	kg
2	50	90	41	90	41	97	44	107	49	111	50	90	41	45	20
3	80	----	----	----	----	172	78	182	83	186	84	----	----	80	36
4	100	----	----	----	----	201	91	225	102	270	122	----	----	85	39

## Ordering Guide

### Type (Select One)

- Type EZL
- Type EZLOSX

### Body Size (Select One)

- NPS 2 / DN 50 Body\*\*\*
- NPS 3 / DN 80 Body\*\*\*
- NPS 4 / DN 100 Body\*\*\*

### Body Material and End Connection Style (Select One)

#### WCC Steel

- NPT (2 in. only)\*\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- BWE\_\_\_\_\_ (Indicate Schedule 40 or 80)\*\*
- SWE\*\*

#### Cast Iron

- NPT (2 in. only)\*\*\*
- CL125 FF\*\*\*
- CL250 RF\*\*\*

### Main Valve Seat Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Outlet Pressure Range (Select One)

#### Type 61L

- 0.25 to 2 psig / 0.017 to 0.14 bar, Red\*\*\*
- 1 to 5 psig / 0.069 to 0.35 bar, Yellow\*\*\*
- 2 to 10 psig / 0.14 to 0.69 bar, Blue\*\*\*
- 5 to 15 psig / 0.35 to 1.03 bar, Brown\*\*\*
- 10 to 20 psig / 0.69 to 1.38 bar, Green\*\*\*

#### Type 61HP

- 15 to 45 psig / 1.03 to 3.10 bar, Yellow\*\*\*
- 35 to 100 psig / 2.41 to 6.90 bar, Blue\*\*\*
- 100 to 300 psig / 6.90 to 20.7 bar, Red<sup>(1)</sup>\*\*\*

#### Type 6352

- 2 to 10 psig / 0.14 to 0.69 bar, Black\*\*\*

-continued-

1. Operating range is limited to maximum pressure.

## Ordering Guide (continued)

Outlet Pressure Range (Select One) (continued)	
<b>Type 6353</b>	
<input type="checkbox"/>	3 to 40 psig / 0.21 to 2.8 bar, Yellow***
<input type="checkbox"/>	35 to 125 psig / 2.41 to 8.6 bar, Red***
<b>Type 6354L, 6354M or 6354H</b>	
<input type="checkbox"/>	85 to 200 psig / 5.9 to 13.8 bar, Blue***
<input type="checkbox"/>	175 to 220 psig / 12.1 to 15.2 bar, Blue***
<input type="checkbox"/>	200 to 300 psig / 13.8 to 20.7 bar, Green <sup>(1)</sup> ***
<b>Type 161EBM</b>	
<input type="checkbox"/>	5 to 15 psig / 0.35 to 1.03 bar, White***
<input type="checkbox"/>	10 to 40 psig / 0.69 to 2.8 bar, Yellow***
<input type="checkbox"/>	30 to 75 psig / 2.07 to 5.17 bar, Black***
<input type="checkbox"/>	70 to 140 psig / 4.83 to 9.65 bar, Green***
<input type="checkbox"/>	130 to 200 psig / 8.96 to 13.8 bar, Blue***
<input type="checkbox"/>	200 to 350 psig / 13.8 to 24.1 bar, Red <sup>(1)</sup> ***

Pilot Elastomer Material (Select One)	
<input type="checkbox"/>	Nitrile (NBR) (standard)***
<input type="checkbox"/>	Fluorocarbon (FKM)***

Slam-Shut Trip Pressure Setting (Select One)	
<b>Overpressure Protection Only</b>	
<input type="checkbox"/>	Supply setpoint required _____
<b>Underpressure Protection Only</b>	
<input type="checkbox"/>	Supply setpoint required _____
<b>Overpressure Protection and Underpressure Protection</b>	
<input type="checkbox"/>	Supply overpressure setpoint required _____
<input type="checkbox"/>	Supply underpressure setpoint required _____
<b>Overpressure Protection, Underpressure Protection and Underpressure Protection</b>	
<input type="checkbox"/>	Supply overpressure setpoint required _____
<input type="checkbox"/>	Supply overpressure setpoint required _____
<input type="checkbox"/>	Supply underpressure setpoint required _____

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Travel Indicator (Optional)	
<input type="checkbox"/>	Yes***
<input type="checkbox"/>	No***

Main Valve Replacement Parts Kit (Optional)	
<input type="checkbox"/>	Yes, send one replacement parts kit to match this order.

Pilot Replacement Parts Kit (Optional)	
<input type="checkbox"/>	Yes, send one replacement parts kit to match this order.

Explosion-Proof Limit Switch (Optional)	
<input type="checkbox"/>	Yes***

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/>	Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Pressure</b>	
Maximum Inlet Pressure (P <sub>1max</sub> ):	
Minimum Inlet Pressure (P <sub>1min</sub> ):	
Downstream Pressure Setting(s) (P <sub>2</sub> ):	
Maximum Flow (Q <sub>max</sub> ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

# EZR Series

## Pressure Reducing Regulator

FISHER™

### Introduction

The Type EZR pilot-operated, pressure reducing regulator is designed for natural gas transmission/distribution systems and industrial/commercial applications. The Type EZR provides smooth, quiet operation, tight shutoff and long life, even in dirty service. Its internally actuated metal plug eliminates disadvantages associated with boot-style regulators, and the specially engineered flow path deflects debris, protecting the seat from damage and erosion.

The Type EZR is used in conjunction with a 161EB or 161AY Series pilot with the Type 112 restrictor, or with PRX Series pilot (with integral restrictor). The Type EZR pressure reducing regulator can be converted to a high pressure relief valve or backpressure regulator by simply changing to a relief piloting system (refer to Type EZR Relief pages).

For underpressure and/or overpressure protection, Type EZROX Regulator includes Type EZR Regulator with a slam-shut device. The slam-shut device can provide either overpressure or overpressure and underpressure protection by completely shutting off the flow of gas to the downstream system. The slam-shut has a mechanism box and a manometric device.

### Body Sizes and End Connection Styles

See Table 5

### Outlet Pressure Ranges

See Tables 7 and 8

### Maximum Outlet (Casing) Pressure

See Table 9

### Temperature Capabilities

See Table 11

### Differential Pressure Ranges

See Tables 12 and 13

### Maximum Inlet Pressure and Pressure Drops

See Table 13




Figure 1. Type EZR Pressure Reducing Regulator

Figure 2. Type EZROX Pressure Reducing Regulator with Integral Slam-Shut Device

### IEC Sizing Coefficients

See Table 18

### Flow Capacities

See Tables 19 and 20

### Pressure Registration

External

### Shipping Weights

See Table 23

### Options

- Pre-piped Pilot Supply and Pilot Bleed
- Travel Indicator
- Inlet Strainer
- Type 252 Pilot Supply Filter
- Trim Package
- Relief Size-Reduction Trim
- Pilot Diaphragm for Pressure Loading

### Additional Technical Data

Scan or Click the QR code for more information on this product.




[www.Emerson.com](http://www.Emerson.com)


05/19

### Features

- **Tight Shutoff**
- **Robust**
- **Quiet Operation**
- **Internally Actuated**
- **Debris Protection**
- **High Accuracy**
- **Easy In-Line Maintenance**
- **In-Service Travel Indicator**



**Figure 3.** Type EZR with 161EB or 161AY Series Pilot, Type 112 Restrictor and Type 252 Filter Operational Schematic




**Figure 4.** Type EZR with PRX Series Pilot and Type 252 Filter Operational Schematic


# EZR Series

Pressure Reducing Regulator

FISHER™



161AY SERIES PILOT



TYPE EZROX WITH TYPE 161EB PILOT AND TYPE 252 PILOT SUPPLY FILTER

- █ INLET PRESSURE
- █ OUTLET PRESSURE
- █ ATMOSPHERIC PRESSURE
- █ LOADING PRESSURE

Figure 5. Type EZROX Operational Schematics





Table 1. Construction Material	
TYPE EZR MAIN VALVE CONSTRUCTION MATERIAL	
BODY	Cast iron, WCC Steel, or LCC Steel
BONNET	Steel
CAGE	Stainless steel
SPRING	Zinc-plated steel or Stainless steel
TOP PLUG	Stainless steel
BOTTOM PLUG	Stainless steel
INLET STRAINER	Stainless steel
DIAPHRAGM AND O-RING	Nitrile (NBR) or Fluorocarbon (FKM)
FLANGED LOCKNUT	Zinc-plated steel
BACKUP RING	Polytetrafluoroethylene (PTFE)
UPPER SPRING SEAT	Stainless steel
INDICATOR STEM	Stainless steel
INDICATOR FITTING	Stainless steel
TRAVEL INDICATOR PLUG	Stainless steel
TYPE EZROX SLAM-SHUT DEVICE CONSTRUCTION MATERIAL	
MECHANISM BOX	Aluminum alloy
FIRST AND SECOND STAGE MECHANISM	Steel
DIAPHRAGM	Nitrile (NBR)
BELLOW	Stainless steel

Table 2. 161EB Series Pilot Construction Material								
BODY	SPRING CASE	BODY PLUG	CONTROL SPRING	VALVE PLUG	ADJUSTING SCREW	DIAPHRAGM	DIAPHRAGM LIMITER	O-RING
Stainless steel	Stainless steel	Stainless steel	Zinc-plated steel	Nitrile (NBR) or Fluorocarbon (FKM)	Zinc-plated steel	Nitrile (NBR) or Fluorocarbon (FKM)	Stainless steel	Nitrile (NBR)

Table 3. 161AY Series Pilot Construction Material									
BODY	SPRING CASE AND LOWER CASING	STEM GUIDE	CONTROL SPRING	LEVER ASSEMBLY	PUSHER POST	DIAPHRAGM	O-RING	ORIFICE	DISK ASSEMBLY
Cast iron	Ductile iron	Stainless steel	Zinc-plated steel	Stainless steel	Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)	Nitrile (NBR) or Fluorocarbon (FKM)	Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)

Table 4. PRX Series Pilot Construction Material			
BODY	TRIM	ELASTOMER	DISK
Steel	Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)	Polyurethane (PU) or Fluorocarbon (FKM)

Table 5. Main Valve Body Size, End Connection Style and Body Rating					
TYPE	MAIN VALVE BODY SIZE	MAIN VALVE BODY MATERIAL	END CONNECTION STYLE <sup>(1)</sup>	STRUCTURAL DESIGN RATING <sup>(2)</sup>	
				psig	bar
EZR	NPS 2 x 1, 2, 3, 4 and 6 / DN 50 x 25, 50, 80, 100 and 150	Cast iron	NPT 2 x 1 and 2 only	400	28.0
			CL125 FF	200	14.0
	NPS 1, 1-1/4 x 1 <sup>(3)</sup> , 2 x 1, 2, 3, 4, 6 x 4 <sup>(4)</sup> , 8 x 4 <sup>(4)</sup> , 6, 8 x 6 <sup>(4)</sup> and 12 x 6 <sup>(4)</sup> / DN 25, 32 x 25 <sup>(3)</sup> , 50 x 25, 50, 80, 100, 150 x 100 <sup>(4)</sup> , 200 x 100 <sup>(4)</sup> , 150, 200 x 150 <sup>(4)</sup> and 300 x 150 <sup>(4)</sup>	WCC Steel	NPT or SWE NPS 1, 2 x 1 and 2 only / DN 25, 50 x 25 and 50 only	1500	103
			CL150 RF	290	20.0
			CL300 RF	750	52.0
			CL600 RF or BWE	1500	103
			CL150 RF	290	20.0
			CL300 RF	750	52.0
EZROX	NPS 1, 2 x 1, 2, 3, 4 and 6 / DN 25, 50 x 25, 50, 80, 100 and 150	WCC Steel	CL600 RF	1500	103
			CL150 RF	290	20.0
			CL300 RF	750	52.0
			CL600 RF	1500	103

1. Ratings and end connections for other than ASME standard can usually be provided. Contact your local Sales Office for assistance.

2. See Tables 9, 10, 11 and 13 for diaphragm materials and additional pressure ratings.

3. Available in steel NPT only.

4. NPS 6 x 4, 8 x 4, 8 x 6, 12 x 6 / DN 150 x 100, 200 x 100, 200 x 150, 300 x 150 Types EZR and 399 bodies are not the same as the EW valve bodies and are not interchangeable.

# EZR Series

## Pressure Reducing Regulator



**Table 6. Manometric Device Specifications<sup>(1)</sup>**

SPRING RANGE		SPRING COLOR	SPRING PART NUMBER	MAXIMUM SENSING INLET PRESSURE		MANOMETRIC SENSING DEVICE TYPE	MANOMETRIC SENSING DEVICE TYPE	SETPOINT TOLERANCE <sup>(1)</sup>		MAXIMUM DIFFERENCE BETWEEN OVERPRESSURE AND UNDERPRESSURE <sup>(2)</sup>	
				psig	bar			psig	bar	psig	bar
4.02 to 14.1 In. w.c.	10 to 35 mbar	Purple	T14232T0012	75	5.2	162	Diaphragm	0.058	0.004	0.145	0.01
9.97 to 33.2 In. w.c.	25 to 83 mbar	Orange	T14233T0012					0.073	0.005	0.363	0.03
18 In. w.c. to 2.0 psig	45 mbar to 0.14 bar	Red	T14234T0012					0.145	0.01	0.725	0.05
1.0 to 3.5	0.07 to 0.24	Yellow	T14235T0012					0.203	0.01	0.870	0.06
1.7 to 5.6	0.12 to 0.39	Green	T14236T0012					0.261	0.02	2.18	0.15
2 to 11	0.14 to 0.76	Gray	T14238T0012					0.725	0.05	5.08	0.35
4 to 19	0.28 to 1.3	Brown	T14239T0012					1.16	0.08	8.70	0.60
7 to 33	0.48 to 2.3	Black	T14240T0012					2.47	0.17	16.0	1.1
15 to 75	1.0 to 5.2	Blue	T14237T0012	5.08	0.35	36.3	2.5				
31 to 161	2.1 to 11.0	Brown	T14239T0012	235	16.2	71	Piston	10.2	0.70	79.8	5.5
59 to 235	4.1 to 16.2	Black	T14240T0012					23.2	1.6	145	10.0
235 to 323	16.2 to 22.3	Brown	T14239T0012	1470	101	27	Piston	43.5	3.0	Requires use of a Types BMS1 and BMS2	
323 to 588	22.3 to 40.5	Black	T14240T0012					94.3	6.5		
588 to 808	40.5 to 55.7	Brown	T14239T0012	1470	101	17	Bellows	102	7.0		
808 to 1470	55.7 to 101	Black	T14240T0012					174	12.0		
81 to 323	5.6 to 22.3	Brown	T14239T0012	514	35.4	236	Bellows	14.5	1.00	145	10.0
122 to 514	8.4 to 35.0	Black	T14240T0012					36.3	2.5	290	20.0
257 to 1058	17.7 to 72.9	Gray	T14238T0012	1058	72.9	315		72.5	5.0	479	33.0

1. Minimum suggested difference between slam-shut set pressure and normal operating pressure of the system.
2. Maximum difference between overpressure and underpressure when using one manometric device (Type BMS1) with tripping hook. For underpressure and overpressure points greater than this maximum number, use a second manometric device (Type BMS2) for underpressure protection.

**Table 7. Outlet (Control) Pressure Range and Typical Proportional Band**

TYPE	OUTLET (CONTROL) PRESSURE RANGE		PROPORTIONAL BAND <sup>(1)(3)</sup>		PILOT CONTROL SPRING INFORMATION					
	psig	bar	psig	bar	Part Number	Color Code	Wire Diameter		Free Length	
							In.	mm	In.	mm
161AY or 161AYM	6 to 15 In. w.c.	15 to 37 mbar	1 In. w.c. <sup>(2)</sup>	3 mbar <sup>(2)</sup>	18653927022	Olive Drab	0.105	2.67	3.75	95.3
	0.5 to 1.2	34 to 83 mbar	1 In. w.c. <sup>(2)</sup>	3 mbar <sup>(2)</sup>	18537027052	Yellow	0.114	2.90	4.31	109
	1.2 to 2.5	83 mbar to 0.17 bar	0.5 <sup>(2)</sup>	34 mbar <sup>(2)</sup>	18537127022	Light Green	0.156	3.96	4.13	105
	2.5 to 4.5	0.17 to 0.31	0.5 <sup>(2)</sup>	34 mbar <sup>(2)</sup>	18537227022	Light Blue	0.187	4.75	3.94	100
	4.5 to 7	0.31 to 0.48	0.5 <sup>(2)</sup>	34 mbar <sup>(2)</sup>	18537327052	Black	0.218	5.54	4.13	105
161EB or 161EBM	5 to 15	0.34 to 1.0	0.5 <sup>(2)</sup>	34 mbar <sup>(2)</sup>	1781260X012	White	0.120	3.05	3.75	95.3
	10 to 40	0.69 to 2.8	0.5 <sup>(2)</sup>	34 mbar <sup>(2)</sup>	1781262X012	Yellow	0.148	3.76	3.75	95.3
	30 to 75	2.1 to 5.2	0.6 <sup>(2)</sup>	41 mbar <sup>(2)</sup>	1781259X012	Black	0.187	4.75	4.00	102
	70 to 140	4.8 to 9.7	1.3 <sup>(2)</sup>	90 mbar <sup>(2)</sup>	1781261X012	Green	0.225	5.72	3.70	94.0
	130 to 200	9.0 to 13.8	1.5 <sup>(2)</sup>	0.10 <sup>(2)</sup>	1781263X012	Blue	0.262	6.66	3.85	97.8
200 to 350	13.8 to 24.1	3 <sup>(2)</sup>	0.21 <sup>(2)</sup>	1781264X012	Red	0.294	7.47	4.22	107	
161EB <sup>(4)</sup>	30 to 300	2.1 to 20.7	6	0.41	15A9258X012	Green	0.243	6.17	1.88	47.7
161EBH or 161EBHM	250 to 450	17.2 to 31.0	3.5	0.24 <sup>(5)</sup>	1781263X012	Blue	0.262	6.66	3.85	97.8
	400 to 700	27.6 to 48.2	7	0.48 <sup>(5)</sup>	1781264X012	Red	0.294	7.47	4.22	107

1. Proportional band includes outlet pressure drop plus hysteresis (friction), but does not include lockup.
2. Proportional band was determined with a pressure drop ranging from 50 to 150 psi / 3.4 to 10.3 bar. Approximately double the proportional band if the pressure drop is less than 50 psi / 3.4 bar.
3. With Type 112 restrictor set on 2. With Type PRX restrictor turn the restrictor screw one turn counterclockwise from fully seated.
4. Outlet (control) pressure range should only be used as the intermediate reduction pilot on the Type EZR worker/monitor systems.
5. Proportional band was determined with a pressure drop ranging from 100 to 300 psig / 6.9 to 20.7 bar. Approximately double the proportional band if the pressure drop is less than 100 psi / 6.9 bar.

**Table 8. Outlet (Control) Pressure Range and Accuracy Class**

TYPE	OUTLET (CONTROL) PRESSURE RANGE		ACCURACY CLASS <sup>(1)</sup>	PILOT CONTROL SPRING INFORMATION					
	psig	bar		Part Number	Color Code	Wire Diameter		Free Length	
						In.	mm	In.	mm
PRX/120 PRX/125	14.5 to 26	1.00 to 1.8	± 2.5%	M0255240X12	Yellow	0.110	2.79	2.16	54.9
	23 to 44	1.6 to 3.0		M0255230X12	Green	0.126	3.20	2.16	54.9
	41 to 80	2.8 to 5.5		M0255180X12	Blue	0.138	3.51	2.16	54.9
	73 to 123	5.0 to 8.5		M0255220X12	Black	0.157	3.99	2.16	54.9
	116 to 210	8.0 to 14.5	± 1%	M0255210X12	Silver	0.177	4.50	2.16	54.9
203 to 334	14.0 to 23.0	M0255200X12		Gold	0.197	5.00	2.00	50.8	
319 to 435	22.0 to 30.0	M0255860X12		Aluminum	0.236	6.00	2.00	50.8	
PRX/120-AP PRX/125-AP	435 to 1000	30.0 to 69.0	± 1%	M0273790X12	Clear	0.335	8.51	3.94	100

1. Proportional band and Accuracy Class include outlet pressure drop plus hysteresis (friction), but do not include lockup.






Figure 6. Diaphragm Marking

Table 9. Pilot Pressure Rating

TYPE	MAXIMUM INLET PRESSURE		MAXIMUM EMERGENCY OUTLET PRESSURE OR MAXIMUM EMERGENCY SENSE PRESSURE <sup>(1)</sup>		MAXIMUM BLEED (EXHAUST) PRESSURE FOR MONITOR PILOT	
	psig	bar	psig	bar	psig	bar
161AY	150	10.3	150	10.3	----	
161EB and 161EBH	1500	103	1200	82.7	----	
161AYM	150	10.3	150	10.3	150	10.3
161EBM and 161EBHM	1500	103	1200	82.7	1500	103
PRX Series	1480	102	1480	102	1480	102

1. Maximum pressure to prevent the casings from bursting during abnormal operation (leaking to atmosphere and internal parts damage may occur).

Table 10. Diaphragm Imprint Code

THICKNESS		MATERIAL		DIAPHRAGM MATERIAL
Imprint	Ink Code	Imprint	Ink Code	
2	130	2	17E68	17E68 - Nitrile (NBR) (low temperature)
		4	17E88	17E88 - Fluorocarbon (FKM) (high aromatic hydrocarbon content resistant)
		5	17E97	17E97 - Nitrile (NBR) (high-pressure and/or erosion resistant)

Table 11. Diaphragm Temperature Capabilities, Erosion Resistance and Chemical Compatibility

	17E68 NITRILE (NBR)	17E97 <sup>(1)</sup> NITRILE (NBR)	17E88 FLUOROCARBON (FKM)
Gas Temperature (for lower temperatures contact your local Sales Office)	-20 to 150°F / -29 to 66°C	0 to 150°F / -18 to 66°C	0 to 260°F / -18 to 127°C <sup>(2)</sup>
General Applications	Best for low temperatures	Best for high pressure conditions, i.e. transmission service or high pressure industrial service. It is also the best for abrasive or erosive service applications.	Best for natural gas having aromatic hydrocarbons. It is also the best for high temperature applications.
Heavy Particle Erosion	Fair	Excellent	Good
<b>Natural Gas With:</b>			
Up to 3% aromatic hydrocarbon content <sup>(3)</sup>	Good	Excellent	Excellent
3 to 15% aromatic hydrocarbon content <sup>(3)</sup>	Poor	Good	Excellent
15 to 50% aromatic hydrocarbon content <sup>(3)</sup>	Not recommended	Poor	Excellent
Up to 3% H <sub>2</sub> S (hydrogen sulfide or sour gas)	Good	Good	Good
Up to 3% ketone	Fair	Fair	Fair
Up to 10% alcohol	Good	Good	Fair
Up to 3% synthetic lube	Fair	Fair	Good

1. The NPS 6 / DN 150, 17E97 diaphragm will perform in gas temperatures as low as -20°F / -29°C.  
 2. For differential pressures above 400 psid / 27.6 bar d diaphragm temperature is limited to 150°F / 66°C.  
 3. The aromatic hydrocarbon content is based on percent volume.

# EZR Series

## Pressure Reducing Regulator



**Table 12. Main Valve Minimum Differential Pressures<sup>(1)</sup>**

MAIN VALVE BODY SIZE		MAIN SPRING PART NUMBER AND COLOR CODE	DIAPHRAGM MATERIAL	MINIMUM DIFFERENTIAL, PERCENT OF CAGE CAPACITY											
				For 90% Capacity						For 100% Capacity					
				100% Trim		60% Trim		30% Trim		100% Trim		60% Trim		30% Trim	
NPS	DN			psid	bar d	psid	bar d	psid	bar d	psid	bar d	psid	bar d	psid	bar d
1, 1-1/4 x 1	25, 32 x 25	19B2400X012, Light Blue	17E68 and 17E88	24	1.7	29	2.0	31	2.1	24	1.7	31	2.1	40	2.8
		GE12727X012, Black	17E97	35	2.4	38	2.6	42	2.9	35	2.4	39	2.7	52	3.6
			17E68 and 17E88	30	2.1	35	2.4	39	2.7	30	2.1	36	2.5	52	3.6
		19B2401X012, Black with White Stripe <sup>(3)</sup>	17E88 and 17E97	43	3.0	50	3.4	56	3.9	43	3.0	53	3.7	68	4.7
2 x 1	50 x 25	19B2400X012, Light Blue	17E68 and 17E88	24	1.7	29	2.0	31	2.1	24	1.7	31	2.1	40	2.8
		19B2401X012, Black with White Stripe	17E97	43	3.0	50	3.4	56	3.9	43	3.0	53	3.7	68	4.7
			17E68 and 17E88	43	3.0	50	3.4	56	3.9	43	3.0	53	3.7	68	4.7
		GE12501X012, Red Stripe <sup>(3)</sup>	17E97	68	4.7	73	5.0	88	6.1	72	5.0	81	5.6	102	7.0
2	50	19B0951X012, Yellow <sup>(2)</sup>	17E68 and 17E88	12	0.8	15	1.0	15	1.0	12	0.8	25	1.7	20	1.4
		18B2126X012, Green	17E97	24	1.7	25	1.7	26	1.8	24	1.7	30	2.1	37	2.6
			17E68 and 17E88	18	1.2	20	1.4	22	1.5	19	1.3	26	1.8	28	1.9
		18B5955X012, Red <sup>(3)</sup> GE05504X012, Purple <sup>(3)</sup>	17E88 and 17E97	29	2.0	29	2.0	31	2.1	31	2.1	35	2.4	43	3.0
3	80	T14184T0012, Yellow <sup>(2)</sup>	17E68 and 17E88	16	1.1	19	1.3	24	1.7	23	1.6	23	1.6	29	2.0
		19B0781X012, Light Blue	17E97	23	1.6	23	1.6	23	1.6	23	1.6	23	1.6	25	1.7
			17E68 and 17E88	21	1.5	22	1.5	28	1.9	28	1.9	28	1.9	33	2.3
		19B0782X012, Black <sup>(3)</sup>	17E88 and 17E97	32	2.2	33	2.3	43	3.0	38	2.6	38	2.6	50	3.4
4, 6 x 4 and 8 x 4	100, 150 x 100 and 200 x 100	T14184T0012, Yellow <sup>(2)</sup>	17E68, 17E88	10	0.7	12	0.8	14	1.0	25	1.7	25	1.7	25	1.7
		18B8501X012, Green	17E97	16	1.1	17	1.2	21	1.5	34	2.3	34	2.3	34	2.3
			17E68 and 17E88	16	1.1	17	1.2	20	1.4	30	2.1	30	2.1	30	2.1
		18B8502X012, Red <sup>(3)</sup>	17E88 and 17E97	21	1.5	24	1.7	26	1.8	40	2.8	40	2.8	40	2.8
6, 8 x 6 and 12 x 6	150, 200 x 150 and 300 x 150	19B0364X012, Yellow <sup>(2)</sup>	17E88	10	0.69	13	0.9	13	0.9	12	0.8	21	1.5	21	1.5
			17E97	10	0.69	11	0.8	14	1.0	12	0.8	16	1.1	16	1.1
		19B0366X012, Green	17E97	14	1.0	22	1.5	22	1.5	19	1.3	29	2.0	29	2.0
			17E88	17	1.2	21	1.5	21	1.5	20	1.4	36	2.5	36	2.5
19B0365X012, Red <sup>(3)</sup>	17E88 and 17E97	23	1.6	29	2.0	29	2.0	30	2.1	41	2.8	41	2.8		
8	200	GE09393X012, Yellow <sup>(2)</sup>	17E97	16	1.1	----	----			19	1.3	----	----		
		GE09396X012, Green		20	1.4					23	1.6				
		GE09397X012, Red <sup>(3)</sup>		26	1.8					30	2.1				

1. See Table 5 for structural design ratings, Table 9 for pilot ratings and Table 13 for maximum pressure ratings.  
 2. The white and yellow springs are only recommended for inlet pressures under 100 psig / 6.9 bar.  
 3. The red, black, purple, red stripe and black with white stripe springs are only recommended for applications where the maximum inlet pressure can exceed 500 psig / 34.5 bar.



**Table 13. Main Valve Maximum Pressure Ratings, Diaphragm Selection Information and Main Spring Selection<sup>(1)</sup>**

BODY SIZE		DIAPHRAGM MATERIAL	MAXIMUM OPERATING INLET PRESSURE <sup>(4)</sup>		MAXIMUM OPERATING DIFFERENTIAL PRESSURE <sup>(4)</sup>		MAXIMUM EMERGENCY INLET AND DIFFERENTIAL PRESSURE		MAIN SPRING COLOR	DIAPHRAGM DESIGNATION
NPS	DN		psig	bar	psid	bar d	psid	bar d		
1, 1-1/4 x 1	25, 32 x 25	17E68 Nitrile (NBR) Low temperature	100	6.9	100.0	6.9	100	6.9	Light Blue	130
			460	31.7	400.0	27.6	460	31.7	Black	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistant	500	34.5	500.0	34.5	1050	72.4	Black	
			1050	72.4	800.0	55.2	1050	72.4	Black with White Stripe <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Light Blue	
			500	34.5	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Black	
750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Black with White Stripe				
2 x 1	50 x 25	17E68 Nitrile (NBR) Low temperature	100	6.9	100.0	6.9	100	6.9	Light Blue	130
			360	24.8	300.0	20.7	360	24.8	Black with White Stripe	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistant	500	34.5	500.0	34.5	500	34.5	Black with White Stripe	
			1050	72.4	800.0	55.2	1050	72.4	Red Stripe <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Light Blue	
			750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Black with White Stripe	
2	50	17E68 Nitrile (NBR) Low temperature	100	6.9	100.0	6.9	100	6.9	Yellow	130
			460	31.7	400.0	27.6	460	31.7	Green	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistant	500	34.5	500.0	34.5	1050	72.4	Green	
			1050	72.4	800.0	55.2	1050	72.4	Red or Purple <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Yellow	
			500	34.5	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Green	
750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Red or Purple <sup>(2)</sup>				
3	80	17E68 Nitrile (NBR) Low temperature	100	6.9	100.0	6.9	100	6.9	Yellow	130
			360	24.8	300.0	20.7	500	34.5	Light Blue	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistant	500	34.5	500.0	34.5	1050	72.4	Light Blue	
			1050	72.4	800.0	55.2	1050	72.4	Black <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Yellow	
			500	34.5	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Light Blue	
750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Black <sup>(2)</sup>				
4, 6 x 4 and 8 x 4	100, 150 x 100 and 200 x 100	17E68 Nitrile (NBR) Low temperature	100	6.9	100	6.9	100	6.9	Yellow	130
			360	24.8	300.0	20.7	500	34.5	Green	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistant	500	34.5	500.0	34.5	1050	72.4	Green	
			1050	72.4	800.0	55.2	1050	72.4	Red <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Yellow	
			500	34.5	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Green	
750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Red <sup>(2)</sup>				
6, 8 x 6 and 12 x 6	150, 200 x 150 and 300 x 150	17E97 Nitrile (NBR) High-pressure and/or erosion resistant	100	6.9	100.0	6.9	100	6.9	Yellow	130
			500	34.5	500.0	34.5	1050	72.4	Green	
			1050	72.4	800.0	55.2	1050	72.4	Red <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistant	100	6.9	100.0	6.9	100	6.9	Yellow	
			500	34.5	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Green	
			750	51.7	500 <sup>(3)</sup>	34.5 <sup>(3)</sup>	750	51.7	Red <sup>(2)</sup>	
8	200	17E97 Nitrile (NBR) High-pressure and/or erosion resistant	100	6.9	100.0	6.9	100	6.9	Yellow	130
			500	34.5	500.0	34.5	1050	72.4	Green	
			1050	72.4	800.0	55.2	1050	72.4	Red <sup>(2)</sup>	

1. See Table 5 for main valve structural design ratings and Table 9 for pilot ratings.

2. The red, black, purple, red stripe and black with white stripe springs are only recommended for applications where the maximum inlet pressure can exceed 500 psig / 34.5 bar.

3. For differential pressures above 400 psid / 27.6 bar d diaphragm temperatures are limited to 150°F / 66°C.

4. These are recommendations that provide the best regulator performance for a typical application. Please contact your local Sales Office for further information if a deviation from the standard recommendations are required.

# EZR Series

## Pressure Reducing Regulator

FISHER™

**Table 14. Restrictor Flow Coefficients**

SET ON START			SET ON RUN			C <sub>1</sub>
C <sub>g</sub>	C <sub>v</sub>		C <sub>g</sub>	C <sub>v</sub>		
6	0.17		1	0.03		35

**Table 15. Pilot Flow Coefficients**

161AY SERIES				161EB SERIES				PRX SERIES						
Orifice Size		C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>	Orifice Size		C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>	Orifice Size		C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>
3/32 In.	2.4 mm	6.9	0.20	35	1/8 In.	3.2 mm	8.5	0.28	30.4	1/8 In.	3.2 mm	10.5	0.36	29
1/8 In.	3.2 mm	12.3	0.35		28.7	9.8	28.9	286	9.9	29.0	275	9.5	28.9	
1/4 In.	6.4 mm	50	1.43		26.3	5.6	26.4	142	5.4	26.1	147	5.6	26.3	

**Table 16. Main Valve Regulating Flow Coefficients for EZR Series, With or Without Slam-Shut Device**

MAIN VALVE BODY SIZE		CAGE STYLE, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE PIPING						2:1 LINE SIZE TO BODY SIZE PIPING					
			With Inlet Strainer			Without Inlet Strainer			With Inlet Strainer			Without Inlet Strainer		
NPS	DN		C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>1</sub>
1	25	100%	494	14.8	33.4	494	15.3	32.4	481	14.4	33.4	478	14.6	32.7
		60%	290	10.1	28.7	282	9.8	28.9	286	9.9	29.0	275	9.5	28.9
		30%	145	5.0	28.8	141	4.9	28.7	144	5.0	28.6	139	4.9	28.5
1-1/4 x 1	32 x 25	100%	572	17.0	33.7	573	16.5	34.6	547	16.1	34.1	550	15.9	34.7
		60%	283	10.5	26.9	291	10.8	26.9	293	10.9	26.7	303	11.3	26.9
		30%	145	5.5	26.3	149	5.6	26.4	142	5.4	26.1	147	5.6	26.3
2 x 1	50 x 25	100%	650	18.4	35.3	650	18.4	35.3	648	18.2	35.6	645	18.2	35.4
		60%	294	10.9	27.0	294	10.9	27.0	294	10.9	27.0	294	10.9	27.0
		30%	145	5.1	28.3	145	5.1	28.2	145	5.1	28.3	145	5.1	28.4
2	50	100%	1890	50.8	37.2	1970	54.6	36.1	1800	50.4	35.7	1840	53.0	34.7
		60%	1040	35.6	29.2	1050	36.3	28.9	1020	35.9	28.4	1020	35.9	28.4
		30%	570	21.4	26.6	570	21.4	26.6	560	21.5	26.0	560	21.5	26.0
3	80	100%	3550	91.4	38.8	3720	99.9	37.2	3390	90.6	37.4	3510	97.1	36.1
		60%	2000	70.3	28.5	2000	70.3	28.5	1970	67.5	29.2	1970	68.3	28.8
		30%	980	38.0	25.8	980	38.0	25.8	970	36.9	26.3	970	36.9	26.3
4	100	100%	5690	147	38.7	5830	154	37.9	5540	145	38.2	5640	151	37.4
		60%	3360	124	27.1	3360	124	27.1	3300	122	27.0	3300	121	27.3
		30%	1710	66.5	25.7	1710	66.5	25.7	1690	66.3	25.5	1690	66.8	25.3
6 x 4	150 x 100	100%	6150	159	38.7	6290	166	37.9	6142	161	38.2	6242	167	37.4
		60%	3790	140	27.1	3810	141	27.1	3930	146	27.0	3890	143	27.3
		30%	1900	74	25.7	1910	74	25.7	1970	77	25.5	1950	77	25.3
8 x 4	200 x 100	100%	6030	156	38.7	6170	163	37.9	5934	155	38.2	6034	161	37.4
		60%	3640	134	27.1	3700	137	27.1	3720	138	27.0	3730	137	27.3
		30%	1830	71	25.8	1860	72	25.8	1870	73	25.6	1880	74	25.3
6	150	100%	11,600	325	35.7	12,000	337	35.6	11,200	314	35.7	11,700	329	35.6
		60%	7120	239	29.8	7200	241	29.9	7150	240	29.8	7230	242	29.9
		30%	3560	135	26.4	3560	134	26.6	3570	135	26.4	3590	135	26.6
8 x 6	200 x 150	100%	13,400	376	35.7	13,700	385	35.6	12,940	363	35.7	13,360	376	35.6
		60%	8250	277	29.8	8290	277	29.9	8280	278	29.8	8320	279	29.9
		30%	4150	157	26.4	4150	156	26.6	4160	157	26.4	4180	157	26.6
12 x 6	300 x 150	100%	13,600	381	35.7	13,700	385	35.6	13,130	368	35.7	13,360	376	35.6
		60%	8210	276	29.8	8220	275	29.9	8240	277	29.8	8250	276	29.9
		30%	4110	155	26.4	4110	155	26.6	4120	156	26.4	4140	156	26.6
8	200	100%	19,700	505	39.0	20,100	517	38.9	19,500	503	38.8	19,700	509	38.7



**Table 17. Main Valve Wide-Open Flow Coefficients for EZR Series, With or Without Slam-Shut Device**

MAIN VALVE BODY SIZE		CAGE STYLE, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE PIPING						2:1 LINE SIZE TO BODY SIZE PIPING					
NPS	DN		With Inlet Strainer			Without Inlet Strainer			With Inlet Strainer			Without Inlet Strainer		
			C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
1	25	100%	509	15.2	33.5	509	15.7	32.5	495	14.8	33.5	493	15.0	32.9
		60%	299	10.4	28.7	291	10.1	28.8	295	10.1	29.0	284	9.8	28.9
		30%	149	5.2	28.8	145	5.1	28.7	148	5.2	28.6	143	5.0	28.5
1-1/4 x 1	32 x 25	100%	590	17.5	33.7	590	17.0	34.6	564	16.5	34.1	566	16.3	34.7
		60%	291	10.8	26.9	299	11.2	26.9	301	11.3	26.7	312	11.6	26.9
		30%	149	5.7	26.3	154	5.8	26.4	146	5.6	26.1	151	5.8	26.3
2 x 1	50 x 25	100%	670	19.0	35.3	670	19.0	35.3	667	18.7	35.6	664	18.7	35.4
		60%	303	11.2	27.0	303	11.2	27.0	303	11.2	27.0	303	11.2	27.0
		30%	149	5.3	28.3	149	5.3	28.2	149	5.3	28.3	149	5.3	28.4
2	50	100%	1950	52.4	37.2	2030	56.2	36.1	1850	51.8	35.7	1900	54.6	34.7
		60%	1070	36.6	29.2	1080	37.4	28.9	1050	37.0	28.4	1050	37.0	28.4
		30%	590	22.2	26.6	590	22.2	26.6	580	22.3	26.0	580	22.3	26.0
3	80	100%	3660	94.1	38.8	3830	102.9	37.2	3490	93.3	37.4	3620	100.2	36.1
		60%	2060	72.4	28.5	2060	72.4	28.5	2030	69.5	29.2	2030	70.0	28.8
		30%	1010	39.1	25.8	1010	39.1	25.8	1000	38.0	26.3	1000	38.0	26.3
4	100	100%	5860	151	38.7	6000	158	37.9	5710	149	38.2	5810	155	37.4
		60%	3460	128	27.1	3460	128	27.1	3400	125	27.3	3400	125	27.3
		30%	1760	68.5	25.7	1770	68.2	26.0	1740	68.2	25.5	1740	68.8	25.3
6 x 4	150 x 100	100%	6250	162	38.7	6390	169	37.9	6131	161	38.2	6231	167	37.4
		60%	3850	142	27.1	3870	143	27.1	3920	144	27.3	3880	142	27.3
		30%	1940	75	25.7	1940	75	26.0	1970	77	25.5	1950	77	25.3
8 x 4	200 x 100	100%	6100	158	38.7	6240	165	37.9	5930	155	38.2	6030	161	37.4
		60%	3680	136	27.1	3750	138	27.1	3720	136	27.3	3720	136	27.3
		30%	1850	72	25.8	1880	72	26.1	1870	73	25.6	1880	74	25.3
6	150	100%	11,950	335	35.7	12,360	348	35.5	11,540	323	35.7	12,050	339	35.5
		60%	7330	246	29.8	7420	248	29.9	7360	247	29.8	7450	249	29.9
		30%	3670	139	26.5	3670	138	26.6	3680	139	26.5	3700	139	26.6
8 x 6	200 x 150	100%	13,800	386	35.7	14,110	397	35.5	13,330	373	35.7	13,760	387	35.6
		60%	8490	285	29.8	8540	286	29.9	8520	286	29.8	8570	287	29.9
		30%	4280	162	26.5	4280	161	26.6	4290	162	26.5	4310	162	26.6
12 x 6	300 x 150	100%	14,010	392	35.7	14,110	397	35.5	13,530	379	35.7	13,760	387	35.6
		60%	8450	284	29.8	8470	283	29.9	8480	285	29.8	8500	284	29.9
		30%	4240	160	26.5	4240	159	26.6	4250	160	26.5	4270	160	26.6
8	200	100%	20,300	520	39.0	20,700	533	38.8	20,100	518	38.8	20,300	524	38.7

**Table 18. IEC Sizing Coefficients<sup>(1)</sup>**

MAIN VALVE BODY SIZE		X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
NPS	DN			
1	25	0.71	0.06	0.94
2	50	0.88	0.09	0.96
3	80	0.95	0.09	0.97
4	100	0.95	0.09	0.92
6	150	0.81	0.13	0.91
8	200	0.96	0.10	0.89

1. At 100% capacity.

# EZR Series

## Pressure Reducing Regulator



**Table 19. Capacities for EZR Series with Type 161AY or 161AYM Pilot**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
25	1.7	up to 2.5	up to 0.17	----	----	101	2.7	191	5.1	299	8.0	586	15.7	941	25.2
		3	0.21	----	----	95	2.5	177	4.7	275	7.4	583	15.6	936	25.1
		5	0.34	----	----	93	2.5	173	4.6	268	7.2	571	15.3	912	24.4
		7	0.48	----	----	----	----	----	----	260	7.0	556	14.9	884	23.7
30	2.1	up to 4.5	up to 0.31	28.0	0.75	114	3.1	215	5.8	336	9.0	660	17.7	1062	28.5
		7	0.48	----	----	105	2.8	196	5.2	304	8.1	646	17.3	1033	27.7
35	2.4	up to 6	up to 0.41	31.3	0.84	126	3.4	239	6.4	374	10.0	738	19.7	1187	31.8
		7	0.48	31.1	0.83	119	3.2	223	6.0	346	9.3	732	19.6	1177	31.5
40	2.8	up to 7	up to 0.48	34.5	0.93	139	3.7	262	7.0	411	11.0	817	21.9	1317	35.3
45	3.1			37.9	1.02	152	4.1	286	7.7	449	12.0	900	24.1	1455	39.0
50	3.4			41.2	1.10	164	4.4	310	8.3	487	13.1	981	26.3	1592	42.7
55	3.8			44.4	1.19	177	4.7	334	8.9	524	14.0	1062	28.5	1727	46.3
60	4.1	up to 7	up to 0.48	47.6	1.28	190	5.1	358	9.6	562	15.1	1143	30.6	1862	49.9
65	4.5			50.8	1.36	203	5.4	382	10.2	599	16.1	1223	32.8	1996	53.5
70	4.8			54.0	1.45	215	5.8	406	10.9	637	17.1	1302	34.9	2129	57.1
75	5.2			57.2	1.53	228	6.1	430	11.5	675	18.1	1381	37.0	2261	60.6
80	5.5	up to 7	up to 0.48	60.3	1.62	241	6.5	454	12.2	712	19.1	1460	39.1	2394	64.2
90	6.2			66.6	1.79	253	6.8	478	12.8	750	20.1	1617	43.3	2658	71.2
100	6.9			72.9	1.95	266	7.1	502	13.5	787	21.1	1773	47.5	2920	78.3
125	8.6			88.4	2.37	355	9.5	670	18.0	1051	28.2	2163	58.0	3575	95.8
150	10.3			104	2.79	419	11.2	790	21.2	1239	33.2	2551	68.4	4227	113

Note: Blank areas indicate where minimum main valve differential pressure is not met.

- continued -

**Table 19. Capacities for EZR Series with Type 161AY or 161AYM Pilot (continued)**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1-1/4 x 1 / DN 32 x 25		NPS 2 x 1 / DN 50 x 25		NPS 6 x 4 / DN 150 x 100		NPS 8 x 4 / DN 200 x 100		NPS 8 x 6 / DN 200 x 150		NPS 12 x 6 / DN 300 x 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
25	1.7	up to 2.5	up to 0.17	----	----	----	----	299	8.0	294	7.9	669	17.9	669	17.9
		3	0.21	----	----	----	----	297	8.0	292	7.8	666	17.8	666	17.8
		5	0.34	----	----	----	----	290	7.8	285	7.6	652	17.5	652	17.5
		7	0.48	----	----	----	----	281	7.5	277	7.4	634	17.0	634	17.0
30	2.1	up to 4.5	up to 0.31	35.9	1.0	35.9	1.0	337	9.0	331	8.9	754	20.2	754	20.2
		7	0.48	35.1	0.9	----	----	328	8.8	323	8.7	737	19.8	737	19.8
35	2.4	up to 6	up to 0.41	40.1	1.1	40.1	1.1	376	10.1	370	9.9	842	22.6	842	22.6
		7	0.48	39.8	1.1	39.8	1.1	374	10.0	367	9.8	836	22.4	836	22.4
40	2.8	up to 7	up to 0.48	44.4	1.2	44.4	1.2	417	11.2	411	11.0	933	25.0	933	25.0
45	3.1			48.9	1.3	48.9	1.3	461	12.4	454	12.2	1027	27.5	1027	27.5
50	3.4			53.3	1.4	53.3	1.4	504	13.5	496	13.3	1120	30.0	1120	30.0
55	3.8			57.7	1.5	57.7	1.5	546	14.6	537	14.4	1213	32.5	1213	32.5
60	4.1	up to 7	up to 0.48	62.0	1.7	62.0	1.7	588	15.8	579	15.5	1304	34.9	1304	34.9
65	4.5			66.3	1.8	66.3	1.8	630	16.9	620	16.6	1396	37.4	1396	37.4
70	4.8			70.6	1.9	70.6	1.9	672	18.0	661	17.7	1486	39.8	1486	39.8
75	5.2			74.9	2.0	74.9	2.0	714	19.1	702	18.8	1577	42.3	1577	42.3
80	5.5	up to 7	up to 0.48	79.2	2.1	79.2	2.1	755	20.2	743	19.9	1667	44.7	1667	44.7
90	6.2			87.7	2.3	87.7	2.3	838	22.5	825	22.1	1846	49.5	1846	49.5
100	6.9			96.1	2.6	96.1	2.6	920	24.7	906	24.3	2025	54.3	2025	54.3
125	8.6			117	3.1	117	3.1	1126	30.2	1108	29.7	2470	66.2	2470	66.2
150	10.3			138	3.7	138	3.7	1330	35.7	1309	35.1	2913	78.1	2913	78.1

Note: Blank areas indicate where minimum main valve differential pressure is not met.





**Table 20. Capacities for EZR Series with Type 161EB, 161EBM or PRX Series Pilot**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
30	2.1	5	0.35	28	0.7	107	2.8	200	5.4	310	8.3	658	17.6	1056	28.3
		10	0.69	----	----	101	2.7	188	5.0	292	7.8	623	16.7	991	26.6
40	2.8	8	0.55	34	0.9	139	3.7	262	7.0	411	11.0	812	21.8	1307	35.0
		15	1.0	33	0.9	125	3.3	232	6.2	360	9.6	767	20.6	1221	32.7
		20	1.38	----	----	117	3.1	216	5.8	335	9.0	719	19.3	1134	30.4
50	3.5	12	0.83	41	1.1	164	4.4	310	8.3	487	13.1	961	25.8	1548	41.5
		15	1.0	40	1.1	154	4.1	287	7.7	446	12.0	945	25.3	1516	40.6
		25	1.7	38	1.0	141	3.8	261	7.0	404	10.8	865	23.2	1368	36.7
		30	2.1	----	----	131	3.5	242	6.5	373	10.0	804	21.5	1263	33.8
60	4.1	16	1.1	47	1.3	190	5.1	358	9.6	562	15.1	1111	29.8	1788	47.9
		25	1.7	45	1.2	172	4.6	319	8.5	495	13.3	1055	28.3	1680	45.0
		35	2.4	42	1.1	155	4.1	287	7.7	444	11.9	954	25.6	1501	40.2
		40	2.8	----	----	143	3.8	264	7.1	409	11.0	882	23.6	1380	37.0
75	5.2	22	1.5	57	1.5	228	6.1	430	11.5	675	18.1	1334	35.8	2149	57.6
		35	2.4	54	1.4	203	5.4	378	10.1	585	15.7	1250	33.5	1986	53.2
		50	3.5	47	1.3	175	4.7	322	8.6	498	13.3	1075	28.8	1684	45.1
		55	3.8	----	----	160	4.3	296	7.9	456	12.2	988	26.5	1541	41.3
100	6.9	32	2.2	72	1.9	291	7.8	550	14.7	863	23.1	1707	45.7	2750	73.7
		60	4.1	65	1.7	241	6.5	447	12.0	691	18.5	1485	39.8	2340	62.7
		75	5.2	55	1.5	203	5.4	375	10.1	578	15.5	1252	33.6	1952	52.3
		80	5.5	----	----	186	5.0	342	9.2	527	14.1	1144	30.7	1777	47.6
125	8.6	43	3.0	88	2.4	355	9.5	670	18.0	1051	28.2	2076	55.6	3342	89.6
		60	4.1	85	2.3	321	8.6	595	15.9	923	24.7	1969	52.8	3134	84.0
		90	6.2	71	1.9	261	7.0	482	12.9	745	20.0	1609	43.1	2515	67.4
		105	7.2	----	----	208	5.6	382	10.2	589	15.8	1282	34.4	1985	53.2
150	10.3	52	3.6	104	2.8	419	11.2	790	21.2	1239	33.2	2453	65.7	3953	106
		60	4.1	103	2.8	393	10.5	732	19.6	1137	30.5	2412	64.6	3868	104
		95	6.5	92	2.5	342	9.2	632	16.9	977	26.2	2102	56.3	3308	88.7
		130	9.0	----	----	228	6.1	419	11.2	646	17.3	1406	37.7	2175	58.3
200	13.8	73	5.0	135	3.6	546	14.6	1030	27.6	1615	43.3	3194	85.6	5145	138
		110	7.6	127	3.4	479	12.8	887	23.8	1375	36.9	2941	78.8	4662	125
		150	10.3	106	2.8	390	10.5	720	19.3	1112	29.8	2406	64.5	3753	101
		180	12.4	----	----	264	7.1	484	13.0	746	20.0	1628	43.6	2511	67.3
300	20.7	115	7.9	198	5.3	800	21.4	1510	40.5	2367	63.4	4677	125	7531	202
		170	11.7	186	5.0	698	18.7	1295	34.7	2006	53.8	4292	115	6801	182
		225	15.5	157	4.2	577	15.5	1065	28.5	1645	44.1	3557	95.3	5553	149
		250	17.0	134	3.6	489	13.1	901	24.1	1389	37.2	3019	80.9	4682	125
		280	19.3	----	----	324	8.7	594	15.9	914	24.5	1998	53.5	3076	82.4
400	27.6	155	10.7	261	7.0	1054	28.2	1990	53.3	3119	83.6	6169	165	9936	266
		200	13.8	253	6.8	961	25.8	1785	47.8	2769	74.2	5899	158	9405	252
		250	17.2	237	6.3	883	23.7	1635	43.8	2530	67.8	5432	146	8568	230
		300	20.9	208	5.6	764	20.5	1410	37.8	2177	58.3	4709	126	7352	197
		350	24.1	158	4.2	572	15.3	1052	28.2	1621	43.4	3530	94.6	5458	146
		380	26.0	----	----	374	10.0	686	18.4	1056	28.3	2311	61.9	3552	95.2

1. For outlet pressures above 435 psig / 30 bar, use Type PRX-AP pilot rather than Type PRX.  
Note: Blank areas indicate where minimum main valve differential pressure is not met.

- continued -

# EZR Series

## Pressure Reducing Regulator

FISHER®

**Table 20. Capacities for EZR Series with Type 161EB, 161EBM or PRX Series Pilot (continued)**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200	
psig	bar	psig	bar	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h	SCFH	Nm³/h
500	34.5	196	13.5	324	8.7	1308	35.1	2470	66.2	3871	104	7656	205	12,331	330
		250	17.2	315	8.4	1195	32.0	2220	59.5	3444	92.3	7334	197	11,697	313
		300	20.7	299	8.0	1121	30.0	2078	55.7	3217	86.2	6894	185	10,900	292
		350	24.1	275	7.4	1018	27.3	1881	50.4	2907	77.9	6268	168	9827	263
		400	28.0	238	6.4	871	23.3	1604	43.0	2475	66.3	5367	144	8348	224
		450	31.0	178	4.8	644	17.3	1183	31.7	1823	48.9	3977	107	6137	164
		480	33.0	----	----	418	11.2	768	20.6	1182	31.7	2586	69.3	3972	106
600	41.4	237	16.3	387	10.4	1562	41.9	2950	79.1	4623	124	9143	245	14,726	395
		250	17.2	386	10.3	1481	39.7	2760	74.0	4287	115	9079	243	14,593	391
		300	20.7	376	10.1	1428	38.3	2655	71.2	4119	111	8770	235	13,989	375
		350	24.1	362	9.70	1358	36.4	2517	67.5	3899	104	8346	224	13,217	354
		400	28.0	340	9.1	1264	33.9	2337	62.6	3614	96.9	7777	208	12,229	328
		500	34.0	265	7.1	966	25.9	1777	47.6	2741	73.5	5956	160	9240	248
		550	38.0	196	5.2	709	19.0	1302	34.9	2006	53.8	4379	117	6749	181
580	40.0	----	----	459	12.3	841	22.5	1295	34.7	2834	76.0	4352	117		
700	48.3	250	17.0	453	12.1	1755	47.0	3278	87.9	5099	134	10,751	288	17,381	466
		278	19.2	450	12.1	1816	48.7	3430	91.9	5375	144	10,630	285	17,121	459
		300	20.7	447	11.9	1715	46.0	3196	85.7	4964	133	10,519	282	16,892	453
		350	24.1	438	11.7	1662	44.5	3090	82.8	4793	128	10,205	273	16,282	436
		400	28.0	424	11.4	1594	42.7	2956	79.2	4579	123	9793	262	15,526	416
		500	34.0	377	10.1	1393	37.3	2572	68.9	3975	107	8577	230	13,435	360
		600	41.0	290	7.8	1052	28.2	1936	51.9	2984	80.0	6493	174	10,055	269
800	55.2	300	21.0	515	13.8	2070	55.5	3910	105	6127	164	12,202	327	19,697	528
		350	24.1	509	13.6	2070	55.5	3910	105	6127	164	11,958	320	19,189	514
		400	28.0	499	13.4	1896	50.8	3525	94.5	5468	147	11,640	312	18,574	498
		500	34.0	467	12.5	1745	46.8	3231	86.6	5001	134	10,732	288	16,938	454
		600	41.0	411	11.0	1512	40.5	2789	74.7	4308	115	9314	250	14,547	390
		700	48.0	312	8.4	1133	30.4	2082	55.8	3209	86.0	6990	187	10,809	290
		----	----	----	----	----	----	----	----	----	----	----	----	----	----
900	62.1	350	24.1	577	15.5	2325	62.3	4389	118	6879	184	13,651	366	22,008	590
		400	28.0	571	15.3	2184	58.5	4067	109	6316	169	13,396	359	21,486	576
		500	34.0	547	14.7	2064	55.3	3830	103	5935	159	12,679	340	20,133	540
		600	41.0	507	13.6	1886	50.5	3487	93.5	5394	145	11,604	311	18,250	489
		700	48.0	442	11.8	1622	43.5	2991	80.2	4617	124	10,000	268	15,584	418
1000	68.9	350	24.1	644	17.3	2579	69.1	4869	130	7631	205	15,306	410	24,771	664
		400	28.0	639	17.1	2579	69.1	4869	130	7631	205	15,096	405	24,316	652
		500	34.0	622	16.7	2364	63.4	4394	118	6817	183	14,510	389	23,158	621
		600	41.0	592	15.9	2220	59.5	4115	110	6372	171	13,650	366	21,592	579
		700	48.0	545	14.6	2017	54.1	3727	99.9	5762	154	12,420	333	19,480	522
1050	72.4	350	24.1	677	18.1	2706	72.5	5109	137	8007	215	16,124	432	26,138	700
		400	28.0	673	18.0	2706	72.5	5109	137	8007	215	15,932	427	25,710	689
		500	34.0	658	17.6	2509	67.4	4668	125	7245	194	15,398	413	24,627	660
		600	41.0	632	16.9	2379	63.8	4412	118	6826	183	14,618	392	23,181	621
		700	48.0	591	15.8	2196	58.9	4063	109	6283	168	13,517	362	21,261	570
900	62.0	432	11.6	1572	42.2	2892	77.6	4459	120	9694	260	15,024	403		

1. For outlet pressures above 435 psig / 30 bar, use Type PRX-AP pilot rather than Type PRX.  
 Note: Blank areas indicate where minimum main valve differential pressure is not met.

- continued -



**Table 20. Capacities for EZR Series with Type 161EB, 161EBM or PRX Series Pilot (continued)**

INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1-1/4 x 1 / DN 32 x 25		NPS 2 x 1 / DN 50 x 25		NPS 6 x 4 / DN 150 x 100		NPS 8 x 4 / DN 200 x 100		NPS 8 x 6 / DN 200 x 150		NPS 12 x 6 / DN 300 x 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
30	2.1	5	0.35	32	0.9	36	1.0	335	8.9	330	8.8	751	20.1	751	20.1
		10	0.69	----	----	----	----	315	8.4	310	8.3	712	19.1	712	19.1
40	2.8	8	0.55	39	1.0	44	1.2	415	11.1	408	10.9	927	24.8	927	24.8
		15	1.0	37	1.0	42	1.1	388	10.4	382	10.2	876	23.5	876	23.5
		20	1.4	----	----	----	----	362	9.7	356	9.5	821	22.0	821	22.0
50	3.5	12	0.8	46	1.2	52	1.4	491	13.2	483	12.9	1098	29.4	1098	29.4
		15	1.0	46	1.2	51	1.4	481	12.9	473	12.7	1079	28.9	1079	28.9
		25	1.7	42	1.1	47	1.3	436	11.7	429	11.5	988	26.5	988	26.5
		30	2.1	----	----	----	----	403	10.8	397	10.6	918	24.6	918	24.6
60	4.1	16	1.1	54	1.4	60	1.6	567	15.2	558	15.0	1268	34.0	1268	34.0
		25	1.7	51	1.4	57	1.5	534	14.3	526	14.1	1204	32.3	1204	32.3
		35	2.4	46	1.2	52	1.4	479	12.8	471	12.6	1089	29.2	1089	29.2
		40	2.8	----	----	----	----	441	11.8	434	11.6	1007	27.0	1007	27.0
75	5.2	22	1.5	64	1.7	73	2.0	681	18.3	671	18.0	1523	40.8	1523	40.8
		35	2.4	61	1.6	68	1.8	632	16.9	622	16.7	1427	38.2	1427	38.2
		50	3.5	52	1.4	59	1.6	538	14.4	529	14.2	1227	32.9	1227	32.9
		55	3.8	----	----	----	----	493	13.2	485	13.0	1128	30.2	1128	30.2
100	6.9	32	2.2	82	2.2	93	2.5	872	23.4	858	23.0	1949	52.2	1949	52.2
		60	4.1	72	1.9	81	2.2	746	20.0	734	19.7	1695	45.4	1695	45.4
		75	5.2	61	1.6	68	1.8	624	16.7	614	16.5	1430	38.3	1430	38.3
		80	5.5	----	----	----	----	569	15.2	560	15.0	1306	35.0	1306	35.0
125	8.6	43	3.0	100	2.7	113	3.0	1060	28.4	1043	28.0	2370	63.5	2370	63.5
		60	4.1	95	2.5	107	2.9	997	26.7	981	26.3	2248	60.2	2248	60.2
		90	6.2	79	2.1	88	2.4	804	21.5	791	21.2	1837	49.2	1837	49.2
		105	7.2	----	----	----	----	636	17.0	626	16.8	1463	39.2	1463	39.2
150	10.3	52	3.6	118	3.2	133	3.6	1253	33.6	1233	33.0	2801	75.1	2801	75.1
		60	4.1	117	3.1	131	3.5	1228	32.9	1208	32.4	2754	73.8	2754	73.8
		95	6.6	102	2.7	114	3.1	1055	28.3	1039	27.8	2400	64.3	2400	64.3
		130	9.0	----	----	----	----	697	18.7	686	18.4	1606	43.0	1606	43.0
200	13.8	73	5.0	154	4.1	174	4.7	1631	43.7	1605	43.0	3647	97.7	3647	97.7
		110	7.6	143	3.8	160	4.3	1485	39.8	1461	39.2	3357	90.0	3357	90.0
		150	10.3	117	3.1	131	3.5	1200	32.2	1181	31.7	2746	73.6	2746	73.6
		180	12.4	----	----	----	----	806	21.6	793	21.2	1858	49.8	1858	49.8
300	20.7	115	7.9	226	6.1	254	6.8	2388	64.0	2350	63.0	5339	143	5339	143
		170	11.7	208	5.6	234	6.3	2166	58.0	2132	57.1	4900	131	4900	131
		225	15.5	174	4.7	194	5.2	1776	47.6	1747	46.8	4061	109	4061	109
		250	17.2	148	4.0	165	4.4	1500	40.2	1476	39.6	3447	92.4	3447	92.4
		280	19.3	----	----	----	----	987	26.5	972	26.0	2281	61.1	2281	61.1
400	27.6	155	10.7	298	8.0	335	9.0	3150	84.4	3100	83.1	7043	189	7043	189
		200	13.8	286	7.7	321	8.6	2990	80.1	2943	78.9	6734	180	6734	180
		250	17.2	264	7.1	296	7.9	2732	73.2	2689	72.1	6202	166	6202	166
		300	20.7	230	6.2	257	6.9	2351	63.0	2313	62.0	5376	144	5376	144
		350	24.1	173	4.6	193	5.2	1750	46.9	1722	46.2	4030	108	4030	108
		380	26.2	----	----	----	----	1141	30.6	1123	30.1	2638	70.7	2638	70.7

1. For outlet pressures above 435 psig / 30 bar, use Type PRX-AP pilot rather than Type PRX.  
Note: Blank areas indicate where minimum main valve differential pressure is not met.

- continued -

# EZR Series


## Pressure Reducing Regulator

FISHER™

**Table 20. Capacities for EZR Series with Type 161EB, 161EBM or PRX Series Pilot (continued)**


INLET PRESSURE		OUTLET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS USING 1:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAINER											
				NPS 1-1/4 x 1 / DN 32 x 25		NPS 2 x 1 / DN 50 x 25		NPS 6 x 4 / DN 150 x 100		NPS 8 x 4 / DN 200 x 100		NPS 8 x 6 / DN 200 x 150		NPS 12 x 6 / DN 300 x 150	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
500	34.5	196	13.5	369	9.9	416	11.1	3910	105	3847	103	8740	234	8740	234
		250	17.2	355	9.5	399	10.7	3719	99.7	3659	98.1	8373	224	8373	224
		300	20.9	335	9.0	375	10.1	3473	93.1	3418	91.6	7870	211	7870	211
		350	24.1	305	8.2	342	9.2	3139	84.1	3089	82.8	7156	192	7156	192
		400	28.0	262	7.0	293	7.8	2672	71.6	2630	70.5	6128	164	6128	164
		450	31.0	195	5.2	217	5.8	1969	52.8	1937	51.9	4540	122	4540	122
		480	33.1	----	----	----	----	1276	34.2	1256	33.7	2952	79.1	2952	79.1
600	41.4	237	16.3	441	11.8	497	13.3	4669	125	4595	123	10,438	280	10,438	280
		250	17.2	438	11.7	493	13.2	4629	124	4556	122	10,365	278	10,365	278
		300	20.9	424	11.4	477	12.8	4447	119	4376	117	10,012	268	10,012	268
		350	24.1	405	10.9	454	12.2	4210	113	4143	111	9528	255	9528	255
		400	28.0	378	10.1	424	11.4	3903	105	3841	103	8879	238	8879	238
		500	34.5	291	7.8	325	8.7	2960	79.3	2913	78.1	6800	182	6800	182
		550	38.0	215	5.8	239	6.4	2166	58.0	2131	57.1	4999	134	4999	134
580	40.0	----	----	----	----	1398	37.5	1376	37.0	3236	86.7	3236	86.7		
700	48.3	250	17.2	518	13.9	584	15.6	5505	148	5418	145	12,274	329	12,274	329
		278	19.2	513	13.7	578	15.5	5428	145	5342	143	12,136	325	12,136	325
		300	20.7	508	13.6	572	15.3	5360	144	5275	141	12,009	322	12,009	322
		350	24.1	494	13.2	555	14.9	5175	139	5093	136	11,650	312	11,650	312
		400	28.0	475	12.7	533	14.3	4944	132	4865	130	11,180	300	11,180	300
		500	34.5	418	11.2	467	12.5	4292	115	4224	113	9793	262	9793	262
		600	41.4	318	8.5	354	9.5	3222	86.4	3171	85.0	7413	199	7413	199
800	55.2	300	21.0	588	15.8	663	17.8	6241	167	6142	165	13,931	373	13,931	373
		350	24.1	578	15.5	650	17.4	6090	163	5993	161	13,652	366	13,652	366
		400	28.0	563	15.1	633	17.0	5904	158	5810	156	13,289	356	13,289	356
		500	34.5	522	14.0	584	15.7	5400	145	5314	142	12,253	328	12,253	328
		600	41.4	454	12.2	508	13.6	4651	125	4577	123	10,634	285	10,634	285
		700	48.0	342	9.2	381	10.2	3465	92.9	3410	91.4	7980	214	7980	214
		700	48.0	342	9.2	381	10.2	3465	92.9	3410	91.4	7980	214	7980	214
900	62.1	350	24.1	658	17.6	742	19.9	6976	187	6865	184	15,584	418	15,584	418
		400	28.0	647	17.3	728	19.5	6820	183	6711	180	15,294	410	15,294	410
		500	34.5	615	16.5	690	18.5	6408	172	6306	169	14,475	388	14,475	388
		600	41.4	565	15.1	632	16.9	5824	156	5731	154	13,247	355	13,247	355
		700	48.0	488	13.1	545	14.6	4985	134	4906	131	11,416	306	11,416	306
1000	68.9	350	24.1	737	19.8	831	22.3	7844	210	7719	207	17,474	468	17,474	468
		400	28.0	728	19.5	820	22.0	7709	207	7587	203	17,235	462	17,235	462
		500	34.5	702	18.8	789	21.1	7361	197	7243	194	16,566	444	16,566	444
		600	41.4	663	17.8	743	19.9	6880	184	6770	181	15,584	418	15,584	418
		700	48.0	605	16.2	677	18.1	6221	167	6122	164	14,179	380	14,179	380
1050	72.4	350	24.1	776	20.8	875	23.5	8273	222	8141	218	18,408	493	18,408	493
		400	28.0	768	20.6	866	23.2	8147	218	8018	215	18,189	487	18,189	487
		500	34.5	745	20.0	837	22.4	7823	210	7699	206	17,579	471	17,579	471
		600	41.4	709	19.0	796	21.3	7381	198	7263	195	16,688	447	16,688	447
		700	48.0	658	17.6	736	19.7	6784	182	6677	179	15,432	414	15,432	414
		900	62.0	474	12.7	529	14.2	4811	129	4719	127	11,068	297	11,068	297

1. For outlet pressures above 435 psig / 30 bar, use Type PRX-AP pilot rather than Type PRX.  
 Note: Blank areas indicate where minimum main valve differential pressure is not met.



82482

TYPE EZR WITH 161AY SERIES PILOT



82483

TYPE EZR WITH 161EB SERIES PILOT

Figure 7. Typical EZR Dimensions


Table 21. Type EZR Dimension

BODY SIZE, NPS / DN	DIMENSIONS, IN. / mm													
	A						E			F			G	V
	SWE NPT	125FF 150RF	250RF 300RF	600RF BWE	C	D	161AY	161EB	PRX	161AY	161EB	PRX		
1, 1-1/4 / 25, 32	8.25 / 210	7.25 / 184	7.75 / 197	8.25 / 210	2 / 51	2.5 / 64	15.7 / 399	6.23 / 158	6.54 / 6.54	10.1 / 257	12.67 / 322	10.89 / 276	8.67 / 220	8 / 203
2, 2 X 1 / 50, 50 X 25	11.25 / 286	10 / 254	10.5 / 267	11.25 / 286	2 / 51	3.06 / 78	15.8 / 401	6.6 / 168	7.2 / 183	10.17 / 258	12.96 / 329	11.13 / 283	8.9 / 226	11 / 279
3 / 80	----	11.75 / 298	12.5 / 317	13.25 / 337	3.8 / 96	3.81 / 97	16.3 / 414	7.54 / 191	8.21 / 208	11.37 / 289	14.99 / 381	13.6 / 334	12.58 / 319	19.5 / 495
4 / 100	----	13.88 / 353	14.5 / 368	15.5 / 394	3.8 / 96	5.06 / 129	16.7 / 424	7.38 / 187	8.68 / 220	12.75 / 324	16.55 / 420	14.53 / 369	14.72 / 374	20.7 / 526
6 X 4 / 150 X 100	----	17.75 / 451	18.62 / 473	20 / 508	3.8 / 96	5.31 / 135	16.7 / 424	8.96 / 228	8.68 / 220	15.3 / 387	17.87 / 454	14.53 / 369	15.75 / 400	21.6 / 549
8 X 4 / 200 X 100	----	21.38 / 543	22.38 / 568	24 / 610	3.8 / 96	6.94 / 176	16.7 / 424	8.96 / 228	8.68 / 220	15.3 / 387	17.93 / 455	14.53 / 369	15.82 / 402	21.6 / 549
6 / 150	----	17.75 / 451	18.62 / 473	20 / 508	3.8 / 96	5.31 / 135	19.1 / 485	9.86 / 250	10.6 / 269	15.2 / 386	17.78 / 451	16.49 / 419	16.49 / 419	22.8 / 579
8 X 6 / 200 X 150	----	21.38 / 543	22.38 / 568	24 / 610	3.8 / 96	7.2 / 183	19.1 / 485	9.86 / 250	10.6 / 269	16.6 / 422	18.6 / 471	16.49 / 419	16.6 / 422	25.9 / 658
12 X 6 / 300 X 150	----	29 / 737	30.5 / 775	32.25 / 819	3.8 / 96	10 / 254	19.1 / 485	9.86 / 250	10.6 / 269	19.3 / 490	18.6 / 471	16.49 / 419	19.3 / 490	29 / 737
8 / 200	----	21.38 / 543	22.38 / 568	24 / 610	4.5 / 114	8.25 / 210	20.5 / 521	14.5 / 368	13.79 / 349	16.5 / 419	23.5 / 597	15.44 / 392	20.6 / 522	27 / 686

# EZR Series

Pressure Reducing Regulator

FISHER™



TYPE EZROX WITH 161AY SERIES PILOTS AND TYPE 252 FILTER

Figure 8. Typical EZROX Dimensions

Table 22. Typical EZROX Dimensions

BODY SIZE, NPS / DN	DIMENSION, IN. / mm		
	H	D	Y
1 / 25	9.78 / 248	12.34 / 313	10.33 / 262
2, 2 X 1 / 50, 50 X 25	10.39 / 264	12.95 / 329	10.94 / 278
3 / 80	11.78 / 299	14.34 / 364	12.33 / 313
4 / 100	13.5 / 343	16.06 / 408	14.05 / 357
6 / 150	12.99 / 330	15.55 / 395	13.54 / 344

Table 23. Approximate Weights Including 161EB Series, 161AY Series, PRX Series Pilot and Restrictor<sup>(1)(2)</sup>

BODY SIZES, NPS / DN	CAST IRON MAIN VALVE BODY, LBS / kg			WCC OR LCC STEEL MAIN VALVE BODY, LBS / kg				WITH INTEGRAL SLAM SHUT, LBS / kg		
	NPT	CL125 FF	CL250 RF	NPT, SWE or BWE	CL150 RF	CL300 RF	CL600 RF	CL150 RF	CL300 RF	CL600 RF
1 and 1-1/4 / 25 and 32	----	----	----	22 / 10	24 / 11	28 / 13	32 / 15	44 / 20	46 / 21	49 / 22
2 and 2 x 1 / 50 and 50 x 25	52 / 24	50 / 23	59 / 27	51 / 23	54 / 24	58 / 26	65 / 29	86 / 39	90 / 41	95 / 43
3 / 80	----	89 / 40	106 / 48	103 / 47	107 / 49	110 / 50	123 / 56	138 / 63	141 / 64	154 / 70
4 / 100		140 / 64	155 / 70	139 / 63	145 / 66	159 / 72	192 / 87	177 / 80	191 / 87	224 / 102
6 x 4 / 150 x 100		270 / 122	280 / 127	292 / 132	394 / 179	----	----	----		
8 x 4 / 200 x 100		390 / 177	461 / 209	515 / 234	600 / 272	----	----	----		
6 / 150		205 / 93	225 / 102	200 / 91	210 / 95	235 / 107	350 / 159	423 / 192	465 / 211	537 / 244
8 x 6 / 200 x 150		600 / 272	571 / 259	625 / 284	680 / 308	----	----	----		
12 x 6 / 300 x 150		1160 / 526	994 / 451	1102 / 500	1590 / 721	----	----	----		
8 / 200		----	635 / 288	685 / 310	790 / 358	----	----	----		

1. Add an additional 15 lbs / 7 kg to get the weight with a 161AY Series pilot.  
 2. Add an additional 5 lbs / 2 kg to get the weight of PRX Series pilot.

## Ordering Guide

**Type (Select One)**

- EZR
- EZROX (with slam shut)

**Body Size (Select One)**

- NPS 1 / DN 25 (Available in steel only)\*\*\*
- NPS 1-1/4 x 1 / DN 32 x 25 (Available in NPT steel only)\*\*\*
- NPS 2 / DN 50\*\*\*
- NPS 2 x 1 / DN 50 x 25\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 x 4 / DN 150 x 100\*\*\*
- NPS 8 x 4 / DN 200 x 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 x 6 / DN 200 x 150\*\*\*
- NPS 12 x 6 / DN 300 x 150\*\*\*
- NPS 8 / DN 200\*\*\*

**Body Material and End Connection Style (Select One)**

**(NPS 8 / DN 200 size available only in LCC Steel CL150, CL300 or CL600 RF)**

**Cast Iron Body**

- NPT (Available in NPS 2 or 2 x 1 / DN 50 or 50 x 25 only)\*\*\*
- CL125 FF\*\*\*

**WCC or LCC Steel Body**

- NPT (Available in NPS 1, 1-1/4 x 1, 2 x 1 or 2 / DN 25, 32 x 25, 50 x 25 or 50 only)\*\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- SWE (Available in NPS 1, 2 x 1 or 2 / DN 25, 50 x 25 or 50 only)\*
- BWE 40\*\*
- PN 16/25/40\* \_\_\_\_\_ specify

**Main Valve Diaphragm Material (Select One)**

- 17E68 Nitrile (NBR); (low temperature capable) (Not available on NPS 6 or 8 / DN 150 or 200 sizes)\*\*\*
- 17E97 Nitrile (NBR); (high-pressure capable/ erosion resistant)\*\*\*
- 17E88 Fluorocarbon (FKM); (high aromatic hydrocarbon resistant) (Not available on NPS 8 / DN 200 size)\*\*

**Cage, Percent of Full Capacity (Select One)**

- 100 percent (standard)\*\*\*
- 60 percent (Not available on NPS 8 / DN 200 size)\*\*\*
- 30 percent (Not available on NPS 8 / DN 200 size)\*\*\*

**Main Valve O-ring Material (Select One)**

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*

**Travel Indicator (Select One)**

- No (standard)\*\*\*
- Yes\*\*\*

**Inlet Strainer (Optional)**

- No (standard)\*\*\*
- Yes\*\*\*

**Main Valve Main Spring (See Table 13 for Maximum Inlet Rating) (Select One)**

**NPS 1, 1-1/4 x 1 or 2 x 1 / DN 25, 32 x 25 or 50 x 25 Main Valve**

- Light Blue\*\*\*
- Black\*\*\*
- Black with white stripe\*\*\*
- Red Stripe\*\*\*

**NPS 2 / DN 50 Main Valve**

- Yellow\*\*\*
- Green\*\*\*
- Red\*\*\*
- Purple

**NPS 3 / DN 80 Main Valve**

- Yellow\*\*\*
- Light Blue\*\*\*
- Black\*\*\*

**NPS 4, 6 x 4 or 8 x 4 / DN 100, 150 x 100 or 200 x 100 Main Valve**

- Yellow\*\*\*
- Green\*\*\*
- Red\*\*\*

**NPS 6, 8 x 6 and 12 x 6 / DN 150, 200 x 150 and 300 x 150 Main Valve**

- Yellow\*\*\*
- Green\*\*\*
- Red\*\*\*

**NPS 8 / DN 200 Main Valve**

- Yellow\*\*\*
- Green\*\*\*
- Red\*\*\*

**Inlet Body Tap (Select One)**

- Inlet body tap only (standard)\*\*\*
- Inlet body tap with pre-piped pilot supply\*\*\*
- Inlet/outlet body taps only\*\*\*
- Inlet/outlet body taps with pre-piped pilot supply and pilot bleed\*\*\*

- continued -

## Ordering Guide (continued)

### Pilot O-ring Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Pilot Valve Plug Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Pilot Diaphragm Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*

### Pilot Type and Outlet Pressure Range (Select One)

#### Type 161AY

- 6 to 15 In. w.c. / 15 to 37 mbar, Olive Drab\*\*\*
- 0.5 to 1.2 psig / 34 to 83 mbar, Yellow\*\*\*
- 1.2 to 2.5 psig / 83 mbar to 0.17 bar, Light Green\*\*\*
- 2.5 to 4.5 psig / 0.17 to 0.31 bar, Light Blue\*\*\*
- 4.5 to 7 psig / 0.31 to 0.48 bar, Black\*\*\*

#### Type 161AYM

- 6 to 15 In. w.c. / 15 to 37 mbar, Olive Drab\*\*\*
- 0.5 to 1.2 psig / 34 to 83 mbar, Yellow\*\*\*
- 1.2 to 2.5 psig / 83 mbar to 0.17 bar, Light Green\*\*\*
- 2.5 to 4.5 psig / 0.17 to 0.31 bar, Light Blue\*\*\*
- 4.5 to 7 psig / 0.31 to 0.48 bar, Black\*\*\*

#### Type 161EB

- 5 to 15 psig / 0.34 to 1.0 bar, White\*\*\*
- 10 to 40 psig / 0.69 to 2.8 bar, Yellow\*\*\*
- 30 to 75 psig / 2.1 to 5.2 bar, Black\*\*\*
- 70 to 140 psig / 4.8 to 9.7 bar, Green\*\*\*
- 130 to 200 psig / 9.0 to 13.8 bar, Blue\*\*\*
- 30 to 300 psig / 2.1 to 20.7 bar, Green (intermediate reduction pilot on the Type EZR worker / monitor systems)\*\*\*
- 200 to 350 psig / 13.8 to 24.1 bar, Red\*\*\*

#### Type 161EBM

- 5 to 15 psig / 0.34 to 1.0 bar, White\*\*\*
- 10 to 40 psig / 0.69 to 2.8 bar, Yellow\*\*\*
- 30 to 75 psig / 2.1 to 5.2 bar, Black\*\*\*
- 70 to 140 psig / 4.8 to 9.7 bar, Green\*\*\*
- 130 to 200 psig / 9.0 to 13.8 bar, Blue\*\*\*
- 200 to 350 psig / 13.8 to 24.1 bar, Red\*\*\*

#### Type 161EBH

- 250 to 450 psig / 17.2 to 31.0 bar, Blue\*\*\*
- 400 to 700 psig / 27.6 to 48.3 bar, Red\*\*\*

#### Type 161EBHM

- 250 to 450 psig / 17.2 to 31.0 bar, Blue\*\*\*
- 400 to 700 psig / 27.6 to 48.3 bar, Red\*\*\*

### Pilot Type and Outlet Pressure Range (Select One) (continued)

#### Type PRX120/125

- 14.5 to 26 psig / 1.00 to 1.8 bar, Yellow\*\*\*
- 23 to 44 psig / 1.6 to 3.0 bar, Green\*\*\*
- 41 to 80 psig / 2.8 to 5.5 bar, Blue\*\*\*
- 73 to 123 psig / 5.0 to 8.5 bar, Black\*\*\*
- 116 to 210 psig / 8.0 to 14.5 bar, Silver\*\*\*
- 203 to 334 psig / 14.0 to 23.0 bar, Gold\*\*\*
- 319 to 435 psig / 22.0 to 30.0 bar, Aluminum\*\*\*

#### Type PRX120/125 - AP

- 435 to 1000 psig / 30.0 to 69.0 bar, Clear\*\*\*

### Type 252 Pilot Supply Filter (Optional)

Material	Length	Drain Valve
<input type="checkbox"/> Stainless Steel***	<input type="checkbox"/> Standard***	<input type="checkbox"/> Yes***
<input type="checkbox"/> Aluminum**	<input type="checkbox"/> Extended**	<input type="checkbox"/> No**

### Conversion Trim Package (Optional, Not available for NPS 8 / DN 200 size)

- Yes, send one conversion trim package. (If ordering replacement trim package for change-out of existing E-body to a Type EZR, be sure to mark selection of the following items on this page: body size, diaphragm material, inlet strainer option and travel indicator option desired.)

### Main Valve Replacement Parts Kit (Optional)

- Yes, send one diaphragm cartridge and O-rings kit to match this order.
- Yes, send one diaphragm and O-rings kit to match this order.

### Pilot Replacement Parts Kit (Optional)

- Yes, send one replacement kit to match this order.

### Wireless Position Monitor Mounting Kit (Optional)

- Yes, send one mounting kit for mounting the Topworx™ 4310 or the Fisher™ 4320 wireless position monitor (requires Travel Indicator option).

- continued -



## Ordering Guide (continued)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/> Yes, which is preferred?	<input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device	
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure ( $P_{1max}$ ):	
Minimum Inlet Pressure ( $P_{1min}$ ):	
Downstream Pressure Setting(s) ( $P_2$ ):	
Maximum Flow ( $Q_{max}$ ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**

Most soft-seated regulators will maintain the pressure within reasonable limits down to zero flow. Therefore, a regulator sized for a high flow rate will usually have a turndown ratio sufficient to handle pilot-light loads during off cycles.

# Type EZR Relief

## Relief Valve or Backpressure Regulator

FISHER™

### Introduction

The Type EZR pilot-operated, pressure relief valve or backpressure regulator is typically used in city gate and district stations as a relief valve for overpressure protection or in commercial and industrial applications as a backpressure regulator. The Type EZR provides smooth, quiet operation, tight shutoff and long life, even in dirty service. Its internally actuated metal plug eliminates disadvantages associated with boot-style relief valves and backpressure regulators. The specially engineered flow path deflects debris, protecting the seat from damage and erosion. The Type EZR relief valve or backpressure regulator can be converted to a pressure reducing regulator simply by changing to a pressure reducing piloting system (see Bulletin 71.2:EZR).

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



05/19

### Features

- **Tight Shutoff**
- **Robust Construction**
- **Quiet Operation**
- **Internally Actuated**
- **Debris Protection**
- **Easy In-Line Maintenance**
- **Fast Pilot Reset**




Figure 1. Type EZR Relief Valve

### Body Sizes and End Connection Styles

See Table 4

### Flow Coefficients

See Table 7

### IEC Sizing Coefficients

See Table 8

### Pressure Registration

External through upstream control line

### Temperature Capabilities

See Table 13

### Maximum Relief (Inlet) Pressure

See Table 9

### Set Pressure Range

20 to 1160 psig / 1.4 to 80.0 bar  
in eleven ranges  
See Tables 5, 10 and 11

### Minimum and Maximum Differential Pressures

See Tables 6 and 9

### Options

- Pre-piped Pilot Supply and Pilot Bleed
- Travel Indicator
- Inlet Strainer
- Type 252 Pilot Supply Filter
- Trim Package




Figure 2. Type EZR with Type 6358EB Relief Pilot Operational Schematic

**Table 1. Main Valve Construction Material**

<b>BODY</b>	Cast iron, WCC Steel or LCC steel
<b>BONNET</b>	LF2 Steel
<b>CAGE</b>	15-5 Stainless steel
<b>SPRING</b>	Zinc-plated steel or 17-7 Stainless steel
<b>TOP PLUG</b>	17-4 Stainless steel
<b>BOTTOM PLUG</b>	416 Stainless steel
<b>INLET STRAINER</b>	316 Stainless steel
<b>DIAPHRAGM AND O-RING</b>	Nitrile (NBR) or Fluorocarbon (FKM)
<b>FLANGED LOCKNUT</b>	Alloy-plated Steel
<b>BACK-UP RING</b>	Polytetrafluoroethylene (PTFE)
<b>UPPER SPRING SEAT</b>	416 Stainless steel
<b>INDICATOR STEM</b>	303 Stainless steel
<b>INDICATOR FITTING</b>	416 Stainless steel
<b>TRAVEL INDICATOR PLUG</b>	416 Stainless steel

**Table 2. 6358 Series Pilot Construction Material**

BODY	SPRING CASE	BODY PLUG	CONTROL SPRING AND SPRING SEAT	VALVE PLUG	ADJUSTING SCREW	STEM GUIDE	DIAPHRAGM AND O-RING	DIAPHRAGM LIMITER	LOWER SPRING SEAT
CF8M Stainless steel	CF8M Stainless steel	303 Stainless steel	Zinc-plated steel	Nitrile (NBR) or Fluorocarbon (FKM) with Stainless steel stem	Zinc-plated steel	Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)	Stainless steel (Type 6358EB only)	Thermoplastic (Types 63EB and 63EBH only)

**Table 3. PRX Series Pilot**

BODY	TRIM	ELASTOMER	DISK MATERIAL
Steel, ASTM 105	Stainless steel	Nitrile (NBR) or Fluorocarbon (FKM)	Polyurethane (PU) or Fluorocarbon (FKM)

**Table 4. Main Valve Body Sizes, End Connection Styles and Body Ratings**

MAIN VALVE BODY SIZE		MAIN VALVE BODY MATERIAL	END CONNECTION STYLE <sup>(1)</sup>	STRUCTURAL DESIGN RATING <sup>(2)</sup>	
NPS	DN			psig	bar
2, 3, 4 and 6	50, 80, 100 and 150	Cast iron	NPT (NPS 2 / DN 50 only)	400	27.6
			CL125 FF	200	13.8
1, 2, 3, 4 and 6	25, 50, 80, 100 and 150	WCC Steel	NPT or SWE (NPS 1 and 2 / DN 25 and 50 only)	1480	102
			CL150 RF	285	19.7
			CL300 RF	740	51.0
			CL600 RF or BWE	1480	102
8	200	LCC Steel	CL150 RF	285	19.7
			CL300 RF	740	51.0
			CL600 RF	1480	102

1. Ratings and end connections for other than ANSI standard can usually be provided. Contact your local Sales Office for assistance.  
2. See Tables 3, 4, 5, 6 and 7 for diaphragm materials and additional pressure ratings.

**Table 5. Set Pressure Ranges, Pilot Pressure Ratings and Pilot Information<sup>(1)</sup>**

PILOT TYPE	RELIEF SET PRESSURE RANGE		PILOT CONTROL INFORMATION									
			Part Number	Color	Wire Diameter		Free Length		Maximum Operating Pressure		Maximum Emergency Pressure	
	psig	bar			In.	mm	In.	mm	psig	bar	psig	bar
6358 or 6358B	20 to 40	1.4 to 2.8	1E392527022 1K748527202 <sup>(3)</sup>	Yellow Red	0.148	3.76	2.00	50.8	150	10.3	150	10.3
	35 to 125 <sup>(3)</sup>	2.4 to 8.6 <sup>(3)</sup>			0.187	4.75	2.19	55.6				
6358EB	75 to 140	5.2 to 9.7	17B1261X012 17B1263X012 17B1264X012	Green Blue Red	0.225	5.72	3.70	94.0	650	44.8	750	51.7
	130 to 200	9.0 to 13.8			0.262	6.65	3.85	97.8				
	180 to 350	12.4 to 24.1			0.294	7.47	4.22	107				
6358EBH	250 to 450	17.2 to 31.0	17B1263X012 17B1264X012	Blue Red	0.262	6.65	3.85	97.8	609	42.0	1480	102
	400 to 600 <sup>(2)</sup>	27.6 to 41.4 <sup>(2)</sup>			0.294	7.47	4.22	107				
PRX/182	29 to 116	2.0 to 8.0	GD25522X012 GD25520X012 GD25519X012	Black Gold Red	0.157	3.99	2.16	54.9	609	42.0	1480	102
	73 to 290	5.0 to 20.0			0.217	5.50	2.01	51.1				
	217 to 609	15.0 to 42.0			0.256	6.50	1.97	50.0				
PRX-AP/182	435 to 1160	30.0 to 80.0	GD27379X012	Clear	0.335	8.51	3.94	100	1160	80.0	1480	102

1. See the Main Valve Body Sizes, End Connections, Structural Design Ratings tables and the Main Valve Diaphragm and Spring Pressure Ratings table for additional pressure ratings.  
2. Fluorocarbon (FKM) diaphragms are limited to 450 psig / 31.0 bar.  
3. Regulator minimum differential pressure is approximately equal to minimum setpoint.

# Type EZR Relief

## Relief Valve or Backpressure Regulator



**Table 6. Main Valve Minimum Differential Pressures<sup>(1)</sup>**

MAIN VALVE BODY SIZE		MAIN SPRING PART NUMBER AND COLOR	DIAPHRAGM MATERIAL	MINIMUM DIFFERENTIAL, PERCENT OF CAGE CAPACITY											
				For 90% Capacity						For 100% Capacity					
				100% Trim		60% Trim		30% Trim		100% Trim		60% Trim		30% Trim	
In.	DN	psid	bar d	psid	bar d	psid	bar d	psid	bar d	psid	bar d	psid	bar d		
1	25	19B2400X012, Light Blue	17E68 and 17E88	24	1.7	29	2.0	31	2.1	24	1.7	31	2.1	40	2.8
		GE12727X012, Black	17E97	35	2.4	38	2.6	42	2.9	35	2.4	39	2.7	52	3.6
		19B2401X012, Black with white stripe <sup>(3)</sup>	17E68 and 17E88	30	2.1	35	2.4	39	2.7	30	2.1	36	2.5	52	3.6
2	50	19B0951X012, Yellow <sup>(2)</sup>	17E68 and 17E88	12	0.83	15	1.0	15	1.0	12	0.83	25	1.7	20	1.4
		18B2126X012, Green	17E97	24	1.7	25	1.7	26	1.8	24	1.7	30	2.1	37	2.5
		17E68 and 17E88	18	1.2	20	1.4	22	1.5	19	1.3	26	1.8	28	1.9	
		18B5955X012, Red <sup>(3)</sup> GE05504X012, Purple <sup>(3)</sup>	17E88 and 17E97	29	2.0	29	2.0	31	2.1	31	2.1	35	2.4	43	3.0
3	80	T14184T0012, Yellow <sup>(2)</sup>	17E68 and 17E88	16	1.1	19	1.3	24	1.7	23	1.6	23	1.6	29	2.0
		17E97	23	1.6	23	1.6	23	1.6	23	1.6	23	1.6	25	1.7	
		19B0781X012, Light Blue	17E68 and 17E88	21	1.4	22	1.5	28	1.9	28	1.9	28	1.9	33	2.3
		19B0782X012, Black <sup>(3)</sup>	17E88 and 17E97	32	2.2	33	2.3	43	3.0	38	2.6	38	2.6	50	3.4
4	100	T14184T0012, Yellow <sup>(2)</sup>	17E68 and 17E88	10	0.69	12	0.83	14	0.97	25	1.7	25	1.7	25	1.7
		17E97	16	1.1	17	1.2	21	1.4	34	2.3	34	2.3	34	2.3	
		18B8501X012, Green	17E68 and 17E88	16	1.1	17	1.2	20	1.4	30	2.1	30	2.1	30	2.1
		18B8502X012, Red <sup>(3)</sup>	17E88 and 17E97	21	1.4	24	1.7	26	1.8	40	2.8	40	2.8	40	2.8
6	150	19B0364X012, Yellow <sup>(2)</sup>	17E97	10	0.69	11	0.76	14	0.97	12	0.83	16	1.1	16	1.1
		17E88	10	0.69	13	0.90	13	0.90	12	0.83	21	1.4	21	1.4	
		17E97	14	0.97	22	1.5	22	1.5	19	1.3	29	2.0	29	2.0	
		17E88	17	1.2	21	1.4	21	1.4	20	1.4	36	2.5	36	2.5	
		19B0365X012, Red <sup>(3)</sup>	17E88 and 17E97	23	1.6	29	2.0	29	2.0	30	2.1	41	2.8	41	2.8
8	200	GE09393X012, Yellow <sup>(2)</sup>	17E97	16	1.1	----	----	----	----	19	1.3	----	----	----	----
		GE09396X012, Green	17E97	20	1.4	----	----	----	----	23	1.6	----	----	----	----
		GE09397X012, Red <sup>(3)</sup>	17E97	26	1.8	----	----	----	----	30	2.1	----	----	----	----

1. See Table 4 for structural design ratings, Table 5 for pilot ratings and Table 9 for maximum pressure ratings.
2. The yellow springs is only recommended for inlet pressures under 100 psig / 6.9 bar.
3. The red, black, purple and black with white stripe springs are only recommended for applications where the maximum inlet pressure can exceed 500 psig / 34.5 bar.

**Table 7. Main Valve Regulating Flow Coefficient<sup>(1)</sup>**

MAIN VALVE BODY SIZE		CAGE STYLE, PERCENT OF CAPACITY	LINE SIZE EQUALS BODY SIZE PIPING						2:1 LINE SIZE TO BODY SIZE PIPING					
			With Inlet Strainer			Without Inlet Strainer			With Inlet Strainer			Without Inlet Strainer		
			C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>
1	25	100%	494	14.8	33.4	494	15.3	32.4	481	14.4	33.4	478	14.6	32.7
2	50	100%	1890	50.8	37.2	1970	54.6	36.1	1800	50.4	35.7	1840	53.0	34.7
3	80	100%	3550	91.4	38.8	3720	99.9	37.2	3390	90.6	37.4	3510	97.1	36.1
4	100	100%	5690	147	38.7	5830	154	37.9	5540	145	38.2	5640	151	37.4
6	150	100%	11,600	325	35.7	12,000	337	35.6	11,200	314	35.7	11,700	329	35.6
8	200	100%	19,700	505	39	20,100	517	38.9	19,500	503	38.8	19,700	509	38.7

1. Km for the NPS 1 / DN 25 body size is 0.88, the NPS 2 / DN 50 is 0.92, the NPS 3 / DN 80 is 0.94, the NPS 4 / DN 100 is 0.84 and the NPS 6 / DN 150 is 0.82.

**Table 8. IEC Sizing Coefficient**

BODY SIZE		X <sub>r</sub>	F <sub>b</sub>	F <sub>L</sub>
In.	DN			
1	25	0.706	0.06	0.94
2	50	0.875	0.09	0.96
3	80	0.952	0.09	0.97
4	100	0.947	0.09	0.92
6	150	0.806	0.09	0.91
8	200	0.96	0.10	0.89



**Table 9. Main Valve Maximum Pressure Ratings, Diaphragm Selection Information and Main Spring Selection<sup>(1)</sup>**

BODY SIZE		DIAPHRAGM MATERIAL	MAXIMUM OPERATING INLET PRESSURE <sup>(4)</sup>		MAXIMUM OPERATING DIFFERENTIAL PRESSURE <sup>(4)</sup>		MAXIMUM EMERGENCY INLET AND DIFFERENTIAL PRESSURE		MAIN SPRING COLOR	DIAPHRAGM STYLE
In.	DN		psig	bar	psid	bar d	psid	bar d		
1	25	17E68 Nitrile (NBR) Low temperature	100	6.9	100	6.9	100	6.9	Light Blue	130
			460	31.7	400	27.6	460	31.7	Black	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistance	500	34.5	500	34.5	1050	72.4	Black	
			1050	72.4	800	55.2	1050	72.4	Black with White Stripe <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistance	100	6.9	100	6.9	100	6.9	Light Blue	
			500	34.5	500	34.5 <sup>(3)</sup>	750	51.7	Black	
750	51.7	500	34.5 <sup>(3)</sup>	750	51.7	Black with White Stripe <sup>(2)</sup>				
2	50	17E68 Nitrile (NBR) Low temperature	100	6.9	100	6.9	100	6.9	Yellow	
			460	31.7	400	27.6	460	31.7	Green	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistance	500	34.5	500	34.5	1050	72.4	Green	
			1050	72.4	800	55.2	1050	72.4	Red or Purple <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5 <sup>(3)</sup>	750	51.7	Green	
750	51.7	500	34.5 <sup>(3)</sup>	750	51.7	Red or Purple <sup>(2)</sup>				
3	80	17E68 Nitrile (NBR) Low temperature	100	6.9	100	6.9	100	6.9	Yellow	
			360	24.8	300	20.7	500	34.5	Light Blue	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistance	500	34.5	500	34.5	1050	72.4	Light Blue	
			1050	72.4	800	55.2	1050	72.4	Black <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5 <sup>(3)</sup>	750	51.7	Light Blue	
750	51.7	500	34.5 <sup>(3)</sup>	750	51.7	Black <sup>(2)</sup>				
4	100	17E68 Nitrile (NBR) Low temperature	100	6.9	100	6.9	100	6.9	Yellow	
			360	24.8	300	20.7	500	34.5	Green	
		17E97 Nitrile (NBR) High-pressure and/or erosion resistance	500	34.5	500	34.5	1050	72.4	Green	
			1050	72.4	800	55.2	1050	72.4	Red <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5 <sup>(3)</sup>	750	51.7	Green	
750	51.7	500	34.5 <sup>(3)</sup>	750	51.7	Red <sup>(2)</sup>				
6	150	17E97 Nitrile (NBR) High-pressure and/or erosion resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5	1050	72.4	Green	
			1050	72.4	800	55.2	1050	72.4	Red <sup>(2)</sup>	
		17E88 Fluorocarbon (FKM) High aromatic hydrocarbon content resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5 <sup>(3)</sup>	750	51.7	Green	
			750	51.7	500	34.5 <sup>(3)</sup>	750	51.7	Red <sup>(2)</sup>	
8	200	17E97 Nitrile (NBR) High-pressure and/or erosion resistance	100	6.9	100	6.9	100	6.9	Yellow	
			500	34.5	500	34.5	1050	72.4	Green	
			1050	72.4	800	55.2	1050	72.4	Red <sup>(2)</sup>	

1. See Table 4 for main valve structural design ratings and Table 5 for pilot ratings.  
 2. The red or purple, black and black with white stripe springs are recommended for applications where the maximum inlet pressures can exceed 500 psig / 34.5 bar.  
 3. For differential pressures above 400 psig / 27.6 bar d diaphragm temperatures are limited to 150°F / 66°C.  
 4. These are recommendations that provide the best regulator performance for a typical application. Please contact your local Sales Office for further information if a deviation from the standard recommendations are required.

# Type EZR Relief

## Relief Valve or Backpressure Regulator



**Table 10. Pilot Information for 6358 Series Pilot**

PILOT TYPE	SET PRESSURE RANGE <sup>(5)</sup> , SPRING PART NUMBER AND COLOR	MAIN VALVE SPRING COLOR	SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESEAT PILOT	
			psig	bar	psig	bar	psig	bar	psig	bar
6358	20 to 40 psig / 1.4 to 2.8 bar 1E392527022 Yellow	Green, Light Blue or Yellow	20	1.4	1.0	69 mbar	2.0	0.14	5.0	0.34
			25	1.7	1.0	69 mbar	2.0	0.14	5.0	0.34
			30	2.1	1.0	69 mbar	2.0	0.14	5.0	0.34
			40	2.8	1.0	69 mbar	2.0	0.14	5.0	0.34
	35 to 125 psig / 2.4 to 8.6 bar <sup>(5)</sup> 1K748527202 Red	Green, Light Blue or Yellow	40	2.8	1.4	0.10	2.5	0.17	5.0	0.34
			60	4.1	1.4	0.10	2.5	0.17	5.0	0.34
			80	5.5	1.5	0.10	2.8	0.19	5.0	0.34
			100	6.9	1.6	0.11	3.0	0.21	5.0	0.34
6358B	20 to 40 psig / 1.4 to 2.8 bar 1E392527022 Yellow	Green, Light Blue or Yellow	20	1.4	1.0	69 mbar	2.0	0.14	1.0	69 mbar
			25	1.7	1.0	69 mbar	2.0	0.14	1.0	69 mbar
			30	2.1	1.0	69 mbar	2.0	0.14	1.0	69 mbar
			40	2.8	1.0	69 mbar	2.0	0.14	1.0	69 mbar
	35 to 125 psig / 2.4 to 8.6 bar <sup>(5)</sup> 1K748527202 Red	Green, Light Blue or Yellow	40	2.8	1.4	0.10	2.5	0.17	1.0	69 mbar
			60	4.1	1.4	0.10	2.5	0.17	1.0	69 mbar
			80	5.5	1.5	0.10	2.8	0.19	1.0	69 mbar
			100	6.9	1.6	0.11	3.0	0.21	1.0	69 mbar
6358EB	75 to 140 psig / 5.2 to 9.7 bar 17B1261X012 Green	Green, Light Blue or Yellow	75	5.2	1.7	0.12	3.0	0.21	2.0	0.14
			100	6.9	1.7	0.12	3.0	0.21	2.0	0.14
			125	8.6	2.1	0.14	3.5	0.24	2.0	0.14
			140	9.7	2.4	0.17	4.0	0.28	2.0	0.14
	130 to 200 psig / 9.0 to 13.8 bar 17B1263X012 Blue	Green or Light Blue	140	9.7	3.0	0.21	5.0	0.34	3.0	0.21
			150	10.3	3.5	0.24	5.5	0.38	3.0	0.21
			175	12.1	4.5	0.31	6.5	0.45	3.0	0.21
			200	13.8	5.0	0.34	7.5	0.52	3.0	0.21
	180 to 350 psig / 12.4 to 24.1 bar 17B1264X012 Red	Green or Light Blue	200	13.8	5.0	0.34	8.0	0.55	3.0	0.21
			225	15.5	5.0	0.34	8.0	0.55	3.0	0.21
			250	17.2	5.0	0.34	8.5	0.59	3.0	0.21
			275	19.0	5.5	0.38	8.5	0.59	3.0	0.21
6358EBH	250 to 450 psig / 17.2 to 31.0 bar <sup>(4)</sup> 17B1263X012 Blue	Green or Light Blue	300	20.7	5.5	0.38	8.5	0.59	3.0	0.21
			325	22.4	5.5	0.38	9.0	0.62	3.0	0.21
			350	24.1	5.5	0.38	9.0	0.62	3.0	0.21
			350	24.1	6.0	0.41	9.5	0.66	6.0	0.41
	400 to 600 psig / 27.6 to 41.4 bar <sup>(4)</sup> 17B1264X012 Red	Green or Light Blue	375	25.9	6.0	0.41	9.5	0.66	6.0	0.41
			400	27.6	6.5	0.45	10.0	0.69	6.0	0.41
			425	29.3	7.0	0.48	10.5	0.72	6.0	0.41
			450	31.0	7.5	0.52	11.0	0.76	6.0	0.41
	Red or Black	450	31.0	7.5	0.52	11.5	0.79	6.0	0.41	
		500	34.5	8.0	0.55	12.0	0.83	6.0	0.41	
		550	37.9	8.5	0.59	13.0	0.90	6.0	0.41	
		600	41.4	9.0	0.62	14.0	0.97	6.0	0.41	

1. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
2. Crack point pressure of the main valve or the inlet pressure build-up over the set pressure at which the main valve starts audible flow.
3. Inlet pressure build-up over the set pressure for the main valve to achieve wide-open flow capacity.
4. The maximum operating pressure for Fluorocarbon (FKM) pilot diaphragms is limited to 450 psig / 31.0 bar.
5. Regulator minimum differential pressure is approximately equal to minimum setpoint.

**Table 11. Pilot Information for PRX Series Pilot**

PILOT TYPE	SET PRESSURE CONTROL RANGE, SPRING PART NUMBER AND COLOR	MAIN VALVE SPRING COLOR	SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESEAT PILOT	
			psig	bar	psig	bar	psig	bar	psig	bar
PRX/182	29 to 116 psig / 2.0 to 8.0 bar GD25522X012 Black	Green or Light Blue	30	2.1	1.9	0.13	3.3	0.23	1.4	0.10
			60	4.1	2.2	0.15	3.6	0.25		
			80	5.5	2.2	0.15	4.0	0.27		
			100	6.9	2.4	0.17	4.2	0.29		
	73 to 290 psig / 5.0 to 20.0 bar GD25520X012 Gold	Green or Light Blue	75	5.2	2.5	0.17	4.1	0.28	1.6	0.11
			100	6.9	3.0	0.21	5.7	0.40		
			150	10.3	3.7	0.26	7.7	0.53		
			200	13.8	4.0	0.27	7.9	0.55		
	217 to 609 psig / 15.0 to 42.0 bar GD25519X012 Red	Green or Light Blue	250	17.2	4.1	0.28	9.1	0.63	2.1	0.14
225			15.5	4.1	0.28	10.4	0.72			
300			20.7	4.3	0.29	12.6	0.87			
400			27.6	4.4	0.30	14.4	0.99			
PRX-AP/182	435 to 1160 psig / 30.0 to 80.0 bar GD27379X012 Clear	Green or Light Blue	450	31.0	5.2	0.36	17.9	1.2	3.1	0.21
			500	34.5	5.6	0.39	18.1	1.2		
		Red or Black	600	41.4	5.5	0.38	19.9	1.4	3.1	0.21
			1050	72.4	7.8	0.54	25.0	1.7		

1. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
2. Crack point pressure of the main valve or the inlet pressure build-up over the set pressure at which the main valve starts audible flow.
3. Inlet pressure build-up over the set pressure for the main valve to achieve wide-open flow capacity.






Figure 3. Diaphragm Markings

Table 12. Diaphragm Imprint Codes

THICKNESS		MATERIAL		DIAPHRAGM MATERIAL
Imprint	Ink Code	Imprint	Ink Code	
2	130	2	17E68	17E68 - Nitrile (NBR) (low temperature)
		4	17E88	17E88 - Fluorocarbon (FKM) (high aromatic hydrocarbon content resistance)
		5	17E97	17E97 - Nitrile (NBR) (high-pressure and/or erosion resistance)

Table 13. Diaphragm Temperature Capabilities, Erosion Resistance and Chemical Compatibility

	17E68 NITRILE (NBR)	17E97 <sup>(3)</sup> NITRILE (NBR)	17E88 FLUOROCARBON (FKM)
Gas Temperature (for lower temperatures contact your local Sales Office)	-20 to 150°F / -29 to 66°C	0 to 150°F / -18 to 66°C	0 to 260°F / -18 to 127°C <sup>(1)</sup>
General Applications	Best for cold temperatures.	Best for high pressure conditions, i.e. transmission service or high pressure industrial service. It is also the best for abrasive or erosive service applications.	Best for natural gas having aromatic hydrocarbons. It is also the best for high temperature applications.
Heavy Particle Erosion	Fair	Excellent	Good
<b>Natural Gas With:</b>			
Up to 3% aromatic hydrocarbon content <sup>(2)</sup>	Good	Excellent	Excellent
3 to 15% aromatic hydrocarbon content <sup>(2)</sup>	Poor	Good	Excellent
15 to 50% aromatic hydrocarbon content <sup>(2)</sup>	Not recommended	Poor	Excellent
Up to 3% H <sub>2</sub> S (hydrogen sulfide or sour gas)	Good	Good	Good
Up to 3% ketone	Fair	Fair	Fair
Up to 10% alcohol	Good	Good	Fair
Up to 3% synthetic lube	Fair	Fair	Good

1. For differential pressures above 400 psid / 27.6 bar d diaphragm temperature is limited to 150°F / 66°C.  
 2. The aromatic hydrocarbon content is based on percent volume.  
 3. The 6 in. / DN 150, 17E97 diaphragm will perform in gas temperatures as low as -20°F / -29°C.

# Type EZR Relief

## Relief Valve or Backpressure Regulator



**Table 14. Capacities for Type 6358 Pilot**

SET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	SET PRESSURE <sup>(1)</sup>		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING AND WITHOUT INLET STRAINER											
			1 in. / DN 25		2 in. / DN 50		3 in. / DN 80		4 in. / DN 100		6 in. / DN 150		8 in. / DN 200	
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
20 to 40 psig / 1.4 to 2.8 bar 1E392527022 Yellow	20	1.4	24	0.6	87	2.3	166	4.4	267	7.2	496	13.3	864	23.2
	25	1.7	27	0.7	99	2.7	189	5.1	303	8.1	576	15.4	1000	26.8
	30	2.1	31	0.8	111	3.0	211	5.7	340	9.1	563	15.1	1133	30.4
	40	2.8	38	1.0	135	3.6	257	6.9	413	11.1	806	21.6	1396	37.4
35 to 125 psig / 2.4 to 8.6 bar 1K748527202 Red	40	2.8	38	1.0	140	3.8	267	7.2	429	11.5	806	21.6	1409	37.8
	60	4.1	52	1.4	183	4.9	350	9.4	562	15.1	1102	29.5	1926	51.7
	80	5.5	67	1.8	231	6.2	441	11.8	709	19.0	1392	37.3	2447	65.6
	100	6.9	81	2.2	279	7.5	533	14.3	856	22.9	1677	44.9	2964	79.5
75 to 140 psig / 5.2 to 9.7 bar 17B1261X012 Green	75	5.2	63	1.7	220	5.9	420	11.3	674	18.1	1320	35.4	2324	62.3
	100	6.9	81	2.2	279	7.5	533	14.3	856	22.9	1677	44.9	2964	79.5
	125	8.6	99	2.7	340	9.1	648	17.4	1042	27.9	2029	54.4	3615	96.9
	140	9.7	110	2.9	377	10.1	719	19.3	1155	31.0	2237	60.0	4010	107.5
130 to 200 psig / 9.0 to 13.8 bar 17B1263X012 Blue	140	9.7	110	2.9	379	10.2	723	19.4	1162	31.1	2237	60.0	4035	108.2
	150	10.3	117	3.1	404	10.8	771	20.7	1238	33.2	2375	63.7	4303	115.4
	175	12.1	136	3.6	466	12.5	888	23.8	1427	38.2	2716	72.8	4965	133.1
	200	13.8	154	4.1	527	14.1	1006	27.0	1617	43.3	3052	81.8	5627	105.9
180 to 350 psig / 12.4 to 24.1 bar 17B1264X012 Red	200	13.8	154	4.1	529	14.2	1008	27.0	1620	43.4	3052	81.8	5639	151.2
	225	15.5	173	4.6	588	15.8	1122	30.1	1802	48.3	3382	90.6	6275	168.3
	250	17.2	193	5.2	648	17.4	1237	33.2	1988	53.3	3708	99.4	6924	185.7
	275	19.0	212	5.7	708	19.0	1350	36.2	2170	58.2	4029	108	7560	202.7
	300	20.7	232	6.2	767	20.6	1463	39.2	2351	63.0	4345	116	8196	219.8
	325	22.4	252	6.8	828	22.2	1579	42.3	2537	68.0	4656	125	8844	237.1
250 to 450 psig / 17.2 to 31.0 bar <sup>(2)</sup> 17B1263X012 Blue	350	24.1	272	7.3	888	23.8	1694	45.4	2732	73.2	4962	133	9492	254.5
	375	25.9	292	7.8	948	25.4	1808	48.5	2904	77.8	5263	141	10,128	271.6
	400	27.6	313	8.4	1008	27.0	1923	51.5	3090	82.8	5559	149	10,776	289.0
	425	29.3	334	9.0	1069	28.6	2038	54.6	3275	87.8	5850	157	11,424	306.3
400 to 600 psig / 27.6 to 41.4 bar <sup>(2)</sup> 17B1264X012 Red	450	31.0	355	9.5	1129	30.3	2154	57.7	3461	92.8	6137	165	12,072	323.7
	500	34.5	398	10.7	1250	33.5	2385	63.9	3832	103	6695	179	13,369	358.5
	550	37.9	442	11.8	1371	36.7	2616	70.1	4203	113	7233	194	14,665	393.2
	600	41.4	487	13.1	1492	40.0	2847	76.3	4574	123	7752	208	15,961	428.0

1. Set pressure is defined as the pressure at which the pilot starts-to-discharge.  
2. The maximum operating pressure for Fluorocarbon (FKM) pilot diaphragms is limited to 450 psig / 31.0 bar.

**Table 15. Capacities for Type PRX/182 Pilot**

SET PRESSURE RANGE, SPRING PART NUMBER AND COLOR	SET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS WITH 2:1 LINE SIZE TO BODY SIZE PIPING WITHOUT INLET STRAIN											
			1 in. / DN 25		2 in. / DN 50		3 in. / DN 80		4 in. / DN 100		6 in. / DN 150		8 in. / DN 200	
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
29 to 116 psig / 2.0 to 8.0 bar GD25522X012 Black	30	2.1	31	0.8	116	3.1	215	5.8	344	9.2	721	19.3	1189	31.9
	60	4.1	52	1.4	196	5.3	364	9.8	583	15.6	1207	32.3	2017	54.1
	80	5.5	65	1.7	247	6.6	461	12.4	738	19.8	1522	40.8	2554	68.4
	100	6.9	79	2.1	301	8.1	561	15.0	898	24.1	1847	49.5	3107	83.3
73 to 290 psig / 5.0 to 20.0 bar GD25519X012 Gold	75	5.2	62	1.6	238	6.4	442	11.8	709	19.0	1462	39.2	2451	65.7
	100	6.9	79	2.1	303	8.1	565	15.1	905	24.3	1861	49.9	3131	83.9
	150	10.3	113	3.0	431	11.6	806	21.6	1291	34.6	2646	70.9	4468	119.7
	200	13.8	146	3.9	561	15.0	1048	28.1	1679	45.0	3436	92.1	5811	155.7
217 to 609 psig / 14.9 to 41.7 bar GD25519X012 Red	225	15.6	164	4.4	629	16.9	1177	31.5	1885	50.5	3855	103.3	6524	174.8
	300	20.7	214	5.7	819	21.9	1533	41.1	2455	65.8	5017	134.5	8498	227.7
	400	27.6	280	7.5	1071	28.7	2006	53.8	3213	86.1	6563	175.9	11,123	298.1
	450	31.0	313	8.4	1198	32.1	2244	60.1	3594	96.3	7339	196.7	12,440	333.4
435 to 1160 psig / 30.0 to 80.0 bar GD27379X012 Clear	450	31.0	313	8.4	1198	32.1	2244	60.1	3594	96.3	7339	196.7	12,440	333.4
	500	34.5	346	9.3	1324	35.5	2481	66.5	3973	106.5	8112	217.4	13,752	368.6
	600	41.4	411	11.0	1575	42.2	2953	79.1	4729	126.7	9654	258.7	16,371	438.7
	1050	72.4	707	18.9	2708	72.6	5078	136.1	8132	217.9	16,597	444.8	28,155	754.6

**Table 16. Shipping Weight**

BODY SIZE		APPROXIMATE SHIPPING WEIGHT													
		Cast Iron Main Valve Body						WCC or LCC Steel Main Valve Body							
		NPT		CL125 FF		CL250 RF		NPT, SWE or BWE		CL150 RF		CL300 RF		CL600 RF	
In.	DN	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg	lbs	kg		
1	25	23	10	22	10	29	13	23	10	22	10	28	13	32	15
2	50	52	24	50	23	59	27	51	23	54	24	58	26	65	29
3	80	----	----	89	40	106	48	103	47	107	49	110	50	123	56
4	100	----	----	140	64	155	70	139	63	145	66	159	72	192	87
6	150	----	----	205	93	225	102	200	91	210	95	235	107	350	159
8	200	----	----	----	----	----	----	----	----	635	288	685	310	790	358








Figure 4. Dimensions

Table 17. Dimension

BODY SIZE		DIMENSION																			
		A								C	D (Maximum)		E 6358 SERIES		E PRX SERIES		G		R		
		SWE or NPT		CL125 FF or CL150 RF		CL250 or CL300 RF		CL600 RF or BWE			In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.
1	25	8.25	210	7.25	184	7.75	197	8.25	210	2	51	2.38	60	7.44	189	6.54	166	8.65	220	9.87	251
2	50	11.25	286	10	254	10.50	267	11.25	286	2	51	3.06	78	7.44	189	11.13	283	9	229	11	279
3	80	----	----	11.75	298	12.5	317	13.25	337	3.75	95	3.81	97	8.19	208	13.6	334	13.3	338	5.9	150
4	100	----	----	13.9	353	14.5	368	15.5	394	3.75	95	5.06	129	8.45	215	14.53	369	14.7	373	20.7	526
6	150	----	----	17.8	452	18.6	472	20	508	3.8	97	5.5	140	10.88	276	16.49	419	15.2	386	32.8	833
8	200	----	----	21.9	558	22.4	570	24.0	610	4.5	114	8.25	210	15.6	397	15.44	392	20.6	522	38	965

## Ordering Guide

### Main Valve Body Size (Select One)

- NPS 1 / DN 25\*\*\* (Available in steel only)
- NPS 2 / DN 50\*\*\*
- NPS 3 / DN 80\*\*\*
- NPS 4 / DN 100\*\*\*
- NPS 6 / DN 150\*\*\*
- NPS 8 / DN 200\*\*\*

### Main Valve Body Material and End Connection Style (Select One)

#### Cast Iron Body

- NPT (Available in 2 in. body size only)\*\*\*
- CL125 FF\*\*\*

#### WCC Steel Body

- NPT (Available in 1 and 2 in. body sizes only)\*\*\*
- CL150 RF\*\*\*
- CL300 RF\*\*\*
- CL600 RF\*\*\*
- SWE (Available in 1 and 2 in. body sizes only)\*
- BWE 40\*
- PN 16/25/40\* specify \_\_\_\_\_

- continued -

# Type EZR Relief

Relief Valve or Backpressure Regulator

FISHER™

## Ordering Guide (continued)

### Main Valve Diaphragm Material (Select One)

- 17E68 Nitrile (NBR) (low temperature)\*\*\*  
(Not available on NPS 6 or 8 / DN 150 or 200)
- 17E97 Nitrile (NBR) (high-pressure/erosion resistance)\*\*\*
- 17E88 Fluorocarbon (FKM) (high aromatic hydrocarbons)\*\*\*  
(Not available on NPS 8 / DN 200)

### Main Valve O-ring Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Main Valve Main Spring (Select One)

#### NPS 1 / DN 25 Main Valve

- Light Blue, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Black, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Black with White Stripe, for inlet pressures over 500 psig / 34.5 bar\*\*\*

#### NPS 2 / DN 50 Main Valve

- Yellow, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Green, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Red/Purple, for inlet pressures over 500 psig / 34.5 bar\*\*\*

#### NPS 3 / DN 80 Main Valve

- Yellow, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Light Blue, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Black, for inlet pressures over 500 psig / 34.5 bar\*\*\*

#### NPS 4 / DN 100 Main Valve

- Yellow, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Green, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Red, for inlet pressures over 500 psig / 34.5 bar\*\*\*

#### NPS 6 / DN 150 Main Valve

- Yellow, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Green, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Red, for inlet pressures over 500 psig / 34.5 bar\*\*\*

#### NPS 8 / DN 200

- Yellow, for inlet pressures under 100 psig / 6.9 bar\*\*\*
- Green, for inlet pressures up to 500 psig / 34.5 bar\*\*\*
- Red, for inlet pressures over 500 psig / 34.5 bar\*\*\*

### Travel Indicator (Select One)

- No **(standard)**\*\*\*
- Yes\*\*\*

### Inlet Strainer (Select One)

- No **(standard)**\*\*\*
- Yes\*\*\*

### Inlet Body Tap (Select One)

- Inlet body tap only **(standard)**\*\*\*
- Inlet body tap with pre-piped pilot supply\*\*\*
- Inlet or outlet body taps only\*\*\*
- Inlet or outlet body taps with pre-piped pilot supply and pilot bleed\*\*\*

### Pilot Type and Set Pressure Range (Select One)

#### Type 6358

- 20 to 40 psig / 1.4 to 2.8 bar, Yellow\*\*\*
- 35 to 125 psig / 2.4 to 8.6 bar, Red\*\*\*

#### Type 6358B

- 20 to 40 psig / 1.4 to 2.8 bar, Yellow\*\*\*
- 35 to 125 psig / 2.4 to 8.6 bar, Red\*\*\*

#### Type 6358EB

- 75 to 140 psig / 5.2 to 9.7 bar, Green\*\*\*
- 130 to 200 psig / 9.0 to 13.8 bar, Blue\*\*\*
- 180 to 350 psig / 12.4 to 24.1 bar, Red\*\*\*

#### Type 6358EBH

- 250 to 450 psig / 17.2 to 31.0 bar, Blue\*\*\*
- 400 to 600 psig / 27.6 to 41.4 bar, Red\*\*\*

#### Type PRX/182

- 29 to 116 psig / 2.0 to 8.0 bar, Black\*\*\*
- 73 to 290 psig / 5.0 to 20.0 bar, Gold\*\*\*
- 217 to 609 psig / 15.0 to 42.0 bar, Red\*\*\*

#### Type PRX-AP/182

- 435 to 1160 psig / 30.0 to 80.0 bar, Clear\*\*\*

### Pilot Diaphragm Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*\*\*

### Pilot O-ring Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*\*

### Pilot Valve Plug Material (Select One)

- Nitrile (NBR) **(standard)**\*\*\*
- Fluorocarbon (FKM)\*\*

- continued -

## Ordering Guide (continued)

### Trim Package (Optional)

- Yes, send one Type EZR trim package. (If ordering replacement trim package for change-out of existing E-body to a Type EZR, be sure to mark selection of the following items on this page: body size, diaphragm material, inlet strainer option and travel indicator option. If other components are required, they may be selected on this page.)

### Main Valve Replacement Parts Kit (Optional)

- Yes, send one diaphragm cartridge and O-rings parts kit to match this order.
- Yes, send one diaphragm and O-rings parts kit to match this order.

### Pilot Replacement Parts Kit (Optional)

- Yes, send one replacement parts kit to match this order.

### Wireless Position Monitor Mounting Kit (Optional)

- Yes, send one mounting kit for mounting the Topworx 4310 or the Fisher™ 4320 wireless position monitor (requires Travel Indicator option).

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet	
<b>Application</b>	
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
<b>Relief Valve Size</b>	
Brand of upstream regulator?	
Orifice size of the upstream regulator?	
Wide-open coefficient of the upstream regulator?	
<b>Pressure</b>	
Maximum Inlet Pressure:	
Downstream Pressure:	
Differential Pressure:	
Relief (Inlet) Set Pressure:	
Maximum Flow:	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

### Regulator Tip:

Keep vents open. Do not use small diameter, long vent lines. Use the rule of thumb of the next nominal pipe size every 10 ft. / 3.1 m of vent line and 3 feet / 0.9 m of vent line for every elbow in the line.

# FA and FAG Series

## Cartridge Filter

TARTARINI™

### Introduction

It is often necessary in regulating and metering stations to protect the valves, pressure regulators, meters and other equipment from foreign particles present in the gases or, particularly during the initial stages of operation, from debris in newly laid pipes. This is the job of the filter.

FA and FAG Series cartridge filters can be used with natural and manufactured gases, air, propane and other gases so long as they do not contain high percentages of benzol.

They come in several versions to meet all application demands. They have threaded connections for the mounting of the drain cock (supplied on request) and other accessories. Even special filters can be made upon request. Simply contact your local Sales Office.

### Available Versions

**FA Series:** High pressure filters

**FAG Series:** Mid and low pressure filters

Type FG/07: Mid and low pressure filters with threaded connections

### Maximum Allowable Pressure

**FA Series:** 1305 psig / 90 bar

**FAG Series:** 276 psig / 19 bar

Type FG/07: 232 psig / 16 bar

See Table 1

### Maximum Casing Pressure

**FA Series:** 1958 psig / 135 bar

**FAG Series:** 435 psig / 30 bar

See Table 1

### Filtering Surface

**FA Series:**

387 to 13,019 in<sup>2</sup> / 0.25 to 8.4 m<sup>2</sup>

**FAG Series:**

93 to 6510 in<sup>2</sup> / 0.06 to 4.2m<sup>2</sup>

See Tables 22 to 25

### Filtering Capability

197 μin / 5 μm

### Body Sizes

**FA Series:** 2, 2-1/2, 3, 4, 6, 8, 10, 12, 14 and 16 NPS / DN 50, 65, 80, 100, 150, 200, 250, 300, 350 and 400

**FAG Series:** 2, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 NPS / DN 50, 65, 80, 100, 125, 150, 200, 250 and 300

### End Connection Styles

PN 16, CL150, CL300 and CL600

See Table 1

### Operating Temperature

**FA Series**

*Standard Version:*

14 to 212°F / -10 to 100°C

*Low Temperature Version:*

-4 to 212°F / -20 to 100°C

**FAG Series**

*Standard Version:*

14 to 140°F / -10 to 60°C

*Low Temperature Version:*

-4 to 140°F / -20 to 60°C

### Options

- Blind flange closure (FA Series)
- Closure flange lifting system (FA Series)
- Drain valve (FAG and FA Series)
- Local clogging indicator (FAG and FA Series)
- Remote clogging indicator (FAG and FA Series)
- Quick-opening version

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15




Figure 1. Type FA Cartridge Filter




Figure 2. Type FAG Cartridge Filter

### Features

- **Versatility**
- **Wide Range of Applications**
- **Maximum Safety**
- **Easy Maintenance**
- **Axial and Right-Angle Connections**
- **Rated Pressures Up to 1305 psig / 90 bar**
- **Quick Opening Version Available on Request**
- **Capacity Up to 22,954,409 SCFH / 650,000 Sm<sup>3</sup>/h**
- **197 μin. / 5 μm Filtering Capability**

**Table 1. FA and FAG Series Maximum Pressure and End Connection Style**

TYPE	END CONNECTION STYLE	MAXIMUM ALLOWABLE PRESSURE		MAXIMUM CASING PRESSURE	
		psig	bar	psig	bar
<b>FA Series</b>					
FA/ and FA-11/	CL150	247	17	370	25.5
FA/ and FA-12/	CL300	435	30	653	45
FA-AP/ and FA-12-AP/	CL600	1305	90	1958	135
<b>FAG Series</b>					
FAG/ and FAG-A/	PN 16 or CL150	87	6	131	9
FAG-AP/ and FAG-A-AP/	CL150	276	19	435	30

**Table 2. Types FA-11, FA-12, FA-12-AP, FA/10 and FA-AP/10 with 2 in. / DN 50 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h
7.3	0.5	10,594	300	12,360	350	12,360	350	12,360	350	----	----	----	----	----	----	----	----
14.5	1	12,713	360	15,892	450	15,892	450	15,892	450	----	----	----	----	----	----	----	----
29.0	2	15,538	440	24,720	700	24,720	700	24,720	700	24,720	700	----	----	----	----	----	----
72.5	5	22,954	650	28,252	800	35,315	1000	44,143	1250	44,143	1250	44,143	1250	----	----	----	----
145	10	31,783	900	45,909	1300	70,629	2000	84,755	2400	88,286	2500	88,286	2500	88,286	2500	----	----
363	25	60,034	1700	70,629	2000	105,943	3000	127,132	3600	148,321	4200	176,572	5000	194,230	5500	194,230	5500
580	40	----	----	----	----	----	----	----	----	----	----	----	----	282,516	8000	317,830	9000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	423,774	12,000	529,717	15,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 3. Types FA-11, FA-12 and FA-12-AP with 2-1/2 in. / DN 65 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h
7.3	0.5	10,594	300	15,538	440	21,189	600	21,189	600	----	----	----	----	----	----	----	----
14.5	1	12,713	360	19,423	550	28,252	800	28,252	800	----	----	----	----	----	----	----	----
29.0	2	15,538	440	24,720	700	35,314	1000	42,377	1200	42,377	1200	----	----	----	----	----	----
72.5	5	22,954	650	35,314	1000	49,440	1400	60,035	1700	70,629	2000	84,755	2400	----	----	----	----
145	10	31,783	900	45,909	1300	70,629	2000	84,755	2400	98,881	2800	113,006	3200	155,384	4400	----	----
363	25	45,909	1300	70,629	2000	105,943	3000	127,132	3600	148,321	4200	176,572	5000	226,013	6400	353,145	10,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	282,516	8000	423,774	12,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	423,774	12,000	565,032	16,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 4. Types FA-11, FA-12, FA-12-AP, FA/15 and FA-AP/15 with 3 in. / DN 80 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h	SCFH	Stm³/h
7.3	0.5	21,189	600	26,486	750	26,486	750	26,486	750	----	----	----	----	----	----	----	----
14.5	1	24,720	700	35,314	1000	35,314	1000	35,314	1000	----	----	----	----	----	----	----	----
29.0	2	28,252	800	45,909	1300	60,035	1700	60,035	1700	60,035	1700	----	----	----	----	----	----
72.5	5	42,377	1200	63,566	1800	91,818	2600	105,943	3000	105,943	3000	105,943	3000	----	----	----	----
145	10	60,035	1700	84,755	2400	127,132	3600	158,915	4500	176,572	5000	176,572	5000	176,572	5000	----	----
363	25	88,286	2500	141,258	4000	211,887	6000	247,201	7000	282,516	8000	353,145	10,000	423,774	12,000	459,088	13,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	565,032	16,000	741,604	21,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	741,604	21,000	1,059,434	30,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 5. Types FA-11, FA-12, FA-12-AP, FA/20 and FA-AP/20 with 4 in. / DN 100 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	21,189	600	31,783	900	45,909	1300	45,909	1300	----	----	----	----	----	----	----	----
14.5	1	24,720	700	35,314	1000	52,972	1500	67,098	1900	----	----	----	----	----	----	----	----
29.0	2	28,252	800	45,909	1300	60,035	1700	77,692	2200	91,818	2600	----	----	----	----	----	----
72.5	5	42,377	1200	63,566	1800	91,818	2600	113,006	3200	123,601	3500	158,915	4500	----	----	----	----
145	10	60,035	1700	84,755	2400	127,132	3600	158,915	4500	176,572	5000	211,887	6000	282,516	8000	----	----
363	25	88,286	2500	141,258	4000	211,887	6000	247,201	7000	282,516	8000	353,145	10,000	423,774	12,000	618,003	17,500
580	40	----	----	----	----	----	----	----	----	----	----	----	----	565,032	16,000	741,604	21,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	741,604	21,000	1,059,434	30,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 6. Types FA-11, FA-12, FA-12-AP, FA/30 and FA-AP/30 with 6 in. / DN 150 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	63,566	1800	98,881	2800	98,881	2800	98,881	2800	----	----	----	----	----	----	----	----
14.5	1	74,160	2100	113,006	3200	141,258	4000	141,258	4000	----	----	----	----	----	----	----	----
29.0	2	91,818	2600	141,258	4000	194,230	5500	194,230	5500	194,230	5500	----	----	----	----	----	----
72.5	5	105,943	3000	155,384	4400	282,516	8000	423,774	11,000	423,774	11,000	423,774	11,000	----	----	----	----
145	10	158,915	4500	229,544	6500	353,145	10,000	423,774	12,000	565,032	16,000	706,290	20,000	706,290	20,000	----	----
363	25	229,544	6500	353,145	10,000	494,403	14,000	635,661	18,000	706,290	20,000	918,176	26,000	1,236,007	35,000	1,624,466	46,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	1,483,208	42,000	2,189,498	62,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	2,118,869	60,000	3,178,303	90,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 7. Types FA-11, FA-12, FA-12-AP, FA/40 and FA-AP/40 with 8 in. / DN 200 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	84,755	2400	127,132	3600	176,572	5000	176,572	5000	----	----	----	----	----	----	----	----
14.5	1	98,881	2800	152,912	4330	222,481	6300	229,544	6500	----	----	----	----	----	----	----	----
29.0	2	123,600	3500	194,230	5500	282,516	8000	353,145	10,000	353,145	10,000	----	----	----	----	----	----
72.5	5	176,572	5000	264,859	7500	423,774	11,000	529,717	15,000	706,290	20,000	706,290	20,000	----	----	----	----
145	10	247,201	7000	353,145	10,000	565,032	16,000	635,661	18,000	776,919	22,000	918,176	26,000	1,236,007	35,000	----	----
363	25	353,145	10,000	565,032	16,000	847,547	24,000	1,059,434	30,000	1,200,692	34,000	1,412,579	40,000	1,765,724	50,000	2,542,642	72,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	2,295,441	65,000	3,178,303	90,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	3,178,303	90,000	4,414,309	125,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 8. Types FA-11, FA-12 and FA-12-AP with 10 in. / DN 250 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	158,915	4500	247,201	7000	282,516	8000	282,516	8000	----	----	----	----	----	----	----	----
14.5	1	194,230	5500	282,516	8000	353,145	10,000	353,145	10,000	----	----	----	----	----	----	----	----
29.0	2	229,544	6500	353,145	10,000	529,717	15,000	529,717	15,000	353,145	15,000	----	----	----	----	----	----
72.5	5	335,488	9500	494,403	14,000	706,290	20,000	1,059,434	30,000	706,290	30,000	706,290	30,000	----	----	----	----
145	10	459,088	13,000	706,290	20,000	1,059,434	30,000	1,271,321	36,000	1,412,579	40,000	1,589,151	45,000	1,942,296	55,000	----	----
363	25	706,290	20,000	1,059,434	30,000	1,589,151	45,000	1,624,466	46,000	2,260,126	64,000	2,683,900	76,000	3,178,303	90,000	4,590,882	130,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	4,237,737	120,000	6,180,033	175,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	6,003,461	170,000	8,828,619	250,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 9. Types FA-11, FA-12, FA-12-AP, FA/50 and FA-AP/50 with 12 in. / DN 300 Body Size Flow Capacity

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	282,516	8000	406,117	11,500	406,117	11,500	406,117	11,500	----	----	----	----	----	----	----	----
14.5	1	317,830	9000	529,717	15,000	529,717	15,000	529,717	15,000	----	----	----	----	----	----	----	----
29.0	2	423,774	12,000	635,661	18,000	812,233	23,000	812,233	23,000	812,233	23,000	----	----	----	----	----	----
72.5	5	600,346	17,000	918,176	26,000	1,236,007	35,000	1,589,151	45,000	1,589,151	45,000	1,589,151	45,000	----	----	----	----
145	10	847,547	24,000	1,271,321	36,000	1,906,982	54,000	2,260,126	64,000	2,472,013	70,000	3,001,730	85,000	3,001,730	85,000	----	----
363	25	1,236,007	35,000	1,906,982	54,000	2,825,158	80,000	3,531,448	100,000	3,884,592	110,000	4,944,027	140,000	6,003,461	170,000	7,062,895	200,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	7,062,895	200,000	10,594,343	300,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	10,594,343	300,000	12,360,066	350,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 10. Types FA-11, FA-12 and FA-12-AP with 14 in. / DN 350 Body Size Flow Capacity (Available on request)

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	282,516	8000	441,431	12,500	406,117	15,000	406,117	15,000	----	----	----	----	----	----	----	----
14.5	1	317,830	9000	529,717	15,000	706,290	20,000	706,290	20,000	----	----	----	----	----	----	----	----
29.0	2	423,774	12,000	635,661	18,000	882,862	25,000	882,862	25,000	882,862	25,000	----	----	----	----	----	----
72.5	5	600,346	17,000	918,176	26,000	1,236,007	35,000	1,765,724	50,000	2,118,869	60,000	2,118,869	60,000	----	----	----	----
145	10	847,547	24,000	1,271,321	36,000	1,906,982	54,000	2,260,126	64,000	2,472,013	70,000	3,178,303	90,000	3,884,592	110,000	----	----
363	25	1,236,007	35,000	1,906,982	54,000	2,825,158	80,000	3,531,448	100,000	3,884,592	110,000	4,944,027	140,000	6,003,461	170,000	8,475,474	240,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	7,062,895	200,000	10,594,343	300,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	10,594,343	300,000	12,360,066	350,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 11. Types FA-11, FA-12 and FA-12-AP with 16 in. / DN 400 Body Size Flow Capacity (Available on request)

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	441,431	12,500	706,290	20,000	706,290	20,000	706,290	20,000	----	----	----	----	----	----	----	----
14.5	1	529,717	15,000	847,547	24,000	918,176	26,000	918,176	26,000	----	----	----	----	----	----	----	----
29.0	2	635,661	18,000	918,176	26,000	1,412,579	40,000	1,412,579	40,000	1,412,579	40,000	----	----	----	----	----	----
72.5	5	953,491	27,000	1,412,579	40,000	2,118,869	60,000	6,180,033	75,000	2,825,158	80,000	2,825,158	80,000	----	----	----	----
145	10	1,341,950	38,000	1,942,296	55,000	2,966,416	84,000	3,531,448	100,000	4,061,165	115,000	4,944,027	140,000	4,944,027	140,000	----	----
363	25	1,977,611	56,000	2,966,416	84,000	4,590,882	130,000	5,650,316	160,000	6,356,606	180,000	7,769,185	220,000	9,181,764	260,000	12,360,066	350,000
580	40	----	----	----	----	----	----	----	----	----	----	----	----	12,360,066	350,000	17,657,238	500,000
1015	70	----	----	----	----	----	----	----	----	----	----	----	----	17,657,238	500,000	22,954,409	650,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 12. Type 0.5 (FAG-A and FAG Series) with 2 in. / DN 50 Body Size Flow Capacity

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	2649	75	3885	110	4238	120	4238	120	----	----	----	----	----	----	----	----
14.5	1	3178	90	4944	140	6004	170	6004	170	----	----	----	----	----	----	----	----
29.0	2	3885	110	6004	170	8829	250	8829	250	8829	250	----	----	----	----	----	----
73	5	----	----	----	----	12,360	350	13,243	375	17,657	500	17,657	500	----	----	----	----
145	10	----	----	----	----	----	----	----	----	22,954	650	24,720	700	24,720	700	----	----
232	16	----	----	----	----	----	----	----	----	----	----	----	----	35,315	1000	35,315	1000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 13. Type 1 (FAG-A and FAG Series) with 2-1/2 in. / DN 65 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	5297	150	7769	220	12,007	340	14,126	400	----	----	----	----	----	----	----	----
14.5	1	6357	180	9888	280	14,126	400	15,892	450	----	----	----	----	----	----	----	----
29.0	2	7769	220	12,007	340	17,657	500	21,189	600	24,720	700	----	----	----	----	----	----
73	5	11,301	320	17,657	500	24,720	700	26,486	750	35,315	1000	42,377	1200	----	----	----	----
145	10	15,892	450	22,954	650	35,315	1000	42,377	1200	45,909	1300	56,503	1600	77,692	2200	----	----
232	16	19,423	550	28,252	800	42,377	1200	52,972	1500	60,035	1700	70,629	2000	97,115	2750	134,195	3800

**Table 14. Type 1.5 (FAG-A and FAG Series) with 3 in. / DN 80 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	10,594	300	15,185	430	22,954	650	28,252	800	----	----	----	----	----	----	----	----
14.5	1	12,007	340	19,423	550	26,486	750	31,783	900	----	----	----	----	----	----	----	----
29.0	2	14,126	400	22,954	650	33,549	950	38,846	1100	45,909	1300	----	----	----	----	----	----
73	5	21,189	600	31,783	900	45,909	1300	56,503	1600	67,098	1900	77,692	2200	----	----	----	----
145	10	30,017	850	42,377	1200	63,566	1800	77,692	2200	88,286	2500	105,943	3000	132,429	3750	----	----
232	16	35,315	1000	49,440	1400	77,692	2200	98,881	2800	113,006	3200	141,258	4000	158,915	4500	211,887	6000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 15. Type 2 (FAG-A and FAG Series) with 4 in. / DN 100 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	21,189	600	31,783	900	45,909	1300	45,909	1300	----	----	----	----	----	----	----	----
14.5	1	24,720	700	38,846	1100	52,972	1500	60,035	1700	----	----	----	----	----	----	----	----
29.0	2	30,017	850	45,909	1300	67,098	1900	77,692	2200	77,692	2200	----	----	----	----	----	----
73	5	30,017	850	45,909	1300	97,115	2750	113,006	3200	132,429	3750	167,744	4750	----	----	----	----
145	10	42,377	1200	63,566	1800	105,943	3000	123,601	3500	176,572	5000	220,716	6250	300,173	8500	----	----
232	16	49,440	1400	77,692	2200	113,006	3200	141,258	4000	194,230	5500	229,544	6500	353,145	10,000	423,774	12,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 16. Type 2.5 (FAG-A and FAG Series) with 5 in. / DN 125 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	31,783	900	45,909	1300	70,629	2000	70,629	2000	----	----	----	----	----	----	----	----
14.5	1	35,315	1000	56,503	1600	97,115	2750	97,115	2750	----	----	----	----	----	----	----	----
29.0	2	44,143	1250	70,629	2000	98,881	2800	105,943	3000	123,601	3500	----	----	----	----	----	----
73	5	52,972	1500	77,692	2200	141,258	4000	176,572	5000	194,230	5500	211,887	6000	----	----	----	----
145	10	77,692	2200	113,006	3200	176,572	5000	211,887	6000	264,859	7500	300,173	8500	353,145	10,000	----	----
232	16	88,286	2500	141,258	4000	211,887	6000	247,201	7000	282,516	8000	353,145	10,000	423,774	12,000	635,661	18,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

**Table 17. Type 3 (FAG-A and FAG Series) with 6 in. / DN 150 Body Size Flow Capacity**

INLET PRESSURE (pu)		PRESSURE LOSS ( $\Delta p$ ) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	56,503	1600	88,286	2500	105,943	3000	105,943	3000	----	----	----	----	----	----	----	----
14.5	1	67,098	1900	105,943	3000	132,429	3750	132,429	3750	----	----	----	----	----	----	----	----
29.0	2	88,286	2500	141,258	4000	158,915	4500	167,744	4750	194,230	5500	----	----	----	----	----	----
73	5	105,943	3000	158,915	4500	264,859	7500	317,830	9000	353,145	10,000	388,459	11,000	----	----	----	----
145	10	123,601	3500	183,635	5200	282,516	8000	353,145	10,000	423,774	12,000	529,717	15,000	635,661	18,000	----	----
232	16	141,258	4000	229,544	6500	317,830	9000	423,774	12,000	459,088	13,000	565,032	16,000	776,919	22,000	1,094,749	31,000

— In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.



Table 18. Type 3.5 (FAG-A and FAG Series) with 6 in. / DN 150 Body Size Flow Capacity

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	67,098	1900	98,881	2800	123,601	3500	123,601	3500	----	----	----	----	----	----	----	----
14.5	1	77,692	2200	123,601	3500	141,258	4000	141,258	4000	----	----	----	----	----	----	----	----
29.0	2	97,115	2750	150,087	4250	211,887	6000	211,887	6000	211,887	6000	----	----	----	----	----	----
73	5	141,258	4000	211,887	6000	317,830	9000	353,145	10,000	406,117	11,500	423,774	12,000	----	----	----	----
145	10	194,230	5500	282,516	8000	459,088	13,000	529,717	15,000	600,346	17,000	706,290	20,000	776,919	22,000	----	----
232	16	211,887	6500	353,145	10,000	529,717	15,000	635,661	18,000	776,919	22,000	918,176	26,000	1,094,749	31,000	1,094,749	31,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.43 ft/s / 30 m/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 19. Type 4 (FAG-A and FAG Series) with 8 in. / DN 200 Body Size Flow Capacity

PRESSURE LOSS (Δp) in psig / mbar		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	79,458	2250	120,069	3400	176,572	5000	176,572	5000	----	----	----	----	----	----	----	----
14.5	1	88,286	2500	141,258	4000	194,230	5500	247,201	7000	----	----	----	----	----	----	----	----
29.0	2	105,943	3000	176,572	5000	247,201	7000	317,830	9000	353,145	10,000	----	----	----	----	----	----
73	5	158,915	4500	247,201	7000	353,145	10,000	441,431	12,500	529,717	15,000	618,003	17,500	----	----	----	----
145	10	229,544	6500	353,145	10,000	529,717	15,000	635,661	18,000	688,632	19,500	776,919	22,000	1,059,434	30,000	----	----
232	16	282,516	8000	423,774	12,000	635,661	18,000	776,919	22,000	882,862	25,000	1,094,749	31,000	1,236,007	35,000	1,765,724	50,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.42 ft/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 20. Type 5 (FAG-A and FAG Series) with 10 in. / DN 250 Body Size Flow Capacity

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	123,601	3500	194,230	5500	282,516	8000	282,516	8000	----	----	----	----	----	----	----	----
14.5	1	132,429	3750	247,201	7000	388,459	11,000	388,459	11,000	----	----	----	----	----	----	----	----
29.0	2	229,544	6500	300,173	8500	441,431	12,500	565,032	16,000	565,032	16,000	----	----	----	----	----	----
73	5	300,173	8500	459,088	13,000	618,003	17,500	741,604	21,000	918,176	26,000	1,130,063	32,000	----	----	----	----
145	10	423,774	12,000	635,661	18,000	953,491	27,000	1,130,063	32,000	1,236,007	35,000	1,412,579	40,000	2,012,925	57,000	----	----
232	16	494,403	14,000	776,919	22,000	1,130,063	32,000	1,412,579	40,000	1,589,151	45,000	1,942,296	55,000	2,295,441	65,000	3,178,303	90,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.42 ft/s) in the filter's tubes. It is recommended that these values not be exceeded.

Table 21. Type 6 (FAG-A and FAG Series) with 12 in. / DN 300 Body Size Flow Capacity

INLET PRESSURE (pu)		PRESSURE LOSS (Δp) in psig / mbar															
		0.15 / 10		0.36 / 25		0.73 / 50		1.09 / 75		1.45 / 100		2.18 / 150		3.63 / 250		7.25 / 500	
psig	bar	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h	SCFH	Stm <sup>3</sup> /h
7.3	0.5	211,887	6000	317,830	9000	388,459	11,000	406,117	11,500	----	----	----	----	----	----	----	----
14.5	1	247,201	7000	353,145	10,000	529,717	15,000	529,717	15,000	----	----	----	----	----	----	----	----
29.0	2	282,516	8000	459,088	13,000	670,975	19,000	812,233	23,000	812,233	23,000	----	----	----	----	----	----
73	5	476,745	13,500	706,290	20,000	882,862	25,000	1,059,434	30,000	1,236,007	35,000	1,589,151	45,000	----	----	----	----
145	10	670,975	19,000	988,805	28,000	1,483,208	42,000	1,695,095	48,000	1,765,724	50,000	2,118,869	60,000	3,001,730	85,000	----	----
232	16	776,919	22,000	1,236,007	35,000	1,765,724	50,000	2,189,498	62,000	2,472,013	70,000	3,001,730	85,000	3,178,303	90,000	4,590,882	130,000

----- In the grey-marked areas, capacity is restricted by gas speed (max 98.42 ft/s) in the filter's tubes. It is recommended that these values not be exceeded.

# FA and FAG Series

## Cartridge Filter

TARTARINI




Figure 3. FA-11, FA-12 and FA-12-AP Series Dimensions

Table 22. FA-11, FA-12 and FA-12-AP Series (Flanged Opening) Dimension and Weight

BODY SIZE	DIMENSION																VOLUME		FILTERING SURFACE		CARTRIDGE		WEIGHT				
	a		B		C		D		E		F		G		H		gal	L	in <sup>2</sup>	m <sup>2</sup>	Type	Qty	FA/11		FA/12		
NPS	DN	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	gal	L	in <sup>2</sup>	m <sup>2</sup>	Type	Qty	Lb	kg	Lb	kg
2	50	8.86	225	18.50	470	25.98	660	5.56	141.3	17.72	450	----	----	----	----	----	2.25	8.5	387.48	0.250	G 1	2	77	35	97	44	
2-1/2	65	10.24	260	20.08	510	28.15	715	6.63	168.3	19.69	500	----	----	----	----	----	3.83	14.5	387.48	0.250	G 1	2	88	40	110	50	
3	80	11.81	300	23.39	594	33.66	855	7.64	194	23.62	600	----	----	----	----	----	6.08	23	712.96	0.460	G 1.5	2	101	46	176	80	
4	100	11.81	300	23.39	594	33.66	855	7.64	194	23.62	600	----	----	----	----	----	6.47	24.5	712.96	0.460	G 1.5	2	110	50	207	94	
4	100S	14.96	380	28.74	730	40.55	1030	8.63	219.1	27.56	700	----	----	----	----	----	8.45	32	1456.9	0.940	G 2	2	----	----	375	170	
6	150	16.14	410	36.22	920	51.57	1310	10.75	273	31.50	800	47.24	1200	10.04	255	18.50	470	21.13	80	2247.4	1.450	G 2.5	2	419	190	661	300
8	200	18.90	480	40.39	1026	53.54	1360	14.02	356	35.43	900	52.20	1326	11.81	300	21.26	540	34.35	130	2944.8	1.900	G 3	2	573	260	882	400
10	250	22.44	570	44.88	1140	61.14	1553	16.00	406.4	39.37	1000	58.15	1477	13.19	335	24.80	630	49.93	189	4494.7	2.900	G 4	2	992	450	1521	690
12	300	25.98	660	56.54	1436	77.95	1980	20.00	508	47.24	1200	66.34	1685	15.24	387	28.62	727	103	390	7129.6	4.600	G 5	2	1433	650	2160	980
14	350																			7129.6	4.600	G 5	2				
16	400																			13,019	8.40	G 6	2				

--- Available on request.

Note: Starting from 6 in. / DN 150 the filters are supplied with support (recommended height 31.5 in. / 800 mm, other heights are available for different installations).




Figure 4. FA and FA-AP Series Dimensions

Table 23. FA and FA-AP Series (Quick Opening) Dimension and Weight

TYPE	BODY SIZE		DIMENSION																VOLUME		FILTERING SURFACE		CARTRIDGE		WEIGHT			
			A		B		C		D		E		F		G		H								Standard		Davit	
			In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm							gal	L	in <sup>2</sup>	m <sup>2</sup>
FA/10	2	50	6.61	168	22.72	577	29.06	738	5.55	141	17.72	450	----	----	----	----	----	1.98	7.5	387.48	0.250	G 1	2	97	44	----	----	
FA/15	3	80	7.64	194	29.02	737	36.73	933	6.61	168	19.69	500	----	----	----	----	----	3.70	14	712.96	0.460	G 1.5	2	176	80	----	----	
FA/20	4	100	10.63	270	35.12	892	45.12	1146	8.62	219	23.62	600	----	----	----	----	----	9.51	36	1456.9	0.940	G 2	2	308	140	----	----	
FA/25	5	125	11.81	300	37.32	948	50.20	1275	10.75	273	29.53	750	----	----	----	----	----	15.59	59	2247.4	1.450	G 2.5	2	569	258	----	----	
FA/30	6	150	14.76	375	41.38	1051	55.16	1401	12.76	324	31.50	800	55.24	1403	8.94	227	14.57	370	24.83	94	2944.8	1.900	G 3	2	----	----	926	420
FA/40	8	200	18.11	460	51.65	1312	68.58	1742	15.98	406	39.37	1000	65.08	1653	10.63	270	17.60	447	47.29	179	4494.7	2.900	G 4	2	----	----	1312	595
FA/50	12	300	22.24	565	60.87	1546	80.55	2046	20.00	508	43.31	1100	78.31	1989	12.68	322	21.18	538	87.19	330	7129.6	4.600	G 5	2	----	----	2657	1205

Note: Starting from Type FA/25 the filters are supplied with support (recommended height 31.5 in. / 800 mm, other heights are available for different installations).




Figure 5. FAG-A and FAG-A-AP Series Dimensions

Table 24. FAG-A and FAG-A-AP Series Dimension and Weight

TYPE	BODY SIZE		DIMENSION										VOLUME		FILTERING SURFACE		CARTRIDGE		WEIGHT	
			A		B		C		D		E									
	In.	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	gal	L	in <sup>2</sup>	m <sup>2</sup>	Type	Qty	Lb	kg
0.5	2	50	17.72	450	4.50	114.3	8.43	214	13.50	343	8.27	210	0.95	3.6	92.99	0.06	G 0.5	1	50.71	23
0.5-AP							8.58	218	13.35	339	9.00	228.6							0.92	3.5
1	2-1/2	65	17.72	450	5.56	141.3	10.47	266	16.30	414	9.45	240	1.59	6	193.7	0.125	G 1	1	66.14	30
1-AP							10.75	273	16.54	420	10.00	254							88.18	40
1.5	3	80	23.62	600	6.63	168.3	13.74	349	20.98	533	10.43	265	3.17	12	356.5	0.23	G 1.5	1	88.18	40
1.5-AP							14.13	359	21.34	542	11.00	279.4							88.18	40
2	4	100	23.62	600	8.63	219.1	16.85	428	24.33	618	12.60	320	5.02	19	728.5	0.47	G 2	1	141.10	64
2-AP							16.54	420	24.69	627	13.50	342.9							6.08	23
2.5	5	125	31.50	800	10.75	273	17.87	454	27.32	694	14.76	375	11.10	42	1123.7	0.725	G 2.5	1	205.03	93
2.5-AP							17.87	454	27.32	694	16.00	406.4							10.57	40
3	6	150	35.43	900	12.75	323.8	19.49	495	30.59	777	17.32	440	17.44	66	1472.4	0.95	G 3	1	286.60	130
3-AP							19.88	505	30.98	787	19.00	482.6							16.91	64
3.5	6	150	35.43	900	16.00	406.4	17.32	440	29.92	760	21.26	540	23.78	90	1472.4	0.95	G 3.5	1	451.95	205
3.5-AP							18.11	460	30.71	780	23.43	595							24.31	92
4	8	200	39.37	1000	16.00	406.4	25.51	648	39.29	998	21.26	540	34.87	132	2247.4	1.45	G 4	1	502.65	228
4-AP							26.46	672	40.24	1022	23.43	595							34.61	131
5	10	250	47.24	1200	20.00	508	29.02	737	46.50	1181	25.39	645	64.99	246	3564.8	2.30	G 5	1	749.57	340
5-AP							29.21	742	46.38	1178	27.56	700							63.94	242
6	12	300	47.24	1200	24.02	610	36.42	925	53.07	1348	29.53	750	103.83	393	6509.6	4.20	G 6	1	1102.31	500
6-AP							36.42	925	53.07	1348	29.53	750							101.98	386

Note: Filters can be ordered with smaller DN (nominal diameters) than those listed in the table and with greater A length.




Figure 6. FAG and FAG-AP Series Dimensions

Table 25. FAG and FAG-AP Series Dimension and Weight

TYPE	BODY SIZE		DIMENSION												VOLUME		FILTERING SURFACE		CARTRIDGE		WEIGHT	
			A		B		C		D		E		F									
			In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm								
0.5	2	50	8.86	225	8.86	225	4.50	114.3	8.43	214	13.50	343	8.27	210	0.95	3.6	92.99	0.06	G 0.5	1	50.71	23
0.5-AP									8.58	218	13.35	339	9.00	228.6	0.92	3.5					55.12	25
1	2-1/2	65	8.86	225	8.86	225	5.56	141.3	10.47	266	16.30	414	9.45	240	1.59	6	193.7	0.125	G 1	1	66.14	30
1-AP									10.75	273	16.54	420	10.00	254							88.18	40
1.5	3	80	11.81	300	11.81	300	6.63	168.3	13.74	349	20.98	533	10.43	265	3.17	12	356.5	0.23	G 1.5	1	88.18	40
1.5-AP									14.13	359	21.34	542	11.00	279.4							88.18	40
2	4	100	11.81	300	11.81	300	8.63	219.1	16.85	428	24.33	618	12.60	320	5.02	19	728.5	0.47	G 2	1	141.10	64
2-AP									16.54	420	24.69	627	13.50	342.9							6.08	23
2.5	5	125	15.75	400	15.75	400	10.75	273	17.87	454	27.32	694	14.76	375	11.10	42	1123.7	0.725	G 2.5	1	205.03	93
2.5-AP									17.87	454	27.32	694	16.00	406.4							10.57	40
3	6	150	17.72	450	17.72	450	12.75	323.8	19.49	495	30.59	777	17.32	440	17.44	66	1472.4	0.95	G 3	1	286.60	130
3-AP									19.88	505	30.98	787	19.00	482.6							16.91	64
3.5	6	150	17.72	450	17.72	450	16.00	406.4	17.32	440	29.92	760	21.26	540	23.78	90	1472.4	0.95	G 3.5	1	451.95	205
3.5-AP									18.11	460	30.71	780	23.43	595							24.31	92
4	8	200	19.69	500	19.69	500	16.00	406.4	25.51	648	39.29	998	21.26	540	34.87	132	2247.4	1.45	G 4	1	502.65	228
4-AP									26.46	672	40.24	1022	23.43	595							34.61	131
5	10	250	23.62	600	23.62	600	20.00	508	29.02	737	46.50	1181	25.39	645	64.99	246	3564.8	2.30	G 5	1	749.57	340
5-AP									29.21	742	46.38	1178	27.56	700							63.94	242
6	12	300	23.62	600	23.62	600	24.02	610	36.42	925	53.07	1348	29.53	750	103.83	393	6509.6	4.20	G 6	1	1102.31	500
6-AP									36.42	925	53.07	1348	29.53	750							101.98	386

Note: Filters can be ordered with smaller DN (nominal diameters) than those listed in the table and with greater A and B lengths.

### Ordering Guide

#### Type (Select One)

- FA/
- FA-AP/
- FA-11/
- FA-12/
- FA-12-AP/
- FAG/
- FAG-A/
- FAG-AP/
- FAG-A-AP/

#### Body Size (Select One)

- 2 NPS / DN 50\*\*\*
- 2-1/2 NPS / DN 65\*\*\*
- 3 NPS / DN 80\*\*\*
- 4 NPS / DN 100\*\*\*
- 5 NPS / DN 125, FAG Series only\*\*\*
- 6 NPS / DN 150\*\*\*
- 8 NPS / DN 200\*\*\*
- 10 NPS / DN 250\*\*\*
- 12 NPS / DN 300\*\*\*
- 14 NPS / DN 350, FA Series only\*\*\*
- 16 NPS / DN 400, FA Series only\*\*\*

#### End Connection Styles (Select One)

##### FAG Series

- PN 16\*\*\*
- CL150\*\*\*

##### FA Series

- CL150\*\*\*
- CL300\*\*\*
- CL600\*\*\*

#### Operating Temperature (Select One)

- Standard\*\*\*
- Low Temperature\*\*

#### Inlet/Outlet Pressure Required

\_\_\_\_\_ please specify

#### Options (Select all that apply)

- Blind Flange Closure - FA Series only\*\*\*
- Closure Flange Lifting System - FA Series only\*\*\*
- Drain Valve\*\*\*
- Local Clogging Indicator\*\*\*
- Remote Clogging Indicator\*\*\*

#### Special Requirements (Optional)

\_\_\_\_\_  
\_\_\_\_\_

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

#### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### Regulator Tip:

Four easy ways to find the products you need . . .

1. Section headers at the top of each page are grouped by application of product (i.e., Natural Gas).
2. The Product Index at the back of this Application Guide contains a detailed list of products arranged by type and application.
3. If you know the application and product number, turn to the Application Map of that section and locate the Section Outline which indexes all of the products found in that section.
4. Look for the product type number in the Quick Reference Chart in the Table of Contents.

### Introduction

The FL Series regulators are accurate pilot-operated, regulators designed for high pressure transmission/city gate, large capacity distribution systems and power plant feeds. The FL Series provides smooth, quiet operation, tight shutoff and long service life. The regulator uses a main valve actuator, a Type PRX pressure reducing pilot and a Type SA/2 pilot supply pressure regulator.

This regulator's superior performance is due to the amplifying effect of the pilot and two-path control system. Outlet pressure changes act quickly on the actuator diaphragm to provide fast response to system change.

### Available Configurations

**Type FL<sup>(1)</sup>:** Regulator for medium to high outlet pressures

**Type FL-BP:** Type FL for lower operating pressures

**Type MFL:** Type FL regulator and monitor in one unit for overpressure protection

**Type MFL-BP:** Type MFL for lower operating pressures

**Type BFL:** Regulator with built-in shutoff valve

**Type BFL-BP:** Type BFL for lower operating pressures

### Body Sizes

#### Same Inlet and Outlet:

NPS 1<sup>(1)</sup>, 1-1/2<sup>(1)</sup>, 2<sup>(1)</sup>, 2-1/2<sup>(1)</sup>, 3<sup>(1)</sup>, 4<sup>(1)</sup>, 6<sup>(1)(2)</sup>, 8<sup>(1)(3)</sup> and 10<sup>(1)(3)</sup> / DN 25<sup>(1)</sup>, 40, 50<sup>(1)</sup>, 65, 80<sup>(1)</sup>, 100<sup>(1)</sup>, 150<sup>(1)(2)</sup>, 200<sup>(1)(3)</sup> and 250<sup>(1)(3)</sup>

#### Different Inlet and Outlet with

##### Type SRS Silencer:

NPS 1 x 4<sup>(1)</sup>, 1-1/2 x 6, 2 x 6<sup>(1)</sup>, 2-1/2 x 8, 3 x 10<sup>(1)</sup>, 4 x 10<sup>(1)</sup>, 6 x 12<sup>(1)(4)</sup> and 8 x 16<sup>(1)</sup> / DN 25 x 100<sup>(1)</sup>, 40 x 150, 50 x 150<sup>(1)</sup>, 65 x 200, 80 x 250<sup>(1)</sup>, 100 x 250<sup>(1)</sup>, 150 x 300<sup>(1)(4)</sup> and 200 x 400<sup>(1)</sup>

### Main Valve End Connection Style and Pressure Ratings

#### Type FL-BP Configurations

CL150 RF/PN 16/25: 363 psig / 25.0 bar

#### Type FL Configurations

CL300 RF: 740 psig / 51.0 bar

CL600 RF: 1480 psig / 102 bar

1. North American market is limited to Type FL only.

2. NPS 6 / DN 150 Types FL and FL-BP only.

3. NPS 8 and 10 / DN 200 and 250 Type FL only.

4. NPS 6 x 12 / DN 150 x 300 Types FL and FL-BP only.

5. Low-temperature version is temperature capability of Type FL in North America.

### Maximum Allowable Pressure

#### Type FL-BP Configurations:

Up to 363 psig / 25.0 bar

#### Type FL Configurations:

Up to 1480 psig / 102 bar

### Minimum Operating Differential Pressure

#### Type FL-BP Configurations:

2.9 psid / 0.20 bar d

#### Type FL Configurations:

Start Open: 7.3 psid / 0.50 bar d

Full Open: 14.5 psid / 1.00 bar d

### Outlet Pressure Ranges

See Tables 3 and 4

### Flow Coefficients

See Table 2

### Temperature Capabilities

#### Standard version:

Working: 14 to 140°F / -10 to 60°C

#### Low-Temperature Version<sup>(5)</sup>:

Working: -20 to 140°F / -29 to 60°C

### Accuracy Class

Up to ± 1%

### Approximate Weights (Including Pilot)

See Tables 5 and 6

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



01/17

### Features

- Control Accuracy
- High Capacity
- Versatility
- Easy In-Line Maintenance
- Easy Startup
- No Atmospheric Bleed
- Tight Shutoff
- Quiet Operation
- In-Service Travel Indicator
- Full Strength diaphragm



TYPE FL WITH PRX SERIES PILOT



TYPE MFL REGULATOR AND MONITOR



TYPE BFL REGULATOR WITH SHUTOFF VALVE

Figure 1. FL Series Regulators




Figure 2. Noise Abatement Construction

# FL Series

## Pressure Reducing Regulator

TARTARINI™




Figure 3. Type FL Operational Schematic




Figure 4. Working (Operating) Monitor Operational Schematic



**Table 1. Main Valve Construction Materials**

MAIN BODY, FLANGE, SLEEVE, DISK HOLDER AND DIAPHRAGM PLATE	DIAPHRAGM	DISK	O-RING
Steel	Nitrile (NBR) with PVC Coating	Nitrile (NBR), Fluorocarbon (FKM) or Polyurethane (PU)	Nitrile (NBR) or Fluorocarbon (FKM)

**Table 2. Flow Coefficients<sup>(1)</sup>**

BODY SIZE		COEFFICIENT	TYPE NUMBER										
NPS	DN		FL-BP* FL*	FL-BP-SR* FL-SR*	FL-SRII <sup>(2)</sup>	FL-BP-SRS FL-SR/SRS	FL-SRII/SRS	MFL-BP* MFL*	MFL-BP-SR* MFL-SR*	MFL-BP-SRS MFL-SRS	BFL-BP* BFL*	BFL-BP-SR* BFL-SR*	BFL-BP-SRS BFL-SRS
1	25	C <sub>B</sub>	590	580	540	570	530	440	430	400	430	420	370
		C <sub>V</sub>	18.4	17.3	16.0	15.6	14.3	14.7	14.3	12.5	14.3	14	11.6
		C <sub>I</sub>	32.1	33.4	33.5	36.6	37.1	30	30	32	30	30	32
1-1/2	40	C <sub>B</sub>	1400	1350	-----	1200	-----	1130	1100	1020	1130	1110	970
		C <sub>V</sub>	50	48.2	-----	40	-----	39	37.9	32.9	39	38.3	31.3
		C <sub>I</sub>	28	28	-----	30	-----	29	29	31	29	29	31
2	50	C <sub>B</sub>	2300	2200	2000	1900	1700	1850	1800	1600	1850	1800	1530
		C <sub>V</sub>	70.6	65.3	59.8	48.9	44.8	66.1	64.3	53.3	66.1	64.3	51
		C <sub>I</sub>	32.6	33.7	33.4	38.9	38.0	28	28	30	28	28	30
2-1/2	65	C <sub>B</sub>	3500	3350	-----	2900	-----	2800	2700	2450	2850	2750	2360
		C <sub>V</sub>	121	116	-----	93.5	-----	93.3	90	76.6	95	91.7	73.8
		C <sub>I</sub>	29	29	-----	31	-----	30	30	32	30	30	32
3	80	C <sub>B</sub>	5200	5000	4400	4000	3500	4100	4000	3550	4150	4050	3390
		C <sub>V</sub>	161.9	151.7	138	111.7	101.6	137	133	111	138	135	106
		C <sub>I</sub>	32.1	33	30	35.8	34.4	30	30	32	30	30	32
4	100	C <sub>B</sub>	8000	7400	6500	6200	5400	6800	6600	5800	6900	6700	5490
		C <sub>V</sub>	249.3	226.5	196.5	164.7	142.9	243	236	193	246	239	183
		C <sub>I</sub>	32.1	32.7	32.9	37.7	37.8	28	28	30	28	28	30
6	150	C <sub>B</sub>	20,300	17,800	16,200	14,000	12,700	-----	-----	-----	-----	-----	-----
		C <sub>V</sub>	735.8	597.5	480.7	436.3	351.0	-----	-----	-----	-----	-----	-----
		C <sub>I</sub>	27.6	29.8	31.7	32.1	36.2	-----	-----	-----	-----	-----	-----
8	200	C <sub>B</sub>	30,900	-----	25,335	-----	20,100	-----	-----	-----	-----	-----	-----
		C <sub>V</sub>	1080.4	-----	784	-----	515.0	-----	-----	-----	-----	-----	-----
		C <sub>I</sub>	28.6	-----	32.3	-----	39.0	-----	-----	-----	-----	-----	-----
10	250	C <sub>B</sub>	52,100	-----	42,500	-----	-----	-----	-----	-----	-----	-----	-----
		C <sub>V</sub>	1615.4	-----	1197.9	-----	-----	-----	-----	-----	-----	-----	-----
		C <sub>I</sub>	32.3	-----	35.5	-----	-----	-----	-----	-----	-----	-----	-----

1. Flow coefficients (regulating) shown apply only to regulators with line size equals body size.  
 2. Type SRII Silencer is applicable only for Type FL.  
 \* Values valid also for widened outlet version.

**Table 3. Outlet Pressure Ranges of Regulator or Monitor Pilots**

TYPE	USE	OUTLET PRESSURE RANGE		ALLOWABLE PRESSURE		BODY AND COVER MATERIAL
		psig	bar	psig	bar	
PS/79-1 <sup>(1)</sup>	Regulator or Monitor	0.15 to 7.3	0.01 to 0.50	363	25.0	Aluminum
PS/79-2 <sup>(1)</sup>	Regulator or Monitor					
PS/79 <sup>(1)</sup>	Regulator or Monitor	7.3 to 580	0.50 to 3.0	1450	100	Steel
PSO/79 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/79 <sup>(1)</sup>	Operating Monitor - Monitor					
PS/80 <sup>(1)</sup>	Regulator or Monitor	22 to 580	1.5 to 40.0	1450	100	Steel
PSO/80 <sup>(1)</sup>	Operating Monitor - Regulator					
REO/80 <sup>(1)</sup>	Operating Monitor - Monitor					
PRX/120 <sup>(2)</sup>	Regulator or Monitor	14.5 to 26 23 to 44 41 to 80 73 to 123	1.00 to 1.8 1.6 to 3.0 2.8 to 5.5 5.0 to 8.5	1450	100	Steel
PRX/125 <sup>(2)</sup>	Monitor	116 to 210 203 to 334 319 to 435	8.0 to 14.5 14.0 to 23.0 22.0 to 30.0			
PRX-AP/120 <sup>(2)</sup>	Regulator or Monitor	435 to 1160	30.0 to 80.0	1450	100	Steel
PRX-AP/125 <sup>(2)</sup>	Monitor					

1. All PS Series pilots are supplied with a filter (5-micron filtering degree) and built-in pressure stabilizer, with the exception of Types PSO/79 and PSO/80.  
 2. The Type SA/2 pressure pre-reducer must be used with PRX Series pilots.

# FL Series

## Pressure Reducing Regulator

TARTARINI




Figure 5. Dimensions for Type FL-BP Configurations

Table 4. Outlet Pressure Ranges of Shutoff Device Pilots of Type BFL/BFL-BP

TYPE	SERVOMOTOR BODY RESISTANCE		OVERPRESSURE SET RANGE: $W_{HO}$				UNDERPRESSURE SET RANGE: $W_{HU}$			
			Minimum		Maximum		Minimum		Maximum	
	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
OS/80X-BP	73	5.0	0.44	0.03	29	2.00	0.15	0.01	8.7	0.60
OS/80X-BPA-D	290	20.0	0.44	0.03	29	2.00	0.15	0.01	8.7	0.60
OS/80X-MPA-D	1450	100	7.3	0.50	73	5.00	3.6	0.25	58	4.0
OS/80X-APA-D	1450	100	29	2.00	145	10.0	4.4	0.30	102	7.0
OS/84X	1450	100	73	5.00	595	41.0	58	4.0	232	16.0
OS/88X	1450	100	261	18.0	1160	80.0	116	8.0	1015	70.0
OS/80X-PN <sup>(1)</sup>	1450	100	7.3	0.50	580	40.0	7.3	0.50	580	40.0
OS/84X-PN <sup>(1)</sup>	1450	100	435	30.0	1160	80.0	435	30.0	1160	80.0

1. The following pilots are used with BFL Series regulator with built-in shutoff device.

Table 5. Dimensions and Shipping Weights for Type FL-BP Configurations

BODY SIZE		DIMENSION										APPROXIMATE SHIPPING WEIGHT							
		Standard and with Type SR										PN 16/25 or CL150 RF							
		I (Face-to-Face)						A		B									
		Type FL-BP		Type MFL-BP		Type BFL-BP													
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lb	kg	lb	kg	lb	kg		
1	25	7.2	184	14.2	360	14.0	355	11.2	285	7.8	199	53	24	106	48	84	38		
1-1/2	40	8.7	222	16.7	424	16.1	410	12.0	306	8.1	206	82	37	170	77	110	50		
2	50	10.0	254	20.1	510	19.1	485	13.2	335	8.4	213	106	48	214	97	132	60		
2-1/2	65	10.9	276	21.3	542	20.9	530	14.6	370	8.9	227	150	68	309	140	220	100		
3	80	11.7	298	22.2	564	22.0	560	15.7	400	9.6	245	183	83	370	168	291	132		
4	100	13.9	352	26.6	675	26.4	670	17.7	450	10.6	269	231	105	527	239	434	197		
6	150	17.8	451	----	----	----	----	23.2	590	----	----	562	255	----	----	----	----		
		Widened Outlet and With Type SRS																	
		1 x 4	25 x 100	11.4	290	18.3	466	18.2	461	11.2	285	7.8	199	66	30	119	54	97	44
		1-1/2 x 6	40 x 150	13.8	350	21.7	552	21.2	538	12.0	306	8.1	206	104	47	192	87	132	60
		2 x 6	50 x 150	15.0	380	25.0	636	24.1	611	13.2	335	8.4	213	128	58	236	107	154	70
		2-1/2 x 8	65 x 200	16.5	420	27.0	686	26.5	674	14.6	370	8.9	227	198	90	357	162	269	122
		3 x 10	80 x 250	18.5	470	29.0	736	28.8	732	15.7	400	9.6	245	282	128	470	213	390	177
		4 x 10	100 x 250	20.7	525	33.4	848	33.2	843	17.7	450	10.6	269	331	150	626	284	534	242
6 x 12	150 x 300	24.8	630	----	----	----	----	23.2	590	----	----	838	380	----	----	----	----		




Figure 6. Dimensions for Type FL Configurations

Table 6. Dimensions and Shipping Weights for Type FL Configurations

BODY SIZE		DIMENSION											APPROXIMATE SHIPPING WEIGHT						
		Standard and with Type SR/SRII											CL300 or CL600 RF						
		I (Face-to-Face)						A	B	C	Type FL			Type MFL			Type BFL		
		CL300 or CL600 RF									Type FL			Type MFL			Type BFL		
NPS	DN	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lb	kg	lb	kg	lb	kg
1	25	8.3	210	15.2	385	15.4	390	8.9	225	7.8	199	17.1	430	68	31	161	73	108	49
1-1/2	40	9.9	251	17.7	450	17.5	445	10.4	265	8.1	206	----	----	103	47	212	96	157	71
2	50	11.3	286	21.1	535	20.3	515	11.3	287	8.4	213	19.5	490	132	60	249	113	198	90
2-1/2	65	12.2	311	22.6	574	22.0	560	14.0	355	8.9	227	----	----	194	88	384	174	284	129
3	80	13.3	337	23.6	600	23.6	600	15.7	400	9.6	245	23.4	590	326	148	653	296	459	208
4	100	15.5	394	28.3	720	28.0	710	18.9	480	10.6	269	26.8	680	443	201	803	364	655	297
6	150	20.0	508	----	----	----	----	24.0	610	----	----	33.9	860	1058	480	----	----	----	----
8 (CL300)	200 (CL300)	22.4	569	----	----	----	----	25.7	653	----	----	39.5	1000	1367	620	----	----	----	----
8 (CL600)	200 (CL600)	24.0	610	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----
10 (CL300)	250 (CL300)	27.8	708	----	----	----	----	30.9	785	----	----	43.3	1100	2623	1190	----	----	----	----
10 (CL600)	250 (CL600)	29.6	752	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----
Widened outlet and With Type SRS																			
1x4	25 x 100	11.9	300	18.7	475	18.9	480	8.9	225	7.8	199	17.1	430	99	45	192	87	139	63
1-1/2x6	40 x 150	14.6	370	22.4	569	22.2	564	10.4	265	8.1	206	----	----	163	74	271	123	216	98
2x6	50 x 150	15.7	400	25.6	649	24.8	629	11.3	287	8.4	213	19.5	490	192	87	309	140	258	117
2-1/2x8	65 x 200	17.3	440	27.7	703	27.1	689	14.0	355	8.9	227	----	----	297	135	485	220	388	176
3x10	80 x 250	19.7	500	30.0	763	30.0	763	15.7	400	9.6	245	23.4	590	514	233	838	380	646	293
4x10	100 x 250	20.7	525	33.5	851	33.1	841	18.9	480	10.6	269	26.8	680	631	286	992	450	842	382
6x12	150 x 300	26.0	660	----	----	----	----	24.0	610	----	----	33.9	860	1367	620	----	----	----	----
8x16 (CL300)	200 x 400 (CL300)	28.4	722	----	----	----	----	25.7	653	----	----	39.5	1000	1984	900	----	----	----	----
8x16 (CL600)	200 x 400 (CL600)	29.5	750	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

## Ordering Guide

### Type (Select One)

- FL
- FL-BP
- MFL
- MFL-BP
- BFL
- BFL-BP

### Body Size (Select One)

#### Same Inlet and Outlet

- NPS 1 / DN 25\*\*
- NPS 1-1/2 / DN 40\*\*
- NPS 2 / DN 50\*\*
- NPS 2-1/2 / DN 65\*\*
- NPS 3 / DN 80\*\*
- NPS 4 / DN 100\*\*
- NPS 6 / DN 150 - Types FL-BP and FL only\*\*
- NPS 8 / DN 200 - Type FL only\*\*
- NPS 10 / DN 250 - Type FL only\*\*

#### Different Inlet and Outlet (with Type SRS Silencer)

- NPS 1 x 4 / DN 25 x 100\*\*
- NPS 1-1/2 x 6 / DN 40 x 150\*\*
- NPS 2 x 6 / DN 50 x 150\*\*
- NPS 2-1/2 x 8 / DN 65 x 200\*\*
- NPS 3 x 10 / DN 80 x 250\*\*
- NPS 4 x 10 / DN 100 x 250\*\*
- NPS 6 x 12 / DN 150 x 300 - Types FL and FL-BP only\*\*
- NPS 8 x 16 / DN 200 x 400 - Type FL only\*\*

### Silencer - For Clean Gas Only (Select One)

- Type SR\*\*
- Type SRII\*\*
- Type SR/SRS\*\*
- Type SRII/SRS\*\*
- None

### Outlet Flange Spacer (Optional)

- Yes\*\*
- No

### End Connection Style (Select One)

#### Type FL-BP Configuration

- PN 16\*\*
- PN 25\*\*
- CL150 RF\*\*

#### Type FL Configuration

- CL300 RF\*\*
- CL600 RF\*\*

### O-ring Material (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*

### Disk Material (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*
- Polyurethane (PU)\*\*

### Valve Disk (Select One)

- Polyurethane (PU)\*\*
- Fluorocarbon (FKM)\*\*

### Pilot Diaphragm (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*

### Type SA/2 O-ring and Diaphragm Material (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*

### Working Temperature Range (Select One)

- Standard Version: 14 to 140°F / -10 to 60°C\*\*
- Low Temperature Version: -20 to 140°F / -29 to 60°C\*\*

### Pilot Type (Select One - See Table 3)

- PS/79\*\*
- PS/79-1\*\*
- PS/79-2\*\*
- PSO/79\*\*
- REO/79\*\*
- PS/80\*\*
- PSO/80\*\*
- REO/80\*\*
- PRX/120\*\*
- PRX125\*\*
- PRX-AP/120\*\*
- PRX-AP/125\*\*

- continued -

## Ordering Guide (continued)

<b>Setpoint (Fill in - See Table 3 or 4)</b>
Regulator Outlet Pressure: _____
Built-in Monitor Outlet Pressure: _____
Built-in Safety Shutoff Device Minimum Pressure: _____
Built-in Safety Shutoff Device Maximum Pressure: _____
<b>Monitor Booster Valve Type (Select One)</b>
<input type="checkbox"/> V/31-1**
<input type="checkbox"/> PRX/131**
<input type="checkbox"/> PRX-AP/131**
<b>PED Certificate (Mandatory Only for CE Market)</b>
<input type="checkbox"/> Yes**

<b>Replacement Parts Kit (Optional)</b>
<input type="checkbox"/> Yes, send one replacement parts kit to match this order.
<b>Installation (Select One)</b>
<b>Horizontal Flow</b>
<input type="checkbox"/> Left to Right
<input type="checkbox"/> Right to Left
<b>Vertical Flow</b>
<input type="checkbox"/> Downward
<input type="checkbox"/> Upward

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

When installing a working monitor station, get as much volume between the two regulators as possible. This will give the upstream regulator more room to control intermediate pressure.

# FL Series Relief

Relief Valve or Backpressure Regulator

TARTARINI™

## Introduction

FL Series relief valve or backpressure regulator is accurate, pilot-operated and designed for high-pressure transmission/city gate, large capacity distribution systems and power plant feeds. FL Series provides smooth, tight shutoff and long service life.

The relief valve or backpressure regulator utilizes a main valve actuator, a Type PRX/182 or PRX-AP/182 pilot. The regulator's superior performance is due to the amplifying effect of the pilot and two-path control system. Changes in inlet pressure act quickly on the actuator diaphragm to provide fast response to system change.

## Available Construction

**Types FL and VS-FL:** Medium to high pressure applications with Pilot

Type PRX/182 or PRX-AP/182

Type VS-FL-BP: Low to medium pressure applications with Pilot Type PRX/182

## Body Sizes

**Types FL and VS-FL:** NPS 1, 1-1/2, 2, 2-1/2, 3, 4, 6, 8 and 10 / DN 25, 40, 50, 65, 80, 100, 150, 200 and 250

Type VS-FL-BP: NPS 1, 1-1/2, 2, 2-1/2, 3, 4, and 6 / DN 25, 40, 50, 65, 80, 100 and 150

## Main Valve End Connection Style and Pressure Ratings<sup>(1)</sup>

PN 16: 232 psig / 16 bar

CL150 RF: 290 psig / 20 bar

CL300 RF: 740 psig / 51.0 bar<sup>(2)</sup>

CL600 RF: 1480 psig / 102 bar<sup>(2)</sup>

## Minimum Differential Pressure

7.25 psid / 0.50 bar d

## Set (Control) Pressure Ranges

See Table 1

## Flow and Sizing Coefficients

See Table 3

## Pilot Regulator Flow Coefficients

Type PRX Pilot: C<sub>g</sub>: 10.5; C<sub>v</sub>: 0.36; C<sub>1</sub>: 29

## Pilot Connections

1/4 NPT

## Pressure Registration

External

## Temperature Capabilities<sup>(1)(3)</sup>

### Type FL

Nitrile (NBR) or Fluorocarbon (FKM) Disk:

-4 to 140°F / -20 to 60°C

Nitrile (NBR) Disk<sup>(2)</sup>:

-20 to 140°F / -29 to 60°C

### Types VS-FL and VS-FL-BP

Standard Version: 14 to 140°F / -10 to 60°C

Low Temperature Version: -4 to 140°F /

-20 to 60°C

## Approximate Weights (Including Pilot)

See Table 5

## Construction Materials

### Type FL Main Valve

Main Body and Flanges: Steel

Sleeve and Disk Holder: Steel

Diaphragm Plates: Steel

Diaphragm: Nitrile (NBR) with PVC coating

Disk O-rings: Nitrile (NBR) or

Fluorocarbon (FKM)

Disk: Nitrile (NBR) or Fluorocarbon (FKM)

### Type PRX Pilot

Body: Steel

Trim: Stainless Steel

Diaphragm: Nitrile (NBR) or


Fluorocarbon (FKM)

Disk O-rings: Nitrile (NBR) or

Fluorocarbon (FKM)

Disk: Polyurethane (PU) or

Fluorocarbon (FKM)




P1667

Figure 1. Type FL Relief Valve or Backpressure Regulator

## Features

- Control Accuracy
- Versatility
- Tight Shutoff
- Easy Startup
- High Capacity
- In-Service Travel Indicator
- Full Strength Diaphragm
- Modular Design



## Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

01/15

1. The pressure/temperature limits in this Datasheet and any applicable standard or code limitation should not be exceeded.  
2. Meets or exceeds ANSI/FCI 70-3 Class VI/VII leakage limits at maximum operating differential pressure.  
3. Type PRX Fluorocarbon (FKM) elastomer is limited to 0°F / -18°C.

**Table 1. Type FL Relief Set Pressure Control**

PILOT TYPE	RELIEF SET PRESSURE RANGE		PILOT CONTROL INFORMATION									
	psig	bar	Part Number	Color	Wire Diameter		Free Length		Maximum Operating Pressure		Maximum Emergency Pressure	
					In.	mm	In.	mm	psig	bar	psig	bar
PRX/182	29 to 116	2.0 to 8.0	M0255220X12	Black	0.157	4.00	2.16	55.0	609	42.0	1480	102
	73 to 290	5.0 to 20.0	M0255200X12	Gold	0.217	5.50	2.01	51.0				
	217 to 609	15.0 to 42	M0255190X12	Red	0.256	6.50	1.97	50.0				
PRX-AP/182	435 to 1160	30.0 to 80.0	M0273790X12	Clear	0.335	8.50	3.94	100	1160	80.0	1480	102

**Table 2. Pilot Set Pressure Build-Up**

PILOT TYPE	SET PRESSURE CONTROL RANGE, SPRING PART NUMBER AND COLOR	SET PRESSURE <sup>(1)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO BEGIN OPENING MAIN VALVE <sup>(2)</sup>		BUILD-UP OVER SET PRESSURE NEEDED TO FULLY OPEN MAIN VALVE <sup>(3)</sup>		PRESSURE DROP BELOW SET PRESSURE NEEDED TO RESEAT PILOT		
		psig	bar	psig	bar	psig	bar	psig	bar	
PRX/182	29 to 116 psig / 2.0 to 8.0 bar M0255220X12 Black	30	2.1	1.2	0.08	2.8	0.19	1.0	0.69	
		60	4.1	1.7	0.12	3.7	0.26	1.0	0.69	
		80	5.5	1.9	0.13	4.0	0.28	1.0	0.69	
		100	6.9	2.8	0.19	5.0	0.35	1.0	0.69	
	73 to 290 psig / 5.0 to 20.0 bar M0255200X12 Gold	75	5.2	2.3	0.16	0.16	5.1	0.35	2.1	0.14
		100	6.9	2.5	0.17	0.17	5.9	0.41	2.1	0.14
		150	10.3	3.5	0.24	0.24	6.8	0.47	2.1	0.14
		200	13.8	4.0	0.28	0.28	8.0	0.55	2.1	0.14
	217 to 609 psig / 14.9 to 41.7 bar M0255190X12 Red	250	17.2	4.0	0.28	0.28	8.9	0.61	2.1	0.14
		225	15.5	4.0	0.28	0.28	10.2	0.70	2.7	0.19
		300	20.7	4.0	0.28	0.28	10.5	0.72	2.7	0.19
		400	27.6	4.1	0.28	0.28	10.7	0.74	2.7	0.19
PRX-AP/182	435 to 1160 psig / 30.0 to 80.0 bar M0273790X12 Clear	450	31.0	4.3	0.3	11.0	0.76	2.7	0.19	
		450	31.0	4.3	0.3	11.0	0.76	3.3	0.23	
		500	34.5	4.5	0.31	11.1	0.77	3.3	0.23	
		600	41.4	5.1	0.35	11.1	0.77	3.3	0.23	
		1050	72.4	5.1	0.35	11.1	0.77	3.3	0.23	

1. Set pressure is defined as the pressure at which the pilot starts-to-discharge.
2. Crack point pressure of the main valve of the inlet pressure build-up over the set pressure at which the main valve starts audible flow.
3. Inlet pressure build-up over the set pressure for the main valve to achieve wide-open flow capacity.

**Table 3. Type FL Flow and Sizing Coefficients**

BODY SIZE, NPS / DN	LINE SIZE EQUALS BODY SIZE						2:1 LINE SIZE TO BODY SIZE RATIO					
	Regulating		C <sub>1</sub>	IEC Sizing Coefficient			Regulating		C <sub>1</sub>	IEC Sizing Coefficient		
	C <sub>g</sub>	C <sub>v</sub>		X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>	C <sub>g</sub>	C <sub>v</sub>		X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>
1 / 25	590	18.4	32.1	0.65	0.73	0.89	550	16.4	33.5	0.71	0.69	0.89
2 / 50	2300	70.6	32.6	0.67	0.69	0.89	2200	67.7	32.5	0.67	0.68	0.89
3 / 80	5200	161.9	32.1	0.69	0.70	0.89	4900	161.4	30.4	0.58	0.70	0.89
4 / 100	8000	249.3	32.1	0.65	0.65	0.89	7900	244.9	32.3	0.66	0.64	0.89
6 / 150	20,300	735.8	27.6	0.48	0.71	0.89	18,400	666.7	27.6	0.48	0.67	0.89
8 / 200	30,900	1080.4	28.6	0.52	0.66	0.89	30,600	1069.9	28.6	0.52	0.65	0.89
10 / 250	52,100	1615.4	32.3	0.66	0.69	0.89	51,500	1599.7	32.2	0.66	0.69	0.89

**Table 4. Type FL Relief Capacities**

SET PRESSURE RANGE, PILOT SPRING PART NUMBER AND COLOR	SET PRESSURE		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS														
	psig	bar	NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 10 / DN 250		
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
29 to 116 psig / 2.0 to 8.0 bar M0255220X12 Black	30	2.1	37	1.0	147	3.9	331	8.9	503	13.5	1282	34.4	2011	53.9	3285	88.0	
	60	4.1	62	1.7	243	6.5	547	14.7	830	22.2	2115	56.7	3320	89.0	5425	145	
	80	5.5	78	2.1	306	8.2	688	18.4	1045	28.0	2663	71.4	4179	112	6830	183	
	100	6.9	94	2.5	371	9.9	834	22.4	1267	34.0	3230	86.6	5069	136	8283	222	
73 to 290 psig / 5.0 to 20.0 bar M0255200X12 Gold	75	5.2	75	2.0	294	7.9	661	17.7	1004	26.9	2558	68.6	4014	108	6560	176	
	100	6.9	95	2.5	374	10.0	841	22.5	1277	34.2	3254	87.2	5107	137	8345	224	
	150	10.3	135	3.6	531	14.2	1196	32.1	1816	48.7	4627	124	7262	195	11,867	318	
	200	13.8	175	4.7	690	18.5	1553	41.6	2358	63.2	6009	161	9430	253	15,410	413	
217 to 609 psig / 14.9 to 41.7 bar M0255190X12 Red	250	17.2	215	5.8	848	22.7	1907	51.1	2896	77.6	7382	198	11,585	310	18,932	507	
	225	15.5	197	5.3	774	20.7	1742	46.7	2645	70.9	6743	181	10,582	284	17,292	463	
	300	20.7	256	6.9	1008	27.0	2267	60.8	3443	92.3	8774	235	13,770	369	22,503	603	
	400	27.6	335	9.0	1318	35.3	2966	79.5	4503	121	11,478	308	18,013	483	29,437	789	
435 to 1160 psig / 30.0 to 80.0 bar M0273790X12 Clear	450	31	375	10.1	1474	39.5	3316	88.9	5036	135	12,835	344	20,143	540	32,917	882	
	450	31	375	10.1	1474	39.5	3316	88.9	5036	135	12,835	344	20,143	540	32,917	882	
	500	34.5	414	11.1	1629	43.7	3666	98.2	5566	149	14,187	380	22,265	597	36,384	975	
	600	41.4	493	13.2	1939	52.0	4363	117	6625	178	16,885	453	26,499	710	43,304	1161	
		1050	72.4	847	22.7	3333	89.3	7500	201	11,389	305	29,027	778	45,554	1221	74,442	1995

# FL Series Relief

Relief Valve or Backpressure Regulator

TARTARINI™




Figure 3. Type FL Outlet Flange Spacer Installation

Table 5. Dimensions

BODY SIZE		DIMENSION														APPROXIMATE WEIGHT			
NPS	DN	(Face-to-Face / I) CL300 - CL600		A		B		E		F		G		S		lbs	kg		
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm				
1	25	8.3	211	8.9	225	17.1	430	4.7	120	0.39	10	----	----	1.18	30	68	31		
1-1/2	40	9.88	251	10.4	265	----	----	----	----	----	----	----	----	----	----	104	47		
2	50	11.3	286	11.3	287	19.5	490	4.7	120	0.39	10	----	----	1.97	50	132	60		
2-1/2	65	12.24	311	14.0	355	----	----	----	----	----	----	----	----	----	----	194	88		
3	80	13.3	337	15.7	400	23.4	590	4.7	120	0.39	10	----	----	2.36	60	326	148		
4	100	15.5	394	18.9	480	26.8	680	4.7	120	0.39	10	----	----	2.36	60	443	201		
6	150	20.0	508	24.0	610	33.9	860	4.7	120	0.39	10	0.47	12	3.15	80	1058	480		
8	200	CL300		25.7	653	39.5	1000	4.7	120	0.39	10	0.47	12	3.93	100	1367	620		
		22.4	569																
		CL600																	
10	250	CL300		30.9	785	43.3	1100	4.7	120	0.39	10	0.47	12	3.93	100	2623	1190		
		27.8	708																
		CL600																	
BODY SIZE	DN	DIMENSION														WEIGHT			
		Face-to-Face / I				H													
		PN 16 - CL150		CL300 - CL600		PN 16 - CL150				CL300 - CL600				PN 16 - CL150 RF		CL300 - CL600			
		Type VS-FL-BP		Type VS-FL		Type VS-FL-BP				Type VS-FL				Type VS-FL-BP		Type VS-FL			
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lbs	kg	lbs	kg	lbs	kg		
1	25	7.24	184	8.3	210	11.22	285	8.86	225	52.9	24	1.2	31						
1-1/2	40	8.74	222	9.9	251	12.05	306	10.43	265	81.6	37	1.9	47						
2	50	10.0	254	11.3	286	13.19	335	11.3	287	106	48	2.4	60						
2-1/2	65	10.87	276	12.2	311	14.57	370	13.98	355	150	68	3.5	88						
3	80	11.73	298	13.3	337	15.75	400	15.75	400	183	83	5.8	148						
4	100	13.86	352	15.5	394	17.72	450	18.9	480	231	105	7.9	201						
6	150	17.75	451	20.0	508	23.23	590	24	610	562	255	18.9	480						
8	200	----	----	24.0	610	----	----	25.7	653	----	----	24.4	620						
10	250	----	----	29.6	752	----	----	30.9	785	----	----	45.3	1150						






Figure 4. Dimensions

## Ordering Guide

### Type (Select One)

- FL or VS-FL
- VS-FL-BP

### Type FL

#### Body Size (Select One)

- NPS 1 / DN 25\*\*
- NPS 1-1/2 / DN 40\*\*
- NPS 2 / DN 50\*\*
- NPS 2-1/2 / DN 65\*\*
- NPS 3 / DN 80\*\*
- NPS 4 / DN 100\*\*
- NPS 6 / DN 150\*\*
- NPS 8 / DN 200\*\*
- NPS 10 / DN 250\*\*

#### End Connection Style (Select One)

- CL300 RF\*\*
- CL600 RF\*\*
- PN16 and CL150 RF\*\*

#### O-ring Material (Select One)

- Nitrile (NBR)\*\*
- Fluorocarbon (FKM)\*\*

#### Disk Material (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*

### Pilot Type (Select One)

- PRX/182
- PRX-AP/182

### Outlet Flange Spacer (Optional)

- Yes\*\*
- No

### Set Pressure Range (Select One)

#### Type PRX/182

- 29 to 116 psig / 2.00 to 8.00 bar, Black\*\*
- 73 to 290 psig / 5.00 to 20.0 bar, Gold\*\*\*
- 217 to 609 psig / 15.0 to 42.0 bar, Red\*\*

#### Type PRX-AP/182

- 435 to 1160 / 30.0 to 80.0 bar, Clear\*\*

### Main Valve Mounting Position (Select One)

- Horizontal
- Vertical

### Pilot Diaphragm (Select One)

- Nitrile (NBR) (standard)\*\*\*
- Fluorocarbon (FKM)\*\*

### Pilot Disk (Select One)

- Polyurethane (PU) (standard)\*\*
- Fluorocarbon (FKM)\*\*

- continued -

# FL Series Relief

Relief Valve or Backpressure Regulator

TARTARINI™

## Ordering Guide (continued)

### Main Valve Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

### Main Valve Replacement Commission Kit (Optional)

Yes, send one commission kit to match this order.

### Pilot Valve Replacement Parts Kit (Optional)

Yes, send one replacement parts kit to match this order.

### Inlet/Outlet Pressure Required

\_\_\_\_\_ please specify

### Setpoint

\_\_\_\_\_ please specify

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Adequate overpressure protection should be installed to protect the regulator from overpressure. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure.

## Introduction

The Type H120 direct-operated relief valve registers directly on a spring-opposed poppet assembly which includes a Nitrile (NBR) disk. When the inlet pressure increases above the spring setting, the poppet and disk assembly is pushed away from the metal seat. Springs are available that provide various fixed relief pressures from 35 to 350 psig / 2.4 to 24.1 bar.

With this simple operation and wide spring setting selection, the Type H120 relief valve may be used where venting to atmosphere is acceptable, where the process gas is compatible with the Nitrile (NBR) disk, where its relief capacity is adequate, and where some pressure relieving tolerance is acceptable. Common applications include use on pneumatic control lines of air drills, jackhammers, and other similar equipment and on high-pressure installations such as the side outlet of a Type 1301F regulator.

### Inlet Connection Size and Style

1/4 NPT

### Maximum Allowable Relief (Inlet) Pressure<sup>(1)</sup>

420 psig / 29.0 bar

### Fixed Relief Pressures<sup>(1)</sup>

35 to 350 psig / 2.4 to 24.1 bar with nine fixed settings  
See Table 1




Figure 1. Type H120 Relief Valve

Figure 2. Operational Schematic

### Wide-Open Flow Coefficient

C<sub>g</sub>: 0.80

### Temperature Capabilities<sup>(1)</sup>

-20 to 160°F / -29 to 71°C

### Approximate Shipping Weight

0.25 lb / 0.11 kg

### Available Option

Type P206 raincap

### Construction Materials

Body, Poppet and Spring Retainer: Brass and Stainless steel  
Disk: Nitrile (NBR)  
Spring: Stainless steel  
Retainer Pin: Steel and Stainless steel

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

08/16

## Features

- Space-Saving Construction
- Economical
- Durable
- Optional Protective Cap

Table 1. Relief Pressure and Capacities

FIXED RELIEF PRESSURE SETTING <sup>(1)</sup>		BUILD-UP OVER RELIEF PRESSURE SETTING		CAPACITY IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(2)</sup>		SPRING PART NUMBER	SPRING COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h			In.	mm	In.	mm
35	2.4	25	1.7	6000	161	T1217837022	Yellow	0.047	1.19	0.91	23.1
60	4.1	25	1.7	8175	219						
120	8.3	25	1.7	12,825	344	T12687T0012	Orange	0.051	1.30	0.94	23.9
150	10.3	30	2.1	14,890	399	T12688T0012	Brown	0.056	1.42	1.17	29.7
175	12.1	35	2.4	17,400	466						
200	13.8	40	2.8	20,350	545	1F790837022	Black	0.062	1.58	1.13	28.7
225	15.5	45	3.1	21,750	583						
275	19.0	55	3.8	23,525	630						
350	24.1	70	4.8	34,560	926						

1. This is the initial leak point, the point at which the relief valve begins to discharge.  
2. To convert to equivalent capacities of other gases, multiply the table value by 0.775 for air or 0.789 for nitrogen.

1. The pressure/temperature limits in this datasheet or any applicable standard limitation should not be exceeded.


# Type H120

## Relief Valve

FISHER™

**Table 2. Dimensions for Related H100 Series**

TYPE NUMBER	A, BODY SIZE	DIMENSIONS					
		B		C		D	
		In.	mm	In.	mm	In.	mm
H110	1/4 in. NPT	1.36	34.5	0.84	21.3	1.93	49.0
H120							
H123							
H124							
H135	1/2 in. NPT	2.55	64.8	1.11	28.2	2.55	64.8
H144							
H148							
H160	3/4 in. NPT	2.55	64.8	1.11	28.2	2.55	64.8
H173							
H174							
H185	3/4 in. NPT	2.90	73.7	1.68	42.7	3.69	93.7



AF6126-J

**Figure 3.** Related H100 Series Construction Details and Outline Dimensions

## Ordering Guide

### Fixed Relief Pressure Setting (Select One)

- 35 psig / 2.4 bar\*\*\*
- 60 psig / 4.1 bar\*\*\*
- 120 psig / 8.3 bar\*\*\*
- 150 psig / 10.3 bar\*\*\*
- 175 psig / 12.1 bar\*\*\*
- 200 psig / 13.8 bar\*\*\*
- 225 psig / 15.5 bar\*\*\*
- 275 psig / 19.0 bar\*\*
- 350 psig / 24.1 bar\*\*

### Quantity

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

Adequate overpressure protection should be installed to protect the regulator from overpressure. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure.

## Introduction

The H200 Series Pop™ relief valves are direct-operated relief valves with preset and pinned spring retainers. The inlet pressure registers directly on a spring-opposed poppet assembly that includes a Nitrile (NBR) disk. When the inlet gas pressure increases above the spring setting, the poppet and disk assembly is pushed away from the orifice.

With this simple operation and wide spring setting selection, the H200 Series pop relief valves may be used where venting to atmosphere is acceptable and where some pressure relieving tolerance is acceptable. Common applications include use on pneumatic control lines and farm tap installations.

## Available Configurations and End Connections

Type H202: 3/4 NPT  
Type H203: 1 NPT

## Wide-Open Flow Coefficient

C<sub>g</sub>: 405

## Maximum Allowable Relief (Inlet) Pressure<sup>(1)</sup>

400 psig / 27.6 bar

## Fixed Relief Pressures<sup>(1)</sup>

25 to 300 psig / 1.7 to 20.7 bar with 12 fixed settings

See Table 2

## Approximate Shipping Weight

0.5 lb / 0.2 kg

## Temperature Capabilities<sup>(1)</sup>

-20 to 160°F / -29 to 71°C

## Option

- Type P145 Raincap

## Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



12/19

## Features

- Space-Saving Construction
- Economical
- Durable



W1929\_1

Figure 1. H200 Series Relief Valve

BODY, POPPET AND SPRING RETAINER	DISK	SPRING
Brass	Nitrile (NBR)	302 Stainless steel

RELIEF SET PRESSURE <sup>(1)</sup>		SET PRESSURE PLUS BUILD-UP		CAPACITY OF 0.6 SPECIFIC GRAVITY NATURAL GAS <sup>(2)</sup>		RELIEF SETTING TOLERANCE	
psig	bar	psig	bar	SCFH	Nm <sup>3</sup> /h	psig	bar
25	1.7	50	3.4	34,200	916	±5	±0.34
50	3.4	75	5.2	47,400	1270		
75	5.2	100	6.9	60,000	1608	±8	±0.55
100	6.9	120	8.3	69,600	1865		
125	8.6	150	10.3	83,400	2235		
150	10.3	180	12.4	100,500	2693		
175	12.1	210	14.5	117,600	3152	±15	±1.03
200	13.8	240	16.5	132,000	3538		
225	15.5	270	18.6	150,000	4020		
250	17.2	300	20.7	165,000	4422		
275	19.0	330	22.7	180,000	4824		
300	20.7	360	24.8	195,000	5226		

1. This is the initial leak point (the point at which the relief valve begins to discharge).  
2. 0.6 Specific Gravity Gas. To convert to equivalent capacities of other gases, multiply the table values by 0.775 for air or 0.789 for nitrogen. Multiply the flow obtained by 0.0268 to convert to (Nm<sup>3</sup>/h) at 0°C and 1.01 bar.




Figure 2. Operational Schematic and Dimensions

1. The pressure/temperature limits in this Datasheet or any applicable code limitations should not be exceeded.

# H200 Series

Relief Valve

FISHER™

## Ordering Guide

### Body Size and End Connection Style (Select One)

- 3/4 NPT\*\*\*
- 1 NPT\*\*\*

### Fixed Relief Pressure Setting (Select One)

#### 3/4 NPT

- 25 psig / 1.7 bar\*\*\*
- 35 psig / 2.4 bar\*\*\*
- 50 psig / 3.4 bar\*\*\*
- 75 psig / 5.2 bar\*\*\*
- 250 psig / 17.2 bar\*\*\*

#### 1 NPT

- 25 psig / 1.7 bar\*\*\*
- 35 psig / 2.4 bar\*\*\*
- 50 psig / 3.4 bar\*\*\*
- 60 psig / 4.1 bar\*\*\*
- 75 psig / 5.2 bar\*\*\*
- 100 psig / 6.9 bar\*\*\*
- 125 psig / 8.6 bar\*\*\*
- 150 psig / 10.3 bar\*\*\*
- 175 psig / 12.1 bar\*\*\*
- 200 psig / 13.8 bar\*\*\*
- 250 psig / 17.2 bar\*\*\*
- 300 psig / 20.7 bar\*\*\*

### Type P145 Raincap (Optional)

- Yes

### Quantity (Specify)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

#### Application

Relief Valve    Backpressure Regulator

#### Specific Use:

Line Size:

Gas Type and Specific Gravity:

Gas Temperature:

#### Relief Valve Size

Brand of upstream regulator?

Orifice size of the upstream regulator?

Wide-open coefficient of the upstream regulator?

#### Pressure

Maximum Inlet Pressure:

Downstream Pressure:

Differential Pressure:

Relief (Inlet) Set Pressure:

Maximum Flow:

#### Performance Required

Accuracy requirements?

Need for extremely fast response?

#### Other Requirements:

#### Regulator Tip:

All regulators should be installed and used in accordance with federal, state and local codes and regulations.

### Introduction

The Type HSR direct-operated, spring-loaded regulators provide economical pressure reducing control in a variety of residential, commercial and industrial applications.

In addition, the Type HSR regulators have internal relief across the diaphragm to help minimize overpressure.

### Body Sizes (Inlet x Outlet) and End Connection Styles

**Globe Body:** 3/4, 3/4 x 1, 1 and 1-1/4 NPT

**Angle Body:** 3/4, 3/4 x 1 and 1 NPT

### Outlet Pressure Ranges

See Table 2

### Allowable Inlet Pressures<sup>(1)</sup>

**Emergency:** 150 psig / 10.3 bar

Maximum Operating Pressure:  
See Table 3

### Allowable Outlet Pressures<sup>(1)</sup>

**Emergency (Casing):** 25 psig / 1.7 bar

Maximum Operating Pressure to Avoid Internal Parts Damage: 3 psi / 0.21 bar differential above outlet pressure setting

### Flow and Sizing Coefficients

See Table 5

### Internal Relief Performance

**Approximate Internal Relief Start-To-Discharge Point:** 6 to 12 in. w.c. / 15 to 30 mbar above outlet pressure setting (Applies to 6 to 8 in. w.c. / 15 to 20 mbar and 8 to 10 in. w.c. / 20 to 25 mbar springs only)

Relief Performance: See Figures 3 and 4

### Temperature Capabilities

-20 to 160°F / -29 to 71°C

### Pressure Registration

Internal

### Spring Case Vent Connection

**Standard:** 1 NPT with removable screen

**Optional:** 3/4 NPT with removable screen

#### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



12/17

### Features

- Angle Bodies
- Globe Bodies
- Fixed Factor / PFM Accuracy
- Meets or Exceeds ANSI B109.4 / CSA 6.18 Requirements
- High Capacity Internal Relief
- Compact Design
- High Capacity



Figure 1. Type HSR Pressure Reducing Regulator




Figure 2. Type HSR Pressure Regulator Operational Schematic

1. The pressure/temperature limits in this Datasheet and any applicable standard or code limitation should not be exceeded.

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 1. Construction Material**

BODY	BODY GASKET	CLOSING CAP	ADJUSTING SCREW	DIAPHRAGM CASE, SPRING CASE, ORIFICE AND VALVE STEM	PUSHER POST OR RELIEF VALVE SEAT	DIAPHRAGM AND DISK	CONTROL SPRING	RELIEF VALVE SPRING AND RETAINER, VENT SCREEN AND LEVER PIN	SPRING SEAT, LEVER AND OTHER METAL PARTS	DIAPHRAGM PLATE
Cast iron	Nitrile (NBR)	ASA thermoplastic (provides UV-ray protection)	Delrin®	Aluminum	Delrin®	Nitrile (NBR)	Zinc-plated steel	Stainless steel	Plated steel	Aluminum

**Table 2. Outlet Pressure Range**

OUTLET PRESSURE RANGE		SPRING PART NUMBER	SPRING COLOR	CLOSING CAP	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
In. w.c.	mbar				In.	mm	In.	mm
4 to 6	10 to 15	T14398T0012	Orange	Black	0.062	1.57	3.40	86.4
6 to 8	15 to 20	T14399T0012	Yellow	Black	0.067	1.70	3.61	91.7
8 to 10	20 to 25	T14405T0012	Black	Black	0.067	1.70	3.71	94.2
10 to 12.5	25 to 31	T14400T0012	Silver	Black	0.072	1.83	4.10	104
12.5 to 20	31 to 50	T14401T0012	Gray	Black	0.080	2.03	3.60	91.4
20 to 35	50 to 87	T14402T0012	Pink	Black	0.093	2.36	3.52	89.4
1.25 to 2.2 psig	0.09 to 0.15 bar	T14403T0012	Light Blue	Red	0.105	2.67	3.66	93.0

**Table 3. Maximum Operating Inlet Pressure**

ORIFICE SIZE		MAXIMUM OPERATING INLET PRESSURE TO OBTAIN GOOD REGULATING PERFORMANCE	
In.	mm	psig	bar
1/8	3.2	125	8.6
3/16	4.8	100	6.9
1/4	6.4	60	4.1
3/8	9.5	30	2.1
1/2	13	20	1.4

**Table 4. Lockup Performance During Normal Operation**

ORIFICE SIZE		LOCKUP ABOVE SETPOINT		LOCKUP ABOVE SETPOINT	
In.	mm	In. w.c.	mbar	psi	mbar
1/8	3.2	1	2	0.15	10.3
3/16	4.8	1	2	0.15	10.3
1/4	6.4	2	5	0.15	10.3
3/8	9.5	2.5	6	0.15	10.3
1/2	12	3	7	0.15	10.3

**Table 5. Flow and Sizing Coefficient**

ORIFICE SIZE		WIDE-OPEN FOR RELIEF SIZING		C <sub>1</sub>	IEC SIZING COEFFICIENT		
In.	mm	C <sub>g</sub>	C <sub>v</sub>		X <sub>r</sub>	F <sub>b</sub>	F <sub>L</sub>
1/8	3.2	12.5	0.36	35	0.78	0.82	0.89
3/16	4.8	28.2	0.81			0.82	
1/4	6.4	50	1.43			0.82	
3/8	9.5	105	3.00			0.79	
1/2	13	185	5.29			0.79	

Delrin® is a mark owned by E.I. du Pont de Nemours and Co.





**Table 6. 3/4 NPT Globe Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7 in. w.c. / 17 mbar 6 to 8 in. w.c. / 15 to 20 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	70	1.9	120	3.2	170	4.6	240	6.4	300	8.0
	1	0.07	100	2.7	180	4.8	240	6.4	340	9.1	430	11.5
	2	0.14	130	3.5	250	6.7	330	8.8	510	13.7	630	16.9
	3	0.21	170	4.6	340	9.1	420	11.3	680	18.2	770	20.6
	5	0.35	220	5.9	420	11.3	650	17.4	900	24.1	960	25.7
	10	0.69	330	8.8	730	19.6	1100	29.5	1310	35.1	1310	35.1
	15	1.0	430	11.5	1000	26.8	1380	37.0	1520	40.7	1520	40.7
	20	1.4	530	14.2	1200	32.2	1560	41.8	1620	43.4	1620	43.4
	30	2.1	680	18.2	1550	41.5	1840	49.3	1750	46.9		
	40	2.8	850	22.8	1900	50.9	1950	52.3				
	50	3.4	970	26.0	2200	59.0	2000	53.6				
	60	4.1	1150	30.8	2280	61.1	2100	56.3				
	80	5.5	1450	38.9	2350	63.0						
100	6.9	1750	46.9	1900	50.9							
125	8.6	2100	56.3									
11 in. w.c. / 27 mbar 10 to 12.5 in. w.c. / 25 to 31 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	150	4.0	200	5.4	240	6.4	330	8.8
	2	0.14	120	3.2	200	5.4	270	7.2	420	11.3	530	14.2
	3	0.21	150	4.0	250	6.7	350	9.4	530	14.2	680	18.2
	5	0.35	190	5.1	340	9.1	480	12.9	770	20.6	860	23.0
	10	0.69	290	7.8	550	14.7	910	24.4	1210	32.4	1210	32.4
	15	1.0	400	10.7	840	22.5	1210	32.4	1380	37.0	1380	37.0
	20	1.4	480	12.9	1140	30.6	1550	41.5	1590	42.6	1590	42.6
	30	2.1	670	18.0	1530	41.0	1830	49.0	1810	48.5		
	40	2.8	820	22.0	1970	52.8	1950	52.3				
	50	3.4	970	26.0	2150	57.6	1990	53.3				
	60	4.1	1120	30.0	2260	60.6	2050	54.9				
	80	5.5	1420	38.1	2390	64.1						
	100	6.9	1730	46.4	1950	52.3						
125	8.6	2110	56.6									
14 in. w.c. / 35 mbar 12.5 to 20 in. w.c. / 31 to 50 mbar 2 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	140	3.8	190	5.1	290	7.8	330	8.8
	2	0.14	120	3.2	230	6.2	300	8.0	430	11.5	570	15.3
	3	0.21	160	4.3	290	7.8	360	9.6	580	15.5	730	19.6
	5	0.35	210	5.6	360	9.6	500	13.4	760	20.4	970	26.0
	10	0.69	320	8.6	570	15.3	890	23.9	1190	31.9	1290	34.6
	15	1.0	410	11.0	820	22.0	1210	32.4	1460	39.1	1560	41.8
	20	1.4	500	13.4	1050	28.1	1440	38.6	1660	44.5	1700	45.6
	30	2.1	670	18.0	1500	40.2	1790	48.0	1850	49.6		
	40	2.8	830	22.2	1830	49.0	2020	54.1				
	50	3.4	970	26.0	2100	56.3	2100	56.3				
	60	4.1	1140	30.6	2120	56.8	2180	58.4				
	80	5.5	1440	38.6	2220	59.5						
	100	6.9	1770	47.4	2250	60.3						
125	8.6	2140	57.4									

- Gray areas indicate capacities limited by either droop or boost.  
 - Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 6. 3/4 NPT Globe Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
			1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 1% ABS	2	0.14	120	3.2	250	6.7	310	8.3	420	11.3	570	15.3
	3	0.21	150	4.0	280	7.5	380	10.2	570	15.3	770	20.6
	5	0.35	220	5.9	380	10.2	550	14.7	830	22.2	1040	27.9
	10	0.69	330	8.8	600	16.1	890	23.9	1310	35.1	1570	42.1
	15	1.0	410	11.0	810	21.7	1220	32.7	1600	42.9	1860	49.9
	20	1.4	510	13.7	1020	27.3	1490	39.9	1790	48.0	2020	54.1
	30	2.1	660	17.7	1440	38.6	1820	48.8	2100	56.3		
	40	2.8	830	22.2	1800	48.2	2080	55.7				
	50	3.4	970	26.0	1980	53.1	2280	61.1				
	60	4.1	1130	30.3	2320	62.2	2380	63.8				
	80	5.5	1440	38.6	2400	64.3						
	100	6.9	1760	47.2	2500	67.0						
125	8.6	2150	57.6									
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 2% ABS	2	0.14	150	4.0	310	8.3	470	12.6	710	19.0	930	24.9
	3	0.21	180	4.8	390	10.5	590	15.8	940	25.2	1230	33.0
	5	0.35	250	6.7	530	14.2	840	22.5	1290	34.6	1600	42.9
	10	0.69	360	9.7	810	21.7	1320	35.4	1890	50.7	2200	59.0
	15	1.0	430	11.5	1010	27.1	1650	44.2	2290	61.4	2530	67.8
	20	1.4	530	14.2	1200	32.2	1940	52.0	2490	66.7	2750	73.7
	30	2.1	670	18.0	1570	42.1	2430	65.1	2900	77.7		
	40	2.8	830	22.2	1920	51.5	2720	72.9				
	50	3.4	970	26.0	2280	61.1	2830	75.8				
	60	4.1	1130	30.3	2630	70.5	3050	81.7				
	80	5.5	1440	38.6	3050	81.7						
	100	6.9	1760	47.1	3150	84.4						
125	8.6	2150	57.6									
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 1% ABS	3	0.21	120	3.2	190	5.1	250	6.7	330	8.8	450	12.1
	5	0.35	150	4.0	270	7.2	360	9.6	560	15.0	750	20.1
	10	0.69	250	6.7	430	11.5	620	16.6	1020	27.3	1340	35.9
	15	1.0	330	8.8	600	16.1	800	21.4	1350	36.2	1480	39.7
	20	1.4	410	11.0	740	19.8	1040	27.9	1540	41.3	1800	48.2
	30	2.1	560	15.0	1050	28.1	1450	38.9	1850	49.6		
	40	2.8	730	19.6	1320	35.4	1640	44.0				
	50	3.4	870	23.3	1620	43.4	1900	50.9				
	60	4.1	1030	27.6	1910	51.2	2140	57.4				
	80	5.5	1350	36.2	2090	56.0						
	100	6.9	1650	44.2	2180	58.4						
	125	8.6	2000	53.6								
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 2% ABS	3	0.21	150	4.0	270	7.2	420	11.3	600	16.1	790	21.2
	5	0.35	210	5.6	420	11.3	620	16.6	960	25.7	1230	33.0
	10	0.69	340	9.1	700	18.8	1050	28.1	1430	38.3	1880	50.4
	15	1.0	440	11.8	940	25.2	1350	36.2	1880	50.4	2230	59.8
	20	1.4	520	13.9	1150	30.8	1620	43.4	2260	60.6	2540	68.1
	30	2.1	670	18.0	1540	41.3	2110	56.6	2520	67.5		
	40	2.8	830	22.2	1880	50.4	2430	65.1				
	50	3.4	970	26.0	2170	58.2	2640	70.8				
	60	4.1	1130	30.3	2460	65.9	2850	76.4				
	80	5.5	1450	38.9	2850	76.4						
	100	6.9	1750	46.9	3000	80.4						
	125	8.6	2100	56.3								

Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.



**Table 7. 3/4 x 1 NPT Globe Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
5 in. w.c. / 12 mbar 4 to 6 in. w.c. / 10 to 15 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	----	----	----	----	190	5.1	240	6.4	285	7.6
	1	0.07	110	3.0	220	5.9	250	6.7	355	9.5	450	12.1
	2	0.14	170	4.6	250	6.7	340	9.1	490	13.1	770	20.6
	3	0.21	210	5.6	340	9.1	500	13.4	750	20.1	1000	26.8
	5	0.35	245	6.6	400	10.7	750	20.1	1190	31.9	1330	35.6
	10	0.69	375	10.1	785	21.0	1290	34.6	1585	42.5		
	15	1.0	475	12.7	995	26.7	1590	42.6				
	20	1.4	565	15.1	1160	31.1	1850	49.6				
	30	2.1	740	19.8	1475	39.5						
	40	2.8	900	24.1	1840	49.3						
	50	3.4	1050	28.1	2180	58.4						
	60	4.1	1215	32.6								
	80	5.5	1555	41.7								
	100	6.9	1880	50.4								
9 in. w.c. / 22 mbar 8 to 10 in. w.c. / 20 to 25 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	----	----	150	4.0	170	4.6	240	6.4	325	8.7
	2	0.14	125	3.4	190	5.1	225	6.0	345	9.3	475	12.7
	3	0.21	195	5.2	220	5.9	270	7.2	475	12.7	660	17.7
	5	0.35	210	5.6	275	7.4	400	10.7	685	18.4	880	23.6
	10	0.69	280	7.5	440	11.8	710	19.0	1235	33.1	1250	33.5
	15	1.0	370	9.9	685	18.4	1360	36.4	1585	42.5	1400	37.5
	20	1.4	485	13.0	945	25.3	1610	43.1	1820	48.8	1540	41.3
	30	2.1	680	18.2	1485	39.8	2080	55.7	2110	56.6		
	40	2.8	885	23.7	1840	49.3	2300	61.6				
	50	3.4	1050	28.1	2150	57.6	2760	74.0				
	60	4.1	1215	32.6	2475	66.3	3115	83.5				
	80	5.5	1530	41.0	3150	84.4						
	100	6.9	1855	49.7	2900	77.7						
	125	8.6	2300	61.6								

- Gray areas indicate capacities limited by either droop or boost.  
 - Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 8. 1 NPT Globe Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7 in. w.c. / 17 mbar 6 to 8 in. w.c. / 15 to 20 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	70	1.9	120	3.2	170	4.7	240	6.4	300	8.0
	1	0.07	100	2.7	180	4.8	240	6.4	340	9.1	430	11.5
	2	0.14	130	3.5	250	6.7	330	8.8	510	13.7	630	16.9
	3	0.21	170	4.7	340	9.1	420	11.3	680	18.2	770	20.6
	5	0.35	220	5.9	420	11.3	650	17.4	960	25.7	1080	28.9
	10	0.69	330	8.8	730	19.6	1100	29.5	1310	35.1	1600	42.9
	15	1.0	430	11.5	1000	26.8	1440	38.6	1770	47.4	1800	48.2
	20	1.4	530	14.2	1200	32.2	1810	48.5	2100	56.3	1960	52.5
	30	2.1	680	18.2	1550	41.5	2100	56.3	2450	65.7		
	40	2.8	850	22.8	1900	50.9	2150	57.6				
	50	3.4	970	26.0	2200	59.0	2690	72.1				
	60	4.1	1150	30.8	2280	61.1	3010	80.7				
	80	5.5	1450	38.9	2350	63.0						
100	6.9	1750	46.9	1900	50.9							
125	8.6	2100	56.3									
11 in. w.c. / 27 mbar 10 to 12.5 in. w.c. / 25 to 31 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	150	4.0	200	5.4	240	6.4	330	8.8
	2	0.14	120	3.2	200	5.4	270	7.2	420	11.3	530	14.2
	3	0.21	150	4.0	250	6.7	350	9.4	530	14.2	680	18.2
	5	0.35	190	5.1	340	9.1	480	12.9	770	20.6	870	23.3
	10	0.69	290	7.8	550	14.7	910	24.4	1230	33.0	1350	36.2
	15	1.0	400	10.7	840	22.5	1290	34.6	1450	38.9	1630	43.7
	20	1.4	480	12.9	1140	30.6	1420	38.1	1650	44.2	1870	50.1
	30	2.1	670	18.0	1530	41.0	1680	45.0	2100	56.3		
	40	2.8	820	22.0	1970	52.8	1750	46.9				
	50	3.4	970	26.0	2150	57.6	1840	49.3				
	60	4.1	1120	30.0	2260	60.6	2130	57.1				
	80	5.5	1420	38.1	2390	64.1						
	100	6.9	1730	46.4	1950	52.3						
125	8.6	2110	56.6									
14 in. w.c. / 35 mbar 12.5 to 20 in. w.c. / 31 to 50 mbar 2 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	140	3.7	190	5.1	290	7.8	330	8.8
	2	0.14	120	3.2	230	6.2	300	8.0	430	11.5	570	15.3
	3	0.21	160	4.3	290	7.8	360	9.7	580	15.5	730	19.6
	5	0.35	210	5.6	360	9.7	500	13.4	760	20.4	970	26.0
	10	0.69	320	8.6	570	15.3	890	23.9	1190	31.9	1530	41.0
	15	1.0	410	11.0	820	22.0	1210	32.4	1460	39.1	1780	47.7
	20	1.4	500	13.4	1050	28.1	1440	38.6	1660	44.5	1950	52.3
	30	2.1	670	18.0	1500	40.2	1790	48.0	2200	59.0		
	40	2.8	830	22.2	1830	49.0	2020	54.1				
	50	3.4	970	26.0	2100	56.3	2100	56.3				
	60	4.1	1140	30.6	2350	63.0	2180	58.4				
	80	5.5	1440	38.6	3000	80.4						
	100	6.9	1770	47.4	2550	68.3						
125	8.6	2140	57.4									

Gray areas indicate capacities limited by either droop or boost.  
Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -



**Table 8. 1 NPT Globe Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 1% ABS	2	0.14	120	3.2	250	6.7	310	8.3	420	11.3	570	15.3
	3	0.21	150	4.0	280	7.5	380	10.2	570	15.3	770	20.6
	5	0.35	220	5.9	380	10.2	550	14.7	830	22.2	1040	27.9
	10	0.69	330	8.8	600	16.1	890	23.9	1310	35.1	1570	42.1
	15	1.0	410	11.0	810	21.7	1220	32.7	1600	42.9	2000	53.6
	20	1.4	510	13.7	1020	27.3	1490	39.9	2000	53.6	2300	61.6
	30	2.1	660	17.7	1440	38.6	1820	48.8	2450	65.7		
	40	2.8	830	22.2	1800	48.2	2080	55.7				
	50	3.4	970	26.0	2120	56.8	2430	65.1				
	60	4.1	1130	30.3	2340	62.7	2800	75.0				
	80	5.5	1440	38.6	2800	75.0						
	100	6.9	1760	47.2	3100	83.1						
125	8.6	2150	57.6									
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 2% ABS	2	0.14	150	4.0	310	8.3	470	12.6	710	19.0	970	26.0
	3	0.21	180	4.8	390	10.5	590	15.8	940	25.2	1290	34.6
	5	0.35	250	6.7	530	14.2	840	22.5	1380	37.0	1710	45.8
	10	0.69	360	9.7	810	21.7	1320	35.4	2060	55.2	2500	67.0
	15	1.0	430	11.5	1010	27.1	1750	46.9	2550	68.3	3030	81.2
	20	1.4	530	14.2	1200	32.2	2130	57.1	2930	78.5	3380	90.6
	30	2.1	670	18.0	1570	42.1	2790	74.8	2550	68.3		
	40	2.8	830	22.2	1920	51.5	3400	91.1				
	50	3.4	970	26.0	2280	61.1	3800	102				
	60	4.1	1130	30.3	2630	70.5	4050	109				
	80	5.5	1440	38.6	3330	89.2						
	100	6.9	1760	47.2	4050	109						
125	8.6	2150	57.6									
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 1% ABS	3	0.21	120	3.2	190	5.1	250	6.7	330	8.8	450	12.1
	5	0.35	150	4.0	270	7.2	360	9.7	560	15.0	750	20.1
	10	0.69	250	6.7	430	11.5	620	16.6	1020	27.3	1340	35.9
	15	1.0	330	8.8	600	16.1	800	21.4	1350	36.2	1600	42.9
	20	1.4	410	11.0	740	19.8	1040	27.9	1580	42.3	2040	54.7
	30	2.1	560	15.0	1050	28.1	1350	36.2	1980	53.1		
	40	2.8	730	19.6	1320	35.4	1790	48.0				
	50	3.4	870	23.3	1620	43.4	1960	52.5				
	60	4.1	1030	27.6	1910	51.2	2140	57.4				
	80	5.5	1350	36.2	2350	63.0						
	100	6.9	1650	44.2	2600	69.7						
	125	8.6	2000	53.6								
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 2% ABS	3	0.21	150	4.0	270	7.2	420	11.3	600	16.1	790	21.2
	5	0.35	210	5.6	420	11.3	620	16.6	960	25.7	1230	33.0
	10	0.69	340	9.1	700	18.8	1050	28.1	1650	44.2	2000	53.6
	15	1.0	440	11.8	940	25.2	1450	38.9	2130	57.1	2580	69.1
	20	1.4	520	13.9	1150	30.8	1750	46.9	2600	69.7	2980	79.9
	30	2.1	670	18.0	1540	41.3	2290	61.4	3180	85.2		
	40	2.8	830	22.2	1880	50.4	2740	73.4				
	50	3.4	970	26.0	2220	59.5	2310	61.9				
	60	4.1	1130	30.3	2600	69.7	3600	96.5				
	80	5.5	1450	38.9	3340	89.5						
	100	6.9	1750	46.9	4000	107						
	125	8.6	2100	56.3								

Gray areas indicate capacities limited by either droop or boost.  
Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 9. 1-1/4 NPT Globe Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7 in. w.c. / 17 mbar 6 to 8 in. w.c. / 15 to 20 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	55	1.47	105	2.81	145	3.89	195	5.23	320	8.58
	1	0.07	90	2.41	145	3.89	215	5.76	310	8.31	340	9.11
	2	0.14	125	3.35	230	6.16	285	7.64	400	10.7	400	10.7
	3	0.21	170	4.56	225	6.03	365	9.78	545	14.6	580	15.5
	5	0.35	225	6.03	295	7.91	480	12.9	710	19.0	965	25.9
	10	0.69	275	7.37	450	12.1	670	18.0	1190	31.9	1495	40.1
	15	1.0	380	10.2	585	15.7	945	25.3	1745	46.8	1760	47.2
	20	1.4	475	12.7	780	20.9	1320	35.4	2275	61.0	2115	56.7
	30	2.1	625	16.8	1000	26.8	2275	61.0	3430	91.9		
	40	2.8	775	20.8	1045	28.0	3035	81.3				
	50	3.4	940	25.2	1570	42.1	3595	96.3				
	60	4.1	1065	28.5	1085	29.1	1200	32.2				
	80	5.5	1165	31.2	925	24.8						
	100	6.9	1260	33.8	995	26.7						
125	8.6	1300	34.8									
11 in. w.c. / 27 mbar 10 to 12.5 in. w.c. / 25 to 31 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	70	1.88	125	3.35	145	3.89	205	5.49	220	5.90
	2	0.14	110	2.95	165	4.42	190	5.09	300	8.04	355	9.51
	3	0.21	160	4.29	190	5.09	255	6.83	370	9.92	470	12.6
	5	0.35	205	5.49	220	5.90	350	9.38	500	13.4	710	19.0
	10	0.69	255	6.83	325	8.71	485	13.0	855	22.9	1315	35.2
	15	1.0	310	8.31	420	11.3	605	16.2	1360	36.4	1615	43.3
	20	1.4	420	11.3	475	12.7	685	18.4	1930	51.7	1905	51.1
	30	2.1	530	14.2	625	16.8	800	21.4	2850	76.4		
	40	2.8	670	18.0	720	19.3	830	22.2				
	50	3.4	830	22.2	820	22.0	890	23.9				
	60	4.1	930	24.9	920	24.7	905	24.3				
	80	5.5	1030	27.6	1020	27.3						
	100	6.9	1075	28.8	945	25.3						
	125	8.6	1135	30.4								

Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -



**Table 9. 1-1/4 NPT Globe Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
14 in. w.c. / 35 mbar 12.5 to 20 in. w.c. / 31 to 50 mbar 2 in. w.c. droop 2 in. w.c. boost	1	0.07	70	1.88	125	3.35	220	5.90	220	5.90	310	8.31
	2	0.14	100	2.68	170	4.56	240	6.43	360	9.65	455	12.2
	3	0.21	150	4.02	175	4.69	310	8.31	420	11.3	620	16.6
	5	0.35	120	3.22	240	6.43	410	11.0	600	16.1	860	23.0
	10	0.69	180	4.82	415	11.1	605	16.2	860	23.0	1350	36.2
	15	1.0	345	9.25	530	14.2	740	19.8	1395	37.4	1690	45.3
	20	1.4	370	9.92	645	17.3	890	23.9	1710	45.8	1990	53.3
	30	2.1	585	15.7	830	22.2	1195	32.0	2900	77.7		
	40	2.8	625	16.8	1025	27.5	1825	48.9				
	50	3.4	825	22.1	1155	31.0	2565	68.7				
	60	4.1	1030	27.6	1360	36.4	3045	81.6				
	80	5.5	1110	29.7	1665	44.6						
	100	6.9	1190	31.9	1385	37.1						
125	8.6	1290	34.6									
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 1% ABS	2	0.14	85	2.28	160	4.29	260	6.97	315	8.44	475	12.7
	3	0.21	105	2.81	205	5.49	315	8.44	500	13.4	600	16.1
	5	0.35	140	3.75	245	6.57	485	13.0	670	18.0	920	24.7
	10	0.69	195	5.23	420	11.3	600	16.1	1190	31.9	1345	36.0
	15	1.0	295	7.91	505	13.5	850	22.8	1495	40.1	1825	48.9
	20	1.4	330	8.84	665	17.8	1030	27.6	1790	48.0	2070	55.5
	30	2.1	530	14.2	965	25.9	1425	38.2	2585	69.3		
	40	2.8	500	13.4	1120	30.0	1935	51.9				
	50	3.4	810	21.7	1360	36.4	2320	62.2				
	60	4.1	745	20.0	1485	39.8	2915	78.1				
	80	5.5	930	24.9	2120	56.8						
	100	6.9	1360	36.4	1895	50.8						
	125	8.6	1580	42.3								

☐ – Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 9. 1-1/4 NPT Globe Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS										
			Orifice Size, In. /mm										
			1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
	psig	bar	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 2% ABS	2	0.14	110	2.95	240	6.43	410	11.0	570	15.3	875	23.4	
	3	0.21	135	3.62	270	7.24	550	14.7	905	24.3	1200	32.2	
	5	0.35	185	4.96	395	10.6	765	20.5	1220	32.7	1655	44.4	
	10	0.69	270	7.24	540	14.5	915	24.5	2040	54.7	2490	66.7	
	15	1.0	375	10.0	855	22.9	1530	41.0	2605	69.8	3045	81.6	
	20	1.4	435	11.7	985	26.4	1760	47.2	3010	80.7	3750	100	
	30	2.1	615	16.5	1355	36.3	2270	60.8	4250	114			
	40	2.8	650	17.4	1690	45.3	2900	77.7					
	50	3.4	905	24.3	2010	53.9	3515	94.2					
	60	4.1	955	25.6	2285	61.2	4095	110					
	80	5.5	1210	32.4	3020	80.9							
	100	6.9	1615	43.3	3645	97.7							
125	8.6	2030	54.4										
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 1% ABS	3	0.21	80	2.14	265	7.10	210	5.63	275	7.37	380	10.2	
	5	0.35	95	2.55	240	6.43	320	8.58	465	12.5	630	16.9	
	10	0.69	185	4.96	360	9.65	560	15.0	810	21.7	1060	28.4	
	15	1.0	150	4.02	490	13.1	730	19.6	1130	30.3	1260	33.8	
	20	1.4	255	6.83	600	16.1	810	21.7	1400	37.5	1690	45.3	
	30	2.1	395	10.6	795	21.3	1065	28.5	1935	51.9			
	40	2.8	425	11.4	960	25.7	1410	37.8					
	50	3.4	540	14.5	1110	29.7	1605	43.0					
	60	4.1	685	18.4	1360	36.4	1960	52.5					
	80	5.5	1015	27.2	1670	44.8							
	100	6.9	1085	29.1	1575	42.2							
	125	8.6	1055	28.3									
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 2% ABS	3	0.21	105	2.81	300	8.04	350	9.38	535	14.3	755	20.2	
	5	0.35	125	3.35	350	9.38	530	14.2	885	23.7	1245	33.4	
	10	0.69	235	6.30	580	15.5	950	25.5	1530	41.0	2010	53.9	
	15	1.0	230	6.16	770	20.6	1240	33.2	2040	54.7	2565	68.7	
	20	1.4	300	8.04	965	25.9	1505	40.3	2530	67.8	3070	82.3	
	30	2.1	470	12.6	1310	35.1	1990	53.3	3410	91.4			
	40	2.8	530	14.2	1640	44.0	2710	72.6					
	50	3.4	675	18.1	1890	50.7	3140	84.2					
	60	4.1	805	21.6	2330	62.4	3790	102					
	80	5.5	1225	32.8	3010	80.7							
	100	6.9	1390	37.3	3480	93.3							
	125	8.6	1250	33.5									

Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.





**Table 10. 3/4 NPT Angle Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7 in. w.c. / 17 mbar 6 to 8 in. w.c. / 15 to 20 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	70	1.9	120	3.2	170	4.6	240	6.4	300	8.0
	1	0.07	100	2.7	180	4.8	240	6.4	340	9.1	430	11.5
	2	0.14	130	3.5	250	6.7	330	8.8	510	13.7	630	16.9
	3	0.21	170	4.6	340	9.1	420	11.3	680	18.2	770	20.6
	5	0.35	220	5.9	420	11.3	650	17.4	900	24.1	960	25.7
	10	0.69	330	8.8	730	19.6	1100	29.5	1310	35.1	1310	35.1
	15	1.0	430	11.5	1000	26.8	1380	37.0	1520	40.7	1520	40.7
	20	1.4	530	14.2	1200	32.2	1560	41.8	1620	43.4	1620	43.4
	30	2.1	680	18.2	1550	41.5	1840	49.3	1750	46.9		
	40	2.8	850	22.8	1900	50.9	1950	52.3				
	50	3.4	970	26.0	2200	59.0	2000	53.6				
	60	4.1	1150	30.8	2280	61.1	2100	56.3				
	80	5.5	1450	38.9	2350	63.0						
	100	6.9	1750	46.9	1900	50.9						
125	8.6	2100	56.3									
11 in. w.c. / 27 mbar 10 to 12.5 in. w.c. / 25 to 31 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	150	4.0	200	5.4	240	6.4	330	8.8
	2	0.14	120	3.2	200	5.4	270	7.2	420	11.3	530	14.2
	3	0.21	150	4.0	250	6.7	350	9.4	530	14.2	680	18.2
	5	0.35	190	5.1	340	9.1	480	12.9	770	20.6	860	23.1
	10	0.69	290	7.8	550	14.7	910	24.4	1210	32.4	1210	32.4
	15	1.0	400	10.7	840	22.5	1210	32.4	1380	37.0	1380	37.0
	20	1.4	480	12.9	1140	30.6	1550	41.5	1590	42.6	1590	42.6
	30	2.1	670	18.0	1530	41.0	1830	49.0	1780	47.7		
	40	2.8	820	22.0	1970	52.8	1950	52.3				
	50	3.4	970	26.0	2150	57.6	1990	53.3				
	60	4.1	1120	30.0	2260	60.6	2050	54.9				
	80	5.5	1420	38.0	2390	64.1						
	100	6.9	1730	46.4	1950	52.3						
	125	8.6	2110	56.6								
14 in. w.c. / 35 mbar 12.5 to 20 in. w.c. / 31 to 50 mbar 2 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	140	3.8	190	5.1	290	7.8	330	8.8
	2	0.14	120	3.2	230	6.2	300	8.0	430	11.5	570	15.3
	3	0.21	160	4.3	290	7.8	360	9.7	580	15.5	730	19.6
	5	0.35	210	5.6	360	9.7	500	13.4	760	20.4	970	26.0
	10	0.69	320	8.6	570	15.3	890	23.9	1190	31.9	1290	34.6
	15	1.0	410	11.0	820	22.0	1210	32.4	1460	39.1	1560	41.8
	20	1.4	500	13.4	1050	28.1	1440	38.6	1660	44.5	1700	45.6
	30	2.1	670	18.0	1500	40.2	1790	48.0	1850	49.6		
	40	2.8	830	22.2	1830	49.0	2020	54.1				
	50	3.4	970	26.0	2100	56.3	2100	56.3				
	60	4.1	1140	30.6	2120	56.8	2180	58.4				
	80	5.5	1440	38.6	2220	59.5						
	100	6.9	1770	47.4	2250	60.3						
	125	8.6	2140	57.4								

- Gray areas indicate capacities limited by either droop or boost.  
 - Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 10. 3/4 NPT Angle Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS										
			Orifice Size, In. / mm										
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13		
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 1% ABS	2	0.14	120	3.2	250	6.7	310	8.3	420	11.3	570	15.3	
	3	0.21	150	4.0	280	7.5	380	10.2	570	15.3	770	20.6	
	5	0.35	220	5.9	380	10.2	550	14.7	830	22.2	1040	27.9	
	10	0.69	330	8.8	600	16.1	890	23.9	1310	35.1	1570	42.1	
	15	1.0	410	11.0	810	21.7	1220	32.7	1600	42.9	1860	49.9	
	20	1.4	510	13.7	1020	27.3	1490	39.9	1790	48.0	2020	54.1	
	30	2.1	660	17.7	1440	38.6	1820	48.8	2100	56.3			
	40	2.8	830	22.2	1800	48.2	2080	55.7					
	50	3.4	970	26.0	1980	53.1	2280	61.1					
	60	4.1	1130	30.3	2320	62.2	2380	63.8					
	80	5.5	1440	38.6	2400	64.3							
	100	6.9	1760	47.2	2500	67.0							
125	8.6	2150	57.6										
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 2% ABS	2	0.14	150	4.0	310	8.3	470	12.6	710	19.0	930	24.9	
	3	0.21	180	4.8	390	10.5	590	15.8	940	25.2	1230	33.0	
	5	0.35	250	6.7	530	14.2	840	22.5	1290	34.6	1600	42.9	
	10	0.69	360	9.7	810	21.7	1320	35.4	1890	50.7	2200	59.0	
	15	1.0	430	11.5	1010	27.1	1650	44.2	2290	61.4	2530	67.8	
	20	1.4	530	14.2	1200	32.2	1940	52.0	2490	66.7	2750	73.7	
	30	2.1	670	18.0	1570	42.1	2430	65.1	2900	77.7			
	40	2.8	830	22.2	1920	51.5	2720	72.9					
	50	3.4	970	26.0	2280	61.1	2830	75.8					
	60	4.1	1130	30.3	2630	70.5	3050	81.7					
	80	5.5	1440	38.6	3050	81.7							
	100	6.9	1760	47.2	3150	84.4							
125	8.6	2150	57.6										
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 1% ABS	3	0.21	120	3.2	190	5.1	250	6.7	330	8.8	450	12.1	
	5	0.35	150	4.0	270	7.2	360	9.7	560	15.0	750	20.1	
	10	0.69	250	6.7	430	11.5	620	16.6	1020	27.3	1340	35.9	
	15	1.0	330	8.8	600	16.1	800	21.4	1350	36.2	1480	39.7	
	20	1.4	410	11.0	740	19.8	1040	27.9	1540	41.3	1800	48.2	
	30	2.1	560	15.0	1050	28.1	1450	38.9	1850	49.6			
	40	2.8	730	19.6	1320	35.4	1640	44.0					
	50	3.4	870	23.3	1620	43.4	1900	50.9					
	60	4.1	1030	27.6	1910	51.2	2140	57.4					
	80	5.5	1350	36.2	2090	56.0							
	100	6.9	1650	44.2	2180	58.4							
	125	8.6	2000	53.6									
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 2% ABS	3	0.21	150	4.0	270	7.2	420	11.3	600	16.1	790	21.2	
	5	0.35	210	5.6	420	11.3	620	16.6	960	25.7	1230	32.9	
	10	0.69	340	9.1	700	18.8	1050	28.1	1430	38.3	1880	50.4	
	15	1.0	440	11.8	940	25.2	1350	36.2	1880	50.4	2230	59.8	
	20	1.4	520	13.9	1150	30.8	1620	43.4	2260	60.6	2540	68.1	
	30	2.1	670	18.0	1540	41.3	2110	56.6	2520	67.5			
	40	2.8	830	22.2	1880	50.4	2430	65.1					
	50	3.4	970	26.0	2170	58.2	2640	70.8					
	60	4.1	1130	30.3	2460	65.9	2850	76.4					
	80	5.5	1450	38.9	2850	76.4							
	100	6.9	1750	46.9	3000	80.4							
	125	8.6	2100	56.3									

Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.



**Table 11. 1 NPT Angle Body Capacities**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7 in. w.c. / 17 mbar 6 to 8 in. w.c. / 15 to 20 mbar 1 in. w.c. droop 2 in. w.c. boost	0.5	0.03	70	1.9	120	3.2	170	4.6	240	6.4	300	8.0
	1	0.07	100	2.7	180	4.8	240	6.4	340	9.1	430	11.5
	2	0.14	130	3.5	250	6.7	330	8.8	510	13.7	630	16.9
	3	0.21	170	4.6	340	9.1	420	11.3	680	18.2	860	23.1
	5	0.35	220	5.9	420	11.3	650	17.4	1030	27.6	1130	30.3
	10	0.69	330	8.8	730	19.6	1100	29.5	1560	41.8	1520	40.7
	15	1.0	430	11.5	1000	26.8	1560	41.8	1830	49.0	1820	48.8
	20	1.4	530	14.2	1200	32.2	2220	59.5	2270	60.8	2370	63.5
	30	2.1	680	18.2	1550	41.5	2880	77.2	2770	74.2		
	40	2.8	850	22.8	1900	50.9	3550	95.1				
	50	3.4	970	26.0	2200	59.0	4000	107				
	60	4.1	1150	30.8	2280	61.1	4200	113				
	80	5.5	1450	38.7	2350	63.0						
100	6.9	1750	46.9	1900	50.9							
125	8.6	2100	56.3									
11 in. w.c. / 27 mbar 10 to 12.5 in. w.c. / 25 to 31 mbar 1 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	150	4.0	200	5.4	240	6.4	330	8.8
	2	0.14	120	3.2	200	5.4	270	7.2	420	11.3	530	14.2
	3	0.21	150	4.0	250	6.7	350	9.4	530	14.2	680	18.2
	5	0.35	190	5.1	340	9.1	480	12.9	770	20.6	970	26.0
	10	0.69	290	7.8	550	14.7	1050	28.1	1230	33.0	1430	38.3
	15	1.0	400	10.7	840	22.5	1470	39.4	1750	46.9	1760	47.2
	20	1.4	480	12.9	1140	30.6	1920	51.5	2230	59.8	2450	65.7
	30	2.1	670	18.0	1530	41.0	2430	65.1	2900	77.7		
	40	2.8	820	22.0	1970	52.8	2870	76.9				
	50	3.4	970	26.0	2150	57.6	3420	91.7				
	60	4.1	1120	30.0	2260	60.6	3750	101				
	80	5.5	1420	38.1	2390	64.1						
	100	6.9	1730	46.4	1950	52.3						
125	8.6	2110	56.6									
14 in. w.c. / 35 mbar 12.5 to 20 in. w.c. / 31 to 50 mbar 2 in. w.c. droop 2 in. w.c. boost	1	0.07	80	2.1	140	3.8	190	5.1	290	7.8	330	8.8
	2	0.14	120	3.2	230	6.2	300	8.0	430	11.5	570	15.3
	3	0.21	160	4.3	290	7.8	360	9.7	580	15.5	730	19.6
	5	0.35	210	5.6	360	9.7	500	13.4	760	20.4	1000	26.8
	10	0.69	320	8.6	570	15.3	890	23.9	1290	34.6	1480	39.7
	15	1.0	410	11.0	820	22.0	1210	32.4	1570	42.1	1760	47.2
	20	1.4	500	13.4	1050	28.1	1510	40.5	1800	48.2	2400	64.3
	30	2.1	670	18.0	1500	40.2	1980	53.1	2430	65.1		
	40	2.8	830	22.2	1880	50.4	2250	60.3				
	50	3.4	970	26.0	2190	58.7	2570	68.9				
	60	4.1	1140	30.6	2450	65.7	3400	91.1				
	80	5.5	1440	38.6	3390	90.9						
	100	6.9	1770	47.4	2600	69.7						
125	8.6	2140	57.4									

- Gray areas indicate capacities limited by either droop or boost.  
 - Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.

- continued -

# Type HSR

## Pressure Reducing Regulator

FISHER™

**Table 11. 1 NPT Angle Body Capacities (continued)**

OUTLET PRESSURE SETTING, SPRING RANGE, DROOP AND BOOST	INLET PRESSURE		CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
			Orifice Size, In. / mm									
	psig	bar	1/8 / 3.2		3/16 / 4.8		1/4 / 6.4		3/8 / 9.5		1/2 / 13	
			SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 1% ABS	2	0.14	120	3.2	250	6.7	310	8.3	420	11.3	570	15.3
	3	0.21	150	4.0	280	7.5	380	10.2	570	15.3	770	20.6
	5	0.35	220	5.9	380	10.2	550	14.7	830	22.2	1150	30.8
	10	0.69	330	8.8	600	16.1	890	23.9	1310	35.1	1700	45.6
	15	1.0	410	11.0	810	21.7	1220	32.7	1720	46.1	2200	59.0
	20	1.4	510	13.7	1020	27.3	1490	39.9	2100	56.3	2500	67.0
	30	2.1	660	17.7	1440	38.6	2120	56.8	2650	71.0		
	40	2.8	830	22.2	1800	48.2	2500	67.0				
	50	3.4	970	26.0	2120	56.8	2900	77.7				
	60	4.1	1130	30.3	2340	62.7	3350	89.8				
	80	5.5	1440	38.6	2800	75.0						
	100	6.9	1760	47.2	3100	83.1						
125	8.6	2150	57.6									
28 in. w.c. / 70 mbar 20 to 35 in. w.c. / 50 to 87 mbar ± 2% ABS	2	0.14	150	4.0	310	8.3	470	12.6	710	19.0	1030	27.6
	3	0.21	180	4.8	390	10.5	590	15.8	940	25.2	1380	37.0
	5	0.35	250	6.7	530	14.2	840	22.5	1380	37.0	1850	49.6
	10	0.69	360	9.7	810	21.7	1320	35.4	2170	58.2	2650	71.0
	15	1.0	430	11.5	1010	27.1	1750	46.9	2800	75.0	3250	87.1
	20	1.4	530	14.2	1200	32.2	2130	57.1	3300	88.4	3650	97.8
	30	2.1	670	18.0	1570	42.1	2790	74.8	4000	107		
	40	2.8	830	22.2	1920	51.5	3550	95.1				
	50	3.4	970	26.0	2280	61.1	4150	111				
	60	4.1	1130	30.3	2630	70.5	4800	129				
	80	5.5	1440	38.6	3330	89.2						
	100	6.9	1760	47.2	4050	109						
125	8.6	2150	57.6									
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 1% ABS	3	0.21	120	3.2	190	5.1	250	6.7	330	8.8	450	12.1
	5	0.35	150	4.0	270	7.2	360	9.7	560	15.0	750	20.1
	10	0.69	250	6.7	430	11.5	620	16.6	1020	27.3	1340	35.9
	15	1.0	330	8.8	600	16.2	800	21.4	1350	36.2	1600	42.9
	20	1.4	410	11.0	740	19.8	1040	27.9	1700	45.6	2040	54.7
	30	2.1	560	15.0	1050	28.1	1650	44.2	2240	60.0		
	40	2.8	730	19.6	1320	35.4	1920	51.5				
	50	3.4	870	23.3	1620	43.4	2130	57.1				
	60	4.1	1030	27.6	1910	51.2	2500	67.0				
	80	5.5	1350	36.2	2350	63.0						
	100	6.9	1650	44.2	2600	69.7						
	125	8.6	2000	53.6								
2 psig / 0.14 bar 1.25 to 2.2 psig / 0.09 to 0.15 bar ± 2% ABS	3	0.21	150	4.0	270	7.2	420	11.3	600	16.1	790	21.2
	5	0.35	210	5.6	420	11.3	620	16.6	960	25.7	1320	35.4
	10	0.69	340	9.1	700	18.8	1050	28.1	1650	44.2	2150	57.6
	15	1.0	440	11.8	940	25.2	1450	38.9	2230	59.8	2720	72.9
	20	1.4	520	13.9	1150	30.8	1750	46.9	2730	73.2	3240	86.8
	30	2.1	670	18.0	1540	41.3	2470	66.2	3520	94.3		
	40	2.8	830	22.2	1880	50.4	2930	78.5				
	50	3.4	970	26.0	2220	59.5	3600	96.5				
	60	4.1	1130	30.3	2600	69.7	4200	113				
	80	5.5	1450	38.9	3340	89.5						
	100	6.9	1750	46.9	4000	107						
	125	8.6	2100	56.3								

Blank areas indicate where maximum operating inlet pressure is exceeded for a given orifice.






Figure 3. 7 in. w.c. / 17 mbar Setpoint Relief Curves (with Lever Disconnected, No Vent Piping and 3/4 or 1 NPT Vent)




Figure 4. 2 psig / 0.14 bar Setpoint Relief Curves (with Lever Disconnected, No Vent Piping and 3/4 or 1 NPT Vent)

Table 12. Relief Performance <sup>(1)</sup>				
ORIFICE SIZE		MAXIMUM ALLOWABLE INLET PRESSURE IF OUTLET PRESSURE IS HELD AT OR BELOW 2 psig / 0.14 bar		
In.	mm	psig	bar	
1/8	3.2	125	8.6	
3/16	4.8	65	4.5	
1/4	6.4	30	2.1	
3/8	9.5	10	0.69	
1/2	13	7	0.48	

1. The relief performance testing is in accordance with ANSI B109.4 and CSA 6.18 with the regulator set at 7 in. w.c. / 17 mbar stem linkage disconnected and vented directly to atmosphere using the 3/4 or 1 NPT vent.

# Type HSR

## Pressure Reducing Regulator

FISHER™





Figure 5. Regulator Body and Spring Case Vent Locations (Body Position is with Regard to the Outlet)



NOTE: THE STANDARD BODY ORIENTATION FOR THE ANGLE BODY IS WITH THE BODY OUTLET ROTATED 90° TOWARD THE READER. COMPARED TO FIGURE 5, THE OUTLET OF THE ANGLE BODY WILL POINT IN THE SAME DIRECTION AS POSITION "3" OF A GLOBE BODY.

IN. /  
mm

Figure 6. Dimensions



## Ordering Guide

Body Type, Size and End Connection Style (Select One)	
Globe	Angle
<input type="checkbox"/> 3/4 NPT***	<input type="checkbox"/> 3/4 NPT***
<input type="checkbox"/> 3/4 x 1 NPT***	<input type="checkbox"/> 3/4 x 1 NPT***
<input type="checkbox"/> 1 NPT***	<input type="checkbox"/> 1 NPT***
<input type="checkbox"/> 1-1/4 NPT***	

Outlet Pressure Range (Select One)
<input type="checkbox"/> 4 to 6 in. w.c. / 10 to 15 mbar, Orange***
<input type="checkbox"/> 6 to 8 in. w.c. / 15 to 20 mbar, Yellow***
<input type="checkbox"/> 8 to 10 in. w.c. / 20 to 25 mbar, Black***
<input type="checkbox"/> 10 to 12.5 in. w.c. / 25 to 31 mbar, Silver***
<input type="checkbox"/> 12.5 to 20 in. w.c. / 31 to 50 mbar, Gray***
<input type="checkbox"/> 20 to 35 in. w.c. / 50 to 87 mbar, Pink***
<input type="checkbox"/> 1.25 to 2.2 psig / 0.09 to 0.15 bar, Light Blue***

Orifice Size (Select One)
<input type="checkbox"/> 1/8 in. / 3.2 mm***
<input type="checkbox"/> 3/16 in. / 4.8 mm***
<input type="checkbox"/> 1/4 in. / 6.4 mm***
<input type="checkbox"/> 3/8 in. / 9.5 mm***
<input type="checkbox"/> 1/2 in. / 13 mm***

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Body Orientation (Select One)	
Globe	Angle
<input type="checkbox"/> Position 1***	<input type="checkbox"/> Position 1***
<input type="checkbox"/> Position 2***	<input type="checkbox"/> Position 2***
<input type="checkbox"/> Position 3 (standard)***	<input type="checkbox"/> Position 3 (standard)***
<input type="checkbox"/> Position 4***	<input type="checkbox"/> Position 4***

Vent Size (Select One)
<input type="checkbox"/> 3/4 NPT***
<input type="checkbox"/> 1 NPT***

Vent Orientation (Select One)	
Globe	Angle
<input type="checkbox"/> Position C***	<input type="checkbox"/> Position C***
<input type="checkbox"/> Position D***	<input type="checkbox"/> Position D***
<input type="checkbox"/> Position E***	<input type="checkbox"/> Position E (standard)***
<input type="checkbox"/> Position F (standard)***	<input type="checkbox"/> Position F***

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure (P <sub>1max</sub> ):
Minimum Inlet Pressure (P <sub>1min</sub> ):
Downstream Pressure Setting(s) (P <sub>2</sub> ):
Maximum Flow (Q <sub>max</sub> ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Do not oversize regulators. Pick the smallest orifice size or regulator that will work. Keep in mind when sizing a station that most restricted trims that do not reduce the main port size do not help with improved low flow control.

# M Series

## Pressure Regulator

TARTARINI™

### Introduction

The M Series spring-loaded regulators are ideal for applications requiring sudden changes in capacity or where gas shutoff is solenoid-controlled as with domestic or industrial burners. These regulators can be used with natural, manufactured, propane, other gases and air so long as they are filtered and do not contain high percentages of benzol.

### Available Configurations

See Table 1

### Body Sizes and End Connection Styles

See Table 2

### Flow Capacities

See Tables 5 through 40

### MN and MF Series

#### Allowable Pressure:

Body: Up to 290 psig / Up to 20.0 bar

Actuator: 58 psig / 4.0 bar

#### Highest Operating Pressure:

43.5 psig / 3.0 bar

#### Permissible Inlet Pressure:

Standard Version NPS 1 through 2 /

DN 25 through 50: 145 psig / 10.0 bar

Standard Version NPS 2-1/2 through 4 /

DN 65 through 100: 72.5 psig / 5.0 bar

PST, AP and APA Versions: 284 psig / 19.6 bar<sup>(1)</sup>

#### Set Range:

Standard Version: 0.15 to 7.25 psig /  
10 to 500 mbar<sup>(2)</sup>

PST Version: 3.63 to 7.25 psig /  
0.25 to 0.5 bar

AP Version: 7.25 to 14.5 psig /  
0.50 to 1.00 bar

APA Version: 14.5 to 43.5 psig /  
1.00 to 3.0 bar

### Accuracy Class

Up to ±5%

### Lockup Pressure Class

Up to 10%

### Class of Lockup Pressure Zone

Up to 10%

### Shut-off Device Independent Pneumatic Control

Accuracy Class: ±5%

Response Time: ≤ 1 second

### Temperature Capabilities

#### Standard Version:

Working: 14 to 140°F / -10 to 60°C

#### Low Temperature Version:

Working: -4 to 140°F / -20 to 60°C

### Options

Built-in Type SR Silencer

1. At average ambient temperature.

2. For DN 80 and 100 the operating outlet set pressure range 0.01 to 0.08 bar is allowable with M...-BP version.




Figure 1. MN Series Regulator



Figure 2. MF Series Regulator






Figure 3. MF Series Cross-Sectional View



■ INLET PRESSURE  
■ OUTLET PRESSURE  
■ ATMOSPHERIC PRESSURE

Figure 4. MBF-M Series Operational Schematic



■ OUTLET PRESSURE  
■ ATMOSPHERIC PRESSURE

Figure 5. Type OS/66 Shut-off Device Operational Schematic

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Counterbalanced Valve
- Overpressure and Underpressure Slam-Shut Valve
- Full Seal at Zero Flow
- Ease of Maintenance
- Fail Open Regulator
- Wide Pressure Regulation Range



Table 1. Available Configuration

CONFIGURATION	TYPE							
	MN				MF			
	Standard	AP	APA	PST	Standard	AP	APA	PST
Regulator	MN	MN-AP	MN-APA	MN-PST	MF	MF-AP	MF-APA	MF-PST
Regulator with Shut-off	MBN	MBN-AP	MBN-APA	MBN-PST	MBF	MBF-AP	MBF-APA	MBF-PST
Monitor with Shut-off	MBN-M	MBN-M-AP	MBN-M-APA	MBN-M-PST	MBF-M	MBF-M-AP	MBF-M-APA	MBF-M-PST

Table 2. Body Size and End Connection Style

SERIES	BODY SIZE		END CONNECTION
	NPS	DN	
MN	1 X 2-1/2	25 X 65	PN 16, CL150 RF
	1-1/2 X 3	40 X 80	
	2 X 4	50 X 100	
	2-1/2 X 4	65 X 100	
	3 X 6	80 X 150	
	4 X 8	100 X 200	
MF	1	25	
	1-1/2	40	
	2	50	
	3	80	
	4	100	

Table 3. Construction Material

BODY	FLANGE AND COVER	DIAPHRAGM	PAD
Steel	Steel	Fabric Nitrile (NBR) and Polyvinyl Chloride (PVC)/Nitrile (NBR)	Nitrile (NBR)

Table 4. Set Range of Safety Shut-Off Device Pilot

TYPE	SERVOMOTOR BODY RESISTANCE		OVERPRESSURE SET RANGE				UNDERPRESSURE SET RANGE			
			Minimum		Maximum		Minimum		Maximum	
	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
OS/66	87	6.0	0.3	0.02	8.7	0.60	0.10	7 mbar	6.53	0.45
OS/66-AP			2.9	0.20	73	5.0	1.45	0.10	36	2.5

Table 5. MN Series Capacities for NPS 1 / DN 25 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																					
		Inlet Pressure, psig / bar																					
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0					
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h				
0.29	0.02	2119	60.0	6003	170	8829	250	10,947	310	14,126	400	21,189	600	33,549	950	33,549	950	----					
0.73	0.05	----	----	5650	160	8475	240	10,594	300					14,126	400	21,189	600	37,080	1050	42,377	1200	42,377	1200
1.45	0.10			4944	140	8122	230											5650	160	9182	260	13,420	380
3.63	0.25			7.25	0.50	----	----	----	----					5650	160	12,360	350	21,189	600	49,440	1400	49,440	1400

----- Capacities for PST version.

Table 6. MN Series Capacities for NPS 1 / DN 25 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.00		72.5 / 5.00		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	5650	160	12,360	350	21,189	600	37,080	1050	49,440	1400	49,440	1400		
8.70	0.60	----	----	11,301	320					52,972	1500	52,972	1500		
10.2	0.70			10,241	290	20,836	590			56,503	1600	56,503	1600		
11.6	0.80			8829	250	20,482	580			60,035	1700	60,035	1700		
14.5	1.00	----	----	19,776	560	70,629	2000	67,098	1900						

**Table 7. MN Series Capacities for NPS 1 / DN 25 Body, APA Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	19,776	560	37,080	1050	70,629	2000	67,098	1900
21.8	1.5	15,892	450					77,692	2200
29.0	2.0	----		35,314	1000				
36.3	2.5								
43.5	3.0								

**Table 8. MN Series Capacities for NPS 1-1/2 / DN 40 Body, Standard Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	5297	150	12,007	340	16,598	470	20,482	580	25,073	710	37,080	1050	63,566	1800	63,566	1800	----	
0.73	0.05	----		11,301	320	15,892	450	19,776	560					65,332	1850	65,332	1850		
1.45	0.10			9535	270	15,185	430	19,070	540	24,720	700	74,160	2100	74,160	2100	74,160	2100		
3.63	0.25			----		12,360	350	18,010	510	22,601	640	35,314	1000	88,286	2500	88,286	2500		
7.25	0.50	----				----		11,301	320	22,601	640	35,314	1000	88,286	2500	88,286	2500		

----- Capacities for PST version.

**Table 9. MN Series Capacities for NPS 1-1/2 / DN 40 Body, AP Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
		Inlet Pressure, psig / bar											
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
7.25	0.50	11,301	320	22,601	640	35,314	1000	74,160	2100	88,286	2500	88,286	2500
8.70	0.60	----		21,189	600					91,818	2600	91,818	2600
10.2	0.70			19,423	550	98,881	2800	98,881	2800				
11.6	0.80			16,245	460	34,608	980	102,412	2900	102,412	2900		
14.5	1.00	----		----		33,549	950	109,475	3100	109,475	3100		

**Table 10. MN Series Capacities for NPS 1-1/2 / DN 40 Body, APA Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	33,549	950	74,160	2100	109,475	3100	109,475	3100
21.8	1.5	29,664	840					127,132	3600
29.0	2.0	----		72,395	2050	137,726	3900	148,321	4200
36.3	2.5			63,566	1800				
43.5	3.0								

**Table 11. MN Series Capacities for NPS 2 / DN 50 Body, Standard Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	7063	200	16,951	480	23,308	660	28,252	800	35,314	1000	51,206	1450	91,818	2600	91,818	2600	----	
0.73	0.05	----		15,892	450	22,954	650	27,898	790					93,583	2650	93,583	2650		
1.45	0.10			13,773	390	22,248	630	27,545	780	97,115	2750	97,115	2750						
3.63	0.25			----		17,304	490	25,426	720	100,646	2850	109,475	3100	109,475	3100				
7.25	0.50	----				----		15,892	450	32,842	930	141,258	4000	141,258	4000				

----- Capacities for PST version.

Table 12. MN Series Capacities for NPS 2 / DN 50 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
		Inlet Pressure, psig / bar											
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
7.25	0.50	15,892	450	32,842	930	51,206	1450	100,646	2850	141,258	4000	141,258	4000
8.70	0.60	----	----	31,077	880					148,321	4200	148,321	4200
10.2	0.70			28,252	800					162,447	4600	162,447	4600
11.6	0.80			24,014	680					173,041	4900	173,041	4900
14.5	1.00			----	----					49,440	1400	190,698	5400

Table 13. MN Series Capacities for NPS 2 / DN 50 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	49,440	1400	100,646	2850	190,698	5400	187,167	5300
21.8	1.5	42,377	1200					208,355	5900
29.0	2.0	----	----					208,355	5900
36.3	2.5								
43.5	3.0								

Table 14. MN Series Capacities for NPS 2-1/2 / DN 65 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	10,594	300	25,426	720	35,314	1000	44,143	1250	56,503	1600	84,755	2400	155,384	4400	----	----		
0.73	0.05	----	----	23,661	670									158,915	4500				
1.45	0.10			19,776	560	33,902	960	167,744	4750										
3.63	0.25			----	----	28,252	800	40,612	1150	173,041	4900	190,698	5400	190,698	5400				
7.25	0.50			----	----	----	----	25,780	730	52,972	1500	229,544	6500	229,544	6500				

▒ - Capacities for PST version.

Table 15. MN Series Capacities for NPS 2-1/2 / DN 65 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
		Inlet Pressure, psig / bar											
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
7.25	0.50	25,780	730	52,972	1500	84,755	2400	173,041	4900	229,544	6500	229,544	6500
8.70	0.60	----	----	49,440	1400					243,670	6900	243,670	6900
10.2	0.70			45,909	1300					261,327	7400	261,327	7400
11.6	0.80			38,846	1100					275,453	7800	275,453	7800
14.5	1.00			----	----					82,989	2350	307,236	8700

Table 16. MN Series Capacities for NPS 2-1/2 / DN 65 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	82,989	2350	173,041	4900	307,236	8700	307,236	8700
21.8	1.5	70,629	2000			339,019	9600		
29.0	2.0	----	----			314,299	8900		
36.3	2.5								
43.5	3.0							169,509	4800

**Table 17. MN Series Capacities for NPS 3 / DN 80 Body, Standard Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	16,598	470	38,846	1100	52,972	1500	63,566	1800	81,223	2300	120,069	3400	243,670	6900	---	---	---	---
0.73	0.05	---	---	35,314	1000	---	---	---	---	---	---	---	---	---	---	---	---	---	---
1.45	0.10	---	---	31,077	880	51,206	1450	---	---	---	---	---	---	---	---	---	---	---	---
3.63	0.25	---	---	---	---	40,612	1150	58,269	1650	---	---	---	---	---	---	423,774	12,000	423,774	12,000
7.25	0.50	---	---	---	---	---	---	35,314	1000	75,926	2150	---	---	---	---	444,962	12,600	487,340	13,800

--- Capacities for PST version.

**Table 18. MN Series Capacities for NPS 3 / DN 80 Body, AP Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.00		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	35,314	1000	75,926	2150	---	---	---	---	---	---	---	---		
8.70	0.60	---	---	70,629	2000	---	---	---	---	---	---	---	---		
10.2	0.70	---	---	65,332	1850	120,069	3400	243,670	6900	444,962	12,600	487,340	13,800		
11.6	0.80	---	---	52,972	1500	---	---	---	---	---	---	---	---		
14.5	1.00	---	---	---	---	---	---	---	---	---	---	---	---		

**Table 19. MN Series Capacities for NPS 3 / DN 80 Body, APA Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
		Inlet Pressure, psig / bar									
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
14.5	1.00	120,069	3400	---	---	---	---	---	---		
21.8	1.5	100,646	2850	243,670	6900	444,962	12,600	487,340	13,800		
29.0	2.0	---	---	---	---	---	---	---	---		
36.3	2.5	---	---	---	---	---	---	---	---		
43.5	3.0	---	---	240,138	6800	---	---	---	---		

**Table 20. MN Series Capacities for NPS 4 / DN 100 Body, Standard Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.9 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	25,780	730	60,035	1700	82,989	2350	98,881	2800	125,366	3550	---	---	---	---	---	---	---	---
0.73	0.05	---	---	56,503	1600	81,223	2300	---	---	---	---	---	---	---	---	---	---	---	---
1.45	0.10	---	---	47,675	1350	77,692	2200	97,115	2750	---	---	187,167	5300	370,802	10,500	---	---	---	---
3.63	0.25	---	---	---	---	61,800	1750	90,052	2550	123,601	3500	---	---	---	---	678,038	19,200	741,604	21,000
7.25	0.50	---	---	---	---	---	---	56,503	1600	116,538	3300	---	---	---	---	---	---	---	---

--- Capacities for PST version.

**Table 21. MN Series Capacities for NPS 4 / DN 100 Body, AP Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	56,503	1600	116,538	3300	---	---	---	---	---	---	---	---		
8.70	0.60	---	---	109,475	3100	---	---	---	---	---	---	---	---		
10.2	0.70	---	---	100,646	2850	187,167	5300	370,802	10,500	678,038	19,200	741,604	21,000		
11.6	0.80	---	---	84,755	2400	---	---	---	---	---	---	---	---		
14.5	1.00	---	---	---	---	183,635	5200	---	---	---	---	---	---		

Table 22. MN Series Capacities for NPS 4 / DN 100 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	183,635	5200	370,802	10,500	678,038	19,200	741,604	21,000
21.8	1.5	155,384	4400						
29.0	2.0	----							
36.3	2.5	----							
43.5	3.0	----		----		----		----	

Table 23. MF Series Capacities for NPS 1 / DN 25 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																				
		Inlet Pressure, psig / bar																				
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0				
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h			
0.29	0.02	2119	60	6003	170	8829	250	9888	280	9888	280	9888	280	9888	280	9888	280	----	----	----		
0.73	0.05	----		5650	160	8475	240	10,241	290	10,241	290	10,241	290	10,241	290	10,241	290					
1.45	0.10	----		4944	140	8122	230	10,594	300	10,594	300	10,594	300	10,594	300	10,594	300					
3.63	0.25	----		----		5650	160	9182	260	12,007	340	12,007	340	12,007	340	12,007	340				12,007	340
7.25	0.50	----		----		----		5650	160	12,360	350	14,126	400	14,126	400	14,126	400				14,126	400

----- - Capacities for PST version.

Table 24. MF Series Capacities for NPS 1 / DN 25 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
7.25	0.50	5650	160	12,360	350	14,126	400	14,126	400	14,126	400	14,126	400	14,126	400
8.70	0.60	----		11,301	320	15,538	440	15,538	440	15,538	440	15,538	440	15,538	440
10.2	0.70	----		10,241	290	15,185	430	15,185	430	15,185	430	15,185	430	15,185	430
11.6	0.80	----		8829	250	17,657	500	17,657	500	17,657	500	17,657	500	17,657	500
14.5	1.00	----		----		19,776	560	19,776	560	19,776	560	19,776	560	19,776	560

Table 25. MF Series Capacities for NPS 1 / DN 25 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	19,070	540	22,601	640	22,601	640	22,601	640
21.8	1.5	15,892	450	24,014	680	24,014	680	24,014	680
29.0	2.0	----		28,252	800	28,252	800	28,252	800
36.3	2.5	----		33,549	950	33,549	950	33,549	950
43.5	3.0	----		35,314	1000	35,314	1000	35,314	1000

Table 26. MF Series Capacities for NPS 1-1/2 / DN 40 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	5297	150	12,007	340	16,598	470	20,482	580	25,073	710	25,073	710	25,073	710	25,073	710	----	----
0.73	0.05	----		11,301	320	15,892	450	19,776	560										
1.45	0.10	----		9535	270	15,185	430	19,070	540										
3.63	0.25	----		----		12,360	350	18,010	510			24,720	700	30,724	870	30,724	870		
7.25	0.50	----		----		----		11,301	320	22,601	640	35,314	1000	35,314	1000	35,314	1000	35,314	1000

----- - Capacities for PST version.

**Table 27. MF Series Capacities for NPS 1-1/2 / DN 40 Body, AP Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	11,301	320	22,601	640	35,314	1000	35,314	1000	35,314	1000	35,314	1000		
8.70	0.60	-----	-----	21,189	600			38,846	1100	38,846	1100	38,846	1100	38,846	1100
10.2	0.70			19,423	550			42,377	1200	42,377	1200	42,377	1200	42,377	1200
11.6	0.80			16,245	460			34,608	980	45,909	1300	45,909	1300	45,909	1300
14.5	1.00	-----		-----		33,549	950	47,675	1350	47,675	1350	47,675	1350		

**Table 28. MF Series Capacities for NPS 1-1/2 / DN 40 Body, APA Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	33,549	950	47,675	1350	47,675	1350	47,675	1350
21.8	1.5	29,664	840	74,160	2100	63,566	1800	63,566	1800
29.0	2.0	-----	-----	72,395	2050	77,692	2200	77,692	2200
36.3	2.5			63,566	1800	84,755	2400	84,755	2400
43.5	3.0			98,881	2800	98,881	2800		

**Table 29. MF Series Capacities for NPS 2 / DN 50 Body, Standard Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	7063	200	16,951	480	23,308	660	28,252	800	35,314	1000	38,846	1100	38,846	1100	38,846	1100	-----	-----
0.73	0.05	-----	-----	15,892	450	22,954	650	27,898	790			42,377	1200	42,377	1200	42,377	1200		
1.45	0.10			13,773	390	22,248	630	27,545	780			47,675	1350	47,675	1350	47,675	1350		
3.63	0.25			17,304	490	25,426	720	47,675	1350			47,675	1350	47,675	1350	47,675	1350		
7.25	0.50	-----		-----		15,892	450	32,842	930	51,206	1450	56,503	1600	56,503	1600	56,503	1600		

----- Capacities for PST version.

**Table 30. MF Series Capacities for NPS 2 / DN 50 Body, AP Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS											
		Inlet Pressure, psig / bar											
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
7.25	0.50	15,892	450	32,842	930	51,206	1450	56,503	1600	56,503	1600	56,503	1600
8.70	0.60	-----	-----	31,077	880			60,035	1700	60,035	1700	60,035	1700
10.2	0.70			28,252	800			63,566	1800	63,566	1800	63,566	1800
11.6	0.80			24,014	680			67,098	1900	67,098	1900	67,098	1900
14.5	1.00	-----		-----		49,440	1400	75,926	2150	75,926	2150	75,926	2150

**Table 31. MF Series Capacities for NPS 2 / DN 50 Body, APA Version**

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	49,440	1400	75,926	2150	75,926	2150	75,926	2150
21.8	1.5	42,377	1200	95,349	2700	95,349	2700	95,349	2700
29.0	2.0	-----	-----	100,646	2850	113,006	3200	113,006	3200
36.3	2.5					134,195	3800	134,195	3800
43.5	3.0					151,852	4300	151,852	4300

Table 32. MF Series Capacities for NPS 3 / DN 80 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	16,598	470	38,846	1100	52,972	1500	63,566	1800	81,223	2300	98,881	2800	98,881	2800	----	----	----	----
0.73	0.05	----	----	35,314	1000							102,412	2900	102,412	2900				
1.45	0.10			31,077	880	51,206	1450	107,709	3050	107,709	3050								
3.63	0.25	----	----	40,612	1150	58,269	1650	75,926	2150	120,069	3400	123,601	3500	123,601	3500	123,601	3500	123,601	3500
7.25	0.50									146,555	4150	146,555	4150	146,555	4150	146,555	4150		

Capacities for PST version.

Table 33. MF Series Capacities for NPS 3 / DN 80 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	35,314	1000	75,926	2150	120,069	3400	146,555	4150	146,555	4150	146,555	4150		
8.70	0.60	----	----	70,629	2000			157,149	4450	157,149	4450	157,149	4450	157,149	4450
10.2	0.70			65,332	1850	165,978	4700	165,978	4700	165,978	4700				
11.6	0.80			52,972	1500	176,572	5000	176,572	5000	176,572	5000				
14.5	1.00	----	----	----	----	----	----	194,230	5500	194,230	5500	194,230	5500		
								194,230	5500	194,230	5500				

Table 34. MF Series Capacities for NPS 3 / DN 80 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS									
		Inlet Pressure, psig / bar									
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
14.5	1.00	120,069	3400	194,230	5500	194,230	5500	194,230	5500		
21.8	1.5	100,646	2850	243,670	6900	243,670	6900	243,670	6900		
29.0	2.0	----	----			293,110	8300	293,110	8300		
36.3	2.5			342,550	9700	342,550	9700				
43.5	3.0			240,138	6800	395,522	11,200	395,522	11,200		

Table 35. MF Series Capacities for NPS 4 / DN 100 Body, Standard Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS																	
		Inlet Pressure, psig / bar																	
		0.73 / 0.05		2.90 / 0.20		5.80 / 0.40		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	25,780	730	60,035	1700	82,989	2350	98,881	2800	125,366	3550	155,384	4400	155,384	4400	----	----	----	----
0.73	0.05	----	----	56,503	1600	81,223	2300	125,366	3550	158,915	4500	158,915	4500						
1.45	0.10			47,675	1350	77,692	2200			97,115	2750	169,509	4800	169,509	4800				
3.63	0.25	----	----	61,800	1750	90,052	2550	123,601	3500	187,167	5300	190,698	5400	190,698	5400	190,698	5400	190,698	5400
7.25	0.50											229,544	6500	229,544	6500	229,544	6500	229,544	6500

Capacities for PST version.


Table 36. MF Series Capacities for NPS 4 / DN 100 Body, AP Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
		Inlet Pressure, psig / bar													
		8.70 / 0.60		14.5 / 1.00		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0			
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h		
7.25	0.50	56,503	1600	116,538	3300	187,167	5300	229,544	6500	229,544	6500	229,544	6500		
8.70	0.60	----	----	109,475	3100			247,201	7000	247,201	7000	247,201	7000	247,201	7000
10.2	0.70			100,646	2850	261,327	7400	261,327	7400	261,327	7400				
11.6	0.80			84,755	2400	275,453	7800	275,453	7800	275,453	7800				
14.5	1.00	----	----	----	----	183,635	5200	307,236	8700	307,236	8700	307,236	8700		
								307,236	8700	307,236	8700				

# M Series


## Pressure Regulator

TARTARINI™



\*\* ONLY APPLICABLE FOR MODELS WITH INTERNAL IMPULSE CONNECTION:  
NPS 1, 1-1/2, 2 AND 2-1/2 /  
DN 25, 40, 50 AND 65

MN, MBN AND MBN-M SERIES



MF, MBF AND MBF-M SERIES

IN. /  
mm

Figure 6. Dimensions

Table 37. MF Series Capacities for NPS 4 / DN 100 Body, APA Version

OUTLET PRESSURE		CAPACITIES IN SCFH / Sm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
		29.0 / 2.0		72.5 / 5.0		145 / 10.0		160 to 276 / 11.0 to 19.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
14.5	1.00	183,635	5200	307,236	8700	307,236	8700	307,236	8700
21.8	1.5	155,384	4400	370,802	10,500	384,928	10,900	384,928	10,900
29.0	2.0	----				459,088	13,000	459,088	13,000
36.3	2.5	----				540,311	15,300	540,311	15,300
43.5	3.0	----				618,003	17,500	618,003	17,500

Table 38. Overall Dimension and Approximate Shipping Weight

BODY SIZE		DIMENSION												APPROXIMATE SHIPPING WEIGHT					
		i		A				H	H1	H2 Monitor Version									
				Standard or PST		AP APA													
		MN, MBN and MBN-M Series												MN Series		MBN Series		MBN-M Series	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lbs	kg	lbs	kg	lbs	kg
1 x 2-1/2	25 x 65	7.24	184	14.96	380	14.96	380	19.69	500	3.74	95	5.51	140	68.34	31	72.8	33	81.57	37
1-1/2 x 3	40 x 80	8.74	222	19.69	500	14.96	380	22.84	580	3.94	100	6.30	160	117	53	121	55	130	59
2 x 4	50 x 100	10	254	19.69	500	14.96	380	23.62	600	4.72	120	6.69	170	130	59	137	62	148	67
2-1/2 x 4	65 x 100	10.87	276	19.69	500	14.96	380	24.41	620	5.20	132	7.87	200	137	62	146	66	159	72
3 x 6	80 x 150	11.73	298	19.69	500	14.96	380	25.59	650	5.71	145	8.47	215	176	80	185	84	198	90
				24.41 <sup>(1)</sup>	620 <sup>(1)</sup>														
4 x 8	100 x 200	13.86	352	19.69	500	19.69	500	25.98	660	7.09	180	10.43	265	276	125	287	130	309	140
				24.41 <sup>(1)</sup>	620 <sup>(1)</sup>														
		MF, MBF and MBF-M Series												MF Series		MBF Series		MBF-M Series	
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lbs	kg	lbs	kg	lbs	kg
1	25	7.24	184	14.96	380	14.96	380	19.69	500	3.74	95	5.51	140	59.52	27	63.93	29	72.75	33
1-1/2	40	8.74	222	19.69	500	14.96	380	22.84	580	3.94	100	6.30	160	110	50	115	52	123	56
2	50	10	254	19.69	500	14.96	380	23.62	600	4.72	120	7.09	180	121	55	130	59	141	64
3	80	11.73	298	19.69	500	14.96	380	25.59	650	5.71	145	8.47	215	161	73	170	77	183	83
				24.41 <sup>(1)</sup>	620 <sup>(1)</sup>														
4	100	13.86	352	19.69	500	19.69	500	25.98	660	7.09	180	10.43	265	243	110	254	115	276	125
				24.41 <sup>(1)</sup>	620 <sup>(1)</sup>														

1. For outlet pressure from 8 to 32 in. w.c. / 20 to 80 mbar only.



# Ordering Guide

Body Sizes and End Connection Styles (Select One)	
<b>MN Series Widened Outlet Flanges Configuration</b>	
<input type="checkbox"/>	NPS 1 x 2-1/2 / DN 25 x 65***
<input type="checkbox"/>	NPS 1-1/2 x 3 / DN 40 x 80***
<input type="checkbox"/>	NPS 2 x 4 / DN 50 x 100***
<input type="checkbox"/>	NPS 2-1/2 x 4 / DN 65 x 100***
<input type="checkbox"/>	NPS 3 x 6 / DN 80 x 150***
<input type="checkbox"/>	NPS 4 x 8 / DN 100 x 200***
<b>MF Series Same Inlet/Outlet Flanges Configuration</b>	
<input type="checkbox"/>	NPS 1 / DN 25***
<input type="checkbox"/>	NPS 1-1/2 / DN 40***
<input type="checkbox"/>	NPS 2 / DN 50***
<input type="checkbox"/>	NPS 3 / DN 80***
<input type="checkbox"/>	NPS 4 / DN 100***
End Connection Style (Select One)	
<input type="checkbox"/>	PN 16
<input type="checkbox"/>	CL150 RF
Elastomer Part (Select One)	
<input type="checkbox"/>	Nitrile (NBR)***
Working Temperature Range (Select One)	
<input type="checkbox"/>	Standard Version: 14 to 140°F / -10 to 60°C***
<input type="checkbox"/>	Low Temperature Version: -4 to 140°F / -20 to 60°C**
Built-In Monitor (Optional)	
<input type="checkbox"/>	Yes

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Built-In Shut-off Device (Optional)	
<input type="checkbox"/>	Type OS/66
Built-In Type SR Silencer - For Clean Gas Only (Optional)	
<input type="checkbox"/>	Yes
Setpoint (Fill in - see Table 4)	
Regulator Outlet Pressure: _____	
Built-in Monitor Outlet Pressure: _____	
Built-in Safety Shut-off Device Minimum Pressure: _____	
Built-in Safety Shut-off Device Maximum Pressure: _____	
PED Certificate (Mandatory Only for CE Market)	
<input type="checkbox"/>	Yes**
Installation (Select One)	
<b>Horizontal Flow</b>	<input type="checkbox"/> Left to Right <input type="checkbox"/> Right to Left
Replacement Parts Kit (Optional)	
<input type="checkbox"/>	Yes, please send one parts kit to match this order.

Specification Worksheet	
<b>Application</b>	
Specific Use:	
Line Size:	
Gas Type and Specific Gravity:	
Gas Temperature:	
Does the application require overpressure protection?	
<input type="checkbox"/>	Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/>	Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?	
<b>Pressure</b>	
Maximum Inlet Pressure (P <sub>1max</sub> ):	
Minimum Inlet Pressure (P <sub>1min</sub> ):	
Downstream Pressure Setting(s) (P <sub>2</sub> ):	
Maximum Flow (Q <sub>max</sub> ):	
<b>Performance Required</b>	
Accuracy requirements?	
Need for extremely fast response?	
<b>Other Requirements:</b>	

**Regulator Tip:**  
Make control line connections in a straight run of pipe about 10 pipe diameters downstream of any area of turbulence, such as elbows, pipe swages or block valves.

# MIC Series, MI/150 and MIR/65

## Standard Underground Module

TARTARINI™

### Introduction

The Underground Module was designed in order to avoid environmental impact due to both traditional cabinet installations and masonry structures.

With this solution, it is possible to reduce the noise pollution and environmental impact and to obtain protection against impacts and damages due to vandalism or accidental acts.

The module is made up of two main parts:

- The metal underground container
- The gas control unit

The metal container is not pressurized and is provided with connections suitable to be welded directly to the inlet and outlet piping.

The gas control unit is completely placed inside the metal container and consists of a regulating line complete with by-pass assembled with standard version equipment. The gas control unit is easily accessible for maintenance or replacement purposes.

### Permissible Inlet Pressure

**Type MI/150:** 276 psig / 19.0 bar

**MIC Series:** 87 psig / 6.0 bar

**Type MIR/65:** 87 psig / 6.0 bar

### Design Temperature

**Type MI/150, MIC Series and**

**Type MIR/65:** 14 to 140°F / -10 to 60°C

### Minimum Operating Differential Pressure

**Type MI/150, MIC Series and**

**Type MIR/65:** 4.35 psid / 0.30 bar d

### Features

- Only Ventilation Ducts Installed Above-Ground
- Environmental Impact Reduction
- Noise Pollution Reduction
- Protection Against Impacts and Damages
- Reduced Administrative Installation Procedures

### Accuracy Class

**Type MI/150, MIC Series and Type MIR/65:** Up to 2.5%

### Lockup Pressure Class

**Type MI/150, MIC Series and Type MIR/65:** Up to 10%

### Available Models

In order to offer a very versatile product, we have designed three series of underground modules available in different models according to the flow rate required:

**Type MI/150:** The Type MI/150 employs pilot operated pressure regulators Type FL-BP in monitor and regulator configuration, and slam shut valve Type BM5/.

Inlet and outlet valves together with the regulating line system by-pass and the relief valve are placed inside the container.

**MIC Series:** This series is composed of Types MIC/25, MIC/50 and MIC/80, employs pilot-operated pressure regulators and Cronos Series with regulator monitor and slam-shut functions.

Inlet and outlet valves, together with the regulating line system by-pass and the relief valve, are placed inside the container.

**Type MIR/65:** The Type MIR/65 employs spring loaded pressure regulators Type MBN/ and slam shut valve Type BM5/.

Inlet and outlet valves together with the relief valve are placed inside the container.




Figure 1. MI/150



Figure 2. MIC Series




Figure 3. MIR Series

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15




Figure 4. Type MI/150 Overall Dimensions

Table 1. Type MI/150 Construction Feature

PART NAME	TYPE MI/150
Inlet Pipe	NPS 10 / DN 250
Inlet Valve	NPS 10 / DN 250
Filter Cartridge	G 5
Slam-Shut Valve	Type BM5/ NPS 6 / DN 150
Monitor Regulator	Type -FL-BP/ NPS 6 / DN 150
Outlet Valve	NPS 12 / DN 300
Outlet Pipe	NPS 12 / DN 300
By-Pass	NPS 6 / DN 150
Relief Valve	1 in.

Table 2. Type MI/150 Flow Rate



OUTLET PRESSURE		FLOW RATE					
		Inlet Pressure, psig / bar					
		Type MI/150					
				7.25 / 0.50		21.8 / 1.5	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	233,046	6600	233,046	6600	233,046	6600
2.18	0.15	247,170	7000	261,294	7400	261,294	7400
14.5	1.00	----	----	391,941	11,100	459,030	13,000
43.5	3.0	----	----	----	----	617,925	17,500

Note: For different flow rate please contact your local Sales Office.



# MIC Series, MI/150 and MIR/65

Standard Underground Module



TARTARINI



TYPE MIC/25



TYPE MIC/50



TYPE MIC/80

IN. /  
mm

Figure 5. MIC Series Overall Dimensions

**Table 3. MIC Series Construction Feature**

PART NAME	TYPE MIC/25	TYPE MIC/50	TYPE MIC/80
Inlet Pipe	NPS 2 / DN 50	NPS 4 / DN 100	NPS 6 / DN 150
Inlet Valve	NPS 2 / DN 50	NPS 4 / DN 100	NPS 6 / DN 150
Filter Cartridge	G 1	G 2	G 3
Monitor Regulator and Slam-Shut	Type Cronos CCB/ NPS 1 / DN 25	Type Cronos CCB/ NPS 2 / DN 50	Type Cronos CCB/ NPS 3 / DN 80
Outlet Valve	NPS 3 / DN 80	NPS 6 / DN 150	NPS 10 / DN 250
Outlet Pipe	NPS 3 / DN 80	NPS 6 / DN 150	NPS 10 / DN 250
By-Pass <sup>(1)</sup>	NPS 1 / DN 25	NPS 2 / DN 50	NPS 3 / DN 80
Relief Valve	1 in.	1 in.	1 in.

1. Second reducing line available upon request.

**Table 4. MIC Series Flow Rate**

OUTLET PRESSURE		FLOW RATE																	
		Inlet Pressure, psig / bar																	
		Type MIC/25						Type MIC/50						Type MIC/80					
		7.25 / 0.5		21.8 / 1.5		72.5 / 5.0		7.25 / 0.5		21.8 / 1.5		72.5 / 5.0		7.25 / 0.5		21.8 / 1.5		72.5 / 5.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	12,184	345	13,773	390	13,773	390	45,909	1300	45,909	1300	45,909	1300	102,412	2900	132,429	3750	132,429	3750
2.18	0.15	11,301	320	14,656	415	14,656	415	45,909	1300	50,500	1430	50,500	1430	102,412	2900	139,845	3960	139,845	3960
14.5	1.00	----	----	15,892	450	24,720	700	----	----	60,035	1700	91,818	2600	----	----	144,790	4100	206,590	5850
43.5	3.0	----	----	----	----	24,720	700	----	----	----	----	97,115	2750	----	----	----	----	264,859	7500

Note: For different flow rate please contact your local Sales Office.

**Table 5. Type MIR/65 Construction Feature**

PART NAME	TYPE MIR/65
Inlet Pipe	NPS 5 / DN 125
Inlet Valve	NPS 5 / DN 125
Filter Cartridge	G 2.5
Slam-Shut Valve	Type BM5/NPS 2-1/2 / DN 65
Regulator	Type MBN/NPS 2-1/2 x 4 / DN 65 x 100
Outlet Valve	NPS 6 / DN 150
Outlet Pipe	NPS 6 / DN 150
Relief Valve	1 in.

**Table 6. Type MIR/65 Flow Rate**

OUTLET PRESSURE		FLOW RATE					
		Inlet Pressure, psig / bar					
		Type MIR/65					
		7.25 / 0.50		21.8 / 1.5		72.5 / 5.0	
psig	bar	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h	SCFH	Sm <sup>3</sup> /h
0.29	0.02	49,440	1400	56,503	1600	56,503	1600
2.18	0.15	45,909	1300	60,035	1700	60,035	1700
14.5	1.00	----	----	70,629	2000	113,006	3200
43.5	3.0	----	----	----	----	141,258	4000

Note: For different flow rate please contact your local Sales Office.

# MIC Series, MI/150 and MIR/65

Standard Underground Module

TARTARINI




Figure 6. Type MIR/65 Overall Dimensions

## Ordering Guide

### Available Models

- MIC/25\*\*\*
- MIC/50\*\*\*
- MIC/80\*\*\*
- MIR/65\*\*\*
- MI/150\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

If you don't see what you're looking for in this Application Guide. . . ask us about it. Space in this Application Guide does not always permit us to list all of the options or products available to you. If you don't see the product you're looking for, just pick up the phone and ask your local Sales Office to help you find the item you need. To locate your local Sales Office, log on to Emerson.com/ContactUs.

### Introduction

Absorption-type odorizing systems are employed in small and middle-sized stations with flow rates up to 3,531,000 SCFH / 100,000 Sm<sup>3</sup>/h. However, they are used as stand-by and emergency systems in all injection-type odorizing installations. For the proper operation, it is necessary to reach a differential pressure, preferably by means of a Type VFA-MRO (refer to VFA Series pages) valve.

### Type

- OL-25:** Volume: 6.60 gallons / 25 liters
- OL-50:** Volume: 13.2 gallons / 50 liters
- OL-100:** Volume: 26.4 gallons / 100 liters
- OL-150:** Volume: 39.6 gallons / 150 liters
- OL-250:** Volume: 66.0 gallons / 250 liters
- OL-300:** Volume: 79.3 gallons / 300 liters
- OL-1000:** Volume: 264 gallons / 1000 liters

### Flanged Connections

- PN 6, PN 16 - CL150 (BP Version)
- CL600 (AP Version)

### Maximum Allowable Pressure

Up to 1305 psig / 90.0 bar

### Allowable Temperature

**Minimum:** -4°F / -20°C  
**Maximum:** 140°F / 60°C

### Configurations

#### Tank and Valves:

- Carbon steel
- Stainless steel

#### Level Indicator:

- Vertical
- Diagonal
- Magnetic for Remote Control



Figure 1. OL Series Absorption Odorizing System

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

### Features

- Direct Reading Level Gauge
- Regulating, Shutoff and Filling Valves

## Ordering Guide

Type (Select One)	
<input type="checkbox"/>	OL-25***
<input type="checkbox"/>	OL-50***
<input type="checkbox"/>	OL-100***
<input type="checkbox"/>	OL-150***
<input type="checkbox"/>	OL-250***
<input type="checkbox"/>	OL-300***
<input type="checkbox"/>	OL-1000***

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to: [Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Flange Rating (Select One)	
<input type="checkbox"/>	PN 6***
<input type="checkbox"/>	PN 16***
<input type="checkbox"/>	CL150***
<input type="checkbox"/>	CL600***

Elastomer Part (Select One)	
<input type="checkbox"/>	Nitrile (NBR)***
<input type="checkbox"/>	Fluorocarbon (FKM)**

Material (Select One)	
<input type="checkbox"/>	Carbon steel***
<input type="checkbox"/>	Stainless steel***

Option (Select One)	
<input type="checkbox"/>	Vertical level indicator***
<input type="checkbox"/>	Diagonal level indicator**
<input type="checkbox"/>	Magnetic level indicator for Remote Control

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

# Type OSE

## Slam-Shut Valve

FISHER™

### Introduction

The Type OSE slam-shut device is to totally and rapidly cut the flow of gas when the inlet and/or outlet pressure in the system either exceed or drop below setpoints. The Type OSE consists of a valve, water-tight mechanism box (Type BM1 or BM2) and either one or two modular sensing elements called manometric devices (Type BMS1 or BMS2).

A double stage mechanism detects any pressure variances. Detection is the first stage and the mechanism will only trip when the pipeline pressure reaches the set pressure. The second stage is the power stage; once tripped, the closing spring causes the valve plug to slam shut and remain closed until the valve is manually reset.

### Body Sizes and End Connection Styles

**WCC Steel:** 1 and 2 NPT; NPS 1, 2, 3, 4 and 6 / DN 25, 50, 80, 100 and 150; CL150 RF, CL300 RF or CL600 RF

**LCC Steel:** NPS 8 and 10 / DN 200 and 250; CL150 RF, CL300 RF or CL600 RF

**Cast iron:** 1 and 2 NPT; NPS 1, 2, 3, 4 and 6 / DN 25, 50, 80, 100 and 150; CL125 FF

### Flow and IEC Sizing Coefficients

See Table 1

### Maximum Flow Pressure Differential<sup>(1)</sup>

See Table 3

### Flow Capacities

See Table 4

### Maximum Inlet Pressure<sup>(1)</sup>

**NPT Cast iron:** 400 psig / 27.6 bar

125 FF Cast iron: 200 psig / 23.8 bar

150 RF Steel: 290 psig / 20 bar

300 RF Steel: 750 psi / 51.7 bar

600 RF and NPT Steel: 1470 psi / 101 bar

### Maximum Set Pressure

1470 psig / 101 bar or maximum body rating, whichever is lower

### Set Pressure Ranges

See Table 5

### Vent Connection

1/4 NPT

### Pressure Registration

External

### Temperature Capabilities<sup>(1)</sup>

-20 to 180°F / -29 to 82°C

### Approximate Shipping Weights

See Table 8

\* Approximate weights

### Options

- Explosion-proof limit switch for Remote Alarm
- Manual Push Button Trigger Switch<sup>(2)</sup>
- Additional manometric device for extra pressure sensing

### Features

- Positive Shutoff
- Overpressure and Underpressure Protection
- High Shock and Vibration Resistance
- Internal Bypass Valve for NPS 1 through 6 / DN 25 through 150 and External for NPS 8 and 10 / DN 200 and 250 Body Sizes
- High Accuracy
- Water Tight
- Easy In-Line Maintenance
- Remote Alarm Capability
- Remote Shutoff Capability



Figure 1. Type OSE Slam-Shut Valve

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

06/19




Figure 2. Type OSE Slam-Shut Valve Operational Schematic

1. The pressure/temperature limits in this datasheet or any applicable standard limitation should not be exceeded.  
2. The push button connects at the same BM2 port as a Type BMS2 would.



Table 1. Flow and IEC Sizing Coefficient

BODY SIZE		PORT DIAMETER		FLOW COEFFICIENT			BYPASS FLOW COEFFICIENT		IEC SIZING COEFFICIENT		
NPS	DN	In.	mm	C <sub>g</sub>	C <sub>v</sub>	C <sub>i</sub>	C <sub>g</sub>	C <sub>i</sub>	X <sub>r</sub>	F <sub>D</sub>	F <sub>L</sub>
1	25	1.18	30	505	14.4	35	25.7	35	0.775	1.0	0.89
2	50	2.00	51	2210	60.6	35			0.775	1.0	0.89
3	80	3.15	80	4670	141	33			0.689	1.0	0.89
4	100	3.94	100	7860	244	32			0.648	1.0	0.89
6	150	5.91	150	14,850	454	33			0.648	1.0	0.89
8	200	7.87	200	28,830	833	34.6	133	32.8	0.580	1.0	0.89
10	250	9.84	250	42,180	1188	35.5			0.797	1.0	0.89

Table 2. Construction Material

BODY	BONNET	VALVE PLUG AND SEAT RING	O-RING AND DIAPHRAGM	BELLOW AND PISTON	MECHANISM BOX
WCC Steel or Cast Iron	Steel	Stainless steel	Nitrile (NBR)	316 Stainless steel	Aluminum

Table 3. Maximum Flowing Pressure Differential

BODY SIZE		MAXIMUM FLOWING PRESSURE DIFFERENCE	
NPS	DN	psi	bar
1	25	360	24.8
2	50	360	24.8
3	80	360	24.8
4	100	150	10.3
6	150	85	5.9
8	200	119	8.2
10	250	67	4.6

Table 4. Capacities

INLET PRESSURE		PRESSURE DROP		CAPACITIES IN THOUSANDS OF SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
psig	bar	psi	bar	Body Size													
				NPS 1 / DN 25		NPS 2 / DN 50		NPS 3 / DN 80		NPS 4 / DN 100		NPS 6 / DN 150		NPS 8 / DN 200		NPS 10 / DN 250	
				SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
5	0.34	1	0.07	4.8	0.1	21.1	0.6	47	1.3	81.5	2.2	150	4	278	7.4	396	10.6
				5.4	0.1	23.7	0.6	53	1.4	91.8	2.5	168	4.5	312	8.4	446	11.9
				8.9	0.2	38.8	1	86.9	2.3	151	4	276	7.4	512	13.7	730	19.6
				11.8	0.3	51.8	1.4	116	3.1	202	5.4	369	9.9	684	18.3	976	26.1
				16.2	0.4	71.1	1.9	159	4.3	276	7.4	506	13.6	938	25.1	1337	35.8
				19.7	0.5	86.1	2.3	193	5.2	335	9	614	16.4	1136	30.4	1620	43.4
				22.6	0.6	98.9	2.6	222	5.9	385	10.3	705	18.9	1305	35	1861	49.9
				25.2	0.7	110	3	247	6.6	429	11.5	785	21	1454	39	2074	55.5
				27.5	0.7	120	3.2	270	7.2	468	12.5	858	23	1589	42.6	2266	60.7
				31.7	0.8	139	3.7	311	8.3	539	14.5	988	26.5	1830	49	2610	69.9
35.4	0.9	155	4.1	347	9.3	602	16.1	1103	29.6	2043	54.7	2913	78				
10	0.69	5	0.34	11.1	0.3	46.6	1.2	103	2.8	173	4.6	344	9.2	644	17.2	923	24.7
				19.2	0.5	80.4	2.1	178	4.8	325	8.7	597	16.0	1111	29.8	1587	42.5
				26.0	0.7	109	2.9	240	6.4	441	11.8	810	21.7	1504	40.3	2147	57.5
				36.0	1.0	150	4.0	332	8.9	611	16.4	1121	30.0	2079	55.7	2966	79.5
				43.7	1.2	182	4.9	404	10.8	743	19.9	1365	36.6	2526	67.7	3603	96.6
				50.3	1.3	210	5.6	465	12.5	855	22.9	1567	42.0	2905	77.8	4144	111
				56.1	1.5	234	6.3	518	13.9	954	25.6	1748	46.8	3240	86.8	4621	124
				61.3	1.6	256	6.9	567	15.2	1040	27.9	1912	51.2	3544	95.0	5054	135
				70.7	1.9	295	7.9	654	17.5	1203	32.2	2204	59.1	4084	109	5824	156
				78.9	2.1	330	8.8	730	19.6	1343	36.0	2462	66.0	4560	122	6503	174
20	3.5	20	1.4	34.2	0.9	143	3.8	329	8.8	565	15.1	1047	28.1	1937	51.9	2834	75.9
				48.8	1.3	204	5.5	473	12.7	817	21.9	1506	40.4	2756	73.9	4032	108
				69.5	1.9	290	7.8	678	18.2	1173	31.4	2157	57.8	3922	105	5737	154
				85.4	2.3	357	9.6	835	22.4	1446	38.8	2655	71.2	4815	129	7045	189
				98.8	2.6	413	11.1	966	25.9	1675	44.9	3074	82.4	5568	149	8146	218
				121	3.2	506	13.6	1187	31.8	2058	55.2	3775	101	6830	183	9992	268
				140	3.7	585	15.7	1372	36.8	2380	63.8	4365	117	7892	212	11,547	309
				156	4.2	655	17.6	1536	41.2	2664	71.4	4884	131	8828	237	12,916	346

**Table 5. Set Pressure Range and Manometric Device Specification**

SPRING RANGE		SPRING COLOR	SPRING PART NUMBER	MANOMETRIC SENSING DEVICE TYPE	MANOMETRIC SENSING DEVICE STYLE	MAXIMUM SENSING INLET PRESSURE		RECOMMENDED SETPOINT DEADBAND <sup>(1)</sup>		MAXIMUM DIFFERENCE BETWEEN OVERPRESSURE AND UNDERPRESSURE <sup>(2)</sup>		SPRING WIRE DIAMETER		SPRING FREE LENGTH					
psig	bar					psig	bar	psig	bar	psig	bar	in.	mm	in.	mm				
4.0 to 14 in. w.c.	10 to 35 mbar	Purple	FA113195X12	162	Diaphragm	74	5.1	1.6 in. w.c.	4 mbar	4.0 in. w.c.	10 mbar	0.08	2.03	2.36	59.9				
10 to 33 in. w.c.	25 to 83 mbar	Orange	FA113196X12					2.0 in. w.c.	5 mbar	10 in. w.c.	25 mbar	0.105	2.67	2.36	59.9				
18 in. w.c. to 2.0 psig	45 mbar to 0.14 bar	Red	FA113197X12					4.0 in. w.c.	10 mbar	20 in. w.c.	50 mbar	0.12	3.05	2.36	59.9				
1.0 to 3.5	70 mbar to 0.24 bar	Yellow	FA113198X12					5.6 in. w.c.	14 mbar	24 in. w.c.	60 mbar	0.135	3.43	2.36	59.9				
1.7 to 5.6	0.12 to 0.39	Green	FA113199X12					7.2 in. w.c.	18 mbar	2.2	0.15	0.156	3.96	2.36	59.9				
2 to 11	0.14 to 0.76	Gray	FA113201X12					20 in. w.c.	50 mbar	5.1	0.35	0.192	4.88	2.36	59.9				
4 to 19	0.28 to 1.3	Brown	FA113202X12					1.16	80 mbar	8.7	0.6	0.207	5.26	2.36	59.9				
7 to 33	0.48 to 2.3	Black	FA114139X12					2.47	0.17	16	1.1	0.25	6.35	2.36	59.9				
15 to 75	1.0 to 5.2	Blue	FA113200X12					5.08	0.35	36.3	2.5	0.177	4.5	2.36	59.9				
31 to 161	2.1 to 11.1	Brown	FA113202X12					71	Piston	235	16.2	10.2	0.7	79.8	5.5	0.207	5.26	2.36	59.9
59 to 235	4.1 to 16.2	Black	FA114139X12	23.2	1.6	145	10					0.25	6.35	2.36	59.9				
235 to 323	16.2 to 22.3	Brown	FA113202X12	43.5	3	Requires use of Type BMS1 or BMS2						0.25	5.26	2.36	59.9				
323 to 588	22.3 to 40.5	Black	FA114139X12	94.3	6.5							0.25	6.35	2.36	59.9				
588 to 808	40.5 to 55.7	Brown	FA113202X12	102	7							0.207	5.26	2.36	59.9				
808 to 1470	55.7 to 101	Black	FA114139X12	174	12							0.25	6.35	2.36	59.9				
81 to 323	5.60 to 22.3	Brown	FA113202X12	236	Bellows	514	35.4					14.5	1	145	10	0.207	5.26	2.36	59.9
122 to 514	8.41 to 35.4	Black	FA114139X12									36.3	2.5	290	20	0.25	6.35	2.36	59.9
257 to 1058	17.7 to 73.0	Gray	FA113201X12									1058	73	72.5	5	479	33	0.192	4.88

1. Minimum suggested difference between slam-shut set pressure and normal operating pressure of the system.

2. Maximum difference between overpressure and underpressure when using one manometric device (Type BMS1) with tripping hook. For underpressure and overpressure points greater than this maximum number, use a second manometric device (Type BMS2) for underpressure protection.

**Table 6. Application and Construction Guide**


APPLICATION	MECHANISM BOX REQUIRED		MANOMETRIC SENSING DEVICE REQUIRED	
	Type BM1	Type BM2	Type BMS1	Type BMS2
Overpressure Shutoff (OPSO)	Yes	No	Yes	No
Underpressure Shutoff (UPSO)	Yes	No	Yes	No
Overpressure Shutoff (OPSO) and Underpressure Shutoff (UPSO)	Yes	No	Yes <sup>(1)</sup>	No
Overpressure Shutoff (OPSO) and Underpressure Shutoff (UPSO)	No	Yes	Yes <sup>(2)</sup>	Yes
Overpressure Shutoff (OPSO), Overpressure Shutoff and Underpressure Shutoff (OPSO/UPSO)	No	Yes	Yes <sup>(2)</sup>	Yes <sup>(1)</sup>

1. When using one Type BMS1 or BMS2 for both overpressure and underpressure shutoff, make sure that the difference between set pressures falls below the maximum range shown in Table 5.

2. When using Types BMS1 and BMS2, the Type BMS1 can only be used for high trip.

**Table 7. Dimensions**

BODY SIZE		DIMENSION																						
		A								B						C		D				E		
		NPT		CL125 FF, CL150 RF		CL300 RF		CL600 RF		CL125 FF, CL150 RF		CL300 RF		CL600 RF				CL125 FF, CL150 RF		CL250 RF, CL300 RF, CL600 RF				
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm					
NPS	DN	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm			
1	25	8.25	210	7.25	184	7.75	197	8.25	210	2.2	56	2.5	63	2.5	63	12.6	320	4.6	117	4.9	124	----		
2	50	11.25	286	10	254	10.5	267	11.25	286	3	76	3.3	84	3.3	84	13.2	335	6	152	6.5	165			
3	80	----		11.75	298	12.5	317	13.25	337	3.7	94	4.1	104	4.1	104	14.2	361	7.5	190	8.3	211			
4	100			13.88	353	14.5	368	15.5	394	4.5	114	5	127	5	127	16	406	9	229	10	254			
6	150			17.75	451	18.62	473	20	508	5.5	140	6.6	168	6.6	168	16.2	411	14	356	14	356			
8	200			21.38	543	22.38	568	24	610	6.8	173	7.5	190	8.2	208	22.8	579	17.6	447	17.6	447		13.2	335
10	250			26.5	673	27.9	708	29.6	752	8	203	8.7	221	10	254	26.3	668	19.6	498	19.6	498		14.3	363



NPS 1 THROUGH 6 / DN 25 THROUGH 150 BODY SIZES

NPS 8 AND 10 / DN 200 AND 250 BODY SIZES

IN. /  
mm

Figure 3. Type OSE Dimensions

Table 8. Approximate Weights				
BODY SIZE		APPROXIMATE SHIPPING WEIGHT		
NPS	DN	Lb	kg	
1	25	36	16	
2	50	70	32	
3	80	121	55	
4	100	216	98	
6	150	445	202	
8	200	785	356	
10	250	1272	577	

## Ordering Guide

Body Size (Select One)
<input type="checkbox"/> NPS 1 / DN 25***
<input type="checkbox"/> NPS 2 / DN 50***
<input type="checkbox"/> NPS 3 / DN 80***
<input type="checkbox"/> NPS 4 / DN 100***
<input type="checkbox"/> NPS 6 / DN 150***
<input type="checkbox"/> NPS 8 / DN 200**
<input type="checkbox"/> NPS 10 / DN 250**

Body Material and End Connection Style (Select One)
<b>Cast Iron Body</b>
<input type="checkbox"/> NPT (NPS 1 and 2 / DN 25 and 50 only)***
<input type="checkbox"/> CL125 FF** (NPS 1 to 6 / DN 25 to 150 only)
<b>WCC Steel Body</b>
<input type="checkbox"/> NPT (NPS 1 and 2 / DN 25 and 50 only)***
<input type="checkbox"/> CL150 RF***
<input type="checkbox"/> CL300 RF**
<input type="checkbox"/> CL600 RF**

- continued -

## Ordering Guide (continued)

### Slam-Shut Trip Pressure Setting (Select One)

- Overpressure Protection Only (OPSO)**  
Supply setpoint required \_\_\_\_\_
- Underpressure Protection Only (UPSO)**  
Supply setpoint required \_\_\_\_\_
- Overpressure Protection and Underpressure Protection (OPSO/UPSO)**  
Supply overpressure setpoint required \_\_\_\_\_  
Supply underpressure setpoint required \_\_\_\_\_
- Overpressure Protection (OPSO), Overpressure Protection and Underpressure Protection (OPSO/UPSO)**  
Supply overpressure setpoint required \_\_\_\_\_  
Supply overpressure setpoint required \_\_\_\_\_  
Supply underpressure setpoint required \_\_\_\_\_

### Explosion-Proof Limit Switch (Optional)

- Yes\*\*

### Manual Push Button Trigger Switch (Optional)

- Yes\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Use control lines of equal or greater size than the control tap on the regulator. If a long control line is required, make it bigger. A rule of thumb is to use the next nominal pipe size for every 20 feet / 6.1 m of control line. Small control lines cause a delayed response of the regulator, leading to increased chance of instability. 3/8-inch / 9.5 mm OD tubing is the minimum recommended control line size.

**Introduction**

P590 Series filters are designed to remove dirt, scale or other solid substances from gases just upstream from pilot supply lines for air or gas pressure regulators.

The filter elements in all P590 Series filters are readily accessible and easily cleaned.

**Filtering Densities**

The phenolic resin impregnated cellulose filter elements of these units are capable of removing all particles larger than 40 microns, 0.0016 in. / 0.04 mm in diameter.

**Sizing Coefficient**

The gas sizing coefficient ( $C_g$ ) for all two filter elements at 75% clogged is in a range from 15 to 20.

**Body Size and End Connection Style**

**Connections:** 1/4 NPT  
Length: 3.25 in. / 83 mm

**Approximate Weight**

2 lbs / 1 kg

**Maximum Working Pressures<sup>(1)</sup>**

**Type P594-1 with Brass Body:**

1400 psig / 96.5 bar

**Type P593-1 with Aluminum Body:**

600 psig / 41.4 bar

**Filer Types and Materials**

**Type P593-1<sup>(2)</sup>:**

Body: Aluminum

Filter Element: Cellulose

**Type P594-1:**


Body: Brass

Filter Element: Cellulose

**Ordering Information**

To receive the fastest order processing, please specify type number and (for Type P593-1 only) the NACE option (NACE International standard MR0175-2003).

1. The pressure/temperature limits is this Datasheet or any applicable standard limitation should not be exceeded.  
2. NACE option is available.



**Additional Technical Data**  
Scan or Click the QR code for more information on this product.  
[www.Emerson.com](http://www.Emerson.com)



10/09

**Features**

- Compact Design
- Install in Any Position
- Economical

**Ordering Guide**

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

# R Series

## Pressure Reducing Regulator

TARTARINI™

### Introduction

The R Series spring-loaded regulators provide pressure reducing control for domestic and industrial use, such as burners, furnaces, boilers and other installations requiring proper regulation and quick response time. These regulators can be used with non-corrosive gases, such as natural gas, compressed air and nitrogen.

The R Series regulators achieve high accuracy and flow rates even with low inlet pressure and strong inlet pressure variations.

### Types R/70, R/71, R/72, R/72-FS, R/73, R/74 and R/75

#### Allowable Inlet Pressure

87 psig / 6.0 bar

#### Inlet Pressure Range

1.45 to 87 psig / 0.10 to 6.0 bar<sup>(1)</sup>

#### Set Range

0.22 to 1.02 psig / 15 to 70 mbar

#### Accuracy Class

Up to ±5%

#### Lockup Pressure Class

Up to 10%

### Types R/70-AP, R/71-AP, R/72-AP, R/72-FS-AP, R/73-AP, R/74-AP and R/75-AP

#### Allowable Inlet Pressure

145 psig / 10.0 bar

#### Inlet Pressure Range

1.45 to 145 psig / 0.10 to 10.0 bar<sup>(1)</sup>

#### Set Range

1.02 to 4.35 psig / 70 to 300 mbar

#### Accuracy Class

Up to ±5%

#### Lockup Pressure Class

Up to 10%

#### Built-In Slam-Shut Valve

##### Overpressure Set Range:

0.44 to 5.5 psig / 30 to 380 mbar

##### Underpressure Set Range:

0.12 to 2.25 psig / 8 to 155 mbar

**Response time:** ≤ 1 s

### Connections

#### Types R/70 and R/70-AP:

G 3/4-in. x G 1-1/4-in.  
UNI ISO 228/1 - right angle  
(3/4-in. soft seal x 1-1/4-in. Gas)

#### Types R/71 and R/71-AP:

G 3/4-in. x G 1-1/4-in.  
UNI ISO 228/1 - right angle  
(3/4-in. metallic seal x 1-1/4-in. Gas)

#### Types R/72 and R/72-AP:

G 1-in. UNI ISO 228/1 - axial flow  
(1-in. Gas)

Types R/72-FS, R/72-FS-AP:  
1-in. / DN 25, PN 16 - axial flow

Types R/73, R/73-AP:  
G 1-1/4-in. UNI ISO 228/1 - axial flow  
(1-1/4-in. Gas)

Types R/74 and R/74-AP:  
G 3/4-in. x G 1-1/4-in.  
UNI ISO 228/1 - axial flow  
(3/4-in. soft seal x 1-1/4-in. Gas)

Types R/75 and R/75-AP:  
G 3/4-in. x G 1-in.  
UNI ISO 228/1 - axial flow  
(3/4-in. soft seal x 1-in. Gas)

### Operating Temperature

**Working:** -4 to 140°F / -20 to 60°C

**Ambient:** -22 to 140°F / -30 to 60°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)




02/15

### Features

- Two-Stage Regulation
- Built-In Relief Valve (Optional)
- Overpressure and Underpressure Slam-Shut Valve
- Manual Reset
- Built-In Filter with 0.02 in. / 0.5 mm Filtering Capacity



Figure 1. R Series Pressure Regulator



SLAM-SHUT DETAIL




Figure 2. R Series Regulator Cut Away with Slam-Shut Detail

1. According to the standards enacted.




Figure 3. 0.29 psig / 20 mbar Set Characteristic Curves

BODY	1ST AND 2ND STAGE COVER	SLAM-SHUT VALVE COVER	CONNECTION	SEAL	SLAM-SHUT VALVE DIAPHRAGM	1ST AND 2ND STAGE DIAPHRAGM
Die-cast Aluminum	Die-cast Aluminum	Die-cast Zama	Brass	Nitrile (NBR)	Nitrile (NBR)	Clothed Nitrile (NBR)



OUTLET PRESSURE		CAPACITIES IN SCFH / Sm³/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS							
		Inlet Pressure, psig / bar							
psig	mbar	1.45 / 0.10	2.90 / 0.20	4.35 / 0.30	5.80 / 0.40	7.25 / 0.50	10.9 / 0.75	14.5 to 87 / 1 to 6	14.5 to 145 / 1 to 10
0.22	15	882 / 25.0	1236 / 35.0	1765 / 50.0	2118 / 60.0	2472 / 70.0	2472 / 70.0	2648 / 75.0	----
0.29	20	882 / 25.0	1236 / 35.0	1765 / 50.0	2118 / 60.0	2472 / 70.0	2472 / 70.0	2648 / 75.0	----
0.44	30	882 / 25.0	1059 / 30.0	1589 / 45.0	1942 / 55.0	2472 / 70.0	2472 / 70.0	2648 / 75.0	----
0.58	40	882 / 25.0	1059 / 30.0	1412 / 40.0	1765 / 50.0	2295 / 65.0	2472 / 70.0	2472 / 70.0	----
0.73	50	706 / 20.0	1059 / 30.0	1412 / 40.0	1765 / 50.0	2295 / 65.0	2472 / 70.0	2472 / 70.0	----
0.87	60	529 / 15.0	1059 / 30.0	1412 / 40.0	1765 / 50.0	2118 / 60.0	2118 / 60.0	2295 / 65.0	----
1.02	70	529 / 15.0	1059 / 30.0	1412 / 40.0	1589 / 45.0	1942 / 55.0	2118 / 60.0	2118 / 60.0	----
1.02	70	706 / 20.0	1059 / 30.0	1412 / 40.0	1589 / 45.0	1942 / 55.0	2472 / 70.0	----	3531 / 100
1.16	80	706 / 20.0	1059 / 30.0	1236 / 35.0	1589 / 45.0	1942 / 55.0	2472 / 70.0	----	3354 / 95.0
1.03	90	706 / 20.0	1059 / 30.0	1236 / 35.0	1589 / 45.0	1765 / 50.0	2472 / 70.0	----	3178 / 90.0
1.45	100	----	706 / 20.0	1059 / 30.0	1236 / 35.0	1589 / 45.0	2295 / 65.0	----	2825 / 80.0
2.18	150	----	706 / 20.0	1059 / 30.0	1236 / 35.0	1589 / 45.0	2118 / 60.0	----	2648 / 75.0
2.90	200	----	----	882 / 25.0	1059 / 30.0	1412 / 40.0	1765 / 50.0	----	2472 / 70.0
3.63	250	----	----	706 / 20.0	1059 / 30.0	1412 / 40.0	1765 / 50.0	----	2118 / 60.0
4.35	300	----	----	----	882 / 25.0	1059 / 30.0	1589 / 45.0	----	2118 / 60.0

Types R/70, R/71, R/72, R/72-FS, R/73, R/74 and R/75  
 Types R/70-AP, R/71-AP, R/72-AP, R/72-FS-AP, R/73-AP, R/74-AP and R/75-AP


# R Series

## Pressure Reducing Regulator


TARTARINI™




TYPE R/70 OR R/70-AP




TYPE R/71 OR R/71-AP




TYPE R/72 OR R/72-AP




TYPE R/72-FS OR R/72-FS-AP



TYPE R/73 OR R/73-AP



TYPE R/74 OR R/74-AP



TYPE R/75 OR R/75-AP

In. /  
mm

Figure 4. Dimensions



## Ordering Guide

<b>Type (Select One)</b>
<input type="checkbox"/> R/70 or R/70-AP*** <input type="checkbox"/> R/71 or R/71-AP*** <input type="checkbox"/> R/72 or R/72-AP*** <input type="checkbox"/> R/72-FS or R/72-FS-AP*** <input type="checkbox"/> R/73 or R/73-AP*** <input type="checkbox"/> R/74 or R/74-AP*** <input type="checkbox"/> R/75 or R/75-AP***
<b>Inlet Pressure</b>
_____ please specify
<b>Outlet Pressure</b>
_____ please specify
<b>Special Requirements (Optional)</b>
_____

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

Specification Worksheet
<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired?
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

**Regulator Tip:**

Downstream pressure always changes to some extent when inlet pressure changes.

# Type R622

## Pressure Reducing Regulator

FISHER™

### Introduction

Type R622 direct-operated, spring-loaded regulators provide economical pressure reducing control in a variety of residential, commercial and industrial applications. These regulators can be used with natural, manufactured or propane gas and have the same inlet and outlet pressure capabilities.

In addition, Type R622 regulators have internal relief across the diaphragm to help minimize overpressure. Any outlet pressure above the start-to-discharge point of the nonadjustable relief valve spring moves the diaphragm off of the relief valve seat, allowing excess pressure to bleed out through the screened spring case vent.

### Body Size and End Connection Style

1/2 NPT (inlet and outlet)

### Maximum Allowable Inlet Pressure

**Operating:** 125 psig / 8.6 bar

**Emergency:** 125 psig / 8.6 bar

Except 1.8 to 2.2 in. w.c. / 4 to 5 mbar spring range which has operating and emergency pressures of 60 psig / 4.1 bar

### Relief Performance

See Figure 3

### Outlet Pressure Ranges

See Table 2

### Maximum Allowable Outlet (Casing) Pressure

**Operating to Avoid Internal Parts**

**Damage:** 3 psid / 0.21 bar d above outlet pressure setting

**Emergency:** 20 psi / 1.4 bar

### Flow Capacities

See Table 3

### Orifice Size

1/8 in. / 3.2 mm

### Flow Coefficients

**Wide-Open  $C_g$  for Relief Sizing:** 12.5

**Wide-Open  $C_v$  for Relief Sizing:** 0.36

$C_1$ : 35

### IEC Sizing Coefficients

$X_T$ : 0.78

$F_D$ : 0.82

$F_L$ : 0.89

### Pressure Registration


Internal

### Temperature Capabilities

-20 to 160°F / -29 to 71°C

### Approximate Shipping Weight

2.35 lbs / 1 kg



W8806

Figure 1. Type R622 Pressure Reducing Regulator

### Features

- Compact Design
- High Capacity
- Protective Inlet Screen
- Internal Relief
- Light Weight
- Inlet and Outlet Pressure Gauge Taps

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



06/10





Figure 2. Type R622 Operational Schematic



NOTE: TESTED UNDER THE FOLLOWING CONDITIONS: 10 psig / 0.69 bar INLET PRESSURE, 7 IN. W.C. / 17 mbar OUTLET PRESSURE SETTING AND 50 SCFH / 1.3 Nm<sup>3</sup>/h OF 0.6 SPECIFIC GRAVITY NATURAL GAS

Figure 3. Industrial Relief Performance

Table 1. Construction Material

PART NAME	MATERIAL
Body, Spring Case, Diaphragm Plate and Orifice	Aluminum
Diaphragm, Disk and O-ring	Nitrile (NBR)
Adjusting Screw and Pusher Post	Delrin®
Closing Cap	ASA Thermoplastic (UV-Ray Resistant)
Control Spring	Zinc-plated steel
Machine Screw, Spring Seat and Lever	Zinc-plated steel
Valve Stem	Zinc
Relief Valve Spring, Relief Spring Retainer, Lever Pin and Vent Screen	Stainless steel

Table 2. Outlet Pressure Range

OUTLET PRESSURE RANGE		CONTROL SPRING PART NUMBER	CONTROL SPRING COLOR CODE	SPRING WIRE DIAMETER		SPRING FREE LENGTH	
in. w.c.	mbar			In.	mm	In.	mm
1.8 to 2.2	4 to 5	T14453T0012	Purple	0.051	1.30	3.40	86.4
5 to 7	12 to 17	T14398T0012	Orange	0.062	1.58	3.40	86.4
6.5 to 9	16 to 22	T14399T0012	Yellow	0.067	1.70	3.61	91.7
9 to 13	22 to 32	T14400T0012	Silver	0.072	1.83	4.10	104
13 to 20	32 to 50	T14401T0012	Gray	0.080	2.03	3.60	91.4
16 to 35	40 to 87	T14402T0012	Pink	0.093	2.36	3.52	89.4
1 to 2.2 psig	69 to 152	T14403T0012	Light Blue	0.105	2.67	3.66	93.0

Delrin® is a mark owned by E.I. Du Pont de Nemours and Co.

# Type R622


## Pressure Reducing Regulator

FISHER™

**Table 3. Typical Regulating Capacities in SCFH / Nm<sup>3</sup>/h of 0.6 Specific Gravity Natural Gas for Type R622 Regulator**


OUTLET PRESSURE SETTING, CONTROL SPRING RANGE, SPRING PART NUMBER, COLOR CODE AND DROOP	INLET PRESSURE		1/2 NPT INLET AND OUTLET	
	psig	bar	SCFH	Nm <sup>3</sup> /h
Setting: 2 in. w.c. / 5 mbar Range: 1.8 to 2.2 in. w.c. / 4 to 5 mbar T14453T0012, Purple Droop: 1 in. w.c. / 2 mbar	5	0.35	287	7.7
	10	0.69	380	10.2
	25	1.7	451	12.1
	50	3.4	493	13.2
	60	4.1	506	13.6
	5	0.35	271	7.3
Setting: 5 in. w.c. / 12 mbar Range: 5 to 7 in. w.c. / 12 to 17 mbar T14398T0012, Orange Droop: 1 in. w.c. / 2 mbar	10	0.69	367	9.8
	25	1.7	468	12.5
	50	3.4	484	13.0
	60	4.1	428	11.5
	75	5.2	444	11.9
	100	6.9	536	14.4
	125	8.6	536	14.4
Setting: 7 in. w.c. / 17 mbar Range: 6.5 to 9 in. w.c. / 16 to 22 mbar T14399T0012, Yellow Droop: 1 in. w.c. / 2 mbar	5	0.35	246	6.6
	10	0.69	347	9.3
	25	1.7	451	12.1
	50	3.4	469	12.6
	60	4.1	477	12.8
	75	5.2	445	11.9
	100	6.9	507	13.6
Setting: 11 in. w.c. / 27 mbar Range: 9 to 13 in. w.c. / 22 to 32 mbar T14400T0012, Silver Droop: 2 in. w.c. / 5 mbar	125	8.6	511	13.7
	5	0.35	274	7.3
	10	0.69	401	10.7
	25	1.7	623	16.7
	50	3.4	708	19.0
	60	4.1	735	19.7
	75	5.2	676	18.1
Setting: 14 in. w.c. / 35 mbar Range: 13 to 20 in. w.c. / 32 to 50 mbar T14401T0012, Gray Droop: 2 in. w.c. / 5 mbar	100	6.9	721	19.3
	125	8.6	738	19.8
	5	0.35	246	6.6
	10	0.69	364	9.8
	25	1.7	551	14.8
	50	3.4	641	17.2
	60	4.1	661	17.7
Setting: 1 psig / 69 mbar Range: 16 to 35 in. w.c. / 40 to 87 mbar T14402T0012, Pink Droop: 10%	75	5.2	614	16.5
	100	6.9	677	18.1
	125	8.6	727	19.5
	5	0.35	174	4.7
	10	0.69	337	9.0
	25	1.7	533	14.3
	50	3.4	679	18.2
Setting: 2 psig / 0.14 bar Range: 1.2 to 2.2 psi / 83 to 152 mbar T14403T0012, Light Blue Droop: 10%	60	4.1	708	19.0
	75	5.2	756	20.3
	100	6.9	762	20.4
	125	8.6	796	21.3
	5	0.35	222	6.0
	10	0.69	381	10.2
	25	1.7	630	16.9
Setting: 2 psig / 0.14 bar Range: 1.2 to 2.2 psi / 83 to 152 mbar T14403T0012, Light Blue Droop: 10%	50	3.4	923	24.7
	60	4.1	976	26.2
	75	5.2	1007	27.0
	100	6.9	1285	34.4
	125	8.6	1028	27.6





T80577

Figure 4. Vent Position



T14439

IN. / mm

Figure 5. Dimensions

# Type R622

Pressure Reducing Regulator

FISHER™

## Ordering Guide

### Outlet Pressure Range (Select One)

- 1.8 to 2.2 in. w.c. / 4 to 5 mbar, Purple\*\*\*
- 5 to 7 in. w.c. / 12 to 17 mbar, Orange\*\*\*
- 6.5 to 9 in. w.c. / 16 to 22 mbar, Yellow\*\*\*
- 9 to 13 in. w.c. / 22 to 32 mbar, Silver\*\*\*
- 13 to 20 in. w.c. / 32 to 50 mbar, Gray\*\*\*
- 16 to 35 in. w.c. / 40 to 87 mbar, Pink\*\*\*
- 1 to 2.2 psig / 69 to 152 mbar, Light Blue\*\*\*

### Vent Position (Select One)

- Position 1 (vent over inlet)\*\*\*
- Position 2\*\*\*
- Position 3 (vent over outlet)\*\*\*
- Position 4\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Regulator Tip:

Keep vents open. Do not use small diameter, long vent lines. Use the rule of thumb of the next nominal pipe size every 10 feet / 3.1 m of vent line and 3 feet / 0.9 m of vent line for every elbow in the line.

### Introduction

The REGAL 3 Series is a direct-operated, spring setpoint pressure regulator, used for supplying industries and commercial businesses.

As an option, it can be equipped with a slam-shut Type VSX2 or OS2 which permits the gas flow to be cut off rapidly and totally in the case of under or over outlet regulator pressure. As a standard feature for outlet pressure settings inferior or equal to 72.3 in. w.c. / 180 mbar, a relief valve is provided. On request, this relief valve may be disconnected and replaced by a dampener.

Upon request, for pressures 72.3 in. w.c. / 180 mbar > P<sub>2</sub> ≤ 442 in. w.c. / 1100 mbar, the REGAL 3 Series can be equipped with a relief valve. This relief valve can be factory adjusted.

The REGAL 3 Series is in conformity with the Pressure Equipment Directive (PED) requirements.

### Body Size and End Connection Styles

2 in. / DN 50 with NPT, PN 10/16, PN 20 or CL150 RF end connections

### Maximum Flow Capacity

126,866 SCFH / 3400 Nm<sup>3</sup>/h

### Maximum Inlet Pressure

145 psig / 10.0 bar

### Maximum Outlet Pressure

**PED Version:** 21.8 psig / 1500 mbar

**Non-PED Version:** 43.5 psig / 3000 mbar

### Outlet Pressure Range

**PED Version:** 3.2 in. w.c. to 21.8 psig / 8 to 1500 mbar

**Non-PED Version:** 29 to 43.5 psig / 2000 to 3000 mbar

### Slam-Shut Pressure Ranges

See Table 4

### Regulating Accuracy

AC10

### Lockup Pressure Class

SG20

### Pressure Registration

External

### Internal Relief Setting

P<sub>1</sub> + 1.3 psig / P<sub>1</sub> + 90 mbar

### Temperature Capabilities

-22 to 160°F / -30 to 71°C

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



10/13

### Features

- Integral Slam-Shut Valve
- Installation Flexibility
- Ease of Installation
- Precise Flows
- Internal Relief




Figure 1. Type REGAL 3-VSX2 Pressure Reducing Regulator



Figure 2. Type REGAL 3-OS2 Pressure Reducing Regulator




Figure 3. REGAL 3 Series Operational Schematic

# REGAL 3 Series

## Pressure Reducing Regulator

FRANCEL™




Figure 4. Sizing Diagram

Table 1. Regulator Construction Material

BODY	PLUG	PLUG DISK	ORIFICE	DIAPHRAGM	O-RING
Ductile iron	Aluminum	Nitrile (NBR)	Brass	Reinforced Nitrile (NBR)	Nitrile (NBR)

Table 2. Slam-Shut Valve Construction Material

BODY	PLUG	PLUG DISK	DIAPHRAGM	O-RING	RESET BUTTON
Aluminum	Aluminum	Nitrile (NBR)	Reinforced Nitrile (NBR)	Nitrile (NBR)	Brass

Table 3. Outlet Pressure Range

OUTLET PRESSURE RANGE		NOMINAL OUTLET PRESSURE		SPRING WIRE DIAMETER	
psig	bar	psig	bar	In.	mm
0.116 to 0.36	8 to 25	0.3	20	0.12	3.04
0.29 to 0.80	20 to 55	0.51	40	0.16	4.06
0.58 to 1.3	40 to 90	0.87	60	0.18	4.60
0.87 to 2.0	60 to 140	1.5	100	0.22	5.60
1.16 to 2.61	80 to 180	2.32	160	0.24	6.10
1.5 to 4.9	100 to 340	4.35	300	0.30	7.62
4.35 to 8.0	300 to 550	7.3	500	0.32	8.12
5.8 to 16	400 to 1100	15	1000	0.40	10.16
10.9 to 21.8	750 to 1500	21.8	1500	0.32	8.13

Table 4. Outlet Pressure Range of Shutoff Device Pilot

NOMINAL OUTLET PRESSURE		TYPE VSX2							TYPE OS2				
		Overpressure Range		Maximum Spring		Underpressure Range		Minimum Spring Diameter		Pressure Range		Spring Wire	
psig	mbar	psig	mbar	In.	mm	psig	mbar	In.	mm	psig	mbar	In.	mm
0.29	20	0.44 to 0.87	30 to 60	0.067	1.70	0.073 to 0.44	5 to 30	0.043	1.09	----	----	----	----
0.51	40	0.73 to 1.89	50 to 130	0.079	2.00	0.073 to 0.44	5 to 30	0.043	1.09	----	----	----	----
0.87	60	0.73 to 1.89	50 to 130	0.079	2.00	0.145 to 1.09	10 to 75	0.055	1.40	----	----	----	----
1.45	100	1.38 to 3.48	95 to 240	0.091	2.31	0.145 to 1.09	10 to 75	0.055	1.40	1.01 to 3.48	70 to 240	0.138	3.50
2.32	160	2.18 to 5.51	150 to 380	0.102	2.60	0.363 to 2.32	25 to 160	0.067	1.70	1.01 to 3.48	70 to 240	0.138	3.50
4.35	300	3.77 to 8.70	260 to 600	0.122	3.10	1.45 to 5.08	100 to 350	0.094	2.39	2.0 to 10.9	140 to 750	0.197	5.00
7.25	500	5.8 to 16.0	400 to 1100	0.138	3.50	1.45 to 7.25	100 to 500	0.094	2.39	2.0 to 10.9	140 to 750	0.197	5.00
14.5	1000	11.6 to 23.2	800 to 1600	0.161	4.09	1.45 to 10.9	100 to 750	0.126	3.20	6.53 to 33.36	450 to 2300	0.256	6.50
21.8	1500	16.0 to 29	1100 to 2000	0.122	3.10	7.3 to 16.0	500 to 1100	0.094	2.40	6.53 to 33.36	450 to 2300	0.256	6.50








Figure 5. Dimensions

**Table 5. Capacities at 10% Regulating Accuracy**

INLET PRESSURE, psig / bar	CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
	Outlet Pressure, psig / mbar													
	0.29 / 20		0.51 / 35		0.87 / 60		1.5 / 100		4.35 / 300		7.3 / 500		15 / 1000	
	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7.3 / 0.5	10,075	270	11,940	320	14,179	380	11,940	320	11,940	320	----	----	----	----
15 / 1.0	17,537	470	17,537	470	19,403	520	20,896	560	20,522	550	19,030	510	----	----
29 / 2.0	29,851	800	29,851	800	35,448	950	35,448	950	37,313	1000	37,313	1000	35,448	950
58 / 4.0	52,239	1400	54,104	1450	57,836	1550	61,567	1650	61,567	1650	65,299	1750	65,299	1750
116 / 8.0	87,687	2350	93,284	2500	104,478	2800	108,209	2900	108,209	2900	108,209	2900	108,209	2900
145 / 10	97,015	2600	108,209	2900	119,403	3200	119,403	3200	119,403	3200	126,866	3400	126,866	3400

**Table 6. Capacities at 20% Regulating Accuracy**

INLET PRESSURE, psig / bar	CAPACITIES IN SCFH / Nm <sup>3</sup> /h OF 0.6 SPECIFIC GRAVITY NATURAL GAS													
	Outlet Pressure, psig / mbar													
	0.29 / 20		0.51 / 35		0.87 / 60		1.5 / 100		4.35 / 300		7.3 / 500		15 / 1000	
	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h	SCFH	Nm <sup>3</sup> /h
7.3 / 0.5	17,910	480	17,910	480	17,910	480	17,910	480	15,672	420	----	----	----	----
15 / 1.0	26,866	720	26,866	720	26,866	720	26,866	720	25,373	680	23,507	630	----	----
29 / 2.0	44,776	1200	44,776	1200	44,776	1200	44,776	1200	44,776	1200	44,776	1200	39,179	1050
58 / 4.0	69,030	1850	69,030	1850	69,030	1850	67,164	1800	67,164	1800	65,299	1750	65,299	1750
116 / 8.0	104,478	2800	108,209	2900	108,209	2900	108,209	2900	108,209	2900	108,209	2900	108,209	2900
145 / 10	119,403	3200	126,866	3400	126,866	3400	126,866	3400	126,866	3400	126,866	3400	126,866	3400

**Table 7. Shipping Weight**

TYPE	APPROXIMATE SHIPPING WEIGHT, lb / kg
Type Regal 3 with Type VSX2 Slam-Shut Valve	41.4 / 19
Type Regal 3 with Type OS2 Slam-Shut Valve	52.9 / 24
Type Regal 3 without Slam-Shut Valve	39.7 / 18

## Ordering Guide

### End Connection Style (Select One)

- PN 10/16\*\*\*
- PN 20/CL150 RF\*\*\*
- NPT\*\*\*

### Outlet Pressure Range (Select One)

- 0.116 to 0.36 psig / 8 to 25 mbar
- 0.29 to 0.80 psig / 20 to 55 mbar
- 0.58 to 1.3 psig / 40 to 90 mbar
- 0.87 to 2.0 psig / 60 to 140 mbar
- 1.16 to 2.61 psig / 80 to 180 mbar
- 1.5 to 4.9 psig / 100 to 340 mbar
- 4.35 to 8.0 psig / 300 to 550 mbar
- 5.8 to 16 psig / 400 to 1100 mbar
- 10.9 to 21.8 psig / 750 to 1500 mbar

### Slam-Shut Valve (Optional)

- Type VSX2
- Type OS2

### Slam-Shut Valve Range

#### Type VSX2

##### Underpressure Range

- 0.073 to 0.44 psig / 5 to 30 mbar
- 0.145 to 1.09 psig / 10 to 75 mbar
- 0.363 to 2.32 psig / 25 to 160 mbar
- 1.45 to 5.08 psig / 100 to 350 mbar
- 1.45 to 7.25 psig / 100 to 500 mbar
- 1.45 to 10.9 psig / 100 to 750 mbar
- 7.3 to 16.0 psig / 500 to 1100 mbar

##### Overpressure Range

- 0.44 to 0.87 psig / 30 to 60 mbar
- 0.73 to 1.89 psig / 50 to 130 mbar
- 1.38 to 3.48 psig / 95 to 240 mbar
- 2.18 to 5.51 psig / 150 to 380 mbar
- 3.77 to 8.70 psig / 260 to 600 mbar
- 5.80 to 16.0 psig / 400 to 1100 mbar
- 11.6 to 23.2 psig / 800 to 1600 mbar
- 16.0 to 29 psig / 1100 to 2000 mbar

#### Type OS2

##### Pressure Range

- 1.01 to 3.48 psig / 70 to 240 mbar
- 2.0 to 10.9 psig / 140 to 750 mbar
- 6.53 to 33.36 psig / 450 to 2300 mbar

### Slam-Shut (Optional)

- Explosion-Proof Switch (Type OS2 only)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Specification Worksheet

<b>Application</b>
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
Does the application require overpressure protection?
<input type="checkbox"/> Yes, which is preferred? <input type="checkbox"/> No
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Monitor Regulator <input type="checkbox"/> Shutoff Device
Is overpressure protection equipment selection assistance desired? <input type="checkbox"/> Yes <input type="checkbox"/> No
<b>Pressure</b>
Maximum Inlet Pressure ( $P_{1max}$ ):
Minimum Inlet Pressure ( $P_{1min}$ ):
Downstream Pressure Setting(s) ( $P_2$ ):
Maximum Flow ( $Q_{max}$ ):
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

### Introduction

The Type RPE is used for reheating gas supplying pressure reducing regulator pilots.

The Type RPE avoids the inconveniences caused by freezing which occur during large pressure drops and/or low ambient temperatures.

There are two versions of the Type RPE:

#### Electrical Pilot Heater (with Heating Element)

The Type RPE (with a heating element) is installed with the vertical thermometer pocket axle using the fixing part supplied with the regulator actuator bolt.

#### Regulator Bottom Electrical Heater

This version is normally used for relief lines. The Type RPE is assembled on the regulator bottom with 4 fixing screws M8 x 20.

The Type RPE can be installed in an explosive risk zone.

The thermostat and power relay must be installed in a non-explosive risk zone.

The Type RPE is in conformity with the Directive for Equipment or Protective System intended for use in potentially explosive atmospheres 2014/34/UE. It is classified under group II, Category 2.

#### Maximum Operating Pressure Thermometer Pocket with Heating Element: 1450 psig / 100 bar

#### Temperature Measurement Interchangeable Thermic Probe: 10 kΩ

#### Heater 2 Interchangeable Heating Cartridges: 280 W - 230 V Connected in Series: 140 W

#### Temperature Regulation Range Thermostat: -22 to 194°F / -30 to 90°C

#### Power Supply Power Relay: I<sub>max</sub> 2 A U 250 V~

### Protection

**Thermostat:** 2 A  
**Power Relay:** 2 A

### Pneumatic Connections

**Inlet/Outlet:** 1/4 NPT - tube 8/10

### Electrical Connections

**Electrical Type RPE Box:** Packing gland 3/4 NPT for cable snap-on  
**Electrical Wiring:** Customer

### Weights

**Heater:** 3.1 pounds / 1.4 kg  
**Heater with Heating Element:** 9.9 pounds / 4.5 kg

### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



09/18

### Features

- Robust
- Protection in Case of High Overpressure
- Large Range of Utilization





Figure 1. Type RPE Electric Pilot Heater



HEATER ONLY : 1.4 KG  
HEATER + HEATING ELEMENT: 4.5 KG

Figure 2. Dimensions




Figure 3. Installation

**Table 1. Recommended Thermostat Setting**

SELECTOR FOR TEMPERATURE A RANGE	ADJUSTMENT FOR B SETTING	DIFFERENTIAL SELECTOR C
0/30	30	2

**Table 2. Electric Material For Explosive Atmospheres**

GROUP ACCORDING TO DIRECTIVE 2014/34/UE	CATEGORY ACCORDING TO DIRECTIVE 2014/34/UE	PROTECTION	CERTIFICATE	POWER SUPPLY	POWER CONSUMPTION	RECOMMENDED OPERATING TEMPERATURE	MAXIMUM ALLOWABLE ADMITTED TEMPERATURE
Group II	Category 2	EEx d IIC T2	CML 18 ATEX 1081	230 V 50 to 60 Hz	140 W	32 to 86°F / 0 to 30°C	140°F / 60°C

## Ordering Guide

### Version (Select One)

- Electrical pilot heater\*\*\*
- Electrical pilot heater with thermostat and power relay\*\*\*
- Electrical heater for regulator bottom\*\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

If you don't see what you're looking for in this Application Guide. . . ask us about it. Space in this Application Guide does not always permit us to list all of the options or products available to you. If you don't see the product you're looking for, just pick up the phone and ask your local Sales Office to help you find the item you need. To locate your local Sales Office, log on to Emerson.com/ContactUs.

### Introduction

Emerson has many years of experience designing and assembling regulating and metering stations.




An array of standard and customized installations are available for transmission, distribution and utilization application

Emerson's regulation and metering stations can be developed for open air, underground or cabinet/building protected applications.

### Additional Technical Data



Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



# Skids

## Regulating and Metering Installations and Final Regulating Installations



### Regulator Tip:

If you don't see what you're looking for in this Application Guide. . . ask us about it. Space in this Application Guide does not always permit us to list all of the options or products available to you. If you don't see the product you're looking for, just pick up the phone and ask your local Sales Office to help you find the item you need. To locate your local Sales Office, log on to [Emerson.com/ContactUs](http://Emerson.com/ContactUs).

### Introduction

#### Type SR

Type SR multi-path noise abatement device is incorporated into the regulator on the seat area. It consists of plated stainless steel wires containing no sound deadening materials. This is a solution providing a good result in noise reduction. When crossing the silencer steel wires the gas flow is split, many micro vortices are created, thus “turbulence bubbles” as well as “shock waves” are reduced. The efficiency of Type SR silencer is kept very high up to a theoretical velocity of 262 ft/s / 80 m/s in the outlet flange; the  $C_g$  reduction is by about 3% and noise reduction can be as much as 20 dB(A).

The Type SR Silencer can be used with FL Series, Types Cronos and 971 regulators.

#### Type SRII

The Type SRII noise abatement device is the next generation of Type SR and is used in case of extreme service conditions (dirty gas, high pressure drops and high gas velocities). Noise characteristics are very similar to the standard Type SR. The Type SRII can also be used with FL Series regulators.

#### Type SRS

Type SRS consists of a Type SR or SRII plus a widened outlet flange in which a second silencer is fitted. This configuration allows the limits set by velocity to be exceeded. In the outlet flange, there is a second silencer made of a first reactive section and a second section with multiple chambers. Noise reduction is based on the principle of stream splitting and expansion division in several stages.

The use of a wider outlet flange allows the introduction of the silencer and the installation of the regulator directly into the downstream piping without making use of expansion joints which cause a noise increase.

This silencer, being efficient under all working conditions, presents the advantage to reduce the length of the turbulent mixing area and the noise propagation along the downstream piping. Typical noise reduction reaches 25 dB(A) without limiting the velocity in the outlet flange. The  $C_g$  reduction is by about 15%. The Type SRS is used with FL Series and Type Cronos regulators.

#### Whisper Trim™

Whisper Trim cage provides effective attenuation of aerodynamic noise in gas applications involving high pressure drop ratios. Aerodynamic noise is generated by the turbulence created in the flow of gas as

the fluid passes through the port. To achieve effective noise attenuation, a Whisper Trim cage utilizes multiple orifices of special shape, size and spacing. These orifices break up turbulent fluid streams, reducing noise-producing interactions. Whisper Trim Cage reduces noise by up to 8 dB(A). The Whisper Trim cage is a noise attenuation solution for Types EZH and EZHSO.

#### Type STP

Type STP is an absorption type silencer made of one or more porous channels surrounded by deadening material. The sound penetrating the absorbing layer is then converted into heat by friction.

This type of silencer prevents noise propagation along the piping. It is normally introduced downstream the Type SRS silencer and produces a further noise reduction by 20 dB(A) depending on the approximate length.

This type of silencer is suitably dimensioned in order to satisfy working needs and obtain noise reductions without jeopardizing capacity values.

#### Type STL

These silencers have been specially developed to be introduced into “T” couplings of pipings. They are reactive-absorption mixed type silencers and allow not to experience any noise increase in the “T” coupling and get a noise reduction in the downstream piping. A suitable dimensioning of the silencer and downstream manifold allows not to experience significant power losses and thus capacity values are not jeopardized. Type STL provides noise reduction of 15 dB(A).

#### Additional Technical Data

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



03/10

#### Features

- Reduces Noise and has an Excellent Cost / Benefit Ratio
- Filters Recommended to Prevent Erosion or Damage from Foreign Particles



Figure 1. Type SR Built-in Regulator Silencer



Figure 2. Type SRII Built-in Regulator Silencer



Figure 3. Type SRS Built-in Regulator Silencer




Figure 4. Whisper Trim Built-in Regulator Silencer



Figure 5. Type STP Regulator Silencer




Figure 6. Type STL Regulator Silencer

# Types SR, SRII, SRS, STP, STL and Whisper Trim™

Silencers for Pressure Regulator and Regulating Installation

TARTARINI™




Figure 7. Typical Sound Emission Comparison among the Different Configurations

## Ordering Guide

### Type (Select One)

- SR\*\*\*
- SRII\*\*\*
- SRS\*\*\*
- STP
  - STP10 (10 dB(A) attenuation, with length of approximately 1m)\*\*\*
  - STP20 (20 dB(A) attenuation, with length of approximately 2m)\*\*\*
- STL\*\*\*
- Whisper Trim™ Cage\*\*\*

### Special Requirements (Specify)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

Looking for a specific product? When you know the application and Type or Series of the product you need, you can use the Quick Product Index in the Table of Contents, the Section Outline in the Application Map of each section, or the Product Index at the back of this Application Guide to direct you to the page on which the product is described.



**Introduction**

The VS100 Series slam-shut device is designed to shut off the flow of gas to the downstream system in the event of outlet pressure rising above or falling below the predefined levels.

The VS100 Series consists of the following:

- A body with a removable orifice, enclosed by a bonnet
- A VSX4 or VSX8 Series controller

**Available Configurations**

See Table 3

**Connections**

**Slam-Shut Vent:** 1/4 NPT

External Sensing Line: 1/4 NPT

**Body Material**

Ductile Iron (GS)

Steel (WCC)

**Body Sizes and End Connection Styles**

See Table 5

**Slam-shut Type**

**DS:** Differential Strength

**IS:** Integral Strength

**Maximum Allowable Pressure (PS)<sup>(1)</sup>**

**Differential Strength (DS):**

290 psig / 20.0 bar

Integral Strength (IS):

87 psig / 6.0 bar

**Maximum Inlet Pressure (P<sub>umax</sub>)<sup>(1)</sup>**

**Differential Strength (DS):**

232 psig / 16.0 bar

Integral Strength (IS):

87 psig / 6.0 bar

**Specific Maximum Allowable Pressure (PS<sub>s</sub>)<sup>(1)</sup>**

87 psig / 6.0 bar

**Operating Temperature (TS)<sup>(1)</sup>**

**PED:** -4 to 150°F / -20 to 66°C

**Non-PED:** -20 to 150°F / -30 to 66°C

**Response Time (ta)**

< 1 second

**CE Marking**

0062

**European EN Reference Standard**

EN 14382

**Functional Class**

**A:** OPSO and UPSO; **B:** OPSO only

**Orifice Diameter**

**Medium Capacity Body (MC):**

0.75 in. / 19 mm

High Capacity Body (HC):

1.18 in. / 30 mm

**Valve Plug Size**

**Medium Capacity Body (MC) Ø:**

0.94 in. / 24 mm

High Capacity Body (HC) Ø:

1.53 in. / 39 mm

**Flow Coefficient (NPS 1)<sup>(2)</sup>**

C<sub>g</sub>: 306; C<sub>v</sub>: 52

**Resetting Trip Mechanism**

Manually after fault rectification

**Pressure Detection**

External

**Approximate Shipping Weights**

See Table 5

**Option**

- Wire Seal
- Reed switch

**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



06/19




Figure 1. Type VS110

Figure 2. Type VS120

**Features**


- Medium and High Capacity Body Sizes Available
- Quick Response Time
- Ductile Iron and Steel Body Construction
- Complies with the Pressure Equipment Directive (PED) Requirements
- Overpressure and Underpressure trips available
- Modular Body Construction allows for adding regulator module in the future with no pipe charges

1. The pressure/temperature limits in this Datasheet or any applicable standard limitation should not be exceeded.  
2. NPS 1 x 2-1/4, Gaz Body

# VS100 Series

## Slam-Shut Device

FISHER™



- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

VSX4 AND VSX8 SERIES CONTROLLER WITH FLANGED BODY

Figure 3. VS100 Series Operational Schematic

Table 1. PED Information			
TYPE	DESCRIPTION	PED DIRECTORY	FLUID GROUP
VS100	Regulator body with VSX4 or VSX8 Series controller	IV	Groups 1 and 2 according to PED, 1st and 2nd family gas according to EN 437 or other gases (compressed air and nitrogen). The gas must be non-corrosive, clean (filtration on inlet side necessary) and dry.

Table 2. Accuracy According to EN 14382 - VS100 Series				
ACCURACY GROUP (AG)	$P_d < 0.507 \text{ psig} / 35 \text{ mbar}$	$0.507 \text{ psig} \leq P_d < 0.87 \text{ psig} / 35 \text{ mbar} \leq P_d < 60 \text{ mbar}$	$0.87 \text{ psig} \leq P_d < 1.5 \text{ psig} / 60 \text{ mbar} \leq P_d < 100 \text{ mbar}$	$P_d \geq 1.5 \text{ psig} / 100 \text{ mbar}$
$AG_{min}$	30	15	10	5
$AG_{max}$	10	10		

Note: Stable inlet pressure  $AG_{min} = AG 10$  ( $P_d < 0.87 \text{ psig} / 60 \text{ mbar}$ ) and  $AG 5$  ( $P_d > 0.87 \text{ psig} / 60 \text{ mbar}$ ),  $AG_{max} = AG 5$

Table 3. VS100 Series Configuration								
PRODUCT TYPE	BODY SIZE	ORIFICE DIAMETER		CONTROLLER	OVERPRESSURE MONITORING RANGE (Wdo)		UNDERPRESSURE MONITORING RANGE (Wdu)	
		in.	mm		psig	mbar	psig	mbar
VS111	Medium Capacity	0.75	19	VSX4L	0.44 to 23.2	30 to 1600	0.07 to 10.9	5 to 750
VS112				VSX4H	16.0 to 79.8	1100 to 5500	7.25 to 40.6	500 to 2800
VS121	High Capacity	1.18	30	VSX8L	0.44 to 23.2	30 to 1600	0.07 to 7.25	5 to 500
VS122				VSX8H	16.0 to 79.8	1100 to 5500	7.25 to 40.6	500 to 2800

**Table 4a. Overpressure Shut-off OPSO Ranges Only, psig**

REGULATOR		SLAM SHUT DEVICE				
Type	Typical Setpoint	Type (Maximum Operating Inlet)	Over Pressure Shut-off (OPSO)	Factory Set	Spring Part Number	Spring Color
			Set Range	OPSO		
	psig		psig	psig		
VS111 VS121	7 in. w.c.	VSX4L VSX8L (125 psi)	12 to 24 in. w.c.	22 in. w.c.	GF02168X012	Brown
	11 in. w.c.		16 in. w.c. to 1.6 psig	25 in. w.c.	GF02169X012	Red
	14 in. w.c.		24 in. w.c. to 2.8 psig	1.1	GF02170X012	Orange
	1		1.4 to 4.1	2	GF02171X012	Pink
	2		2.0 to 7.3	3.5	GF02172X012	Green
	3		2.0 to 7.3	5	GF02172X012	Green
	5		3.2 to 11.0	7	GF02173X012	Silver
	10		5.8 to 21	12	GF04353X012	Yellow
VS111 VS121	7 in. w.c.	VSX4L VSX8L (232 psi)	12 to 24 in. w.c.	22 in. w.c.	GF02168X012	Brown
	11 in. w.c.		16 in. w.c. to 1.6 psig	25 in. w.c.	GF02169X012	Red
	14 in. w.c.		24 in. w.c. to 2.8 psig	1.1	GF02170X012	Orange
	1		1.4 to 4.1	2	GF02171X012	Pink
	2		2.0 to 7.3	3.5	GF02172X012	Green
	3		2.0 to 7.3	5	GF02172X012	Green
	5		3.2 to 11.0	7	GF02173X012	Silver
	10		5.8 to 21	12	GF04353X012	Yellow
VS112 VS122	15	VSX4H VSX8H (232 psi)	13.1 to 43.5	19	GF02173X012	Silver
	20		13.1 to 43.5	25	GF02173X012	Silver
	30		13.1 to 43.5	35	GF02173X012	Silver
	40		23.2 to 79.8	45	GF04353X012	Yellow

**Table 4b. Overpressure Shut-off OPSO Ranges Only, bar**

REGULATOR		SLAM SHUT DEVICE				
Type	Typical Setpoint	Type (Maximum Operating Inlet)	Over Pressure Shut-off (OPSO)	Factory Set	Spring Part Number	Spring Color
			Set Range	OPSO		
	bar		bar	bar		
VS111 VS121	17.4 mbar	VSX4L VSX8L (125 psi / 8.62 bar)	29.9 to 59.8 mbar	54.8 mbar	GF02168X012	Brown
	27.4 mbar		39.9 mbar to 0.11 bar	62.3 mbar	GF02169X012	Red
	34.9 mbar		59.8 mbar to 0.19 bar	0.08	GF02170X012	Orange
	0.07		0.10 to 0.28	0.14	GF02171X012	Pink
	0.14		0.14 to 0.50	0.24	GF02172X012	Green
	0.21		0.14 to 0.50	0.34	GF02172X012	Green
	0.35		0.22 to 0.76	0.48	GF02173X012	Silver
	0.69		0.40 to 1.45	0.83	GF04353X012	Yellow
VS111 VS121	17.4 mbar	VSX4L VSX8L (232 psi / 16.0 bar)	29.9 to 59.8 mbar	54.8 mbar	GF02168X012	Brown
	27.4 mbar		39.9 mbar to 0.11 bar	62.3 mbar	GF02169X012	Red
	34.9 mbar		59.8 mbar to 0.19 bar	0.08	GF02170X012	Orange
	0.07		0.10 to 0.28	0.14	GF02171X012	Pink
	0.14		0.14 to 0.50	0.24	GF02172X012	Green
	0.21		0.14 to 0.50	0.34	GF02172X012	Green
	0.35		0.22 to 0.76	0.48	GF02173X012	Silver
	0.69		0.40 to 1.45	0.83	GF04353X012	Yellow
VS112 VS122	1.03	VSX4H VSX8H (232 psi / 16.0 bar)	0.90 to 3.0	1.30	GF02173X012	Silver
	1.38		0.90 to 3.0	1.72	GF02173X012	Silver
	2.07		0.90 to 3.0	2.40	GF02173X012	Silver
	2.76		1.60 to 5.50	3.10	GF04353X012	Yellow

# VS100 Series

## Slam-Shut Device



**Table 4c. Overpressure and Underpressure Shut-off OPSO/USPO Ranges, psig**

REGULATOR		SLAM SHUT DEVICE									
Type	Typical Setpoint psig	Type (Maximum Operating Inlet)	Under Pressure Shut-off (USPO)	Spring Part Number	Spring Color	Over Pressure Shut-off (OPSO)	Spring Part Number	Spring Color	Factory Set		
			Set Range			Set Range			USPO	Adjusted OPSO Range	OPSO
			psig			psig					
VS111 VS121	7 in. w.c.	VSX4L VSX8L (125 psi)	3 to 12 in. w.c.	ERAA05835A0	White	16 to 29 in. w.c.	GF02168X012	Brown	3 in. w.c.	19 in. w.c. to 1.2 psig	22 in. w.c.
	11 in. w.c.		3 to 12 in. w.c.	ERAA05835A0	White	16 to 29 in. w.c.	GF02168X012	Brown	6 in. w.c.	22 in. w.c. to 1.3 psig	25 in. w.c.
	14 in. w.c.		4 in. w.c. to 1.1 psig	T14169T0012	Blue	20 in. w.c. to 1.8 psig	GF02169X012	Red	9 in. w.c.	2.1 to 1.0	1.1
	1		10 in. w.c. to 2.3 psig	T14169T0012	Blue	1.2 to 3.2	GF02169X012	Red	14 in. w.c.	1.7 to 3.7	2
	2		10 in. w.c. to 2.3 psig	T14169T0012	Blue	1.2 to 3.2	GF02170X012	Orange	1	2.2 to 4.2	3.5
	3		1.5 to 7.3	T14170T0012	Silver	2.6 to 5.6	GF02171X012	Pink	2	4.6 to 7.6	5
	5		1.5 to 7.3	FA142869X12	Orange Stripe	2.6 to 5.6	GF02171X012	Pink	3	5.6 to 8.6	7
10	1.5 to 7.3	FA142869X12	Orange Stripe	3.5 to 8.2	GF02172X012	Green	5	8.5 to 13.2	12		
VS111 VS121	7 in. w.c.	VSX4L VSX8L (232 psi)	3 to 12 in. w.c.	ERAA05835A0	White	18 to 30	GF02168X012	Brown	3 in. w.c.	21 in. w.c. to 1.2 psig	22 in. w.c.
	11 in. w.c.		3 to 12 in. w.c.	ERAA05835A0	White	18 to 30	GF02168X012	Brown	6 in. w.c.	24 in. w.c. to 1.3 psig	25 in. w.c.
	14 in. w.c.		4 in. w.c. to 1.1 psig	T14169T0012	Blue	25 to 1.9	GF02169X012	Red	9 in. w.c.	1.2 to 2.2	1.1
	1		10 in. w.c. to 2.3 psig	T14169T0012	Blue	1.2 to 3.2	GF02170X012	Orange	14 in. w.c.	1.7 to 3.7	2
	2		10 in. w.c. to 2.3 psig	T14170T0012	Silver	1.2 to 3.2	GF02170X012	Orange	1	2.2 to 4.2	3.5
	3		1.5 to 7.3	FA142869X12	Orange Stripe	2.6 to 5.6	GF02171X012	Pink	2	4.6 to 7.6	5
	5		1.5 to 7.3	FA142869X12	Orange Stripe	2.6 to 5.6	GF02171X012	Pink	3	5.6 to 8.6	7
10	1.5 to 7.3	FA142869X12	Orange Stripe	3.5 to 8.2	GF02172X012	Green	5	8.5 to 13.2	12		
15	1.5 to 10.9	T14171T0012	Olive	6.7 to 13.5	GF02173X012	Silver	7	13.7 to 20.5	19		
VS112 VS122	20	VSX4H VSX8H (232 psi)	7.3 to 29.0	FA142869X12	Orange Stripe	15.2 to 22.8	GF02171X012	Pink	10	25.2 to 32.8	25
	30		7.3 to 29.0	FA142869X12	Orange Stripe	18.1 to 33.4	GF02172X012	Green	15	33.1 to 48.4	35

**Table 4d. Overpressure and Underpressure Shut-off OPSO/USPO Ranges, bar**

REGULATOR		SLAM SHUT DEVICE									
Type	Typical Setpoint bar	Type (Maximum Operating Inlet)	Under Pressure Shut-off (USPO)	Spring Part Number	Spring Color	Over Pressure Shut-off (OPSO)	Spring Part Number	Spring Color	Factory Set		
			Set Range			Set Range			USPO	Adjusted OPSO Range	OPSO
			bar			bar					
VS111 VS121	17.4 mbar	VSX4L VSX8L (125 psi / 8.62 bar)	7.47 to 30.0 mbar	ERAA05835A0	White	39.9 to 72.2 mbar	GF02168X012	Brown	7.47 mbar	47.3 mbar to 0.08 bar	54.8 mbar
	27.4 mbar		7.47 to 30.0 mbar	ERAA05835A0	White	39.9 to 72.2 mbar	GF02168X012	Brown	14.9 mbar	54.8 mbar to 0.09 bar	62.3 mbar
	34.9 mbar		9.96 mbar to 0.76 bar	T14169T0012	Blue	49.8 mbar to 0.12 bar	GF02169X012	Red	22.4 mbar	0.15 to 0.07	0.08
	0.07		24.9 mbar to 0.16 bar	T14169T0012	Blue	0.08 to 0.22	GF02169X012	Red	34.9 mbar	0.12 to 0.26	0.14
	0.14		24.9 mbar to 0.16 bar	T14169T0012	Blue	0.08 to 0.22	GF02170X012	Orange	0.07	0.15 to 0.29	0.24
	0.21		0.10 to 0.50	T14170T0012	Silver	0.18 to 0.39	GF02171X012	Pink	0.14	0.32 to 0.52	0.35
	0.35		0.10 to 0.50	FA142869X12	Orange Stripe	0.18 to 0.39	GF02171X012	Pink	0.21	0.39 to 0.59	0.48
0.69	0.10 to 0.50	FA142869X12	Orange Stripe	0.24 to 0.57	GF02172X012	Green	0.35	0.59 to 0.91	0.83		
VS111 VS121	17.4 mbar	VSX4L VSX8L (232 psi / 16.0 bar)	7.47 to 30.0 mbar	ERAA05835A0	White	44.8 to 74.7	GF02168X012	Brown	7.47 mbar	52.3 mbar to 0.08 bar	54.8 mbar
	27.4 mbar		7.47 to 30.0 mbar	ERAA05835A0	White	44.8 to 74.7	GF02168X012	Brown	14.9 mbar	59.8 mbar to 0.09	62.3 mbar
	34.9 mbar		9.96 mbar to 0.76 bar	T14169T0012	Blue	62.3 mbar to 0.13 bar	GF02169X012	Red	22.4 mbar	0.08 to 0.15	0.08
	0.07		24.9 mbar to 0.16 bar	T14169T0012	Blue	0.08 to 0.22	GF02170X012	Orange	34.9 mbar	0.12 to 0.26	0.14
	0.14		24.9 mbar to 0.16 bar	T14170T0012	Silver	0.08 to 0.22	GF02170X012	Orange	0.07	0.15 to 0.29	0.24
	0.21		0.10 to 0.50	FA142869X12	Orange Stripe	0.18 to 0.39	GF02171X012	Pink	0.14	0.32 to 0.52	0.35
	0.35		0.10 to 0.50	FA142869X12	Orange Stripe	0.18 to 0.39	GF02171X012	Pink	0.21	0.39 to 0.59	0.48
0.69	0.10 to 0.50	FA142869X12	Orange Stripe	0.24 to 0.57	GF02172X012	Green	0.35	0.59 to 0.91	0.83		
1.03	0.10 to 0.75	T14171T0012	Olive	0.46 to 0.93	GF02173X012	Silver	0.48	0.95 to 1.41	1.31		
VS112 VS122	1.38	VSX4H VSX8H (232 psi / 16.0 bar)	0.50 to 2.0	FA142869X12	Orange Stripe	1.05 to 1.57	GF02171X012	Pink	0.69	1.74 to 2.26	1.72
	2.07		0.50 to 2.0	FA142869X12	Orange Stripe	1.25 to 2.30	GF02172X012	Green	1.03	2.28 to 3.34	2.41






Figure 4. VS100 Series Dimensions

Table 5. VS100 Series Body, Dimension and Weight

TYPE	BODY MATERIAL	INLET SIZE, NPS	OUTLET SIZE, NPS	END CONNECTION	DIMENSION, In. / mm				WEIGHT					
					A	B	C	D	E	F	lbs	kg		
VS111 and VS112 (Medium Capacity)	Ductile Iron	1	2-1/4	Rp x GAZ	4.1 / 105	2.2 / 55	2.6 / 67	8.1 / 205	5.8 / 147	4.7 / 118	7.3	3.3		
		1-1/4	1-1/4	Rp	4.5 / 114	2.3 / 57					7.9	3.6		
		1-1/2	1-1/2	Rp							7.9	3.6		
		1	1	NPT							3.9 / 100	2.0 / 50	6.8	3.1
		1	1	Rp	6.8	3.1								
		1-1/4	1-1/4	NPT	4.5 / 114	2.3 / 57							7.9	3.6
		1-1/2	1-1/2	NPT									7.9	3.6
	1-1/2	1-1/2	PN 16 slip-on	7.2 / 184	2.3 / 57	1.8 / 46.3	8.3 / 210	5.8 / 147	4.7 / 118	14.8	6.7			
	Steel	1	1	NPT	3.9 / 100	2.0 / 50	2.6 / 67	8.1 / 205	5.8 / 147	4.7 / 118	6.8	3.1		
		1-1/4	1-1/4	NPT	4.5 / 114	2.3 / 57					7.9	3.6		
		1-1/2	1-1/2	NPT	4.5 / 114	2.3 / 57					7.9	3.6		
		1	1	Rp	3.9 / 100	2.0 / 50					6.8	3.1		
		1-1/4	1-1/4	Rp	4.5 / 114	2.3 / 57					7.9	3.6		
		1-1/2	1-1/2	Rp	4.5 / 114	2.3 / 57					7.9	3.6		
2		2	Rp	4.5 / 114	2.3 / 57	15.2					6.9			
VS121 (High Capacity)	Ductile Iron	1-1/4	1-1/4	NPT	6.1 / 155	3.1 / 77.5	3.6 / 91.4	8.4 / 212.7	5.8 / 147	4.6 / 118	15.2	6.9		
		1-1/2	1-1/2	NPT							15.2	6.9		
		2	2	NPT							15.7	7.1		
		1-1/4	1-1/4	Rp							15.2	6.9		
		1-1/2	1-1/2	Rp							15.2	6.9		
		2	2	Rp							15.7	7.1		
		2	2	CL125 FF x CL150 FF	7.5 / 191	3.8 / 95.5					29.1	13.2		
		2	2	CL125 FF x CL150 FF	10 / 254	5.0 / 127					34.8	15.8		
		2	2	CL125 FF x CL150 FF	11 / 267	5.3 / 133.5					34.8	15.8		
		2	2	PN 10/16	7.5 / 191	3.8 / 95.5					29.1	13.2		
	2	2	PN 10/16	10 / 254	5.0 / 127	34.8	15.8							
	Steel	1-1/4	1-1/4	NPT	6.1 / 155	3.1 / 77.5	3.6 / 91.4	8.4 / 212.7	5.8 / 147	4.6 / 118	15.2	6.9		
		1-1/2	1-1/2	NPT							15.2	6.9		
		2	2	NPT							15.7	7.1		
1-1/4		1-1/4	Rp	15.2							6.9			
1-1/2		1-1/2	Rp	15.2							6.9			
2		2	Rp	15.7							7.1			
2	2	CL150 RF	10 / 254	5.0 / 127	34.2	15.5								
2	2	PN 10/16	10 / 254	5.0 / 127	34.2	15.5								

Note: Reset trip clearance 1.0 in. / 25 mm on all sizes.

## Ordering Guide

### Type (Select One)

- VS111     VS112     VS121     VS122

### Slam-Shut Controller Type (Select One)

- VSX4L     VSX4H     VSX8L     VSX8H

### Body Size and End Connection Style (Select One)

#### Ductile Iron

##### Medium Capacity

- 1 NPT  
 1-1/4 NPT  
 1-1/2 NPT  
 NPS 1 / DN 25, Rp x GAZ  
 NPS 1-1/4 / DN 32, Rp  
 NPS 1-1/2 / DN 40, Rp  
 NPS 1 / DN 25, Rp  
 NPS 1-1/2 / DN 40, PN 16 slip-on

##### High Capacity

- 1-1/4 NPT  
 1-1/2 NPT  
 2 NPT  
 NPS 1-1/4 / DN 32, Rp  
 NPS 1-1/2 / DN 40, Rp  
 NPS 2 / DN 50, Rp  
 NPS 2 / DN 50, CL125 FF x CL150 FF  
 NPS 2 / DN 50, PN 10/16

#### WCC Steel

##### Medium Capacity

- 1 NPT  
 1-1/4 NPT  
 1-1/2 NPT  
 NPS 1 / DN 25, Rp  
 NPS 1-1/4 / DN 32, Rp  
 NPS 1-1/2 / DN 40, Rp

##### High Capacity

- 1-1/4 NPT  
 1-1/2 NPT  
 2 NPT  
 NPS 1-1/4 / DN 32, Rp  
 NPS 1-1/2 / DN 40, Rp  
 NPS 2 / DN 50, Rp  
 NPS 2 / DN 50, CL150 FF  
 NPS 2 / DN 50, PN 10/16

### Slam-Shut Trip Pressure Setting (Select One)

- Overpressure (OPSO) trip only  
 Indicate Overpressure Trip Point \_\_\_\_\_
- Over and Underpressure (OPSO/UPS0) trip  
 Indicate Overpressure Trip Point \_\_\_\_\_  
 Indicate Underpressure Trip Point \_\_\_\_\_

### Specification Worksheet

#### Application

- Specific Use: \_\_\_\_\_
- Line Size: \_\_\_\_\_
- Gas Type and Specific Gravity: \_\_\_\_\_
- Gas Temperature: \_\_\_\_\_
- Relief Valve Size**
- Brand of upstream regulator? \_\_\_\_\_
- Orifice size of the upstream regulator? \_\_\_\_\_
- Wide-open coefficient of the upstream regulator? \_\_\_\_\_

#### Pressure

- Maximum Inlet Pressure: \_\_\_\_\_
- Downstream Pressure: \_\_\_\_\_
- Differential Pressure: \_\_\_\_\_
- Relief (Inlet) Set Pressure: \_\_\_\_\_
- Maximum Flow: \_\_\_\_\_

#### Performance Required

- Accuracy requirements? \_\_\_\_\_
- Need for extremely fast response? \_\_\_\_\_

#### Other Requirements:

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
[Emerson.com/ContactUs](http://Emerson.com/ContactUs)

### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

Adequate overpressure protection should be installed to protect the regulator from overpressure. Adequate overpressure protection should also be installed to protect all downstream equipment in the event of regulator failure.

**Introduction**

VFA Series butterfly valves are wafer flangeless type and are used typically in gas reducing stations for an on-off service. They have very low pressure losses and excellent seal due to their particular construction features.

Their reduced overall dimensions allow simple installation and easy maintenance.

**Types**

**Type VFA:** Lever-operated

Type VFA-MR: Gear-operated

Type VFA-MRO: Gear-operated for use with absorbing odorizer

**Allowable Pressure**

**PN 16:** 232 psig/ 16 bar

CL150 RF: 276 psig/19 bar

**Flanged Connections**

NPS 2, 2-1/2, 3, 4, 5, 6, 8 and 10 /  
DN 50, 65, 80, 100, 125, 150, 200 and 250

**Flanged Rating**

PN16 UNI/DIN  
CL150 RF

**Temperature Capabilities**

**Standard Version:**

Working: 14 to 140°F / -10 to 60°C

**Low Temperature Version:**

Working: -4 to 140°F / -20 to 60°C

**Applications**

- Non-corrosive Gases (natural gases, compressed air, nitrogen, etc.)
- Clean Fluids

**Materials**

**Body:** Steel

Disk: Pressed steel

Shaft: Stainless steel

Gasket: Nitrile (NBR) **(standard)** or Fluorocarbon (FKM)



Figure 1. Type VFA



Figure 2. Type VFA-MR




Figure 3. Type VFA Dimension

**Additional Technical Data**

Scan or Click the QR code for more information on this product.

[www.Emerson.com](http://www.Emerson.com)



02/15

**Features**

- Hermetic Seal
- Compact Design
- Easy Installation in All Positions
- Easy Maintenance
- Very Low Pressure Loss

# VFA Series

## Butterfly Valve Soft Sealed Body

TARTARINI™




Figure 4. Types VFA-MR and VFA-MRO Dimension

Table 1. VFA Series Dimension and Shipping Weight

BODY SIZE		DIMENSION										APPROXIMATE SHIPPING WEIGHT	
		A		B				C		D			
				PN 16		CL150 RF							
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lb	kg
2	50	1.69	43	5.35	136	6.81	173	5.79	147	18.5	470	26	12
2-1/2	65	1.81	46	5.47	139	7.44	189	6.18	157	18.5	470	31	14
3	80	1.81	46	5.87	149	7.44	189	6.42	163	18.5	470	40	18
4	100	2.05	52	6.26	159	8.19	208	6.85	174	18.5	470	46	21
5	125	2.20	56	6.65	169	9.33	237	8.23	209	19.3	490	64	29
6	150	2.20	56	6.65	169	9.33	237	8.94	227	19.3	490	79	36
8	200	2.36	60	7.36	187	10.5	267	9.92	252	19.3	490	112	51
10	250	2.68	68	8.43	214	10.9	278	9.41	239	20.9	530	214	97

Table 2. Types VFA-MR and VFA-MRO Dimension and Shipping Weight

BODY SIZE		DIMENSION												APPROXIMATE SHIPPING WEIGHT			
		A		B				E		F		G				H	
				PN 16		CL150 RF											
NPS	DN	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	lb	kg
2	50	1.69	43	5.35	136	6.81	173	6.30	160	7.48	190	4.92	125	4.72	120	31	14
2-1/2	65	1.81	46	5.47	139	7.44	189	6.30	160	7.87	200	4.92	125	4.72	120	35	16
3	80	1.81	46	5.87	149	7.44	189	6.30	160	8.07	205	4.92	125	4.72	120	44	20
4	100	2.05	52	6.26	159	8.19	208	6.30	160	8.46	215	4.92	125	4.72	120	51	23
5	125	2.20	56	6.65	169	9.33	237	11.8	300	13.2	335	11.8	300	6.61	168	77	35
6	150	2.20	56	6.65	169	9.33	237	11.8	300	13.6	345	11.8	300	6.61	168	93	42
8	200	2.36	60	7.36	187	10.5	267	11.8	300	14.8	375	11.8	300	6.61	168	126	57
10	250	2.68	68	8.43	214	10.9	278	11.8	300	16.9	430	11.8	300	6.61	168	227	103



## Ordering Guide

**Type (Select One)**

VFA\*\*\*

VFA-MR\*\*\*

VFA-MRO\*\*\*

**Flanged Connection (Select One)**

NPS 2 / DN 50\*\*\*

NPS 2-1/2 / DN 65\*\*\*

NPS 3 / DN 80\*\*\*

NPS 4 / DN 100\*\*\*

NPS 5 / DN 125\*\*\*

NPS 6 / DN 150\*\*\*

NPS 8 / DN 200\*\*\*

NPS 10 / DN 250\*\*\*

**Flanged Rating (Select One)**

PN 16 UNI/DIN\*\*\*

CL150 RF\*\*\*

**Elastomer Part (Select One)**

Nitrile (NBR)\*\*\*

Fluorocarbon (FKM)\*\*

**Temperature Construction (Select One)**

**Standard** (14 to 140°F / -10 to 60°C)\*\*\*

Low Temperature (-4 to 140°F / -20 to 60°C)\*\*

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

Regulators Quick Order Guide	
***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

### Regulator Tip:

Four easy ways to find the products you need:

1. Section headers at the top of each page are grouped by application of product (i.e., Natural Gas).
2. The Product Index at the back of this Application Guide contains a detailed list of products arranged by type and application.
3. If you know the application and product number, turn to the Application Map of that section and locate the Section Outline which indexes all of the products found in that section.
4. Look for the product type number in the Quick Reference Chart in the Table of Contents.

# V Series

## Spring-Loaded Relief Valve

TARTARINI™

### Introduction

The spring-loaded relief valves are designed to keep line pressure below preset values. They are mounted downstream of regulators and perform the specific function of releasing small amounts of gas in the event of the regulator not closing perfectly.

V Series relief valves are ideal for use in civil and industrial equipment employing natural gas, propane, butane and noncorrosive gases in general because of their effective release capacity and compact size. The valves are extremely easy to install and are designed for ready and easy maintenance.

The V/50 and V/60 Series relief valves are especially designed for use with low pressures. Their construction features ensure a very low hysteresis value and maximum operation accuracy and sensitivity.

Type V/20-2 relief valve is designed for use at medium and high pressures and cover a wide range of pressure set values, i.e., from 21.8 to 580 psig / 1.5 to 40 bar.

To change setting, simply replace the spring with the one appropriate for the desired value.

### Allowable Pressures

#### V/50 Series:

58 psig / 4.0 bar

#### V/60 Series:

36 psig / 2.5 bar

#### Type V/20-2:

1450 psig / 100 bar

### Set Pressure Ranges ( $W_h$ )

#### Type V/50:

0.36 to 1.16 psig / 0.025 to 0.08 bar

#### Type V/51:

1.09 to 10.9 psig / 0.075 to 0.75 bar

#### Type V/52:

10.2 to 29 psig / 0.70 to 2.0 bar

#### Type V/60:

0.36 to 1.3 psig / 0.025 to 0.09 bar

#### Type V/61:

1.16 to 10.9 psig / 0.08 to 0.75 bar

#### Type V/62:

10.2 to 29 psig / 0.70 to 2.0 bar

#### Type V/20-2:

21.8 to 580 psig / 1.5 to 40.0 bar

### Seat Diameter

V/50 Series: 1-1/4 in. / 32 mm

V/60 Series: 1-1/2 in. / 40 mm

Type V/20-2: 1 in. / 25.4 mm

### Threaded Connections

V/50 Series: 1 x 1-1/2 in. BSP

V/60 Series: 1-1/2 x 2 in. BSP

Type V/20-2: 1 in. NPT

### Temperature Capabilities

#### Standard:

14 to 140°F / -10 to 60°C

#### Low Temperature:

-4 to 140°F / -20 to 60°C

### Approximate Weights:

V/50 Series: 2.9 lbs / 1.3 kg

V/60 Series: 4.2 lbs / 1.9 kg

Type V/20-2: 3.5 lbs / 1.6 kg

### Applications

Natural Gas  
Propane  
Butane  
Non-corrosive gases

### Additional Technical Data

Scan or Click the QR code for more information on this product.



[www.Emerson.com](http://www.Emerson.com)

12/13

### Features

- Types V/50 and V/60: for Very Low Pressure Applications
- Types V/51 and V/61: for Low Pressure Applications
- Types V/52 and V/62: for Medium Pressure Applications
- Type V/20-2: for Medium and High Pressure Applications



P1419

Figure 1. Type V/50 Spring-Loaded Relief Valve



Figure 2. Type V/60 Spring-Loaded Relief Valve



Figure 3. Type V/20-2 Spring-Loaded Relief Valve




Figure 4. Type V/50 Flow Capacity Curve




Figure 5. Type V/51 Flow Capacity Curve

Table 1. V/50 and V/60 Series Construction Material

BODY	COVER	VALVE SEAT	DIAPHRAGM	GASKET
Aluminum	Aluminum	Brass	Fabric Nitrile (NBR)	Nitrile (NBR)

Table 2. Type V/20-2 Construction Material

BODY	PAD RETAINER	PAD HOLDER	ADJUSTING RING	OUTLET CONNECTION	PAD
Brass	Brass	Brass	Brass	Brass	Nitrile (NBR)

# V Series

## Spring-Loaded Relief Valve

TARTARINI™




Figure 6. Type V/52 Flow Capacity Curve




Figure 7. Type V/60 Flow Capacity Curve




Figure 8. Type V/61 Flow Capacity Curve






Figure 9. Type V/62 Flow Capacity Curve




Figure 10. V/50 and V/60 Series Dimensions




Figure 11. Type V/20-2 Dimensions

IN. /  
mm

Table 3. V/50 and V/60 Series Dimension

SERIES	DIMENSION							
	A		B (Diameter)		C		D	
	In.	mm	In.	mm	In.	mm	In.	mm
V/50	9.29	236	6.46	164	1.70	43	3.74	95
V/60	10.16	258	7.80	198	2.76	70	4.33	110

### Ordering Guide

#### Type (Select One)

- V/50\*\*\*
- V/51\*\*\*
- V/52\*\*\*
- V/60\*\*\*
- V/61\*\*\*
- V/62\*\*\*
- V/20-2\*\*\*

#### Setpoint (Please Specify)

#### Maximum Flow Rate (Please Specify)

To order this product, complete the Ordering Guide Section or complete the Specification Worksheet and forward to your local Sales Office.

If the construction you need is not offered on this page, contact your local Sales Office.

To locate your local Sales Office log on to:  
Emerson.com/ContactUs

#### Regulators Quick Order Guide

***	Readily Available for Shipment
**	Allow Additional Time for Shipment
*	Special Order, Constructed from Non-Stocked Parts. Consult your local Sales Office for Availability.
Availability of the product being ordered is determined by the component with the longest shipping time for the requested construction.	

#### Specification Worksheet

<b>Application</b>
<input type="checkbox"/> Relief Valve <input type="checkbox"/> Backpressure Regulator
Specific Use:
Line Size:
Gas Type and Specific Gravity:
Gas Temperature:
<b>Relief Valve Size</b>
Brand of upstream regulator?
Orifice size of the upstream regulator?
Wide-open coefficient of the upstream regulator?
<b>Pressure</b>
Maximum Inlet Pressure:
Downstream Pressure:
Differential Pressure:
Relief (Inlet) Set Pressure:
Maximum Flow:
<b>Performance Required</b>
Accuracy requirements?
Need for extremely fast response?
<b>Other Requirements:</b>

#### Regulator Tip:

Keep vents open. Do not use small diameter, long vent lines. Use the rule of thumb of the next nominal pipe size every 10 feet / 3.1 m of vent line and 3 feet / 0.9 m of vent line for every elbow in the line.



The need for training is more critical than ever to achieving and maintaining cost-effective operations.

Emerson’s Educational Services offers various courses and other training programs to provide the knowledge and skills to operate, maintain and manage pressure regulators and systems within customers’ operations. Through a mixture of theoretical and practical applications, training program participants learn the fundamentals of and advancements in, pressure control and regulator operations and maintenance.

Whether it is classroom-based training, web-based discussions or eLearning programs, Emerson works hard to ensure customers know how to get the best from their entire process and operation.

For more information, contact Educational Services.

**Educational Services**  
**Tel:** 972-548-3534  
**Email:** [Education.Regulators@Emerson.com](mailto:Education.Regulators@Emerson.com)

# Technical



**The Technical Reference section** includes articles covering regulator theory, sizing, selection, overpressure protection and other topics relating to regulators. This section begins with the basic theory of regulators and ends with conversion tables and other informative charts.

This section is for general reference only. For additional information please contact your local Sales Office.



## Regulator Control Theory

Fundamentals of Gas Pressure Regulators .....	542
Pilot-Operated Regulators .....	543
Conclusion .....	543

## Regulator Components

Straight Stem Style Direct-Operated .....	544
Lever Style Direct-Operated .....	545
Loading Style (Two-Path Control) Pilot-Operated .....	546
Unloading Style Pilot-Operated .....	547

## Introduction to Regulators

Specific Regulator Types .....	548
Pressure Reducing Regulators .....	548
Backpressure Regulators and Relief Valves .....	549
Pressure Switching Valves .....	549
Vacuum Regulators and Breakers .....	549
Types of Pressure Reducing Regulators .....	548
Direct-Operated (Self-Operated) Regulators .....	548
Pilot-Operated Regulators .....	548
Regulator Selection Criteria .....	550
Control Application .....	550
Pressure Reducing Regulator Selection .....	550
Outlet Pressure to be Controlled .....	550
Inlet Pressure of the Regulator .....	550
Capacity Required .....	550
Shutoff Capability .....	550
Process Fluid .....	551
Process Fluid Temperature .....	551
Accuracy Required .....	551
Pipe Size Required .....	551
End Connection Style .....	551
Required Materials .....	551
Control Lines .....	551
Stroking Speeds .....	551
Overpressure Protection .....	551
Regulator Replacement .....	552
Regulator Price .....	552

Backpressure Regulator Selection .....	552
Relief Valve Selection .....	552

## Theory

### Principles of Direct-Operated Regulators

Introduction .....	553
Regulator Basics .....	553
Essential Elements .....	553
Restricting Element .....	554
Measuring Element .....	554
Loading Element .....	554
Regulator Operation .....	554
Increasing Demand .....	554
Decreasing Demand .....	554
Weights versus Springs .....	554
Spring Rate .....	555
Equilibrium with a Spring .....	555
Spring as Loading Element .....	555
Throttling Example .....	555
Regulator Operation and $P_2$ .....	556
Regulator Performance .....	556
Performance Criteria .....	556
Setpoint .....	556
Droop .....	556
Capacity .....	556
Accuracy .....	556
Lockup .....	556
Spring Rate and Regulator Accuracy .....	557
Spring Rate and Droop .....	557
Effect on Plug Travel .....	557
Light Spring Rate .....	557
Practical Limits .....	557
Diaphragm Area and Regulator Accuracy .....	557
Diaphragm Area .....	557
Increasing Diaphragm Area .....	558
Diaphragm Size and Sensitivity .....	558
Restricting Element and Regulator Performance .....	558
Critical Flow .....	558
Orifice Size and Capacity .....	558
Orifice Size and Stability .....	559
Orifice Size, Lockup and Wear .....	559

# Table of Contents

Orifice Guideline .....	559
Increasing $P_1$ .....	559
Factors Affecting Regulator Accuracy .....	559
Performance Limits .....	559
Cycling .....	559
Design Variations .....	559
Improving Regulator Accuracy with a Pitot Tube ...	560
Numerical Example .....	560
Decreased Droop (Boost) .....	560
Improving Performance with a Lever .....	560

## Principles of Pilot-Operated Regulators

Pilot-Operated Regulator Basics .....	561
Regulator Pilots .....	561
Gain .....	561
Identifying Pilots .....	561
Setpoint .....	561
Spring Action .....	561
Pilot Advantage .....	561
Gain and Restrictions .....	561
Stability .....	561
Restrictions, Response Time and Gain .....	562
Loading and Unloading Designs .....	562
Two-Path Control (Loading Design) .....	562
Two-Path Control Advantages .....	563
Unloading Control .....	563
Unloading Control Advantages .....	563
Performance Summary .....	563
Accuracy .....	563
Capacity .....	563
Lockup .....	564
Applications .....	564
Two-Path Control .....	564
Type 1098-EGR .....	564
Type 99 .....	565
Unloading Design .....	565

## Selecting and Sizing Pressure Reducing Regulators

Introduction .....	566
Quick Selection Guides .....	566
Product Pages .....	566

Special Requirements .....	566
The Role of Experience .....	566
Sizing Equations .....	566
General Sizing Guidelines .....	567
Body Size .....	567
Construction .....	567
Pressure Ratings .....	567
Wide-Open Flow Rate .....	567
Outlet Pressure Ranges and Springs .....	567
Accuracy .....	567
Inlet Pressure Losses .....	567
Orifice Diameter .....	567
Speed of Response .....	567
Turn-Down Ratio .....	567
Direct-operated Regulators vs Pilot-operated .....	567
Sizing Exercise: Industrial Plant Gas Supply .....	568

## Overpressure Protection Methods

Methods of Overpressure Protection .....	569
Relief Valves .....	569
Types of Relief Valves .....	569
Advantages .....	569
Disadvantages .....	569
Monitoring Regulators .....	570
Advantages .....	570
Disadvantages .....	570
Working Monitor .....	570
Series Regulation .....	570
Advantages .....	571
Disadvantages .....	571
Shutoff Devices .....	571
Advantages .....	571
Disadvantages .....	571
Relief Monitor .....	571
Summary .....	572

## Principles of Relief Valves

Overpressure Protection .....	573
Maximum Pressure Considerations .....	573
Downstream Equipment .....	573
Main Regulator .....	573

# Table of Contents

Piping .....	573	Regulator Lockup Pressure .....	580
Relief Valves .....	573	Identify Appropriate Relief Valves .....	580
Relief Valve Popularity .....	574	Final Selection .....	580
Relief Valve Types .....	574	Applicable Regulations .....	580
Selection Criteria .....	574	Sizing and Selection Exercise .....	580
Pressure Buildup .....	574	Initial Parameters .....	580
Periodic Maintenance .....	574	Performance Considerations .....	580
Cost versus Performance .....	574	Upstream Regulator .....	580
Installation and Maintenance Considerations .....	574	Pressure Limits .....	580
Pop Type Relief Valve .....	574	Relief Valve Flow Capacity .....	580
Operation .....	574	Relief Valve Selection .....	581
Typical Applications .....	575		
Advantages .....	575	<b>Principles of Series Regulation and Monitor Regulators</b>	
Disadvantage .....	575	Series Regulation .....	582
Direct-Operated Relief Valves .....	575	Failed System Response .....	582
Operation .....	575	Regulator Considerations .....	582
Product Example .....	576	Applications and Limitations .....	582
Typical Applications .....	576	Upstream Wide-Open Monitors .....	582
Selection Criteria .....	576	System Values .....	582
Pilot-Operated Relief Valves .....	577	Normal Operation .....	582
Operation .....	577	Worker Regulator B Fails .....	583
Product Example .....	577	Equipment Considerations .....	583
Performance .....	578	Downstream Wide-Open Monitors .....	583
Typical Applications .....	578	Normal Operation .....	583
Selection Criteria .....	578	Worker Regulator A Fails .....	583
Internal Relief .....	578	Upstream Versus Downstream Monitors .....	583
Operation .....	578	Working Monitors .....	583
Product Example .....	578	Downstream Regulator .....	584
Performance and Typical Applications .....	579	Upstream Regulator .....	584
Selection Criteria .....	579	Normal Operation .....	584
Selection and Sizing Criteria .....	579	Downstream Regulator Fails .....	584
Maximum Allowable Pressure .....	579	Upstream Regulator Fails .....	584
Regulator Ratings .....	579	Sizing Monitor Regulators .....	584
Piping .....	579	Estimating Flow when Pressure Drop is Critical .....	584
Maximum Allowable System Pressure .....	579	Assuming $P_{intermediate}$ to Determine Flow .....	584
Determining Required Relief Valve Flow .....	579	Fisher Monitor Sizing Program .....	584
Determine Constant Demand .....	580		
Selecting Relief Valves .....	580	<b>Vacuum Control</b>	
Required Information .....	580	Vacuum Applications .....	585

# Table of Contents

Vacuum Terminology .....	585
Vacuum Control Devices .....	585
Vacuum Regulators .....	585
Vacuum Breakers (Relief Valves) .....	585
Vacuum Regulator Installation Examples .....	587
Vacuum Breaker Installation Examples.....	588
Gas Blanketing in Vacuum .....	590
Features of Fisher™ Brand Vacuum Regulators and Breakers .....	590

## Valve Sizing Calculations (Traditional Method)

Introduction .....	591
Sizing for Liquid Service .....	591
Viscosity Corrections .....	591
Finding Valve Size .....	591
Predicting Flow Rate .....	593
Predicting Pressure Drop .....	593
Flashing and Cavitation .....	593
Choked Flow .....	594
Liquid Sizing Summary .....	596
Liquid Sizing Nomenclature .....	596
Sizing for Gas or Steam Service .....	597
Universal Gas Sizing Equation .....	597
General Adaptation for Steam and Vapors .....	598
Special Equation for Steam Below 1000 psig .....	598
Gas and Steam Sizing Summary .....	598

## Valve Sizing (Standardized Method)

Introduction .....	600
Liquid Sizing .....	600
Sizing Valves for Liquids .....	600
Determining Allowable Sizing Pressure Drop ( $\Delta P_{max}$ ) .....	603
Liquid Sizing Sample Problem .....	603
Gas and Steam Sizing .....	606
Sizing Valves for Compressible Fluids .....	606
Compressible Fluid Sizing Sample Problem .....	607

## Temperature Considerations

### Cold Temperature Considerations

Regulators Rated for Low Temperatures .....	612
Selection Criteria .....	612

### Freezing

Introduction .....	613
Reducing Freezing Problems .....	613
Heat the Gas .....	613
Antifreeze Solution .....	613
Equipment Selection .....	613
System Design .....	614
Water Removal .....	614
Summary .....	614

## Sulfide Stress Cracking— NACE MR0175-2002, MR0175/ISO 15156

The Details .....	615
These NACE Standards are Applied to .....	615
NACE MR0175-2002 and Prior .....	615
NACE MR0175/ISO 15156 .....	616
NACE MR0103 .....	617
Exposed Bolting .....	617
Coatings .....	617
Elastomers .....	617

## Reference

### Chemical Compatibility of Elastomers and Metals

Introduction .....	618
Elastomers: Chemical Names and Uses .....	618
General Properties of Elastomers .....	619
Fluid Compatibility of Elastomers .....	620
Compatibility of Metals .....	621

### Regulator Tips

Regulator Tips .....	623
----------------------	-----

# Table of Contents

## Conversions, Equivalents and Physical Data

Pressure Equivalents	629	Average Properties of Propane	657
Pressure Conversion - Pounds per Square Inch (PSI) to Bar	629	Orifice Capacities for Propane	657
Volume Equivalents	629	Standard Domestic Propane Tank Specifications	657
Volume Rate Equivalents	630	Approximate Vaporization Capacities of Propane Tanks	657
Mass Conversion—Lbs to kg	630	Pipe and Tubing Sizing	658
Temperature Conversion Formulas	630	Vapor Pressures of Propane	658
Area Equivalents	630	Converting Volumes of Gas	658
Kinematic-Viscosity Conversion Formulas	630	BTU Comparisons	658
Conversion Units	631	Capacities of Spuds and Orifices	659
Other Useful Conversions	631	Kinematic Viscosity - Centistokes	662
Converting Volumes of Gas	631	Specific Gravity of Typical Fluids vs Temperature	663
Fractional In. to mm	632	Effect of Inlet Swage On Critical Flow C <sub>g</sub> Requirements	664
Length Equivalents	632	Seat Leakage Classifications	665
Whole In.-mm Equivalents	632	Class VI Seat Leakage Allowable	661
Metric Prefixes and Symbols	632	Flange, Valve Size and Pressure-Temperature Rating Designations	666
Greek Alphabet	632	Pipe Thread Standards	666
Length Equivalents - Fractional and Decimal In. to mm	633	Pressure-Temperature Ratings for Valve Bodies	667
Temperature Conversions	634	Diameter of Bolt Circles	669
A.P.I. and Baumé Gravity Tables and Weight Factors	637	ASME Face-To-Face Dimensions for Flanged Regulators	669
Characteristics of the Elements	638	Wear and Galling Resistance Chart of Material Combinations	670
Recommended Standard Specifications for Valve Materials Pressure-Containing Castings	639	Equivalent Lengths of Pipe Fittings and Valves	670
Physical Constants of Hydrocarbons	642	Pipe Data: Carbon and Alloy Steel—Stainless Steel	671
Physical Constants of Various Fluids	643	American Pipe Flange Dimensions	673
Properties of Water	645	EN 1092-1 Cast Steel Flange Standards	673
Properties of Saturated Steam	645	EN 1092-1 Pressure/Temperature Ratings for Cast Steel Valve Ratings	673
Properties of Saturated Steam—Metric Units	648	Drill Sizes for Pipe Taps	675
Properties of Superheated Steam	649	Standard Twist Drill Sizes	675
Determine Velocity of Steam in Pipes	652		
Recommended Steam Pipe Line Velocities	652		
Typical Condensation Rates in Insulated Pipes	652		
Typical Condensation Rates without Insulation	652		
Flow of Water Through Schedule 40 Steel Pipes	653		
Flow of Air Through Schedule 40 Steel Pipes	655		
		<b>Glossary</b>	
		Glossary of Terms	676

# Regulator Control Theory

## Fundamentals of Gas Pressure Regulators

The primary function of any gas regulator is to match the flow of gas through the regulator to the demand for gas placed upon the system. At the same time, the regulator must maintain the system pressure within certain acceptable limits.

A typical gas pressure system might be similar to that shown in Figure 1, where the regulator is placed upstream of the valve or other device that is varying its demand for gas from the regulator.




Figure 1

If the load flow decreases, the regulator flow must decrease also. Otherwise, the regulator would put too much gas into the system and the pressure ( $P_2$ ) would tend to increase. On the other hand, if the load flow increases, then the regulator flow must increase also in order to keep  $P_2$  from decreasing due to a shortage of gas in the pressure system.

From this simple system, it is easy to see that the prime job of the regulator is to put exactly as much gas into the piping system as the load device takes out.

If the regulator were capable of instantaneously matching its flow to the load flow, then we would never have major transient variation in the pressure ( $P_2$ ) as the load changes rapidly. From practical experience we all know that this is normally not the case, and in most real-life applications, we would expect some fluctuations in  $P_2$  whenever the load changes abruptly.

Because the regulator's job is to modulate the flow of gas into the system, we can see that one of the essential elements of any regulator is a restricting element that will fit into the flow stream and provide a variable restriction that can modulate the flow of gas through the regulator.

Figure 2 shows a schematic of a typical regulator restricting element. This restricting element is usually some type of valve arrangement. It can be a single-port globe valve, a cage style valve, butterfly valve or any other type of valve that is capable of operating as a variable restriction to the flow.

In order to cause this restricting element to vary, some type of loading force will have to be applied to it. Thus we see that the second essential element of a gas regulator is a Loading Element that can apply the needed force to the restricting element.




Figure 2

The loading element can be one of any number of things such as a weight, a hand jack, a spring, a diaphragm actuator or a piston actuator, to name a few of the more common ones.

A diaphragm actuator and a spring are frequently combined, as shown in Figure 3, to form the most common type of loading element. A loading pressure is applied to a diaphragm to produce a loading force that will act to close the restricting element. The spring provides a reverse loading force which acts to overcome the weight of the moving parts and to provide a fail-safe operating action that is more positive than a pressure force.

So far, we have a restricting element to modulate the flow through the regulator and we have a loading element that can apply the necessary force to operate the restricting element. But, how do we know when we are modulating the gas flow correctly? How do we know when we have the regulator flow matched to the load flow? It is rather obvious that we need some type of Measuring Element which will tell us when these two flows have been perfectly matched. If we had some economical method of directly measuring these flows, we could use that approach; however, this is not a very feasible method.




Figure 3

We noted earlier in our discussion of Figure 1 that the system pressure ( $P_2$ ) was directly related to the matching of the two flows. If the restricting element allows too much gas into the system,  $P_2$  will increase. If the restricting element allows too little gas into the system,  $P_2$  will decrease. We can use this convenient fact to provide a

simple means of measuring whether or not the regulator is providing the proper flow.

Manometers, Bourdon tubes, bellows, pressure gauges and diaphragms are some of the possible measuring elements that we might use. Depending upon what we wish to accomplish, some of these measuring elements would be more advantageous than others. The diaphragm, for instance, will not only act as a measuring element which responds to changes in the measured pressure, but it also acts simultaneously as a loading element. As such, it produces a force to operate the restricting element that varies in response to changes in the measured pressure. If we add this typical measuring element to the loading element and the restricting element that we selected earlier, we will have a complete gas pressure regulator as shown in Figure 4.




Figure 4

Let's review the action of this regulator. If the restricting element tries to put too much gas into the system, the pressure ( $P_2$ ) will increase. The diaphragm, as a measuring element, responds to this increase in pressure and, as a loading element, produces a force which compresses the spring and thereby restricts the amount of gas going into the system. On the other hand, if the regulator doesn't put enough gas into the system, the pressure ( $P_2$ ) falls and the diaphragm responds by producing less force. The spring will then overcome the reduced diaphragm force and open the valve to allow more gas into the system. This type of self-correcting action is known as negative feedback. This example illustrates that there are three essential elements needed to make any operating gas pressure regulator. They are a restricting element, a loading element and a measuring element. Regardless of how sophisticated the system may become, it still must contain these three essential elements.

## Pilot-Operated Regulators

So far we have only discussed direct-operated regulators. This is the name given to that class of regulators where the measured pressure is applied directly to the loading element with no intermediate hardware. There are really only two

basic configurations of direct-operated regulators that are practical. These two basic types are illustrated in Figures 4 and 5.




Figure 5

If the proportional band of a given direct-operated regulator is too great for a particular application, there are a number of things we can do. From our previous examples we recall that spring rate, valve travel and effective diaphragm area were the three parameters that affect the proportional band. In the last section we pointed out the way to change these parameters in order to improve the proportional band. If these changes are either inadequate or impractical, the next logical step is to install a pressure amplifier in the measuring or sensing line. This pressure amplifier is frequently referred to as a pilot.


## Conclusion

It should be obvious at this point that there are fundamentals to understand in order to properly select and apply a gas regulator to do a specific job. Although these fundamentals are profuse in number and have a sound theoretical base, they are relatively straightforward and easy to understand.

As you are probably aware by now, we made a number of simplifying assumptions as we progressed. This was done in the interest of gaining a clearer understanding of these fundamentals without getting bogged down in special details and exceptions. By no means has the complete story of gas pressure regulation been told. The subject of gas pressure regulation is much broader in scope than can be presented in a single document such as this, but it is sincerely hoped that this application guide will help to gain a working knowledge of some fundamentals that will enable one to do a better job of designing, selecting, applying, evaluating or troubleshooting any gas pressure regulation equipment.

# Regulator Components

## Straight Stem Style Direct-Operated Regulator Components



A6555


- INLET PRESSURE
- BOOST PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

Type 133L

**NOTE:**  
THE INFORMATION PRESENTED IS FOR REFERENCE ONLY. FOR MORE SPECIFIC APPLICATION INFORMATION, PLEASE REFERENCE PRODUCT DOCUMENTATION ON: [Emerson.com](http://Emerson.com)



## Lever Style Direct-Operated Regulator Components



A6557


- INLET PRESSURE
- OUTLET PRESSURE
- ATMOSPHERIC PRESSURE

Type 627

**NOTE:**  
THE INFORMATION PRESENTED IS FOR REFERENCE ONLY. FOR MORE SPECIFIC APPLICATION INFORMATION, PLEASE REFERENCE PRODUCT DOCUMENTATION ON: [Emerson.com](http://Emerson.com)

# Regulator Components

## Loading Style (Two-Path Control) Pilot-Operated Regulator Components




A6563

- INLET PRESSURE
- OUTLET PRESSURE
- LOADING PRESSURE
- ATMOSPHERIC PRESSURE

Type 1098-EGR

**NOTE:**  
THE INFORMATION PRESENTED IS FOR REFERENCE ONLY. FOR MORE SPECIFIC APPLICATION INFORMATION,  
PLEASE REFERENCE PRODUCT DOCUMENTATION ON: [Emerson.com](http://Emerson.com)

## Unloading Style Pilot-Operated Regulator Components



W7438

- INLET PRESSURE
- OUTLET PRESSURE
- LOADING PRESSURE
- ATMOSPHERIC PRESSURE

Type EZR

**NOTE:**  
THE INFORMATION PRESENTED IS FOR REFERENCE ONLY. FOR MORE SPECIFIC APPLICATION INFORMATION,  
PLEASE REFERENCE PRODUCT DOCUMENTATION ON: [Emerson.com](http://Emerson.com)

# Introduction to Regulators

Instrument engineers agree that the simpler a system is the better it is, as long as it provides adequate control. In general, regulators are simpler devices than control valves. Regulators are self-contained, direct-operated control devices which use energy from the controlled system to operate whereas control valves require external power sources, transmitting instruments and control instruments.

## Specific Regulator Types

Within the broad categories of direct-operated and pilot-operated regulators fall virtually all of the general regulator designs, including:

- Pressure reducing regulators
- Backpressure regulators
- Pressure relief valves
- Pressure switching valves
- Vacuum regulators and breakers

## Pressure Reducing Regulators

A pressure reducing regulator maintains a desired reduced outlet pressure while providing the required fluid flow to satisfy a downstream demand. The pressure which the regulator maintains is the outlet pressure setting (setpoint) of the regulator.

## Types of Pressure Reducing Regulators

This section describes the various types of regulators. All regulators fit into one of the following two categories:

1. Direct-Operated (also sometimes called Self-Operated)
2. Pilot-Operated

## Direct-Operated (Self-Operated) Regulators

Direct-operated regulators are the simplest style of regulators. At low set pressures, typically below 1 psig / 0.07 bar, they can have very accurate ( $\pm 1\%$ ) control. At high control pressures, up to 500 psig / 34.5 bar, 10 to 20% control is typical.

In operation, a direct-operated, pressure reducing regulator senses the downstream pressure through either internal pressure registration or an external control line. This downstream pressure opposes a spring which moves the diaphragm and valve plug to change the size of the flow path through the regulator.

## Pilot-Operated Regulators

Pilot-operated regulators are preferred for high flow rates or where precise pressure control is required. A popular type of pilot-operated system uses two-path control. In two-path control, the main valve diaphragm responds quickly to downstream pressure changes, causing an immediate correction in the main valve plug position. At the same




Figure 1. Type 627 Direct-Operated Regulator and Operational Schematic




Figure 2. Type 1098-EGR Pilot-Operated Regulator and Operational Schematic

# Introduction to Regulators

time, the pilot diaphragm diverts some of the reduced inlet pressure to the other side of the main valve diaphragm to control the final positioning of the main valve plug. Two-path control results in fast response and accurate control.

## Backpressure Regulators and Pressure Relief Valves

A backpressure regulator maintains a desired upstream pressure by varying the flow in response to changes in upstream pressure. A pressure relief valve limits pressure build-up (prevents overpressure) at its location in a pressure system. The relief valve opens to prevent a rise of internal pressure in excess of a specified value. The pressure at which the relief valve begins to open pressure is the relief pressure setting.

Relief valves and backpressure regulators are the same devices. The name is determined by the application. Fisher™ relief valves are not ASME safety relief valves.




Figure 3. Type 63EG-98HM Pilot-Operated Relief Valve or Backpressure Regulator Schematic

## Pressure Switching Valves

Pressure switching valves are used in pneumatic logic systems. These valves are for either two-way or three-way switching. Two-way switching valves are used for on/off service in pneumatic systems.

Three-way switching valves direct inlet pressure from one outlet port to another whenever the sensed pressure exceeds or drops below a preset limit.




Figure 4. Typical Vacuum Breaker




Figure 5. Typical Vacuum Regulator

## Vacuum Regulators and Breakers

Vacuum regulators and vacuum breakers are devices used to control vacuum. A vacuum regulator maintains a constant vacuum at the regulator inlet with a higher vacuum connected to the outlet. During operation, a vacuum regulator remains closed until a vacuum decrease (a rise in absolute pressure) exceeds the spring setting and opens the valve disk. A vacuum breaker prevents a vacuum from exceeding a specified value. During operation, a vacuum breaker remains closed until an increase in vacuum (a decrease in absolute pressure) exceeds the spring setting and opens the valve disk.

# Introduction to Regulators

## Regulator Selection Criteria

This section describes the procedure normally used to select regulators for various applications. For most applications, there is generally a wide choice of regulators that will accomplish the required function. The vendor and the customer, working together, have the task of deciding which of the available regulators is best suited for the job at hand. The selection procedure is essentially a process of elimination wherein the answers to a series of questions narrow the choice down to a specific regulator.

## Control Application

To begin the selection procedure, it is necessary to define what the regulator is going to do. In other words, what is the control application? The answer to this question will determine the general type of regulator required, such as:

- Pressure reducing regulators
- Backpressure regulators
- Pressure relief valves
- Vacuum regulators
- Vacuum breakers

The selection criteria used in selecting each of these general regulator types is described in greater detail in the following subsections.

## Pressure Reducing Regulator Selection

The majority of applications require a pressure reducing regulator. Assuming the application calls for a pressure reducing regulator, the following parameters must be determined:

- Outlet pressure to be controlled
- Inlet pressure to the regulator
- Capacity required
- Shutoff capability required
- Process fluid
- Process fluid temperature
- Accuracy required
- Pipe size required
- End connection style
- Material requirements
- Control line needed
- Stroking speed
- Overpressure protection

## Outlet Pressure to be Controlled

For a pressure reducing regulator, the first parameter to determine is the required outlet pressure. When the outlet pressure is known, it helps determine:

- Spring requirements
- Casing pressure rating
- Body outlet rating
- Orifice rating and size
- Regulator size

## Inlet Pressure of the Regulator

The next parameter is the inlet pressure. The inlet pressure (minimum and maximum) determines the:

- Pressure rating for the body inlet
- Orifice pressure rating and size
- Main spring (in a pilot-operated regulator)
- Regulator size

If the inlet pressure varies significantly, it can have an effect on:

- Accuracy of the controlled pressure
- Capacity of the regulator
- Regulator style (two-stage or unloading)

## Capacity Required

The required flow capacity influences the following decisions:

- Size of the regulator
- Orifice size
- Style of regulator (direct-operated or pilot-operated)

## Shutoff Capability

The required shutoff capability determines the type of disk material:

- Standard disk materials are Nitrile (NBR) and Neoprene (CR), these materials provide the tightest shutoff.
- Other materials, such as Nylon (PA), Polytetrafluoroethylene (PTFE), Fluorocarbon (FKM) and Ethylenepropylene (EPDM) are used when standard material cannot be used.
- Metal disks are used in high temperatures and when elastomers are not compatible with the process fluid; however, tight shutoff is typically not achieved.

## Process Fluid

Each process fluid has its own set of unique characteristics in terms of its chemical composition, corrosive properties, impurities, flammability, hazardous nature, toxic effect, explosive limits and molecular structure. In some cases special care must be taken to select the proper materials that will come in contact with the process fluid.

## Process Fluid Temperature

Fluid temperature might determine the materials used in the regulator. Standard regulators use Steel and Nitrile (NBR) or Neoprene (CR) elastomers that are good for a temperature range of -40 to 180°F / -40 to 82°C. Temperatures above and below this range may require other materials, such as Stainless steel, Ethylenepropylene (EPDM) or Perfluoroelastomer (FFKM).

## Accuracy Required

The accuracy requirement of the process determines the acceptable droop (also called proportional band or offset). Regulators fall into the following groups as far as droop is concerned:

- **Rough-cut Group** — This group generally includes many first-stage, rough-cut direct-operated regulators. This group usually has the highest amount of droop. However, some designs are very accurate, especially the low-pressure gas or air types, such as house service regulators, which incorporate a relatively large diaphragm casing.
- **Close-control Group** — This group usually includes pilot-operated regulators. They provide high accuracy over a large range of flows. Applications that require close control include these examples:
  - Burner control where the fuel/air ratio is critical to burner efficiency and the gas pressure has a significant effect on the fuel/air ratio.
  - Metering devices, such as gas meters, which require constant input pressures to ensure accurate measurement.

## Pipe Size Required

If the pipe size is known, it gives the specifier of a new regulator a more defined starting point. If, after making an initial selection of a regulator, the regulator is larger than the pipe size, it usually means that an error has been made either in selecting the pipe size or the regulator or in determining the original parameters (such as pressure or flow) required for regulator selection. In many cases, the outlet piping needs to be larger than the regulator for the regulator to reach full capacity.

## End Connection Style

In general, the following end connections are available for the indicated regulator sizes:

- Pipe threads or socket weld: 2 in. / DN 50 and smaller
- Flanged: 1 in. / DN 25 and larger
- Butt weld: 1 in. / DN 25 and larger

Note: Not all end connections are available for all regulators.

## Required Materials

The regulator construction materials are generally dictated by the application. Standard materials are:

- Aluminum
- Cast iron or Ductile iron
- Steel
- Bronze and Brass
- Stainless steel

Special materials required by the process can have an effect on the type of regulator that can be used. Oxygen service, for example, requires special materials, requires special cleaning preparation and requires that no oil or grease be in the regulator.

## Control Lines

For pressure registration, control lines are connected downstream of a pressure reducing regulator and upstream of a backpressure regulator. Typically large direct-operated regulators have external control lines and small direct-operated regulators have internal registration instead of a control line. Most pilot-operated regulators have external control lines, but this should be confirmed for each regulator type considered.

## Stroking Speed

Stroking speed is often an important selection criteria. Direct-operated regulators are very fast and pilot-operated regulators are slightly slower. Both types are faster than most control valves. When speed is critical, techniques can be used to decrease stroking time.

## Overpressure Protection

Overpressure protection methods should be employed to protect employees, the public, and equipment. The Overpressure Protection Methods section details the advantages and disadvantages of the most common overpressure protection methods including relief valves, monitors and slam shuts.

# Introduction to Regulators

## Regulator Replacement

When a regulator is being selected to replace an existing regulator, the existing regulator can provide the following information:

- Style of regulator
- Size of regulator
- Type number of the regulator
- Special requirements for the regulator, such as downstream pressure sensing through a control line versus internal pressure registration.

## Regulator Price


The price of a regulator is only a part of the cost of ownership. Additional costs include installation and maintenance. In selecting a regulator, you should consider all of the costs that will accrue over the life of the regulator. The regulator with a low initial cost might not be the most economical in the long run. For example, a direct-operated regulator is generally less expensive, but a pilot-operated regulator might provide more capacity for the initial investment. To illustrate, a 2 in. / DN 50 pilot-operated regulator can have the same capacity and a lower price than a 3 in. / DN 80, direct-operated regulator.

## Backpressure Regulator Selection


Backpressure regulators control the inlet pressure rather than the outlet pressure. The selection criteria for a backpressure regulator the same as for a pressure reducing regulator.

## Relief Valve Selection

An external relief valve is a form of backpressure regulator. A relief valve opens when the inlet pressure exceeds a set value. Relief is generally to atmosphere. The selection criteria is the same as for a pressure reducing regulator.



RELIEF PRESSURE CONTROL AT RELIEF VALVE INLET



BACKPRESSURE CONTROL

Figure 6. Backpressure Regulator/Relief Valve Applications



# Principles of Direct-Operated Regulators

## Introduction

Pressure regulators have become very familiar items over the years and nearly everyone has grown accustomed to seeing them in factories, public buildings, by the roadside and even on the outside of their own homes. As is frequently the case with such familiar items, we have a tendency to take them for granted. It's only when a problem develops or when we are selecting a regulator for a new application, that we need to look more deeply into the fundamentals of the regulator's operation.

Regulators provide a means of controlling the flow of a gas or other fluid supply to downstream processes or customers. An ideal regulator would supply downstream demand while keeping downstream pressure constant; however, the mechanics of direct-operated regulator construction are such that there will always be some deviation (droop or offset) in downstream pressure.



Figure 1. Direct-Operated Regulators

## Regulator Basics

A pressure reducing regulator must satisfy a downstream demand while maintaining the system pressure within certain acceptable limits. When the flow rate is low, the regulator plug or disk approaches its seat and restricts the flow. When demand increases, the plug or disk moves away from its seat, creating a larger opening and increased flow. Ideally, a regulator should provide a constant downstream pressure while delivering the required flow.

The service regulator mounted on the meter outside virtually every home serves as an example. As appliances such as a furnace or stove call for the flow of more gas, the service regulator responds by delivering the required flow. As this happens, the pressure should be held constant. This is important because the gas meter, which is the cash register of the system, is often calibrated for a given pressure.

Direct-operated regulators have many commercial and residential uses. Typical applications include industrial, commercial and domestic gas service, instrument air supply and a broad range of applications in industrial processes.

Regulators automatically adjust flow to meet downstream demand. Before regulators were invented, someone had to watch a pressure gauge for pressure drops which signaled an increase in downstream demand. When the downstream pressure decreased, more flow was required. The operator then opened the regulating valve until the gauge pressure increased, showing that downstream demand was being met.

## Essential Elements

Direct-operated regulators have three essential elements:

- A restricting element— a valve, disk or plug
- A measuring element— generally a diaphragm
- A loading element— generally a spring




Figure 2. Three Essential Elements

# Principles of Direct-Operated Regulators

## Restricting Element

The regulator's restricting element is generally a disk or plug that can be positioned fully open, fully closed or somewhere in between to control the amount of flow. When fully closed, the disk or plug seats tightly against the valve orifice or seat ring to shutoff flow.

## Measuring Element

The measuring element is usually a flexible diaphragm that senses downstream pressure ( $P_2$ ). The diaphragm moves as pressure beneath it changes. The restricting element is often attached to the diaphragm with a stem so that when the diaphragm moves, so does the restricting element.

## Loading Element

A weight or spring acts as the loading element. The loading element counterbalances downstream pressure ( $P_2$ ). The amount of unbalance between the loading element and the measuring element determines the position of the restricting element. Therefore, we can adjust the desired amount of flow through the regulator or setpoint, by varying the load. Some of the first direct-operated regulators used weights as loading elements. Most modern regulators use springs.

## Regulator Operation

To examine how the regulator works, let's consider these values for a direct-operated regulator installation:

- Upstream Pressure ( $P_1$ ) = 100 psig
- Downstream Pressure ( $P_2$ ) = 10 psig
- Pressure Drop Across the Regulator ( $P$ ) = 90 psi
- Diaphragm Area ( $A_D$ ) = 10 in<sup>2</sup>
- Loading Weight = 100 lbs.

Let's examine a regulator in equilibrium as shown in Figure 3. The pressure acting against the diaphragm creates a force acting up to 100 lbs.

$$\begin{aligned} \text{Diaphragm Force (F}_D\text{)} &= \text{Pressure (P}_2\text{)} \times \text{Area of} \\ &\quad \text{Diaphragm (A}_D\text{)} \\ &\quad \text{or} \\ \text{F}_D &= 10 \text{ psig} \times 10 \text{ in}^2 = 100 \text{ lbs} \end{aligned}$$

The 100 lbs weight acts down with a force of 100 lbs, so all the opposing forces are equal and the regulator plug remains stationary.

## Increasing Demand

If the downstream demand increases,  $P_2$  will drop. The pressure on the diaphragm drops, allowing the regulator to open further. Suppose in our example  $P_2$  drops to 9 psig. The




Figure 3. Elements

force acting up then equals 90 lbs (9 psig x 10 in<sup>2</sup> = 90 lbs). Because of the unbalance of the measuring element and the loading element, the restricting element will move to allow passage of more flow.

## Decreasing Demand

If the downstream demand for flow decreases, downstream pressure increases. In our example, suppose  $P_2$  increases to 11 psig. The force acting up against the weight becomes 110 lbs (11 psig x 10 in<sup>2</sup> = 110 lbs). In this case, unbalance causes the restricting element to move up to pass less flow or lockup.

## Weights versus Springs

One of the problems with weight-loaded systems is that they are slow to respond. So if downstream pressure changes rapidly, our weight-loaded regulator may not be able to keep up. Always behind, it may become unstable and cycle—continuously going from the fully open to the fully closed position. There are other problems. Because the amount of weight controls regulator setpoint, the regulator is not easy to adjust. The weight will always have to be on top of the diaphragm. So, let's consider using a spring. By using a spring instead of a weight, regulator stability increases because a spring has less stiffness.

# Principles of Direct-Operated Regulators




Figure 4. Spring as Element

## Spring Rate

We choose a spring for a regulator by its spring rate ( $K$ ).  $K$  represents the amount of force necessary to compress the spring 1 in. For example, a spring with a rate of 100 lbs/in. needs 100 lbs of force to compress it 1 in., 200 lbs of force to compress it 2 in. and so on.

## Equilibrium with a Spring

Instead of a weight, let's substitute a spring with a rate of 100 lbs/in. And, with the regulator's spring adjuster, we'll wind in 1 in. of compression to provide a spring force ( $F_S$ ) of 100 lbs. This amount of compression of the regulator spring determines setpoint or the downstream pressure that we want to hold constant. By adjusting the initial spring compression, we change the spring loading force, so  $P_2$  will be at a different value in order to balance the spring force.

Now the spring acts down with a force of 100 lbs and the downstream pressure acts up against the diaphragm producing a force of 100 lbs ( $F_D = P_2 \times A_D$ ). Under these conditions the regulator has achieved equilibrium; that is, the plug or disk is holding a fixed position.

## Spring as Loading Element

By using a spring instead of a fixed weight, we gain better control and stability in the regulator. The regulator will now be less likely to go fully open or fully closed for any change in downstream pressure ( $P_2$ ). In effect, the spring acts like a multitude of different weights.

## Throttling Example

Assume we still want to maintain 10 psig downstream. Consider what happens now when downstream demand increases and pressure  $P_2$  drops to 9 psig. The diaphragm force ( $F_D$ ) acting up is now 90 lbs.

$$F_D = P_2 \times A_D$$

$$F_D = 9 \text{ psig} \times 10 \text{ in}^2$$

$$F_D = 90 \text{ lbs}$$

We can also determine how much the spring will move (extend) which will also tell us how much the disk will travel. To keep the regulator in equilibrium, the spring must produce a force ( $F_S$ ) equal to the force of the diaphragm. The formula for determining spring force ( $F_S$ ) is:

$$F_S = (K)(X)$$

where  $K$  = spring rate in lbs/in. and  $X$  = travel or compression in in.

We know  $F_S$  is 90 lbs and  $K$  is 100 lbs/in., so we can solve for  $X$  with:





Figure 5. Plug Travel

# Principles of Direct-Operated Regulators



AS THE FLOW RATE APPROACHES ZERO,  $P_2$  INCREASES STEEPLY. LOCKUP IS THE TERM APPLIED TO THE VALUE OF  $P_2$  AT ZERO FLOW.

Figure 6. Typical Performance Curve

$$\begin{aligned} X &= F_s \div K \\ X &= 90 \text{ lbs} \div 100 \text{ lbs/in.} \\ X &= 0.9 \text{ in.} \end{aligned}$$

The spring, and therefore the disk, has moved down 1/10 in., allowing more flow to pass through the regulator body.

## Regulator Operation and $P_2$

Now we see the irony in this regulator design. We recall that the purpose of an ideal regulator is to match downstream demand while keeping  $P_2$  constant. But for this regulator design to increase flow, there must be a change in  $P_2$ .

## Regulator Performance

We can check the performance of any regulating system by examining its characteristics. Most of these characteristics can be best described using pressure versus flow curves as shown in Figure 6.

## Performance Criteria

We can plot the performance of an ideal regulator such that no matter how the demand changes, our regulator will match that demand (within its capacity limits) with no change in the downstream pressure ( $P_2$ ). This straight line performance becomes the standard against which we can measure the performance of a real regulator.

## Setpoint

The constant pressure desired is represented by the setpoint. But no regulator is ideal. The downward sloping line on the diagram represents pressure ( $P_2$ ) plotted as a function of flow for an actual direct-operated regulator. The setpoint is determined by the initial compression of the regulator spring.

By adjusting the initial spring compression you change the spring loading force, so  $P_2$  will be at a different value in order to balance the spring force. This establishes setpoint.

## Droop

Droop, proportional band and offset are terms used to describe the phenomenon of  $P_2$  dropping below setpoint as flow increases. Droop is the amount of deviation from setpoint at a given flow, expressed as a percentage of setpoint. This “droop” curve is important to a user because it indicates regulating (useful) capacity.

## Capacity

Capacities published by regulator manufacturers are given for different amounts of droop. Let’s see why this is important.

Let’s say that for our original problem, with the regulator set at 10 psig, our process requires 200 SCFH (standard cubic feet per hour) with no more than a 1 psi drop in setpoint. We need to keep the pressure at or above 9 psig because we have a low limit safety switch set at 9 psig that will shut the system down if pressure falls below this point.

Figure 6 illustrates the performance of a regulator that can do the job. And, if we can allow the downstream pressure to drop below 9 psig, the regulator can allow even more flow.

The capacities of a regulator published by manufacturers are generally given for 10% droop and 20% droop. In our example, this would relate to flow at 9 psig and at 8 psig.

## Accuracy

The accuracy of a regulator is determined by the amount of flow it can pass for a given amount of droop. The closer the regulator is to the ideal regulator curve (setpoint), the more accurate it is.

## Lockup

Lockup is the pressure above setpoint that is required to shut the regulator off tight. In many regulators, the orifice has a knife edge while the disk is a soft material. Some extra pressure,  $P_2$ , is required to force the soft disk into the knife edge to make a tight seal. The amount of extra pressure required is lockup pressure. Lockup pressure may be important for a number of reasons. Consider the example above where a low pressure limit switch would shut down the system if  $P_2$  fell below 9 psig. Now consider the same system with a high pressure safety cut out switch set at 10.5 psig. Because our regulator has a lockup pressure of 11 psig, the high limit switch will shut the system down before the regulator can establish tight shutoff. Obviously, we’ll want to select a regulator with a lower lockup pressure.

# Principles of Direct-Operated Regulators

## Spring Rate and Regulator Accuracy

Using our initial problem as an example, let's say we now need the regulator to flow 300 SCFH at a droop of 10% from our original setpoint of 10 psig. Ten percent of 10 psig = 1 psig, so  $P_2$  cannot drop below 10 to 1 or 9 psi. Our present regulator would not be accurate enough. For our regulator to pass 300 SCFH,  $P_2$  will have to drop to 8 psig or 20% droop.

## Spring Rate and Droop

One way to make our regulator more accurate is to change to a lighter spring rate. To see how spring rate affects regulator accuracy, let's return to our original example. We first tried a spring with a rate of 100 lbs/in. Let's substitute one with a rate of 50 lbs/in. To keep the regulator in equilibrium, we'll have to initially adjust the spring to balance the 100 lbs force produced by  $P_2$  acting on the diaphragm. Recall how we calculate spring force:

$$F_S = K (\text{spring rate}) \times X (\text{compression})$$

Knowing that  $F_S$  must equal 100 lbs and  $K = 50$  lbs/in., we can solve for  $X$  or spring compression, with:

$$X = F_S \div K \text{ or } X = 2 \text{ in.}$$

So, we must wind in 2 in. of initial spring compression to balance diaphragm force,  $F_D$ .

## Effect on Plug Travel

We saw before that with a spring rate of 100 lbs/in., when  $P_2$  dropped from 10 to 9 psig, the spring relaxed (and the valve disk traveled) 0.1 in. Now let's solve for the amount of disk travel with the lighter spring rate of 50 lbs/in. The force produced by the diaphragm is still 90 lbs.

$$F_D = P_2 \times A_D$$

To maintain equilibrium, the spring must also produce a force of 90 lbs. Recall the formula that determines spring force:

$$F_S = (K)(X)$$

Because we know  $F_S$  must equal 90 lbs and our spring rate ( $K$ ) is 50 lbs/in., we can solve for compression ( $X$ ) with:

$$X = F_S \div K$$

$$X = 90 \text{ lbs} \div 50 \text{ lbs/in.}$$

$$X = 1.8 \text{ in.}$$

To establish setpoint, we originally compressed this spring 2 in. Now it has relaxed so that it is only compressed 1.8 in., a change of 0.2 in. So with a spring rate of 50 lbs/in., the regulator responded to a 1 psig drop in  $P_2$  by opening twice as far as it did with a spring rate of 100 lbs/in. Therefore, our regulator is now more accurate because it has greater capacity for the same change in  $P_2$ . In other words, it has less droop or offset. Using this example, it is easy to see how capacity and accuracy are related and how they are related to spring rate.

## Light Spring Rate

Experience has shown that choosing the lightest available spring rate will provide the most accuracy (least droop). For example, a spring with a range of 35 to 100 psig is more accurate than a spring with a range of 90 to 200 psig. If you want to set your regulator at 100 psig, the 35 to 100 psig spring will provide better accuracy.

## Practical Limits

While a lighter spring can reduce droop and improve accuracy, using too light a spring can cause instability problems. Fortunately, most of the work in spring selection is done by regulator manufacturers. They determine spring rates that will provide good performance for a given regulator and publish these rates along with other sizing information.

## Diaphragm Area and Regulator Accuracy

### Diaphragm Area

Until this point, we have assumed the diaphragm area to be constant. In practice, the diaphragm area changes with travel. We're interested in this changing area because it has a major influence on accuracy and droop.

Diaphragms have convolutions in them so that they are flexible enough to move over a rated travel range. As they change position, they also change shape because of the pressure applied to them. Consider the example shown in Figure 7. As downstream pressure ( $P_2$ ) drops, the diaphragm moves down. As it moves down, it changes shape and diaphragm area increases because the centers of the convolutions become further apart. The larger diaphragm area magnifies the effect of  $P_2$  so even less  $P_2$  is required to hold the diaphragm in place. This is called diaphragm effect. The result is decreased accuracy because incremental changes in  $P_2$  do not result in corresponding changes in spring compression or disk position.

# Principles of Direct-Operated Regulators




Figure 7. Changing Diaphragm Area

## Increasing Diaphragm Area

To better understand the effects of changing diaphragm area, let's calculate the forces in the exaggerated example given in Figure 7. First, assume that the regulator is in equilibrium with a downstream pressure  $P_2$  of 10 psig. Also assume that the area of the diaphragm in this position is 10 in<sup>2</sup>. The diaphragm force ( $F_D$ ) is:

$$F_D = (P_2)(A_D)$$
$$F_D = (10 \text{ psi})(10 \text{ in}^2)$$
$$F_D = 100 \text{ lbs}$$

Now assume that downstream pressure drops to 9 psig signaling the need for increased flow. As the diaphragm moves, its area increases to 11 in<sup>2</sup>. The diaphragm force now produced is:

$$F_D = (9 \text{ psi})(11 \text{ in}^2)$$
$$F_D = 99 \text{ lbs}$$

The change in diaphragm area increases the regulator's droop. While it's important to note that diaphragm effect contributes to droop, diaphragm sizes are generally determined by manufacturers for different regulator types, so there is rarely a user option.

## Diaphragm Size and Sensitivity

Also of interest is the fact that increasing diaphragm size can result in increased sensitivity. A larger diaphragm area will produce more force for a given change in  $P_2$ . Therefore, larger diaphragms are often used when measuring small changes in low-pressure applications. Service regulators used in domestic gas service are an example.




Figure 8. Critical Flow

## Restricting Element and Regulator Performance

### Critical Flow

Although changing the orifice size can increase capacity, a regulator can pass only so much flow for a given orifice size and inlet pressure, no matter how much we improve the unit's accuracy. Shown in Figure 8, after the regulator is wide-open, reducing  $P_2$  does not result in higher flow. This area of the flow curve identifies critical flow. To increase the amount of flow through the regulator, the flowing fluid must pass at higher and higher velocities. But, the fluid can only go so fast. Holding  $P_1$  constant while decreasing  $P_2$ , flow approaches a maximum which is the speed of sound in that particular gas or its sonic velocity. Sonic velocity depends on the inlet pressure and temperature for the flowing fluid. Critical flow is generally anticipated when downstream pressure ( $P_2$ ) approaches a value that is less than or equal to one-half of inlet pressure ( $P_1$ ).

### Orifice Size and Capacity

One way to increase capacity is to increase the size of the orifice. The variable flow area between disk and orifice depends directly on orifice diameter. Therefore, the disk will not have to travel as far with a larger orifice to establish the required regulator flow rate and droop is reduced. Sonic velocity is still a limiting factor, but the flow rate at sonic velocity is greater because more gas is passing through the larger orifice.

Stated another way, a given change in  $P_2$  will produce a larger change in flow rate with a larger orifice than it would with a smaller orifice. However, there are definite limits to the size of orifice that can be used. Too large an orifice makes the regulator more sensitive to fluctuating inlet pressures. If the regulator is overly sensitive, it will have a tendency to become unstable and cycle.

# Principles of Direct-Operated Regulators

## Orifice Size and Stability

One condition that results from an oversized orifice is known as the “bathtub stopper” effect. As the disk gets very close to the orifice, the forces of fluid flow tend to slam the disk into the orifice and shutoff flow. Downstream pressure drops and the disk opens. This causes the regulator to cycle—open, closed, open, closed. By selecting a smaller orifice, the disk will operate farther away from the orifice so the regulator will be more stable.

## Orifice Size, Lockup and Wear

A larger orifice size also requires a higher shutoff pressure or lockup pressure. In addition, an oversized orifice usually produces faster wear on the valve disk and orifice because it controls flow with the disk near the seat. This wear is accelerated with high flow rates and when there is dirt or other erosive material in the flow stream.

## Orifice Guideline

Experience indicates that using the smallest possible orifice is generally the best rule-of-thumb for proper control and stability.

## Increasing $P_1$

Regulator capacity can be increased by increasing inlet pressure ( $P_1$ ).

## Factors Affecting Regulator Accuracy

As we have seen, the design elements of a regulator—the spring, diaphragm and orifice size—can affect its accuracy. Some of these inherent limits can be overcome with changes to the regulator design.




Figure 9. Increased Sensitivity

## Performance Limits

The three curves in Figure 9 summarize the effects of spring rate, diaphragm area and orifice size on the shape of the controlled pressure-flow rate curve. Curve A is a reference curve representing a typical regulator. Curve B represents the improved performance from either increasing diaphragm area or decreasing spring rate. Curve C represents the effect of increasing orifice size. Note that increased orifice size also offers higher flow capabilities. But remember that too large an orifice size can produce problems that will negate any gains in capacity.




Figure 10. Cycling

## Cycling

The sine wave in Figure 10 might be what we see if we increase regulator sensitivity beyond certain limits. The sine wave indicates instability and cycling.

## Design Variations

All direct-operated regulators have performance limits that result from droop. Some regulators are available with features designed to overcome or minimize these limits.

# Principles of Direct-Operated Regulators




Figure 11. Pitot Tube

## Improving Regulator Accuracy with a Pitot Tube

In addition to the changes we can make to diaphragm area, spring rate, orifice size and inlet pressure, we can also improve regulator accuracy by adding a pitot tube as shown in Figure 11. Internal to the regulator, the pitot tube connects the diaphragm casing with a low-pressure, high velocity region within the regulator body. The pressure at this area will be lower than  $P_2$  further downstream. By using a pitot tube to measure the lower pressure, the regulator will make more dramatic changes in response to any change in  $P_2$ . In other words, the pitot tube tricks the regulator, causing it to respond more than it would otherwise.




Figure 12. Performance with Pitot Tube

## Numerical Example

For example, we'll establish setpoint by placing a gauge downstream and adjusting spring compression until the gauge reads 10 psig for  $P_2$ . Because of the pitot tube, the regulator might actually be sensing a lower pressure. When  $P_2$  drops from 10 psig to 9 psig, the pressure sensed by the pitot tube may drop from 8 psig to 6 psig. Therefore, the regulator opens further than it would if it were sensing actual downstream pressure.

## Decreased Droop (Boost)

The pitot tube offers one chief advantage for regulator accuracy, it decreases droop. Shown in Figure 12, the diaphragm pressure,  $P_D$ , must drop just as low with a pitot tube as without to move the disk far enough to supply the required flow. But the solid curve shows that  $P_2$  does not decrease as much as it did without a pitot tube. In fact,  $P_2$  may increase. This is called boost instead of droop. So the use of a pitot tube, or similar device, can dramatically improve droop characteristics of a regulator.




Figure 13. Lever Style Regulator

## Improving Performance with a Lever

The lever style regulator is a variation of the simple direct-operated regulator. It operates in the same manner, except that it uses a lever to gain mechanical advantage and provide a high shutoff force.

In earlier discussions, we noted that the use of a larger diaphragm can result in increased sensitivity. This is because any change in  $P_2$  will result in a larger change in diaphragm force. The same result is obtained by using a lever to multiply the force produced by the diaphragm as shown in Figure 13.

The main advantage of lever designs is that they provide increased force for lockup without the extra cost, size and weight associated with larger diaphragms, diaphragm casings and associated parts.



# Principles of Pilot-Operated Regulators

## Pilot-Operated Regulator Basics

In the evolution of pressure regulator designs, the shortcomings of the direct-operated regulator naturally led to attempts to improve accuracy and capacity. A logical next step in regulator design is to use what we know about regulator operation to explore a method of increasing sensitivity that will improve all of the performance criteria discussed.




Figure 1. Pilot-Operated Regulator

## Regulator Pilots

To improve the sensitivity of our regulator, we would like to be able to sense  $P_2$  and then somehow make a change in loading pressure ( $P_L$ ) that is greater than the change in  $P_2$ . To accomplish this, we can use a device called a pilot or pressure amplifier.

The major function of the pilot is to increase regulator sensitivity. If we can sense a change in  $P_2$  and translate it into a larger change in  $P_L$ , our regulator will be more responsive (sensitive) to changes in demand. In addition, we can significantly reduce droop so its effect on accuracy and capacity is minimized.

## Gain

The amount of amplification supplied by the pilot is called “gain”. To illustrate, a pilot with a gain of 20 will multiply the effect of a 1 psi change on the main diaphragm by 20. For example, a decrease in  $P_2$  opens the pilot to increase  $P_L$  20 times as much.

## Identifying Pilots

Analysis of pilot-operated regulators can be simplified by viewing them as two independent regulators connected together. The smaller of the two is generally the pilot.

## Setpoint

We may think of the pilot as the “brain” of the system. Setpoint and many performance variables are determined by the pilot. It senses  $P_2$  directly and will continue to make changes in  $P_L$  on the main regulator until the system is in equilibrium. The main regulator is the “muscle” of the system and may be used to control large flows and pressures.

## Spring Action

Notice that the pilot uses a spring-open action as found in direct-operated regulators. The main regulator, shown in Figure 1, uses a spring-close action. The spring, rather than loading pressure, is used to achieve shutoff. Increasing  $P_L$  from the pilot onto the main diaphragm opens the main regulator.

## Pilot Advantage

Because the pilot is the controlling device, many of the performance criteria we have discussed apply to the pilot. For example, droop is determined mainly by the pilot. By using very small pilot orifices and light springs, droop can be made small. Because of reduced droop, we will have greater usable capacity. Pilot lockup determines the lockup characteristics for the system. The main regulator spring provides tight shutoff whenever the pilot is locked up.

## Gain and Restrictions

### Stability

Although increased gain (sensitivity) is often considered an advantage, it also increases the gain of the entire pressure regulator system. If the system gain is too high, it may become unstable. In other words, the regulator might tend to oscillate; over-reacting by continuously opening and closing. Pilot gain can be modified to tune the regulator to the system. To provide a means for changing gain, every pilot-operated regulator system contains both a fixed and a variable restriction. The relative size of one restriction compared to the other can be varied to change gain and speed of response.

# Principles of Pilot-Operated Regulators




Figure 2. Fixed Restrictions and Gain (Used on Two-Path Control Systems)

## Restrictions, Response Time and Gain

Consider the example shown in Figure 2 with a small fixed restriction. Decreasing  $P_2$  will result in pressure  $P_L$  increasing. Increasing  $P_2$  will result in a decrease in  $P_L$  while  $P_L$  bleeds out through the small fixed restriction.

If a larger fixed restriction is used with a variable restriction, the gain (sensitivity) is reduced. A larger decrease in  $P_2$  is required to increase  $P_L$  to the desired level because of the larger fixed restriction.

## Loading and Unloading Designs

A loading pilot-operated design (Figure 2), also called two-path control, is so named because the action of the pilot loads  $P_L$  onto the main regulator measuring element. The variable restriction or pilot orifice, opens to increase  $P_L$ .

An unloading pilot-operated design (Figure 3) is so named because the action of the pilot unloads  $P_L$  from the main regulator.




Figure 3. Unloading Systems

## Two-Path Control (Loading Design)

In two-path control systems (Figure 4), the pilot is piped so that  $P_2$  is registered on the pilot diaphragm and on the main regulator diaphragm at the same time. When downstream demand is constant,  $P_2$  positions the pilot diaphragm so that flow through the pilot will keep  $P_2$  and  $P_L$  on the main regulator diaphragm. When  $P_2$  changes, the force on top of the main regulator diaphragm and on the bottom of the pilot diaphragm changes. As  $P_2$  acts on the main diaphragm, it begins repositioning the main valve plug. This immediate reaction to changes in  $P_2$  tends to make two-path designs faster than other pilot-operated regulators. Simultaneously,  $P_2$  acting on the pilot diaphragm repositions the pilot valve.




Figure 4. Two-Path Control

# Principles of Pilot-Operated Regulators




Figure 5. Unloading Control




Figure 6. Pilot-Operated Regulator Performance

and changes  $P_L$  on the main regulator diaphragm. This adjustment to  $P_L$  accurately positions the main regulator valve plug.  $P_L$  on the main regulator diaphragm bleeds through a fixed restriction until the forces on both sides are in equilibrium. At that point, flow through the regulator valve matches the downstream demand.

## Two-Path Control Advantages

The primary advantages of two-path control are speed and accuracy. These systems may limit droop to less than 1%. They are well suited to systems with requirements for high accuracy, large capacity and a wide range of pressures.

## Unloading Control

Unloading systems (Figure 5) locate the pilot so that  $P_2$  acts only on the pilot diaphragm.  $P_1$  constantly loads under the regulator diaphragm and has access to the top of the diaphragm through a fixed restriction.

When downstream demand is constant, the pilot valve is open enough that  $P_L$  holds the position of the main regulator diaphragm. When downstream demand changes,  $P_2$  changes and the pilot diaphragm reacts accordingly. The pilot valve adjusts  $P_L$  to reposition and hold the main regulator diaphragm.

## Unloading Control Advantages

Unloading systems are not quite as fast as two-path systems and they can require higher differential pressures to operate. However, they are simple and more economical, especially in large regulators. Unloading control is used with popular elastomer diaphragm style regulators. These regulators use a flexible membrane to throttle flow.

## Performance Summary


### Accuracy

Because of their high gain, pilot-operated regulators are extremely accurate. Droop for a direct-operated regulator might be in the range of 10 to 20% whereas pilot-operated regulators are between 1 and 3% with values under 1% possible.

### Capacity

Pilot-operated designs provide high capacity for two reasons. First, we have shown that capacity is related to droop. And because droop can be made very small by using a pilot, capacity is increased. In addition, the pilot becomes the “brain” of the system and controls a larger, sometimes much larger, main regulator. This also allows increased flow capabilities.


# Principles of Pilot-Operated Regulators



A6563

INLET PRESSURE,  $P_1$   
OUTLET PRESSURE,  $P_2$   
ATMOSPHERIC PRESSURE  
LOADING PRESSURE,  $P_L$

Figure 7. Type 1098-EGR, Typical Two-Path Control



A6469

INLET PRESSURE,  $P_1$   
OUTLET PRESSURE,  $P_2$   
ATMOSPHERIC PRESSURE  
LOADING PRESSURE,  $P_L$

Figure 8. Type 99, Typical Two-Path Control with Integrally Mounted Pilot

## Lockup

The lockup characteristics for a pilot-operated regulator are the lockup characteristics of the pilot. Therefore, with small orifices, lockup pressures can be small.

## Applications

Pilot-operated regulators should be considered whenever accuracy, capacity and/or high pressure are important selection criteria. They can often be applied to high capacity services with greater economy than a control valve and actuator with controller.

## Two-Path Control

In some designs (Figure 7), the pilot and main regulator are separate components. In others (Figure 8), the system is integrated into a single package. All, however, follow the basic design concepts discussed earlier.

## Type 1098-EGR

The schematic in Figure 7 illustrates the Type 1098-EGR regulator's operation. It can be viewed as a model for all two-path, pilot-operated regulators. The pilot is simply a sensitive direct-operated regulator used to send loading pressure to the main regulator diaphragm.

Identify the inlet pressure ( $P_1$ ). Find the downstream pressure ( $P_2$ ). Follow it to where it opposes the loading pressure on the main regulator diaphragm. Then, trace  $P_2$  back to where it opposes the control spring in the pilot. Finally, locate the route of  $P_2$  between the pilot and the regulator diaphragm.

Changes in  $P_2$  register on the pilot and main regulator diaphragms at the same time. As  $P_2$  acts on the main diaphragm, it begins repositioning the main valve plug. Simultaneously,  $P_2$  acting on the pilot diaphragm repositions the pilot valve and changes  $P_L$  on the main regulator diaphragm. This adjustment in  $P_L$  accurately positions the main regulator valve plug.

# Principles of Pilot-Operated Regulators




Figure 9. Type EZR, Unloading Design

As downstream demand is met,  $P_2$  rises. Because  $P_2$  acts directly on both the pilot and main regulator diaphragms, this design provides fast response.

## Type 99

The schematic in Figure 8 illustrates another typical two-path control design, the Type 99. The difference between the Type 1098-EGR and the Type 99 is the integrally mounted pilot of the Type 99.

The pilot diaphragm measures  $P_2$ . When  $P_2$  falls below the pilot setpoint, the diaphragm moves away from the pilot orifice and allows loading pressure to increase. This loads the top of the main regulator diaphragm and strokes the main regulator valve open further.

## Unloading Design

Unloading designs incorporate a molded composition diaphragm that serves as the combined loading and restricting component of the main regulator. Full upstream pressure ( $P_1$ ) is used to load the regulator diaphragm when it is seated. The regulator shown in Figure 9 incorporates an elastomeric valve closure member.

Unloading regulator designs are slower than two-path control systems because the pilot must first react to changes in  $P_2$  before the main regulator valve moves. Recall that in two-path designs, the pilot and main regulator diaphragms react simultaneously.

$P_1$  passes through a fixed restriction and fills the space above the regulator diaphragm. This fixed restriction can be adjusted to increase or decrease regulator gain.  $P_1$  also fills the cavity below the regulator diaphragm. Because the surface area on the top side of the diaphragm is larger than the area exposed to  $P_1$  below, the diaphragm is forced down against the cage to close the regulator.

When downstream demand increases, the pilot opens. When the pilot opens, regulator loading pressure escapes downstream much faster than  $P_1$  can bleed through the fixed restriction. As pressure above the regulator diaphragm decreases,  $P_1$  forces the diaphragm away from its seat.

When downstream demand is reduced,  $P_2$  increases until it's high enough to compress the pilot spring and close the pilot valve. As the pilot valve closes,  $P_1$  continues to pass through the fixed restriction and flows into the area above the main regulator diaphragm. This loading pressure,  $P_1$ , forces the diaphragm back toward the cage, reducing flow through the regulator.

# Selecting and Sizing Pressure Reducing Regulators

## Introduction

Those who are new to the regulator selection and sizing process are often overwhelmed by the sheer number of regulator types available and the seemingly endless lists of specifications in manufacturer's literature. This application guide is designed to assist you in selecting a regulator that fits your application's specific needs.

Although it might seem obvious, the first step is to consider the application itself. Some applications immediately point to a group of regulators designed specifically for that type of service. The Application Guide has sections to help identify regulators that are designed for specific applications. There are Application Maps, Quick Selection Guides, an Applications section and Product Pages. The Application Map shows some of the common applications and the regulators that are used in those applications. The Quick Selection Guide lists the regulators by application and provides important selection information about each regulator. The Applications section explains the applications covered in the section and it also explains many of the application considerations. The Product Pages provide specific details about the regulators that are suitable for the applications covered in the section. To begin selecting a regulator, turn to the Quick Selection Guide in the appropriate Applications section.

## Quick Selection Guides

Quick Selection Guides identify the regulators with the appropriate pressure ratings, outlet pressure ranges and capacities. These guides quickly narrow the range of potentially appropriate regulators. The choices identified by using a Quick Selection Guide can be narrowed further by using the Product Pages to find more information about each of the regulators.

## Product Pages

Identifying the regulators that can pass the required flow narrows the possible choices further. When evaluating flow requirements, consider the minimum inlet pressure and maximum flow requirements. Again, this worst case combination ensures that the regulator can pass the required flow under all anticipated conditions.

After one or more regulators have been identified as potentially suitable for the service conditions, consult specific Product Pages to check regulator specifications and capabilities. The application requirements are compared to regulator specifications to narrow the range of appropriate

selections. The following specifications can be evaluated in the Product Pages:

- Product description and available sizes
- Maximum inlet and outlet pressures (operating and emergency)
- Outlet pressure ranges
- Flow capacity
- End connection styles
- Regulator construction materials
- Accuracy
- Pressure registration (internal or external)
- Temperature capabilities

After comparing the regulator capabilities with the application requirements, the choices can be narrowed to one or a few regulators. Final selection might depend upon other factors including special requirements, availability, price and individual preference.

## Special Requirements

Finally, evaluate any special considerations, such as the need for external control lines, special construction materials or internal overpressure protection. Although overpressure protection might be considered during sizing and selection, it is not covered in this section.

## The Role of Experience

Experience in the form of knowing what has worked in the past and familiarity with specific products, has great value in regulator sizing and selection. Knowing the regulator performance characteristics required for a specific application simplifies the process. For example, when fast speed of response is required, a direct-operated regulator may come to mind; or a pilot-operated regulator with an auxiliary, large capacity pilot to speed changes in loading pressure.

## Sizing Equations

Sizing equations are useful when sizing pilot-operated regulators and relief valves. They can also be used to calculate the wide-open flow of direct-operated regulators. Use the capacity tables or curves in this application guide when sizing direct-operated regulators and relief/backpressure regulators. The sizing equations are in the Valve Sizing Calculations section.

# Selecting and Sizing Pressure Reducing Regulators

## General Sizing Guidelines

The following are intended to serve only as guidelines when sizing pressure reducing regulators. When sizing any regulator, consult with experienced personnel or the regulator manufacturer for additional guidance and information relating to specific applications.

### Body Size

Regulator body size should never be larger than the pipe size. However, a properly sized regulator may be smaller than the pipeline.

### Construction

Be certain that the regulator is available in materials that are compatible with the controlled fluid and the temperatures used. Also, be sure that the regulator is available with the desired end connections.

### Pressure Ratings

While regulators are sized using minimum inlet pressures to ensure that they can provide full capacity under all conditions, pay particular attention to the maximum inlet and outlet pressure ratings.

### Wide-Open Flow Rate

The capacity of a regulator when it has failed wide-open is usually greater than the regulating capacity. For that reason, use the regulating capacities when sizing regulators and the wide-open flow rates only when sizing relief valves.

### Outlet Pressure Ranges and Springs

If two or more available springs have published outlet pressure ranges that include the desired pressure setting, use the spring with the lower range for better accuracy. Also, it is not necessary to attempt to stay in the middle of a spring range, it is acceptable to use the full published outlet pressure range without sacrificing spring performance or life.

### Accuracy

Of course, the need for accuracy must be evaluated. Accuracy is generally expressed as droop or the reduction of outlet pressure experienced as the flow rate increases. It is stated in percent, in. w.c. or lbs/in<sup>2</sup>. It indicates the difference between the outlet pressure at low flow rates and the outlet pressure at the published maximum flow rate. Droop is also called offset or proportional band.

## Inlet Pressure Losses

The regulator inlet pressure used for sizing should be measured directly at the regulator inlet. Measurements made at any distance upstream from the regulator are suspect because line loss can significantly reduce the actual inlet pressure to the regulator. If the regulator inlet pressure is given as a system pressure upstream, some compensation should be considered. Also, remember that downstream pressure always changes to some extent when inlet pressure changes.

## Orifice Diameter

The recommended selection for orifice size is the smallest diameter that will handle the flow. This can benefit operation in several ways: instability and premature wear might be avoided, relief valves may be smaller and lockup pressures may be reduced.

## Speed of Response

Direct-operated regulators generally have faster response to quick flow changes than pilot-operated regulators.

## Turn-Down Ratio

Within reasonable limits, most soft-seated regulators can maintain pressure down to zero flow. Therefore, a regulator sized for a high flow rate will usually have a turndown ratio sufficient to handle pilot-light sized loads during periods of low demand.

## Direct-operated Regulators vs Pilot-operated

	Self-op	Loading Pilot-op	Unloading Pilot-op
Accuracy	★	★★★	★★★★
Capacity	★	★★★	★★
Response Time	★★★	★★	★
Min. Differential	None Required	★★	★
Cost	★★★	★	★★
Maintenance	★★★	★	★★

Direct-operated regulators are the first choice unless the flow or accuracy requirements cannot be met.

### Accuracy

Direct-operated regulators are much less accurate than pilot-operated regulators. Some direct-op products designed for low pressure settings (less than 1 psi) achieve high accuracy by taking advantage of boost. However, in general direct-operated regulators require 20%-40% offset from setpoint whereas pilot-operated regulators require 1%-5%.

# Selecting and Sizing Pressure Reducing Regulators




Figure 1. Natural Gas Supply

## Capacity

Pilot-operated regulators are available in larger sizes and therefore higher capacity. Because of their superior accuracy, essentially all of a pilot-operated regulator's flow capability is usable whereas direct-operated regulator's useful flow capacity is limited due to excessive droop.

## Response Time

Direct-operated regulators have the fastest speed-of-response because changes in outlet pressure move the diaphragm which is tied directly to valve plug travel. Pilot-operated regulators go through the same chain of events but then loading pressure must change prior to repositioning the main valve. Loading-style pilot-ops are slightly faster than unloading-style because the main valve diaphragm senses outlet pressure giving the main valve a head start for outlet pressure changes.

## Minimum Differential Requirement

Direct-ops don't have a required minimum differential. They can continue controlling regardless of pressure differential whereas pilot-operated regulators require a pressure differential between their inlet and outlet in order to open the main valve. Unloading-style pilot-ops have small diaphragms which require higher differential pressures to fully open the main valve.

## Cost/Maintenance

Direct-operated regulators are the least complex and most compact of the regulator styles making them the least expensive and easiest to maintain. Unloading-style pilot-ops are the next least costly because of their simplistic main valve design which merges the diaphragm and valve plug into one component, the boot.

## Sizing Exercise: Industrial Plant Gas Supply

Regulator selection and sizing generally requires some subjective evaluation and decision making. For those with little experience, the best way to learn is through example. Therefore, these

exercises present selection and sizing problems for practicing the process of identifying suitable regulators.

Our task is to select a regulator to supply reduced pressure natural gas to meet the needs of a small industrial plant. The regulated gas is metered before entering the plant. The selection parameters are:

- Minimum inlet pressure,  $P_{1min} = 30$  psig
- Maximum inlet pressure,  $P_{1max} = 40$  psig
- Outlet pressure setting,  $P_2 = 1$  psig
- Flow,  $Q = 95\,000$  SCFH
- Accuracy (droop required) = 10% or less

## Quick Selection Guide

Turn to the Commercial/Industrial Quick Selection Guide. From the Quick Selection Guide, we find that the choices are:

- Type 133
- Type 1098-EGR

## Product Pages

Under the product number on the Quick Selection Guide is the page number of the product page. Look at the flow capacities of each of the possible choices. From the product pages we found the following:

- At 30 psig inlet pressure and 10% droop, the Type 133 has a flow capacity of 90,000 SCFH. This regulator does not meet the required flow capacity.
- At 30 psig inlet pressure, the Type 1098-EGR has a flow capacity of 131,000 SCFH. By looking at the Proportional Band (Droop) table, we see that the Type 6352 pilot with the yellow pilot spring and the green main valve has 0.05 psig droop. This regulator meets the selection criteria.

## Final Selection

We find that the Type 1098-EGR meets the selection criteria.



# Overpressure Protection Methods

Overpressure protective devices are of vital concern. Safety codes and current laws require their installation each time a pressure reducing station is installed that supplies gas from any system to another system with a lower maximum allowable operating pressure.

## Methods of Overpressure Protection

The most commonly used methods of overpressure protection, not necessarily in order of use or importance, include:

- Relief Valves (Figure 1)
- Monitors (Figures 2 and 3)
- Series Regulation (Figure 4)
- Shutoff (Figure 5)
- Relief Monitor (Figure 6)




Figure 1. Relief Valve Schematic

## Relief Valves

A relief valve is a device that vents process fluid to atmosphere to maintain the pressure downstream of the regulator below the safe maximum pressure. Relief is a common form of overpressure protection typically used for low to medium capacity applications. (Note: Fisher™ relief valves are not ASME safety relief valves.)

### Types of Relief Valves

The basic types of relief valves are:

- Pop type
- Direct-operated relief valves
- Pilot-operated relief valves
- Internal relief valves

The pop type relief valve is the simplest form of relief. Pop relief valves tend to go wide-open once the pressure has exceeded its setpoint by a small margin. The setpoint can drift over time and because of its quick opening characteristic the pop relief can sometimes become unstable when relieving, slamming open and closed. Many have a non-adjustable setpoint that is set and pinned at the factory.

If more accuracy is required from a relief valve, the direct-operated relief valve would be the next choice. They can throttle better than a pop relief valve and tend to be more stable, yet are still relatively simple. Although there is less drift in the setpoint of the direct-operated relief valve, a significant amount of build-up is often required to obtain the required capacity.

The pilot-operated relief valves have the most accuracy, but are also the most complicated and expensive type of relief. They use a pilot to dump loading pressure, fully stroking the main valve with very little build-up above setpoint. They have a large capacity and are available in larger sizes than other types of relief.

Many times, internal relief will provide adequate protection for a downstream system. Internal relief uses a relief valve built into the regulator for protection. If the pressure builds too far above the setpoint of the regulator, the relief valve in the regulator opens up, allowing excess pressure to escape through the regulator vent.

### Advantages

The relief valve is considered to be the most reliable type of overpressure protection because it is not subject to blockage by foreign objects in the line during normal operations. It also imposes no decrease in the regulator capacity which it is protecting and it has the added advantage of being its own alarm when it vents. It is normally reasonable in cost and keeps the customer in service despite the malfunction of the pressure reducing valve.

### Disadvantages

When the relief valve blows, it could possibly create a hazard in the surrounding area by venting. The relief valve must be sized carefully to relieve the gas or fluid that could flow through the pressure reducing valve at its maximum inlet pressure and in the wide-open position, assuming no flow to the downstream. Therefore, each application must be sized individually. The requirement for periodic testing of relief valves also creates an operational and/or public relations problem.

# Overpressure Protection Methods




Figure 2. Monitoring Regulators Schematic

## Monitoring Regulators

Monitoring is overpressure control by containment. When the working pressure reducing valve ceases to control the pressure, a second regulator installed in series, which has been sensing the downstream pressure, goes into operation to maintain the downstream pressure at a slightly higher than normal pressure. The monitoring concept is gaining in popularity, especially in low-pressure systems, because very accurate relay pilots permit reasonably close settings of the working and monitoring regulators.

The two types of wide-open monitoring are upstream and downstream monitoring. One question often asked is, “Which is better, upstream or downstream monitoring?” Using two identical regulators, there is no difference in overall capacity with either method.

When using monitors to protect a system or customer who may at times have zero load, a small relief valve is sometimes installed downstream of the monitor system with a setpoint just above the monitor. This allows for a token relief in case dust or dirt in the system prevents bubble tight shutoff of the regulators.

### Advantages

The major advantage is that there is no venting to atmosphere. During an overpressure situation, monitoring keeps the customer on line and keeps the downstream pressure relatively close to the setpoint of the working regulator. Testing is relatively easy and safe. To perform a periodic test on a monitor, increase the outlet set pressure of the working device and watch the pressure to determine if the monitor takes over.

### Disadvantages

Compared to relief valves, monitoring generally requires a higher initial investment. Monitoring regulators are subject to blocking, which is why filters or strainers are specified with increasing frequency. Because the monitor is in series, it is an added restriction in the line. This extra restriction can sometimes force one to use a larger, more expensive working regulator.




Figure 3. Working Monitor Schematic

## Working Monitor

A variation of monitoring overpressure protection that overcomes some of the disadvantages of a wide-open monitor is the “working monitor” concept wherein a regulator upstream of the working regulator uses two pilots. This additional pilot permits the monitoring regulator to act as a series regulator to control an intermediate pressure during normal operation. In this way, both units are always operating and can be easily checked for proper operation. Should the downstream pressure regulator fail to control, however, the monitoring pilot takes over the control at a slightly higher than normal pressure and keeps the customer on line. This is pressure control by containment and eliminates public relations problems.




Figure 4. Series Regulation Schematic

## Series Regulation

Series regulation is also overpressure protection by containment in that two regulators are set in the same pipeline. The first unit maintains an inlet pressure to the second valve that is within the maximum allowable operating pressure of the downstream system. Under this setup, if either regulator should fail, the resulting downstream pressure maintained by the other regulator would not exceed the safe maximum pressure.

This type of protection is normally used where the regulator station is reducing gas to a pressure substantially below the maximum allowable operating pressure of the distribution system being supplied. Series regulation is also found frequently in farm taps and in similar situations within the guidelines mentioned above.

# Overpressure Protection Methods

## Advantages

Again, nothing is vented to atmosphere.

## Disadvantages

Because the intermediate pressure must be cut down to a pressure that is safe for the entire downstream, the second-stage regulator often has very little pressure differential available to create flow. This can sometimes make it necessary to increase the size of the second regulator significantly. Another drawback occurs when the first-stage regulator fails and no change in the final downstream pressure is noticed because the system operates in what appears to be a “normal” manner without benefit of protection. Also, the first-stage regulator and intermediate piping must be capable of withstanding and containing maximum upstream pressure.

The second-stage regulator must also be capable of handling the full inlet pressure in case the first-stage unit fails to operate. In case the second-stage regulator fails, its actuator will be subjected to the intermediate pressure set by the first-stage unit. The second-stage actuator pressure ratings should reflect this possibility.




Figure 5. Shutoff Schematic

## Shutoff Devices

The shutoff device also accomplishes overpressure protection by containment. In this case, the customer is shutoff completely until the cause of the malfunction is determined and the device is manually reset. Many gas distribution companies use this as an added measure of protection for places of public assembly such as schools, hospitals, churches and shopping centers. In those cases, the shutoff device is a secondary form of overpressure protection. Shutoff valves are also commonly used by boiler manufacturers in combustion systems.

## Advantages

By shutting off the customer completely, the safety of the downstream system is assured. Again, there is no public relations problem or hazard from venting gas or other media.

## Disadvantages

The customer may be shutoff because debris has temporarily lodged under the seat of the operating regulator, preventing tight shutoff. A small relief valve can take care of this situation.

On a distribution system with a single supply, using a slam-shut can require two trips to each customer, the first to shutoff the service valve and the second visit after the system pressure has been restored to turn the service valve back on and re-light the appliances. In the event a shutoff is employed on a service line supplying a customer with processes such as baking, melting metals or glass making, the potential economic loss could dictate the use of an overpressure protection device that would keep the customer online.

Another problem associated with shutoffs is encountered when the gas warms up under no-load conditions. For instance, a regulator locked up at approximately 7 in. w.c. could experience a pressure rise of approximately 0.8 in. w.c. per degree Fahrenheit rise, which could cause the high-pressure shutoff to trip when there is actually no equipment failure.




Figure 6. Relief Monitor Schematic

## Relief Monitor

Another concept in overpressure protection for small industrial and commercial loads, up to approximately 10,000 ft<sup>3</sup>/hr, incorporates both an internal relief valve and a monitor. In this device, the relief capacity is purposely restricted to prevent excess venting of gas in order to bring the monitor into operation more quickly. The net result is that the downstream pressure is protected, in some cases to less than 1 psig. The amount of gas vented under maximum inlet pressure conditions does not exceed the amount vented by a domestic relief type service regulator.

# Overpressure Protection Methods

**Table 1. Types Of Overpressure Protection**

PERFORMANCE QUESTIONS	RELIEF	WORKING MONITOR	MONITOR	SERIES REGULATION	SHUTOFF	RELIEF MONITOR
Keeps application online?	Yes	Yes	Yes	Yes	No	Yes
Venting to atmosphere?	Yes	No	No	No	No	Minor
Manual resetting required after operation?	No	No	No	No	Yes	No
Reduces capacity of regulator?	No	Yes	Yes	Yes	No	No
Constantly working during normal operation?	No	Yes	No	Yes	No	Yes
Demands "emergency" action?	Yes	No	No	No	Yes	Maybe
Will surveillance of pressure charts indicate partial loss of performance of overpressure devices?	No	Yes	Maybe	Yes	No	No
Will surveillance of pressure charts indicate regulator has failed and safety device is in control?	Yes	Yes	Yes	Yes	Yes	Yes

With this concept, the limitation by regulator manufacturers of inlet pressure by orifice size, as is found in "full relief" devices, is overcome. Downstream protection is maintained, even with abnormally high inlet pressure. Public relations problems are kept to a minimum by the small amount of vented gas. Also, the unit does not require manual resetting, but can go back into operation automatically.

Dust or dirt can clear itself off the seat, but if the obstruction to the disk closing still exists when the load goes on, the customer would be kept online. When the load goes off, the downstream pressure will again be protected. During normal operation, the monitoring portion of the relief monitor is designed to move slightly with minor fluctuations in downstream pressure or flow.

## Summary

From the foregoing discussion, it becomes obvious that there are many design philosophies available and many choices of equipment to meet overpressure protection requirements.

Also, assume the overpressure device will be called upon to operate sometime after it is installed. The overall design must include an analysis of the conditions created when the protection device operates.

Table 1 shows:

- What happens when the various types of overpressure protection devices operate
- The type of reaction required
- The effect upon the customer or the public
- Some technical conditions

These are the general characteristics of the various types of safety devices. From the conditions and results shown, it is easier to decide which type of overpressure equipment best meets your needs. Undoubtedly, compromises will have to be made between the conditions shown here and any others which may govern your operating parameters.

## Overpressure Protection

Overpressure protection is a primary consideration in the design of any piping system. The objective of overpressure protection is to maintain the pressure downstream of a regulator at a safe maximum value.




Figure 1. Distribution System

In the system shown in Figure 1, a high-pressure transmission system delivers natural gas through a pressure reducing regulator to a lower pressure system that distributes gas to individual customers. The regulators, the piping and the devices that consume gas are protected from overpressure by relief valves. The relief valve's setpoint is adjusted to a level established by the lowest maximum pressure rating of any of the lower pressure system components.

## Maximum Pressure Considerations

Overpressure occurs when the pressure of a system is above the setpoint of the device controlling its pressure. It is evidence of some failure in the system (often the upstream regulator) and it can cause the entire system to fail if it's not limited. To implement overpressure protection, the weakest part in the pressure system is identified and measures are taken to limit overpressure to that component's maximum pressure rating. The most vulnerable components are identified by examining the maximum pressure ratings of the:

- Downstream equipment
- Low-pressure side of the main regulator
- Piping

The lowest maximum pressure rating of the three is the maximum allowable pressure.

## Downstream Equipment

The downstream component (appliance, burner, boiler, etc.) with the lowest maximum pressure rating sets the highest pressure that all the downstream equipment can be subjected to.

## Main Regulator

Pressure reducing regulators have different pressure ratings which refer to the inlet, outlet and internal components. The lowest of these should be used when determining the maximum allowable pressure.

## Piping

Piping is limited in its ability to contain pressure. In addition to any physical limitations, some applications must also conform to one or more applicable pressure rating codes or regulations.

## Relief Valves

Relief involves maintaining the pressure downstream of a regulator at a safe maximum pressure using any device that vents fluid to a lower pressure system (often the atmosphere). Relief valve exhaust must be directed or piped to a safe location. Relief valves perform this function. They are considered to be one of the most reliable types of overpressure protection available and are available in a number of different types. Fisher™ relief valves are not ASME safety relief valves.



Figure 2. Types of Relief Valves

# Principles of Relief Valves

## Relief Valve Popularity

Relief valves are popular for several reasons. They do not block the normal flow through a line. They do not decrease the capacities of the regulators they protect. And, they have the added advantage of being an alarm if they vent to atmosphere.

## Relief Valve Types

Relief valves are available in four general types. These include: pop type, direct-operated, pilot-operated and internal relief valves.

## Selection Criteria

### Pressure Build-up

A relief valve has a setpoint at which it begins to open. For the valve to fully open and pass the maximum flow, pressure must build up to some level above the setpoint of the relief valve. This is known as pressure build-up over setpoint or simply build-up.




Figure 3. Pressure Build-up

### Periodic Maintenance

A relief valve installed in a system that normally performs within design limits is very seldom exercised. The relief valve sits and waits for a failure. If it sits for long periods it may not perform as expected. Disks may stick in seats, setpoints can shift over time and small passages can become clogged with pipeline debris. Therefore, periodic maintenance and inspection is recommended. Maintenance requirements might influence the selection of a relief valve.

## Cost Versus Performance

Given several types of relief valves to choose from, selecting one type is generally based on the ability of the valve to provide adequate protection at the most economical cost. Reduced pressure build-up and increased capacity generally come at an increased price.

## Installation and Maintenance Considerations

Initial costs are only a part of the overall cost of ownership. Maintenance and installation costs must also be considered over the life of the relief valve. For example, internal relief might be initially more economical than an external relief valve. However, maintaining a regulator with internal relief requires that the system be shut down and the regulator isolated. This may involve additional time and the installation of parallel regulators and relief valves if flow is to be maintained to the downstream system during maintenance operations.

## Pop Type Relief Valve

The most simple type of relief valve is the pop type. They are used wherever economy is the primary concern and some setpoint drift is acceptable.




Figure 4. Pop Type Relief Valve Construction and Operation

### Operation

Pop type relief valves are essentially on-off devices. They operate in either the closed or wide-open position. Pop type designs register pressure directly on a spring-opposed poppet. The poppet assembly includes a soft disk for tight shutoff against the seat ring. When the inlet pressure increases above setpoint, the poppet assembly is pushed away from the seat. As the poppet rises, pressure registers against a greater surface area of the poppet. This dramatically increases the force on the poppet. Therefore, the poppet tends to travel to the fully open position reducing pressure build-up.

## Build-up Over Setpoint

Recall that pressure build-up relates capacity to pressure; increasing capacity requires some increase in pressure. In throttling relief valves, pressure build-up is related to accuracy. In pop type relief valves, build-up over setpoint results largely because the device is a restriction to flow rather than the spring rate of the valve's loading spring.

## Fixed Setpoint

The setpoint of a pop type valve cannot be adjusted by the user. The spring is initially loaded by the manufacturer. A pinned spring retainer keeps the spring in position. This is a safety measure that prevents tampering with the relief valve setpoint.

## Typical Applications

This type of relief valve may be used where venting to the atmosphere is acceptable, when the process fluid is compatible with the soft disk and when relief pressure variations are allowable. They are often used as inexpensive token relief. For example, they may be used simply to provide an audible signal of an overpressure condition.

These relief valves may be used to protect against overpressure stemming from a regulator with a minimal amount of seat leakage. Unchecked, this seat leakage could allow downstream pressure to build to full  $P_1$  over time. The use of a small pop type valve can be installed to protect against this situation.

These relief valves are also commonly installed with a regulator in a natural gas system farm tap, in pneumatic lines used to operate air drills, jackhammers and other pneumatic equipment and in many other applications.

## Advantages

Pop type relief valves use few parts. Their small size allows installation where space is limited. Also, low initial cost, easy installation and high capacity per dollar invested can result in economical system relief.

## Disadvantages

The setpoint of a pop type relief valve may change over time. The soft disk may stick to the seat ring and cause the pop pressure to increase.

As an on-off device, this style of relief valve does not throttle flow over a pressure range. Because of its on-off nature, this type of relief valve may create pressure surges in the downstream system.




Figure 5. Direct-Operated Relief Valve Schematic

If the relief valve capacity is significantly larger than the failed regulator's capacity, the relief valve may over-compensate each time it opens and closes. This can cause the downstream pressure system to become unstable and cycle. Cycling can damage the relief valve and downstream equipment.

## Direct-Operated Relief Valves

Compared to pop type relief valves, direct-operated relief valves provide throttling action and may require less pressure build-up to open the relief valve.

## Operation

A schematic of a direct-operated relief valve is shown in Figure 5. It looks like an ordinary direct-operated regulator except that it senses upstream pressure rather than downstream pressure. And, it uses a spring-close rather than a spring-open action. It contains the same essential elements as a direct-operated regulator:

- A diaphragm that measures system pressure
- A spring that provides the initial load to the diaphragm and is used to establish the relief setpoint
- A valve that throttles the relief flow

# Principles of Relief Valves

## Opening the Valve

As the inlet pressure rises above the setpoint of the relief valve, the diaphragm is pushed upward moving the valve plug away from the seat. This allows fluid to escape.

## Pressure Build-up Over Setpoint

As system pressure increases, the relief valve opens wider. This allows more fluid to escape and protects the system. The increase in pressure above the relief setpoint that is required to produce more flow through the relief valve is referred to as pressure build-up. The spring rate and orifice size influence the amount of pressure build-up that is required to fully stroke the valve.




Figure 6. Type 289 Relief Valve with Pitot Tube

## Product Example

### Pitot Tube

The relief valve shown in Figure 6 includes a pitot tube to reduce pressure build-up. When the valve is opening, high fluid velocity through the seat ring creates an area of relatively low pressure. Low pressure near the end of the pitot tube draws fluid out of the volume above the relief valve diaphragm and creates a partial vacuum which helps to open the valve. The partial vacuum above the diaphragm increases the relief valve capacity with less pressure build-up over setpoint.


### Typical Applications

Direct-operated relief valves are commonly used in natural gas systems supplying commercial enterprises such as restaurants and laundries and in industry to protect industrial furnaces and other equipment.


## Selection Criteria

### Pressure Build-up

Some direct-operated relief valves require significant pressure build-up to achieve maximum capacity. Others, such as those using pitot tubes, often pass high flow rates with minimal pressure build-up. Direct-operated relief valves can provide good accuracy within their design capacities.



PLUG AND SEAT RING MAIN VALVE



- INLET PRESSURE
- LOADING PRESSURE
- EXHAUST
- ATMOSPHERIC PRESSURE

ELASTOMERIC ELEMENT MAIN VALVE

Figure 7. Pilot-Operated Designs



## Cost Versus Performance

The purchase price of a direct-operated relief valve is typically lower than that of a pilot-operated design of the same size. However, pilot-operated designs may cost less per unit of capacity at very high flow rates.

## Pilot-Operated Relief Valves

Pilot-operated relief valves utilize a pair of direct-operated relief valves; a pilot and a main relief valve. The pilot increases the effect of changes in inlet pressure on the main relief valve.

## Operation

The operation of a pilot-operated relief valve is quite similar to the operation of a pilot-operated pressure reducing regulator. In normal operation, when system pressure is below setpoint of the relief valve, the pilot remains closed. This allows loading pressure to register on top of the main relief valve diaphragm. Loading pressure on top of the diaphragm is opposed by an equal pressure (inlet pressure) on the bottom side of the diaphragm. With little or no pressure differential across the diaphragm, the spring keeps the valve seated. Notice that a light-rate spring may be used because it does not oppose a large pressure differential across the diaphragm. The light-rate spring enables the main valve to travel to the wide-open position with little pressure build-up.

### Increasing Inlet Pressure

When the inlet pressure rises above the relief setpoint, the pilot spring is compressed and the pilot valve opens. The open pilot bleeds fluid out of the main valve spring case, decreasing pressure above the main relief valve diaphragm. If loading pressure escapes faster than it can be replaced through the restriction, the loading pressure above the main relief valve diaphragm is reduced and the relief valve opens. System overpressure exhausts through the vent.

### Decreasing Inlet Pressure

If inlet pressure drops back to the relief valve setpoint, the pilot loading spring pushes the pilot valve plug back against the pilot valve seat. Inlet pressure again loads the main relief valve diaphragm and closes the main valve.




Figure 8. Pilot-Operated Relief Valve

## Control Line

The control line connects the pilot with the pressure that is to be limited. When overpressure control accuracy is a high priority, the control line tap is installed where protection is most critical.

## Product Example

### Physical Description


This relief valve is a direct-operated relief valve with a pilot attached (Figure 8). The pilot is a modified direct-operated relief valve, the inlet pressure loads the diaphragm and flows through a restriction to supply loading pressure to the main relief valve diaphragm.

### Operation

During normal operation, the pilot is closed allowing loading pressure to register above the main relief valve's diaphragm. This pressure is opposed by inlet pressure acting on the bottom of the diaphragm.

If inlet pressure rises above setpoint, the pilot valve opens, exhausting the loading pressure. If loading pressure is reduced above the main relief valve diaphragm faster than it is replaced through the pilot fixed restriction, loading pressure is reduced and inlet pressure below the diaphragm will cause the main regulator to open.

# Principles of Relief Valves



REGULATORS THAT INCLUDE INTERNAL RELIEF VALVES OFTEN ELIMINATE THE REQUIREMENT FOR EXTERNAL OVERPRESSURE PROTECTION. THE ILLUSTRATION ON THE LEFT SHOWS THE REGULATOR WITH BOTH THE RELIEF VALVE AND THE REGULATOR VALVE IN THE CLOSED POSITION. THE ILLUSTRATION ON THE RIGHT SHOWS THE SAME UNIT AFTER  $P_1$  HAS INCREASED ABOVE THE RELIEF VALVE SETPOINT. THE DIAPHRAGM HAS MOVED OFF THE RELIEF VALVE SEAT ALLOWING FLOW (EXCESS PRESSURE) TO EXHAUST THROUGH THE SCREENED VENT.

Figure 9. Internal Relief Design

If inlet pressure falls below the relief set pressure, the pilot spring will again close the pilot exhaust, increasing loading pressure above the main relief valve diaphragm. This increasing loading pressure causes the main valve to travel towards the closed position.

## Performance

Pilot-operated relief valves are able to pass large flow rates with a minimum pressure build-up.

## Typical Applications

Pilot-operated relief valves are used in applications requiring high capacity and low pressure build-up.

## Selection Criteria

### Minimal Build-up

The use of a pilot to load and unload the main diaphragm and the light-rate spring enables the main valve to travel wide-open with little pressure build-up over setpoint.

### Throttling Action

The sensitive pilot produces smooth throttling action when inlet pressure rises above setpoint. This helps to maintain a steady downstream system pressure.

## Internal Relief

Regulators that include internal relief valves may eliminate the requirement for external overpressure protection.

## Operation

The regulator shown in Figure 9 includes an internal relief valve. The relief valve has a measuring element (the main regulator diaphragm), a loading element (a light spring) and a restricting element (a valve seat and disk). The relief valve assembly is located in the center of the regulator diaphragm.

### Build-up Over Setpoint

Like other spring-loaded designs, internal relief valves will only open wider if the inlet pressure increases. The magnitude of pressure build-up is determined by the spring rates of the loading spring plus the main spring. Both springs are considered because they act together to resist diaphragm movement when pressure exceeds the relief valve setpoint.

## Product Example

A typical internal relief regulator construction is shown in Figure 9. The illustration on the left shows the regulator with both the relief valve and regulator valve in the closed position. The illustration on the right shows the same unit after the inlet pressure has increased above the relief valve setpoint. The diaphragm has moved off the relief valve seat allowing the excess pressure to exhaust through the vent.

## Performance and Typical Applications

This design is available in configurations that can protect many pressure ranges and flow rates. Internal relief is often used in applications such as farm taps, industrial applications where atmospheric exhaust is acceptable and house service regulators.

### Selection Criteria

#### **Pressure Build-up**

Relief setpoint is determined by a combination of the relief valve and regulator springs; this design generally requires significant pressure build-up to reach its maximum relief flow rate. For the same reason, internal relief valves have limited relief capacities. They may provide full relief capacity, but should be carefully sized for each application.

#### **Space**

Internal relief has a distinct advantage when there is not enough space for an external relief valve.

#### **Cost versus Performance**

Because a limited number of parts are simply added to the regulator, this type of overpressure protection is relatively inexpensive compared to external relief valves of comparable capacity.

#### **Maintenance**

Because the relief valve is an integral part of the regulator's diaphragm, the regulator must be taken out of service when maintenance is performed. Therefore, the application should be able to tolerate either the inconvenience of intermittent supply or the expense of parallel regulators and relief valves.

## Selection and Sizing Criteria

There are a number of common steps in the relief valve selection and sizing process. For every application, the maximum pressure conditions, the wide-open regulator flow capacity and constant downstream demand should be determined. Finally, this information is used to select an appropriate relief valve for the application.

### Maximum Allowable Pressure

Downstream equipment includes all the components of the system that contain pressure; household appliances, tanks, tools, machines, outlet rating of the upstream regulators or other equipment. The component with the lowest maximum pressure rating establishes the maximum allowable system pressure.

### Regulator Ratings

Pressure reducing regulators upstream of the relief valve have ratings for their inlet, outlet and internal components. The lowest rating should be used when determining maximum allowable pressure.

### Piping

Piping pressure limitations imposed by governmental agencies, industry standards, manufacturers or company standards should be verified before defining the maximum overpressure level.

### Maximum Allowable System Pressure

The smallest of the pressure ratings mentioned above should be used as the maximum allowable pressure. This pressure level should not be confused with the relief valve setpoint which must be set below the maximum allowable system pressure.

### Determining Required Relief Valve Flow

A relief valve must be selected to exhaust enough flow to prevent the pressure from exceeding the maximum allowable system pressure. To determine this flow, review all upstream components for the maximum possible flow that will cause overpressure. If overpressure is caused by a pressure reducing regulator, use the regulator's wide-open flow coefficient to calculate the required flow of the relief valve. This regulator's wide-open flow is larger than the regulating flow used to select the pressure reducing regulator.

Sizing equations have been developed to standardize valve sizing. Refer to the Valve Sizing Calculations section to find these equations and explanations on how they are used.

# Principles of Relief Valves

## Determine Constant Demand

In some applications, the required relief capacity can be reduced by subtracting any load that is always on the system. This procedure should be approached with caution because it may be difficult to predict the worst-case scenario for downstream equipment failures. It may also be important to compare the chances of making a mistake in predicting the level of continuous flow consumption with the potential negative aspects of an error. Because of the hazards involved, relief valves are often sized assuming no continuous flow to downstream equipment.

## Selecting Relief Valves

### Required Information

We have already reviewed the variables required to calculate the regulator's wide-open flow rate. In addition, we need to know the type and temperature of the fluid in the system and the size of the piping. Finally, if a vent stack will be required, any additional build-up due to vent stack resistance should be considered.

### Regulator Lockup Pressure

A relief valve setpoint is adjusted to a level higher than the regulator's lockup pressure. If the relief valve setpoint overlaps lockup pressure of the regulator, the relief valve may open while the regulator is still attempting to control the system pressure.

### Identify Appropriate Relief Valves

Once the size, relief pressure and flow capacity are determined, we can identify a number of potentially suitable relief valves using the Quick Selection Guide in the front of each application section in this application guide. These selection guides give relief set (inlet) pressures, capacities and type numbers. These guides can then be further narrowed by reviewing individual product pages in each section.

### Final Selection

Final selection is usually a matter of compromise. Relief capacities, build-up levels, sensitivity, throttling capabilities, cost of installation and maintenance, space requirements, initial purchase price and other attributes are all considered when choosing any relief valve.

## Applicable Regulations

The relief valves installed in some applications must meet governmental, industry or company criteria.

## Sizing and Selection Exercise

To gain a better understanding of the selection and sizing process, it may be helpful to step through a typical relief valve sizing exercise.

### Initial Parameters

We'll assume that we need to specify an appropriate relief valve for a regulator serving a large plant air supply. There is sufficient space to install the relief valve and the controlled fluid is clean plant air that can be exhausted without adding a vent stack.

### Performance Considerations

The plant supervisor wants the relief valve to throttle open smoothly so that pressure surges will not damage instruments and equipment in the downstream system. This will require the selection of a relief valve that will open smoothly. Plant equipment is periodically shut down but the air supply system operates continuously. Therefore, the relief valve must also have the capacity to exhaust the full flow of the upstream system.

### Upstream Regulator

The regulator used is 1 in. in size with a 3/8 in. orifice. The initial system parameters of pressure and flow were determined when the regulator was sized for this application.

### Pressure Limits

The plant maintenance engineer has determined that the relief valve should begin to open at 20 psig and downstream pressure should not rise above 30 psig maximum allowable system pressure.

### Relief Valve Flow Capacity

The wide-open regulator flow is calculated to be 23,188 SCFH.

## Relief Valve Selection

### Quick Selection Guide


Find the Relief Valve Quick Selection Guide in this Application Guide; it gives relief set (inlet) pressures and comparative flow capacities of various relief valves. Because this guide is used to identify potentially suitable relief valves, we can check the relief set (inlet) pressures closest to 20 psig and narrow the range of choices. We find that two relief valves have the required flow capacity at our desired relief set (inlet) pressure.

### Product Pages

If we look at the product pages for the potential relief valves, we find that a 1 in. Type 289H provides the required capacity within the limits of pressure build-up specified in our initial parameters.

### Checking Capacity

Capacity curves for the 1 in. Type 289H with this spring are shown in Figure 10. By following the curve for the 20 psig setpoint to the point where it intersects with the 30 psig division, we find that our relief valve can handle more than the 23,188 SCFH required.



B2309

Figure 10. Type 289H Flow Capacities

# Principles of Series Regulation and Monitor Regulators

## Series Regulation

Series regulation is one of the simplest systems used to provide overpressure protection by containment. In the example shown in Figure 1, the inlet pressure is 100 psig, the desired downstream pressure is 10 psig and the maximum allowable operating pressure (MAOP) is 40 psig. The setpoint of the downstream regulator is 10 psig and the setpoint of the upstream regulator is 30 psig.




Figure 1. Series Regulation

## Failed System Response

If regulator B fails, downstream pressure ( $P_2$ ) is maintained at the setpoint of regulator A less whatever drop is required to pass the required flow through the failed regulator B. If regulator A fails, the intermediate pressure will be 100 psig. Regulator B must be able to withstand 100 psig inlet pressure.

## Regulator Considerations

Either direct-operated or pilot-operated regulators may be used in this system. Should regulator A fail,  $P_{intermediate}$  will approach  $P_1$  so the outlet rating and spring casing rating of regulator A must be high enough to withstand full  $P_1$ . This situation may suggest the use of a relief valve between the two regulators to limit the maximum value of  $P_{intermediate}$ .


## Applications and Limitations

A problem with series regulation is maintaining tight control of  $P_2$  if the downstream regulator fails. In this arrangement, it is often impractical to have the setpoints very close together. If they are, the pressure drop across regulator B will be quite small. With a small pressure drop, a very large regulator may be required to pass the desired flow.

Because of the problem in maintaining close control of  $P_2$ , series regulation is best suited to applications where the regulator station is reducing pressure to a value substantially below the maximum allowable operating pressure of the downstream system. Farm taps are a good example. The problem of low-pressure drop across the second regulator is less pronounced in low flow systems.

## Upstream Wide-Open Monitors

The only difference in configuration between series regulation and monitors is that in monitor installations, both regulators sense downstream pressure,  $P_2$ . Thus, the upstream regulator must have a control line.



IN WIDE-OPEN MONITOR SYSTEMS, BOTH REGULATORS SENSE DOWNSTREAM PRESSURE. SETPOINTS MAY BE VERY CLOSE TO EACH OTHER. IF THE WORKER REGULATOR FAILS, THE MONITOR ASSUMES CONTROL AT A SLIGHTLY HIGHER SETPOINT. IF THE MONITOR REGULATOR FAILS, THE WORKER CONTINUES TO PROVIDE CONTROL.

Figure 2. Wide-Open Upstream Monitor

## System Values

In the example shown in Figure 2, assume that  $P_1$  is 100 psig and the desired downstream pressure,  $P_2$ , is 10 psig. Also assume that the maximum allowable operating pressure of the downstream system is 20 psig; this is the limit we cannot exceed. The setpoint of the downstream regulator is set at 10 psig to maintain the desired  $P_2$  and the setpoint of the upstream regulator is set at 15 psig to maintain  $P_2$  below the maximum allowable operating pressure.

## Normal Operation

When both regulators are functioning properly, regulator B holds  $P_2$  at its setpoint of 10 psig. Regulator A, sensing a pressure lower than its setpoint of 15 psig tries to increase  $P_2$  by going wide-open. This configuration is known as an upstream wide-open monitor where upstream regulator A monitors the pressure established by regulator B. Regulator A is referred to as the monitor or standby regulator while regulator B is called the worker or the operator.

# Principles of Series Regulation and Monitor Regulators

## Worker Regulator B Fails

If regulator B fails open, regulator A, the monitor, assumes control and holds  $P_2$  at 15 psig. Note that pressure  $P_{\text{Intermediate}}$  is now  $P_2$  plus whatever drop is necessary to pass the required flow through the failed regulator B.


## Equipment Considerations

Wide-open monitoring systems may use either direct- or pilot-operated regulators, the choice of which is dependent on other system requirements. Obviously, the upstream regulator must have external registration capability in order to sense downstream pressure,  $P_2$ .

In terms of ratings,  $P_{\text{Intermediate}}$  will rise to full  $P_1$  when regulator A fails, so the body outlet of regulator A and the inlet of regulator B must be rated for full  $P_1$ .

## Downstream Wide-Open Monitors

The difference between upstream and downstream monitor systems (Figure 3) is that the functions of the two regulators are reversed. In other words, the monitor or standby regulator, is downstream of the worker or operator. Systems can be changed from upstream to downstream monitors, and vice versa, by simply reversing the setpoints of the two regulators.



THE ONLY DIFFERENCE BETWEEN UPSTREAM WIDE-OPEN MONITOR SYSTEMS AND DOWNSTREAM WIDE-OPEN MONITOR SYSTEMS IS THE ROLE EACH REGULATOR PLAYS. WORKERS AND MONITORS MAY BE SWITCHED BY SIMPLY REVERSING THE SETPOINTS.

Figure 3. Wide-Open Downstream Monitor

## Normal Operation

Again, assume an inlet pressure of 100 psig and a controlled pressure ( $P_2$ ) of 10 psig. Regulator A is now the worker so it maintains  $P_2$  at its setpoint of 10 psig. Regulator B, the monitor, is set at 15 psig and so remains open.

## Worker Regulator A Fails

If the worker, regulator A, fails in an open position, the monitor, regulator B, senses the increase in  $P_2$  and holds  $P_2$  at its setpoint of 15 psig. Note that  $P_{\text{Intermediate}}$  is now  $P_1$  minus whatever drop is taken across the failed regulator A.


## Upstream Versus Downstream Monitors

The decision to use either an upstream or downstream monitor system is largely a matter of personal preference or company policy.

In normal operation, the monitor remains open while the worker is frequently exercised. Many users see value in changing the system from an upstream to a downstream monitor at regular intervals, much like rotating the tires on an automobile. Most fluids have some impurities such as moisture, rust or other debris, which may deposit on regulator components, such as stems and cause them to become sticky or bind. Therefore, occasionally reversing the roles of the regulators so that both are exercised is sometimes seen as a means of ensuring that protection is available when needed. The job of switching is relatively simple as only the setpoints of the two regulators are changed. In addition, the act of changing from an upstream to a downstream monitor requires that someone visit the site so there is an opportunity for routine inspection.

## Working Monitors

Working monitors (Figure 4) use design elements from both series regulation and wide-open monitors. In a working monitor installation, the two regulators are continuously working as series regulators to take two pressure cuts.



WORKING MONITOR SYSTEMS MUST USE A PILOT-OPERATED REGULATOR AS THE MONITOR, WHICH IS ALWAYS IN THE UPSTREAM POSITION. TWO PILOTS ARE USED ON THE MONITOR REGULATOR; ONE TO CONTROL THE INTERMEDIATE PRESSURE AND ONE TO MONITOR THE DOWNSTREAM PRESSURE. BY TAKING TWO PRESSURE DROPS, BOTH REGULATORS ARE ALLOWED TO EXERCISE.

Figure 4. Working Monitor

# Principles of Series Regulation and Monitor Regulators

## Downstream Regulator

The downstream regulator may be either direct or pilot-operated. It is installed just as in a series or wide-open monitor system. Its setpoint controls downstream pressure,  $P_2$ .

## Upstream Regulator

The upstream regulator must be a pilot-operated type because it uses two pilots; a monitor pilot and a worker pilot. The worker pilot is connected just as in series regulation and controls the intermediate pressure  $P_{\text{Intermediate}}$ . Its setpoint 45 psig is at some intermediate value that allows the system to take two pressure drops. The monitor pilot is in series ahead of the worker pilot and is connected so that it senses downstream pressure,  $P_2$ . The monitor pilot setpoint 15 psig is set slightly higher than the normal  $P_2$  10 psig.

## Normal Operation

When both regulators are performing properly, downstream pressure is below the setting of the monitor pilot, so it is fully open trying to raise system pressure. Standing wide-open, the monitor pilot allows the worker pilot to control the intermediate pressure,  $P_{\text{Intermediate}}$  at 45 psig. The downstream regulator is controlling  $P_2$  at 10 psig.

## Downstream Regulator Fails

If the downstream regulator fails, the monitor pilot will sense the increase in pressure and take control at 15 psig.

## Upstream Regulator Fails

If the upstream regulator fails, the downstream regulator will remain in control at 10 psig. Note that the downstream regulator must be rated for the full system inlet pressure  $P_1$  of 100 psig because this will be its inlet pressure if the upstream regulator fails. Also note that the outlet rating of the upstream regulator and any other components that are exposed to  $P_{\text{Intermediate}}$  must be rated for full  $P_1$ .

## Sizing Monitor Regulators

Due to the tortuous path through the regulator, the monitor causes some pressure loss, decreasing the available differential pressure for the worker and consequently decreasing its flow capability. At low flows, the pressure loss will be minimal while at high flow rates, it will be larger. Impact is typically minor in applications with large differentials between inlet of the station and outlet but can be substantial in small differential applications.

Historically, monitors have been sized using a rule-of-thumb stating that installing a monitor reduces the worker's flow capacity by 30%. In many cases this imprecise rule leads to oversized stations. There are some low pressure differential applications where this rule-of-thumb actually undersizes the station. The best way of sizing monitors is to first determine the maximum pressure drop across the monitor. Either the below formula can be used or a sizing program capable of solving for pressure drop. Once the worst-case pressure drop across the monitor is known, the worker can be sized as a stand-alone regulator using the available pressure differential to determine if the selected regulator will satisfy the flow requirement.

For an upstream monitor, use the following equation:

$$\Delta P = P_1 \left[ \sin^{-1} \left( Q / \left( C_g P_1 \sqrt{\frac{520}{GT}} \right) \right) \text{deg} \cdot \frac{C_1}{3417} \right]^2$$

or

$$\Delta P = P_1 \left[ \sin^{-1} \left( Q / \left( C_g P_1 \sqrt{\frac{520}{GT}} \right) \right) \text{rad} \cdot \frac{C_1}{59.64} \right]^2$$

Where,

$\Delta P$  = pressure drop across the regulator, psi

$P_1$  = absolute inlet pressure, psia ( $P_1$  gauge + 14.7)

$Q$  = maximum gas flow rate, SCFH

$C_g$  = regulating gas sizing coefficient

$G$  = specific gravity of the gas

$T$  = absolute temperature of gas at inlet, °Rankine

$C_1$  = flow coefficient

For downstream monitors, the same equation can be used to determine the intermediate pressure by solving via iteration. In this case,  $P_1$  is the intermediate pressure instead of inlet pressure and  $\Delta P$  is the difference between intermediate pressure and outlet pressure.



## Vacuum Applications

Vacuum regulators and vacuum breakers are widely used in process plants. Conventional regulators and relief valves might be suitable for vacuum service if applied correctly. This section provides fundamentals and examples.




Figure 1. Vacuum Terminology

## Vacuum Terminology

Engineers use a variety of terms to describe vacuum, which can cause some confusion. Determine whether the units are in absolute pressure or gauge pressure (0 psig / 0 bar g) is atmospheric pressure.

- 5 psig / 0.34 bar g vacuum is 5 psi / 0.34 bar below atmospheric pressure.
- -5 psig / -0.34 bar g is 5 psi / 0.34 bar below atmospheric pressure.
- 9.7 psia / 0.67 bar a is 9.7 psi / 0.67 bar above absolute zero or 5 psi / 0.34 bar below atmospheric pressure (14.7 psia - 5 psi = 9.7 psi / 1.01 bar a - 0.34 bar = 0.67 bar a).

## Vacuum Control Devices

Just like there are pressure reducing regulators and pressure relief valves for positive pressure service, there are also two basic types of valves for vacuum service. The terms used for each are sometimes confusing. Therefore, it is sometimes necessary to ask further questions to determine the required function of the valve. The terms vacuum regulator and vacuum breaker will be used in these pages to differentiate the two types.

## Vacuum Regulators

Vacuum regulators maintain a constant vacuum at the regulator inlet. A loss of this vacuum (increase in absolute pressure) beyond setpoint registers on the diaphragm and opens the disk. It depends on the valve as to which side of the diaphragm control pressure is measured. Opening the valve plug permits a downstream vacuum of lower absolute pressure than the controlled vacuum to restore the upstream vacuum to its original setting.

Besides the typical vacuum regulator, a conventional regulator can be suitable if applied correctly. Any pressure reducing regulator (spring to open device) that has an external control line connection and an O-ring stem seal can be used as a vacuum regulator. Installation requires a control line to connect the vacuum being controlled and the spring case. The regulator spring range is now a negative pressure range and the body flow direction is the same as in conventional pressure reducing service.

## Vacuum Breakers (Relief Valves)

Vacuum breakers are used in applications where an increase in vacuum must be limited. An increase in vacuum (decrease in absolute pressure) beyond a certain value causes the diaphragm to move and open the disk. This permits atmospheric pressure or a positive pressure or an upstream vacuum that has higher absolute pressure than the downstream vacuum, to enter the system and restore the controlled vacuum to its original pressure setting.

A vacuum breaker is a spring-to-close device, meaning that if there is no pressure on the valve the spring will push the valve plug into its seat. There are various Fisher™ brand products to handle this application. Some valves are designed as vacuum breakers. Fisher brand relief valves can also be used as vacuum breakers.

# Vacuum Control




Figure 2. Typical Vacuum Regulator





Figure 3. Typical Vacuum Breaker

A conventional relief valve can be used as a vacuum breaker, as long as it has a threaded spring case vent so a control line can be attached. If inlet pressure is atmospheric air, then the internal pressure registration from body inlet to lower casing admits atmospheric pressure to the lower casing. If inlet pressure is not atmospheric, a relief valve in which the lower casing can be vented to atmosphere when the body inlet is pressurized must be chosen. In this case, the terminology “blocked throat” and “external registration with O-ring stem seal” are used for clarity.


A spring that normally has a range of 6 to 11 in. w.c. / 15 to 27 mbar positive pressure will now have a range of 6 to 11 in. w.c. / 15 to 27 mbar vacuum (negative pressure). It may be expedient to bench set the vacuum breaker if the type chosen uses a spring case closing cap. Removing the closing cap to gain access to the adjusting screw will admit air into the spring case when in vacuum service.

## Vacuum Regulator Installation Examples



- A6555
- CONTROL PRESSURE (VACUUM)
  - ATMOSPHERIC PRESSURE
  - OUTLET PRESSURE (VACUUM)

Figure 4. Type 133L



- CONTROL PRESSURE (VACUUM)
- LOADING PRESSURE
- ATMOSPHERIC PRESSURE
- OUTLET PRESSURE (VACUUM)

Figure 5. Type T208VRM used with Type 1098-EGR in a Vacuum Regulator Installation

# Vacuum Control

## Vacuum Breaker Installation Examples




Figure 6. Type 1805






Figure 7. Type T205VB used with Type 1098-EGR in a Vacuum Breaker Installation. If the positive pressure exceeds the Type 1098-EGR casing rating, then a Type 67CF with a Type H800 relief valve should be added.

## Vacuum Breaker Installation Examples



If inlet is positive pressure:

- Select balancing diaphragm and tapped lower casing construction.
- Leave lower casing open to atmospheric pressure.

Figure 8. Type 289H Relief Valve used in a Vacuum Breaker Installation

Figure 9. Type 66R Relief Valve used in a Vacuum Breaker Installation




Figure 10. Type 66RR Relief Valve used in a Vacuum Breaker Installation

# Vacuum Control




Figure 11. Example of Gas Blanketing in Vacuum

## Gas Blanketing in Vacuum

When applications arise where the gas blanketing requirements are in vacuum, a combination of a vacuum breaker and a regulator may be used. For example, in low inches of water column vacuum, a Type T205VB vacuum breaker and a Type 66-112 vacuum regulator can be used for very precise control.

Vacuum blanketing is useful for vessel leakage to atmosphere and the material inside the vessel is harmful to the surrounding environment. If leakage were to occur, only outside air would enter the vessel because of the pressure differential in the tank. Therefore, any process vapors in the tank would be contained.

## Features of Fisher™ Brand Vacuum Regulators and Breakers

- **Precision Control of Low Pressure Settings**—Large diaphragm areas provide more accurate control at low pressure settings. Some of these regulators are used as pilots on our Tank Blanketing and Vapor Recovery Regulators. Therefore, they are designed to be highly accurate, usually within 1 in. w.c. / 2 mbar.
- **Corrosion Resistance**—Constructions are available in a variety of materials for compatibility with corrosive process gases. Wide selection of elastomers compatible with flowing media.
- **Rugged Construction**—Diaphragm case and internal parts are designed to withstand vibration and shock.
- **Wide Product Offering**—Fisher brand regulators can be either direct-operated or pilot-operated regulators.
- **Fisher Brand Advantage**—Widest range of products and a proven history in the design and manufacture of process control equipment. A sales channel that offers local stock and support.
- **Spare Parts**—Low cost parts that are interchangeable with other Fisher brand in your plant.
- **Easy Sizing and Selection**—Most applications can be sized utilizing the Fisher brand Sizing Program and Sizing Coefficients.

# Valve Sizing Calculations (Traditional Method)

## Introduction

Fisher™ regulators and valves have traditionally been sized using equations derived by the company. There are now standardized calculations that are becoming accepted worldwide. Some product literature continues to demonstrate the traditional method, but the trend is to adopt the standardized method. Therefore, both methods are covered in this application guide.

Improper valve sizing can be both expensive and inconvenient. A valve that is too small will not pass the required flow and the process will be starved. An oversized valve will be more expensive and it may lead to instability and other problems.

The days of selecting a valve based upon the size of the pipeline are gone. Selecting the correct valve size for a given application requires a knowledge of process conditions that the valve will actually see in service. The technique for using this information to size the valve is based upon a combination of theory and experimentation.

## Sizing for Liquid Service

Using the principle of conservation of energy, Daniel Bernoulli found that as a liquid flows through an orifice, the square of the fluid velocity is directly proportional to the pressure differential across the orifice and inversely proportional to the specific gravity of the fluid. The greater the pressure differential, the higher the velocity; the greater the density, the lower the velocity. The volume flow rate for liquids can be calculated by multiplying the fluid velocity times the flow area.

By taking into account units of measurement, the proportionality relationship previously mentioned, energy losses due to friction and turbulence and varying discharge coefficients for various types of orifices (or valve bodies), a basic liquid sizing equation can be written as follows

$$Q = C_v \sqrt{\Delta P / G} \quad (1)$$

where:

- Q = Capacity in gallons per minute
- C<sub>v</sub> = Valve sizing coefficient determined experimentally for each style and size of valve, using water at standard conditions as the test fluid
- ΔP = Pressure differential in psi
- G = Specific gravity of fluid (water at 60°F = 1.0000)

Thus, C<sub>v</sub> is numerically equal to the number of U.S. gallons of water at 60°F that will flow through the valve in one minute when the pressure differential across the valve is 1 lb/in<sup>2</sup>. C<sub>v</sub> varies with both size and style of valve, but provides an index for comparing liquid capacities of different valves under a standard set of conditions.




Figure 1. Standard FCI Test Piping for C<sub>v</sub> Measurement

To aid in establishing uniform measurement of liquid flow capacity coefficients (C<sub>v</sub>) among valve manufacturers, the Fluid Controls Institute (FCI) developed a standard test piping arrangement, shown in Figure 1. Using such a piping arrangement, most valve manufacturers develop and publish C<sub>v</sub> information for their products, making it relatively easy to compare capacities of competitive products.

To calculate the expected C<sub>v</sub> for a valve controlling water or other liquids that behave like water, the basic liquid sizing equation above can be re-written as follows

$$C_v = Q \sqrt{\frac{G}{\Delta P}} \quad (2)$$

## Viscosity Corrections

Viscous conditions can result in significant sizing errors in using the basic liquid sizing equation, since published C<sub>v</sub> values are based on test data using water as the flow medium. Although the majority of valve applications will involve fluids where viscosity corrections can be ignored or where the corrections are relatively small, fluid viscosity should be considered in each valve selection.

Emerson has developed a nomograph (Figure 2) that provides a viscosity correction factor (F<sub>v</sub>). It can be applied to the standard C<sub>v</sub> coefficient to determine a corrected coefficient (C<sub>vr</sub>) for viscous applications.

## Finding Valve Size

Using the C<sub>v</sub> determined by the basic liquid sizing equation and the flow and viscosity conditions, a fluid Reynolds number can be found by using the nomograph in Figure 2. The graph of Reynolds number vs. viscosity correction factor (F<sub>v</sub>) is used to determine the correction factor needed. (If the Reynolds number is greater than 3500, the correction will be ten percent or less.) The actual required C<sub>v</sub> (C<sub>vr</sub>) is found by the equation:

$$C_{vr} = F_v C_v \quad (3)$$

From the valve manufacturer's published liquid capacity information, select a valve having a C<sub>v</sub> equal to or higher than the required coefficient (C<sub>vr</sub>) found by the equation above.

# Valve Sizing Calculations (Traditional Method)




Figure 2. Nomograph for Determining Viscosity Correction

## Nomograph Instructions

Use this nomograph to correct for the effects of viscosity. When assembling data, all units must correspond to those shown on the nomograph. For high-recovery, ball-type valves, use the liquid flow rate Q scale designated for single-ported valves. For butterfly and eccentric disk rotary valves, use the liquid flow rate Q scale designated for double-ported valves.

## Nomograph Equations

1. Single-Ported Valves: 
$$N_R = 17,250 \frac{Q}{\sqrt{C_v v_{CS}}}$$

2. Double-Ported Valves: 
$$N_R = 12,200 \frac{Q}{\sqrt{C_v v_{CS}}}$$

## Nomograph Procedure

1. Lay a straight edge on the liquid sizing coefficient on  $C_v$  scale and flow rate on Q scale. Mark intersection on index line. Procedure A uses value of  $C_{vc}$ ; Procedures B and C use value of  $C_{vr}$ .
2. Pivot the straight edge from this point of intersection with index line to liquid viscosity on proper  $n$  scale. Read Reynolds number on  $N_R$  scale.
3. Proceed horizontally from intersection on  $N_R$  scale to proper curve and then vertically upward or downward to  $F_v$  scale. Read  $C_v$  correction factor on  $F_v$  scale.



# Valve Sizing Calculations (Traditional Method)

## Predicting Flow Rate

Select the required liquid sizing coefficient ( $C_{vr}$ ) from the manufacturer's published liquid sizing coefficients ( $C_v$ ) for the style and size valve being considered. Calculate the maximum flow rate ( $Q_{max}$ ) in gallons per minute (assuming no viscosity correction required) using the following adaptation of the basic liquid sizing equation:

$$Q_{max} = C_{vr} \sqrt{\Delta P / G} \quad (4)$$

Then incorporate viscosity correction by determining the fluid Reynolds number and correction factor  $F_v$  from the viscosity correction nomograph and the procedure included on it.

Calculate the predicted flow rate ( $Q_{pred}$ ) using the formula:

$$Q_{pred} = \frac{Q_{max}}{F_v} \quad (5)$$

## Predicting Pressure Drop

Select the required liquid sizing coefficient ( $C_{vr}$ ) from the published liquid sizing coefficients ( $C_v$ ) for the valve style and size being considered. Determine the Reynolds number and correct factor  $F_v$  from the nomograph and the procedure on it. Calculate the sizing coefficient ( $C_{vc}$ ) using the formula:

$$C_{vc} = \frac{C_{vr}}{F_v} \quad (6)$$

Calculate the predicted pressure drop ( $\Delta P_{pred}$ ) using the formula:

$$\Delta P_{pred} = G (Q/C_{vc})^2 \quad (7)$$

## Flashing and Cavitation

The occurrence of flashing or cavitation within a valve can have a significant effect on the valve sizing procedure. These two related physical phenomena can limit flow through the valve in many applications and must be taken into account in order to accurately size a valve. Structural damage to the valve and adjacent piping may also result. Knowledge of what is actually happening within the valve might permit selection of a size or style of valve which can reduce or compensate for, the undesirable effects of flashing or cavitation.




Figure 3. Vena Contracta




Figure 4. Comparison of Pressure Profiles for High and Low Recovery Valves

The “physical phenomena” label is used to describe flashing and cavitation because these conditions represent actual changes in the form of the fluid media. The change is from the liquid state to the vapor state and results from the increase in fluid velocity at or just downstream of the greatest flow restriction, normally the valve port. As liquid flow passes through the restriction, there is a necking down or contraction, of the flow stream. The minimum cross-sectional area of the flow stream occurs just downstream of the actual physical restriction at a point called the vena contracta, as shown in Figure 3.

To maintain a steady flow of liquid through the valve, the velocity must be greatest at the vena contracta, where cross sectional area is the least. The increase in velocity (or kinetic energy) is accompanied by a substantial decrease in pressure (or potential energy) at the vena contracta. Farther downstream, as the fluid stream expands into a larger area, velocity decreases and pressure increases. But, of course, downstream pressure never recovers completely to equal the pressure that existed upstream of the valve. The pressure differential ( $\Delta P$ ) that exists across the valve is a measure

# Valve Sizing Calculations (Traditional Method)

of the amount of energy that was dissipated in the valve. Figure 4 provides a pressure profile explaining the differing performance of a streamlined high recovery valve, such as a ball valve and a valve with lower recovery capabilities due to greater internal turbulence and dissipation of energy.

Regardless of the recovery characteristics of the valve, the pressure differential of interest pertaining to flashing and cavitation is the differential between the valve inlet and the vena contracta. If pressure at the vena contracta should drop below the vapor pressure of the fluid (due to increased fluid velocity at this point) bubbles will form in the flow stream. Formation of bubbles will increase greatly as vena contracta pressure drops further below the vapor pressure of the liquid. At this stage, there is no difference between flashing and cavitation, but the potential for structural damage to the valve definitely exists.

If pressure at the valve outlet remains below the vapor pressure of the liquid, the bubbles will remain in the downstream system and the process is said to have “flashed.” Flashing can produce serious erosion damage to the valve trim parts and is characterized by a smooth, polished appearance of the eroded surface. Flashing damage is normally greatest at the point of highest velocity, which is usually at or near the seat line of the valve plug and seat ring.

However, if downstream pressure recovery is sufficient to raise the outlet pressure above the vapor pressure of the liquid, the bubbles will collapse or implode, producing cavitation. Collapsing of the vapor bubbles releases energy and produces a noise similar to what one would expect if gravel were flowing through the valve. If the bubbles collapse in close proximity to solid surfaces, the energy released gradually wears the material leaving a rough, cylinder like surface. Cavitation damage might extend to the downstream pipeline, if that is where pressure recovery occurs and the bubbles collapse. Obviously, “high recovery” valves tend to be more subject to cavitation, since the downstream pressure is more likely to rise above the vapor pressure of the liquid.

## Choked Flow

Aside from the possibility of physical equipment damage due to flashing or cavitation, formation of vapor bubbles in the liquid flow stream causes a crowding condition at the vena contracta which tends to limit flow through the valve. So, while the basic liquid sizing equation implies that there is no limit to the amount of flow through a valve as long as the differential pressure across the valve increases, the realities of flashing and cavitation prove otherwise. If valve




Figure 5. Flow Curve Showing  $C_v$  and  $K_m$





Figure 6. Relationship Between Actual  $\Delta P$  and  $\Delta P$  Allowable


pressure drop is increased slightly beyond the point where bubbles begin to form, a choked flow condition is reached. With constant upstream pressure, further increases in pressure drop (by reducing downstream pressure) will not produce increased flow. The limiting pressure differential is designated  $\Delta P_{allow}$  and the valve recovery coefficient ( $K_m$ ) is experimentally determined for each valve, in order to relate choked flow for that particular valve to the basic liquid sizing equation.  $K_m$  is normally published with other valve capacity coefficients. Figures 5 and 6 show these flow vs. pressure drop relationships.

# Valve Sizing Calculations (Traditional Method)



USE THIS CURVE FOR WATER. ENTER ON THE ABSCISSA AT THE WATER VAPOR PRESSURE AT THE VALVE INLET. PROCEED VERTICALLY TO INTERSECT THE CURVE. MOVE HORIZONTALLY TO THE LEFT TO READ THE CRITICAL PRESSURE RATIO,  $r_c$ , ON THE ORDINATE.

Figure 7. Critical Pressure Ratios for Water



USE THIS CURVE FOR LIQUIDS OTHER THAN WATER. DETERMINE THE VAPOR PRESSURE/CRITICAL PRESSURE RATIO BY DIVIDING THE LIQUID VAPOR PRESSURE AT THE VALVE INLET BY THE CRITICAL PRESSURE OF THE LIQUID. ENTER ON THE ABSCISSA AT THE RATIO JUST CALCULATED AND PROCEED VERTICALLY TO INTERSECT THE CURVE. MOVE HORIZONTALLY TO THE LEFT AND READ THE CRITICAL PRESSURE RATIO,  $r_c$ , ON THE ORDINATE.

Figure 8. Critical Pressure Ratios for Liquid Other than Water

Use the following equation to determine maximum allowable pressure drop that is effective in producing flow. Keep in mind, however, that the limitation on the sizing pressure drop,  $\Delta P_{allow}$ , does not imply a maximum pressure drop that may be controlled by the valve.

$$\Delta P_{allow} = K_m (P_1 - r_c P_v) \quad (8)$$

where:

- $\Delta P_{allow}$  = maximum allowable differential pressure for sizing purposes, psi
- $K_m$  = valve recovery coefficient from manufacturer's literature
- $P_1$  = body inlet pressure, psia
- $r_c$  = critical pressure ratio determined from Figures 7 and 8
- $P_v$  = vapor pressure of the liquid at body inlet temperature, psia (vapor pressures and critical pressures for many common liquids are provided in the Physical Constants of Hydrocarbons and Physical Constants of Fluids tables; refer to the Table of Contents for the page number).

After calculating  $\Delta P_{allow}$ , substitute it into the basic liquid sizing equation  $Q = C_v \sqrt{\Delta P / G}$  to determine either  $Q$  or  $C_v$ . If the actual  $\Delta P$  is less than the  $\Delta P_{allow}$ , then the actual  $\Delta P$  should be used in the equation.

The equation used to determine  $\Delta P_{allow}$  should also be used to calculate the valve body differential pressure at which significant cavitation can occur. Minor cavitation will occur at a slightly lower pressure differential than that predicted by the equation, but should produce negligible damage in most globe-style control valves.

Consequently, initial cavitation and choked flow occur nearly simultaneously in globe-style or low-recovery valves.

However, in high-recovery valves such as ball or butterfly valves, significant cavitation can occur at pressure drops below that which produces choked flow. So although  $\Delta P_{allow}$  and  $K_m$  are useful in predicting choked flow capacity, a separate cavitation index ( $K_c$ ) is needed to determine the pressure drop at which cavitation damage will begin ( $\Delta P_c$ ) in high-recovery valves.

The equation can be expressed:

$$\Delta P_c = K_c (P_1 - P_v) \quad (9)$$

This equation can be used anytime outlet pressure is greater than the vapor pressure of the liquid.

Addition of anti-cavitation trim tends to increase the value of  $K_m$ . In other words, choked flow and incipient cavitation will occur at substantially higher pressure drops than was the case without the anti-cavitation accessory.

# Valve Sizing Calculations (Traditional Method)

**Table 1. Liquid Sizing Equation Application**

EQUATION		
1	$Q = C_v \sqrt{\Delta P / G}$	Basic liquid sizing equation. Use to determine proper valve size for a given set of service conditions. (Remember that viscosity effects and valve recovery capabilities are not considered in this basic equation.)
2	$C_v = Q \sqrt{\frac{G}{\Delta P}}$	Use to calculate expected $C_v$ for valve controlling water or other liquids that behave like water.
3	$C_{vr} = F_v C_v$	Use to find actual required $C_v$ for equation (2) after including viscosity correction factor.
4	$Q_{max} = C_{vr} \sqrt{\Delta P / G}$	Use to find maximum flow rate assuming no viscosity correction is necessary.
5	$Q_{pred} = \frac{Q_{max}}{F_v}$	Use to predict actual flow rate based on equation (4) and viscosity factor correction.
6	$C_{vc} = \frac{C_{vr}}{F_v}$	Use to calculate corrected sizing coefficient for use in equation (7).
7	$\Delta P_{pred} = G (Q/C_{vc})^2$	Use to predict pressure drop for viscous liquids.
8	$\Delta P_{allow} = K_m (P_1 - r_c P_v)$	Use to determine maximum allowable pressure drop that is effective in producing flow.
9	$\Delta P_c = K_c (P_1 - P_v)$	Use to predict pressure drop at which cavitation will begin in a valve with high recovery characteristics.

## Liquid Sizing Summary

The most common use of the basic liquid sizing equation is to determine the proper valve size for a given set of service conditions. The first step is to calculate the required  $C_v$  by using the sizing equation. The  $\Delta P$  used in the equation must be the actual valve pressure drop or  $\Delta P_{allow}$ , whichever is smaller. The second step is to select a valve, from the manufacturer's literature, with a  $C_v$  equal to or greater than the calculated value.

Accurate valve sizing for liquids requires use of the dual coefficients of  $C_v$  and  $K_m$ . A single coefficient is not sufficient to describe both the capacity and the recovery characteristics of the valve. Also, use of the additional cavitation index factor  $K_c$  is appropriate in sizing high recovery valves, which may develop damaging cavitation at pressure drops well below the level of the choked flow.

## Liquid Sizing Nomenclature

- $C_v$  = valve sizing coefficient for liquid determined experimentally for each size and style of valve, using water at standard conditions as the test fluid
- $C_{vc}$  = calculated  $C_v$  coefficient including correction for viscosity
- $C_{vr}$  = corrected sizing coefficient required for viscous applications

- $\Delta P$  = differential pressure, psi
- $\Delta P_{allow}$  = maximum allowable differential pressure for sizing purposes, psi
- $\Delta P_c$  = pressure differential at which cavitation damage begins, psi
- $F_v$  = viscosity correction factor
- $G$  = specific gravity of fluid (water at 60°F = 1.0000)
- $K_c$  = dimensionless cavitation index used in determining  $\Delta P_c$
- $K_m$  = valve recovery coefficient from manufacturer's literature
- $P_1$  = body inlet pressure, psia
- $P_v$  = vapor pressure of liquid at body inlet temperature, psia
- $Q$  = flow rate capacity, gallons per minute
- $Q_{max}$  = designation for maximum flow rate, assuming no viscosity correction required, gallons per minute
- $Q_{pred}$  = predicted flow rate after incorporating viscosity correction, gallons per minute
- $r_c$  = critical pressure ratio

# Valve Sizing Calculations (Traditional Method)

## Sizing for Gas or Steam Service

A sizing procedure for gases can be established based on adaptations of the basic liquid sizing equation. By introducing conversion factors to change flow units from gallons per minute to cubic feet per hour and to relate specific gravity in meaningful terms of pressure, an equation can be derived for the flow of air at 60°F. Because 60°F corresponds to 520° on the Rankine absolute temperature scale and because the specific gravity of air at 60°F is 1.0, an additional factor can be included to compare air at 60°F with specific gravity (G) and absolute temperature (T) of any other gas. The resulting equation can be written:

$$Q_{SCFH} = 59.64 C_v P_1 \sqrt{\frac{\Delta P}{P_1}} \sqrt{\frac{520}{GT}} \quad (A)$$

The equation shown above, while valid at very low pressure drop ratios, has been found to be very misleading when the ratio of pressure drop ( $\Delta P$ ) to inlet pressure ( $P_1$ ) exceeds 0.02. The deviation of actual flow capacity from the calculated flow capacity is indicated in Figure 8 and results from compressibility effects and critical flow limitations at increased pressure drops.

Critical flow limitation is the more significant of the two problems mentioned. Critical flow is a choked flow condition caused by increased gas velocity at the vena contracta. When velocity at the vena contracta reaches sonic velocity, additional increases in  $\Delta P$  by reducing downstream pressure produce no increase in flow. So, after critical flow condition is reached (whether at a pressure drop/inlet pressure ratio of about 0.5 for globe valves or at much lower ratios for high recovery valves) the equation above becomes completely useless. If applied, the  $C_v$  equation gives a much higher indicated capacity than actually will exist. And in the case of a high recovery valve which reaches critical flow at a low pressure drop ratio (as indicated in Figure 8), the critical flow capacity of the valve may be overestimated by as much as 300 percent.

The problems in predicting critical flow with a  $C_v$ -based equation led to a separate gas sizing coefficient based on air flow tests. The coefficient ( $C_g$ ) was developed experimentally for each type and size of valve to relate critical flow to absolute inlet pressure. By including the correction factor used in the previous equation to compare air at 60°F with other gases at other absolute temperatures, the critical flow equation can be written:

$$Q_{critical} = C_g P_1 \sqrt{520/GT} \quad (B)$$




Figure 9. Critical Flow for High and Low Recovery Valves with Equal  $C_v$

## Universal Gas Sizing Equation

To account for differences in flow geometry among valves, equations (A) and (B) were consolidated by the introduction of an additional factor ( $C_1$ ).  $C_1$  is defined as the ratio of the gas sizing coefficient and the liquid sizing coefficient and provides a numerical indicator of the valve's recovery capabilities. In general,  $C_1$  values can range from about 16 to 37, based on the individual valve's recovery characteristics. As shown in the example, two valves with identical flow areas and identical critical flow ( $C_g$ ) capacities can have widely differing  $C_1$  values dependent on the effect internal flow geometry has on liquid flow capacity through each valve. Example:

### High Recovery Valve

$$\begin{aligned} C_g &= 4680 \\ C_v &= 254 \\ C_1 &= C_g/C_v \\ &= 4680/254 \\ &= 18.4 \end{aligned}$$

### Low Recovery Valve

$$\begin{aligned} C_g &= 4680 \\ C_v &= 135 \\ C_1 &= C_g/C_v \\ &= 4680/135 \\ &= 34.7 \end{aligned}$$

# Valve Sizing Calculations (Traditional Method)

So we see that two sizing coefficients are needed to accurately size valves for gas flow— $C_g$  to predict flow based on physical size or flow area and  $C_1$  to account for differences in valve recovery characteristics. A blending equation, called the Universal Gas Sizing Equation, combines equations (A) and (B) by means of a sinusoidal function and is based on the “perfect gas” laws. It can be expressed in either of the following manners:

$$Q_{SCFH} = \sqrt{\frac{520}{GT}} C_g P_1 \sin \left[ \frac{59.64}{C_1} \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ rad} \quad (C)$$

$$Q_{SCFH} = \sqrt{\frac{520}{GT}} C_g P_1 \sin \left[ \frac{3417}{C_1} \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg} \quad (D)$$

In either form, the equation indicates critical flow when the sine function of the angle designated within the brackets equals unity. The pressure drop ratio at which critical flow occurs is known as the critical pressure drop ratio. It occurs when the sine angle reaches  $\pi/2$  radians in equation (C) or 90 degrees in equation (D). As pressure drop across the valve increases, the sine angle increases from zero up to  $\pi/2$  radians (90°). If the angle were allowed to increase further, the equations would predict a decrease in flow. Because this is not a realistic situation, the angle must be limited to 90 degrees maximum.

Although “perfect gases,” as such, do not exist in nature, there are a great many applications where the Universal Gas Sizing Equation, (C) or (D), provides a very useful and usable approximation.

## General Adaptation for Steam and Vapors

The density form of the Universal Gas Sizing Equation is the most general form and can be used for both perfect and non-perfect gas applications. Applying the equation requires knowledge of one additional condition not included in previous equations, that being the inlet gas, steam or vapor density ( $d_1$ ) in lbs/ft<sup>3</sup>. (Steam density can be determined from tables.)

Then the following adaptation of the Universal Gas Sizing Equation can be applied:

$$Q_{lb/hr} = 1.06 \sqrt{d_1 P_1} C_g \sin \left[ \frac{3417}{C_1} \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg} \quad (E)$$

## Special Equation Form for Steam Below 1000 psig

If steam applications do not exceed 1000 psig, density changes can be compensated for by using a special adaptation of the Universal Gas Sizing Equation. It incorporates a factor for amount of superheat in degrees Fahrenheit ( $T_{sh}$ ) and also a sizing coefficient ( $C_s$ ) for steam. Equation (F) eliminates the need for finding the density of superheated steam, which was required in Equation (E). At pressures below 1000 psig, a constant relationship exists between the gas sizing coefficient ( $C_g$ ) and the steam coefficient ( $C_s$ ). This relationship can be expressed:  $C_s = C_g/20$ . For higher steam pressure application, use Equation (E).

$$Q_{lb/hr} = \left[ \frac{C_s P_1}{1 + 0.00065 T_{sh}} \right] \sin \left[ \frac{3417}{C_1} \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg} \quad (F)$$

## Gas and Steam Sizing Summary

The Universal Gas Sizing Equation can be used to determine the flow of gas through any style of valve. Absolute units of temperature and pressure must be used in the equation. When the critical pressure drop ratio causes the sine angle to be 90 degrees, the equation will predict the value of the critical flow. For service conditions that would result in an angle of greater than 90 degrees, the equation must be limited to 90 degrees in order to accurately determine the critical flow.

Most commonly, the Universal Gas Sizing Equation is used to determine proper valve size for a given set of service conditions. The first step is to calculate the required  $C_g$  by using the Universal Gas Sizing Equation. The second step is to select a valve from the manufacturer’s literature. The valve selected should have a  $C_g$  which equals or exceeds the calculated value. Be certain that the assumed  $C_1$  value for the valve is selected from the literature.

It is apparent that accurate valve sizing for gases that requires use of the dual coefficient is not sufficient to describe both the capacity and the recovery characteristics of the valve.

Proper selection of a control valve for gas service is a highly technical problem with many factors to be considered. Leading valve manufacturers provide technical information, test data, sizing catalogs, nomographs, sizing slide rules and computer or calculator programs that make valve sizing a simple and accurate procedure.

# Valve Sizing Calculations (Traditional Method)

**Table 2. Gas and Steam Sizing Equation Application**

EQUATION		
A	$Q_{SCFH} = 59.64 C_v P_1 \sqrt{\frac{\Delta P}{P_1}} \sqrt{\frac{520}{GT}}$	Use only at very low pressure drop ( $\Delta P/P_1$ ) ratios of 0.02 or less.
B	$Q_{critical} = C_g P_1 \sqrt{520/GT}$	Use only to determine critical flow capacity at a given inlet pressure.
C	$Q_{SCFH} = \sqrt{\frac{520}{GT}} C_g P_1 \sin \left[ \left( \frac{59.64}{C_1} \right) \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ rad}$ OR	Universal Gas Sizing Equation. Use to predict flow for either high or low recovery valves, for any gas adhering to the perfect gas laws and under any service conditions.
D	$Q_{SCFH} = \sqrt{\frac{520}{GT}} C_g P_1 \sin \left[ \left( \frac{3417}{C_1} \right) \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg}$	
E	$Q_{lb/hr} = 1.06 \sqrt{d_1 P_1} C_g \sin \left[ \left( \frac{3417}{C_1} \right) \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg}$	Use to predict flow for perfect or non-perfect gas sizing applications, for any vapor including steam, at any service condition when fluid density is known.
F	$Q_{lb/hr} = \left[ \frac{C_s P_1}{1 + 0.00065 T_{sh}} \right] \sin \left[ \left( \frac{3417}{C_1} \right) \left( \sqrt{\frac{\Delta P}{P_1}} \right) \right] \text{ Deg}$	Use only to determine steam flow when inlet pressure is 1000 psig or less.

## Gas and Steam Sizing Nomenclature

$$C_1 = C_g/C_v$$

$C_g$  = gas sizing coefficient

$C_s$  = steam sizing coefficient,  $C_g/20$

$C_v$  = liquid sizing coefficient

$d_1$  = density of steam or vapor at inlet, lbs/ft<sup>3</sup>

$G$  = gas specific gravity (air = 1.0)

$P_1$  = valve inlet pressure, psia

$\Delta P$  = pressure drop across valve, psi

$Q_{critical}$  = critical flow rate, SCFH

$Q_{SCFH}$  = gas flow rate, SCFH

$Q_{lb/hr}$  = steam or vapor flow rate, lbs/hr

$T$  = absolute temperature of gas at inlet, degrees Rankine

$T_{sh}$  = degrees of superheat, °F

# Valve Sizing (Standardized Method)

## Introduction

Fisher™ regulators and valves have traditionally been sized using equations derived by the company. There are now standardized calculations that are becoming accepted world wide. Some product literature continues to demonstrate the traditional method, but the trend is to adopt the standardized method. Therefore, both methods are covered in this application guide.

## Liquid Valve Sizing

Standardization activities for control valve sizing can be traced back to the early 1960s when a trade association, the Fluids Control Institute, published sizing equations for use with both compressible and incompressible fluids. The range of service conditions that could be accommodated accurately by these equations was quite narrow and the standard did not achieve a high degree of acceptance. In 1967, the ISA established a committee to develop and publish standard equations. The efforts of this committee culminated in a valve sizing procedure that has achieved the status of American National Standard. Later, a committee of the International Electrotechnical Commission (IEC) used the ISA works as a basis to formulate international standards for sizing control valves. (Some information in this introductory material has been extracted from ANSI/ISA S75.01 standard with the permission of the publisher, the ISA.) Except for some slight differences in nomenclature and procedures, the ISA and IEC standards have been harmonized. ANSI/ISA Standard S75.01 is harmonized with IEC Standards 534-2-1 and 534-2-2. (IEC Publications 534-2, Sections One and Two for incompressible and compressible fluids, respectively.)

In the following sections, the nomenclature and procedures are explained and sample problems are solved to illustrate their use.

## Sizing Valves for Liquids

Following is a step-by-step procedure for the sizing of control valves for liquid flow using the IEC procedure. Each of these steps is important and must be considered during any valve sizing procedure. Steps 3 and 4 concern the determination of certain sizing factors that may or may not be required in the sizing equation depending on the service conditions of the sizing problem. If one, two or all three of these sizing factors are to be included in the equation for a particular sizing problem, refer to the appropriate factor determination section(s) located in the text after the sixth step.

1. Specify the variables required to size the valve as follows:

- Desired design
- Process fluid (water, oil, etc.) and
- Appropriate service conditions  $q$  or  $w$ ,  $P_1$ ,  $P_2$  or  $\Delta P$ ,  $T_1$ ,  $C_f$ ,  $P_v$ ,  $P_c$  and  $v$ .

The ability to recognize which terms are appropriate for a specific sizing procedure can only be acquired through experience with different valve sizing problems. If any of the above terms appears to be new or unfamiliar, refer to the Abbreviations and Terminology Table 1 for a complete definition.

2. Determine the equation constant,  $N$ .

$N$  is a numerical constant contained in each of the flow equations to provide a means for using different systems of

units. Values for these various constants and their applicable units are given in the Equation Constants Table 2.

Use  $N_1$ , if sizing the valve for a flow rate in volumetric units (GPM or  $\text{Nm}^3/\text{h}$ ).

Use  $N_6$ , if sizing the valve for a flow rate in mass units (lb/hr or kg/hr).

3. Determine  $F_p$ , the piping geometry factor.

$F_p$  is a correction factor that accounts for pressure losses due to piping fittings such as reducers, elbows or tees that might be attached directly to the inlet and outlet connections of the control valve to be sized. If such fittings are attached to the valve, the  $F_p$  factor must be considered in the sizing procedure. If, however, no fittings are attached to the valve,  $F_p$  has a value of 1.0 and simply drops out of the sizing equation.

For rotary valves with reducers (swaged installations) and other valve designs and fitting styles, determine the  $F_p$  factors by using the procedure for determining  $F_p$ , the Piping Geometry Factor, page 637.

4. Determine  $q_{\text{max}}$  (the maximum flow rate at given upstream conditions) or  $\Delta P_{\text{max}}$  (the allowable sizing pressure drop).

The maximum or limiting flow rate ( $q_{\text{max}}$ ), commonly called choked flow, is manifested by no additional increase in flow rate with increasing pressure differential with fixed upstream conditions. In liquids, choking occurs as a result of vaporization of the liquid when the static pressure within the valve drops below the vapor pressure of the liquid.

The IEC standard requires the calculation of an allowable sizing pressure drop ( $\Delta P_{\text{max}}$ ), to account for the possibility of choked flow conditions within the valve. The calculated  $\Delta P_{\text{max}}$  value is compared with the actual pressure drop specified in the service conditions and the lesser of these two values is used in the sizing equation. If it is desired to use  $\Delta P_{\text{max}}$  to account for the possibility of choked flow conditions, it can be calculated using the procedure for determining  $q_{\text{max}}$ , the Maximum Flow Rate or  $\Delta P_{\text{max}}$ , the Allowable Sizing Pressure Drop. If it can be recognized that choked flow conditions will not develop within the valve,  $\Delta P_{\text{max}}$  need not be calculated.

5. Solve for required  $C_v$ , using the appropriate equation:

- For volumetric flow rate units:

$$C_v = \frac{q}{N_1 F_p \sqrt{\frac{P_1 - P_2}{G_f}}}$$

- For mass flow rate units:

$$C_v = \frac{w}{N_6 F_p \sqrt{(P_1 - P_2) \gamma}}$$

In addition to  $C_v$ , two other flow coefficients,  $K_v$  and  $A_v$ , are used, particularly outside of North America. The following relationships exist:

$$K_v = (0.865) (C_v)$$

$$A_v = (2.40 \times 10^{-5}) (C_v)$$

6. Select the valve size using the appropriate flow coefficient table and the calculated  $C_v$  value.



# Valve Sizing (Standardized Method)

**Table 1. Abbreviations and Terminology**

SYMBOL		SYMBOL	
$C_v$	Valve sizing coefficient	$P_1$	Upstream absolute static pressure
$d$	Nominal valve size	$P_2$	Downstream absolute static pressure
$D$	Internal diameter of the piping	$P_c$	Absolute thermodynamic critical pressure
$F_d$	Valve style modifier, dimensionless	$P_v$	Vapor pressure absolute of liquid at inlet temperature
$F_f$	Liquid critical pressure ratio factor, dimensionless	$\Delta P$	Pressure drop ( $P_1 - P_2$ ) across the valve
$F_k$	Ratio of specific heats factor, dimensionless	$\Delta P_{\max(L)}$	Maximum allowable liquid sizing pressure drop
$F_L$	Rated liquid pressure recovery factor, dimensionless	$\Delta P_{\max(LP)}$	Maximum allowable sizing pressure drop with attached fittings
$F_{LP}$	Combined liquid pressure recovery factor and piping geometry factor of valve with attached fittings (when there are no attached fittings, $F_{LP}$ equals $F_f$ ), dimensionless	$q$	Volume rate of flow
$F_p$	Piping geometry factor, dimensionless	$q_{\max}$	Maximum flow rate (choked flow conditions) at given upstream conditions
$G_f$	Liquid specific gravity (ratio of density of liquid at flowing temperature to density of water at 60°F), dimensionless	$T_1$	Absolute upstream temperature (Kelvin or deg Rankine)
$G_g$	Gas specific gravity (ratio of density of flowing gas to density of air with both at standard conditions <sup>(1)</sup> , i.e., ratio of molecular weight of gas to molecular weight of air), dimensionless	$w$	Mass rate of flow
$k$	Ratio of specific heats, dimensionless	$x$	Ratio of pressure drop to upstream absolute static pressure ( $\Delta P/P_1$ ), dimensionless
$K$	Head loss coefficient of a device, dimensionless	$x_f$	Rated pressure drop ratio factor, dimensionless
$M$	Molecular weight, dimensionless	$Y$	Expansion factor (ratio of flow coefficient for a gas to that for a liquid at the same Reynolds number), dimensionless
$N$	Numerical constant	$Z$	Compressibility factor, dimensionless
		$\gamma^1$	Specific weight at inlet conditions
		$\nu$	Kinematic viscosity, centistokes

1. Standard conditions are defined as 60°F and 14.7 psia.

**Table 2. Equation Constants<sup>(1)</sup>**

	<b>N</b>	<b>w</b>	<b>q</b>	<b>p<sup>(2)</sup></b>	<b><math>\gamma</math></b>	<b>T</b>	<b>d, D</b>
$N_1$	0.0865	----	Nm <sup>3</sup> /h	kPa	----	----	----
	0.865	----	Nm <sup>3</sup> /h	bar	----	----	----
	1.00	----	GPM	psia	----	----	----
$N_2$	0.00214	----	----	----	----	----	mm
	890	----	----	----	----	----	in.
$N_5$	0.00241	----	----	----	----	----	mm
	1000	----	----	----	----	----	in.
$N_6$	2.73	kg/hr	----	kPa	kg/m <sup>3</sup>	----	----
	27.3	kg/hr	----	bar	kg/m <sup>3</sup>	----	----
	63.3	lb/hr	----	psia	lb/ft <sup>3</sup>	----	----
$N_7^{(3)}$	Normal Conditions $T_N = 0^\circ\text{C}$	3.94	----	Nm <sup>3</sup> /h	kPa	Kelvin	----
	Standard Conditions $T_s = 16^\circ\text{C}$	394	----	Nm <sup>3</sup> /h	bar	Kelvin	----
	Standard Conditions $T_s = 60^\circ\text{F}$	4.17	----	Nm <sup>3</sup> /h	kPa	Kelvin	----
		417	----	Nm <sup>3</sup> /h	bar	Kelvin	----
		1360	----	SCFH	psia	deg Rankine	----
$N_8$	0.948	kg/hr	----	kPa	----	Kelvin	----
	94.8	kg/hr	----	bar	----	Kelvin	----
	19.3	lb/hr	----	psia	----	deg Rankine	----
$N_9^{(3)}$	Normal Conditions $T_N = 0^\circ\text{C}$	21.2	----	Nm <sup>3</sup> /h	kPa	Kelvin	----
	Standard Conditions $T_s = 16^\circ\text{C}$	2120	----	Nm <sup>3</sup> /h	bar	Kelvin	----
	Standard Conditions $T_s = 60^\circ\text{F}$	22.4	----	Nm <sup>3</sup> /h	kPa	Kelvin	----
		2240	----	Nm <sup>3</sup> /h	bar	Kelvin	----
		7320	----	SCFH	psia	deg Rankine	----

1. Many of the equations used in these sizing procedures contain a numerical constant, N, along with a numerical subscript. These numerical constants provide a means for using different units in the equations. Values for the various constants and the applicable units are given in the above table. For example, if the flow rate is given in U.S. GPM and the pressures are psia,  $N_1$  has a value of 1.00. If the flow rate is Nm<sup>3</sup>/h and the pressures are kPa, the  $N_1$  constant becomes 0.0865.  
2. All pressures are absolute.  
3. Pressure base is 101.3 kPa = 1.01 bar = 14.7 psia.

# Valve Sizing (Standardized Method)

## Determining Piping Geometry Factor ( $F_p$ )

Determine an  $F_p$  factor if any fittings such as reducers, elbows or tees will be directly attached to the inlet and outlet connections of the control valve that is to be sized. When possible, it is recommended that  $F_p$  factors be determined experimentally by using the specified valve in actual tests.

Calculate the  $F_p$  factor using the following equation:

$$F_p = \left[ 1 + \frac{\sum K}{N_2} \left( \frac{C_v}{d^2} \right)^2 \right]^{-1/2}$$

where,

$N_2$  = Numerical constant found in Table 2. Equation Constants

$d$  = Assumed nominal valve size

$C_v$  = Valve sizing coefficient at 100% travel for the assumed valve size

In the above equation, the  $\sum K$  term is the algebraic sum of the velocity head loss coefficients of all of the fittings that are attached to the control valve.

$$\sum K = K_1 + K_2 + K_{B1} - K_{B2}$$

where,

$K_1$  = Resistance coefficient of upstream fittings

$K_2$  = Resistance coefficient of downstream fittings

$K_{B1}$  = Inlet Bernoulli coefficient

$K_{B2}$  = Outlet Bernoulli coefficient

The Bernoulli coefficients,  $K_{B1}$  and  $K_{B2}$ , are used only when the diameter of the piping approaching the valve is different from the diameter of the piping leaving the valve, whereby:

$$K_{B1} \text{ or } K_{B2} = 1 - \left( \frac{d}{D} \right)^4$$

where,

$d$  = Nominal valve size

$D$  = Internal diameter of piping

If the inlet and outlet piping are of equal size, then the Bernoulli coefficients are also equal,  $K_{B1} = K_{B2}$  and therefore they are dropped from the equation.

The most commonly used fitting in control valve installations is the short-length concentric reducer. The equations for this fitting are as follows:

- For an inlet reducer:

$$K_1 = 0.5 \left( 1 - \frac{d^2}{D^2} \right)^2$$

- For an outlet reducer:

$$K_2 = 1.0 \left( 1 - \frac{d^2}{D^2} \right)^2$$

- For a valve installed between identical reducers:

$$K_1 + K_2 = 1.5 \left( 1 - \frac{d^2}{D^2} \right)^2$$

## Determining Maximum Flow Rate ( $q_{max}$ )

Determine either  $q_{max}$  or  $\Delta P_{max}$  if it is possible for choked flow to develop within the control valve that is to be sized. The values can be determined by using the following procedures.

$$q_{max} = N_1 F_L C_v \sqrt{\frac{P_1 - F_F P_V}{G_f}}$$

Values for  $F_F$ , the liquid critical pressure ratio factor, can be obtained from Figure 1 or from the following equation:

$$F_F = 0.96 - 0.28 \sqrt{\frac{P_V}{P_C}}$$

Values of  $F_L$ , the recovery factor for rotary valves installed without fittings attached, can be found in published coefficient tables. If the given valve is to be installed with fittings such as reducer attached to it,  $F_L$  in the equation must be replaced by the quotient  $F_{LP}/F_p$ , where:

$$F_{LP} = \left[ \frac{K_1}{N_2} \left( \frac{C_v}{d^2} \right)^2 + \frac{1}{F_L^2} \right]^{-1/2}$$

and

$$K_1 = K_1 + K_{B1}$$


where,

$K_1$  = Resistance coefficient of upstream fittings

$K_{B1}$  = Inlet Bernoulli coefficient

(See the procedure for Determining  $F_p$ , the Piping Geometry Factor, for definitions of the other constants and coefficients used in the above equations.)

# Valve Sizing (Standardized Method)



USE THIS CURVE FOR WATER, ENTER ON THE ABSCISSA AT THE WATER VAPOR PRESSURE AT THE VALVE INLET, PROCEED VERTICALLY TO INTERSECT THE CURVE, MOVE HORIZONTALLY TO THE LEFT TO READ THE CRITICAL PRESSURE RATIO,  $F_F$ , ON THE ORDINATE.

Figure 1. Liquid Critical Pressure Ratio Factor for Water

## Determining Allowable Sizing Pressure Drop ( $\Delta P_{max}$ )

$\Delta P_{max}$  (the allowable sizing pressure drop) can be determined from the following relationships:

For valves installed without fittings:

$$\Delta P_{max(L)} = F_L^2 (P_1 - F_F P_V)$$

For valves installed with fittings attached:

$$\Delta P_{max(LP)} = \left( \frac{F_{LP}}{F_F} \right)^2 (P_1 - F_F P_V)$$

where,

$P_1$  = Upstream absolute static pressure

$P_2$  = Downstream absolute static pressure

$P_V$  = Absolute vapor pressure at inlet temperature

Values of  $F_F$ , the liquid critical pressure ratio factor, can be obtained from Figure 1 or from the following equation:

$$F_F = 0.96 - 0.28 \sqrt{\frac{P_V}{P_c}}$$

An explanation of how to calculate values of  $F_{LP}$ , the recovery factor for valves installed with fittings attached, is presented in the preceding procedure Determining  $q_{max}$  (the Maximum Flow Rate).

Once the  $\Delta P_{max}$  value has been obtained from the appropriate equation, it should be compared with the actual service pressure differential ( $\Delta P = P_1 - P_2$ ). If  $\Delta P_{max}$  is less than  $\Delta P$ , this is an indication that choked flow conditions will exist under the service conditions specified. If choked flow conditions do

exist ( $\Delta P_{max} < P_1 - P_2$ ), then step 5 of the procedure for Sizing Valves for Liquids must be modified by replacing the actual service pressure differential ( $P_1 - P_2$ ) in the appropriate valve sizing equation with the calculated  $\Delta P_{max}$  value.


### Note

Once it is known that choked flow conditions will develop within the specified valve design ( $\Delta P_{max}$  is calculated to be less than  $\Delta P$ ), a further distinction can be made to determine whether the choked flow is caused by cavitation or flashing. The choked flow conditions are caused by flashing if the outlet pressure of the given valve is less than the vapor pressure of the flowing liquid. The choked flow conditions are caused by cavitation if the outlet pressure of the valve is greater than the vapor pressure of the flowing liquid.

## Liquid Sizing Sample Problem

Assume an installation that, at initial plant startup, will not be operating at maximum design capability. The lines are sized for the ultimate system capacity, but there is a desire to install a control valve now which is sized only for currently anticipated requirements. The line size is 8 in. / DN 200 and an ASME CL300 globe valve with an equal percentage cage has been specified. Standard concentric reducers will be used to install the valve into the line. Determine the appropriate valve size.

# Valve Sizing (Standardized Method)



USE THIS CURVE FOR LIQUIDS OTHER THAN WATER. DETERMINE THE VAPOR PRESSURE/CRITICAL PRESSURE RATIO BY DIVIDING THE LIQUID VAPOR PRESSURE AT THE VALVE INLET BY THE CRITICAL PRESSURE OF THE LIQUID. ENTER ON THE ABSCISSA AT THE RATIO JUST CALCULATED AND PROCEED VERTICALLY TO INTERSECT THE CURVE. MOVE HORIZONTALLY TO THE LEFT AND READ THE CRITICAL PRESSURE RATIO,  $F_p$ , ON THE ORDINATE.

Figure 2. Liquid Critical Pressure Ratio Factor for Liquids Other Than Water

1. Specify the necessary variables required to size the valve:

- Desired Valve Design—ASME CL300 globe valve with equal percentage cage and an assumed valve size of 3 in.
- Process Fluid—liquid propane
- Service Conditions— $q = 800 \text{ GPM} / 3028 \text{ l/min}$   
 $P_1 = 300 \text{ psig} / 20.7 \text{ bar} = 314.7 \text{ psia} / 21.7 \text{ bar a}$   
 $P_2 = 275 \text{ psig} / 19.0 \text{ bar} = 289.7 \text{ psia} / 20.0 \text{ bar a}$   
 $\Delta P = 25 \text{ psi} / 1.7 \text{ bar}$   
 $T_1 = 70^\circ\text{F} / 21^\circ\text{C}$   
 $G_f = 0.50$   
 $P_v = 124.3 \text{ psia} / 8.6 \text{ bar a}$   
 $P_c = 616.3 \text{ psia} / 42.5 \text{ bar a}$

2. Use an  $N_1$  value of 1.0 from Table 2. Equation Constants.

3. Determine  $F_p$ , the piping geometry factor.

Because it is proposed to install a 3 in. / DN 200 line, it will be necessary to determine the piping geometry factor,  $F_p$ , which corrects for losses caused by fittings attached to the valve.

$$F_p = \left[ 1 + \frac{\sum K}{N_2} \left( \frac{C_v}{d^2} \right)^2 \right]^{-1/2}$$

where,

$N_2 = 890$ , from Table 2. Equation Constants

$d = 3 \text{ in.} / 76 \text{ mm}$ , from step 1

$C_v = 121$ , from the flow coefficient table for an ASME CL300, 3 in. globe valve with equal percentage cage

To compute  $\sum K$  for a valve installed between identical concentric reducers:

$$\begin{aligned} \sum K &= K_1 + K_2 \\ &= 1.5 \left( 1 - \frac{d^2}{D^2} \right)^2 \\ &= 1.5 \left( 1 - \frac{(3)^2}{(8)^2} \right)^2 \\ &= 1.11 \end{aligned}$$

# Valve Sizing (Standardized Method)

where,

$D = 8$  in. / 203 mm, the internal diameter of the piping so,

$$F_p = \left[ 1 + \frac{1.11 \left( \frac{121}{3^2} \right)^2}{890} \right]^{-1/2}$$

$$= 0.90$$

4. Determine  $\Delta P_{\max}$  (the Allowable Sizing Pressure Drop.)

Based on the small required pressure drop, the flow will not be choked ( $\Delta P_{\max} > \Delta P$ ).

5. Solve for  $C_v$ , using the appropriate equation.

$$C_v = \frac{q}{N_1 F_p \sqrt{\frac{P_1 - P_2}{G_f}}}$$

$$= \frac{800}{(1.0)(0.90) \sqrt{\frac{25}{0.5}}}$$

$$= 125.7$$

6. Select the valve size using the flow coefficient table and the calculated  $C_v$  value.

The required  $C_v$  of 125.7 exceeds the capacity of the assumed valve, which has a  $C_v$  of 121. Although for this example it may be obvious that the next larger size (4 in.) would be the correct valve size, this may not always be true and a repeat of the above procedure should be carried out.

Assuming a 4 in. valve,  $C_v = 203$ . This value was determined from the flow coefficient table for an ASME CL300, 4 in. globe valve with an equal percentage cage.

Recalculate the required  $C_v$  using an assumed  $C_v$  value of 203 in the  $F_p$  calculation.

where,

$$\Sigma K = K_1 + K_2$$

$$= 1.5 \left( 1 - \frac{d^2}{D^2} \right)^2$$

$$= 1.5 \left( 1 - \frac{16}{64} \right)^2$$

$$= 0.84$$

and

$$F_p = \left[ 1.0 + \frac{\Sigma K \left( \frac{C_v}{d^2} \right)^2}{N_2} \right]^{-1/2}$$

$$= \left[ 1.0 + \frac{0.84 \left( \frac{203}{4^2} \right)^2}{890} \right]^{-1/2}$$

$$= 0.93$$

and

$$C_v = \frac{q}{N_1 F_p \sqrt{\frac{P_1 - P_2}{G_f}}}$$

$$= \frac{800}{(1.0)(0.93) \sqrt{\frac{25}{0.5}}}$$

$$= 121.7$$

This solution indicates only that the 4 in. valve is large enough to satisfy the service conditions given. There may be cases, however, where a more accurate prediction of the  $C_v$  is required. In such cases, the required  $C_v$  should be redetermined using a new  $F_p$  value based on the  $C_v$  value obtained above. In this example,  $C_v$  is 121.7, which leads to the following result:

$$F_p = \left[ 1.0 + \frac{\Sigma K \left( \frac{C_v}{d^2} \right)^2}{N_2} \right]^{-1/2}$$

$$= \left[ 1.0 + \frac{0.84 \left( \frac{121.7}{4^2} \right)^2}{890} \right]^{-1/2}$$

$$= 0.97$$

The required  $C_v$  then becomes:

$$C_v = \frac{q}{N_1 F_p \sqrt{\frac{P_1 - P_2}{G_f}}}$$

$$= \frac{800}{(1.0)(0.97) \sqrt{\frac{25}{0.5}}}$$

$$= 116.2$$

Because this newly determined  $C_v$  is very close to the  $C_v$  used initially for this recalculation (116.2 versus 121.7), the valve sizing procedure is complete and the conclusion is that a 4 in. valve opened to about 75% of total travel should be adequate for the required specifications.

# Valve Sizing (Standardized Method)

## Gas and Steam Valve Sizing

### Sizing Valves for Compressible Fluids

Following is a six-step procedure for the sizing of control valves for compressible flow using the ISA standardized procedure. Each of these steps is important and must be considered during any valve sizing procedure. Steps 3 and 4 concern the determination of certain sizing factors that may or may not be required in the sizing equation depending on the service conditions of the sizing problem. If it is necessary for one or both of these sizing factors to be included in the sizing equation for a particular sizing problem, refer to the appropriate factor determination section(s), which is referenced and located in the following text.

1. Specify the necessary variables required to size the valve as follows:

- Desired valve design (e.g. balanced globe with linear cage)
- Process fluid (air, natural gas, steam, etc.) and
- Appropriate service conditions—  
q or w, P<sub>1</sub>, P<sub>2</sub> or ΔP, T<sub>1</sub>, G<sub>g</sub>, M, k, Z and γ<sub>1</sub>

The ability to recognize which terms are appropriate for a specific sizing procedure can only be acquired through experience with different valve sizing problems. If any of the above terms appear to be new or unfamiliar, refer to the Abbreviations and Terminology Table 1 in Liquid Valve Sizing Section for a complete definition.

2. Determine the equation constant, N.

N is a numerical constant contained in each of the flow equations to provide a means for using different systems of units. Values for these various constants and their applicable units are given in the Equation Constants Table 2 in Liquid Valve Sizing Section.

Use either N<sub>7</sub> or N<sub>9</sub> if sizing the valve for a flow rate in volumetric units (SCFH or Nm<sup>3</sup>/h). Which of the two constants to use depends upon the specified service conditions. N<sub>7</sub> can be used only if the specific gravity, G<sub>g</sub>, of the following gas has been specified along with the other required service conditions. N<sub>9</sub> can be used only if the molecular weight, M, of the gas has been specified.

Use either N<sub>6</sub> or N<sub>8</sub> if sizing the valve for a flow rate in mass units (lb/hr or kg/hr). Which of the two constants to use depends upon the specified service conditions. N<sub>6</sub> can be used only if the specific weight, γ<sub>1</sub>, of the flowing gas has been specified along with the other required service conditions. N<sub>8</sub> can be used only if the molecular weight, M, of the gas has been specified.

3. Determine F<sub>p</sub>, the piping geometry factor.

F<sub>p</sub> is a correction factor that accounts for any pressure losses due to piping fittings such as reducers, elbows or tees that might be attached directly to the inlet and outlet connections of the control valves to be sized. If

such fittings are attached to the valve, the F<sub>p</sub> factor must be considered in the sizing procedure. If, however, no fittings are attached to the valve, F<sub>p</sub> has a value of 1.0 and simply drops out of the sizing equation.

Also, for rotary valves with reducers and other valve designs and fitting styles, determine the F<sub>p</sub> factors by using the procedure for Determining F<sub>p</sub>, the Piping Geometry Factor, which is located in Liquid Valve Sizing Section.

4. Determine Y, the expansion factor, as follows:

$$Y = 1 - \frac{x}{3F_k x_T}$$

where,

F<sub>k</sub> = k/1.4, the ratio of specific heats factor

k = Ratio of specific heats

x = ΔP/P<sub>1</sub>, the pressure drop ratio

x<sub>T</sub> = The pressure drop ratio factor for valves installed without attached fittings. More definitively, x<sub>T</sub> is the pressure drop ratio required to produce critical or maximum flow through the valve when F<sub>k</sub> = 1.0

If the control valve to be installed has fittings such as reducers or elbows attached to it, then their effect is accounted for in the expansion factor equation by replacing the x<sub>T</sub> term with a new factor x<sub>TP</sub>. A procedure for determining the x<sub>TP</sub> factor is described in the following section for Determining x<sub>TP</sub>, the Pressure Drop Ratio Factor.

#### Note

**Conditions of critical pressure drop are realized when the value of x becomes equal to or exceeds the appropriate value of the product of either F<sub>k</sub>x<sub>T</sub> or F<sub>k</sub>x<sub>TP</sub> at which point:**

$$y = 1 - \frac{x}{3F_k x_T} = 1 - 1/3 = 0.667$$

Although in actual service, pressure drop ratios can and often will, exceed the indicated critical values, this is the point where critical flow conditions develop. Thus, for a constant P<sub>1</sub>, decreasing P<sub>2</sub> (i.e., increasing ΔP) will not result in an increase in the flow rate through the valve. Values of x, therefore, greater than the product of either F<sub>k</sub>x<sub>T</sub> or F<sub>k</sub>x<sub>TP</sub> must never be substituted in the expression for Y. This means that Y can never be less than 0.667. This same limit on values of x also applies to the flow equations that are introduced in the next section.

5. Solve for the required C<sub>v</sub> using the appropriate equation:

For volumetric flow rate units—

- If the specific gravity, G<sub>g</sub>, of the gas has been specified:

$$C_v = \frac{q}{N_7 F_p P_1 Y \sqrt{\frac{x}{G_g T_1 Z}}}$$

# Valve Sizing (Standardized Method)

- If the molecular weight,  $M$ , of the gas has been specified:

$$C_v = \frac{q}{N_7 F_p P_1 Y \sqrt{\frac{x}{M T_1 Z}}}$$

For mass flow rate units—

- If the specific weight,  $\gamma_1$ , of the gas has been specified:

$$C_v = \frac{w}{N_6 F_p Y \sqrt{x P_1 \gamma_1}}$$

- If the molecular weight,  $M$ , of the gas has been specified:

$$C_v = \frac{w}{N_8 F_p P_1 Y \sqrt{\frac{x M}{T_1 Z}}}$$

In addition to  $C_v$ , two other flow coefficients,  $K_v$  and  $A_v$ , are used, particularly outside of North America. The following relationships exist:

$$K_v = (0.865)(C_v)$$

$$A_v = (2.40 \times 10^{-5})(C_v)$$

6. Select the valve size using the appropriate flow coefficient table and the calculated  $C_v$  value.

## Determining $x_{TP}$ , the Pressure Drop Ratio Factor

If the control valve is to be installed with attached fittings such as reducers or elbows, then their effect is accounted for in the expansion factor equation by replacing the  $x_T$  term with a new factor,  $x_{TP}$ .

$$x_{TP} = \frac{x_T}{F_p^2} \left[ 1 + \frac{x_T K_i}{N_5} \left( \frac{C_v}{d^2} \right)^2 \right]^{-1}$$

where,

$N_5$  = Numerical constant found in Table 2. Equation Constants

$d$  = Assumed nominal valve size

$C_v$  = Valve sizing coefficient from flow coefficient table at 100% travel for the assumed valve size

$F_p$  = Piping geometry factor

$x_T$  = Pressure drop ratio for valves installed without fittings attached.  $x_T$  values are included in the flow coefficient tables

In the above equation,  $K_i$  is the inlet head loss coefficient, which is defined as:

$$K_i = K_1 + K_{B1}$$

where,

$K_1$  = Resistance coefficient of upstream fittings (see the procedure for Determining  $F_p$ , the Piping Geometry Factor, which is contained in the section for Sizing Valves for Liquids).

$K_{B1}$  = Inlet Bernoulli coefficient (see the procedure for Determining  $F_p$ , the Piping Geometry Factor, which is contained in the section for Sizing Valves for Liquids).

## Compressible Fluid Sizing Sample Problem No. 1

Determine the size and percent opening for a Fisher™ Design V250 ball valve operating with the following service conditions. Assume that the valve and line size are equal.

1. Specify the necessary variables required to size the valve:

- Desired valve design—Design V250 valve

- Process fluid—Natural gas

- Service conditions—

$$P_1 = 200 \text{ psig} / 13.8 \text{ bar} = 214.7 \text{ psia} / 14.8 \text{ bar a}$$

$$P_2 = 50 \text{ psig} / 3.4 \text{ bar} = 64.7 \text{ psia} / 4.5 \text{ bar a}$$

$$\Delta P = 150 \text{ psi} / 10.3 \text{ bar}$$

$$x = \Delta P / P_1 = 150 / 214.7 = 0.70$$

$$T_1 = 60^\circ\text{F} / 16^\circ\text{C} = 520^\circ\text{R}$$

$$M = 17.38$$

$$G_g = 0.60$$

$$k = 1.31$$

$$q = 6.0 \times 10^6 \text{ SCFH}$$

2. Determine the appropriate equation constant,  $N$ , from the Equation Constants Table 2 in Liquid Valve Sizing Section.

Because both  $G_g$  and  $M$  have been given in the service conditions, it is possible to use an equation containing either  $N_7$  or  $N_9$ . In either case, the end result will be the same. Assume that the equation containing  $G_g$  has been arbitrarily selected for this problem. Therefore,  $N_7 = 1360$ .

3. Determine  $F_p$ , the piping geometry factor.

Since valve and line size are assumed equal,  $F_p = 1.0$ .

4. Determine  $Y$ , the expansion factor.

$$F_k = \frac{k}{1.40}$$

$$= \frac{1.31}{1.40}$$

$$= 0.94$$

It is assumed that an 8 in. Design V250 valve will be adequate for the specified service conditions. From the flow coefficient Table 4,  $x_T$  for an 8 in. Design V250 valve at 100% travel is 0.137.

$x = 0.70$  (This was calculated in step 1.)

# Valve Sizing (Standardized Method)

Since conditions of critical pressure drop are realized when the calculated value of  $x$  becomes equal to or exceeds the appropriate value of  $F_k x_T$ , these values should be compared.

$$F_k x_T = (0.94)(0.137) \\ = 0.129$$

Because the pressure drop ratio,  $x = 0.70$  exceeds the calculated critical value,  $F_k x_T = 0.129$ , choked flow conditions are indicated. Therefore,  $Y = 0.667$  and  $x = F_k x_T = 0.129$ .

5. Solve for required  $C_v$  using the appropriate equation.

$$C_v = \frac{q}{N_7 F_p P_1 Y \sqrt{\frac{x}{G_g T_1 Z}}}$$

The compressibility factor,  $Z$ , can be assumed to be 1.0 for the gas pressure and temperature given and  $F_p = 1$  because valve size and line size are equal.

$$\text{So,} \\ C_v = \frac{6.0 \times 10^6}{(1360)(1.0)(214.7)(0.667) \sqrt{\frac{0.129}{(0.6)(520)(1.0)}}} = 1515$$

6. Select the valve size using the flow coefficient table and the calculated  $C_v$  value.

The above result indicates that the valve is adequately sized (rated  $C_v = 2190$ ). To determine the percent valve opening, note that the required  $C_v$  occurs at approximately 83 degrees for the 8 in. Design V250 valve. Note also that, at 83 degrees opening, the  $x_T$  value is 0.252, which is substantially different from the rated value of 0.137 used initially in the problem. The next step is to rework the problem using the  $x_T$  value for 83 degrees travel.

The  $F_k x_T$  product must now be recalculated.

$$x = F_k x_T \\ = (0.94)(0.252) \\ = 0.237$$

The required  $C_v$  now becomes:

$$C_v = \frac{q}{N_7 F_p P_1 Y \sqrt{\frac{x}{G_g T_1 Z}}} \\ = \frac{6.0 \times 10^6}{(1360)(1.0)(214.7)(0.667) \sqrt{\frac{0.237}{(0.6)(520)(1.0)}}} \\ = 1118$$

The reason that the required  $C_v$  has dropped so dramatically is attributable solely to the difference in the  $x_T$  values at rated and 83 degrees travel. A  $C_v$  of 1118 occurs between 75 and 80 degrees travel.

The appropriate flow coefficient table indicates that  $x_T$  is higher at 75 degrees travel than at 80 degrees travel. Therefore, if the problem were to be reworked using a higher  $x_T$  value, this should result in a further decline in the calculated required  $C_v$ .

Reworking the problem using the  $x_T$  value corresponding to 78 degrees travel (i.e.,  $x_T = 0.328$ ) leaves:

$$x = F_k x_T \\ = (0.94)(0.328) \\ = 0.308$$

and,

$$C_v = \frac{q}{N_7 F_p P_1 Y \sqrt{\frac{x}{G_g T_1 Z}}} \\ = \frac{6.0 \times 10^6}{(1360)(1.0)(214.7)(0.667) \sqrt{\frac{0.308}{(0.6)(520)(1.0)}}} \\ = 980$$

The above  $C_v$  of 980 is quite close to the 75 degree travel  $C_v$ . The problem could be reworked further to obtain a more precise predicted opening; however, for the service conditions given, an 8 in. Design V250 valve installed in an 8 in. / 203 mm line will be approximately 75 degrees open.

## Compressible Fluid Sizing Sample Problem No. 2

Assume steam is to be supplied to a process designed to operate at 250 psig / 17 bar. The supply source is a header maintained at 500 psig / 34.5 bar and 500°F / 260°C. A 6 in. / DN 150 line from the steam main to the process is being planned. Also, make the assumption that if the required valve size is less than 6 in. / DN 150, it will be installed using concentric reducers. Determine the appropriate Design ED valve with a linear cage.

1. Specify the necessary variables required to size the valve:

- Desired valve design—ASME CL300 Design ED valve with a linear cage. Assume valve size is 4 in.
- Process fluid—superheated steam
- Service conditions—
  - $w = 125,000 \text{ lbs/hr} / 56,700 \text{ kg/hr}$
  - $P_1 = 500 \text{ psig} / 34.5 \text{ bar} = 514.7 \text{ psia} / 35.5 \text{ bar a}$
  - $P_2 = 250 \text{ psig} / 17 \text{ bar} = 264.7 \text{ psia} / 18.3 \text{ bar a}$
  - $P = 250 \text{ psi} / 17 \text{ bar}$
  - $x = \Delta P / P_1 = 250 / 514.7 = 0.49$
  - $T_1 = 500^\circ\text{F} / 260^\circ\text{C}$
  - $\gamma_1 = 1.0434 \text{ lb/ft}^3 / 16.71 \text{ kg/m}^3$   
(from Properties of Saturated Steam Table)
  - $k = 1.28$  (from Properties of Saturated Steam Table)



# Valve Sizing (Standardized Method)

2. Determine the appropriate equation constant,  $N$ , from the Equation Constants Table 2 in Liquid Valve Sizing Section.

Because the specified flow rate is in mass units, (lb/hr) and the specific weight of the steam is also specified, the only sizing equation that can be used is that which contains the  $N_6$  constant. Therefore,

$$N_6 = 63.3$$

3. Determine  $F_p$ , the piping geometry factor.

$$F_p = \left[ 1 + \frac{\Sigma K}{N_2} \left( \frac{C_v}{d^2} \right)^2 \right]^{-1/2}$$

where,

$N_2 = 890$ , determined from Table 2. Equation Constants

$d = 4$  in.

$C_v = 236$ , which is the value listed in the flow coefficient Table 5 for a 4 in. Design ED valve at 100% total travel.

$$\Sigma K = K_1 + K_2$$

$$= 1.5 \left( 1 - \frac{d^2}{D^2} \right)^2$$

$$= 1.5 \left( 1 - \frac{4^2}{6^2} \right)^2$$

$$= 0.463$$

Finally,

$$F_p = \left[ 1 + \frac{0.463}{890} \left( \frac{(1.0)(236)}{(4)^2} \right)^2 \right]^{-1/2}$$

$$= 0.95$$

4. Determine  $Y$ , the expansion factor.

$$Y = 1 - \frac{x}{3F_k x_{TP}}$$

where,

$$F_k = \frac{k}{1.40}$$

$$= \frac{1.28}{1.40}$$

$$= 0.91$$

$$x = 0.49 \text{ (As calculated in step 1.)}$$

Because the 4 in. valve is to be installed in a 6 in. line, the  $x_T$  term must be replaced by  $x_{TP}$ .

$$x_{TP} = \frac{x_T}{F_p^2} \left[ 1 + \frac{x_T K_i}{N_5} \left( \frac{C_v}{d^2} \right)^2 \right]^{-1}$$

where,

$N_5 = 1000$ , from Table 2. Equation Constants

$d = 4$  in.

$F_p = 0.95$ , determined in step 3

$x_T = 0.688$ , a value determined from the appropriate listing in the flow coefficient table

$C_v = 236$ , from step 3

and

$$K_i = K_1 + K_{B1}$$

$$= 0.5 \left( 1 - \frac{d^2}{D^2} \right)^2 + \left[ 1 - \left( \frac{d}{D} \right)^4 \right]$$

$$= 0.5 \left( 1 - \frac{4^2}{6^2} \right)^2 + \left[ 1 - \left( \frac{4}{6} \right)^4 \right]$$

$$= 0.96$$

where  $D = 6$  in.

so:

$$x_{TP} = \frac{0.69}{0.95^2} \left[ 1 + \frac{(0.69)(0.96)(236)^2}{1000(4^2)} \right]^{-1} = 0.67$$

Finally:

$$Y = 1 - \frac{x}{3F_k x_{TP}}$$

$$= 1 - \frac{0.49}{(3)(0.91)(0.67)}$$

$$= 0.73$$

5. Solve for required  $C_v$  using the appropriate equation.

$$C_v = \frac{w}{N_6 F_p Y \sqrt{x P_1 \gamma_1}}$$

$$= \frac{125,000}{(63.3)(0.95)(0.73) \sqrt{(0.49)(514.7)(1.0434)}}$$

$$= 176$$

# Valve Sizing (Standardized Method)

**Table 3. Representative Sizing Coefficients for Type 1098-EGR Regulator**

BODY SIZE		LINEAR CAGE						
		Line Size Equals Body Size		2:1 Line Size to Body Size		X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>
		C <sub>v</sub>		C <sub>v</sub>				
In.	DN	Regulating	Wide-Open	Regulating	Wide-Open			
1	25	16.8	17.7	17.2	18.1	0.806	0.43	0.84
2	50	63.3	66.7	59.6	62.8	0.820	0.35	
3	80	132	139	128	135	0.779	0.30	
4	100	202	213	198	209	0.829	0.28	
6	150	397	418	381	404	0.668	0.28	
BODY SIZE		WHISPER TRIM™ CAGE						
		Line Size Equals Body Size Piping		2:1 Line Size to Body Size Piping		X <sub>T</sub>	F <sub>D</sub>	F <sub>L</sub>
		C <sub>v</sub>		C <sub>v</sub>				
In.	DN	Regulating	Wide-Open	Regulating	Wide-Open			
1	25	16.7	17.6	15.6	16.4	0.753	0.10	0.89
2	50	54	57	52	55	0.820	0.07	
3	80	107	113	106	110	0.775	0.05	
4	100	180	190	171	180	0.766	0.04	
6	150	295	310	291	306	0.648	0.03	

**Table 4. Representative Sizing Coefficients for Rotary Shaft Valves**

VALVE SIZE, IN.	VALVE STYLE	DEGREES OF VALVE OPENING	C <sub>v</sub>	F <sub>L</sub>	X <sub>T</sub>	F <sub>D</sub>
1	V-Notch Ball Valve	60	15.6	0.86	0.53	----
		90	34.0	0.86	0.42	----
1-1/2	V-Notch Ball Valve	60	28.5	0.85	0.50	----
		90	77.3	0.74	0.27	----
2	V-Notch Ball Valve	60	59.2	0.81	0.53	----
		90	132	0.77	0.41	----
	High Performance Butterfly Valve	60	58.9	0.76	0.50	0.49
		90	80.2	0.71	0.44	0.70
3	V-Notch Ball Valve	60	120	0.80	0.50	0.92
		90	321	0.74	0.30	0.99
	High Performance Butterfly Valve	60	115	0.81	0.46	0.49
		90	237	0.64	0.28	0.70
4	V-Notch Ball Valve	60	195	0.80	0.52	0.92
		90	596	0.62	0.22	0.99
	High Performance Butterfly Valve	60	270	0.69	0.32	0.49
		90	499	0.53	0.19	0.70
6	V-Notch Ball Valve	60	340	0.80	0.52	0.91
		90	1100	0.58	0.20	0.99
	High Performance Butterfly Valve	60	664	0.66	0.33	0.49
		90	1260	0.55	0.20	0.70
8	V-Notch Ball Valve	60	518	0.82	0.54	0.91
		90	1820	0.54	0.18	0.99
	High Performance Butterfly Valve	60	1160	0.66	0.31	0.49
		90	2180	0.48	0.19	0.70
10	V-Notch Ball Valve	60	1000	0.80	0.47	0.91
		90	3000	0.56	0.19	0.99
	High Performance Butterfly Valve	60	1670	0.66	0.38	0.49
		90	3600	0.48	0.17	0.70
12	V-Notch Ball Valve	60	1530	0.78	0.49	0.92
		90	3980	0.63	0.25	0.99
	High Performance Butterfly Valve	60	2500	----	----	0.49
		90	5400	----	----	0.70
16	V-Notch Ball Valve	60	2380	0.80	0.45	0.92
		90	8270	0.37	0.13	1.00
	High Performance Butterfly Valve	60	3870	0.69	0.40	----
		90	8600	0.52	0.23	----



# Valve Sizing (Standardized Method)

**Table 5. Representative Sizing Coefficients for Design ED Single-Ported Globe Style Valve Bodies**

VALVE SIZE, IN.	VALVE PLUG STYLE	FLOW CHARACTERISTIC	PORT DIAMETER		RATED TRAVEL		C <sub>v</sub>	F <sub>L</sub>	X <sub>T</sub>	F <sub>D</sub>
			In.	mm	In.	mm				
1/2	Post Guided	Equal Percentage	0.38	9.7	0.50	12.7	2.41	0.90	0.54	0.61
3/4	Post Guided	Equal Percentage	0.56	14.2	0.50	12.7	5.92	0.84	0.61	0.61
1	Micro-Form™	Equal Percentage	3/8	9.5	3/4	19.1	3.07	0.89	0.66	0.72
			1/2	12.7	3/4	19.1	4.91	0.93	0.80	0.67
			3/4	19.1	3/4	19.1	8.84	0.97	0.92	0.62
	Cage Guided	Linear	1-5/16	33.3	3/4	19.1	20.6	0.84	0.64	0.34
Equal Percentage			1-5/16	33.3	3/4	19.1	17.2	0.88	0.67	0.38
1-1/2	Micro-Form™	Equal Percentage	3/8	9.5	3/4	19.1	3.20	0.84	0.65	0.72
			1/2	12.7	3/4	19.1	5.18	0.91	0.71	0.67
			3/4	19.1	3/4	19.1	10.2	0.92	0.80	0.62
	Cage Guided	Linear	1-7/8	47.6	3/4	19.1	39.2	0.82	0.66	0.34
Equal Percentage			1-7/8	47.6	3/4	19.1	35.8	0.84	0.68	0.38
2	Cage Guided	Linear	2-5/16	58.7	1-1/8	28.6	72.9	0.77	0.64	0.33
		Equal Percentage	2-5/16	58.7	1-1/8	28.6	59.7	0.85	0.69	0.31
3	Cage Guided	Linear	3-7/16	87.3	1-1/2	38.1	148	0.82	0.62	0.30
		Equal Percentage	----	----	----	----	136	0.82	0.68	0.32
4	Cage Guided	Linear	4-3/8	111	2	50.8	236	0.82	0.69	0.28
		Equal Percentage	----	----	----	----	224	0.82	0.72	0.28
6	Cage Guided	Linear	7	178	2	50.8	433	0.84	0.74	0.28
		Equal Percentage	----	----	----	----	394	0.85	0.78	0.26
8	Cage Guided	Linear	8	203	3	76.2	846	0.87	0.81	0.31
		Equal Percentage	----	----	----	----	818	0.86	0.81	0.26

6. Select the valve size using flow coefficient tables and the calculated C<sub>v</sub> value.

Refer to the flow coefficient Table 5 for Design ED valves with linear cage. Because the assumed 4 in. valve has a C<sub>v</sub> of 236 at 100% travel and the next smaller size (3 in.) has a C<sub>v</sub> of only 148, it can be surmised that the assumed size is correct. In the event that the calculated required C<sub>v</sub> had been small enough to have been handled by the next smaller size or if it had been larger than the rated C<sub>v</sub> for the assumed size, it would have been necessary to rework the problem again using values for the new assumed size.

7. Sizing equations for compressible fluids.

The equations listed below identify the relationships between flow rates, flow coefficients, related installation factors and pertinent service conditions for control valves handling compressible fluids. Flow rates for compressible fluids may be encountered in either mass or volume units and thus equations are necessary to handle both situations. Flow coefficients may be calculated using the appropriate equations selected from the following. A sizing flow chart for compressible fluids is given in Annex B.

The flow rate of a compressible fluid varies as a function of the ratio of the pressure differential to the absolute inlet pressure ( $\Delta P/P_1$ ), designated by the symbol  $x$ . At values of  $x$  near zero, the equations in this section can be traced to the basic Bernoulli equation for Newtonian incompressible fluids. However, increasing values of  $x$  result in expansion and compressibility effects that require the use of appropriate factors (see Buresh, Schuder and Driskell references).

## 7.1 Turbulent flow

### 7.1.1 Non-choked turbulent flow

#### 7.1.1.1 Non-choked turbulent flow without attached fittings

[Applicable if  $x < F_T X_T$ ]

The flow coefficient shall be calculated using one of the following equations:

Eq. 6 
$$C = \frac{W}{N_6 Y \sqrt{x P_1 \rho_1}}$$

Eq. 7 
$$C = \frac{W}{N_8 P_1 Y} \sqrt{\frac{T_1 Z}{x M}}$$

Eq. 8a 
$$C = \frac{Q}{N_9 P_1 Y} \sqrt{\frac{M T_1 Z}{x}}$$

Eq. 8b 
$$C = \frac{Q}{N_7 P_1 Y} \sqrt{\frac{G_g T_1 Z}{x}}$$

NOTE 1 Refer to 8.5 for details of the expansion factor  $Y$ .

NOTE 2 See Annex C for values of  $M$ .

#### 7.1.1.2 Non-choked turbulent flow with attached fittings

[Applicable if  $x < F_T X_{TP}$ ]

# Cold Temperature Considerations

## Regulators Rated for Low Temperatures

In some areas of the world, regulators periodically operate in temperatures below -20°F / -29°C. These cold temperatures require special construction materials to prevent regulator failure. Emerson offers regulator constructions that are RATED for use in service temperatures below -20°F / -29°C.

## Selection Criteria

When selecting a regulator for extreme cold temperature service, the following guidelines should be considered:

- The body material should be 300 Series stainless steel, LCC or LCB due to low carbon content in the material makeup.
- Give attention to the bolts used. Generally, special stainless steel bolting is required.
- Gaskets and O-rings may need to be addressed if providing a seal between two parts exposed to the cold.
- Special springs may be required in order to prevent fracture when exposed to extreme cold.
- Soft parts in the regulator that are also being used as a seal gasket between two metal parts (such as a diaphragm) may need special consideration. Alternate diaphragm materials should be used to prevent leakage caused by hardening and stiffening of the standard materials.

## Introduction

Freezing has been a problem since the birth of the gas industry. This problem will likely continue, but there are ways to minimize the effects of the phenomenon.

There are two areas of freezing. The first is the formation of ice from water travelling within the gas stream. Ice will form when temperatures drop below 32°F / 0°C.

The second is hydrate formation. Hydrate is a frozen mixture of water and hydrocarbons. This bonding of water around the hydrocarbon molecule forms a compound which can freeze above 32°F / 0°C. Hydrates can be found in pipelines that are saturated with water vapor. It is also common to have hydrate formation in natural gas of high BTU content. Hydrate formation is dependent upon operating conditions and gas composition.

## Reducing Freezing Problems

To minimize problems, we have several options.

1. Keep the fluid temperature above the freezing point by applying heat.
2. Feed an antifreeze solution into the flow stream.
3. Select equipment that is designed to be ice-free in the regions where there are moving parts.
4. Design systems that minimize freezing effects.
5. Remove the water from the flow stream.

## Heat the Gas

Obviously, warm water does not freeze. What we need to know is when is it necessary to provide additional heat.

Gas temperature is reduced whenever pressure is reduced. This temperature drop is about 1°F / -17°C for each 15 psi / 1.03 bar pressure drop. Potential problems can be identified by calculating the temperature drop and subtracting from the initial temperature. Usually ground temperature, about 50°F / 10°C is the initial temperature. If a pressure reducing station dropped the pressure from 400 to 250 psi / 28 to 17 bar and the initial temperature is 50°F / 10°C, the final temperature would be 40°F / 4°C.

$$50^{\circ}\text{F} - (400 \text{ to } 250 \text{ psi}) (1^{\circ}\text{F}/15 \text{ psi}) = 40^{\circ}\text{F}$$

$$(10^{\circ}\text{C} - (28 \text{ to } 17 \text{ bar}) (-17^{\circ}\text{C}/1.03 \text{ bar}) = 5^{\circ}\text{C})$$

In this case, a freezing problem is not expected. However, if the final pressure was 25 psi / 1.7 bar instead of 250 psi / 17 bar, the final temperature would be 25°F / -4°C. We should expect freezing in this example if there is any moisture in the gas stream.

We can heat the entire gas stream with line heaters where the situation warrants. However, this does involve some large equipment and considerable fuel requirements.

Many different types of large heaters are on the market today. Some involve boilers that heat a water/glycol solution which is circulated through a heat exchanger in the main gas line. Two important considerations are: (1) fuel efficiencies and (2) noise generation.

In many cases, it is more practical to build a box around the pressure reducing regulator and install a small catalytic heater to warm the regulator. When pilot-operated regulators are used, we may find that the ice passes through the regulator without difficulty but plugs the small ports in the pilot. A small heater can be used to heat the pilot supply gas or the pilot itself. A word of caution is appropriate. When a heater remains in use when it is not needed, it can overheat the rubber parts of the regulator. They are usually designed for 180°F / 82°C maximum. Using an automatic temperature control thermostat can prevent overheating.

## Antifreeze Solution

An antifreeze solution can be introduced into the flow stream where it will combine with the water. The mixture can pass through the pressure reducing station without freezing. The antifreeze is dripped into the pipeline from a pressurized reservoir through a needle valve. This system is quite effective if one remembers to replenish the reservoir. There is a system that allows the antifreeze to enter the pipeline only when needed. We can install a small pressure regulator between the reservoir and the pipeline with the control line of the small regulator connected downstream of the pressure reducing regulator in the pipeline. The small regulator is set at a lower pressure than the regulator in the pipeline. When the controlled pressure is normal, the small regulator remains closed and conserves the antifreeze. When ice begins to block the regulator in the pipeline, downstream pressure will fall below the setpoint of the small regulator which causes it to open, admitting antifreeze into the pipeline as it is needed. When the ice is removed, the downstream pressure returns to normal and the small regulator closes until ice begins to re-form. This system is quite reliable as long as the supply of the antifreeze solution is maintained. It is usually used at low volume pressure reducing stations.

## Equipment Selection

We can select equipment that is somewhat tolerant of freezing if we know how ice forms in a pressure reducing regulator. Since the pressure drop occurs at the orifice, this is the spot where we might expect the ice formation. However, this is not necessarily the case. Metal regulator bodies are good heat conductors. As a result, the body, not just the port, is cooled by the pressure drop. The moisture in the incoming gas strikes the cooled surface as it enters the body and freezes to the body wall before it reaches the orifice. If the valve plug is located upstream of the orifice, there is a good chance that it will become trapped in the ice

# Freezing

and remain in the last position. This ice often contains worm holes which allow gas to continue to flow. In this case, the regulator will be unable to control downstream pressure when the flow requirement changes. If the valve plug is located downstream of the port, it is operating in an area that is frequently ice-free. It must be recognized that any regulator can be disabled by ice if there is sufficient moisture in the flow stream.

## System Design

We can arrange station piping to reduce freezing if we know when to expect freezing. Many have noted that there are few reported instances of freezing when the weather is very cold (0°F / -18°C). They have observed that most freezing occurs when the atmospheric temperature is between 35 and 45°F / 2 and 7°C. When the atmospheric temperature is quite low, the moisture within the gas stream freezes to the pipe wall before it reaches the pressure reducing valve which leaves only dry gas to pass through the valve. We can take advantage of this concept by increasing the amount of piping that is exposed above ground upstream of the pressure reducing valve. This will assure ample opportunity for the moisture to contact the pipe wall and freeze to the wall.

When the atmospheric temperature rises enough to melt the ice from the pipe wall, it is found that the operating conditions are not favorable to ice formation in the pressure reducing valve. There may be sufficient solar heat gain to warm the regulator body or lower flow rates which reduces the refrigeration effect of the pressure drop.

Parallel pressure reducing valves make a practical antifreeze system for low flow stations such as farm taps. The two parallel regulators are set at slightly different pressures (maybe one at 50 psi / 3.4 bar and one at 60 psi / 4.1 bar). The flow will automatically go through the regulator with the higher setpoint. When this regulator freezes closed, the pressure will drop and the second regulator will open and carry the load. Since most freezing instances occur when the atmospheric temperature is between 35 and 45°F / 2 and 7°C, we expect the ice in the first regulator to begin thawing as soon as the flow stops. When the ice melts from the first regulator, it will resume flowing gas. These two regulators will continue to alternate between flowing and freezing until the atmospheric temperature decreases or increases, which will get the equipment out of the ice formation temperature range.

## Water Removal

Removing the moisture from the flow stream solves the problem of freezing. However, this can be a difficult task. Where moisture is a significant problem, it may be beneficial to use a method of dehydration. Dehydration is a process that removes the water from the gas stream. Effective dehydration removes enough water to prevent reaching the dew point at the lowest temperature and highest pressure.

Two common methods of dehydration involve glycol absorption and desiccants. The glycol absorption process requires the gas stream to pass through glycol inside a contactor. Water vapor is absorbed by the glycol which in turn is passed through a regenerator that removes the water by distillation. The glycol is reused after being stripped of the water. The glycol system is continuous and fairly low in cost. It is important, however, that glycol is not pushed downstream with the dried gas.

The second method, solid absorption or desiccant, has the ability to produce much drier gas than glycol absorption. The solid process has the gas stream passing through a tower filled with desiccant. The water vapor clings to the desiccant, until it reaches saturation. Regeneration of the desiccant is done by passing hot gas through the tower to dry the absorption medium. After cooling, the system is ready to perform again. This is more of a batch process and will require two or more towers to keep a continuous flow of dry gas. The desiccant system is more expensive to install and operate than the glycol units.

Most pipeline gas does not have water content high enough to require these measures. Sometimes a desiccant dryer installed in the pilot gas supply lines of a pilot-operated regulator is quite effective. This is primarily true where water is present on an occasional basis.

## Summary

It is ideal to design a pressure reducing station that will never freeze, but anyone who has spent time working on this problem will acknowledge that no system is foolproof. We can design systems that minimize the freezing potential by being aware of the conditions that favor freezing.

## Details

NACE International is a technical society concerned with corrosion and corrosion-related issues. NACE is responsible for a large number of standards, but by far the most influential and well known is MR0175, formerly entitled “Sulfide Stress Cracking Resistant Metallic Materials for Oilfield Equipment”. MR0175 was issued by NACE in 1975 to provide guidelines for the selection of materials that are resistant to failure in hydrogen sulfide – containing oil and gas production environments. MR0175 has been so widely referenced that, throughout the process industry, the term “NACE” has become nearly synonymous with “MR0175”. However, the situation changed in 2003.

MR0175 was modified significantly in a 2003 revision to cover chloride stress corrosion cracking in addition to sulfide stress cracking. Then, in late 2003, the document was reformatted and released as a joint NACE/ISO document called NACE MR0175/ISO 15156, “Petroleum and Natural Gas Industries – Materials for Use in H<sub>2</sub>S – Containing Environments in Oil and Gas Production”.

In April 2003, NACE also released a new standard, MR0103, which is entitled, “Materials Resistant to Sulfide Stress Cracking in Corrosive Petroleum Refining Environments.” This standard is essentially the refining industry’s “NACE MR0175”. MR0103 only addresses sulfide stress cracking, and as such is similar in many respects to the pre-2003 revisions of MR0175.

## These NACE standards are applied to:

- MR0175-2002 (and prior)—Intended primarily for upstream (*Oil and gas production*) applications; has historically also been applied to downstream (refinery) applications
- MR0175/ISO 15156—Applies to upstream (*Oil and gas production*) applications only; does not apply to refineries; Includes stress corrosion cracking
- MR0103—Applies to downstream (*Refinery*) applications only
- MR0175-2003—Applies to upstream (*Oil and gas production*); Replaced by MR0175/ISO 15156




Figure 1. Photomicrograph Showing Stress Corrosion Cracking

## NACE MR0175-2002 and Prior

The following statements, although based on information and requirements in the pre-2003 revisions of MR0175, cannot be presented in the detail furnished in the actual standard and do not guarantee suitability for any given material in hydrogen sulfide-containing sour environments. The reader is urged to refer to the actual standard before selecting equipment for sour service.

- Most ferrous metals can become susceptible to sulfide stress cracking (SSC) due to hardening by heat treatment and/or cold work. Conversely, many ferrous metals can be heat treated to improve resistance to SSC.
- Carbon and low-alloy steels must be properly heat treated to provide resistance to SSC. A maximum hardness limit of 22 HRC applies to carbon and low-alloy steels.
- Austenitic stainless steels are most resistant to SSC in the annealed condition; some specific grades and conditions of stainless steels are acceptable up to 35 HRC.

# NACE Sulfide Stress Cracking

- Copper-base alloys are inherently resistant to SSC, but are generally not used in critical parts of equipment without the approval of the purchaser due to concerns about general corrosion.
- Nickel alloys generally provide the best resistance to SSC. Some precipitation-hardenable nickel alloys are acceptable for use in applications requiring high strength and/or hardness up to 40 HRC.
- Chromium, nickel and other types of plating offer no protection against SSC. Their use is allowed in sour applications for wear resistance, but they cannot be used in an attempt to protect a non-resistant base material from SSC.
- Weld repairs and fabrication welds on carbon and low-alloy steels must be properly processed to ensure that they meet the 22 HRC maximum hardness requirement in the base metal, heat-affected zone (HAZ) and weld deposit. Alloy steels require post-weld heat treatment, and post-weld heat treatment is generally used for carbon steels as well.
- Conventional identification stamping is permissible in low stress areas, such as on the outside diameter of line flanges. Low-stress identification stamping must be used in other areas.
- The standard precludes using ASTM A193 Grade B7 bolting for applications that are considered “exposed”. Use of SSC-resistant bolting materials (such as ASTM A193 Grade B7M) sometimes necessitates to derating of valves designed originally to use B7 bolting.

## NACE MR0175/ISO 15156

NACE MR0175/ISO 15156 introduced significant changes to the standard. However, many end users continue to specify NACE MR0175-2002, feeling that it adequately meets their needs in providing good service life. The most significant changes in NACE MR0175/ISO 15156 include:




Figure 2. Schematic Showing the Generation of Hydrogen Producing SSC

- The revision addresses both sulfide stress cracking and chloride stress corrosion cracking. Prior versions simply listed most materials as acceptable or unacceptable. Because its scope was expanded to cover chloride stress corrosion cracking, the new standard lists all corrosion-resistant alloys as acceptable within limits, referred to as “environmental limits or environmental restrictions”. These are typically expressed in terms of H<sub>2</sub>S partial pressure, maximum temperature, ppm chlorides and the presence of free sulfur.
- 316 stainless steel usage is still allowed but under very limited environmental conditions. The impact, if strictly followed, is that this material will find very little use.
- The standard applies only to petroleum production, drilling, gathering and flow line equipment and field processing facilities to be used in H<sub>2</sub>S bearing hydrocarbon service. It does not apply to refineries.
- There is clear responsibility placed on the buyer to specify the correct materials. The manufacturer is responsible for meeting the metallurgical requirements of MR0175/ISO 15156.



## NACE MR0103

As mentioned, NACE MR0103 is similar in many respects to the pre-2003 revisions of NACE MR0175. The following are some major differences:

- MR0103 utilizes different, refinery-based definitions for what constitutes a sour environment. The user is responsible for imposing the requirements of MR0103 when they are applicable. The manufacturer is responsible for meeting the metallurgical requirements of NACE MR0103.
- The 2002 and prior revisions of MR0175 included environmental restrictions on a few materials that were continued in the latter editions. MR0103 only deals with sulfide stress cracking. It does not impose environmental limits on any materials. Materials are either acceptable or not.
- Carbon steel base materials that are classified as P-No. 1, group 1 or 2 steels in the ASME Boiler and Pressure Vessel Code are acceptable per MR0103 without base metal hardness requirements. P-No. 1 groups 1 and 2 include WCC and LCC castings, A105 forgings, A516 Grade 70 plate and the other common carbon steel pressure vessel materials.
- MR0103 imposes welding controls on carbon steels that are more rigorous than those imposed by MR0175-2002. MR0103 requires that P-No. 1 carbon steels be welded per another NACE document called SP0472 “Methods and Controls to Prevent In-Service Environmental Cracking of Carbon Steel Weldments in Corrosive Petroleum Refining Environments”. SP0472 imposes controls that ensure both the weld deposit and heat affected zone (HAZ) in a weldment will be soft enough to resist sulfide stress cracking. SP0472 invokes actual hardness testing of weld deposits in production,

although hardness testing is waived if certain welding process/filler material combinations are employed. HAZ hardness may be controlled by either post-weld heat treatment (PWHT) or by a combination of cooling rate controls and base material chemistry restrictions such as imposing a maximum carbon equivalent (CE).

## Exposed Bolting

It is the user’s responsibility to determine if the body-to-bonnet bolting is considered exposed. NACE defines exposed bolting as any bolting that is exposed to the sour service. However, the NACE documents also extend the definition to include external bolting (such as body-to-bonnet bolting) that is buried, insulated, equipped with flange protectors, or otherwise denied direct atmospheric exposure. The logic is that, in these situations, the sour environment might be trapped around the bolting in the event of a gasket leak, so the bolting is to be treated as if it were inside the pressure containment.

## Coatings

NACE standards only address the base materials, and do not include restrictions on coatings or hard facing options. Coatings may be used provided the base metal is in a condition which is acceptable per the NACE standard. The coatings may not be used to protect a base metal which is susceptible to stress corrosion cracking.

## Elastomers

NACE standards only limit metallic materials, since they were written to address corrosion induced wear. There are still possible limitations of certain elastomers based on your process fluid, temperature and pressures. Please consult product bulletins and literature for more information.

# Chemical Compatibility of Elastomers and Metals

## Introduction

This section explains the uses and compatibilities of elastomers commonly used in Fisher™ regulators. The following tables provide the compatibility of the most common elastomers and metals to a variety of chemicals and/or compounds.

The information contained herein is extracted from data we believe to be reliable. However, because of variable service conditions over which we have no control, we do not in any way make any warranty, either express or implied, as to the properties of any materials or as to the performance of any such materials in any particular application and we hereby expressly disclaim any responsibility for the accuracy of any of the information set forth herein.

Refer to the applicable process gas service code or standard to determine if a specific material found in the Process Gases Application Guide is allowed to be used in that service.

## Elastomers: Chemical Names and Uses

**NBR** - Nitrile Rubber, also called Buna-N, is a copolymer of butadiene and acrylonitrile. Nitrile is recommended for: general purpose sealing, petroleum oils and fluids, water, silicone greases and oils, di-ester based lubricants (such as MIL-L-7808) and ethylene glycol based fluids (Hydrolubes). It is not recommended for: halogenated hydrocarbons, nitro hydrocarbons (such as nitrobenzene and aniline), phosphate ester hydraulic fluids (Skydrol, Cellulube, Pydraul), ketones (MEK, acetone), strong acids, ozone and automotive brake fluid. Its temperature range is -60 to 225°F / -51 to 107°C, although this would involve more than one compound and would depend upon the stress state of the component in service.

**EPDM, EPM** - Ethylenepropylene rubber is an elastomer prepared from ethylene and propylene monomers. EPM is a copolymer of ethylene and propylene, while EPDM contains a small amount of a third monomer (a diene) to aid in the curing process. EP is recommended for: phosphate ester based hydraulic fluids, steam to 400°F / 204°C, water, silicone oils and greases, dilute acids, dilute alkalis, ketones, alcohols and automotive brake fluids. It is not recommended for: petroleum oils and di-ester based lubricants. Its temperature range is -60 to 500°F / -51 to 260°C (the high limit would make use of a special high temperature formulation developed for geothermal applications).

**FKM** - This is a Fluorocarbon of the polymethylene type having substituent fluoro and perfluoroalkyl or perfluoroalkoxy groups on the polymer chain. Viton® and Fluorel® are the most common trade names. FKM is recommended for: petroleum oils, di-ester based lubricants, silicate ester based lubricants (such as MLO 8200, MLO 8515, OS-45), silicone fluids and greases, halogenated hydrocarbons, selected phosphate ester fluids and some acids. It is not recommended for: ketones, Skydrol 500, amines (UDMH), anhydrous ammonia, low molecular weight esters and ethers and hot hydrofluoric and chlorosulfonic acids. Its temperature range is -20 to 450°F / -29 to 232°C, (this extended range would require special grades and would limit use on each end of the range).

**CR** - This is chloroprene, commonly known as Neoprene, which is a homopolymer of chloroprene (chlorobutadiene). CR is recommended for: refrigerants (Freons, ammonia), high aniline point petroleum oils, mild acids and silicate ester fluids. It is not recommended for: phosphate ester fluids and ketones. Its temperature range is -60 to 200°F / -51 to 93°C, although this would involve more than one compound.

**NR** - This is natural rubber which is a natural polyisoprene, primarily from the tree, Hevea Brasiliensis. The synthetics have all but completely replaced natural rubber for seal use. NR is recommended for automotive brake fluid and it is not recommended for petroleum products. Its temperature range is -80 to 180°F / -62 to 82°C.

**FXM** - This is a copolymer of tetrafluoroethylene and propylene; hence, it is sometimes called PTFE/P rubber. Common trade names are Aflas® (Asahi Glass Co., Ltd) and Fluoraz® (Greene, Technologies, Inc.). It is generally used where resistance to both hydrocarbons and hot water are required. Its temperature range is 20 to 400°F / -7 to 204°C.

**ECO** - This is commonly called Hydrin® rubber, although that is a trade name for a series of rubber materials by B.F. Goodrich. CO is the designation for the homopolymer of epichlorohydrin, ECO is the designation for a copolymer of ethylene oxide and chloromethyl oxirane (epichlorohydrin copolymer) and ETER is the designation for the terpolymer of epichlorohydrin, ethylene oxide and an unsaturated monomer. All the epichlorohydrin rubbers exhibit better heat resistance than nitrile rubbers, but corrosion with aluminum may limit applications. Normal temperature range is (-40 to 250°F / -40 to 121°C), while maximum temperature ranges are -40 to 275°F / -40 to 135°C (for homopolymer CO) and -65 to 275°F / -54 to 135°C (for copolymer ECO and terpolymer ETER).

**FFKM** - This is a perfluoroelastomer generally better known as Kalrez® (DuPont) and Chemraz® (Greene, Technologies, Inc.). Perfluoro rubbers of the polymethylene type have all substituent groups on the polymer chain of fluoro, perfluoroalkyl or perfluoroalkoxy groups. The resulting polymer has superior chemical resistance and heat temperature resistance. This elastomer is extremely expensive and should be used only when all else fails. Its temperature range is 0 to 480°F / -18 to 249°C. Some materials, such as Kalrez® 1050LF is usable to 550°F / 288°C and Kalrez® 4079 can be used to 600°F / 316°C.

**FVMQ** - This is fluorosilicone rubber which is an elastomer that should be used for static seals because it has poor mechanical properties. It has good low and high temperature resistance and is reasonably resistant to oils and fuels because of its fluorination. Because of the cost, it only finds specialty use. Its temperature range is -80 to 400°F / -62 to 204°C.

**VMQ** - This is the most general term for silicone rubber. Silicone rubber can be designated MQ, PMQ and PVMQ, where the Q designates any rubber with silicon and oxygen in the polymer chain and M, P and V represent methyl, phenyl and vinyl substituent groups on the polymer chain. This elastomer is used only for static seals due to its poor mechanical properties. Its temperature range is -175 to 600°F / -115 to 316°C (extended temperature ranges require special compounds for high or low temperatures).

# Chemical Compatibility of Elastomers and Metals

**Table 1. General Properties of Elastomers**

PROPERTY		NATURAL RUBBER	BUNA-S	NITRILE (NBR)	NEOPRENE (CR)	BUTYL	THIOLKOL®	SILICONE	HYPALON®	FLUORO-CARBON <sup>(1,2)</sup> (FKM)	POLY-URETHANE <sup>(2)</sup>	POLY-ACRYLIC <sup>(1)</sup>	ETHYLENE-PROPYLENE <sup>(3)</sup> (EPDM)
Tensile Strength, psi / bar	Pure Gum	3000 / 207	400 / 28	600 / 41	3500 / 241	3000 / 207	300 / 21	200 to 450 / 14 to 31	4000 / 276	----	----	100 / 7	----
	Reinforced	4500 / 310	3000 / 207	4000 / 276	3500 / 241	3000 / 207	1500 / 103	1100 / 76	4400 / 303	2300 / 159	6500 / 448	1800 / 124	2500 / 172
Tear Resistance		Excellent	Poor-Fair	Fair	Good	Good	Fair	Poor-Fair	Excellent	Good	Excellent	Fair	Poor
Abrasion Resistance		Excellent	Good	Good	Excellent	Fair	Poor	Poor	Excellent	Very Good	Excellent	Good	Good
Aging: Sunlight Oxidation		Poor Good	Poor Fair	Poor Fair	Excellent Good	Excellent Good	Good Good	Good Very Good	Excellent Very Good	Excellent Excellent	Excellent Excellent	Excellent Excellent	---- Good
Heat (Maximum Temperature)		200°F / 93°C	200°F / 93°C	250°F / 121°C	200°F / 93°C	200°F / 93°C	140°F / 60°C	450°F / 232°C	300°F / 149°C	400°F / 204°C	200°F / 93°C	350°F / 177°C	350°F / 177°C
Static (Shelf)		Good	Good	Good	Very Good	Good	Fair	Good	Good	----	----	Good	Good
Flex Cracking Resistance		Excellent	Good	Good	Excellent	Excellent	Fair	Fair	Excellent	----	Excellent	Good	----
Compression Set Resistance		Good	Good	Very Good	Excellent	Fair	Poor	Good	Poor	Poor	Good	Good	Fair
Solvent Resistance: Aliphatic Hydrocarbon Aromatic Hydrocarbon Oxygenated Solvent Halogenated Solvent		Very Poor Very Poor Good Very Poor	Very Poor Very Poor Good Very Poor	Good Fair Poor Very Poor	Fair Poor Fair Very Poor	Poor Very Poor Good Poor	Excellent Good Fair Poor	Poor Very Poor Poor Very Poor	Fair Poor Poor Very Poor	Excellent Very Good Good ----	Very Good Fair Poor ----	Good Poor Poor Poor	Poor Fair ---- Poor
Oil Resistance: Low Aniline Mineral Oil High Aniline Mineral Oil Synthetic Lubricants Organic Phosphates		Very Poor Very Poor Very Poor Very Poor	Very Poor Very Poor Very Poor Very Poor	Excellent Excellent Fair Very Poor	Fair Good Very Poor Very Poor	Very Poor Very Poor Poor Good	Excellent Excellent Poor Poor	Poor Good Fair Poor	Fair Good Poor Poor	Excellent Excellent ---- Poor	---- ---- ---- Poor	Excellent Excellent Fair Poor	Poor Poor Poor Very Good
Gasoline Resistance: Aromatic Non-Aromatic		Very Poor Very Poor	Very Poor Very Poor	Good Excellent	Poor Good	Very Poor Very Poor	Excellent Excellent	Poor Good	Poor Fair	Good Very Good	Fair Good	Fair Poor	Fair Poor
Acid Resistance: Diluted (Under 10%) Concentrated <sup>(4)</sup>		Good Fair	Good Poor	Good Poor	Fair Fair	Good Fair	Poor Very Poor	Fair Poor	Good Good	Excellent Very Good	Fair Poor	Poor Poor	Very Good Good
Low Temperature Flexibility (Maximum)		-65°F / -54°C	-50°F / -46°C	-40°F / -40°C	-40°F / -40°C	-40°F / -40°C	-40°F / -40°C	-100°F / -73°C	-20°F / -29°C	-30°F / -34°C	-40°F / -40°C	-10°F / -23°C	-50°F / -45°C
Permeability to Gases		Fair	Fair	Fair	Very Good	Very Good	Good	Fair	Very Good	Good	Good	Good	Good
Water Resistance		Good	Very Good	Very Good	Fair	Very Good	Fair	Fair	Fair	Excellent	Fair	Fair	Very Good
Alkali Resistance: Diluted (Under 10%) Concentrated		Good Fair	Good Fair	Good Fair	Good Good	Very Good Very Good	Poor Poor	Fair Poor	Good Good	Excellent Very Good	Fair Poor	Poor Poor	Excellent Good
Resilience		Very Good	Fair	Fair	Very Good	Very Good	Poor	Good	Good	Good	Fair	Very Poor	Very Good
Elongation (Maximum)		700%	500%	500%	500%	700%	400%	300%	300%	425%	625%	200%	500%

1. Do not use with steam.
2. Do not use with ammonia.
3. Do not use with petroleum based fluids. Use with ester based non-flammable hydraulic oils and low pressure steam applications to 300°F / 149°C.
4. Except for nitric and sulfuric acid.

# Chemical Compatibility of Elastomers and Metals

**Table 2. Fluid Compatibility of Elastomers**

FLUID	MATERIAL				
	Neoprene (CR)	Nitrile (NBR)	Fluorocarbon (FKM)	Ethylenepropylene (EPDM)	Perfluoroelastomer (FFKM)
Acetic Acid (30%)	B	C	C	A	A
Acetone	C	C	C	A	A
Air, Ambient	A	A	A	A	A
Air, Hot (200°F / 93°C)	C	B	A	A	A
Alcohol (Ethyl)	A	C	C	A	A
Alcohol (Methyl)	A	A	C	A	A
Ammonia (Anhydrous) (Cold)	A	A	C	A	A
Ammonia (Gas, Hot)	B	C	C	B	A
Beer	A	A	A	A	A
Benzene	C	C	B	C	A
Brine (Calcium Chloride)	A	A	B	A	A
Butadiene Gas	C	C	B	C	A
Butane (Gas)	A	A	A	C	A
Butane (Liquid)	C	A	A	C	A
Carbon Tetrachloride	C	C	A	C	A
Chlorine (Dry)	C	C	A	C	A
Chlorine (Wet)	C	C	B	C	A
Coke Oven Gas	C	C	A	C	A
Ethyl Acetate	C	C	C	B	A
Ethylene Glycol	A	A	A	A	A
Freon 11	C	B	A	C	A
Freon 12	A	A	B	B	A
Freon 22	A	C	C	A	A
Freon 114	A	A	B	A	A
Gasoline (Automotive)	C	B	A	C	A
Hydrogen Gas	A	A	A	A	A
Hydrogen Sulfide (Dry)	A	A <sup>(1)</sup>	C	A	A
Hydrogen Sulfide (Wet)	B	C	C	A	A
Jet Fuel (JP-4)	B	A	A	C	A
Methyl Ethyl Ketone (MEK)	C	C	C	A	A
MTBE	C	C	C	C	A
Natural Gas	A	A	A	C	A
Nitric Acid (50 to 100%)	C	C	B	C	A
Nitrogen	A	A	A	A	A
Oil (Fuel)	C	A	A	C	A
Propane	B	A	A	C	A
Sulfur Dioxide	A	C	A	A	A
Sulfuric Acid (up to 50%)	B	C	A	B	A
Sulfuric Acid (50 to 100%)	C	C	A	B	A
Water (Ambient)	A	A	A	A	A
Water (at 200°F / 93°C)	C	B	B	A	A

1. Performance worsens with hot temperatures.  
A - Recommended  
B - Minor to moderate effect. Proceed with caution.  
C - Unsatisfactory  
N/A - Information not available

# Chemical Compatibility of Elastomers and Metals

Table 3. Compatibility of Metals

CORROSION INFORMATION														
Fluid	Material													
	Carbon Steel	Cast Iron	S302 or S304 Stainless Steel	S316 Stainless Steel	Bronze	Monel®	Hastelloy® B	Hastelloy® C	Durimet® 20	Titanium	Cobalt-Base Alloy 6	S416 Stainless Steel	440C Stainless Steel	17-4PH Stainless Steel
Acetaldehyde	A	A	A	A	A	A	IL	A	A	IL	IL	A	A	A
Acetic Acid, Air Free	C	C	B	B	B	B	A	A	A	A	A	C	C	B
Acetic Acid, Aerated	C	C	A	A	A	A	A	A	A	A	A	C	C	B
Acetic Acid Vapors	C	C	A	A	B	B	IL	A	B	A	C	C	C	B
Acetone	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Acetylene	A	A	A	A	IL	A	A	A	A	IL	A	A	A	A
Alcohols	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Aluminum Sulfate	C	C	A	A	B	B	A	A	A	IL	C	C	IL	IL
Ammonia	A	A	A	A	C	A	A	A	A	A	A	A	A	IL
Ammonium Chloride	C	C	B	B	B	B	A	A	A	A	C	C	C	IL
Ammonium Nitrate	A	C	A	A	C	C	A	A	A	A	A	B	B	IL
Ammonium Phosphate (Mono Basic)	C	C	A	A	B	B	A	A	B	A	A	B	B	IL
Ammonium Sulfate	C	C	B	A	B	A	A	A	A	A	C	C	IL	IL
Ammonium Sulfite	C	C	A	A	C	C	IL	A	A	A	B	B	IL	IL
Aniline	C	C	A	A	C	B	A	A	A	A	C	C	C	IL
Asphalt	A	A	A	A	A	A	A	A	A	IL	A	A	A	A
Beer	B	B	A	A	B	A	A	A	A	A	A	B	B	A
Benzene (Benzol)	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Benzoic Acid	C	C	A	A	A	A	IL	A	A	A	A	A	A	A
Boric Acid	C	C	A	A	A	A	A	A	A	A	A	B	B	IL
Butane	A	A	A	A	A	A	A	A	A	IL	A	A	A	A
Calcium Chloride (Alkaline)	B	B	C	B	C	A	A	A	A	A	IL	C	C	IL
Calcium Hypochlorite	C	C	B	B	B	B	C	A	A	A	IL	C	C	IL
Carbolic Acid	B	B	A	A	A	A	A	A	A	A	IL	IL	IL	IL
Carbon Dioxide, Dry	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Carbon Dioxide, Wet	C	C	A	A	B	A	A	A	A	A	A	A	A	A
Carbon Disulfide	A	A	A	A	C	B	A	A	A	A	A	B	B	IL
Carbon Tetrachloride	B	B	B	B	A	A	B	A	A	IL	C	A	A	IL
Carbonic Acid	C	C	B	B	B	A	A	A	A	IL	IL	A	A	A
Chlorine Gas, Dry	A	A	B	B	B	A	A	A	A	C	B	C	C	C
Chlorine Gas, Wet	C	C	C	C	C	C	C	B	C	A	B	C	C	C
Chlorine, Liquid	C	C	C	C	B	C	C	A	B	C	B	C	C	C
Chromic Acid	C	C	C	B	C	A	C	A	C	A	B	C	C	C
Citric Acid	IL	C	B	A	A	B	A	A	A	IL	IL	B	B	B
Coke Oven Gas	A	A	A	A	B	B	A	A	A	A	A	A	A	A
Copper Sulfate	C	C	B	B	B	C	IL	A	A	A	IL	A	A	A
Cottonseed Oil	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Creosote	A	A	A	A	C	A	A	A	A	IL	A	A	A	A
Ethane	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Ether	B	B	A	A	A	A	A	A	A	A	A	A	A	A
Ethyl Chloride	C	C	A	A	A	A	A	A	A	A	A	B	B	IL
Ethylene	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Ethylene Glycol	A	A	A	A	A	A	IL	IL	A	IL	A	A	A	A
Ferric Chloride	C	C	C	C	C	C	C	B	C	A	B	C	C	IL
Formaldehyde	B	B	A	A	A	A	A	A	A	A	A	A	A	A
Formic Acid	IL	C	B	B	A	A	A	A	A	C	B	C	C	B
Freon, Wet	B	B	B	A	A	A	A	A	A	A	A	IL	IL	IL
Freon, Dry	B	B	A	A	A	A	A	A	A	A	A	IL	IL	IL
Furfural	A	A	A	A	A	A	A	A	A	A	A	B	B	IL
Gasoline, Refine	A	A	A	A	A	A	A	A	A	A	A	A	A	A

A - Recommended  
 B - Minor to moderate effect. Proceed with caution.  
 C - Unsatisfactory  
 IL - Information lacking

- continued -



# Chemical Compatibility of Elastomers and Metals

Table 3. Compatibility of Metals (continued)

CORROSION INFORMATION														
Fluid	Material													
	Carbon Steel	Cast Iron	S302 or S304 Stainless Steel	S316 Stainless Steel	Bronze	Monel®	Hastelloy® B	Hastelloy® C	Durimet® 20	Titanium	Cobalt-Base Alloy 6	S416 Stainless Steel	440C Stainless Steel	17-4PH Stainless Steel
Glucose	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Hydrochloric Acid, Aerated	C	C	C	C	C	C	A	B	C	C	B	C	C	C
Hydrochloric Acid, Air free	C	C	C	C	C	C	A	B	C	C	B	C	C	C
Hydrofluoric Acid, Aerated	B	C	C	B	C	C	A	A	B	C	B	C	C	C
Hydrofluoric Acid, Air free	A	C	C	B	C	A	A	A	B	C	IL	C	C	IL
Hydrogen	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Hydrogen Peroxide	IL	A	A	A	C	A	B	B	A	A	IL	B	B	IL
Hydrogen Sulfide, Liquid	C	C	A	A	C	C	A	A	B	A	A	C	C	IL
Magnesium Hydroxide	A	A	A	A	B	A	A	A	A	A	A	A	A	IL
Mercury	A	A	A	A	C	B	A	A	A	A	A	A	A	B
Methanol	A	A	A	A	A	A	A	A	A	A	A	A	B	A
Methyl Ethyl Ketone	A	A	A	A	A	A	A	A	A	IL	A	A	A	A
Milk	C	C	A	A	A	A	A	A	A	A	A	C	C	C
Natural Gas	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Nitric Acid	C	C	A	B	C	C	C	B	A	A	C	C	C	B
Oleic Acid	C	C	A	A	B	A	A	A	A	A	A	A	A	IL
Oxalic Acid	C	C	B	B	B	B	A	A	A	B	B	B	B	IL
Oxygen	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Petroleum Oils, Refined	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Phosphoric Acid, Aerated	C	C	A	A	C	C	A	A	A	B	A	C	C	IL
Phosphoric Acid, Air Free	C	C	A	A	C	B	A	A	A	B	A	C	C	IL
Phosphoric Acid Vapors	C	C	B	B	C	C	A	IL	A	B	C	C	C	IL
Picric Acid	C	C	A	A	C	C	A	A	A	IL	IL	B	B	IL
Potassium Chloride	B	B	A	A	B	B	A	A	A	A	IL	C	C	IL
Potassium Hydroxide	B	B	A	A	B	A	A	A	A	A	IL	B	B	IL
Propane	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Rosin	B	B	A	A	A	A	A	A	A	IL	A	A	A	A
Silver Nitrate	C	C	A	A	C	C	A	A	A	A	B	B	B	IL
Sodium Acetate	A	A	B	A	A	A	A	A	A	A	A	A	A	A
Sodium Carbonate	A	A	A	A	A	A	A	A	A	A	A	B	B	A
Sodium Chloride	C	C	B	B	A	A	A	A	A	A	A	B	B	B
Sodium Chromate	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Sodium Hydroxide	A	A	A	A	C	A	A	A	A	A	A	B	B	A
Sodium Hypochloride	C	C	C	C	B-C	B-C	C	C	A	B	IL	C	C	IL
Sodium Thiosulfate	C	C	A	A	C	C	A	A	A	A	IL	B	B	IL
Stannous Chloride	B	B	C	A	C	B	A	A	A	A	IL	C	C	IL
Stearic Acid	A	C	A	A	B	B	A	A	A	A	B	B	B	IL
Sulfate Liquor (Black)	A	A	A	A	C	A	A	A	A	A	A	IL	IL	IL
Sulfur	A	A	A	A	C	A	A	A	A	A	A	A	A	A
Sulfur Dioxide, Dry	A	A	A	A	A	A	B	A	A	A	A	B	B	IL
Sulfur Trioxide, Dry	A	A	A	A	A	A	B	A	A	A	A	B	B	IL
Sulfuric Acid (Aerated)	C	C	C	C	C	C	A	A	A	B	C	C	C	C
Sulfuric Acid (Air Free)	C	C	C	C	B	B	A	A	A	B	C	C	C	C
Sulfurous Acid	C	C	B	B	B	C	A	A	A	A	B	C	C	IL
Tar	A	A	A	A	A	A	A	A	A	A	A	A	A	A
Trichloroethylene	B	B	B	A	A	A	A	A	A	A	A	B	B	IL
Turpentine	B	B	A	A	A	B	A	A	A	A	A	A	A	A
Vinegar	C	C	A	A	B	A	A	A	A	IL	A	C	C	A
Water, Boiler Feed	B	C	A	A	C	A	A	A	A	A	A	B	A	A
Water, Distilled	A	A	A	A	A	A	A	A	A	A	A	B	B	IL
Water, Sea	B	B	B	B	A	A	A	A	A	A	A	C	C	A
Whiskey and Wines	C	C	A	A	A	B	A	A	A	A	A	C	C	IL
Zinc Chloride	C	C	C	C	C	C	A	A	A	A	B	C	C	IL
Zinc Sulfate	C	C	A	A	B	A	A	A	A	A	B	B	B	IL

A - Recommended  
 B - Minor to moderate effect. Proceed with caution.  
 C - Unsatisfactory  
 IL - Information lacking

## SIZING AND SELECTION

### Spring Selection

- If two or more available springs have published pressure ranges that include the desired pressure setting, use the spring with the lower range for better accuracy.
- The full advertised range of a spring can be used without sacrificing performance or spring life.

### Sizing Guidelines

- Do not oversize regulators. Pick the smallest regulator and orifice that will handle the maximum flow requirement.
- Regulator body size should not be larger than the pipe size. The regulator body is often smaller than the pipe size.
- Regulating  $C_g$  (coefficient of flow) can only be used for calculating flow capacities on pilot-operated regulators. Use capacity tables or flow charts for determining a direct-operated regulator's capacity.
- When sizing direct-operated regulators, use interpolation for application pressures differing from the values in the capacity tables. For best results, use data from within the same spring range.
- Parallel runs can improve the turndown at stations with large differences between the maximum and minimum flow.
- Restricted trims do not improve low flow control unless they reduce the flow area size when the valve plug is at low travel.

### Pilot-operated Regulators

- Pilot-operated regulators require a pressure differential to operate the main valve. The published minimum differential requirement is the pressure needed to overcome the force from the main spring and fully open the main valve.
- A pilot-supply regulator can be an invaluable tool for achieving optimum performance with a pilot-operated regulator. It improves accuracy by eliminating inlet sensitivity, increases stability by reducing gain and improves closing speed-of-response.

### Monitors and Slamshuts

- The intermediate piping in monitor and slamshut applications can reach full inlet pressure so the equipment must have sufficient pressure ratings.
- Wide-open monitors and stand-alone slamshuts create a pressure drop, reducing the available pressure drop for sizing the working regulator. To determine the flowrate of the station, calculate the maximum pressure drop of the wide-open monitor or slamshut using the Non-critical Pressure Drop Sizing Equation. Use the remaining pressure differential to size the working regulator.
- To maximize flow with working monitors, take roughly 35% of the pressure drop of the station in the first cut.

### Reliefs

- The relief valve will not see the maximum regulator inlet pressure if properly sized; therefore, its pressure rating is often lower. The inlet pressure to the regulator is only relevant when determining the maximum flow through the regulator.
- Relief valves require a buildup over set pressure to fully open the valve. This buildup should be considered when determining the correct relief valve for the application.

### Speed of Response

- Speed of response, in order:
  - Direct-operated (a.k.a. self-operated)
  - Two-path pilot-operated
  - Unloading pilot-operated
  - Control valve

Note: Although direct-operated regulators give the fastest response, all types provide quick response.

- Fuel gas applications requiring pilot-operated regulators sometimes necessitate special regulator constructions to quicken opening and/or closing.

### Liquid Service

- Due to differences in viscosity, regulators used in liquid service typically have larger pilot orifices and larger restrictors to improve speed-of-response.
- Cavitation is a function of pressure drop. Selecting a different regulator size will not affect cavitation.
- To avoid cavitation in pressure regulators, take large pressure drops in stages.

### Noise

- Regulators with high flows and large pressure drops generate high aerodynamic noise. Regulator types with the most tortuous paths generate the greatest turbulence and therefore the highest noise. Noise attenuating trims are utilized to prevent initial noise attenuation by reducing turbulence, staging the pressure drop and lowering fluid velocities to subsonic levels.
- If noise attenuating trim is found insufficient, consider additional noise reduction methods such as working monitor setups to split the pressure drop, parallel runs to split the flow and reduce outlet velocity, increasing the outlet pipe thickness and/or swaging up the outlet piping to reduce outlet velocity. If these solutions are insufficient, path treatments such as acoustic insulation, enclosures, and noise barriers should be considered.

# Regulator Best Practices

## STATION DESIGN

### Conditioning

- For every 15 psig / 1.0 bar d pressure differential across the regulator in gas service, expect approximately 1°F / 0.55 °C temperature decrease due to the natural refrigeration effect. Preheating is sometimes necessary to ensure the regulator's elastomers retain flexibility and to prevent freezing problems both inside and outside the pipe.
- To prevent plugging or damaging regulator components, ensure the process fluid is free of pipeline debris and contaminants using the appropriate equipment (filter, separator, strainer, etc.).

### Overpressure Protection

- Adequate overpressure protection should be installed to protect employees, the public, the regulators, piping and downstream equipment.
- Frequently recommended 2-layer Overpressure protection configurations include:
  - 1st Stage: Monitor, 2nd Stage: Slamshut
  - 1st Stage: Monitor, 2nd Stage: Relief Valve
  - 1st Stage: Relief Valve, 2nd Stage: Slamshut
- Ensure that vent stacks for relief devices carry the relieving fluid away from maintenance activities and ignition sources.

### Underpressure Protection

- To prevent a malfunctioning regulator from shutting down the gas feed, use a duplicate regulator run on standby. By setting the standby run at a slightly lower pressure than the primary run, the standby run will stay closed but prepared to open if the downstream pressure decreases for any reason.

### Piping Setup

- Design downstream piping to accommodate proper control line placement. At least 6 pipe diameters of straight pipe are required, free of any turbulence generating equipment, such as elbows, pipe swages, regulators or block valves.
- When installing a working monitor station, include at least 10 pipe diameters between the upstream and downstream regulators. The upstream regulator requires adequate piping volume for stable control of intermediate pressure.
- Pipe bypasses or redundant regulator runs allow continued operation during maintenance.
- Piping supports prevent strain on equipment.
- Ensure the number of pressure taps is sufficient both for connecting regulator supply/control lines and for pressure gauges connections. Additional pressure taps are useful for troubleshooting, testing and future expansion or upgrades.
- A vent valve is required in the downstream piping to allow depressurization prior to maintenance.
- In liquid service, ensure that you have proper piping and regulator orientation to avoid trapping air in the actuator

### Maintenance Considerations

- Allow sufficient clearance for maintenance and lifting. If the weight of the regulator requires lifting assistance, ensure accommodations are included for lifting equipment



## INSTALLATION

### Regulator Body

- Install the regulator so that the flow arrow on the regulator matches the flow direction of the process fluid.
- Regulators are not designed to align piping that is out-of-alignment. Using Cast Iron regulator bodies to force pipelines into alignment can result in damage.

### Vents

- Diaphragms leak a small amount due to the migration of gas through elastomer diaphragms. To allow escape of this gas, be sure casing vents (where provided) remain open.
- Keep vents open. Do not use small diameter, long vent lines. As a rule of thumb, increase one nominal pipe size every 10 ft. / 3.1 m of vent line for units with internal relief and every 50 ft. / 15.2 m for units without internal relief (in both cases, an elbow is equivalent to 3 ft / 0.9 m of vent line).
- Vents should be pointed down to help avoid the accumulation of water condensation or other materials in the spring case.
- Burying regulators is not recommended. However, if you must, the vent should be protected from moisture and plugging.

### Control Lines

- Make control line connections in a straight run of pipe at least 6 pipe diameters downstream of any area of turbulence, such as elbows, pipe swages, meters or block valves.
- Use control lines of equal or greater size than the control tap on the regulator. For every 10 feet of control line, increase the entire control line by one nominal pipe size. Small control lines cause a delayed response of the regulator, leading to an increased chance of instability. 3/8 in. / 9.5 mm OD tubing is the minimum recommended control line size.
- Valves used in the control line, should be full port valves. Needle valves or other restrictions may adversely affect speed-of-response.

## STARTUP

- Pressurize the inlet to the regulator prior to outlet or regulator damage can occur. On pilot-operated regulators, avoid damage by first applying pressure to the piloting system through the inlet supply line. This method protects the regulator from reverse pressurization and slowly fills the pipe between the regulator and the outlet block valve.

### Setpoints

- When adjusting setpoint, a direct-operated regulator should be flowing approximately 5% of the published capacity. Setting the regulator at other flow conditions will shift lockup and droop correspondingly.
- Do not make the setpoints of the regulator/monitor too close together. The monitor may try to take over if the setpoints are too close causing instability and reduced capacity. Set them at least one proportional band apart.
- When using relief valves, remember that the reset point is lower than the start-to-bubble point. To avoid unwanted leakage, ensure the lockup of the regulator and the reset of the relief valve do not overlap.
- Relief valve setpoint is defined as first bubble which occurs at the pilot in pilot-operated relief valves.

# Troubleshooting

Symptom	Problem	Details / Solutions
<b>Outlet pressure is above expected setpoint</b> (at zero flow demand)	Valve plug or orifice damaged	A damaged valve plug or orifice prevents proper sealing, causing higher lockup pressures. Preventative maintenance of your regulator can identify worn or damaged parts. Consider filtration in your process line.
		Improper seal between orifice and body due to improper installation, incorrect torque, or debris can cause leakage downstream. Keep in mind that metal seats are allowed leakage to ANSI/FCI 70-3 Class IV.
		For pilot-operated regulators, check the valve plug and orifice of both the pilot and main valve. Tip: block valves can be used to isolate whether the pilot or main valve is the leak source.
	Operating pressures and temperatures outside published limits	Exceeding maximum pressure, differential pressure or temperature specifications can result in leakage downstream. Consult product bulletin for proper specifications.
	Physical obstruction	Foreign debris in the trim or spring case can prevent a regulator from closing, preventing shutoff.
	Setpoint made at unrepresentative process conditions	Setpoint made at a higher than recommended flow may result in higher than desired lockup pressure. Setpoint should typically be made at 1-5% of flowing capacity. Turn the adjusting screw until you've reached the desired setpoint.
	Moving parts damaged	Inspect metal parts for scoring, deformation, or other damage. Inspect elastomeric parts for cuts, cracks, tears or chemical attack. Damaged parts can keep your regulator from functioning properly. Preventative maintenance of your regulator can identify worn or damaged parts. Consider filtration in your process line
	Thermal buildup	Sunlight on the outlet piping can heat the gas, increasing pressure.
Leakage through alternate flowpath	Verify that bypass lines, parallel runs and associated equipment are not leaking. Some pilot-operated monitor setups bleed downstream through the bleed line until setpoint is met.	
<b>Outlet pressure is above expected setpoint</b> (under flowing conditions)	Incorrect control spring	Verify the spring is correct using product literature.
	Using product beyond published capacities	Verify that the flowrate is within the published capacity. Keep in mind that some internal sensing self-operated regulators boost above setpoint rather than drooping.
	Fluctuating inlet pressure (Inlet Sensitivity)	Consider adding a regulator in series upstream to remove inlet variations to the final regulator (two-stage pressure cut setup).
		A pilot supply regulator can be used to deliver a constant pilot supply pressure.
	Control line disconnected	If the control line is open to the atmosphere (disconnected, damaged, etc.), the regulator will sense a pressure lower than setpoint and remain fully open.
	Restrictor is plugged	If the restrictor is plugged, the main valve may not close properly. Remove the obstruction and consider installing a filter in the supply line to reduce the risk of future obstructions.
Moving parts are damaged	Inspect metal parts for scoring, deformation or other damage. Inspect elastomeric parts for cuts, cracks, tears or chemical attack. Damaged parts can keep your regulator from functioning properly. Preventative maintenance of your regulator can identify worn or damaged parts. Consider filtration in your process line.	

 Applicable only for Pilot-Operated Regulators

Symptom	Problem	Details / Solutions
<b>Outlet pressure is below expected setpoint</b>	Droop	Self-operated regulators typically show reduction in outlet pressure below setpoint with increasing flow (droop) as published.
	Improper sizing	An undersized regulator will not reach the flow requirements because it will travel towards the wide open position as outlet pressure decreases.
	Using product beyond published capacities	Verify that the flowrate is within the published capacity. Self-operated regulators typically show reduction in outlet pressure below setpoint with increasing flow (droop).
	Setpoint made at unrepresentative process conditions	Setpoint made at a lower than recommended flow may result in lower than desired control pressure. Setpoint should typically be made at 1-5% of flowing capacity. Turn the adjusting screw until you've reached the desired setpoint.
	Incorrect control spring	Verify the spring is correct using product literature.
	Low inlet pressure	If the actual inlet pressure is lower than was used while sizing, the regulator could have insufficient capacity or minimum differential pressure. Inlet pressure must always be higher than the expected setpoint.
	Obstructed orifice or flowpath	Debris, ice build-up at the orifice and closed block valves can obstruct the flow path and prevent the regulator from reaching the outlet pressure setpoint. Clear obstruction from the lines and regulator body and make the appropriate process changes.
	Obstructed spring case vent	Clear the vent if clogged.
<b>Slow speed of response</b>	Incorrect product selection	Self-operated regulators have the fastest speed of response. See Regulator Best Practice section on Sizing and Selection
	Improper control line placement	For units with external control lines, the control line should be located in a straight run of pipe, at least 6 pipe diameters downstream from any area of turbulence such as elbows, pipe swages, meters or block valves. Sense location should be closer to demand source for quicker reaction
	Control line size inadequate for long length	Use control lines of equal or greater size than the control tap on the regulator. For every 10 feet of control line, increase the entire control line by one nominal pipe size. Control line size is most critical on low pressure systems.
	Alternative solution: If your pilot-operated regulator is closing too slowly	Increase restrictor size to increase closing speed.
		Consider a quick dumping pilot or adding a booster pilot.
		A pilot supply regulator can be used to reduce pilot gain
		Switching to a self-operated regulator will increase the speed of response
	Alternative solution: If your pilot-operated regulator is opening too slowly	Decrease restrictor size to increase opening speed.
		Increasing differential pressure allows pilot-operated pressures to open quicker.
		Consider a different pilot or larger pilot orifice size.
Adding an additional pilot, tubed in parallel, can increase opening speed. Switching to a self-operated regulator will increase the speed of response		
<b>Excessive Aerodynamic Noise</b>	Noise generated by flowrate and pressure drop	See Regulator Best Practice sections on Sizing and Selection and Station Design

Applicable only for Pilot-Operated Regulators

# Troubleshooting

Symptom	Problem	Details / Solutions
<b>Instability or Cycling -</b> Condition in which the regulator vibrates or the setpoint does not stabilize	Oversizing	Be sure to choose the smallest regulator and orifice that will meet the application's maximum flow requirement. Oversizing causes the disk to operate too close to the orifice, resulting in instability. Consult your local sales office to verify proper sizing
	Improper control line placement	For units with external control lines, the control line should be located in a straight run of pipe, at least 6 pipe diameters downstream from any areas of turbulence such as elbows, pipe swages, meters or block valves. Turbulence near the sensing port of the regulator leads to rapid fluctuations in sensed inlet pressure, leading to instability.
		For units with internal sensing, the piping should be on a straight run. Turbulence near the sensing port of the regulator from sources such as rotary meters, elbows and block valves leads to rapid fluctuations in sensed inlet pressure.
	Restriction in Control Line	Valves used in the control line, should be full port valves. Needle valves or other restrictions in the lines may affect speed-of-response so use only when all other options have been exhausted.
	Control line size inadequate for long length	Use control lines of equal or greater size than the control tap on the regulator. For every 10 ft. of control line, increase the entire control line by one nominal pipe size. Control line size is most critical on low pressure.
	Insufficient piping volume	Small pipeline volume can cause the controlled pressure to change rapidly when the regulator opens or closes.
	Regulator's gain is too high	Increase restrictor opening. A larger opening decreases the operating speed, leading to a more stable system.
		On a loading-style (two-path) pilot-operated regulator, add a pilot supply regulator to dampen out the pressure cycles in the control system. Set the pilot supply regulator slightly above the main valve's required minimum differential value.
	Operating pressures outside published limits	Exceeding maximum pressure or pressure differential specifications can result in instability. Consult product bulletin for proper specifications.
	The spring case vent is obstructed	Clear the vent if clogged. Ensure the screen is in place.
		Verify the vent is oriented downward to protect it from the weather on applications without vent piping and ensure there is no moisture in the spring case. In colder climates, ensure snow and ice build-up does not block the vent.
		Vent piping should be as large as the nominal size of the vent connection and as a rule-of-thumb increase one nominal pipe size for every 50 ft. of linear pipe. (One elbow is equivalent to 3 ft. of linear pipe). (Note: regulators with internal relief require larger piping to prevent ensure adequate overpressure protection)
	Pilot bleed interfering with the pilot's sensing	If the regulator is designed to use combined pilot bleed and control lines, use a control line at least as large as the control line port. If the line is not large enough, the exhaust can cause backpressure or erratic flow, leading to instability.
If the regulator is designed to use separate pilot bleed and control lines, use an individual tap for the bleed and control lines within the same pipe section.		
Alternative solution if above methods are unsuccessful	Use a heavier control spring. If the desired setpoint is within the next largest control spring's published range, replace the current control spring.	

Applicable only for Pilot-Operated Regulators

# Conversions, Equivalents and Physical Data

**Table 1. Pressure Equivalents**

MULTIPLY NUMBER OF BY TO OBTAIN	KG PER SQUARE CM	PSI	ATMOSPHERE	BAR	IN. OF MERCURY	KPA	IN. W.C.	FT. OF W.C.
<b>Kg per square cm</b>	1	14.22	0.9678	0.98067	28.96	98.067	394.05	32.84
<b>Psi</b>	0.07031	1	0.06804	0.06895	2.036	6.895	27.7	2.309
<b>Atmosphere</b>	1.0332	14.696	1	1.01325	29.92	101.325	407.14	33.93
<b>Bar</b>	1.01972	14.5038	0.98692	1	29.53	100	402.156	33.513
<b>Inches of Mercury</b>	0.03453	0.4912	0.03342	0.033864	1	3.3864	13.61	1.134
<b>Kilopascals</b>	0.0101972	0.145038	0.0098696	0.01	0.2953	1	4.02156	0.33513
<b>In. of Water</b>	0.002538	0.0361	0.002456	0.00249	0.07349	0.249	1	0.0833
<b>Ft. of Water</b>	0.3045	0.4332	0.02947	0.029839	0.8819	2.9839	12	1

1 ounce per square in. = 0.0625 psi

**Table 2. Pressure Conversion - Psi to Bar<sup>(1)</sup>**

PSI	0	1	2	3	4	5	6	7	8	9
	Bar									
0	0.000	0.069	0.138	0.207	0.276	0.345	0.414	0.482	0.552	0.621
10	0.689	0.758	0.827	0.896	0.965	1.034	1.103	1.172	1.241	1.310
20	1.379	1.448	1.517	1.586	1.655	1.724*	1.793	1.862	1.931	1.999
30	2.068	2.137	2.206	2.275	2.344	2.413	2.482	2.551	2.620	2.689
40	2.758	2.827	2.896	2.965	3.034	3.103	3.172	3.241	3.309	3.378
50	3.447	3.516	3.585	3.654	3.723	3.792	3.861	3.930	3.999	4.068
60	4.137	4.205	4.275	4.344	4.413	4.482	4.551	4.619	4.688	4.758
70	4.826	4.894	4.964	5.033	5.102	5.171	5.240	5.309	5.378	5.447
80	5.516	5.585	5.654	5.723	5.792	5.861	5.929	5.998	6.067	6.136
90	6.205	6.274	6.343	6.412	6.481	6.550	6.619	6.688	6.757	6.826
100	6.895	6.964	7.033	7.102	7.171	7.239	7.308	7.377	7.446	7.515

1. To convert to kilopascals, move decimal point two positions to the right; to convert to megapascals, move decimal point one position to the left.  
 \*Note: Round off decimal points to provide no more than the desired degree of accuracy.  
 To use this table, see the shaded example.  
 25 psig (20 from the left column plus five from the top row) = 1.724 bar

**Table 3. Volume Equivalents**

MULTIPLY NUMBER OF BY TO OBTAIN	DM <sup>3</sup> (L)	IN <sup>3</sup>	FT <sup>3</sup>	U.S. QUART	U.S. GAL.	IMPERIAL GAL.	U.S. BARREL (PETROLEUM)
<b>Dm<sup>3</sup> (L)</b>	1	61.0234	0.03531	1.05668	0.264178	0.220083	0.00629
<b>In.<sup>3</sup></b>	0.01639	1	5.787 x 10 <sup>-4</sup>	1.01732	0.004329	0.003606	0.000103
<b>Ft.<sup>3</sup></b>	28.317	1728	1	29.9221	7.48055	6.22888	0.1781
<b>U.S. Quart</b>	0.94636	57.75	0.03342	1	0.25	0.2082	0.00595
<b>U.S. Gal.</b>	3.78543	231	0.13368	4	1	0.833	0.02381
<b>Imperial Gal.</b>	4.54374	277.274	0.16054	4.80128	1.20032	1	0.02877
<b>U.S. Barrel (Petroleum)</b>	158.98	9702	5.6146	168	42	34.973	1

1 m<sup>3</sup> = 1,000,000 cm<sup>3</sup>  
 1 l = 1000 ml = 1000 cm<sup>3</sup>

# Conversions, Equivalents and Physical Data

**Table 4. Volume Rate Equivalents**

MULTIPLY NUMBER OF	BY	TO OBTAIN					
		L/MIN	M <sup>3</sup> /H	FT <sup>3</sup> /H	L/H	U.S. GAL./MIN	U.S. BARRELS/DAY
	l/m	1	0.06	2.1189	60	0.264178	9.057
	m <sup>3</sup> /h	16.667	1	35.314	1000	4.403	151
	ft <sup>3</sup> /h	0.4719	0.028317	1	28.317	0.1247	4.2746
	l/h	0.016667	0.001	0.035314	1	0.004403	0.151
	U.S. Gal./Min	3.785	0.2273	8.0208	227.3	1	34.28
	U.S. Barrels/Day	0.1104	0.006624	0.23394	6.624	0.02917	1

**Table 5. Mass Conversion - Lbs to kg**

LBS	Kg									
	0	1	2	3	4	5	6	7	8	9
0	0.00	0.45	0.91	1.36	1.81	2.27	2.72	3.18	3.63	4.08
10	4.54	4.99	5.44	5.90	6.35	6.80	7.26	7.71	8.16	8.62
20	9.07	9.53	9.98	10.43	10.89	11.34*	11.79	12.25	12.70	13.15
30	13.61	14.06	14.52	14.97	15.42	15.88	16.33	16.78	17.24	17.69
40	18.14	18.60	19.05	19.50	19.96	20.41	20.87	21.32	21.77	22.23
50	22.68	23.13	23.59	24.04	24.49	24.95	25.40	25.86	26.31	26.76
60	27.22	27.67	28.12	28.58	29.03	29.48	29.94	30.39	30.84	31.30
70	31.75	32.21	32.66	33.11	33.57	34.02	34.47	34.93	35.38	35.83
80	36.29	36.74	37.20	37.65	38.10	38.56	39.01	39.46	39.92	40.37
90	40.82	41.28	41.73	42.18	42.64	43.09	43.55	44.00	44.45	44.91

1 lb = 0.4536 kg  
 \*NOTE: To use this table, see the shaded example.  
 25 lbs (20 from the left column plus five from the top row) = 11.34 kg

**Table 6. Area Equivalents**

MULTIPLY NUMBER OF	BY	TO OBTAIN				
		M <sup>2</sup>	IN <sup>2</sup>	FT <sup>2</sup>	MI <sup>2</sup>	KM <sup>2</sup>
	M <sup>2</sup>	1	1549.99	10.7639	3.861 x 10 <sup>7</sup>	1 x 10 <sup>-6</sup>
	In <sup>2</sup>	0.0006452	1	6.944 x 10 <sup>-3</sup>	2.491 x 10 <sup>-10</sup>	6.452 x 10 <sup>-10</sup>
	Ft <sup>2</sup>	0.0929	144	1	3.587 x 10 <sup>-8</sup>	9.29 x 10 <sup>-8</sup>
	Mi <sup>2</sup>	2,589,999	----	27,878,400	1	2.59
	Km <sup>2</sup>	1,000,000	----	10,763,867	0.3861	1

1 m<sup>2</sup> = 10,000 cm<sup>2</sup>  
 1 m<sup>2</sup> = 0.01 cm<sup>2</sup> = 0.00155 in<sup>2</sup>

**Table 7. Temperature Conversion Formulas**

TO CONVERT FROM	TO	SUBSTITUTE IN FORMULA
Degrees Celsius	Degrees Fahrenheit	(°C x 9/5) + 32
Degrees Celsius	Kelvin	(°C + 273.16)
Degrees Fahrenheit	Degrees Celsius	(°F - 32) x 5/9
Degrees Fahrenheit	Degrees Rankine	(°F + 459.69)

**Table 8. Kinematic-Viscosity Conversion Formulas**

VISCOSITY SCALE	RANGE OF t, SEC	KINEMATIC VISCOSITY, STROKES
Saybolt Universal	32 < t < 100 t > 100	0.00226t - 1.95/t 0.00220t - 1.35/t
Saybolt Furol	25 < t < 40 t > 40	0.0224t - 1.84/t 0.0216t - 0.60/t
Redwood No. 1	34 < t < 100 t > 100	0.00226t - 1.79/t 0.00247t - 0.50/t
Redwood Admiralty	----	0.027t - 20/t
Engler	----	0.00147t - 3.74/t

# Conversions, Equivalents and Physical Data

**Table 9. Conversion Units**

MULTIPLY	BY	TO OBTAIN
<b>Volume</b>		
cm <sup>3</sup>	0.06103	In <sup>3</sup>
Ft <sup>3</sup>	7.4805	Gal. (US)
Ft <sup>3</sup>	28.316	L
Ft <sup>3</sup>	1728	In <sup>3</sup>
Gal. (US)	0.1337	Ft <sup>3</sup>
Gal. (US)	3.785	L
Gal. (US)	231	In <sup>3</sup>
L	1.057	Quarts (US)
L	2.113	Pints (US)
<b>Miscellaneous</b>		
BTU	0.252	Calories
Decitherm	10,000	BTU
kg	2.205	lbs
kWh	3412	BTU
Oz	28.35	g
Lbs	0.4536	kg
Lbs	453.5924	g
Lbs	21,591	LPG BTU
Therm	100,000	BTU
API Bbbls	42	Gal. (US)
Gal. of Propane	26.9	KWH
HP	746	KWH
HP (Steam)	42,418	BTU
<b>Pressure</b>		
g/cm <sup>2</sup>	0.0142	Psi
in. of mercury	0.4912	Psi
in. of mercury	1.133	ft. of water
in. of water	0.0361	Psi
in. of water	0.0735	in. of mercury
in. of water	0.5781	oz/in <sup>2</sup>
in. of water	5.204	lbs/ft
kPa	100	Bar
kg/cm <sup>2</sup>	14.22	Psi
kg/m <sup>2</sup>	0.2048	lbs/ft <sup>2</sup>
Psi	0.06804	Atmospheres
Psi	0.07031	kg/cm <sup>2</sup>
Psi	0.145	KPa
Psi	2.036	in. of mercury
Psi	2.307	ft. of water
Psi	14.5	Bar
Psi	27.67	in. of water
<b>Length</b>		
cm	0.3937	in.
ft.	0.3048	m
ft.	30.48	cm
ft.	304.8	mm
in.	2.540	cm
In.	25.40	mm
km	0.6214	mi
m	1.094	Yards
m	3.281	ft
m	39.37	in.
mi (nautical)	1853	m
mi (statute)	1609	m
Yards	0.9144	m
Yards	91.44	cm

**Table 10. Other Useful Conversions**

TO CONVERT FROM	TO	MULTIPLY BY
ft <sup>3</sup> of methane	BTU	1000 (approximate)
ft <sup>3</sup> of water	lbs. of water	62.4
Degrees	Radians	0.01745
Gal.	lbs. of water	8.336
g	oz.	0.0352
hp (mechanical)	ft. lbs./min	33,000
hp (electrical)	Watts	746
kg	lbs.	2.205
kg/m <sup>3</sup>	lbs/ft <sup>3</sup>	0.06243
kW	hp	1.341
Lbs	kg	0.4536
lbs. of Air (14.7 psia and 60°F)	ft <sup>3</sup> of air	13.1
lbs/ft <sup>3</sup>	kg/m <sup>3</sup>	16.0184
lbs/hr (gas)	SCFH	13.1 ÷ Specific Gravity
lbs/hr (water)	Gal./min	0.002
lbs/sec (gas)	SCFH	46,160 ÷ Specific Gravity
Radians	Degrees	57.3
SCFH Air	SCFH Propane	0.81
SCFH Air	SCFH Butane	0.71
SCFH Air	SCFH 0.6 Natural Gas	1.29
SCFH	m <sup>3</sup> /hr	0.028317

**Table 11. Converting Volumes of Gas**

CFH TO CFH OR CFM TO CFM		
Multiply Flow of	By	To Obtain Flow of
Air	0.707	Butane
	1.290	Natural Gas
	0.808	Propane
Butane	1.414	Air
	1.826	Natural Gas
	1.140	Propane
Natural Gas	0.775	Air
	0.547	Butane
	0.625	Propane
Propane	1.237	Air
	0.874	Butane
	1.598	Natural Gas

# Conversions, Equivalents and Physical Data

**Table 12. Fractional In. to mm**

IN.	0	1/16	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	11/16	3/4	13/16	7/8	15/16
	mm															
0	0.0	1.6	3.2	4.8	6.4	7.9	9.5	11.1	12.7	14.3	15.9	17.5	19.1	20.6	22.2	23.8
1	25.4	27.0	28.6	30.2	31.8	33.3	34.9	36.5	38.1	39.7	41.3	42.9	44.5	46.0	47.6	49.2
2	50.8	52.4	54.0	55.6	57.2	58.7	60.3	61.9	63.5	65.1	66.7	68.3	69.9	71.4	73.0	74.6
3	76.2	77.8	79.4	81.0	82.6	84.1	85.7	87.3	88.9	90.5	92.1	93.7	95.3	96.8	98.4	100.0
4	101.6	103.2	104.8	106.4	108.0	109.5	111.1	112.7	114.3	115.9	117.5	119.1	120.7	122.2	123.8	125.4
5	127.0	128.6	130.2	131.8	133.4	134.9	136.5	138.1	139.7	141.3	142.9	144.5	146.1	147.6	149.2	150.8
6	152.4	154.0	155.6	157.2	158.8	160.3	161.9	163.5	165.1	166.7	168.3	169.9	171.5	173.0	174.6	176.2
7	177.8	179.4	181.0	182.6	184.2	185.7	187.3	188.9	190.5	192.1	193.7	195.3	196.9	198.4	200.0	201.6
8	203.2	204.8	206.4	208.0	209.6	211.1	212.7	214.3	215.9	217.5	219.1	220.7	222.3	223.8	225.4	227.0
9	228.6	230.2	231.8	233.4	235.0	236.5	238.1	239.7	241.3	242.9	244.5	246.1	247.7	249.2	250.8	252.4
10	254.0	255.6	257.2	258.8	260.4	261.9	263.5	265.1	266.7	268.3	269.9	271.5	273.1	274.6	276.2	277.8

1 in. = 25.4 mm  
 NOTE: To use this table, see the shaded example.  
 2-1/2 in. (2 from the left column plus 1/2 from the top row) = 63.5 mm

**Table 13. Length Equivalents**

MULTIPLY NUMBER OF	TO OBTAIN						
	M	IN.	FT.	MM	MI.	KM	
m	1	39.37	3.2808	1000	0.0006214	0.001	
In.	0.0254	1	0.0833	25.4	0.00001578	0.0000254	
Ft.	0.3048	12	1	304.8	0.0001894	0.0003048	
mm	0.001	0.03937	0.0032808	1	0.000006214	0.000001	
Mi.	1609.35	63.360	5.280	1,609,350	1	1.60935	
Km	1000	39.370	3280.83	1,000,000	0.62137	1	

1 m = 100 cm = 1000 mm = 0.001 km = 1,000,000 micrometers

**Table 14. Whole In.-mm Equivalents**

IN.	0	1	2	3	4	5	6	7	8	9
	mm									
0	0.00	25.4	50.8	76.2	101.6	127.0	152.4	177.8	203.2	228.6
10	254.0	279.4	304.8	330.2	355.6	381.0	406.4	431.8	457.2	482.6
20	508.0	533.4	558.8	584.2	609.6	635.0	660.4	685.8	711.2	736.6
30	762.0	787.4	812.8	838.2	863.6	889.0	914.4	939.8	965.2	990.6
40	1016.0	1041.4	1066.8	1092.2	1117.6	1143.0	1168.4	1193.8	1219.2	1244.6
50	1270.0	1295.4	1320.8	1346.2	1371.6	1397.0	1422.4	1447.8	1473.2	1498.6
60	1524.0	1549.4	1574.8	1600.2	1625.6	1651.0	1676.4	1701.8	1727.2	1752.6
70	1778.0	1803.4	1828.8	1854.2	1879.6	1905.0	1930.4	1955.8	1981.2	2006.6
80	2032.0	2057.4	2082.8	2108.2	2133.6	2159.0	2184.4	2209.8	2235.2	2260.6
90	2286.0	2311.4	2336.8	2362.2	2387.6	2413.0	2438.4	2463.8	2489.2	2514.6
100	2540.0	2565.4	2590.8	2616.2	2641.6	2667.0	2692.4	2717.8	2743.2	2768.6

Note: All values in this table are exact, based on the relation 1 in. = 25.4 mm.  
 To use this table, see the shaded example.  
 25 in. (20 from the left column plus five from the top row) = 635 mm

**Table 15. Metric Prefixes and Symbols**

MULTIPLICATION FACTOR	PREFIX	SYMBOL
1,000,000,000,000,000,000 = 10 <sup>18</sup>	exa	E
1,000,000,000,000,000 = 10 <sup>15</sup>	peta	P
1,000,000,000,000 = 10 <sup>12</sup>	tera	T
1,000,000,000 = 10 <sup>9</sup>	giga	G
1,000,000 = 10 <sup>6</sup>	mega	M
1,000 = 10 <sup>3</sup>	kilo	k
100 = 10 <sup>2</sup>	hecto	h
10 = 10 <sup>1</sup>	deka	da
0.1 = 10 <sup>-1</sup>	deci	d
0.01 = 10 <sup>-2</sup>	centi	c
0.001 = 10 <sup>-3</sup>	milli	m
0.000 01 = 10 <sup>-6</sup>	micro	μ
0.000 000 001 = 10 <sup>-9</sup>	nano	n
0.000 000 000 001 = 10 <sup>-12</sup>	pico	p
0.000 000 000 000 001 = 10 <sup>-15</sup>	femto	f
0.000 000 000 000 000 001 = 10 <sup>-18</sup>	atto	a

**Table 16. Greek Alphabet**

CAPS	LOWER CASE	GREEK NAME	CAPS	LOWER CASE	GREEK NAME	CAPS	LOWER CASE	GREEK NAME
A	α	Alpha	I	ι	Iota	ρ	ρ	Rho
B	β	Beta	K	κ	Kappa	σ	σ	Sigma
Γ	γ	Gamma	Λ	λ	Lambda	τ	τ	Tau
Δ	δ	Delta	Μ	μ	Mu	Υ	υ	Upsilon
E	ε	Epsilon	N	ν	Nu	Φ	φ	Phi
Z	ζ	Zeta	Ξ	ξ	Xi	Χ	χ	Chi
H	η	Eta	Ο	ο	Omicron	Ψ	ψ	Psi
Θ	θ	Theta	Π	π	Pi	Ω	ω	Omega





# Conversions, Equivalents and Physical Data

**Table 17. Length Equivalents - Fractional and Decimal In. to mm**

IN.		mm	IN.		mm	IN.		mm	IN.		mm
Fractions	Decimals		Fractions	Decimals		Fractions	Decimals		Fractions	Decimals	
	0.00394	0.1		0.23	5.842	1/2	0.50	12.7		0.77	19.558
	0.00787	0.2	15/64	0.234375	5.9531		0.51	12.954		0.78	19.812
	0.01	0.254		0.23622	6.0		0.51181	13.0	25/32	0.78125	19.8438
	0.01181	0.3		0.24	6.096	33/64	0.515625	13.0969		0.78740	20.0
1/64	0.015625	0.3969	1/4	0.25	6.35		0.52	13.208		0.79	20.066
	0.01575	0.4		0.26	6.604		0.53	13.462	51/64	0.796875	20.2406
	0.01969	0.5	17/64	0.265625	6.7469	17/32	0.53125	13.4938		0.80	20.320
	0.02	0.508		0.27	6.858		0.54	13.716		0.81	20.574
	0.02362	0.6		0.27559	7.0	35/64	0.546875	13.8906	13/64	0.8125	20.6375
	0.02756	0.7		0.28	7.112		0.55	13.970		0.82	20.828
	0.03	0.762	9/32	0.28125	7.1438		0.55118	14.0		0.82677	21.0
1/32	0.03125	0.7938		0.29	7.366		0.56	14.224	53/64	0.828125	21.0344
	0.0315	0.8	19/64	0.296875	7.5406	9/16	0.5625	14.2875		0.83	21.082
	0.13543	0.9		0.30	7.62		0.57	14.478		0.84	21.336
	0.03937	1.0		0.31	7.874	37/64	0.578125	14.6844	27/32	0.84375	21.4312
	0.04	1.016	5/16	0.3125	7.9375		0.58	14.732		0.85	21.590
3/64	0.046875	1.1906		0.31496	8.0		0.59	14.986	55/64	0.859375	21.8281
	0.05	1.27		0.32	8.128		0.5905	15.0		0.86	21.844
	0.06	1.524	21/64	0.328125	8.3344	19/32	0.59375	15.0812		0.86614	22.0
1/16	0.0625	1.5875		0.33	8.382		0.60	15.24		0.87	22.098
	0.07	1.778		0.34	8.636	39/64	0.609375	15.4781	7/8	0.875	22.225
5/64	0.078125	1.9844	11/32	0.34375	8.7312		0.61	15.494		0.88	22.352
	0.07874	2.0		0.35	8.89		0.62	15.748		0.89	22.606
	0.08	2.032		0.35433	9.0	5/8	0.625	15.875	57/64	0.890625	22.6219
	0.09	2.286	23/64	0.359375	9.1281		0.62992	16.0		0.90	22.860
3/32	0.09375	2.3812		0.36	9.144		0.63	16.002		0.90551	23.0
	0.1	2.54		0.37	9.398		0.64	16.256	29/32	0.90625	23.0188
7/64	0.109375	2.7781	3/8	0.375	9.525	41/64	0.640625	16.2719		0.91	23.114
	0.11	2.794		0.38	9.652		0.65	16.510		0.92	23.368
	0.11811	3.0		0.39	9.906	21/32	0.65625	16.6688	59/64	0.921875	23.1456
	0.12	3.048	25/64	0.390625	9.9219		0.66	16.764		0.93	23.622
1/8	0.125	3.175		0.39370	10.0		0.66929	17.0	15/16	0.9375	23.8125
	0.13	3.302		0.40	10.16		0.67	17.018		0.94	23.876
	0.14	3.556	13/32	0.40625	10.3188	43/64	0.671875	17.0656		0.94488	24.0
9/64	0.140625	3.5719		0.41	10.414		0.68	17.272		0.95	24.130
	0.15	3.810		0.42	10.668	11/16	0.6875	17.4625	61/64	0.953125	24.2094
5/32	0.15625	3.9688	27/64	0.421875	10.7156		0.69	17.526		0.96	24.384
	0.15748	4.0		0.43	10.922		0.70	17.78	31/32	0.96875	24.6062
	0.16	4.064		0.43307	11.0	45/64	0.703125	17.8594		0.97	24.638
	0.17	4.318	7/16	0.4375	11.1125		0.70866	18.0		0.98	24.892
11/64	0.171875	4.3656		0.44	11.176		0.71	18.034		0.98425	25.0
	0.18	4.572		0.45	11.430	23/32	0.71875	18.2562	63/64	0.984375	25.0031
3/16	0.1875	4.7625	29/64	0.453125	11.5094		0.72	18.288		0.99	25.146
	0.19	4.826		0.46	11.684		0.73	18.542	1	1.00000	25.4000
	0.19685	5.0	15/32	0.46875	11.9062	47/64	0.734375	18.6531			
	0.2	5.08		0.47	11.938		0.74	18.796			
13/64	0.203125	5.1594		0.47244	12.0		0.74803	19.0			
	0.21	5.334		0.48	12.192	3/4	0.75	19.050			
7/32	0.21875	5.5562	31/64	0.484375	12.3031		0.76	19.304			
	0.22	5.588		0.49	12.446	49/64	0.765625	19.4469			

Note: Round off decimal points to provide no more than the desired degree of accuracy.

# Conversions, Equivalents and Physical Data

**Table 18. Temperature Conversions**

°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F
-273.16	-460	-796	-90.00	-130	-202.0	-17.8	0	32.0	21.1	70	158.0
-267.78	-450	-778	-84.44	-120	-184.0	-16.7	2	35.6	22.2	72	161.6
-262.22	-440	-760	-78.89	-110	-166.0	-15.6	4	39.2	23.3	74	165.2
-256.67	-430	-742	-73.33	-100	-148.0	-14.4	6	42.8	24.4	76	168.8
-251.11	-420	-724	-70.56	-95	-139.0	-13.3	8	46.4	25.6	78	172.4
-245.56	-410	-706	-67.78	-90	-130.0	-12.2	10	50.0	26.7	80	176.0
-240.00	-400	-688	-65.00	-85	-121.0	-11.1	12	53.6	27.8	82	179.6
-234.44	-390	-670	-62.22	-80	-112.0	-10.0	14	57.2	28.9	84	183.2
-228.89	-380	-652	-59.45	-75	-103.0	-8.89	16	60.8	30.0	86	186.8
-223.33	-370	-634	-56.67	-70	-94.0	-7.78	18	64.4	31.1	88	190.4
-217.78	-360	-616	-53.89	-65	-85	-6.67	20	68.0	32.2	90	194.0
-212.22	-350	-598	-51.11	-60	-76.0	-5.56	22	71.6	33.3	92	197.6
-206.67	-340	-580	-48.34	-55	-67.0	-4.44	24	75.2	34.4	94	201.2
-201.11	-330	-562	-45.56	-50	-58.0	-3.33	26	78.8	35.6	96	204.8
-195.56	-320	-544	-42.78	-45	-49.0	-2.22	28	82.4	36.7	98	208.4
-190.00	-310	-526	-40.00	-40	-40.0	-1.11	30	86.0	37.8	100	212.0
-184.44	-300	-508	-38.89	-38	-36.4	0	32	89.6	43.3	110	230.0
-178.89	-290	-490	-37.78	-36	-32.8	1.11	34	93.2	48.9	120	248.0
-173.33	-280	-472	-36.67	-34	-29.2	2.22	36	96.8	54.4	130	266.0
-169.53	-273	-459.4	-35.56	-32	-25.6	3.33	38	100.4	60.0	140	284.0
-168.89	-272	-457.6	-34.44	-30	-22.0	4.44	40	104.0	65.6	150	302.0
-167.78	-270	-454.0	-33.33	-28	-18.4	5.56	42	107.6	71.1	160	320.0
-162.22	-260	-436.0	-32.22	-26	-14.8	6.67	44	111.2	76.7	170	338.0
-156.67	-250	-418.0	-31.11	-24	-11.2	7.78	46	114.8	82.2	180	356.0
-151.11	-240	-400.0	-30.00	-22	-7.6	8.89	48	118.4	87.8	190	374.0
-145.56	-230	-382.0	-28.89	-20	-4.0	10.0	50	122.0	93.3	200	392.0
-140.00	-220	-364.0	-27.78	-18	-0.4	11.1	52	125.6	98.9	210	410.0
-134.44	-210	-356.0	-26.67	-16	3.2	12.2	54	129.2	104.4	220	428.0
-128.89	-200	-328.0	-25.56	-14	6.8	13.3	56	132.8	110.0	230	446.0
-123.33	-190	-310.0	-24.44	-12	10.4	14.4	58	136.4	115.6	240	464.0
-117.78	-180	-292.0	-23.33	-10	14.0	15.6	60	140.0	121.1	250	482.0
-112.22	-170	-274.0	-22.22	-8	17.6	16.7	62	143.6	126.7	260	500.0
-106.67	-160	-256.0	-21.11	-6	21.2	17.8	64	147.2	132.2	270	518.0
-101.11	-150	-238.0	-20.00	-4	24.8	18.9	66	150.8	137.8	280	536.0
-95.56	-140	-220.0	-18.89	-2	28.4	20.0	68	154.4	143.3	290	665.0

- continued -



# Conversions, Equivalents and Physical Data

**Table 18. Temperature Conversions (continued)**

°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F
21.1	70	158.0	204.4	400	752.0	454.0	850	1562.0
22.2	72	161.6	210.0	410	770.0	460.0	860	1580.0
23.3	74	165.2	215.6	420	788.0	465.6	870	1598.0
24.4	76	168.8	221.1	430	806.0	471.1	880	1616.0
25.6	78	172.4	226.7	440	824.0	476.7	890	1634.0
26.7	80	176.0	232.2	450	842.0	482.2	900	1652.0
27.8	82	179.6	237.8	460	860.0	487.8	910	1670.0
28.9	84	183.2	243.3	470	878.0	493.3	920	1688.0
30.0	86	186.8	248.9	480	896.0	498.9	930	1706.0
31.1	88	190.4	254.4	490	914.0	504.4	940	1724.0
32.2	90	194.0	260.0	500	932.0	510.0	950	1742.0
33.3	92	197.6	265.6	510	950.0	515.6	960	1760.0
34.4	94	201.2	271.1	520	968.0	521.1	970	1778.0
35.6	96	204.8	276.7	530	986.0	526.7	980	1796.0
36.7	98	208.4	282.2	540	1004.0	532.2	990	1814.0
37.8	100	212.0	287.8	550	1022.0	537.8	1000	1832.0
43.3	110	230.0	293.3	560	1040.0	543.3	1010	1850.0
48.9	120	248.0	298.9	570	1058.0	548.9	1020	1868.0
54.4	130	266.0	304.4	580	1076.0	554.4	1030	1886.0
60.0	140	284.0	310.0	590	1094.0	560.0	1040	1904.0
65.6	150	302.0	315.6	600	1112.0	565.6	1050	1922.0
71.1	160	320.0	321.1	610	1130.0	571.1	1060	1940.0
76.7	170	338.0	326.7	620	1148.0	576.7	1070	1958.0
82.2	180	356.0	332.2	630	1166.0	582.2	1080	1976.0
87.8	190	374.0	337.8	640	1184.0	587.8	1090	1994.0
93.3	200	392.0	343.3	650	1202.0	593.3	1100	2012.0
98.9	210	410.0	348.9	660	1220.0	598.9	1110	2030.0
104.4	220	428.0	354.4	670	1238.0	604.4	1120	2048.0
110.0	230	446.0	360.0	680	1256.0	610.0	1130	2066.0
115.6	240	464.0	365.6	690	1274.0	615.6	1140	2084.0
121.1	250	482.0	371.1	700	1292.0	621.1	1150	2102.0
126.7	260	500.0	376.7	710	1310.0	626.7	1160	2120.0
132.2	270	518.0	382.2	720	1328.0	632.2	1170	2138.0
137.8	280	536.0	287.8	730	1346.0	637.8	1180	2156.0
143.3	290	665.0	393.3	740	1364.0	643.3	1190	2174.0

- continued -

# Conversions, Equivalents and Physical Data

**Table 18. Temperature Conversions (continued)**

°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F	°C	TEMP. IN °C OR °F TO BE CONVERTED	°F
148.9	300	572.0	315.6	600	1112.0	482.2	900	1652.0	648.9	1200	2192.0
154.4	310	590.0	321.1	610	1130.0	487.8	910	1670.0	654.4	1210	2210.0
160.0	320	608.0	326.7	620	1148.0	493.3	920	1688.0	660.0	1220	2228.0
165.6	330	626.0	332.2	630	1166.0	498.9	930	1706.0	665.6	1230	2246.0
171.1	340	644.0	337.8	640	1184.0	504.4	940	1724.0	671.1	1240	2264.0
176.7	350	662.0	343.3	650	1202.0	510.0	950	1742.0	676.7	1250	2282.0
182.2	360	680.0	348.9	660	1220.0	515.6	960	1760.0	682.2	1260	2300.0
187.8	370	698.0	354.4	670	1238.0	521.1	970	1778.0	687.8	1270	2318.0
189.9	380	716.0	360.0	680	1256.0	526.7	980	1796.0	693.3	1280	2336.0
193.3	390	734.0	365.6	690	1274.0	532.2	990	1814.0	698.9	1290	2354.0
204.4	400	752.0	371.1	700	1292.0	537.8	1000	1832.0	704.4	1300	2372.0
210.0	410	770.0	376.7	710	1310.0	543.3	1010	1850.0	710.0	1310	2390.0
215.6	420	788.0	382.2	720	1328.0	548.9	1020	1868.0	715.6	1320	2408.0
221.1	430	806.0	387.8	730	1346.0	554.4	1030	1886.0	721.1	1330	2426.0
226.7	440	824.0	393.3	740	1364.0	560.0	1040	1904.0	726.7	1340	2444.0
232.2	450	842.0	398.9	750	1382.0	565.6	1050	1922.0	732.2	1350	2462.0
237.8	460	860.0	404.4	760	1400.0	571.1	1060	1940.0	737.8	1360	2480.0
243.3	470	878.0	410.0	770	1418.0	576.7	1070	1958.0	743.3	1370	2498.0
248.9	480	896.0	415.6	780	1436.0	582.2	1080	1976.0	748.9	1380	2516.0
254.4	490	914.0	421.1	790	1454.0	587.8	1090	1994.0	754.4	1390	2534.0
260.0	500	932.0	426.7	800	1472.0	593.3	1100	2012.0	760.0	1400	2552.0
265.6	510	950.0	432.2	810	1490.0	598.9	1110	2030.0	765.6	1410	2570.0
271.1	520	968.0	437.8	820	1508.0	604.4	1120	2048.0	771.1	1420	2588.0
276.7	530	986.0	443.3	830	1526.0	610.0	1130	2066.0	776.7	1430	2606.0
282.2	540	1004.0	448.9	840	1544.0	615.6	1140	2084.0	782.2	1440	2624.0
287.8	550	1022.0	454.4	850	1562.0	621.1	1150	2102.0	787.8	1450	2642.0
293.3	560	1040.0	460.0	860	1580.0	626.7	1160	2120.0	793.3	1460	2660.0
298.9	570	1058.0	465.6	870	1598.0	632.2	1170	2138.0	798.9	1470	2678.0
304.4	580	1076.0	471.1	880	1616.0	637.8	1180	2156.0	804.4	1480	2696.0
310.0	590	1094.0	476.7	890	1634.0	643.3	1190	2174.0	810.0	1490	2714.0

# Conversions, Equivalents and Physical Data

**Table 19. A.P.I. and Baumé Gravity Tables and Weight Factors**

A.P.I. Gravity	Baumé Gravity	Specific Gravity	Lbs/U.S. Gal.	U.S. Gal/ Lb	A.P.I. Gravity	Baumé Gravity	Specific Gravity	Lbs/U.S. Gal.	U.S. Gal/ Lb	A.P.I. Gravity	Baumé Gravity	Specific Gravity	Lbs/U.S. Gal.	U.S. Gal/ Lb	A.P.I. Gravity	Baumé Gravity	Specific Gravity	Lbs/U.S. Gal.	U.S. Gal/ Lb	
0	10.247	1.0760	8.962	0.1116	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----
1	9.223	1.0679	8.895	0.1124	31	30.78	0.9808	7.251	0.1379	61	60.46	0.7351	6.119	0.1634	81	80.25	0.6659	5.542	0.1804	
2	8.198	1.0599	8.828	0.1133	32	31.77	0.8654	7.206	0.1388	62	61.45	0.7313	6.087	0.1643	82	81.24	0.6628	5.516	0.1813	
3	7.173	1.0520	8.762	0.1141	33	32.76	0.8602	7.163	0.1396	63	62.44	0.7275	6.056	0.1651	83	82.23	0.6597	5.491	0.1821	
4	6.148	1.0443	8.698	0.1150	34	33.75	0.8550	7.119	0.1405	64	63.43	0.7238	6.025	0.1660	84	83.22	0.6566	5.465	0.1830	
5	5.124	1.0366	8.634	0.1158	35	34.73	0.8498	7.075	0.1413	65	64.42	0.7201	6.994	0.1668	85	84.20	0.6536	5.440	0.1838	
6	4.099	1.0291	8.571	0.1167	36	35.72	0.8448	7.034	0.1422	66	65.41	0.7165	5.964	0.1677	86	85.19	0.6506	5.415	0.1847	
7	3.074	1.0217	8.509	0.1175	37	36.71	0.8398	6.993	0.1430	67	66.40	0.7128	5.934	0.1685	87	86.18	0.6476	5.390	0.1855	
8	2.049	1.0143	8.448	0.1184	38	37.70	0.8348	6.951	0.1439	68	67.39	0.7093	5.904	0.1694	88	87.17	0.6446	5.365	0.1864	
9	1.025	1.0071	8.388	0.1192	39	38.69	0.8299	6.910	0.1447	69	68.37	0.7057	5.874	0.1702	89	88.16	0.6417	5.341	0.1872	
10	10.00	1.0000	8.328	0.1201	40	39.68	0.8251	6.870	0.1456	70	69.36	0.7022	5.845	0.1711	90	89.15	0.6388	5.316	0.1881	
11	10.99	0.9930	8.270	0.1209	41	40.67	0.8203	6.830	0.1464	71	70.35	0.6988	5.817	0.1719	91	90.14	0.6360	5.293	0.1889	
12	11.98	0.9861	8.212	0.1218	42	41.66	0.8155	6.790	0.1473	72	71.34	0.6953	5.788	0.1728	92	91.13	0.6331	5.269	0.1898	
13	12.97	0.9792	8.155	0.1226	43	42.65	0.8109	6.752	0.1481	73	72.33	0.6919	5.759	0.1736	93	92.12	0.6303	5.246	0.1906	
14	13.96	0.9725	8.099	0.1235	44	43.64	0.8063	6.713	0.1490	74	73.32	0.6886	5.731	0.1745	94	93.11	0.6275	5.222	0.1915	
15	14.95	0.9659	8.044	0.1243	45	44.63	0.8017	6.675	0.1498	75	74.31	0.6852	5.703	0.1753	95	94.10	0.6247	5.199	0.1924	
16	15.94	0.9593	7.989	0.1252	46	45.62	0.7972	6.637	0.1507	76	75.30	0.6819	5.676	0.1762	96	95.09	0.6220	5.176	0.1932	
17	16.93	0.9529	7.935	0.1260	47	50.61	0.7927	6.600	0.1515	77	76.29	0.6787	5.649	0.1770	97	96.08	0.6193	5.154	0.1940	
18	17.92	0.9465	7.882	0.1269	48	50.60	0.7883	6.563	0.1524	78	77.28	0.6754	5.622	0.1779	98	97.07	0.6166	5.131	0.1949	
19	18.90	0.9402	7.930	0.1277	49	50.59	0.7839	6.526	0.1532	79	78.27	0.6722	5.595	0.1787	99	98.06	0.6139	5.109	0.1957	
20	19.89	0.9340	7.778	0.1286	50	50.58	0.7796	6.490	0.1541	80	79.26	0.6690	5.568	0.1796	100	99.05	0.6112	5.086	0.1966	
21	20.88	0.9279	7.727	0.1294	51	50.57	0.7753	6.455	0.1549	The relation of degrees Baume or A.P.I. to Specific Gravity is expressed by these formulas: For liquids lighter than water: $D = \frac{140}{130 + \text{Degrees Baume}}$ For liquids heavier than water: $D = \frac{145}{145 - \text{Degrees Baume}}$										
22	21.87	0.9218	7.676	0.1303	52	51.55	0.7711	6.420	0.1558	Degrees Baume = $\frac{140}{130 + \text{Degrees Baume}}$ Degrees A.P.I. = $\frac{141}{5} - 131.5 G = \frac{141.5}{131.5 + \text{Degrees A.P.I.}}$										
23	22.86	0.9159	7.627	0.1311	53	52.54	0.7669	6.385	0.1566	G = Specific Gravity = ratio of weight of a given volume of oil at 60°F to the weight of the same volume of water at 60°F.										
24	23.85	0.9100	7.578	0.1320	54	53.53	0.7628	6.350	0.1575	The above tables are based on the weight of 1 gal. (U.S.) of oil with a volume of 231 in <sup>3</sup> at 60°F in air at 760 mm pressure and 50% relative humidity. Assumed weight of 1 gal. of water at 60°F in air is 8.32828 lbs.										
25	24.84	0.9042	7.529	0.1328	55	54.52	0.7587	6.316	0.1583	To determine the resulting gravity by mixing oils of different gravities: $D = \frac{md_1 + nd_2}{m + n}$ D = Density or Specific Gravity of mixture m = Proportion of oil of d <sub>1</sub> density n = Proportion of oil of d <sub>2</sub> density d <sub>1</sub> = Specific gravity of m oil d <sub>2</sub> = Specific gravity of n oil										
26	25.83	0.8984	7.481	0.1337	56	55.51	0.7547	6.283	0.1592											
27	26.82	0.8927	7.434	0.1345	57	56.50	0.7507	6.249	0.1600											
28	27.81	0.8871	7.387	0.1354	58	57.49	0.7467	6.216	0.1609											
29	28.80	0.8816	7.341	0.1362	59	58.48	0.7428	6.184	0.1617											
30	29.79	0.8762	7.296	0.1371	60	59.47	0.7389	6.151	0.1626											

# Conversions, Equivalents and Physical Data

Table 20. Characteristics of the Elements

ELEMENT	SYMBOL	ATOMIC NUMBER	MASS NUMBER <sup>(1)</sup>	MELTING POINT (°C)	BOILING POINT (°C)	ELEMENT	SYMBOL	ATOMIC NUMBER	MASS NUMBER <sup>(1)</sup>	MELTING POINT (°C)	BOILING POINT (°C)
Actinium	Ac	89	(227)	1600†		Neon	Ne	10	20	-248.67	-245.9
Aluminum	Al	13	27	659.7	2057	Neptunium	Np	93	(237)		
Americum	Am	95	(243)			Nickel	Ni	28	58	1455	2900
Antimony (Stibium)	Sb	51	121	630.5	1380	Niobium	Nb	41	93	2500±50	3700
Argon	Ar	18	40	-189.2	-185.7	Nitrogen	N	7	14	-209.86	-195.8
Arsenic	As	33	75	sublimes at 615	sublimes at 615	Nobelium	No	102	(253)		
Astatine	At	85	(210)			Osmium	Os	76	192	2700	>5300
Barium	Ba	56	138	850	1140	Oxygen	O	8	16	-218.4	-182.86
Berkelium	Bk	97	(247)			Palladium	Pd	46	106	1549.4	2000
Beryllium	Be	4	9	1278±5	2970	Phosphorus	P	15	31		
Bismuth	Bi	83	209	271.3	1560±5	Platinum	Pt	78	195	1773.5	4300
Boron	B	5	11	2300	2550	Plutonium	Pu	94	(242)		
Bromine	Br	35	79	-7.2	58.78	Polonium	Po	84	(209)		
Cadmium	Cd	48	114	320.9	767±2	Potassium	K	19	39	53.3	760
Calcium	Ca	20	40	842±8	1240	Praseodymium	Pr	59	141	940	
Californium	Cf	98	(249)			Promethium	Pm	61	(145)		
Carbon	C	6	12	>3550	4200	Protactinium	Pa	91	(231)		
Cerium	Ce	58	140	804	1400	Radium	Ra	88	(226)	700	
Cesium	Cs	55	133	28.5	670	Radon	Rn	86	(222)	-71	1140
Chlorine	Cl	17	35	-103±5	-34.6	Rhenium	Re	75	187	3167±60	-61.8
Chromium	Cr	24	52	1890	2480	Rhodium	Rh	45	103	1966±3	>2500
Cobalt	Co	27	59	1495	2900	Rubidium	Rb	37	85	38.5	700
Copper	Cu	29	63	1083	2336	Ruthenium	Ru	44	102	2450	2700
Curium	Cm	96	(248)			Samarium	Sm	62	152	>1300	
Dysprosium	Dy	66	164			Scandium	Sc	21	45	1200	2400
Einsteinium	Es	99	(254)			Selenium	Se	34	80	217	688
Erbium	Er	68	166			Silicon	Si	14	28	1420	2355
Europium	Eu	63	153	1150±50		Silver	Ag	47	107	960.8	1950
Fermium	Fm	100	(252)			Sodium	Na	11	23	97.5	880
Fluorine	F	9	19	-223	-188	Strontium	Sr	38	88	800	1150
Francium	Fr	87	(223)			Sulfur	S	16	32		
Gadolinium	Gd	64	158			Tantalum	Ta	73	180	2996±50	c.4100
Gallium	Ga	31	69	29.78	1983	Technetium	Tc	43	(99)		
Germanium	Ge	32	74	958.5	2700	Tellurium	Te	52	130	452	1390
Gold	Au	79	197	1063	2600	Terbium	Tb	65	159	327±5	
Hafnium	Hf	72	180	1700 <sup>(2)</sup>	>3200	Thallium	Tl	81	205	302	1457±10
Helium	He	2	4	-272	-268.9	Thorium	Th	90	232	1845	4500
Holmium	Ho	67	165			Thulium	Tm	69	169		
Hydrogen	H	1	1	-259.14	-252.8	Tin	Sn	50	120	231.89	2270
Indium	In	49	115	156.4	2000±10	Titanium	Ti	22	48	1800	>3000
Iodine	I	53	127	113.7	184.35	Tungsten (Wolfram)	W	74	184	3370	5900
Iridium	Ir	77	193	2454	>4800	Uranium	U	92	238	c.1133	
Iron	Fe	26	56	1535	3000	Vanadium	V	23	51	1710	3000
Krypton	Kr	36	84	-156.6	-152.9	Xenon	Xe	54	132	-112	-107.1
Lanthanum	La	57	139	826		Ytterbium	Yb	70	174	1800	
Lawrencium	Lw	103	(257)			Yttrium	Y	39	89	1490	2500
Lead	Pb	82	208	327.43	1620	Zinc	Zn	30	64	419.47	907
Lithium	Li	3	7	186	1336±5	Zirconium	Zr	40	90	1857	>2900
Lutetium	Lu	71	175								
Magnesium	Mg	12	24	651	1107						
Manganese	Mn	25	55	1260	1900						
Mendelevium	Mv	101	(256)								
Mercury	Hg	80	202	-38.87	356.58						
Molybdenum	Mo	42	98	2620±10	4800						
Neodymium	Nd	60	142	840							

1. Mass number shown is that of stable isotope most common in nature. Mass numbers shown in parentheses designate the isotope with the longest half-life (slowest rate of radioactive decay) for those elements having an unstable isotope.

2. Calculated  
> Greater than

# Conversions, Equivalents and Physical Data

**Table 21. Recommended Standard Specifications for Valve Materials Pressure-Containing Castings**

1	Carbon Steel ASTM A216 Grade WCC  Temperature Range = -20 to 800°F Composition (Percent)  C 0.25 maximum Mn 1.20 maximum P 0.04 maximum S 0.04 maximum Si 0.60 maximum	2	Carbon Steel ASTM A216 Grade WCB  Temperature Range = -20 to 1000°F Composition (Percent)  C 0.30 maximum Mn 1.00 maximum P 0.05 maximum S 0.06 maximum Si 0.60 maximum	11	Type 304 Stainless Steel ASTM A351 Grade CF-8  Temperature Range = -425 to 1500°F Composition (Percent)  C 0.08 maximum Mn 1.50 maximum Si 2.00 maximum S 0.04 maximum P 0.04 maximum Cr 18.00 to 21.00 Ni 8.00 to 11.00	12	Type 316 Stainless Steel ASTM A351 Grade CF-8M  Temperature Range = -425 to 1500°F Composition (Percent)  C 0.08 maximum Mn 1.50 maximum Si 2.00 maximum P 0.04 maximum S 0.04 maximum Cr 18.00 to 21.00 Ni 9.00 to 12.00 Mo 2.00 to 3.00
3	Carbon Steel ASTM A352 Grade LCC  Temperature Range = -50 to 650°F Composition: same as ASTM A216 Grade WCC	4	Carbon Steel ASTM A352 Grade LCB  Temperature Range = -50 to 650°F Composition: same as ASTM A216 Grade WCB	13	Cast Iron ASTM A126 Class B  Temperature Range = -150 to 450°F Composition (Percent)  P 0.75 maximum S 0.12 maximum	14	Cast Iron ASTM A126 Class C  Temperature Range = -150 to 450°F Composition (Percent)  P 0.75 maximum S 0.12 maximum
5	Chrome Moly Steel ASTM A217 Grade C5  Temperature Range = -20 to 1100°F Composition (Percent)  C 0.20 maximum Mn 0.40 to 0.70 P 0.05 maximum S 0.06 maximum Si 0.75 maximum Cr 4.00 to 6.50 Mo 0.45 to 0.65	6	Carbon Moly Steel ASTM A217 Grade WC1  Temperature Range = -20 to 850°F Composition (Percent)  C 0.25 Mn 0.50 to 0.80 P 0.05 maximum S 0.06 maximum Si 0.60 maximum Mo 0.45 to 0.65	15	Ductile Iron ASTM A395 Type 60-45-15  Temperature Range = -20 to 650°F Composition (Percent)  C 3.00 minimum Si 2.75 maximum P 0.80 maximum	16	Ductile Ni-Resist* Iron ASTM A439 Type D-2B  Temperature Range = -20 to 750°F Composition (Percent)  C 3.00 maximum Si 1.50 to 3.00 Mn 0.70 to 1.25 P 0.08 maximum Ni 18.00 to 22.00 Cr 2.75 to 4.00
7	Chrome Moly Steel ASTM A217 Grade WC6  Temperature Range = -20 to 1000°F Composition (Percent)  C 0.20 maximum Mn 0.50 to 0.80 P 0.05 maximum S 0.06 maximum Si 0.60 maximum Cr 1.00 to 1.50 Mo 0.45 to 0.65	8	Chrome Moly Steel ASTM A217 Grade WC9  Temperature Range = -20 to 1050°F Composition (Percent)  C 0.18 maximum Mn 0.40 to 0.70 P 0.05 maximum Si 0.60 maximum Cr 2.00 to 2.75 Mo 0.90 to 1.20	17	Standard Valve Bronze ASTM B62  Temperature Range = -325 to 450°F Composition (Percent)  Cu 84.00 to 86.00 Sn 4.00 to 6.00 Pb 4.00 to 6.00 Zn 4.00 to 6.00 Ni 1.00 maximum Fe 0.30 maximum P 0.05 maximum	18	Tin Bronze ASTM B143 Alloy 1A  Temperature Range = -325 to 400°F Composition (Percent)  Cu 86.00 to 89.00 Sn 9.00 to 11.00 Pb 0.30 maximum Zn 1.00 to 3.00 Ni 1.00 maximum Fe 0.15 maximum P 0.05 maximum
9	3.5% Nickel Steel ASTM A352 Grade LC3  Temperature Range = -150 to 650°F Composition (Percent)  C 0.15 maximum Mn 0.50 to 0.80 P 0.05 maximum S 0.05 maximum Si 0.60 maximum Ni 3.00 to 4.00	10	Chrome Moly Steel ASTM A217 Grade C12  Temperature Range = -20 to 1100°F Composition (Percent)  C 0.20 maximum Si 1.00 maximum Mn 0.35 to 0.65 Cr 8.00 to 10.00 Mo 0.90 to 1.20 P 0.05 maximum S 0.06 maximum	19	Manganese Bronze ASTM B147 Alloy 8A  Temperature Range = -325 to 350°F Composition (Percent)  Cu 55.00 to 60.00 Sn 1.00 maximum Pb 0.40 maximum Ni 0.50 maximum Fe 0.40 to 2.00 Al 0.50 to 1.50 Mn 1.50 maximum Zn Remainder	20	Aluminum Bronze ASTM B148 Alloy 9C  Temperature Range = -325 to 500°F Composition (Percent)  Cu 83.00 minimum Al 10.00 to 11.50 Fe 3.00 to 5.00 Mn 0.50 Ni 2.50 maximum Minimum total named elements = 99.5

- continued -

# Conversions, Equivalents and Physical Data

**Table 21. Recommended Standard Specifications for Valve Materials Pressure-Containing Castings (continued)**

<p>21 Mondel® Alloy 411 (Weldable Grade)</p> <p>Temperature Range = -325 to 900°F Composition (Percent)</p> <p>Ni 60.00 minimum Cu 26.00 to 33.00 C 0.30 maximum Mn 1.50 maximum Fe 3.50 maximum S 0.015 maximum Si 1.00 to 2.00 Nb 1.00 to 3.00</p>	<p>22 Nickel-Moly Alloy "B" ASTM A494 (Hastelloy® "B" †)</p> <p>Temperature Range = -325 to 700°F Composition (Percent)</p> <p>Cr 1.00 maximum Fe 4.00 to 6.00 C 0.12 maximum Si 1.00 maximum Co 2.50 maximum Mn 1.00 maximum V 0.20 to 0.60 Mo 26.00 to 30.00 P 0.04 maximum S 0.03 maximum Ni Remainder</p>	<p>31 Type 302 Stainless Steel ASTM A276 Type 302</p> <p>Composition (Percent)</p> <p>C 0.15 maximum Mn 2.00 maximum P 0.045 maximum S 0.030 maximum Si 1.00 maximum Cr 17.00 to 19.00 Ni 8.00 to 10.00</p>	<p>32 Type 304 Stainless Steel ASTM A276 Type 304</p> <p>Composition (Percent)</p> <p>C 0.08 maximum Mn 2.00 maximum P 0.045 maximum S 0.030 maximum Si 1.00 maximum Cr 18.00 to 20.00 Ni 8.00 to 12.00</p>
<p>23 Nickel-Moly-Chrome Alloy "C" ASTM A494 (Hastelloy® "C" †)</p> <p>Temperature Range = -325 to 1000°F Composition (Percent)</p> <p>Cr 15.50 to 17.50 Fe 4.50 to 7.50 W 3.75 to 5.25 C 0.12 maximum Si 1.00 maximum Co 2.50 maximum Mn 1.00 maximum V 0.20 to 0.40 Mo 16.00 to 18.00 P 0.04 S 0.03 Ni Remainder</p>	<p>24 Cobalt-based Alloy No.6 Stellite † No. 6</p> <p>Composition (Percent)</p> <p>C 0.90 to 1.40 Mn 1.00 W 3.00 to 6.00 Ni 3.00 Cr 26.00 to 32.00 Mo 1.00 Fe 3.00 Se 0.40 to 2.00 Co Remainder</p>	<p>33 Type 316 Stainless Steel ASTM A276 Type 316</p> <p>Composition (Percent)</p> <p>C 0.08 maximum Mn 2.00 maximum P 0.045 maximum S 0.030 maximum Si 1.00 maximum Cr 16.00 to 18.00 Ni 10.00 to 14.00 Mo 2.00 to 3.00</p>	<p>34 Type 316L Stainless Steel ASTM A276 Type 316L</p> <p>Composition (Percent)</p> <p>C 0.03 maximum Mn 2.00 maximum P 0.045 maximum S 0.030 maximum Si 1.00 maximum Cr 16.00 to 18.00 Ni 10.00 to 14.00 Mo 2.00 to 3.00</p>
<p>25 Aluminum Bar ASTM B211 Alloy 20911-T3</p> <p>Composition (Percent)</p> <p>Si 0.40 maximum Fe 0.70 maximum Cu 5.00 to 6.00 Zn 0.30 maximum Bi 0.20 to 0.60 Pb 0.20 to 0.60 Other Elements 0.15 maximum Al Remainder</p>	<p>26 Yellow Brass Bar ASTM B16 1/2 Hard</p> <p>Composition (Percent)</p> <p>Cu 60.00 to 63.00 Pb 2.50 to 3.70 Fe 0.35 maximum Zn Remainder</p>	<p>35 Type 410 Stainless Steel ASTM A276 Type 410</p> <p>Composition (Percent)</p> <p>C 0.15 maximum Mn 1.00 maximum P 0.040 maximum S 0.030 maximum Si 1.00 maximum Cr 11.50 to 13.50 Al 0.10 to 0.30</p>	<p>36 Type 17-4PH Stainless Steel ASTM A461 Grade 630</p> <p>Composition (Percent)</p> <p>C 0.07 maximum Mn 1.00 maximum Si 1.00 maximum P 0.04 maximum S 0.03 maximum Cr 15.50 to 17.50 Nb 0.05 to 0.45 Cu 3.00 to 5.00 Ni 3.00 to 5.00 Fe Remainder</p>
<p>27 Naval Brass Bar ASTM B21 Allow 464</p> <p>Composition (Percent)</p> <p>Cu 59.00 to 62.00 Sn 0.50 to 1.00 Pb 0.20 maximum Zn Remainder</p>	<p>28 Leaded Steel Bar AISI 12L14</p> <p>Composition (Percent)</p> <p>C 0.15 maximum Mn 0.80 to 1.20 P 0.04 to 0.09 S 0.25 to 0.35 Pb 0.15 to 0.35</p>	<p>37 Nickel-Copper Alloy Bar Alloy K500 (K Monel®*)</p> <p>Composition (Percent)</p> <p>Ni 63.00 to 70.00 Fe 2.00 maximum Mn 1.50 maximum Si 1.00 maximum C 0.25 maximum S 0.01 maximum Al 2.00 to 4.00 Ti 0.25 to 1.00 Cu Remainder</p>	<p>38 Nickel-Moly Alloy "B" Bar ASTM B335 (Hastelloy® "B" †)</p> <p>Composition (Percent)</p> <p>Cr 1.00 maximum Fe 4.00 to 6.00 C 0.04 maximum Si 1.00 maximum Co 2.50 maximum Mn 1.00 maximum V 0.20 to 0.40 Mo 26.00 to 30.00 P 0.025 maximum S 0.030 maximum Ni Remainder</p>
<p>29 Carbon Steel Bar ASTM A108 Grade 1018</p> <p>Composition (Percent)</p> <p>C 0.15 to 0.20 Mn 0.60 to 0.90 P 0.04 maximum S 0.05 maximum</p>	<p>30 AISI 4140 Chrome-Moly Steel (Suitable for ASTM A193 Grade B7 bolt material)</p> <p>Composition (Percent)</p> <p>C 0.38 to 0.43 Mn 0.75 to 1.00 P 0.035 maximum S 0.04 maximum Si 0.20 to 0.35 Cr 0.80 to 1.10 Mo 0.15 to 0.25 Fe Remainder</p>	<p>39 Nickel-Moly-Chrome Alloy "C" Bar ASTM B336 (Hastelloy® "C" †)</p> <p>Composition (Percent)</p> <p>Cr 14.50 to 16.50 Fe 4.00 to 7.00 W 3.00 to 4.50 C 0.08 maximum Si 1.00 maximum Co 2.50 maximum Mn 1.00 maximum Va 0.35 maximum Mo 15.00 to 17.00 P 0.04 S 0.03 Ni Remainder</p>	



# Conversions, Equivalents and Physical Data

**Table 22. Recommended Standard Specifications for Valve Materials Pressure-Containing Castings**

MATERIAL CODE AND DESCRIPTION			MINIMUM PHYSICAL PROPERTIES				MODULUS OF ELASTICITY AT 70°F (psi x 10 <sup>6</sup> )	APPROXIMATE BRINELL HARDNESS
			Tensile (psi)	Yield Point (psi)	Elong. in 2 in. (%)	Reduction of Area (%)		
1	Carbon Steel	ASTM A 216 Grade WCC	70,000	40,000	22	35	30.4	137 to 187
2	Carbon Steel	ASTM A 216 Grade WCB	70,000	36,000	22	35	27.9	137 to 187
3	Carbon Steel	ASTM A 352 Grade LCC	70,000	40,000	22	35	29.9	137 to 187
4	Carbon Steel	ASTM A 352 Grade LCB	65,000	35,000	24	35	27.9	137 to 187
5	Chrome Moly Steel	ASTM A217 Grade C5	90,000	60,000	18	35	27.4	241 Maximum
6	Carbon Moly Steel	ASTM A217 Grade WC1	65,000	35,000	24	35	29.9	215 Maximum
7	Chrome Moly Steel	ASTM A217 Grade WC6	70,000	40,000	20	35	29.9	215 Maximum
8	Chrome Moly Steel	ASTM A217 Grade WC9	70,000	40,000	20	35	29.9	241 Maximum
9	3.5% Nickel Steel	ASTM A352 Grade LC3	65,000	40,000	24	35	27.9	137
10	Chrome Moly Steel	ASTM A217 Grade C12	90,000	60,000	18	35	27.4	180 to 240
11	Type 304 Stainless Steel	ASTM A351 Grade CF8	65,000	28,000	35	----	28.0	140
12	Type 316 Stainless Steel	ASTM A351 Grade CF8M	70,000	30,000	30	----	28.3	156 to 170
13	Cast Iron	ASTM A126 Class B	31,000	----	----	----	----	160 to 220
14	Cast Iron	ASTM A126 Class C	41,000	----	----	----	----	160 to 220
15	Ductile Iron	ASTM A395 Type 60-45-15	60,000	45,000	15	----	23-26	143 to 207
16	Ductile Ni-Resist Iron <sup>(1)</sup>	ASTM A439 Type D-2B	58,000	30,000	7	----	----	148 to 211
17	Standard Valve Bronze	ASTM B62	30,000	14,000	20	17	13.5	55 to 65*
18	Tin Bronze	ASTM B143 Alloy 1A	40,000	18,000	20	20	15	75 to 85*
19	Manganese Bronze	ASTM B147 Alloy 8A	65,000	25,000	20	20	15.4	98*
20	Aluminum Bronze	ASTM B148 Alloy 9C	75,000	30,000	12 minimum	12	17	150
21	Monel Alloy 411	(Weldable Grade)	65,000	32,500	25	----	23	120 to 170
22	Nickel-Moly Alloy "B"	ASTM A494 (Hastelloy® "B")	72,000	46,000	6	----	----	----
23	Nickel-Moly-Chrome Alloy "C"	ASTM A494 (Hastelloy® "C")	72,000	46,000	4	----	----	----
24	Cobalt-base Alloy No.6	Stellite No. 6	121,000	64,000	1 to 2	----	30.4	----
25	Aluminum Bar	ASTM B211 Alloy 20911-T3	44,000	36,000	15	----	10.2	95
26	Yellow Brass Bar	ASTM B16-1/2 Hard	45,000	15,000	7	50	14	----
27	Naval Brass Bar	ASTM B21 Alloy 464	60,000	27,000	22	55	----	----
28	Leaded Steel Bar	AISI 12L14	79,000	71,000	16	52	----	163
29	Carbon Steel Bar	ASTM A108 Grade 1018	69,000	48,000	38	62	----	143
30	AISI 4140 Chrome-Moly Steel	(Suitable for ASTM A193 Grade B7 bolt material)	135,000	115,000	22	63	29.9	255
31	Type 302 Stainless Steel	ASTM A276 Type 302	85,000	35,000	60	70	28	150
32	Type 304 Stainless Steel	ASTM A276 Type 304	85,000	35,000	60	70	----	149
33	Type 316 Stainless Steel	ASTM A276 Type 316	80,000	30,000	60	70	28	149
34	Type 316L Stainless Steel	ASTM A276 Type 316L	81,000	34,000	55	----	----	146
35	Type 410 Stainless Steel	ASTM A276 Type 410	75,000	40,000	35	70	29	155
36	Type 17-4PH Stainless Steel	ASTM A461 Grade 630	135,000	105,000	16	50	29	275 to 345
37	Nickel-Copper Alloy Bar	Alloy K500 (K Monel®)	100,000	70,000	35	----	26	175 to 260
38	Nickel-Moly Alloy "B" Bar	ASTM B335 (Hastelloy® "B")	100,000	46,000	30	----	----	----
39	Nickel-Moly Alloy "C" Bar	ASTM B336 (Hastelloy® "C")	100,000	46,000	20	----	----	----

1. 500 kg load.

# Conversions, Equivalents and Physical Data

**Table 23. Physical Constants of Hydrocarbons**

NO.	COMPOUND	FORMULA	MOLECULAR WEIGHT	BOILING POINT AT 14.696 psia (°F)	VAPOR PRESSURE AT 100°F (psia)	FREEZING POINT AT 14.696 PSIA (°F)	CRITICAL CONSTANTS		SPECIFIC GRAVITY AT 14.696 PSIA	
							Critical Temperature (°F)	Critical Pressure (psia)	Liquid <sup>(3)(4)</sup> , 60°F/60°F	Gas at 60°F (Air = 1) <sup>(1)</sup>
1	Methane	CH <sub>4</sub>	16.043	-258.69	5000 <sup>(2)</sup>	-296.46 <sup>(5)</sup>	-116.63	667.8	0.3000 <sup>(8)</sup>	0.5539
2	Ethane	C <sub>2</sub> H <sub>6</sub>	30.070	-127.48	800 <sup>(2)</sup>	-297.89 <sup>(5)</sup>	90.09	707.8	0.3564 <sup>(7)</sup>	1.0382
3	Propane	C <sub>3</sub> H <sub>8</sub>	44.097	-43.67	190	-305.84 <sup>(5)</sup>	206.01	616.3	0.5077 <sup>(7)</sup>	1.5225
4	n-Butane	C <sub>4</sub> H <sub>10</sub>	58.124	31.10	51.6	-217.05	305.65	550.7	0.5844 <sup>(7)</sup>	2.0068
5	Isobutane	C <sub>4</sub> H <sub>10</sub>	58.124	10.90	72.2	-255.29	274.98	529.1	0.5631 <sup>(7)</sup>	2.0068
6	n-Pentane	C <sub>5</sub> H <sub>12</sub>	72.151	96.92	15.570	-201.51	385.7	488.6	0.6310	2.4911
7	Isopentane	C <sub>5</sub> H <sub>12</sub>	72.151	82.12	20.44	-255.83	369.10	490.4	0.6247	2.4911
8	Neopentane	C <sub>5</sub> H <sub>12</sub>	72.151	49.10	35.9	-25.17	321.13	464.0	0.5967 <sup>(7)</sup>	2.4911
9	n-Hexane	C <sub>6</sub> H <sub>14</sub>	86.178	155.72	4.956	-139.58	453.7	436.9	0.6640	2.9753
10	2-Methylpentane	C <sub>6</sub> H <sub>14</sub>	86.178	140.47	6.767	-244.63	435.83	436.6	0.6579	2.9753
11	3-Methylpentane	C <sub>6</sub> H <sub>14</sub>	86.178	145.89	6.098	----	448.3	453.1	0.6689	2.9753
12	Neohexane	C <sub>6</sub> H <sub>14</sub>	86.178	121.52	9.856	-147.72	420.13	446.8	0.6540	2.9753
13	2,3-Dimethylbutane	C <sub>6</sub> H <sub>14</sub>	86.178	136.36	7.404	-199.38	440.29	453.5	0.6664	2.9753
14	n-Heptane	C <sub>7</sub> H <sub>16</sub>	100.205	209.17	1.620	-131.05	512.8	396.8	0.6882	3.4596
15	2-Methylhexane	C <sub>7</sub> H <sub>16</sub>	100.205	194.09	2.271	-180.89	495.00	396.5	0.6830	3.4596
16	3-Methylhexane	C <sub>7</sub> H <sub>16</sub>	100.205	197.32	2.130	----	503.78	408.1	0.6917	3.4596
17	3-Ethylpentane	C <sub>7</sub> H <sub>16</sub>	100.205	200.25	2.012	-181.48	513.48	419.3	0.7028	3.4596
18	2,2-Dimethylpentane	C <sub>7</sub> H <sub>16</sub>	100.205	174.54	3.492	-190.86	477.23	402.2	0.6782	3.4596
19	2,4-Dimethylpentane	C <sub>7</sub> H <sub>16</sub>	100.205	176.89	3.292	-182.63	475.95	396.9	0.6773	3.4596
20	3,3-Dimethylpentane	C <sub>7</sub> H <sub>16</sub>	100.205	186.91	2.773	-210.01	505.85	427.2	0.6976	3.4596
21	Triptane	C <sub>7</sub> H <sub>16</sub>	100.205	177.58	3.374	-12.82	496.44	428.4	0.6946	3.4596
22	n-Octane	C <sub>8</sub> H <sub>18</sub>	114.232	258.22	0.537	-70.18	564.22	360.6	0.7068	3.9439
23	Diisobutyl	C <sub>8</sub> H <sub>18</sub>	114.232	228.39	1.101	-132.07	530.44	360.6	0.6979	3.9439
24	Isooctane	C <sub>8</sub> H <sub>18</sub>	114.232	210.63	1.708	-161.27	519.46	372.4	0.6962	3.9439
25	n-Nonane	C <sub>9</sub> H <sub>20</sub>	128.259	303.47	0.179	-64.28	610.68	332	0.7217	4.4282
26	n-Decane	C <sub>10</sub> H <sub>22</sub>	142.286	345.48	0.0597	-21.36	652.1	304	0.7342	4.9125
27	Cyclopentane	C <sub>5</sub> H <sub>10</sub>	70.135	120.65	9.914	-136.91	461.5	653.8	0.7504	2.4215
28	Methylcyclopentane	C <sub>6</sub> H <sub>12</sub>	84.162	161.25	4.503	-224.44	499.35	548.9	0.7536	2.9057
29	Cyclohexane	C <sub>6</sub> H <sub>12</sub>	84.162	177.29	3.264	43.77	536.7	591	0.7834	2.9057
30	Methylcyclohexane	C <sub>7</sub> H <sub>14</sub>	98.189	213.68	1.609	-195.98	570.27	503.5	0.7740	3.3900
31	Ethylene	C <sub>2</sub> H <sub>4</sub>	28.054	-154.62	----	-272.45 <sup>(5)</sup>	48.58	729.8	----	0.9686
32	Propene	C <sub>3</sub> H <sub>6</sub>	42.081	-53.90	226.4	-301.45 <sup>(5)</sup>	196.9	669	0.5220 <sup>(7)</sup>	1.4529
33	1-Butene	C <sub>4</sub> H <sub>8</sub>	56.108	20.75	63.05	-301.63 <sup>(5)</sup>	295.6	583	0.6013 <sup>(7)</sup>	1.9372
34	Cis-2-Butene	C <sub>4</sub> H <sub>8</sub>	56.108	38.69	45.54	-218.06	324.37	610	0.6271 <sup>(7)</sup>	1.9372
35	Trans-2-Butene	C <sub>4</sub> H <sub>8</sub>	56.108	33.58	49.80	-157.96	311.86	595	0.6100 <sup>(7)</sup>	1.9372
36	Isobutene	C <sub>4</sub> H <sub>8</sub>	56.108	19.59	63.40	-220.61	292.55	580	0.6004 <sup>(7)</sup>	1.9372
37	1-Pentene	C <sub>5</sub> H <sub>10</sub>	70.135	85.93	19.115	-265.39	376.93	590	0.645 <sup>(7)</sup>	2.4215
38	1,2-Butadiene	C <sub>4</sub> H <sub>6</sub>	54.092	51.56	20 <sup>(2)</sup>	-213.16	339 <sup>(2)</sup>	653 <sup>(2)</sup>	0.658 <sup>(7)</sup>	1.8676
39	1,3-Butadiene	C <sub>4</sub> H <sub>6</sub>	54.092	24.06	60 <sup>(2)</sup>	-164.02	306	628	0.6272 <sup>(7)</sup>	1.8676
40	Isoprene	C <sub>5</sub> H <sub>8</sub>	68.119	93.30	16.672	-230.74	412 <sup>(2)</sup>	558.4 <sup>(2)</sup>	0.6861	2.3519
41	Acetylene	C <sub>2</sub> H <sub>2</sub>	26.038	-119 <sup>(6)</sup>	----	-114 <sup>(5)</sup>	95.31	890.4	0.615 <sup>(9)</sup>	0.8990
42	Benzene	C <sub>6</sub> H <sub>6</sub>	78.114	176.17	3.224	41.96	552.22	710.4	0.8844	2.6969
43	Toluene	C <sub>7</sub> H <sub>8</sub>	92.141	231.13	1.032	-138.94	605.55	595.9	0.8718	3.1812
44	Ethylbenzene	C <sub>8</sub> H <sub>10</sub>	106.168	277.16	0.371	-138.91	651.24	523.5	0.8718	3.6655
45	o-Xylene	C <sub>8</sub> H <sub>10</sub>	106.168	291.97	0.264	-13.30	675.0	541.4	0.8848	3.6655
46	m-Xylene	C <sub>8</sub> H <sub>10</sub>	106.168	282.41	0.326	-54.12	651.02	513.6	0.8687	3.6655
47	p-Xylene	C <sub>8</sub> H <sub>10</sub>	106.168	281.05	0.342	55.86	649.6	509.2	0.8657	3.6655
48	Styrene	C <sub>8</sub> H <sub>8</sub>	104.152	293.29	0.24 <sup>(2)</sup>	-23.10	706.0	580	0.9110	3.5959
49	Isopropylbenzene	C <sub>9</sub> H <sub>12</sub>	120.195	306.34	0.188	-140.82	676.4	465.4	0.8663	4.1498

1. Calculated values.
2. ( ) - Estimated values.
3. Air saturated hydrocarbons.
4. Absolute values from weights in vacuum.
5. At saturation pressure (----).
6. Sublimation point.
7. Saturation pressure at 60°F.
8. Apparent value for methane at 60°F.
9. Specific gravity, 119°F/60°F (sublimation point).

# Conversions, Equivalents and Physical Data

**Table 24. Physical Constants of Various Fluids**

FLUID	FORMULA	MOLECULAR WEIGHT	BOILING POINT (°F AT 14.696 psia)	VAPOR PRESSURE AT 70°F (psig)	CRITICAL TEMPERATURE (°F)	CRITICAL PRESSURE (psia)	SPECIFIC GRAVITY	
							Liquid 60°F/60°F	Gas
Acetic Acid	HC <sub>2</sub> H <sub>3</sub> O <sub>3</sub>	60.06	245	----	----	----	1.05	----
Acetone	C <sub>3</sub> H <sub>6</sub> O	58.08	133	----	455	691	0.79	2.01
Air	N <sub>2</sub> O <sub>2</sub>	28.97	-317	----	-221	547	0.86 <sup>3</sup>	1.0
Alcohol, Ethyl	C <sub>2</sub> H <sub>5</sub> O	46.07	173	2.3 <sup>(2)</sup>	470	925	0.794	1.59
Alcohol, Methyl	CH <sub>4</sub> O	32.04	148	4.63 <sup>(2)</sup>	463	1174	0.796	1.11
Ammonia	NH <sub>3</sub>	17.03	-28	114	270	1636	0.62	0.59
Ammonium Chloride <sup>(1)</sup>	NH <sub>4</sub> Cl	----	----	----	----	----	1.07	----
Ammonium Hydroxide <sup>(1)</sup>	NH <sub>4</sub> OH	----	----	----	----	----	0.91	----
Ammonium Sulfate <sup>(1)</sup>	(NH <sub>4</sub> ) <sub>2</sub> SO <sub>4</sub>	----	----	----	----	----	1.15	----
Aniline	C <sub>6</sub> H <sub>5</sub> N	93.12	365	----	798	770	1.02	----
Argon	A	39.94	-302	----	-188	705	1.65	1.38
Bromine	Br <sub>2</sub>	159.84	138	----	575	----	2.93	5.52
Calcium Chloride <sup>(1)</sup>	CaCl <sub>2</sub>	----	----	----	----	----	1.23	----
Carbon Dioxide	CO <sub>2</sub>	44.01	-109	839	88	1072	0.801 <sup>(3)</sup>	1.52
Carbon Disulfide	CS <sub>2</sub>	76.1	115	----	----	----	1.29	2.63
Carbon Monoxide	CO	28.01	-314	----	-220	507	0.80	0.97
Carbon Tetrachloride	CCl <sub>4</sub>	153.84	170	----	542	661	1.59	5.31
Chlorine	Cl <sub>2</sub>	70.91	-30	85	291	1119	1.42	2.45
Chromic Acid	H <sub>2</sub> CrO <sub>4</sub>	118.03	----	----	----	----	1.21	----
Citric Acid	C <sub>6</sub> H <sub>8</sub> O <sub>7</sub>	192.12	----	----	----	----	1.54	----
Copper Sulfate <sup>(1)</sup>	CuSO <sub>4</sub>	----	----	----	----	----	1.17	----
Ether	(C <sub>2</sub> H <sub>5</sub> ) <sub>2</sub> O	74.12	34	----	----	----	0.74	2.55
Ferric Chloride <sup>(1)</sup>	FeCl <sub>3</sub>	----	----	----	----	----	1.23	----
Fluorine	F <sub>2</sub>	38.00	-305	300	-200	809	1.11	1.31
Formaldehyde	H <sub>2</sub> CO	30.03	-6	----	----	----	0.82	1.08
Formic Acid	HCO <sub>2</sub> H	46.03	214	----	----	----	1.23	----
Furfural	C <sub>5</sub> H <sub>4</sub> O <sub>2</sub>	96.08	324	----	----	----	1.16	----
Glycerine	C <sub>3</sub> H <sub>8</sub> O <sub>3</sub>	92.09	554	----	----	----	1.26	----
Glycol	C <sub>2</sub> H <sub>6</sub> O <sub>2</sub>	62.07	387	----	----	----	1.11	----
Helium	He	4.003	-454	----	-450	33	0.18	0.14
Hydrochloric Acid	HCl	36.47	-115	----	----	----	1.64	----
Hydrofluoric Acid	HF	20.01	66	0.9	446	----	0.92	----
Hydrogen	H <sub>2</sub>	2.016	-422	----	-400	188	0.07 <sup>(3)</sup>	0.07
Hydrogen Chloride	HCl	36.47	-115	613	125	1198	0.86	1.26
Hydrogen Sulfide	H <sub>2</sub> S	34.07	-76	252	213	1307	0.79	1.17
Isopropyl Alcohol	C <sub>3</sub> H <sub>8</sub> O	60.09	180	----	----	----	0.78	2.08
Linseed Oil	----	----	538	----	----	----	0.93	----

1. Aqueous Solution - 25% by weight of compound.  
2. Vapor pressure in psia at 100°F.  
3. Density of liquid, gm/ml at normal boiling point.

- continued -

# Conversions, Equivalents and Physical Data

**Table 24. Physical Constants of Various Fluids (continued)**

FLUID	FORMULA	MOLECULAR WEIGHT	BOILING POINT (°F AT 14.696 psia)	VAPOR PRESSURE AT 70°F (psig)	CRITICAL TEMPERATURE (°F)	CRITICAL PRESSURE (psia)	SPECIFIC GRAVITY	
							Liquid 60°F/60°F	Gas
Magnesium Chloride <sup>(1)</sup>	MgCl <sub>2</sub>	----	----	----	----	----	1.22	----
Mercury	Hg	200.61	670	----	----	----	13.6	6.93
Methyl Bromide	CH <sub>3</sub> Br	94.95	38	13	376	----	1.73	3.27
Methyl Chloride	CH <sub>3</sub> Cl	50.49	-11	59	290	969	0.99	1.74
Naphthalene	C <sub>10</sub> H <sub>8</sub>	128.16	424	----	----	----	1.14	4.43
Nitric Acid	HNO <sub>3</sub>	63.02	187	----	----	----	1.5	----
Nitrogen	N <sub>2</sub>	28.02	-320	----	-233	493	0.81 <sup>(3)</sup>	0.97
Oil, Vegetable	----	----	----	----	----	----	0.91 to 0.94	----
Oxygen	O <sub>2</sub>	32	-297	----	-181	737	1.14 <sup>(3)</sup>	1.105
Phosgene	COCl <sub>2</sub>	98.92	47	10.7	360	823	1.39	3.42
Phosphoric Acid	H <sub>3</sub> PO <sub>4</sub>	98.00	415	----	----	----	1.83	----
Potassium Carbonate <sup>(1)</sup>	K <sub>2</sub> CO <sub>3</sub>	----	----	----	----	----	1.24	----
Potassium Chloride <sup>(1)</sup>	KCl	----	----	----	----	----	1.16	----
Potassium Hydroxide <sup>(1)</sup>	KOH	----	----	----	----	----	1.24	----
Refrigerant 11	CCl <sub>3</sub> F	137.38	75	13.4	388	635	----	5.04
Refrigerant 12	CCl <sub>2</sub> F <sub>2</sub>	120.93	-22	70.2	234	597	----	4.2
Refrigerant 13	CClF <sub>3</sub>	104.47	-115	458.7	84	561	----	----
Refrigerant 21	CHCl <sub>3</sub> F	102.93	48	8.4	353	750	----	3.82
Refrigerant 22	CHClF <sub>2</sub>	86.48	-41	122.5	205	716	----	----
Refrigerant 23	CHF <sub>3</sub>	70.02	-119	635	91	691	----	----
Sodium Chloride <sup>(1)</sup>	NaCl	----	----	----	----	----	1.19	----
Sodium Hydroxide <sup>(1)</sup>	NaOH	----	----	----	----	----	1.27	----
Sodium Sulfate <sup>(1)</sup>	Na <sub>2</sub> SO <sub>4</sub>	----	----	----	----	----	1.24	----
Sodium Thiosulfate <sup>(1)</sup>	Na <sub>2</sub> SO <sub>3</sub>	----	----	----	----	----	1.23	----
Starch	(C <sub>6</sub> H <sub>10</sub> O <sub>5</sub> ) <sub>x</sub>	----	----	----	----	----	1.50	----
Sugar Solutions <sup>(1)</sup>	C <sub>12</sub> H <sub>22</sub> O <sub>11</sub>	----	----	----	----	----	1.10	----
Sulfuric Acid	H <sub>2</sub> SO <sub>4</sub>	98.08	626	----	----	----	1.83	----
Sulfur Dioxide	SO <sub>2</sub>	64.6	14	34.4	316	1145	1.39	2.21
Turpentine	----	----	320	----	----	----	0.87	----
Water	H <sub>2</sub> O	18.016	212	0.9492 <sup>(2)</sup>	706	3208	1.00	0.62
Zinc Chloride <sup>(1)</sup>	ZnCl <sub>2</sub>	----	----	----	----	----	1.24	----
Zinc Sulfate <sup>(1)</sup>	ZnSO <sub>4</sub>	----	----	----	----	----	1.31	----

1. Aqueous Solution - 25% by weight of compound.  
 2. Vapor pressure in psia at 100°F.  
 3. Density of liquid, gm/ml at normal boiling point.

# Conversions, Equivalents and Physical Data

**Table 25. Properties of Water**

TEMPERATURE OF WATER (°F)	SATURATION PRESSURE (POUNDS PER SQUARE INCH ABSOLUTE)	WEIGHT (POUNDS PER GALLON)	SPECIFIC GRAVITY 60°F/60°F	CONVERSION FACTOR <sup>(1)</sup> , LBS/HR TO GPM
32	0.0885	8.345	1.0013	0.00199
40	0.1217	8.345	1.0013	0.00199
50	0.1781	8.340	1.0007	0.00199
60	0.2653	8.334	1.0000	0.00199
70	0.3631	8.325	0.9989	0.00200
80	0.5069	8.314	0.9976	0.00200
90	0.6982	8.303	0.9963	0.00200
100	0.9492	8.289	0.9946	0.00201
110	1.2748	8.267	0.9919	0.00201
120	1.6924	8.253	0.9901	0.00200
130	2.2225	8.227	0.9872	0.00202
140	2.8886	8.207	0.9848	0.00203
150	3.718	8.182	0.9818	0.00203
160	4.741	8.156	0.9786	0.00204
170	5.992	8.127	0.9752	0.00205
180	7.510	8.098	0.9717	0.00205
190	9.339	8.068	0.9681	0.00206
200	11.526	8.039	0.9646	0.00207
210	14.123	8.005	0.9605	0.00208
212	14.696	7.996	0.9594	0.00208
220	17.186	7.972	0.9566	0.00209
240	24.969	7.901	0.9480	0.00210
260	35.429	7.822	0.9386	0.00211
280	49.203	7.746	0.9294	0.00215
300	67.013	7.662	0.9194	0.00217
350	134.63	7.432	0.8918	0.00224
400	247.31	7.172	0.8606	0.00232
450	422.6	6.892	0.8270	0.00241
500	680.8	6.553	0.7863	0.00254
550	1045.2	6.132	0.7358	0.00271
600	1542.9	5.664	0.6796	0.00294
700	3093.7	3.623	0.4347	0.00460

1. Multiply flow in pounds per hour by the factor to get equivalent flow in gallons per minute. Weight per gallon is based on 7.48 gal/ft<sup>3</sup>.

**Table 26. Properties of Saturated Steam**

ABSOLUTE PRESSURE		VACUUM (IN. OF HG)	TEMP. (°F)	HEAT OF THE LIQUID (BTU/LB.)	LATENT HEAT OF EVAPORATION (BTU/LB.)	TOTAL HEAT OF STEAM HG (BTU/LB.)	SPECIFIC VOLUME (CUBIC FT./LB.)
psia	In. of Hg						
0.20	0.41	29.51	53.14	21.21	1063.8	1085.0	1526.0
0.25	0.51	29.41	59.30	27.36	1060.3	1087.7	1235.3
0.30	0.61	29.31	64.47	32.52	1057.4	1090.0	1039.5
0.35	0.71	29.21	68.93	36.97	1054.9	1091.9	898.5
0.40	0.81	29.11	72.86	40.89	1052.7	1093.6	791.9
0.45	0.92	29.00	76.38	44.41	1050.7	1095.1	708.5
0.50	1.02	28.90	79.58	47.60	1048.8	1096.4	641.4
0.60	1.22	28.70	85.21	53.21	1045.7	1098.9	540.0
0.70	1.43	28.49	90.08	58.07	1042.9	1101.0	466.9
0.80	1.63	28.29	94.38	62.36	1040.4	1102.8	411.7
0.90	1.83	28.09	98.24	66.21	1038.3	1104.5	368.4
1.0	2.04	27.88	101.74	69.70	1036.3	1106.0	333.6
1.2	2.44	27.48	107.92	75.87	1032.7	1108.6	280.9
1.4	2.85	27.07	113.26	81.20	1029.6	1110.8	243.0
1.6	3.26	26.66	117.99	85.91	1026.9	1112.8	214.3
1.8	3.66	26.26	122.23	90.14	1024.5	1114.6	191.8
2.0	4.07	25.85	126.08	93.99	1022.2	1116.2	173.73
2.2	4.48	25.44	129.62	97.52	1020.2	1117.7	158.85
2.4	4.89	25.03	132.89	100.79	1018.3	1119.1	146.38
2.6	5.29	24.63	135.94	103.83	1016.5	1120.3	135.78
2.8	5.70	24.22	138.79	106.68	1014.8	1121.5	126.65
3.0	6.11	23.81	141.48	109.37	1013.2	1122.6	67.24
3.5	7.13	22.79	147.57	115.46	1009.6	1125.1	61.98
4.0	8.14	21.78	152.97	120.86	1006.4	1127.3	57.50
4.5	9.16	20.76	157.83	125.71	1003.6	1129.3	53.64
5.0	10.18	19.74	162.24	130.13	1001.0	1131.1	50.29
5.5	11.20	18.72	166.30	134.19	998.5	1132.7	67.24
6.0	12.22	17.70	170.06	137.96	996.2	1134.2	61.98
6.5	13.23	16.69	173.56	141.47	994.1	1135.6	57.50
7.0	14.25	15.67	176.85	144.76	992.1	1136.9	53.64
7.5	15.27	14.65	179.94	147.86	990.2	1138.1	50.29
8.0	16.29	13.63	182.86	150.79	988.5	1139.3	47.34
8.5	17.31	12.61	185.64	153.57	986.8	1140.4	44.73
9.0	18.32	11.60	188.28	156.22	985.2	1141.4	42.40
9.5	19.34	10.58	190.80	158.75	983.6	1142.3	40.31
10.0	20.36	9.56	193.21	161.17	982.1	1143.3	38.42
11.0	22.40	7.52	197.75	165.73	979.3	1145.0	35.14
12.0	24.43	5.49	201.96	169.96	976.6	1146.6	32.40
13.0	26.47	3.45	205.88	173.91	974.2	1148.1	30.06
14.0	28.50	1.42	209.56	177.61	971.9	1149.5	28.04

- continued -

# Conversions, Equivalents and Physical Data

**Table 26. Properties of Saturated Steam (continued)**

PRESSURE (psi)		TEMP. (°F)	HEAT OF THE LIQUID (BTU/LB)	LATENT HEAT OF EVAPORATION (BTU/LB)	TOTAL HEAT OF STEAM H <sub>g</sub> (BTU/LB)	SPECIFIC VOLUME ∇ (FT <sup>3</sup> /LB)	PRESSURE (psi)		TEMP. (°F)	HEAT OF THE LIQUID (BTU/LB)	LATENT HEAT OF EVAPORATION (BTU/LB)	TOTAL HEAT OF STEAM H <sub>g</sub> (BTU/LB)	SPECIFIC VOLUME ∇ (FT <sup>3</sup> /LB)
Absolute P'	Gauge P						Absolute P'	Gauge P					
14.696	0.0	212.00	180.07	970.3	1150.4	26.80	----	----	---	----	----	----	----
15.0	0.3	213.03	181.11	969.7	1150.8	26.29	75.0	60.3	-307.60	277.43	904.5	1181.9	5.816
16.0	1.3	216.32	184.42	967.6	1152.0	24.72	76.0	61.3	308.50	278.37	903.7	1182.1	5.743
17.0	2.3	219.44	187.56	965.5	1153.1	23.39	77.0	62.3	309.40	279.30	903.1	1182.4	5.673
18.0	3.3	222.41	190.56	963.6	1154.2	22.17	78.0	63.3	310.29	280.21	902.4	1182.6	5.604
19.0	4.3	225.24	193.42	961.9	1155.3	21.08	79.0	64.3	311.16	281.12	901.7	1182.8	5.537
20.0	5.3	227.96	196.16	960.1	1156.3	20.089	80.0	65.3	312.03	282.02	901.1	1183.1	5.472
21.0	6.3	230.57	198.79	958.4	1157.2	19.192	81.0	66.3	312.89	282.91	900.4	1183.3	5.408
22.0	7.3	233.07	201.33	956.8	1158.1	18.375	82.0	67.3	313.74	283.79	899.7	1183.5	5.346
23.0	8.3	235.49	203.78	955.2	1159.0	17.627	83.0	68.3	314.59	284.66	899.1	1183.8	5.285
24.0	9.3	237.82	206.14	953.7	1159.8	16.938	84.0	69.3	315.42	285.53	898.5	1184.0	5.226
25.0	10.3	240.07	208.42	952.1	1160.6	16.303	85.0	70.3	316.25	286.39	897.8	1184.2	5.168
26.0	11.3	242.25	210.62	950.7	1161.3	15.715	86.0	71.3	317.07	287.24	897.2	1184.4	5.111
27.0	12.3	244.36	212.75	949.3	1162.0	15.170	87.0	72.3	317.88	288.08	896.5	1184.6	5.055
28.0	13.3	246.41	214.83	947.9	1162.7	14.663	88.0	73.3	318.68	288.91	895.9	1184.8	5.001
29.0	14.3	248.40	216.86	946.5	1163.4	14.189	89.0	74.3	319.48	289.74	895.3	1185.1	4.948
30.0	15.3	250.33	218.82	945.3	1164.1	13.746	90.0	75.3	320.27	290.56	894.7	1185.3	4.896
31.0	16.3	252.22	220.73	944.0	1164.7	13.330	91.0	76.3	321.06	291.38	894.1	1185.5	4.845
32.0	17.3	254.05	222.59	942.8	1165.4	12.940	92.0	77.3	321.83	292.18	893.5	1185.7	4.796
33.0	18.3	255.84	224.41	941.6	1166.0	12.572	93.0	78.3	322.60	292.98	892.9	1185.9	4.747
34.0	19.3	257.58	226.18	940.3	1166.5	12.226	94.0	79.3	323.36	293.78	892.3	1186.1	4.699
35.0	20.3	259.28	227.91	939.2	1167.1	11.898	95.0	80.3	324.12	294.56	891.7	1186.2	4.652
36.0	21.3	260.95	229.60	938.0	1167.6	11.588	96.0	81.3	324.87	295.34	891.1	1186.4	4.606
37.0	22.3	262.57	231.26	936.9	1168.2	11.294	97.0	82.3	325.61	296.12	890.5	1186.6	4.561
38.0	23.3	264.16	232.89	935.8	1168.7	11.150	98.0	83.3	326.35	296.89	889.9	1186.8	4.517
39.0	24.3	265.72	234.48	934.7	1169.2	10.750	99.0	84.3	327.08	297.65	889.4	1187.0	4.474
40.0	25.3	267.25	236.03	933.7	1169.7	10.498	100.0	85.3	327.81	298.40	888.8	1187.2	4.432
41.0	26.3	268.74	237.55	932.6	1170.2	10.258	101.0	86.3	328.53	299.15	888.2	1187.4	4.391
42.0	27.3	270.21	239.04	931.6	1170.7	10.029	102.0	87.3	329.25	299.90	887.6	1187.5	4.350
43.0	28.3	271.64	240.51	930.6	1171.1	9.810	103.0	88.3	329.96	300.64	887.1	1187.7	4.310
44.0	29.3	273.05	241.95	929.6	1171.6	9.601	104.0	89.3	330.66	301.37	886.5	1187.9	4.271
45.0	30.3	274.44	243.36	928.6	1172.0	9.401	105.0	90.3	331.36	302.10	886.0	1188.1	4.232
46.0	31.3	275.80	244.75	927.7	1172.4	9.209	106.0	91.3	332.05	302.82	885.4	1188.2	4.194
47.0	32.3	277.13	246.12	926.7	1172.9	9.025	107.0	92.3	332.74	303.54	884.9	1188.4	4.157
48.0	33.3	278.45	247.47	925.8	1173.3	8.848	108.0	93.3	333.42	304.26	884.3	1188.6	4.120
49.0	34.3	279.74	248.79	924.9	1173.7	8.678	109.0	94.3	334.10	304.97	883.7	1188.7	4.084
50.0	35.3	281.01	250.09	924.0	1174.1	8.515	110.0	95.3	334.77	305.66	883.2	1188.9	4.049
51.0	36.3	282.26	251.37	923.0	1174.4	8.359	111.0	96.3	335.44	306.37	882.6	1189.0	4.015
52.0	37.3	283.49	252.63	922.2	1174.8	8.208	112.0	97.3	336.11	307.06	882.1	1189.2	3.981
53.0	38.3	284.70	253.87	921.3	1175.2	8.062	113.0	98.3	336.77	307.75	881.6	1189.4	3.947
54.0	39.3	285.90	255.09	920.5	1175.6	7.922	114.0	99.3	337.42	308.43	881.1	1189.5	3.914
55.0	40.3	287.07	256.30	919.6	1175.9	7.787	115.0	100.3	338.07	309.11	880.6	1189.7	3.882
56.0	41.3	288.28	257.50	918.8	1176.3	7.656	116.0	101.3	338.72	309.79	880.0	1189.8	3.850
57.0	42.3	289.37	258.67	917.9	1176.6	7.529	117.0	102.3	339.36	310.46	879.5	1190.0	3.819
58.0	43.3	290.50	259.82	917.1	1176.9	7.407	118.0	103.3	339.99	311.12	879.0	1190.1	3.788
59.0	44.3	291.61	260.96	916.3	1177.3	7.289	119.0	104.3	340.62	311.78	878.4	1190.2	3.758
60.0	45.3	292.71	262.09	915.5	1177.6	7.175	120.0	105.3	341.25	312.44	877.9	1190.4	3.728
61.0	46.3	293.79	263.20	914.7	1177.9	7.064	121.0	106.3	341.88	313.10	877.4	1190.5	3.699
62.0	47.3	294.85	264.30	913.9	1178.2	6.957	122.0	107.3	342.50	313.75	876.9	1190.7	3.670
63.0	48.3	295.90	265.38	913.1	1178.5	6.853	123.0	108.3	343.11	314.40	876.4	1190.8	3.642
64.0	49.3	296.94	266.45	912.3	1178.8	6.752	124.0	109.3	343.72	315.04	875.9	1190.9	3.614
65.0	50.3	297.97	267.50	911.6	1179.1	6.655	125.0	110.3	344.33	315.68	875.4	1191.1	3.587
66.0	51.3	298.99	268.55	910.8	1179.4	6.560	126.0	111.3	344.94	316.31	874.9	1191.2	3.560
67.0	52.3	299.99	269.58	910.1	1179.7	6.468	127.0	112.3	345.54	316.94	874.4	1191.3	3.533
68.0	53.3	300.98	270.60	909.4	1180.0	6.378	128.0	113.3	346.13	317.57	873.9	1191.5	3.507
69.0	54.3	301.96	271.61	908.7	1180.3	6.291	129.0	114.3	346.73	318.19	873.4	1191.6	3.481
70.0	55.3	302.92	272.61	907.9	1180.6	6.206	130.0	115.3	347.32	318.81	872.9	1191.7	3.455
71.0	56.3	303.88	273.60	907.2	1180.8	6.124	131.0	116.3	347.90	319.43	872.5	1191.9	3.430
72.0	57.3	304.83	274.57	906.5	1181.1	6.044	132.0	117.3	348.48	320.04	872.0	1192.0	3.405
73.0	58.3	305.76	275.54	905.8	1181.3	5.966	133.0	118.3	349.06	320.65	871.5	1192.1	3.381
74.0	59.3	306.68	276.49	905.1	1181.6	5.890	134.0	119.3	349.64	321.25	871.0	1192.2	3.357

- continued -



# Conversions, Equivalents and Physical Data

**Table 26. Properties of Saturated Steam (continued)**

PRESSURE (psi)		TEMP. (°F)	HEAT OF THE LIQUID (BTU/LB)	LATENT HEAT OF EVAPORATION (BTU/LB)	TOTAL HEAT OF STEAM H <sub>g</sub> (BTU/LB)	SPECIFIC VOLUME ∇ (FT <sup>3</sup> /LB)	PRESSURE (psi)		TEMP. (°F)	HEAT OF THE LIQUID (BTU/LB)	LATENT HEAT OF EVAPORATION (BTU/LB)	TOTAL HEAT OF STEAM H <sub>g</sub> (BTU/LB.)	SPECIFIC VOLUME ∇ (CU. FT./LB.)
Absolute P'	Gauge P						Absolute P'	Gauge P					
135.0	120.3	350.21	321.85	870.6	1192.4	3.333	400.0	385.3	444.59	424.0	780.5	1204.5	1.1613
136.0	121.3	350.78	322.45	870.1	1192.5	3.310	420.0	405.3	449.39	429.4	775.2	1204.6	1.1061
137.0	122.3	351.35	323.05	869.6	1192.6	3.287	440.0	425.3	454.02	434.6	770.0	1204.6	1.0556
138.0	123.3	351.91	323.64	869.1	1192.7	3.264	460.0	445.3	458.50	439.7	764.9	1204.6	1.0094
139.0	124.3	352.47	324.23	868.7	1192.9	3.242	480.0	465.3	462.82	444.6	759.9	1204.5	0.9670
140.0	125.3	353.02	324.82	868.2	1193.0	3.220	500.0	485.3	467.01	449.4	755.0	1204.4	0.9278
141.0	126.3	353.57	325.40	867.7	1193.1	3.198	520.0	505.3	471.07	454.1	750.1	1204.2	0.7815
142.0	127.3	354.12	325.98	867.2	1193.2	3.177	540.0	525.3	475.01	458.6	745.4	1204.0	0.8578
143.0	128.3	354.67	326.56	866.7	1193.3	3.155	560.0	545.3	478.85	463.0	740.8	1203.8	0.8265
144.0	129.3	355.21	327.13	866.3	1193.4	3.134	580.0	565.3	482.58	467.4	736.1	1203.5	0.7973
145.0	130.3	355.76	327.70	865.8	1193.5	3.114	600.0	585.3	486.21	471.6	731.6	1203.2	0.7698
146.0	131.3	356.29	328.27	865.3	1193.6	3.094	620.0	605.3	489.75	475.7	727.2	1202.9	0.7440
147.0	132.3	356.83	328.83	864.9	1193.8	3.074	640.0	625.3	493.21	479.8	722.7	1202.5	0.7198
148.0	133.3	357.36	329.39	864.5	1193.9	3.054	660.0	645.3	496.58	483.8	718.3	1202.1	0.6971
149.0	134.3	357.89	329.95	864.0	1194.0	3.034	680.0	665.3	499.88	487.7	714.0	1201.7	0.6757
150.0	135.3	358.42	330.51	863.6	1194.1	3.015	700.0	685.3	503.10	491.5	709.7	1201.2	0.6554
152.0	137.3	359.46	331.61	862.7	1194.3	2.977	720.0	705.3	506.25	495.3	705.4	1200.7	0.6362
154.0	139.3	360.49	332.70	851.8	1194.5	2.940	740.0	725.3	509.34	499.0	701.2	1200.2	0.6180
156.0	141.3	361.52	333.79	860.9	1194.7	2.904	760.0	745.3	512.36	502.6	697.1	1199.7	0.6007
158.0	143.3	362.53	334.86	860.0	1194.9	2.869	780.0	765.3	505.33	506.2	692.9	1199.1	0.5843
160.0	145.3	363.53	335.93	859.2	1195.1	2.834	800.0	785.3	518.23	509.7	688.9	1198.6	0.5687
162.0	147.3	364.53	336.98	858.3	1195.3	2.801	820.0	805.3	521.08	513.2	684.8	1198.0	0.5538
164.0	149.3	365.51	338.02	857.5	1195.5	2.768	840.0	825.3	523.88	516.6	680.8	1197.4	0.5396
166.0	151.3	366.48	339.05	856.6	1195.7	2.736	860.0	845.3	526.63	520.0	676.8	1196.8	0.5260
168.0	153.3	367.45	340.07	855.7	1195.8	2.705	880.0	865.3	529.33	523.3	672.8	1196.1	0.5130
170.0	155.3	368.41	341.09	854.9	1196.0	2.675	900.0	885.3	531.98	526.6	668.8	1195.4	0.5006
172.0	157.3	369.35	342.10	854.1	1196.2	2.645	920.0	905.3	534.59	529.8	664.9	1194.7	0.4886
174.0	159.3	370.29	343.10	853.3	1196.4	2.616	940.0	925.3	537.16	533.0	661.0	1194.0	0.4772
176.0	161.3	371.22	344.09	852.4	1196.5	2.587	960.0	945.3	539.68	536.2	657.1	1193.3	0.4663
178.0	163.3	372.14	345.06	851.6	1196.7	2.559	980.0	965.3	542.17	539.3	653.3	1192.6	0.4557
180.0	165.3	373.06	346.03	850.8	1196.9	2.532	1000.0	985.3	544.61	542.4	649.4	1191.8	0.4456
182.0	167.3	373.96	347.00	850.0	1197.0	2.505	1050.0	1035.3	550.57	550.0	639.9	1189.9	0.4218
184.0	169.3	374.86	347.96	849.2	1197.2	2.479	1100.0	1085.3	556.31	557.4	630.4	1187.8	0.4001
186.0	171.3	375.75	348.92	848.4	1197.3	2.454	1150.0	1135.3	561.86	565.6	621.0	1185.6	0.3802
188.0	173.3	376.64	349.86	847.6	1197.5	2.429	1200.0	1185.3	567.22	571.7	611.7	1183.4	0.619
190.0	175.3	377.51	350.79	846.8	1197.6	2.404	1250.0	1235.3	572.42	578.6	602.4	1181.0	0.3450
192.0	177.3	378.38	351.72	846.1	1197.8	2.380	1300.0	1285.3	577.46	585.4	593.2	1178.6	0.3293
194.0	179.3	379.24	352.64	845.3	1197.9	2.356	1350.0	1335.3	582.35	592.1	584.0	1176.1	0.3148
196.0	181.3	380.10	353.55	844.5	1198.1	2.333	1400.0	1385.3	587.10	598.7	574.7	1173.4	0.3012
198.0	183.3	380.95	354.46	843.7	1198.2	2.310	1450.0	1435.3	591.73	605.2	565.5	1170.7	0.2884
200.0	185.3	381.79	355.36	843.0	1198.4	2.288	1500.0	1485.3	596.23	611.6	556.3	1167.9	0.2765
205.0	190.3	383.86	357.58	841.0	1198.7	2.234	1600.0	1585.3	604.90	624.1	538.0	1162.1	0.2548
210.0	195.3	385.90	359.77	839.2	1199.0	2.183	1700.0	1685.3	613.15	636.3	519.6	1155.9	0.2354
215.0	200.3	387.89	361.91	837.4	1199.3	2.134	1800.0	1785.3	621.03	648.3	501.1	1149.4	0.2179
220.0	205.3	389.86	364.02	835.6	1199.6	2.087	1900.0	1885.3	628.58	660.1	482.4	1142.4	0.2021
225.0	210.3	391.79	366.09	833.8	1199.9	2.0422	2000.0	1985.3	635.82	671.7	463.4	1135.1	0.1878
230.0	215.3	393.68	368.13	832.0	1200.1	1.9992	2100.0	2085.3	642.77	683.3	444.1	1127.4	0.1746
235.0	220.3	395.54	370.14	830.3	1200.4	1.9579	2200.0	2185.3	649.46	694.8	424.4	1119.2	0.1625
240.0	225.3	397.37	372.12	828.5	1200.6	1.9183	2300.0	2285.3	655.91	706.5	403.9	1110.4	0.1513
245.0	230.3	399.18	374.08	826.8	1200.9	1.8803	2400.0	2385.3	662.12	718.4	382.7	1101.1	0.1407
250.0	235.3	400.95	376.00	825.1	1201.1	1.8438	2500.0	2485.3	668.13	730.6	360.5	1091.1	0.1307
255.0	240.3	402.70	377.89	823.4	1201.3	1.8086	2600.0	2585.3	673.94	743.0	337.2	1080.2	0.1213
260.0	245.3	404.42	379.76	821.8	1201.5	1.7748	2700.0	2685.3	679.55	756.2	312.1	1068.3	0.1123
265.0	250.3	406.11	381.60	820.1	1201.7	1.7422	2800.0	2785.3	684.99	770.1	284.7	1054.8	0.1035
270.0	255.3	407.78	383.42	818.5	1201.9	1.7107	2900.0	2885.3	690.26	785.4	253.6	1039.0	0.0947
275.0	260.3	409.43	385.21	816.9	1202.1	1.6804	3000.0	2985.3	695.36	802.5	217.8	1020.3	0.0858
280.0	265.3	411.05	386.98	815.3	1202.3	1.6511	3100.0	3085.3	700.31	825.0	168.1	993.1	0.0753
285.0	270.3	412.65	388.73	813.7	1202.4	1.6228	3200.0	3185.3	705.11	872.4	62.0	934.4	0.0580
290.0	275.3	414.23	390.46	812.1	1202.6	1.5954	3206.2	3191.5	705.40	902.7	0.0	902.7	0.0503
295.0	280.3	415.79	392.16	810.5	1202.7	1.5689	----	----	----	----	----	----	----
300.0	285.3	417.33	393.84	809.0	1202.8	1.5433	----	----	----	----	----	----	----
320.0	305.3	423.29	400.39	803.0	1203.4	1.4485	----	----	----	----	----	----	----
340.0	325.3	428.97	406.66	797.1	1203.7	1.3645	----	----	----	----	----	----	----
360.0	345.3	434.40	412.67	797.4	1204.1	1.2895	----	----	----	----	----	----	----
380.0	365.3	439.60	418.45	785.8	1204.3	1.2222	----	----	----	----	----	----	----

# Conversions, Equivalents and Physical Data

**Table 27. Properties of Saturated Steam (Metric)**

TEMPERATURE, °K	PRESSURE, BAR	VOLUME, m/kg		ENTHALPY, kJ/kg		ENTROPY, kJ/(kg x °K)	
		Condensed	Vapor	Condensed	Vapor	Condensed	Vapor
150	6.30 to 11	1.073 to 3	9.55 + 9	-539.6	2273	-2.187	16.54
160	7.72 to 10	1.074 to 3	9.62 + 8	-525.7	2291	-2.106	15.49
170	7.29 to 9	1.076 to 3	1.08 + 8	-511.7	2310	-2.026	14.57
180	5.38 to 8	1.077 to 3	1.55 + 7	-497.8	2328	-1.947	13.76
190	3.23 to 7	1.078 to 3	2.72 + 6	-483.8	2347	-1.868	16.03
200	1.62 to 6	1.079 to 3	5.69 + 5	-467.5	2366	-1.789	12.38
210	7.01 to 6	1.081 to 3	1.39 + 5	-451.2	2384	-1.711	11.79
220	2.65 to 5	1.082 to 3	3.83 + 4	-435.0	2403	-1.633	11.20
230	8.91 to 5	1.084 to 3	1.18 + 4	-416.3	2421	-1.555	10.79
240	3.72 to 4	1.085 to 3	4.07 + 3	-400.1	2440	-1.478	10.35
250	7.59 to 4	1.087 to 3	1.52 + 3	-318.5	2459	-1.400	9.954
255	1.23 to 3	1.087 to 3	956.4	-369.8	2468	-1.361	9.768
260	1.96 to 3	1.088 to 3	612.2	-360.5	2477	-1.323	9.590
265	3.06 to 3	1.089 to 3	400.4	-351.2	2486	-1.281	9.461
270	4.69 to 3	1.090 to 3	265.4	-339.6	2496	-1.296	9.255
273.15	6.11 to 3	1.091 to 3	206.3	-333.5	2502	-1.221	9.158
273.15	0.00611	1.000 to 3	206.3	0.00	2502	0.000	9.158
275	0.00697	1.000 to 3	181.7	7.80	2505	0.028	9.109
280	0.00990	1.000 to 3	130.4	28.8	2514	0.104	8.890
285	0.01387	1.000 to 3	99.4	49.8	2523	0.178	8.857
290	0.01917	1.001 to 3	69.7	70.7	2532	0.251	8.740
295	0.02617	1.002 to 3	51.94	91.6	2541	0.323	8.627
300	0.03531	1.003 to 3	39.13	112.5	2550	0.393	8.520
305	0.04712	1.005 to 3	27.90	133.4	2559	0.462	8.417
310	0.06221	1.007 to 3	22.93	154.3	2568	0.530	8.318
315	0.08132	1.009 to 3	17.82	175.2	2577	0.597	8.224
320	0.01053	1.011 to 3	13.98	196.1	2586	0.649	8.151
325	0.01351	1.013 to 3	11.06	217.0	2595	0.727	8.046
330	0.01719	1.016 to 3	8.82	237.9	2604	0.791	7.962
335	0.02167	1.018 to 3	7.09	258.8	2613	0.854	7.881
340	0.02713	1.021 to 3	5.74	279.8	2622	0.916	7.804
345	0.3372	1.024 to 3	4.683	300.7	2630	0.977	7.729
350	0.4163	1.027 to 3	3.846	321.7	2639	1.038	7.657
355	0.5100	1.030 to 3	3.180	342.7	2647	1.097	7.588
360	0.6209	1.034 to 3	2.645	363.7	2655	1.156	7.521
365	0.7514	1.038 to 3	2.212	384.7	2663	1.214	7.456
370	0.9040	1.041 to 3	1.861	405.8	2671	1.271	7.394
373.15	1.0133	1.044 to 3	1.679	419.1	2676	1.307	7.356
375	1.0815	1.045 to 3	1.574	426.8	2679	1.328	7.333
380	1.2869	1.049 to 3	1.337	448.0	2687	1.384	7.275
385	1.5233	1.053 to 3	1.142	469.2	2694	1.439	7.210
390	1.794	1.058 to 3	0.980	490.4	2702	1.494	7.163
400	2.455	1.067 to 3	0.731	532.9	2716	1.605	7.058
410	3.302	1.077 to 3	0.553	575.6	2729	1.708	6.959
420	4.370	1.088 to 3	0.425	618.6	2742	1.810	6.865
430	5.699	1.099 to 3	0.331	661.8	2753	1.911	6.775
440	7.333	1.110 to 3	0.261	705.3	2764	2.011	6.689
450	9.319	1.123 to 3	0.208	749.2	2773	2.109	6.607
460	11.71	1.137 to 3	0.167	793.5	2782	2.205	6.528
470	14.55	1.152 to 3	0.136	838.2	2789	2.301	6.451
480	17.90	1.167 to 3	0.111	883.4	2795	2.395	6.377
490	21.83	1.184 to 3	0.0922	929.1	2799	2.479	6.312
500	26.40	1.203 to 3	0.0776	975.6	2801	2.581	6.233
510	31.66	1.222 to 3	0.0631	1023	2802	2.673	6.163
520	37.70	1.244 to 3	0.0525	1071	2801	2.765	6.093
530	44.58	1.268 to 3	0.0445	1119	2798	2.856	6.023
540	52.38	1.294 to 3	0.0375	1170	2792	2.948	5.953
550	61.19	1.323 to 3	0.0317	1220	2784	3.039	5.882
560	71.08	1.355 to 3	0.0269	1273	2772	3.132	5.808
570	82.16	1.392 to 3	0.0228	1328	2757	3.225	5.733
580	94.51	1.433 to 3	0.0193	1384	2737	3.321	5.654
590	108.3	1.482 to 3	0.0163	1443	2717	3.419	5.569
600	123.5	1.541 to 3	0.0137	1506	2682	3.520	5.480
610	137.3	1.612 to 3	0.0115	1573	2641	3.627	5.318
620	159.1	1.705 to 3	0.0094	1647	2588	3.741	5.259
625	169.1	1.778 to 3	0.0085	1697	2555	3.805	5.191
630	179.1	1.856 to 3	0.0075	1734	2515	3.875	5.115
635	190.9	1.935 to 3	0.0066	1783	2466	3.950	5.025
640	202.7	2.075 to 3	0.0057	1841	2401	4.037	4.912
645	215.2	2.351 to 3	0.0045	1931	2292	4.223	4.732
647.31	221.2	3.170 to 3	0.0032	2107	2107	4.443	4.443



# Conversions, Equivalents and Physical Data

**Table 28. Properties of Superheated Steam**

PRESSURE (psi)		SAT. TEMP. (°F)		TOTAL TEMPERATURE — °F (t)										
Absolute p <sup>a</sup>	Gauge p <sup>b</sup>			360°F	400°F	440°F	480°F	500°F	600°F	700°F	800°F	900°F	1000°F	1200°F
14.696	0.0	212.00	∇ h <sub>g</sub>	33.03 1221.1	34.68 1239.9	36.32 1258.8	37.96 1277.6	38.78 1287.1	42.86 1334.8	46.94 1383.2	51.00 1432.3	55.07 1482.3	59.13 1533.1	67.25 1637.5
20.0	5.3	227.96	∇ h <sub>g</sub>	24.21 1220.3	25.43 1239.2	26.65 1258.2	27.86 1277.1	28.46 1286.6	31.47 1334.4	34.47 1382.9	37.46 1432.1	40.45 1482.1	43.44 1533.0	49.41 1637.4
30.0	15.3	250.33	∇ h <sub>g</sub>	16.072 1218.6	16.897 1237.9	17.714 1257.0	18.528 1276.2	18.933 1285.7	20.95 1333.8	22.96 1382.4	24.96 1431.17	26.95 1481.8	28.95 1532.7	32.93 1637.2
40.0	25.3	267.25	∇ h <sub>g</sub>	12.001 1216.9	12.628 1236.5	13.247 1255.9	13.962 1275.2	14.168 1284.8	15.688 1333.1	17.198 1381.9	18.702 1431.3	20.20 1481.4	21.70 1532.4	24.69 1637.0
50.0	35.3	281.01	∇ h <sub>g</sub>	9.557 1215.2	10.065 1235.1	10.567 1254.7	11.062 1274.2	11.309 1283.9	12.532 1332.5	13.744 1381.4	14.950 1430.9	16.152 1481.1	17.352 1532.1	19.747 1636.8
60.0	45.3	292.71	∇ h <sub>g</sub>	7.927 1213.4	8.357 1233.6	8.779 1253.5	9.196 1273.2	9.403 1283.0	10.427 1331.8	11.441 1380.9	12.449 1430.5	13.452 1480.8	14.454 1531.9	16.451 1636.6
70.0	55.3	302.92	∇ h <sub>g</sub>	6.762 1211.5	7.136 1232.1	7.502 1252.3	7.863 1272.2	8.041 1282.0	8.924 1331.1	9.796 1380.4	10.662 1430.1	11.524 1480.5	12.383 1531.6	14.097 1636.3
80.0	65.3	312.03	∇ h <sub>g</sub>	5.888 1209.7	6.220 1230.7	6.544 1251.1	6.862 1271.1	7.020 1281.1	7.797 1330.5	8.562 1379.9	9.322 1429.7	10.077 1480.1	10.830 1531.3	12.332 1636.2
90.0	75.3	320.27	∇ h <sub>g</sub>	5.208 1207.7	5.508 1229.1	5.799 1249.8	6.084 1270.1	6.225 1280.1	6.920 1329.8	7.603 1379.4	8.279 1429.3	8.952 1479.8	9.623 1531.0	10.959 1635.9
100.0	85.3	327.81	∇ h <sub>g</sub>	4.663 1205.7	4.937 1227.6	5.202 1248.6	5.462 1269.0	5.589 1279.1	6.218 1329.1	6.835 1378.9	7.446 1428.9	8.052 1479.5	8.656 1530.8	9.860 1635.7
120.0	105.3	341.25	∇ h <sub>g</sub>	3.844 1201.6	4.081 1224.4	4.307 1246.0	4.527 1266.9	4.636 1277.2	5.165 1327.7	5.683 1377.8	6.195 1428.1	6.702 1478.8	7.207 1530.2	8.212 1635.3
140.0	125.3	353.02	∇ h <sub>g</sub>	3.258 1197.3	3.468 1221.1	3.667 1243.3	3.860 1264.7	3.954 1275.2	4.413 1326.4	4.861 1376.8	5.301 1427.2	5.738 1478.2	6.172 1529.7	7.035 1634.9
160.0	145.3	363.53	∇ h <sub>g</sub>	-----	3.008 1217.6	3.187 1240.6	3.359 1262.4	3.443 1273.1	3.849 1325.0	4.244 1375.7	4.631 1426.4	5.015 1477.5	5.396 1529.1	6.152 1634.5
180.0	165.3	373.06	∇ h <sub>g</sub>	-----	2.649 1214.0	2.813 1237.8	2.969 1260.2	3.044 1271.0	3.411 1323.5	3.964 1374.7	4.110 1425.6	4.452 1476.8	4.792 1528.6	5.466 1634.1
200.0	185.3	381.79	∇ h <sub>g</sub>	-----	2.361 1210.3	2.513 1234.9	2.656 1257.8	2.726 1268.9	3.060 1322.1	3.380 1373.6	3.693 1424.8	4.002 1476.2	4.309 1528.0	4.917 1633.7
220.0	205.3	389.86	∇ h <sub>g</sub>	-----	2.125 1206.5	2.267 1231.9	2.400 1255.4	2.465 1266.7	2.772 1320.7	3.066 1372.6	3.352 1424.0	3.634 1475.5	3.913 1527.5	4.467 1633.3
240.0	225.3	397.37	∇ h <sub>g</sub>	-----	1.9276 1202.5	2.062 1228.8	2.187 1253.0	2.247 1264.5	2.533 1319.2	2.804 1371.5	3.068 1432.2	3.327 1474.8	3.584 1526.9	4.093 1632.9
260.0	245.3	404.42	∇ h <sub>g</sub>	-----	-----	1.8882 1225.7	2.006 1250.5	2.063 1262.3	2.330 1317.7	2.582 1370.4	2.827 1422.3	3.067 1474.2	3.305 1526.3	3.776 1632.5
280.0	265.3	411.05	∇ h <sub>g</sub>	-----	-----	1.7388 1222.4	1.8512 1247.9	1.9047 1260.0	2.156 1316.2	2.392 1369.4	2.621 1421.5	2.845 1473.5	3.066 1525.8	3.504 1632.1
300.0	285.3	417.33	∇ h <sub>g</sub>	-----	-----	1.6090 1219.1	1.7165 1245.3	1.7675 1257.6	2.005 1314.7	2.227 1368.3	2.442 1420.6	2.652 1472.8	2.859 1525.2	3.269 1631.7
320.0	305.3	423.29	∇ h <sub>g</sub>	-----	-----	1.4950 1215.6	1.5985 1242.6	1.6472 1255.2	1.8734 1313.2	2.083 1367.2	2.285 1419.8	2.483 1472.1	2.678 1524.7	3.063 1631.3
340.0	325.3	428.97	∇ h <sub>g</sub>	-----	-----	1.3941 1212.1	1.4941 1239.9	1.5410 1252.8	1.7569 1311.6	1.9562 1366.1	2.147 1419.0	2.334 1471.5	2.518 1524.1	2.881 1630.9
360.0	345.3	434.40	∇ h <sub>g</sub>	-----	-----	1.3041 1208.4	1.4012 1237.1	1.4464 1250.3	1.6533 1310.1	1.8431 1365.0	2.025 1418.1	2.202 1470.8	2.376 1523.5	2.719 1630.5

∇ = specific volume, cubic feet per pound  
h<sub>g</sub> = total heat of steam, BTU per pound

- continued -

# Conversions, Equivalents and Physical Data

**Table 28. Properties of Superheated Steam (continued)**

PRESSURE (psi)		SAT. TEMP. °F	TOTAL TEMPERATURE – °F (t)											
Absolute P'	Gauge P		500°F	540°F	600°F	640°F	660°F	700°F	740°F	800°F	900°F	1000°F	1200°F	
380.0	365.3	439.60	∇ η <sub>g</sub>	1.3616 1247.7	1.4444 1273.1	1.5605 1308.5	1.6345 1331.0	1.6707 1342.0	1.7419 1363.8	1.8118 1385.3	1.9149 1417.3	2.083 1470.1	2.249 1523.0	2.575 1630.0
400.0	385.3	444.59	∇ h <sub>g</sub>	1.2851 1245.1	1.3652 1271.0	1.4770 1306.9	1.5480 1329.6	1.5827 1340.8	1.6508 1362.7	1.7177 1384.3	1.8161 1416.4	1.9767 1469.4	2.134 1522.4	2.445 1629.6
420.0	405.3	449.39	∇ h <sub>g</sub>	1.2158 1242.5	1.2935 1268.9	1.4014 1305.3	1.4697 1328.3	1.5030 1339.5	1.5684 1361.6	1.6324 1383.3	1.7267 1415.5	1.8802 1468.7	2.031 1521.9	2.327 1629.2
440.0	425.3	454.02	∇ h <sub>g</sub>	1.1526 1239.8	1.2282 1266.7	1.3327 1303.6	1.3984 1326.9	1.4306 1338.2	1.4934 1360.4	1.5549 1382.3	1.6454 1414.7	1.7925 1468.1	1.9368 1521.3	2.220 1628.8
460.0	445.3	458.5	∇ h <sub>g</sub>	1.0948 1237.0	1.1685 1264.5	1.2698 1302.0	1.3334 1325.4	1.3644 1336.9	1.4250 1359.3	1.4842 1381.3	1.5711 1413.8	1.7124 1467.4	1.8508 1520.7	2.122 1628.4
480.0	465.3	462.82	∇ h <sub>g</sub>	1.0417 1234.2	1.1138 1262.3	1.2122 1300.3	1.2737 1324.0	1.3038 1335.6	1.3622 1358.2	1.4193 1380.3	1.5031 1412.9	1.6390 1466.7	1.7720 1520.2	2.033 1628.0
500.0	485.3	467.01	∇ h <sub>g</sub>	0.9927 1231.3	1.0633 1260.0	1.1591 1298.6	1.2188 1322.6	1.2478 1334.2	1.3044 1357.0	1.3596 1379.3	1.4405 1412.1	1.5715 1466.0	1.6996 1519.6	1.9504 1627.6
520.0	505.3	471.07	∇ h <sub>g</sub>	0.9473 1228.3	1.0166 1257.7	1.1101 1296.9	1.1681 1321.1	1.1962 1332.9	1.2511 1355.8	1.3045 1378.2	1.3826 1411.2	1.5091 1465.3	1.636 1519.0	1.8743 1627.2
540.0	525.3	475.01	∇ h <sub>g</sub>	0.9052 1225.3	0.9733 1255.4	1.0646 1295.2	1.1211 1319.7	1.1485 1331.5	1.2017 1354.6	1.2535 1377.2	1.3291 1410.3	1.4514 1464.6	1.5707 1518.5	1.8039 1626.8
560.0	545.3	478.85	∇ h <sub>g</sub>	0.8659 1222.2	0.9330 1253.0	1.0224 1293.4	1.0775 1318.2	1.1041 1330.2	1.1558 1353.5	1.2060 1376.1	1.2794 1409.4	1.3978 1463.9	1.5132 1517.9	1.7385 1626.4
580.0	565.3	482.58	∇ h <sub>g</sub>	0.8291 1219.0	0.8954 1250.5	0.9830 1291.7	1.0368 1316.7	1.0627 1328.8	1.1331 1352.3	1.1619 1375.1	1.2331 1408.6	1.3479 1463.2	1.4596 1517.3	1.6776 1626.0
600.0	585.3	486.21	∇ h <sub>g</sub>	0.7947 1215.7	0.8602 1248.1	0.9463 1289.9	0.9988 1315.2	1.0241 1327.4	1.0732 1351.1	1.1207 1374.0	1.1899 1407.7	1.3013 1462.5	1.4096 1516.7	1.6208 1625.5
620.0	605.0	489.75	∇ h <sub>g</sub>	0.7624 1212.4	0.8272 1245.5	0.9118 1288.1	0.9633 1313.7	0.9880 1326.0	1.0358 1349.9	1.0821 1373.0	1.1494 1406.8	1.2577 1461.8	1.3628 1516.2	1.5676 1625.1
640.0	625.3	493.21	∇ h <sub>g</sub>	0.7319 1209.0	0.7963 1243.0	0.8795 1296.2	0.9299 1312.2	0.9541 1324.6	1.0008 1348.6	1.0459 1371.9	1.1115 1405.9	1.2168 1461.1	1.3190 1515.6	1.5178 1624.7
660.0	645.3	496.58	∇ h <sub>g</sub>	0.7032 1205.4	0.7670 1240.4	0.8491 1284.4	0.8985 1310.6	0.9222 1323.2	0.9679 1347.4	1.0119 1370.8	1.0759 1405.0	1.1784 1460.4	1.2778 1515.0	1.4709 1624.3
680.0	665.3	499.88	∇ h <sub>g</sub>	0.6759 1201.8	0.7395 1237.7	0.8205 1282.5	0.8690 1309.1	0.8922 1321.7	0.9369 1346.2	0.9800 1369.8	1.0424 1404.1	1.1423 1459.7	1.2390 1514.5	1.4269 1623.9
700.0	685.3	503.10	∇ h <sub>g</sub>	----- -----	0.7134 1235.0	0.7934 1280.6	0.8411 1307.5	0.8639 1320.3	0.9077 1345.0	0.9498 1368.7	1.0108 1403.2	1.1082 1459.0	1.2024 1513.9	1.3853 1623.5
750.	735.3	510.86	∇ h <sub>g</sub>	----- -----	0.6540 1227.9	0.7319 1275.7	0.7778 1303.5	0.7996 1316.6	0.8414 1341.8	0.8813 1366.0	0.9391 1400.9	1.0310 1457.2	1.1196 1512.4	1.2912 1622.4
800.0	785.3	518.23	∇ h <sub>g</sub>	----- -----	0.6015 1220.5	0.6779 1270.7	0.7223 1299.4	0.7433 1312.9	0.7833 1338.6	0.8215 1363.2	0.8763 1398.6	0.9633 1455.4	1.0470 1511.0	1.2088 1621.4
850.0	835.3	525.26	∇ h <sub>g</sub>	----- -----	0.5546 1212.7	0.6301 1265.5	0.6732 1295.2	0.6934 1309.0	0.7320 1335.4	0.7685 1360.4	0.8209 1396.3	0.9037 1453.6	0.9830 1509.5	1.1360 1620.4
90.0	885.3	531.98	∇ h <sub>g</sub>	----- -----	0.5124 1204.4	0.5873 1260.1	0.6294 1290.9	0.6491 1305.1	0.6863 1332.1	0.7215 1357.5	0.7716 1393.9	0.8506 1451.8	0.9262 1508.1	1.0714 1619.3
950.0	935.3	538.42	∇ h <sub>g</sub>	----- -----	0.4740 1195.5	0.5489 1254.6	0.5901 1286.4	0.6092 1301.1	0.6453 1328.7	0.6793 1354.7	0.7275 1391.6	0.8031 1450.0	0.8753 1506.6	1.0136 1618.3
1000.0	985.3	544.61	∇ h <sub>g</sub>	----- -----	----- -----	0.5140 1248.8	0.5546 1281.9	0.5733 1297.0	0.6084 1325.3	0.6413 1351.7	0.6878 1389.2	0.7604 1448.2	0.8294 1505.1	0.9615 1617.3

∇ = specific volume, cubic feet per pound  
h<sub>g</sub> = total heat of steam, BTU per pound

- continued -



# Conversions, Equivalents and Physical Data

Table 28. Properties of Superheated Steam (continued)

PRESSURE (psi)		SAT. TEMP. °F	TOTAL TEMPERATURE — °F (t)											
Absolute p'	Gauge			660°F	700°F	740°F	760°F	780°F	800°F	860°F	900°F	1000°F	1100°F	1200°F
1100.0	1085.3	556.31	∇ h <sub>g</sub>	0.5110 1288.5	0.5445 1318.3	0.5755 1345.8	0.5904 1358.9	0.6049 1371.7	0.6191 1384.3	0.6601 1420.8	0.6866 1444.5	0.7503 1502.2	0.8117 1558.8	0.8716 1615.2
1200.0	1185.3	567.22	∇ h <sub>g</sub>	0.4586 1279.6	0.4909 1311.0	0.5206 1339.6	0.5347 1353.2	0.5484 1366.4	0.5617 1379.3	0.6003 1416.7	0.6250 1440.7	0.6843 1499.2	0.7412 1556.4	0.7967 1613.1
1300.0	1285.3	577.46	∇ h <sub>g</sub>	0.4139 1270.2	0.4454 1303.4	0.4739 1333.3	0.4874 1347.3	0.5004 1361.0	0.5131 1374.3	0.5496 1412.5	0.5728 1437.0	0.6284 1496.2	0.6816 1553.9	0.7333 1611.0
1400.0	1385.3	587.10	∇ h <sub>g</sub>	0.3753 1260.3	0.4062 1295.5	0.4338 1326.7	0.4468 1341.3	0.4593 1355.4	0.4714 1369.1	0.5061 1408.2	0.5281 1433.1	0.5805 1493.2	0.6305 1551.4	0.6789 1608.9
1500.0	1485.3	596.23	∇ h <sub>g</sub>	0.3413 1249.8	0.3719 1287.2	0.3989 1320.0	0.4114 1335.2	0.4235 1349.7	0.4352 1363.8	0.4684 1403.9	0.4893 1429.3	0.5390 1490.1	0.5862 1548.9	0.6318 1606.8
1600.0	1585.3	604.90	∇ h <sub>g</sub>	0.3112 1238.7	0.3417 1278.7	0.3682 1313.0	0.3804 1328.8	0.3921 1343.9	0.4034 1358.4	0.4353 1399.5	0.4553 1425.3	0.5027 1487.0	0.5474 1546.4	0.5906 1604.6
1700.0	1685.3	613.15	∇ h <sub>g</sub>	0.2842 1226.8	0.3148 1269.7	0.3410 1305.8	0.3529 1322.3	0.3643 1337.9	0.3753 1352.9	0.4061 1395.0	0.4253 1421.4	0.4706 1484.0	0.5132 1543.8	0.5542 1602.5
1800.0	1785.3	621.03	∇ h <sub>g</sub>	0.2597 1214.0	0.2907 1260.3	0.3166 1298.4	0.3284 1315.5	0.3395 1331.8	0.3502 1347.2	0.3801 1390.4	0.3986 1417.4	0.4421 1480.8	0.4828 1541.3	0.5218 1600.4
1900.0	1885.3	628.58	∇ h <sub>g</sub>	0.2371 1200.2	0.2688 1250.4	0.2947 1290.6	0.3063 1308.6	0.3171 1325.4	0.3277 1341.5	0.3568 1385.8	0.3747 1413.3	0.4165 1477.7	0.4556 1538.8	0.4929 1598.2
2000.0	1985.3	635.82	∇ h <sub>g</sub>	0.2161 1184.9	0.2489 1240.0	0.2748 1282.6	0.2863 1301.4	0.2972 1319.0	0.3074 1335.5	0.3358 1381.2	0.3532 1409.2	0.3935 1474.5	0.4311 1536.2	0.4668 1596.1
2100.0	2085.3	642.77	∇ h <sub>g</sub>	0.1962 1167.7	0.2306 1229.0	0.2567 1274.3	0.2682 1294.0	0.2789 1312.3	0.2890 1329.5	0.3167 1376.4	0.3337 1405.0	0.3727 1471.4	0.4089 1533.6	0.4433 1593.9
2200.0	2185.3	649.46	∇ h <sub>g</sub>	0.1768 1147.8	0.2135 1217.4	0.2400 1265.7	0.2514 1286.3	0.2621 1305.4	0.2721 1323.3	0.2994 1371.5	0.3159 1400.8	0.3538 1468.2	0.3887 1531.1	0.4218 1591.8
2300.0	2285.3	655.91	∇ h <sub>g</sub>	0.1575 1123.8	0.1978 1204.9	0.2247 1256.7	0.2362 1278.4	0.2468 1298.4	0.2567 1316.9	0.2835 1366.6	0.2997 1396.5	0.3365 1464.9	0.3703 1528.5	0.4023 1589.6
2400.0	2385.3	662.12	∇ h <sub>g</sub>	----	0.1828 1191.5	0.2105 1247.3	0.2221 1270.2	0.2327 1291.1	0.2425 1310.3	0.2689 1361.6	0.2848 1392.2	0.3207 1461.7	0.3534 1525.9	0.3843 1587.4
2500.0	2485.3	668.13	∇ h <sub>g</sub>	----	0.1686 1176.8	0.1973 1207.6	0.2090 1261.8	0.2196 1283.6	0.2294 1303.6	0.2555 1356.5	0.2710 1387.8	0.3061 1458.4	0.3379 1523.2	0.3678 1585.3
2600.0	2585.3	673.94	∇ h <sub>g</sub>	----	0.1549 1160.6	0.1849 1227.3	0.1967 1252.9	0.2074 1275.8	0.2172 1296.8	0.2431 1351.4	0.2584 1383.4	0.2926 1455.1	0.3236 1520.6	0.3526 1583.1
2700.0	2685.3	679.55	∇ h <sub>g</sub>	----	0.1415 1142.5	0.1732 1216.5	0.1853 1243.8	0.1960 1267.9	0.2059 1289.7	0.2315 1346.1	0.2466 1378.9	0.2801 1451.8	0.3103 1518.0	0.3385 1580.9
2800.0	2785.3	684.99	∇ h <sub>g</sub>	----	0.1281 1121.4	0.1622 1205.1	0.1745 1234.2	0.1854 1259.6	0.1953 1282.4	0.2208 1340.8	0.2356 1374.3	0.2685 1448.5	0.2979 1515.4	0.3254 1578.7
2900.0	2885.3	690.26	∇ h <sub>g</sub>	----	0.1143 1095.9	0.1517 1193.0	0.1644 1224.3	0.1754 1251.1	0.1853 1274.9	0.2108 1335.3	0.2254 1369.7	0.2577 1445.1	0.2864 1512.7	0.3132 1576.5
3000.0	2985.3	695.36	∇ h <sub>g</sub>	----	0.0984 1060.7	0.1416 1180.1	0.1548 1213.8	0.1660 1242.2	0.1760 1267.2	0.2014 1329.7	0.2159 1365.0	0.2476 1441.8	0.2757 1510.0	0.3018 1574.3
3100.0	3085.3	700.31	∇ h <sub>g</sub>	----	----	0.1320 1166.2	0.1456 1202.9	0.1571 1233.0	0.1672 1259.3	0.1926 1324.1	0.2070 1360.3	0.2382 1438.4	0.2657 1507.4	0.2911 1572.1
3200.0	3185.3	705.11	∇ h <sub>g</sub>	----	----	0.1226 1151.1	0.1369 1191.4	0.1486 1223.5	0.1589 1251.1	0.1843 1318.3	0.1986 1355.5	0.2293 1434.9	0.2563 1504.7	0.2811 1569.9
3206.2	3191.5	705.40	∇ h <sub>g</sub>	----	----	0.1220 1150.2	0.1363 1190.6	0.1480 1222.9	0.1583 1250.5	0.1838 1317.9	0.1981 1355.2	0.2288 1434.7	0.2557 1504.5	0.2806 1569.8

∇ = specific volume, cubic feet per pound  
h<sub>g</sub> = total heat of steam, BTU per pound

# Conversions, Equivalents and Physical Data

## Determine Velocity of Steam in Pipes:

$$\text{Velocity (ft/s)} = \frac{(25) (A)}{(V)}$$

Where: A = Nominal pipe section area =  $\frac{\pi (d)^2}{4}$   
 d = Diameter

V = Specific volume from steam tables in ft<sup>3</sup>/lb (m<sup>3</sup>/kg)

**Note:** Specific volume changes with steam pressure and temperature. Make sure to calculate velocities of inlet and outlet piping of the regulator.

**Table 29. Recommended Steam Pipe Line Velocities**

STEAM CONDITION	VELOCITY, FT/SEC / M/SEC
0 to 15 psig / 0 to 1.0 bar, Dry and saturated	100 / 30.5
15 psig / 1.0 bar, Dry and saturated and up	175 / 53.3
200 psig / 13.8 bar, Superheated and up	250 / 76.2

**Table 30. Typical Condensation Rates In Insulated Steam Pipes**

PRESSURE		RATES IN LBS/HR / KG/HR PER FOOT OF PIPE WITH 2 IN. OF INSULATION											
		Pipe Diameter in In.											
		3/4		1		1-1/2		2		3		4	
psig	bar	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr
1	0.069	0.02	0.009	0.03	0.014	0.03	0.014	0.04	0.018	0.05	0.023	0.06	0.027
5	0.34	0.03	0.014	0.03	0.014	0.04	0.018	0.04	0.018	0.05	0.023	0.06	0.027
10	0.69	0.03	0.014	0.03	0.014	0.04	0.018	0.04	0.018	0.05	0.023	0.07	0.032
25	1.7	0.03	0.014	0.04	0.018	0.05	0.023	0.05	0.023	0.06	0.027	0.08	0.036
50	3.4	0.04	0.018	0.04	0.018	0.05	0.023	0.06	0.027	0.09	0.041	0.11	0.05
75	5.2	0.04	0.018	0.05	0.023	0.06	0.027	0.07	0.032	0.11	0.05	0.14	0.064
100	6.9	0.05	0.023	0.05	0.023	0.07	0.032	0.08	0.036	0.12	0.054	0.15	0.068
125	8.6	0.05	0.023	0.06	0.027	0.07	0.032	0.08	0.036	0.13	0.059	0.16	0.073
150	10.3	0.06	0.027	0.06	0.027	0.08	0.036	0.09	0.041	0.14	0.064	0.17	0.077
200	13.8	0.06	0.027	0.07	0.032	0.08	0.036	0.09	0.041	0.15	0.068	0.19	0.086

**Table 31. Typical Condensation Rates In Steam Pipes Without Insulation**

PRESSURE		RATES IN LBS/HR / KG/HR PER FOOT OF BARE PIPE AT 72°F / 22°C AMBIENT AIR											
		Pipe Diameter in In.											
		3/4		1		1-1/2		2		3		4	
psig	bar	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr	lbs/hr	kg/hr
1	0.069	0.11	0.05	0.15	0.068	0.21	0.095	0.25	0.113	0.38	0.172	0.46	0.209
5	0.34	0.14	0.064	0.16	0.073	0.22	0.1	0.26	0.118	0.41	0.186	0.50	0.227
10	0.69	0.15	0.068	0.18	0.082	0.24	0.109	0.29	0.132	0.44	0.2	0.53	0.24
25	1.7	0.17	0.077	0.22	0.1	0.31	0.141	0.36	0.163	0.53	0.24	0.65	0.295
50	3.4	0.22	0.1	0.27	0.122	0.39	0.177	0.46	0.209	0.66	0.299	0.83	0.376
75	5.2	0.26	0.118	0.31	0.141	0.45	0.204	0.54	0.245	0.77	0.349	1.04	0.472
100	6.9	0.29	0.132	0.35	0.159	0.50	0.227	0.61	0.277	0.86	0.39	1.11	0.503
125	8.6	0.32	0.145	0.39	0.177	0.55	0.249	0.68	0.308	0.94	0.426	1.23	0.558
150	10.3	0.35	0.159	0.42	0.191	0.60	0.272	0.74	0.336	1.03	0.467	1.33	0.603
200	13.8	0.40	0.181	0.49	0.222	0.69	0.313	0.81	0.367	1.19	0.54	1.50	0.68

# Conversions, Equivalents and Physical Data

**Table 32. Flow of Water Through Schedule 40 Steel Pipes**

DISCHARGE		PRESSURE DROP PER 100 FT AND VELOCITY IN SCHEDULE 40 PIPE FOR WATER AT 60°F															
Gal/min	Ft <sup>3</sup> /Sec	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)
		1/8 in.		1/4 in.		3/8 in.		1/2 in.		3/4 in.		1 in.		1-1/4 in.		1-1/2 in.	
0.2	0.000446	1.13	1.86	0.616	0.359												
0.3	0.000668	1.69	4.22	0.924	0.903	0.504	0.159	0.317	0.061								
0.4	0.000891	2.26	6.98	1.23	1.61	0.672	0.345	0.422	0.086								
0.5	0.00111	2.82	10.5	1.54	2.39	0.840	0.539	0.528	0.167	0.301	0.033						
0.6	0.00134	3.39	14.7	1.85	3.29	1.01	0.751	0.633	0.240	0.361	0.041						
0.8	0.00178	4.52	25.0	2.46	5.44	1.34	1.25	0.844	0.408	0.481	0.102						
1	0.00223	5.65	37.2	3.08	8.28	1.68	1.85	1.06	0.600	0.602	0.155	0.371	0.048				
2	0.00446	11.29	134.4	6.16	30.1	3.36	6.58	2.11	2.10	1.20	0.526	0.743	0.164	0.429	0.044		
3	0.00668			9.25	64.1	5.04	13.9	3.17	4.33	1.81	1.09	1.114	0.336	0.644	0.090	0.473	0.043
4	0.00891			12.33	111.2	6.72	23.9	4.22	7.42	2.41	1.83	1.49	0.565	0.858	0.150	0.630	0.071
5	0.01114	2 in.				8.40	36.7	5.28	11.2	3.01	2.75	1.86	0.835	1.073	0.223	0.788	0.104
6	0.01337	0.574	0.044	2-1/2 in.		10.08	51.9	6.33	15.8	3.61	3.84	2.23	1.17	1.29	0.309	0.943	0.145
8	0.01782	0.765	0.073			13.44	91.1	8.45	27.7	4.81	6.60	2.97	1.99	1.72	0.518	1.26	0.241
10	0.02228	0.956	0.108	0.670	0.046	3 in.		10.56	42.4	6.02	9.99	3.71	2.99	2.15	0.774	1.58	0.361
15	0.03342	1.43	0.224	1.01	0.094					9.03	21.6	5.57	6.36	3.22	1.63	2.37	0.755
20	0.04456	1.91	3.375	1.34	0.158	0.868	0.056	3-1/2 in.		12.03	37.8	7.43	10.9	4.29	2.78	3.16	1.28
25	0.05570	2.39	0.561	1.68	0.234	1.09	0.083	0.812	0.041	4 in.		9.28	16.7	5.37	4.22	3.94	1.93
30	0.06684	2.87	0.786	2.01	0.327	1.30	0.114	0.974	0.056			11.14	23.8	6.44	5.92	4.73	2.72
35	0.07798	3.35	1.05	2.35	0.436	1.52	0.151	1.14	0.071	0.882	0.041	12.99	32.2	7.51	7.90	5.52	3.64
40	0.08912	3.83	1.35	2.68	0.556	1.74	0.192	1.30	0.095	1.01	0.052	14.85	41.5	8.59	10.24	6.30	4.65
45	0.1003	4.30	1.67	3.02	0.668	1.95	0.239	1.46	0.117	1.13	0.064			9.67	12.80	7.09	5.85
50	0.1114	4.78	2.03	3.35	0.839	2.17	0.288	1.62	0.142	1.26	0.076			10.74	15.66	7.88	7.15
60	0.1337	5.74	2.87	4.02	1.18	2.60	0.46	1.95	0.204	1.51	0.107	5 in.		12.89	22.2	9.47	10.21
70	0.1560	6.70	3.84	4.69	1.59	3.04	0.540	2.27	0.261	1.76	0.143	1.12	0.047			11.05	13.71
80	0.1782	7.65	4.97	5.36	2.03	3.47	0.687	2.60	0.334	2.02	0.180	1.28	0.060			12.62	17.59
90	0.2005	8.60	6.20	6.03	2.53	3.91	0.861	2.92	0.416	2.27	0.224	1.44	0.074	6 in.		14.20	22.0
100	0.2228	9.56	7.59	6.70	3.09	4.34	1.05	3.25	0.509	2.52	0.272	1.60	0.090	1.11	0.036	15.778	26.9
125	0.2785	11.97	11.76	8.38	4.71	5.43	1.61	4.06	0.769	3.15	0.415	2.01	0.135	1.39	0.055	19.72	41.4
150	0.3342	14.36	16.70	10.05	6.69	6.51	2.24	4.87	1.08	3.78	0.580	2.41	0.190	1.67	0.077		
175	0.3899	16.75	22.3	11.73	8.97	7.60	3.00	5.68	1.44	4.41	0.774	2.81	0.253	1.94	0.102		
200	0.4456	19.14	28.8	13.42	11.68	8.68	3.87	6.49	1.85	5.04	0.985	3.21	0.323	2.22	0.130	8 in.	
225	0.5013	----	----	15.09	14.63	9.77	4.83	7.30	2.32	5.67	1.23	3.61	0.401	2.50	0.162	1.44	0.043
250	0.557	----	----	----	----	10.85	5.93	8.12	2.84	6.30	1.46	4.01	0.495	2.78	0.195	1.60	0.051
275	0.6127	----	----	----	----	11.94	7.14	8.93	3.40	6.93	1.79	4.41	0.583	3.05	0.234	1.76	0.061
300	0.6684	----	----	----	----	13.00	8.36	9.74	4.02	7.56	2.11	4.81	0.683	3.33	0.275	1.92	0.072
325	0.7241	----	----	----	----	14.12	9.89	10.53	4.09	8.19	2.47	5.21	0.797	3.61	0.320	2.08	0.083
350	0.7798			----	----	----	----	11.36	5.51	8.82	2.84	5.62	0.919	3.89	0.367	2.24	0.095
375	0.8355			----	----	----	----	12.17	6.18	9.45	3.25	6.02	1.05	4.16	0.416	2.40	0.108
400	0.8912			----	----	----	----	12.98	7.03	10.08	3.68	6.42	1.19	4.44	0.471	2.56	0.121
425	0.9469			----	----	----	----	13.80	7.89	10.71	4.12	6.82	1.33	4.72	0.529	2.73	0.136
450	1.003	10 in.		----	----	----	----	14.61	8.80	11.34	4.60	7.22	1.48	5.00	0.590	2.89	0.151
475	1.059	1.93	0.054			----	----	----	----	11.97	5.12	7.62	1.64	5.27	0.653	3.04	0.166
500	1.114	2.03	0.059			----	----	----	----	12.60	5.65	8.02	1.81	5.55	0.720	3.21	0.182
550	1.225	2.24	0.071			----	----	----	----	13.85	6.79	8.82	2.17	6.11	0.861	3.53	0.219
600	1.337	2.44	0.083			----	----	----	----	15.12	8.04	9.63	2.55	6.66	1.02	3.85	0.258
650	1.448	2.64	0.097			----	----	----	----	----	----	10.43	2.98	7.22	1.18	4.17	0.301

- continued -

# Conversions, Equivalents and Physical Data

**Table 32. Flow of Water Through Schedule 40 Steel Pipes (continued)**

DISCHARGE		PRESSURE DROP PER 100 FT AND VELOCITY IN SCHEDULE 40 PIPE FOR WATER AT 60°F															
Gal/min	Ft <sup>3</sup> /Sec	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)	Velocity (Ft/Sec)	Pressure Drop (psi)
		10 In.		12 In.		14 In.				5 In.		6 In.		8 In.			
700	1.560	2.85	0.112	2.01	0.047							11.23	3.43	7.78	1.35	4.49	0.343
750	1.671	3.05	0.127	2.15	0.054							12.03	3.92	8.33	1.55	4.81	0.392
800	1.782	3.25	0.143	2.29	0.061							12.83	4.43	8.88	1.75	5.13	0.443
850	1.894	3.46	0.160	2.44	0.068	2.02	0.042					13.64	5.00	9.44	1.96	5.45	0.497
900	2.005	3.66	0.179	2.58	0.075	2.13	0.047					14.44	5.58	9.99	2.18	5.77	0.554
950	2.117	3.86	0.198	2.72	0.083	2.25	0.052					15.24	6.21	10.55	2.42	6.09	0.613
1000	2.228	4.07	0.218	2.87	0.091	2.37	0.057					16.04	6.84	11.10	2.68	6.41	0.675
1100	2.451	4.48	0.260	3.15	0.110	2.61	0.068	16 In.				17.65	8.23	12.22	3.22	7.05	0.807
1200	2.674	4.88	0.306	3.44	0.128	2.85	0.800	2.18	0.042					13.33	3.81	7.70	0.948
1300	2.896	5.29	0.355	3.73	0.150	3.08	0.093	2.36	0.048					14.43	4.45	8.33	1.11
1400	3.119	5.70	0.409	4.01	0.171	3.32	0.107	2.54	0.055					15.55	5.13	8.98	1.28
1500	3.342	6.10	0.466	4.30	0.195	3.56	0.122	2.72	0.063	18 In.				16.66	5.85	9.62	1.46
1600	3.565	6.51	0.527	4.59	0.219	3.79	0.138	2.90	0.071					17.77	6.61	10.26	1.65
1800	4.010	7.32	0.663	5.16	0.276	4.27	0.172	3.27	0.088	2.58	0.050			19.99	8.37	11.54	2.08
2000	4.456	8.14	0.808	5.73	0.339	4.74	0.209	3.63	0.107	2.87	0.060			22.21	10.3	12.82	2.55
2500	5.570	10.17	1.24	7.17	0.515	5.93	0.321	4.54	0.163	3.59	0.091	20 In.				16.03	3.94
3000	6.684	12.20	1.76	8.60	0.731	7.11	0.451	5.45	0.232	4.30	0.129	3.46	0.075	24 In.		19.24	5.59
3500	7.798	14.24	2.38	10.03	0.982	8.30	0.607	6.35	0.312	5.02	0.173	4.04	0.101			22.44	7.56
4000	8.912	16.27	3.08	11.47	1.27	9.48	0.787	7.26	0.401	5.74	0.222	4.62	0.129	3.19	0.052	25.65	9.80
4500	10.03	18.31	3.87	12.90	1.60	10.67	0.990	8.17	0.503	6.46	0.280	5.20	0.162	3.59	0.065	28.87	12.2
5000	11.14	20.35	4.71	14.33	1.95	11.85	1.21	9.08	0.617	7.17	0.340	5.77	0.199	3.99	0.079	----	----
6000	13.37	24.41	6.74	17.20	2.77	14.23	1.71	10.89	0.877	8.61	0.483	6.93	0.280	4.79	0.111	----	----
7000	15.60	28.49	9.11	20.07	3.74	16.60	2.31	12.71	1.18	10.04	0.652	8.08	0.376	5.59	0.150	----	----
8000	17.82	----	----	22.93	4.84	18.96	2.99	14.52	1.51	11.47	0.839	9.23	0.488	6.38	0.192	----	----
9000	20.05	----	----	25.79	6.09	21.34	3.76	16.34	1.90	12.91	1.05	10.39	0.608	7.18	0.242	----	----
10,000	22.28	----	----	28.66	7.46	23.71	4.61	18.15	2.34	14.34	1.28	11.54	0.739	7.98	0.294	----	----
12,000	26.74	----	----	34.40	10.7	28.45	6.59	21.79	3.33	17.21	1.83	13.85	1.06	9.58	0.416	----	----
14,000	31.19	----	----	----	----	33.19	8.89	25.42	4.49	20.08	2.45	16.16	1.43	11.17	0.562	----	----
16,000	35.65	----	----	----	----	----	----	29.05	5.83	22.95	3.18	18.47	1.85	12.77	0.723	----	----
18,000	40.10	----	----	----	----	----	----	32.68	7.31	25.82	4.03	20.77	2.32	14.36	0.907	----	----
20,000	44.56	----	----	----	----	----	----	36.31	9.03	28.69	4.93	23.08	2.86	15.96	1.12	----	----

For pipe lengths other than 100 ft., the pressure drop is proportional to the length. Thus, for 50 ft. of pipe, the pressure drop is approximately one half the value given in the table or 300 ft., three times the given value, etc.  
 Velocity is a function of the cross sectional flow area; thus, it is constant for a given flow rate and is independent of pipe length.  
 Extracted from Technical Paper No. 410, Flow of Fluids, with permission of Crane Co.



# Conversions, Equivalents and Physical Data

**Table 33. Flow of Air Through Schedule 40 Steel Pipes**

FREE AIR Q <sup>m</sup> Ft <sup>3</sup> /min at 60°F and 14.7 psia	COMPRESSED AIR Ft <sup>3</sup> /min at 60°F and 100 psig	PRESSURE DROP OF AIR IN PSI PER 100 FT OF SCHEDULE 40 PIPE FOR AIR AT 100 PSIG PRESSURE AND 60°F TEMPERATURE								
		1/8 in.	1/4 in.	3/8 in.	1/2 in.	3/4 in.	1 in.	1-1/4 in.	1-1/2 in.	2 in.
1	0.128	0.361	0.083	0.018						
2	0.256	1.31	0.285	0.064	0.020					
3	0.384	3.06	0.605	0.133	0.042					
4	0.513	4.83	1.04	0.226	0.071					
5	0.641	7.45	1.58	0.343	0.106	0.027				
6	0.769	10.6	2.23	0.408	0.148	0.037				
8	1.025	18.6	3.89	0.848	0.255	0.062	0.019			
10	0.282	28.7	5.96	1.26	0.356	0.094	0.029			
15	1.922	----	13.0	2.73	0.834	0.201	0.062			
20	2.563	----	22.8	4.76	1.43	0.345	0.102	0.026		
25	3.204	----	35.6	7.34	2.21	0.526	0.156	0.039	0.019	
30	3.845	----	----	10.5	3.15	0.748	0.219	0.055	0.026	
35	4.486	----	----	14.2	4.24	1.00	0.293	0.073	0.035	
40	5.126	----	----	18.4	5.49	1.30	0.379	0.095	0.044	
45	5.767	----	----	23.1	6.90	1.62	0.474	0.116	0.055	
50	6.408			28.5	8.49	1.99	0.578	0.149	0.067	0.019
60	7.690	<b>2-1/2 in.</b>		40.7	12.2	2.85	0.819	0.200	0.094	0.027
70	8.971			----	16.5	3.83	1.10	0.270	0.126	0.036
80	10.25	0.019		----	21.4	4.96	1.43	0.350	0.162	0.046
90	11.53	0.023		----	27.0	6.25	1.80	0.437	0.203	0.058
100	12.82	0.029	<b>3 in.</b>		33.2	7.69	2.21	0.534	0.247	0.070
125	16.02	0.044			----	11.9	3.39	0.825	0.380	0.107
150	19.22	0.062	0.021		----	17.0	4.87	1.17	0.537	0.151
175	22.43	0.083	0.028	<b>3-1/2 in.</b>	----	23.1	6.60	1.58	0.727	0.205
200	25.63	0.107	0.036		----	30.0	8.54	2.05	0.937	0.264
225	28.84	0.134	0.045	0.022		37.9	10.8	2.59	1.19	0.331
250	32.04	0.164	0.055	0.027		----	13.3	3.18	1.45	0.404
275	35.24	0.191	0.066	0.032		----	16.0	3.83	1.75	0.484
300	38.45	0.232	0.078	0.037		----	19.0	4.56	2.07	0.573
325	41.65	0.270	0.090	0.043	<b>4 in.</b>	----	22.3	5.32	2.42	0.673
350	44.87	0.313	0.104	0.050		----	25.8	6.17	2.80	0.776
375	48.06	0.356	0.119	0.057	0.030	----	29.6	7.05	3.20	0.887
400	51.26	0.402	0.134	0.064	0.034	----	33.6	8.02	3.64	1.00
425	54.47	0.452	0.151	0.072	0.038	----	37.9	9.01	4.09	1.13
450	57.67	0.507	0.168	0.081	0.042	----	----	10.2	4.59	1.26
475	60.88	0.562	0.187	0.089	0.047		----	11.3	5.09	1.40
500	64.08	0.623	0.206	0.099	0.052		----	12.5	5.61	1.55
550	70.49	0.749	0.248	0.118	0.062		----	15.1	6.79	1.87
600	76.90	0.887	0.293	0.139	0.073	<b>5 in.</b>	----	18.0	8.04	2.21
650	83.30	1.04	0.342	0.163	0.086		----	21.1	9.43	2.60
700	89.71	1.19	0.395	0.188	0.099	0.032		24.3	10.9	3.00
750	96.12	1.36	0.451	0.214	0.113	0.036		27.9	12.6	3.44
800	102.5	1.55	0.513	0.244	0.127	0.041		31.8	14.2	3.90
850	108.9	1.74	0.576	0.274	0.144	0.046	<b>6 in.</b>	35.9	16.0	4.40
900	115.3	1.95	0.642	0.305	0.160	0.051		40.2	18.0	4.91
950	121.8	2.18	0.715	0.340	0.178	0.057	0.023	----	20.0	5.47
1000	128.2	2.40	0.788	0.375	0.197	0.063	0.025	----	22.1	6.06
1100	141.0	2.89	0.948	0.451	0.236	0.075	0.030	----	26.7	7.29
1200	153.8	3.44	1.13	0.533	0.279	0.089	0.035	----	31.8	8.63
1300	166.6	4.01	1.32	0.626	0.327	0.103	0.041	----	37.3	10.1

- continued -

# Conversions, Equivalents and Physical Data

**Table 33. Flow of Air Through Schedule 40 Steel Pipes (continued)**

FREE AIR Q <sup>m</sup> Ft <sup>3</sup> /min at 60°F and 14.7 psia	COMPRESSED AIR Ft <sup>3</sup> /min at 60°F and 100 psig	PRESSURE DROP OF AIR IN PSI PER 100 FT OF SCHEDULE 40 PIPE FOR AIR AT 100 PSIG PRESSURE AND 60°F TEMPERATURE								
		2-1/2 In.	3 In.	3-1/2 In.	4 In.	5 In.	6 In.	8 In.	10 In.	12 In.
1400	179.4	4.65	1.52	0.718	0.377	0.119	0.047			11.8
1500	192.2	5.31	1.74	0.824	0.431	0.136	0.054			13.5
1600	205.1	6.04	1.97	0.932	0.490	0.154	0.061			15.3
1800	230.7	7.65	2.50	1.18	0.616	0.193	0.075			19.3
2000	256.3	9.44	3.06	1.45	0.757	0.237	0.094	0.023		23.9
2500	320.4	14.7	4.76	2.25	1.17	0.366	0.143	0.035		37.3
3000	384.5	21.1	6.82	3.20	1.67	0.524	0.204	0.051	0.016	
3500	448.6	28.8	9.23	4.33	2.26	0.709	0.276	0.068	0.022	
4000	512.6	37.6	12.1	5.66	2.94	0.919	0.358	0.088	0.028	12 In.
4500	576.7	47.6	15.3	7.16	3.69	1.16	0.450	0.111	0.035	
5000	640.8	----	18.8	8.85	4.56	1.42	0.552	0.136	0.043	0.018
6000	769.0	----	27.1	12.7	6.57	2.03	0.794	0.195	0.061	0.025
7000	897.1	----	36.9	17.2	8.94	2.76	1.07	0.262	0.082	0.034
8000	1025	----	----	22.5	11.7	3.59	1.39	0.339	0.107	0.044
9000	1153	----	----	28.5	14.9	4.54	1.76	0.427	0.134	0.055
10,000	1282	----	----	35.2	18.4	5.60	2.16	0.526	0.164	0.067
11,000	1410	----	----	----	22.2	6.78	2.62	0.633	0.197	0.081
12,000	1538	----	----	----	26.4	8.07	3.09	0.753	0.234	0.096
13,000	1666	----	----	----	31.0	9.47	3.63	0.884	0.273	0.112
14,000	1794	----	----	----	36.0	11.0	4.21	1.02	0.316	0.129
15,000	1922	----	----	----	----	12.6	4.84	1.17	0.364	0.148
16,000	2051	----	----	----	----	14.3	5.50	1.33	0.411	0.167
18,000	2307	----	----	----	----	18.2	6.96	1.68	0.520	0.213
20,000	2563	----	----	----	----	22.4	8.60	2.01	0.642	0.260
22,000	2820	----	----	----	----	27.1	10.4	2.50	0.771	0.314
24,000	3076	----	----	----	----	32.3	12.4	2.97	0.918	0.371
26,000	3332	----	----	----	----	37.9	14.5	3.49	1.12	0.435
28,000	3588	----	----	----	----	----	16.9	4.04	1.25	0.505
30,000	3845	----	----	----	----	----	19.3	4.64	1.42	0.520

Extracted from Technical Paper No. 410, Flow of Fluids, with permission of Crane Co.



# Conversions, Equivalents and Physical Data

**Table 34. Average Properties of Propane**

Formula	C <sub>3</sub> H <sub>8</sub>
Boiling Point, °F / °C	-44 / -42
Specific Gravity of Gas (Air = 1.00)	1.53
Lbs/Gal of Liquid at 60°F / 16°C	4.24
BTU/Gal of Gas at 60°F / 16°C	91,547
BTU/Lb of Gas	21,591
BTU/Ft <sup>3</sup> of Gas at 60°F / 16°C	2516
Ft <sup>3</sup> of Vapor at 60°F / 16°C per Gal. of Liquid at 60°F / 16°C	36.39
Ft <sup>3</sup> of Vapor at 60°F / 16°C per Lb. of Liquid at 60°F / 16°C	8.547
Latent Heat of Vaporization at Boiling Point, BTU per Gallon	785.0
<b>Combustion Data</b>	
Ft <sup>3</sup> of Air Required to Burn 1 Ft <sup>3</sup> of Gas	23.86
Flash Point, °F / °C	-156 / -104
Ignition Temperature in Air, °F / °C	920 to 1020 / 493 to 549
Maximum Flame Temperature in Air, °F / °C	3595 / 1979
<b>Limits of Inflammability, Percentage of Gas in Air Mixture</b>	
at Lower Limit	2.4%
at Upper Limit	9.6%
Octane Number (ISO Octane = 100)	Over 100

**Table 35. Standard Domestic Propane Tank Specifications**

CAPACITY		DIAMETER		LENGTH		TANK WEIGHT	
gal	l	in.	mm	in.	mm	lbs	kg
120	454	24	610	68	1727	288	131
150	568	24	610	84	2134	352	160
200	757	30	762	79	2007	463	210
250	946	30	762	94	2387	542	246
325	1230	30	762	119	3023	672	305
500	1893	37	940	119	3023	1062	482
1000	3785	41	1041	192	4877	1983	900

**Table 36. Approximate Vaporization Capacities of Propane Tanks**

BTU PER HOUR WITH 40% LIQUID IN DOMESTIC TANK SYSTEMS		
Tank Size Water Capacity	Prevailing Air Temperature	
	20°F / -7°C	60°F / 16°C
120	235,008	417,792
150	290,304	516,096
200	341,280	606,720
250	406,080	721,920
325	514,100	937,900
500	634,032	1,127,168
1000	1,088,472	1,978,051

**Table 37. Orifice Capacities for Propane**

ORIFICE OR DRILL SIZE	ORIFICE CAPACITY BTU PER HOUR, 11 IN. W.C.	ORIFICE OR DRILL SIZE	ORIFICE CAPACITY BTU PER HOUR, 11 IN. W.C.
0.008	519	51	36531
0.009	656	50	39842
0.010	812	49	43361
0.011	981	48	46983
0.012	1169	47	50088
80	1480	46	53296
79	1708	45	54641
78	2080	44	60229
77	2629	43	64369
76	3249	42	71095
75	3581	41	74924
74	4119	40	78029
73	4678	39	80513
72	5081	38	83721
71	5495	37	87860
70	6375	36	92207
69	6934	35	98312
68	7813	34	100175
67	8320	33	103797
66	8848	32	109385
65	9955	31	117043
64	10535	30	134119
63	11125	29	150366
62	11735	28	160301
61	12367	27	168580
60	13008	26	175617
59	13660	25	181619
58	14333	24	187828
57	15026	23	192796
56	17572	22	200350
55	21939	21	205525
54	24630	20	210699
53	28769	19	223945
52	32805	18	233466

BTU/ft<sup>3</sup> = 2516  
 Specific Gravity = 1.52  
 Pressure at orifice, in. w.c. = 11  
 Orifice Coefficient = 0.9

# Conversions, Equivalents and Physical Data

**Table 38. Pipe and Tubing Sizing**

PROPANE PIPE AND TUBING SIZING BETWEEN SINGLE OR SECOND STAGE LOW PRESSURE REGULATORS AND APPLIANCES												
Pipe or Tubing Length, Ft.	Copper Tubing Size, Outside Diameter (Inside Diameter), Type L					Pipe or Tubing Length, Ft.	Nominal Pipe Size, Outside Diameter (Inside Diameter), Schedule 40					
	3/8 / 0.315	1/2 / 0.430	5/8 / 0.545	3/4 / 0.666	7/8 / 0.785		1/2 / 0.622	3/4 / 0.824	1 / 1.049	1-1/4 / 1.380	1-1/2 / 1.610	2 / 2.067
10	49	110	206	348	536	10	291	608	1146	2353	3525	6789
20	34	76	151	239	368	20	200	418	788	1617	2423	4666
30	27	61	114	192	296	30	161	336	632	1299	1946	3747
40	23	52	97	164	253	40	137	282	541	1111	1665	3207
50	20	46	86	146	224	50	122	557	480	985	1476	2842
60	19	42	78	132	203	60	110	231	435	892	1337	2575
70	17	39	72	121	187	80	94	198	372	764	1144	2204
80	16	36	67	113	174	100	84	175	330	677	1014	1954
90	15	34	63	106	163	125	74	155	292	600	899	1731
100	14	32	59	100	154	150	67	141	265	544	815	1569
150	11	26	48	80	----	----	----	----	----	----	----	----

To convert to capacities in cubic feet per hour, divide by 2.5  
 Note: Maximum undiluted propane capacities listed are based on 11 in. w.c. setting and a 0.5 in. w.c. pressure drop - Capacities in 1000 BTU per hour.

**Table 39. Vapor Pressures of Propane**

TEMPERATURE		PRESSURE		TEMPERATURE		PRESSURE		TEMPERATURE		PRESSURE		TEMPERATURE		PRESSURE	
°F	°C	psig	bar	°F	°C	psig	bar	°F	°C	psig	bar	°F	°C	psig	bar
130	54	257	18	70	21	109	8	20	-7	40	2.8	-20	-29	10	0.69
120	49	225	16	65	18	100	6.9	10	-12	31	2	-25	-32	8	0.55
110	43	197	14	60	16	92	6	0	-17	23	2	-30	-34	5	0.34
100	38	172	12	50	10	77	5	-5	-21	20	1.4	-35	-37	3	0.21
90	32	149	10	40	4	63	4	-10	-23	16	1	-40	-40	1	0.069
80	27	128	9	30	-1	51	4	-15	-26	13	1	-44	-42	0	0

**Table 40. Converting Volumes of Gas**

CFH TO CFH OR CFM TO CFM		
Multiply Flow of	By	To Obtain Flow of
Air	0.707	Butane
	1.290	Natural Gas
	0.808	Propane
Butane	1.414	Air
	1.826	Natural Gas
	1.140	Propane
Natural Gas	0.775	Air
	0.547	Butane
	0.625	Propane
Propane	1.237	Air
	0.874	Butane
	1.598	Natural Gas

**Table 41. BTU Comparisons**

COMMON FUELS	PER GAL.	PER LB
Propane	91,547	21,591
Butane	102,032	21,221
Gasoline	110,250	20,930
Fuel Oil	134,425	16,960



# Conversions, Equivalents and Physical Data

**Table 42. Capacities of Spuds and Orifices**

DRILL DESIGNATION	DIAMETER, IN.	AREA, IN <sup>2</sup>	CAPACITIES IN CFH OF 0.6 GRAVITY HIGH PRESSURE NATURAL GAS AND AN ORIFICE COEFFICIENT OF 1.0																		
			Upstream Pressure, psig																		
			1	2	3	4	5	6	7	8	9	10	12	14	16	18	20	25	30	40	50
80	0.0135	0.000143	1.61	2.26	2.76	3.17	3.52	3.84	4.13	4.40	4.65	4.88	5.31	5.65	6.05	6.44	6.84	7.82	8.80	10.8	12.8
79	0.0145	0.000163	1.85	2.61	3.18	3.65	4.06	4.43	4.77	5.07	5.36	5.63	6.12	6.52	6.98	7.43	7.89	9.02	10.2	12.5	14.7
1/64"	0.0156	0.000191	2.14	3.02	3.68	4.23	4.70	5.13	5.52	5.87	6.20	6.51	7.09	7.55	8.08	8.61	9.13	10.5	11.8	14.4	17.1
78	0.0160	0.000201	2.26	3.18	3.88	4.45	4.94	5.40	5.81	6.18	6.53	6.85	7.46	7.95	8.50	9.05	9.61	11.0	12.4	15.2	17.9
77	0.0180	0.000234	2.85	4.02	4.90	5.62	6.25	6.82	7.34	7.81	8.25	8.66	9.42	10.1	10.8	11.5	12.2	13.9	15.7	19.2	22.7
76	0.0200	0.000314	3.53	4.97	6.05	6.95	7.72	8.43	9.07	9.65	10.2	10.8	11.7	12.5	13.3	14.2	15.0	17.2	19.4	23.7	28.0
75	0.0210	0.000346	3.89	5.48	6.67	7.65	8.51	9.29	10.0	10.7	12.3	11.8	12.9	13.7	14.7	15.6	16.6	19.0	21.3	26.1	30.9
74	0.0225	0.000398	4.47	7.08	7.67	8.80	9.78	10.7	11.5	12.4	13.0	13.6	14.8	15.8	16.9	18.0	19.1	21.8	24.5	30.0	35.5
73	0.0240	0.000452	5.08	7.16	8.71	10.0	11.2	12.2	13.1	13.9	14.7	15.4	16.8	17.9	19.1	20.4	21.6	24.7	27.6	34.1	40.3
72	0.0250	0.000491	5.52	7.78	9.46	10.9	12.1	13.2	14.2	15.1	16.0	16.8	18.3	19.4	20.8	22.1	23.5	26.9	30.3	37.0	43.8
71	0.0260	0.000531	5.97	8.41	10.3	11.8	13.1	14.3	15.4	16.4	17.3	18.1	19.7	21.0	22.5	23.9	25.4	29.1	32.7	40.0	47.3
70	0.0280	0.000616	6.92	9.75	11.9	13.7	15.2	16.6	17.8	19.0	20.0	21.0	22.9	24.4	26.1	27.8	29.5	33.8	38.0	46.4	54.9
69	0.0292	0.000670	7.53	10.6	13.0	14.9	16.5	18.0	19.4	20.0	21.8	22.9	24.9	26.5	28.4	30.2	32.1	36.7	41.3	50.5	59.7
68	0.0310	0.000735	8.48	12.0	14.6	16.7	18.6	20.3	21.9	23.2	24.5	25.8	28.0	29.9	32.0	34.0	36.1	41.3	46.5	56.9	67.3
1/32"	0.0313	0.000765	8.59	12.2	14.8	17.0	18.8	20.6	22.1	23.5	24.9	26.1	28.4	30.3	32.4	34.5	36.6	41.9	47.1	57.7	68.2
67	0.0320	0.000804	9.03	12.8	15.5	17.8	19.8	21.6	23.3	24.7	26.1	27.4	29.9	31.8	34.0	36.2	38.5	44.0	49.5	60.6	71.7
66	0.0330	0.000855	9.60	13.6	16.5	18.9	21.1	23.0	24.7	26.3	27.6	29.2	31.8	33.8	36.2	38.5	40.9	46.8	52.7	64.4	76.2
65	0.0350	0.000962	10.8	15.3	18.6	21.3	23.7	25.9	27.8	29.6	31.3	32.8	35.7	38.1	40.7	43.4	46.0	52.6	59.2	72.5	85.7
64	0.0360	0.001018	11.5	16.2	19.7	22.6	25.1	27.4	29.4	31.3	33.1	34.7	37.8	40.3	42.4	45.9	48.7	55.7	62.7	76.7	90.7
63	0.0370	0.001075	12.1	17.1	20.8	23.8	26.5	28.9	31.1	33.1	34.9	36.7	39.9	42.5	45.5	48.4	51.4	58.8	66.2	81.0	95.8
62	0.0380	0.001134	12.8	18.0	21.9	25.1	27.9	30.5	32.8	34.9	36.8	38.7	42.1	44.8	48.0	51.1	54.2	62.0	69.8	85.4	101
61	0.0390	0.001195	13.5	19.0	23.1	26.5	29.4	32.1	34.6	36.8	38.8	40.8	44.4	47.3	50.6	53.8	57.1	65.4	73.6	90.0	107
60	0.0400	0.001257	14.2	19.9	24.3	27.8	30.9	33.8	36.4	38.7	40.8	42.9	46.7	49.7	53.2	56.6	60.1	68.7	77.4	94.7	112
59	0.0410	0.001320	14.9	20.9	25.5	29.2	32.5	35.5	38.2	40.6	42.9	45.0	49.0	52.2	55.8	59.5	63.1	72.2	81.3	99.5	118
58	0.0420	0.001385	15.6	22.0	26.7	30.7	34.1	37.2	40.0	42.6	45.0	47.2	51.4	54.8	58.6	62.4	66.2	75.7	85.3	105	124
57	0.0430	0.001452	16.3	23.0	28.0	32.1	35.7	39.0	42.0	44.7	47.2	49.5	53.9	57.4	61.4	65.4	69.4	79.4	89.4	110	130
56	0.0465	0.001698	19.1	26.9	32.8	37.6	41.8	45.6	49.1	52.2	55.1	57.9	63.0	67.1	71.8	76.5	81.2	92.8	105	128	152
3/64"	0.0469	0.00173	19.5	27.4	33.4	38.3	42.6	46.5	50.0	53.2	56.2	59.0	64.2	68.4	73.2	77.9	82.7	94.6	107	131	155
55	0.0520	0.00212	23.8	33.6	40.9	46.9	52.1	57.0	61.3	65.2	68.8	72.3	78.7	83.8	89.6	95.5	102	116	131	160	189
54	0.0550	0.00238	26.8	37.7	45.9	52.7	58.5	63.9	68.8	73.2	77.3	81.1	88.3	94.1	101	108	114	132	147	180	212
53	0.0595	0.00278	31.1	44.0	53.6	61.5	68.4	74.7	80.3	85.4	90.3	94.7	104	110	118	126	133	152	172	210	248
1/16"	0.0625	0.00307	34.5	48.6	59.2	67.9	75.5	82.5	88.8	94.4	99.7	105	114	122	130	139	147	168	189	232	274
52	0.0635	0.00317	35.6	50.2	61.1	70.1	78.0	85.1	91.6	97.4	103	108	118	126	134	143	152	174	196	239	283
51	0.0670	0.00353	39.7	55.9	68.0	78.1	86.8	94.8	102	109	115	121	131	140	150	159	169	193	218	266	315
50	0.0700	0.00385	43.3	61.0	74.2	85.2	94.7	104	112	119	125	132	143	153	163	174	184	211	237	290	343
49	0.0730	0.00419	47.1	66.4	80.8	92.7	103	113	121	129	136	143	156	166	178	189	201	229	258	316	374
48	0.0760	0.00454	51.0	71.9	87.5	101	112	122	132	140	148	155	169	180	192	205	217	249	280	342	405
5/64"	0.0781	0.00479	53.8	75.9	92.3	106	118	129	134	148	156	164	178	190	203	216	229	262	295	361	427
47	0.0785	0.00484	54.4	76.6	93.3	107	119	130	140	149	158	165	180	192	205	218	232	265	298	365	432
46	0.0810	0.00515	57.9	81.6	99.2	114	127	139	149	159	168	176	191	204	218	232	246	282	317	388	459
45	0.0820	0.00528	59.3	83.6	102	117	130	141	153	163	172	180	196	209	224	238	253	289	325	398	471
44	0.0860	0.00582	65.3	92.1	113	129	143	157	169	179	189	199	216	230	246	262	278	319	359	439	519
43	0.0890	0.00622	69.9	98.5	120	138	153	167	180	192	202	212	231	246	263	280	298	340	383	469	555
42	0.0935	0.00687	77.2	109	133	152	169	185	199	212	223	234	255	272	291	310	329	376	423	518	612
3/32"	0.0937	0.00690	77.5	110	133	153	170	186	200	212	224	235	256	273	292	311	350	378	425	520	615
41	0.0960	0.00724	81.3	115	140	161	178	195	210	223	235	247	269	287	306	326	346	396	446	546	645
40	0.0980	0.00754	84.7	120	146	167	186	203	218	232	245	257	280	298	319	340	361	413	464	568	672
39	0.0995	0.00778	87.4	124	150	172	192	209	225	239	253	265	289	308	329	351	372	426	479	585	693
38	0.1015	0.00809	90.9	128	156	179	199	218	234	249	263	276	300	320	342	365	387	443	498	610	721
37	0.1040	0.00849	95.4	135	164	188	209	228	246	261	276	290	315	336	359	383	406	464	523	640	757

- continued -



# Conversions, Equivalents and Physical Data

**Table 42. Capacities of Spuds and Orifices (continued)**

DRILL DESIGNATION	DIAMETER, IN.	AREA, IN <sup>2</sup>	CAPACITIES IN CFH OF 0.6 GRAVITY HIGH PRESSURE NATURAL GAS AND AN ORIFICE COEFFICIENT OF 1.0																		
			Upstream Pressure, psig																		
			1	2	3	4	5	6	7	8	9	10	12	14	16	18	20	25	30	40	50
36 7/64"	0.1065 0.1094	0.00891 0.00940	100 106	141 149	172 182	197 208	219 231	240 253	258 272	274 289	290 305	304 321	331 349	352 372	377 398	402 424	426 449	487 514	549 579	671 708	794 838
35 34 33	0.1100 0.1110 0.1130	0.00950 0.00968 0.01003	107 109 113	151 154 159	183 187 194	210 214 222	234 238 247	255 260 270	275 280 290	292 298 309	309 315 326	324 330 342	353 359 372	376 383 393	402 410 424	428 436 452	454 463 480	520 530 549	585 596 618	716 729 756	847 863 894
32 31 1/8"	0.1160 0.1200 0.1250	0.01057 0.01131 0.01227	119 127 138	168 179 195	204 218 237	234 250 272	260 278 302	284 304 330	306 327 355	325 348 377	343 367 399	360 386 418	392 420 456	418 447 485	447 478 519	476 510 553	505 541 587	578 619 671	651 696 756	796 852 924	942 1010 1100
30 29	0.1285 0.1360	0.01296 0.01433	146 164	206 230	250 280	287 322	319 357	348 390	375 420	399 447	421 472	442 495	481 539	512 575	548 615	584 655	620 695	709 795	798 893	976 1100	1160 1300
28 9/64"	0.1405 0.1406	0.01549 0.01553	174 175	246 246	299 300	343 344	381 382	416 417	448 449	476 478	503 504	528 529	575 576	612 614	655 657	698 700	740 742	847 849	954 956	1170 1170	1380 1390
27 26 25	0.1440 0.1470 0.1495	0.01629 0.01697 0.01755	183 191 197	258 269 278	314 327 339	361 376 388	401 417 432	438 456 472	471 491 507	501 522 540	529 551 570	555 579 598	605 630 651	644 671 694	689 718 742	734 764 790	779 811 839	891 928 960	1010 1050 1080	1230 1280 1330	1460 1520 1570
24 23 5/32"	0.1520 0.1540 0.1562	0.01815 0.01863 0.01917	204 210 216	288 295 304	350 359 370	402 412 424	446 458 472	490 501 515	525 539 554	558 573 589	589 605 623	619 635 653	674 691 711	718 737 758	768 788 811	818 839 863	867 890 916	992 1020 1050	1120 1150 1180	1370 1410 1450	1620 1660 1710
22 21	0.1570 0.1590	0.01936 0.01986	218 223	307 315	373 383	428 440	476 488	520 534	560 574	595 611	629 645	660 677	713 737	765 785	819 840	872 894	925 949	1060 1090	1200 1230	1460 1500	1730 1770
20 19 18 11/64"	0.1610 0.1660 0.1695 0.1719	0.02036 0.02164 0.02256 0.02320	229 243 254 261	323 343 358 368	393 417 435 447	451 479 499 513	501 532 555 571	547 581 606 623	589 625 652 671	626 665 694 713	661 703 733 753	694 738 769 790	756 803 837 861	805 855 892 917	861 915 954 981	917 975 1020 1050	973 1040 1080 1110	1120 1190 1240 1270	1260 1340 1390 1430	1540 1630 1700 1750	1820 1930 2010 2070
17	0.1730	0.02351	264	373	453	520	578	632	680	723	763	801	872	929	994	1060	1130	1290	1450	1770	2100
16 15 14 13	0.1770 0.1800 0.1820 0.1850	0.02461 0.02345 0.02602 0.02688	277 286 293 302	390 403 412 426	475 491 502 518	545 563 576 595	605 626 640 661	661 684 699 722	711 736 752 777	756 782 806 826	799 826 845 873	839 868 887 916	913 944 965 997	973 1010 1030 1060	1040 1080 1100 1140	1110 1150 1180 1210	1180 1220 1250 1290	1350 1400 1430 1470	1520 1570 1610 1660	1860 1920 1960 2030	2200 2270 2320 2400
3/16" 12 11 10 9	0.1875 0.1890 0.1910 0.1930 0.1960	0.02761 0.02806 0.02865 0.02940 0.03017	310 315 322 331 339	437 445 454 466 478	532 541 552 567 582	611 621 634 650 667	679 690 704 723 742	742 754 770 790 810	798 811 828 850 872	849 862 881 904 927	896 911 930 955 980	941 956 976 1010 1030	1030 1050 1070 1090 1120	1100 1110 1140 1170 1200	1170 1190 1220 1250 1270	1250 1270 1290 1330 1360	1320 1340 1370 1410 1450	1510 1540 1570 1610 1650	1700 1730 1770 1810 1860	2080 2120 2160 2220 2280	2460 2500 2560 2620 2690
8 7 13/64" 6 5	0.1990 0.2010 0.2031 0.2040 0.2055	0.03110 0.03173 0.03241 0.03269 0.03317	350 357 364 367 373	493 503 513 518 525	600 612 625 630 639	688 702 717 723 734	765 780 797 804 816	835 852 870 878 891	899 917 937 945 959	956 975 996 1010 1020	1010 1030 1060 1070 1080	1060 1090 1110 1120 1130	1160 1180 1210 1220 1230	1230 1260 1290 1300 1320	1320 1350 1370 1390 1410	1400 1430 1460 1480 1500	1490 1520 1550 1570 1590	1700 1740 1780 1790 1820	1920 1960 2000 2020 2050	2350 2390 2450 2470 2500	2770 2830 2890 2920 2960
4 3 7/32" 2 1	0.2090 0.2130 0.2187 0.2210 0.2280	0.03431 0.03563 0.03758 0.03836 0.04083	386 400 422 431 459	543 564 595 608 647	661 687 724 739 787	739 788 831 849 903	844 876 924 943 1010	921 959 1010 1030 1100	991 1030 1090 1110 1180	1060 1100 1160 1180 1260	1120 1160 1220 1250 1330	1170 1220 1280 1310 1400	1280 1330 1400 1430 1520	1360 1410 1490 1520 1620	1450 1510 1590 1630 1730	1550 1610 1700 1730 1840	1640 1710 1800 1840 1950	1880 1950 2060 2100 2240	2120 2200 2320 2370 2520	2590 2690 2830 2890 3080	2770 2830 2890 2920 2960
A 15/64" B C D	0.2340 0.2344 0.2380 0.2420 0.2460	0.04301 0.04314 0.04449 0.04600 0.04733	483 485 500 517 534	681 683 705 725 733	829 831 857 916 975	951 954 984 1020 1060	1060 1060 1100 1130 1170	1160 1160 1200 1240 1280	1250 1250 1290 1330 1370	1330 1330 1450 1420 1460	1400 1400 1520 1500 1550	1470 1470 1520 1570 1620	1600 1600 1650 1710 1770	1700 1710 1880 1820 1880	1820 1830 2010 2080 2010	1940 1950 2010 2200 2280	2060 2070 2130 2520 2600	2360 2360 2440 2520 2600	2650 2660 2740 2840 2930	3240 3250 3350 3470 3580	3060 3180 3350 3420 3640
E=1/4" F G 17/64" H	0.2500 0.2570 0.2610 0.2656 0.2660	0.04909 0.05187 0.05350 0.05542 0.05557	552 583 601 623 624	777 821 847 878 880	946 1000 1040 1070 1070	1090 1150 1190 1230 1230	1210 1280 1320 1370 1370	1320 1400 1440 1490 1500	1420 1500 1550 1610 1610	1510 1600 1650 1710 1710	1600 1690 1740 1810 1810	1680 1770 1830 1890 1900	1830 1930 1990 2060 2070	1940 2050 2120 2190 2200	2080 2200 2270 2350 2350	2210 2340 2410 2500 2510	2350 2480 2560 2650 2660	2690 2840 2930 3030 3040	3030 3200 3300 3410 3420	3700 3910 4030 4180 4190	4380 4620 4770 4940 4950

- continued -




# Conversions, Equivalents and Physical Data

**Table 42. Capacities of Spuds and Orifices (continued)**


DRILL DESIGNATION	DIAMETER, IN.	AREA, IN <sup>2</sup>	CAPACITIES IN CFH OF 0.6 GRAVITY HIGH PRESSURE NATURAL GAS AND AN ORIFICE COEFFICIENT OF 1.0																		
			Upstream Pressure, psig																		
			1	2	3	4	5	6	7	8	9	10	12	14	16	18	20	25	30	40	50
I	0.2720	0.005811	653	916	1120	1290	1430	1560	1680	1790	1890	1980	2160	2300	2460	2620	2780	3180	3580	4380	5180
J	0.2770	0.006026	677	957	1170	1340	1490	1620	1750	1860	1960	2060	2240	2390	2550	2720	2880	3300	3710	4540	5370
K	0.2810	0.006102	697	983	1200	1380	1530	1670	1800	1910	2020	2120	2300	2450	2630	2800	2970	3390	3820	4680	5530
9/32"	0.2812	0.006113	698	984	1200	1380	1530	1670	1800	1910	2020	2120	2310	2460	2630	2800	2970	3400	3830	4680	5540
L	0.2900	0.006605	742	1050	1280	1460	1630	1780	1910	2030	2150	2250	2450	2610	2800	2980	3160	3610	4070	4980	5890
M	0.2930	0.006835	768	1090	1320	1520	1680	1840	1980	2100	2220	2330	2540	2710	2890	3080	3270	3740	4210	5150	6090
19/64"	0.2969	0.006922	778	1100	1340	1530	1710	1860	2000	2130	2250	2360	2570	2740	2930	3120	3310	3790	4260	5220	6170
N	0.3020	0.007163	805	1140	1380	1590	1760	1930	2070	2210	2330	2440	2660	2830	3030	3230	3430	3920	4410	5400	6390
5/16"	0.3125	0.007670	862	1220	1480	1700	1890	2060	2220	2360	2490	2620	2850	3030	3250	3460	3670	4200	4720	5780	6840
O	0.3160	0.007843	881	1250	1520	1740	1930	2110	2270	2410	2550	2660	2910	3100	3320	3540	3750	4290	4830	5910	6990
P	0.3230	0.008194	920	1300	1580	1820	2020	2200	2370	2520	2660	2800	3040	3240	3470	3690	3920	4480	5050	6180	7300
21/64"	0.3281	0.008456	950	1340	1630	1870	2080	2270	2450	2600	2750	2890	3140	3350	3580	3810	4040	4630	5210	6370	7540
Q	0.3320	0.008657	972	1370	1670	1920	2130	2330	2500	2660	2810	2950	3210	3420	3660	3900	4140	4740	5330	6520	7720
R	0.3390	0.009026	1020	1430	1740	2000	2220	2430	2607	2780	2930	3080	3350	3570	3820	4070	4320	4940	5560	6800	8040
11/32"	0.3437	0.009281	1050	1470	1790	2060	2290	2500	2690	2860	3020	3170	3450	3670	3930	4180	4440	5080	5720	6990	8270
S	0.3480	0.009511	1070	1510	1840	2110	2340	2530	2750	2930	3090	3240	3530	3760	4020	4290	4550	5200	5860	7170	8480
T	0.3580	0.1006	1130	1600	1940	2230	2480	2710	2910	3100	3270	3430	3740	4000	4260	4530	4810	5500	6200	7580	8970
23/64"	0.3594	0.1014	1140	1610	1960	2250	2500	2730	2930	3120	3300	3460	3770	4010	4290	4570	4850	5550	6240	7640	9040
U	0.3680	0.1065	1200	1690	2050	2360	2620	2860	3080	3270	3460	3630	3950	4210	4500	4790	5050	5820	6550	8020	9480
3/8"	0.3750	0.1105	1240	1750	2130	2450	2720	2970	3200	3400	3590	3770	4100	4370	4670	4980	5280	6040	6800	8330	9850
V	0.3770	0.1116	1260	1770	2150	2470	2750	3000	3230	3430	3630	3810	4140	4410	4720	5030	5340	6100	6870	8410	9950
W	0.3860	0.1170	1320	1860	2260	2590	2900	3200	3380	3600	3800	3990	4340	4630	5000	5270	5590	6350	7200	8820	10,400
25/64"	0.3960	0.1198	1350	1900	2310	2650	2950	3220	3460	3680	3890	4090	4450	4740	5100	5400	5730	6550	7380	9030	10,700
X	0.3970	0.1238	1390	1960	2390	2740	3050	3330	3580	3810	4020	4220	4600	4900	5240	5580	5920	6770	7620	9330	11,100
Y	0.4040	0.1282	1440	2030	2470	2840	3150	3450	3710	3940	4160	4370	4760	5070	5420	5780	6130	7010	7890	9660	11,500
13/32"	0.4062	0.1295	1460	2060	2500	2870	3190	3480	3750	3990	4210	4420	4810	5120	5480	5840	6200	7090	7980	9760	11,600
Z	0.4130	0.1340	1510	2130	2590	2970	3300	3600	3870	4130	4350	4570	4970	5300	5670	6040	6400	7330	8250	10,100	12,000
27/64"	0.4219	0.1398	1570	2220	2700	3100	3440	3760	4040	4300	4540	4770	5190	5530	5910	6300	6680	7650	8610	10,600	12,500
7/16"	0.4375	0.1503	1690	2380	2900	3330	3700	4040	4350	4620	4880	5120	5580	5940	6360	6770	7200	8220	9250	11,400	13,400
29/64"	0.4531	0.1613	1820	2560	3110	3570	4000	4230	4660	5000	5140	5500	5990	6380	6820	7270	7700	8820	9930	12,200	14,400
15/32"	0.4687	0.1726	1940	2740	3330	3820	4250	4640	4990	5310	5610	5880	6410	6820	7300	7770	8300	9440	10,700	13,000	15,400
31/64"	0.4844	0.1843	2070	3280	3550	4080	4530	4950	5330	5670	5990	6280	6840	7280	7790	8300	8800	10,100	11,400	13,900	16,400
1/2"	0.5000	0.1964	2210	3110	3790	4350	4830	5280	5680	6340	6380	6690	7290	7760	8310	8850	9400	10,800	12,100	14,800	17,500
33/64"	0.5156	0.2088	2350	3310	4030	4620	5140	5610	6040	6420	6780	7120	7750	8250	8490	9400	10,000	11,500	12,900	15,800	18,600
17/32"	0.5313	0.2217	2490	3510	4280	4910	5450	5960	6410	6820	7200	7560	8230	8760	9370	9980	10,600	12,200	13,700	16,700	19,800
35/64"	0.5469	0.2349	2640	3720	4530	5200	5780	6310	6790	7220	7630	8010	8720	9290	9930	10,600	11,300	12,900	14,500	17,700	21,000
9/16"	0.5625	0.2485	2790	3940	4770	5500	6110	6680	7180	7640	8070	8470	9220	9820	10,500	11,200	11,900	13,600	15,300	18,800	22,000
37/64"	0.5781	0.2625	2950	4160	5060	5810	6450	7050	7590	8070	8520	8950	9740	10,370	11,100	11,900	12,600	14,400	16,200	19,800	23,400
19/32"	0.5938	0.2769	3110	4390	5340	6130	6810	7440	8000	8510	8990	9440	10,300	10,940	11,700	12,500	13,300	15,200	17,100	20,900	24,700
39/64"	0.6094	0.2917	3280	4620	5620	6450	7170	7830	8430	8970	9470	9940	10,900	11,600	12,400	13,200	14,000	16,000	18,000	22,000	26,000
5/8"	0.6250	0.3068	3450	4860	5910	6790	7540	8240	8870	9430	9960	10,500	11,400	12,200	12,700	13,900	14,700	16,800	18,900	23,100	27,400
41/64"	0.6406	0.3223	3620	5110	6210	7130	7920	8660	9310	9910	10,500	11,000	12,000	12,800	13,700	14,600	15,400	17,700	19,900	24,300	28,800
21/32"	0.6562	0.3382	3800	5360	6520	7480	8320	9080	9770	10,400	11,000	11,600	12,600	13,400	14,300	15,300	16,200	18,500	20,900	25,500	30,200
43/64"	0.6719	0.3545	3980	5620	6830	7840	8720	9520	10,300	10,900	11,500	12,100	13,200	14,000	15,000	16,000	17,000	19,400	21,900	26,700	31,600
11/16"	0.6875	0.3712	4170	5880	7150	8210	9130	9970	10,600	11,500	12,100	12,700	13,800	14,700	15,700	16,800	17,800	20,300	22,900	28,000	33,100
23/32"	0.7188	0.4057	4560	6430	7820	8970	9970	10,900	11,800	12,500	13,200	13,900	15,100	16,100	17,200	18,300	19,400	22,200	25,000	30,600	36,200
3/4"	0.7500	0.4418	4960	7000	8510	9770	10,900	11,900	12,800	13,600	14,400	15,100	16,400	17,500	18,700	19,900	21,200	24,200	27,200	33,300	39,400
25/32"	0.7812	0.4794	5390	7590	9240	10,600	11,800	12,900	13,900	14,800	15,600	16,400	17,800	19,000	20,300	21,600	22,900	26,200	29,500	36,100	42,800
13/16"	0.8125	0.5185	5830	8210	9990	11,500	12,800	14,000	15,000	16,000	16,900	17,700	19,300	20,500	22,000	23,400	24,800	28,400	32,000	39,100	46,200
27/32"	0.8438	0.5591	6280	8850	10,800	12,400	13,800	15,000	16,200	17,200	18,200	19,100	20,800	22,100	23,700	25,200	26,700	30,600	34,400	42,100	49,800
7/8"	0.8750	0.6013	6760	9520	11,600	13,300	14,800	16,200	17,400	18,500	19,600	20,500	22,300	23,800	25,500	27,100	28,800	32,900	37,000	45,300	53,600
29/32"	0.9062	0.6450	7250	10,200	12,400	14,300	15,900	17,400	18,700	19,900	21,000	22,000	24,000	25,500	26,400	29,100	30,900	35,300	39,700	48,600	57,500
15/16"	0.9375	0.6903	7750	10,900	13,300	15,300	17,000	18,600	20,000	21,200	22,400	23,600	25,600	27,500	29,200	31,100	33,000	37,800	42,500	52,000	61,500
31/32"	0.9688	0.7371	8280	11,700	14,200	16,300	18,200	19,800	21,300	22,700	24,000	25,100	27,400	29,200	31,200	33,200	35,300	40,300	45,400	55,600	65,700
1.0"	1.0000	0.7854	8820	12,400	15,100	17,400	19,300	21,100	22,700	24,200	25,500	26,800	29,200	31,100	33,200	35,400	37,600	43,000	48,400	59,200	70,000



Specific Gravity of Typical Fluids vs. Temperature



## Effect of Inlet Swage On Critical Flow $C_g$ Requirements





# Conversions, Equivalents and Physical Data

**Table 43. Seat Leakage Classifications (In Accordance with ANSI/FCI 70-3-2004)**

LEAKAGE CLASS DESIGNATION	DESCRIPTION	MAXIMUM LEAKAGE ALLOWABLE
I	A modification of any Class II, III or IV regulator where the design intent is the same as the basic class, but by agreement between user and supplier, no test is required.	----
II	This class establishes the maximum permissible leakage generally associated with commercial double-seat regulators with metal-to-metal seats.	0.5% of maximum $C_v$
III	This class establishes the maximum permissible leakage generally associated with Class II, but with a higher degree of seat and seal tightness.	0.1% of maximum $C_v$
IV	This class establishes the maximum permissible leakage generally associated with commercial unbalanced single-seat regulators with metal-to-metal seats.	0.01% of maximum $C_v$
VI	This class establishes the maximum permissible seat leakage generally associated with resilient seating regulators either balanced or unbalanced with O-rings or similar gapless seals.	Leakage per following table as expressed in ml per minute versus seat diameter.
VII	This class establishes the maximum permissible seat leakage generally associated with Class VI, but with test performed at the maximum operating differential pressure.	Leakage per following table as expressed in ml per minute versus seat diameter.

**Table 44. Nominal Port Diameter and Leak Rate**

NOMINAL PORT DIAMETER		LEAK RATE	
mm	In.	Standard ml per Minute <sup>(3)</sup>	Bubbles per Minute <sup>(1)</sup>
≤25 <sup>(2)</sup>	≤1 <sup>(2)</sup>	0.15	1 <sup>(2)</sup>
38	1.5	0.30	2
51	2	0.45	3
64	2.5	0.60	4
76	3	0.90	6
102	4	1.70	11
152	6	4.00	27
203	8	6.75	45
250	10	11.1	----
300	12	16.0	----
350	14	21.6	----
400	16	28.4	----

1. Bubbles per minute as tabulated are an easily measured suggested alternative based on a suitable calibrated measuring device in this case a 0.24 in. / 6 mm O.D. x 0.04 in. / 1 mm wall tube submerged in water to a depth of from 0.12 to 0.24 in. / 3 to 6 mm. The tube end shall be cut square and smooth with no chamfers or burrs and the tube axis shall be perpendicular to the surface of the water. Other apparatus may be constructed and the number of bubbles per minute may differ from those shown as long as they correctly indicate the flow in ml per minute.

2. If valve seat diameter differs by more than 0.08 in. / 2 mm from one of the valves listed, the leakage rate may be obtained by interpolation assuming that the leakage rate varies as the square of the seat diameter.

3. Standard millimeters based on 60°F / 16°C and 14.73 psia / 1.016 bar a.

# Conversions, Equivalents and Physical Data

## Flange, Valve Size and Pressure-Temperature Rating Designations

Sizes of ASME flanges are designated as NPS (for “Nominal Pipe Size”). The nominal size is based on inches, but the units are not required in the designation. For example: NPS 2 is the size. Pressure ratings are designated by class. For example, CL150 is the rating. ASME designations replace ANSI designations.

Sizes of EN and ISO flanges are designated with DN (for “Nominal Diameter”). The nominal diameter is based on millimeters, but the units are not included in the designation. For example: DN 50 is the size. Pressure ratings are designated by PN (for “Nominal Pressure”). For example PN 40 is the pressure rating. EN and ISO designations replace DIN designations through PN 100.

ASME B16.5 flanges will mate with EN 1759 flanges but not with EN 1092 flanges (formerly DIN flanges). ASME B16.5 flanges will mate with most ISO 7005 flanges.

Common size designations in wide use are shown in the table below.

A summary of flange terminology is shown in the table below, and equivalency of flanges is shown in the table on the following page.

## Pipe Thread Standards

There are three pipe thread standards that are accepted globally:

- NPT, ASME B1.20.1: General-purpose pipe threads (inches).
- G Series, ISO 228-1: Pipe threads for use where pressure-tight joints are not made on the threads. The internal and external threads are not tapered but are parallel or straight.
- R Series, ISO 7/1: Pipe threads for use where pressure-tight joints are made on the threads. The internal thread is parallel (straight) or tapered; external is always tapered.

## Notes

Japanese (JIS) valves and flanges are designated according to JIS standards.

European Norm flange types, such as flat-face and raised-face are designated Type A, Type B, Type C. These types do not correspond to the DIN 2526 Form A, Form D, etc., designations.

**Table 45. Common Size Designations**

NPS	1/2	3/4	1	1-1/2	2	2-1/2	3	4	6	8	10	12	14	16	18	20	24
DN	15	20	25	40	50	65	80	100	150	200	250	300	350	400	450	500	600

**Table 46. Summary of Flange Terminology**

	ASME	EUROPEAN NORM	EXAMPLE OF PRINTED PRESENTATION
Pressure Rating	CLASS	PN	CL300 or CL300, PN 40
Size	NPS	DN	NPS 2, DN 50
Pipe Threads (Internal or External)	NPT	NPT, G (Straight), R (Tapered)	G 1/4, 1/4 NPT, 1/4 NPT Internal (or External)

# Conversions, Equivalents and Physical Data

**Table 47. Equivalency Table**

	ISO	ASME	DIN	EUROPEAN NORM	LIMITATION
<b>ASME and European Norm Only</b>	----	Class Flanges ASME B16.5	----	EN 1759-1	Specifies ASTM materials but also permits European materials per EN 1092-1.
<b>European Norm Only</b>		----		EN 1092	Through PN 100 <sup>(1)</sup>
<b>DIN Only</b>		----	DIN <sup>(2)</sup>	----	Above PN 100 <sup>(1)</sup>
<b>ISO and ASME Only</b>	ISO 7005	Class Flanges ASME B16.5		----	A few sizes are compatible to previous DIN standards. An older version contained flange designations that do not appear in the current standard.

1. DIN is no longer used except for pressure ratings above PN 100.  
2. DIN standards 2628, 2629, 2638, 2548, 2549, 2550 and 2551.

**Table 48. Standard Pressure-Temperature Ratings for ASME CL150 Valve Bodies<sup>(1)</sup>**

SERVICE TEMPERATURE		WORKING PRESSURE									
		LCB		LCC/WCC		WCB		CF8 or 304		CF8M/CF3M	
°F	°C	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
-20 to 100	-29 to 38	265	18.3	290	20.0	285	19.7	275	19.0	275	19.0
200	93	255	17.6	260	17.9	260	17.9	230	15.9	235	16.2
300	149	230	15.9	230	15.9	230	15.9	205	14.1	215	14.8
400	204	200	13.8	200	13.8	200	13.8	190	13.1	195	13.4
500	260	170	11.7	170	11.7	170	11.7	170	11.7	170	11.7
600	316	140	9.7	140	9.7	140	9.7	140	9.7	140	9.7
650	343	125	8.6	125	8.6	125	8.6	125	8.6	125	8.6
700	371	110	7.6	110	7.6	110	7.6	110	7.6	110	7.6

1. Table information is extracted from the Valve-Flanged, Threaded and Welding End, ASME Standard B16.34-2004. These tables must be used in accordance with the ASME standard.

**Table 49. Standard Pressure-Temperature Ratings for ASME CL300 Valve Bodies<sup>(1)</sup>**

SERVICE TEMPERATURE		WORKING PRESSURE									
		LCB		LCC/WCC		WCB		CF8 or 304		CF8M/CF3M	
°F	°C	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
-20 to 100	-29 to 38	695	47.9	750	51.7	740	51.0	720	49.6	720	49.6
200	93	660	45.5	750	51.7	680	46.9	600	41.4	620	42.7
300	149	640	44.1	730	50.3	655	45.2	540	37.2	560	38.6
400	204	615	42.4	705	48.6	635	43.8	495	34.1	515	35.5
500	260	585	40.3	665	45.9	605	41.7	465	32.1	480	33.1
600	316	550	37.9	605	41.7	570	39.3	440	30.3	450	31.0
650	343	535	36.8	590	40.7	550	38.0	430	29.6	440	30.3
700	371	510	35.2	555	38.3	530	36.5	420	29.0	435	30.0


1. Table information is extracted from the Valve-Flanged, Threaded and Welding End, ASME Standard B16.34-2004. These tables must be used in accordance with the ASME standard.

# Conversions, Equivalents and Physical Data

**Table 50. Standard Pressure-Temperature Ratings for ASME CL600 Valve Bodies<sup>(1)</sup>**

SERVICE TEMPERATURE		WORKING PRESSURE									
		LCB		LCC/WCC		WCB		CF8 or 304		CF8M/CF3M	
°F	°C	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
-20 to 100	-29 to 38	1395	96.2	1500	103	1480	102	1440	99.3	1440	99.3
200	93	1320	91.0	1500	103	1360	93.7	1200	82.7	1240	85.5
300	149	1275	87.9	1455	100	1310	90.3	1075	74.1	1120	77.2
400	204	1230	84.8	1405	97.0	1265	87.2	995	68.6	1025	70.7
500	260	1175	81.0	1330	91.7	1205	83.1	930	64.1	955	65.8
600	316	1105	76.2	1210	83.4	1135	78.3	885	61.0	900	62.1
650	343	1065	73.4	1175	81.0	1100	75.8	865	59.6	885	61.0
700	371	1025	70.7	1110	76.5	1060	73.1	845	58.3	870	60.0

1. Table information is extracted from the Valve-Flanged, Threaded and Welding End, ASME Standard B16.34-2004. These tables must be used in accordance with the ASME standard.



**Pressure/Temperature Ratings for ASTM A126 Cast Iron Valves**



# Conversions, Equivalents and Physical Data

**Table 51. Diameter of Bolt Circle**

NOMINAL PIPE SIZE, IN.	ASME CL125 (CAST IRON) OR CL150 (STEEL) <sup>(1)</sup>	ASME CL250 (CAST IRON) OR CL300 (STEEL) <sup>(2)</sup>	ASME CL600	ASME CL900	ASME CL1500	ASME CL2500
1	3.12	3.50	3.50	4.00	4.00	4.25
1-1/4	3.50	3.88	3.88	4.38	4.38	5.12
1-1/2	3.88	4.50	4.50	4.88	4.88	5.75
2	4.75	5.00	5.00	6.50	6.50	6.75
2-1/2	5.50	5.88	5.88	7.50	7.50	7.75
3	6.00	6.62	6.62	7.50	8.00	9.00
4	7.50	7.88	8.50	9.25	9.50	10.75
5	8.50	9.25	10.50	11.00	11.50	12.75
6	39.50	10.62	11.50	12.50	12.50	14.50
8	11.75	13.00	13.75	15.50	15.50	17.25
10	14.25	15.25	17.00	18.50	19.00	21.75
12	17.00	17.75	19.25	21.00	22.50	24.38
14	18.75	20.25	20.75	22.00	25.00	----
16	21.25	22.50	23.75	24.25	27.75	----
18	22.75	24.75	25.75	27.00	30.50	----
20	25.00	27.00	28.50	29.50	32.75	----
24	29.50	32.00	33.00	35.50	39.00	----
30	36.00	39.25	----	----	----	----
36	42.75	46.00	----	----	----	----
42	49.50	52.75	----	----	----	----
48	56.00	60.75	----	----	----	----

1. Sizes 1 through 12 in. also apply to ASME CL150 bronze flanges.  
2. Sizes 1 through 8 in. also apply to ASME CL300 bronze flanges.

**Table 52. ASME Face-To-Face Dimensions for Flanged Regulators**

BODY SIZE, IN.	ASME CLASS AND END CONNECTIONS (IN. DIMENSIONS ARE IN ACCORDANCE WITH ISA 54.01.1-1997)											
	CL125 FF (Cast Iron) CL150 RF (Steel)		CL250 RF (Cast Iron) CL300 RF (Steel)		CL150 RJT (Steel)		CL300 RJT (Steel)		CL600 RF (Steel)		CL600 RJT (Steel)	
	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm	In.	mm
1	7.25	184	7.75	197	7.75	197	8.25	210	8.25	210	8.25	210
1-1/4	7.88	200	8.38	213	8.38	213	8.88	226	9.00	229	9.00	229
1-1/2	8.75	222	9.25	235	9.25	235	9.75	248	9.88	251	9.88	251
2	10.00	254	10.50	267	10.50	267	11.12	282	11.25	286	11.38	289
2-1/2	10.88	276	11.50	292	11.38	289	12.12	308	12.25	311	12.38	314
3	11.75	298	12.50	317	12.25	311	13.12	333	13.25	337	13.38	340
4	13.88	353	14.50	368	14.38	365	15.12	384	15.50	394	15.62	397
6	17.75	451	18.62	473	18.25	464	19.25	489	20.00	508	20.12	511
8	21.38	543	22.38	568	21.88	556	23.00	584	24.00	610	24.12	613
10	26.50	673	27.88	708	27.00	686	28.50	724	29.62	752	29.75	756
12	29.00	737	30.50	775	29.50	749	31.12	790	32.25	819	32.38	822
16	40.00	1016	41.62	1057	40.50	1029	42.25	1073	43.62	1108	43.75	1111

FF—Flat-faced, RF—Raised-faced and RJT—Ring Type Joint

# Conversions, Equivalents and Physical Data

**Table 53. Wear and Galling Resistance Chart of Material Combinations**

MATERIAL	304 STAINLESS STEEL	316 STAINLESS STEEL	BRONZE	INCONEL®	MONEL®	HASTELLOY® C	NICKEL
304 Stainless Steel	P	P	F	P	P	F	P
316 Stainless Steel	P	P	F	P	P	F	P
Bronze	F	F	S	S	S	S	S
Inconel®	P	P	S	P	P	F	F
Monel®	P	P	S	P	P	F	F
Hastelloy® C	F	F	S	F	F	F	F
Nickel	P	P	S	P	F	F	P
Alloy 20	P	P	S	P	F	F	P
Type 416 Hard	F	F	F	F	F	F	F
Type 440 Hard	F	F	F	F	F	F	F
17-4PH	F	F	F	F	F	F	F
ENC <sup>(1)</sup>	F	F	F	F	F	F	F
Cr Plate	F	F	F	F	F	S	S
Al Bronze	F	F	F	S	S	S	S

1. Electroless Nickel Coating  
S - Satisfactory F - Fair P - Poor

- continued -

**Table 53. Wear and Galling Resistance Chart of Material Combinations (continued)**

MATERIAL	ALLOY 20	TYPE 416 HARD	TYPE 440 HARD	17-4PH	ENC <sup>(1)</sup>	Cr PLATE	Al BRONZE
304 Stainless Steel	P	F	F	F	F	F	F
316 Stainless Steel	P	F	F	F	F	F	F
Bronze	S	F	F	F	F	F	F
Inconel®	F	F	F	F	F	F	S
Monel®	F	F	F	F	F	F	S
Hastelloy® C	F	F	F	F	F	S	S
Nickel	P	F	F	F	F	F	S
Alloy 20	P	F	F	F	F	F	S
Type 416 Hard	F	F	F	F	S	S	S
Type 440 Hard	F	S	F	S	S	S	S
17-4PH	F	F	S	P	S	S	S
ENC <sup>(1)</sup>	F	S	S	S	P	S	S
Cr Plate	S	S	S	S	S	P	S
Al Bronze	S	S	S	S	S	S	P

1. Electroless Nickel Coating  
S - Satisfactory F - Fair P - Poor

**Table 54. Equivalent Lengths of Pipe Fittings and Valves**

TYPE OF FITTING OR VALVE	LENGTHS IN FEET OF STANDARD PIPE																			
	Nominal Pipe Size in In.																			
	1/2	3/4	1	1-1/4	1-1/2	2	2-1/2	3	4	6	8	10	12	14 O.D.	16 O.D.	18 O.D.	20 O.D.	24 O.D.	30 O.D.	
Standard tee with entry or discharge through side	3.4	4.5	5.5	7.5	9.0	12	14	17	22	33	43	55	65	78	85	105	115	135	170	
Standard elbow or run <sup>(1)</sup> of tee reduced 1/2 <sup>(2)</sup>	1.7	2.2	2.7	3.7	4.3	5.5	6.5	8	12	16	20	26	31	36	42	47	52	64	80	
Medium sweep elbow or run <sup>(1)</sup> of tee reduced 1/4 <sup>(2)</sup>	1.3	1.8	2.3	3.0	3.7	4.6	5.4	6.8	9.0	14	18	22	26	30	35	40	43	55	67	
Long sweep elbow or run <sup>(1)</sup> of standard tee or butterfly valve	1	1.3	1.7	2.3	2.7	3.5	4.2	5.3	7	11	14	17	20	23	26	31	34	41	52	
45° elbow	0.8	1.0	1.2	1.6	2.0	2.5	3.0	3.7	5.0	7.5	10	12	15	17	20	22	24	30	37	
Close return bend	3.7	5.1	6.2	8.5	10	13	15	19	24	37	49	62	75	86	100	110	125	150	185	
Globe valve, wide-open	0.6	22	27	40	43	45	65	82	120	170	240	290	340	400	440	500	550	680	850	
Angle valve, wide-open	8.2	11	14	18	21	28	33	42	56	85	112	145	165	190	220	250	280	340	420	
Swing check valve, wide-open	4.0	5.2	6.6	9.0	11	14	16	19	26	39	52	66	78	92	106	120	130	145	160	
Gate valve, wide-open or slight bushing reduction	0.4	0.5	0.6	0.8	0.9	1.2	1.3	1.7	2.3	3.5	4.5	5.7	6.7	8.0	9.0	11	12	14	17	

1. A fluid is said to flow through the run of a tee when the flow is straight through the tee with no change of direction.  
2. A tee is said to be reduced 1/4 if the internal area of the smaller connecting pipe is 25% less than the internal area of the larger connecting pipe.

# Conversions, Equivalents and Physical Data

**Table 55. Pipe Data: Carbon and Allow Steel—Stainless Steel**

NOMINAL PIPE SIZE, IN.	OUTSIDE DIAMETER, IN.	IDENTIFICATION			WALL THICKNESS (t), IN.	INSIDE DIAMETER (d), IN.	AREA OF METAL, IN <sup>2</sup> .	TRANSVERSE INTERNAL AREA		WEIGHT PIPE, LBS/FT	WEIGHT WATER, LBS/FT OF PIPE
		Steel		Stainless Steel Schedule No.				(a), In <sup>2</sup> .	(A), Ft <sup>2</sup>		
		Iron Pipe Size	Schedule No.								
1/8	0.405	----	----	10S	0.049	0.307	0.0548	0.0740	0.00051	0.19	0.032
		STD	40	40S	0.068	0.269	0.0720	0.0568	0.00040	0.24	0.025
		XS	80	80S	0.095	0.215	0.0925	0.0365	0.00025	0.31	0.016
1/4	0.540	----	----	10S	0.065	0.410	0.0970	0.1320	0.00091	0.33	0.057
		STD	40	40S	0.088	0.364	0.1250	0.1041	0.00072	0.42	0.045
		XS	80	80S	0.119	0.302	0.1574	0.0716	0.00050	0.54	0.031
3/8	0.675	----	----	10S	0.065	0.545	0.1246	0.2333	0.00162	0.42	0.101
		STD	40	40S	0.091	0.493	0.1670	0.1910	0.00133	0.57	0.083
		XS	80	80S	0.126	0.423	0.2173	0.1405	0.00098	0.74	0.061
1/2	0.840	----	----	5S	0.065	0.710	0.1583	0.3959	0.00275	0.54	0.172
		----	----	10S	0.083	0.674	0.1974	0.3568	0.00248	0.67	0.155
		STD	40	40S	0.109	0.622	0.2503	0.3040	0.00211	0.85	0.132
		XS	80	80S	0.147	0.546	0.3200	0.2340	0.00163	1.09	0.102
		----	160	----	0.187	0.466	0.3836	0.1706	0.00118	1.31	0.074
		XXS	----	----	0.294	0.252	0.5043	0.050	0.00035	1.71	0.022
3/4	1.050	----	----	5S	0.065	0.920	0.2011	0.6648	0.00462	0.69	0.288
		----	----	10S	0.083	0.884	0.2521	0.6138	0.00426	0.86	0.266
		STD	40	40S	0.113	0.824	0.3326	0.5330	0.00371	1.13	0.231
		XS	80	80S	0.154	0.742	0.4335	0.4330	0.00300	1.47	0.188
		----	160	----	0.219	0.612	0.5698	0.2961	0.00206	1.94	0.128
		XXS	----	----	0.308	0.434	0.7180	0.148	0.00103	2.44	0.064
1	1.315	----	----	5S	0.065	1.185	0.2553	1.1029	0.00766	0.87	0.478
		----	----	10S	0.109	1.097	0.4130	0.9452	0.00656	1.40	0.409
		STD	40	40S	0.133	1.049	0.4939	0.8640	0.00600	1.68	0.375
		XS	80	80S	0.065	0.957	0.6388	0.7190	0.00499	2.17	0.312
		----	160	----	0.250	0.815	0.8365	0.5217	0.00362	2.84	0.230
		XXS	----	----	0.358	0.599	1.0760	0.282	0.00196	3.66	0.122
1-1/4	1.660	----	----	5S	0.065	1.530	0.3257	1.839	0.01277	1.11	0.797
		----	----	10S	0.109	1.442	0.4717	1.633	0.01134	1.81	0.708
		STD	40	40S	0.140	1.380	0.6685	1.495	0.01040	2.27	0.649
		XS	80	80S	0.191	1.278	0.8815	1.283	0.00891	3.00	0.555
		----	160	----	0.250	1.160	1.1070	1.057	0.00734	3.76	0.458
		XXS	----	----	0.382	0.896	1.534	0.630	0.00438	5.21	0.273
1-1/2	1.900	----	----	5S	0.065	1.770	0.3747	2.461	0.01709	1.28	1.066
		----	----	10S	0.109	1.682	0.6133	2.222	0.01543	2.09	0.963
		STD	40	40S	0.145	1.610	0.7995	2.036	0.01414	2.72	0.882
		XS	80	80S	0.200	1.500	1.068	1.767	0.01225	3.63	0.765
		----	160	----	0.281	1.338	1.429	1.406	0.00976	4.86	0.608
		XXS	----	----	0.400	1.100	1.885	0.950	0.00660	6.41	0.42
2	2.375	----	----	5S	0.065	2.245	0.4717	3.958	0.02749	1.61	1.72
		----	----	10S	0.109	2.157	0.7760	3.654	0.02538	2.64	1.58
		STD	40	40S	0.154	2.067	1.075	3.355	0.02330	3.65	1.45
		XS	80	80S	0.218	1.939	1.477	2.953	0.02050	5.02	1.28
		----	160	----	0.344	1.687	2.190	2.241	0.01556	7.46	0.97
		XXS	----	----	0.436	1.503	2.656	1.774	0.01232	9.03	0.77

Identification, wall thickness and weights are extracted from ASME B36.10 and B39.19.  
 The notations STD, XS and XXS indicate Standard, Extra Strong and Double Extra Strong pipe, respectively.  
 Transverse internal area values listed in "square feet" also represent volume in cubic feet per foot of pipe length.

- continued -

# Conversions, Equivalents and Physical Data

**Table 55. Pipe Data: Carbon and Allow Steel—Stainless Steel (continued)**

NOMINAL PIPE SIZE, IN.	OUTSIDE DIAMETER, IN.	IDENTIFICATION			WALL THICKNESS (t), IN.	INSIDE DIAMETER (d), IN.	AREA OF METAL, IN <sup>2</sup> .	TRANSVERSE INTERNAL AREA		WEIGHT PIPE, LBS/FT	WEIGHT WATER, LBS/FT OF PIPE
		Steel		Stainless Steel Schedule No.				(a), In <sup>2</sup> .	(A), Ft <sup>2</sup> .		
		Iron Pipe Size	Schedule No.								
2-1/2	2.875	----	----	5S	0.083	2.709	0.7280	5.764	0.04002	2.48	2.50
		----	----	10S	0.120	2.635	1.039	5.453	0.03787	3.53	2.36
		STD	40	40S	0.203	2.469	1.704	4.788	0.03322	5.79	2.07
		XS	80	80S	0.279	2.323	2.254	4.238	0.02942	7.66	1.87
		----	160	----	0.375	2.125	2.945	3.546	0.02463	10.01	1.54
		XXS	----	----	0.552	1.771	4.028	2.464	0.01710	13.69	1.07
3	3.500	----	----	5S	0.083	3.334	0.8910	8.730	0.06063	3.03	3.78
		----	----	10S	0.120	3.260	1.274	8.347	0.05796	4.33	3.62
		STD	40	40S	0.216	3.068	2.228	7.393	0.05130	7.58	3.20
		XS	80	80S	0.300	2.900	3.016	6.605	0.04587	10.25	2.86
		----	160	----	0.438	2.624	4.205	5.408	0.03755	14.32	2.35
		XXS	----	----	0.600	2.300	5.466	4.155	0.02885	18.58	1.80
3-1/2	4.000	----	----	5S	0.083	3.834	1.021	11.545	0.08017	3.48	5.00
		----	----	10S	0.120	3.760	1.463	11.104	0.07711	4.97	4.81
		STD	40	40S	0.226	3.548	2.680	9.886	0.06870	9.11	4.29
		XS	80	80S	0.318	3.364	3.678	8.888	0.06170	12.50	3.84
4	4.500	----	----	5S	0.083	4.334	1.152	14.75	0.10245	3.92	6.39
		----	----	10S	0.120	4.260	1.651	14.25	0.09898	5.61	6.18
		STD	40	40S	0.237	4.026	3.174	12.73	0.08840	10.79	5.50
		XS	80	80S	0.337	3.826	4.407	11.50	0.07986	14.98	4.98
		----	120	----	0.438	3.624	5.595	10.31	0.07116	19.00	4.47
		----	160	----	0.531	3.438	6.621	9.28	0.0645	22.51	4.02
5	5.563	----	----	5S	0.109	5.345	1.868	22.44	0.1558	6.36	9.72
		----	----	10S	0.134	5.295	2.285	22.02	0.1529	7.77	9.54
		STD	40	40S	0.258	5.047	4.300	20.01	0.1390	14.62	8.67
		XS	80	80S	0.375	4.813	6.112	18.19	0.1263	20.78	7.88
		----	120	----	0.500	4.563	7.953	16.35	0.1136	27.04	7.09
		----	160	----	0.625	4.313	9.696	14.61	0.1015	32.96	6.33
6	6.625	----	----	5S	0.109	6.407	2.231	32.24	0.2239	7.60	13.97
		----	----	10S	0.134	6.357	2.733	31.74	0.2204	9.29	13.75
		STD	40	40S	0.280	6.065	5.581	28.89	0.2006	18.97	12.51
		XS	80	80S	0.432	5.761	8.405	26.07	0.1810	28.57	11.29
		----	120	----	0.562	5.501	10.70	23.77	0.1650	36.39	10.30
		----	160	----	0.719	5.187	13.32	21.15	0.1469	45.35	9.16
9	8.625	----	----	5S	0.109	8.407	2.916	55.51	0.3855	9.93	24.06
		----	----	10S	0.148	8.329	3.941	54.48	0.3784	13.40	23.61
		----	20	----	0.250	8.125	6.57	51.85	0.3601	22.36	22.47
		----	30	----	0.277	8.071	7.26	51.16	0.3553	24.70	22.17
		STD	40	40S	0.322	7.981	8.40	50.03	0.3474	28.55	21.70
		----	60	----	0.406	7.813	10.48	47.94	0.3329	35.64	20.77
		XS	80	80S	0.500	7.625	12.76	45.66	0.3171	43.39	19.78
		----	100	----	0.594	7.437	14.96	43.46	0.3018	50.95	18.83
		----	120	----	0.719	7.187	17.84	40.59	0.2819	60.71	17.59
		----	140	----	0.812	7.001	19.93	38.50	0.2673	67.76	16.68
10	10.750	----	----	5S	0.134	10.482	4.36	86.29	0.5992	15.19	37.39
		----	----	10S	0.165	10.420	5.49	85.28	0.5922	18.65	36.95
		----	20	----	0.250	10.250	8.24	82.52	0.5731	28.04	35.76
		----	30	----	0.307	10.136	10.07	80.69	0.5603	34.24	34.96
		STD	40	40S	0.365	10.020	11.90	78.86	0.5475	40.48	34.20
		XS	60	80S	0.500	9.750	16.10	74.66	0.5185	54.74	32.35
		----	80	----	0.594	9.562	18.92	71.84	0.4989	64.43	31.13
		----	100	----	0.719	9.312	22.63	68.13	0.4732	77.03	29.53
		----	120	----	0.844	9.062	26.24	64.53	0.4481	89.29	27.96
		XXS	140	----	1.000	8.750	30.63	60.13	0.4176	104.13	26.06
----	160	----	1.125	8.500	34.02	56.75	0.3941	115.64	24.59		

Identification, wall thickness and weights are extracted from ASME B36.10 and B39.19. The notations STD, XS and XXS indicate Standard, Extra Strong and Double Extra Strong pipe, respectively. Transverse internal area values listed in "square feet" also represent volume in cubic feet per foot of pipe length.





# Conversions, Equivalents and Physical Data

**Table 56. American Pipe Flange Dimensions**

ASME CLASS FLANGE DIAMETER - IN., PER ASME B16.1, B16.5 AND B16.24						
Nominal Pipe Size	125 (Cast Iron) or 150 (Steel) <sup>(1)</sup>	250 (Cast Iron) or 300 (Steel) <sup>(2)</sup>	600	900	1500	2500
1	4.25	4.88	4.88	5.88	5.88	6.25
1-1/4	4.62	5.25	5.25	6.25	6.25	7.25
1-1/2	5.00	6.12	6.12	7.00	7.00	8.00
2	6.00	6.50	6.50	8.50	8.50	9.25
2-1/2	7.00	7.50	7.50	9.62	9.62	10.50
3	7.50	8.25	8.25	9.50	10.50	12.00
4	9.00	10.00	10.75	11.50	12.25	14.00
5	10.00	11.00	13.00	13.75	14.75	16.50
6	11.00	12.50	14.00	15.00	15.50	19.00
8	13.50	15.00	16.50	18.50	19.00	21.75
10	16.00	17.50	20.00	21.50	23.00	26.50
12	19.00	20.50	22.00	24.00	26.50	30.00
14	21.00	23.00	23.75	25.25	29.50	----
16	23.50	25.50	27.00	27.75	32.50	----
18	25.00	28.00	29.25	31.00	36.00	----
20	27.50	30.50	32.00	33.75	38.75	----
24	32.00	36.00	37.00	41.00	46.00	----
30	38.75	43.00	----	----	----	----
36	46.00	50.00	----	----	----	----
42	53.00	57.00	----	----	----	----
48	59.50	65.00	----	----	----	----

1. Sizes 1 through 12 in. also apply to ASME CL150 bronze flanges.  
2. Sizes 1 through 8 in. also apply to ASME CL300 bronze flanges.

- continued -

**Table 56. American Pipe Flange Dimensions (continued)**

ASME CLASS, NUMBER OF STUD BOLTS AND HOLE DIAMETER IN IN., PER ASME B16.1, B16.5 AND B16.24												
Nominal Pipe Size	125 (Cast Iron) or 150 (Steel) <sup>(1)</sup>		250 (Cast Iron) or 300 (Steel) <sup>(2)</sup>		600		900		1500		2500	
	No.	Ø	No.	Ø	No.	Ø	No.	Ø	No.	Ø	No.	Ø
1	4	0.50	4	0.62	4	0.62	4	0.88	4	0.88	4	0.88
1-1/4	4	0.50	4	0.62	4	0.62	4	0.88	4	0.88	4	1.00
1-1/2	4	0.50	4	0.75	4	0.75	4	1.00	4	1.00	4	1.12
2	4	0.62	8	0.62	8	0.62	8	0.88	8	0.88	8	1.00
2-1/2	4	0.62	8	0.75	8	0.75	8	1.00	8	1.00	8	1.12
3	4	0.62	8	0.75	8	0.75	8	0.88	8	1.12	8	1.25
4	8	0.62	8	0.75	8	0.75	8	0.12	8	1.25	8	1.50
5	8	0.75	8	0.75	8	1.00	8	1.25	8	1.50	8	1.75
6	8	0.75	12	0.75	12	1.00	12	1.12	12	1.38	8	2.00
8	8	0.75	12	0.88	12	1.12	12	1.38	12	1.62	12	2.00
10	12	0.88	16	1.00	16	1.25	16	1.38	12	1.88	12	2.50
12	12	0.88	16	1.12	20	1.25	20	1.38	16	2.00	12	2.75
14	12	1.00	20	1.12	20	1.38	20	1.50	16	2.25	----	----
16	16	1.00	20	1.25	20	1.50	20	1.62	16	2.50	----	----
18	16	1.12	24	1.25	20	1.62	20	1.88	16	2.75	----	----
20	20	1.12	24	1.25	24	1.62	20	2.00	16	3.00	----	----
24	20	1.25	24	1.50	24	1.88	20	2.50	16	3.50	----	----
30	28	1.25	28	1.75	----	----	----	----	----	----	----	----
36	32	1.50	32	2.00	----	----	----	----	----	----	----	----
42	36	1.50	36	2.00	----	----	----	----	----	----	----	----
48	44	1.50	40	2.00	----	----	----	----	----	----	----	----

1. Sizes 1 through 12 in. also apply to ASME CL150 bronze flanges.  
2. Sizes 1 through 8 in. also apply to ASME CL300 bronze flanges.

**Table 57. EN 1092-1 Cast Steel Flange Standard-PN 16 (Nominal Pressure 16 bar)**

NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm		
		Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter
10	6	90	16	60	4	M12	14
15	6	95	16	65	4	M12	14
20	6.5	105	18	75	4	M12	14
25	7	115	18	85	4	M12	14
32	7	140	18	100	4	M16	18
40	7.5	150	18	110	4	M16	18
50	8	165	20	125	4	M16	18
65	8	185	18	145	4	M16	18
80	8.5	200	20	160	8	M16	18
100	9.5	220	20	180	8	M16	18
125	10	250	22	210	8	M16	18
150	11	285	22	240	8	M20	23
175	12	315	24	270	8	M20	23
200	12	340	24	295	12	M20	23
250	14	405	26	355	12	M24	27
300	15	460	28	410	12	M24	27
350	16	520	30	470	16	M24	27
400	18	580	32	525	16	M27	30
500	21	715	36	650	20	M30	33
600	23	840	40	770	20	M33	36
700	24	910	42	840	24	M33	36
800	26	1025	42	950	24	M36	39
900	27	1125	44	1050	28	M36	39
1000	29	1255	46	1170	28	M39	42
1200	32	1485	52	1390	32	M45	48
1400	34	1685	58	1590	36	M45	48
1600	36	1930	64	1820	40	M52	56
1800	39	2130	68	2020	44	M52	56
2000	41	2345	70	2230	48	M56	62
2200	43	2555	74	2440	52	M56	62

**Table 58. EN 1092-1 Cast Steel Flange Standard-PN 25 (Nominal Pressure 25 bar)**

NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm		
		Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter
10	6	90	16	60	4	M12	14
15	6	95	16	65	4	M12	14
20	6.5	105	18	75	4	M12	14
25	7	115	18	85	4	M12	14
32	7	140	18	100	4	M16	18
40	7.5	150	18	110	4	M16	18
50	8	165	20	125	4	M16	18
65	8.5	185	22	145	8	M16	18
80	9	200	24	160	8	M16	18
100	10	235	24	190	8	M20	23
125	11	270	26	220	8	M24	27
150	12	300	28	250	8	M24	27
175	12	330	28	280	12	M24	27
200	12	360	30	310	12	M24	27
250	14	425	32	370	12	M27	30
300	15	485	34	430	16	M27	30
350	16	555	38	490	16	M30	33
400	18	620	40	550	16	M33	36
500	21	730	44	660	20	M33	36
600	23	845	46	770	20	M36	39
700	24	960	50	875	24	M39	42
800	26	1085	54	990	24	M45	48
900	27	1185	58	1090	28	M45	48
1000	29	1320	62	1210	28	M52	56
1200	32	1530	70	1420	32	M52	56
1400	34	1755	76	1640	36	M56	62
1600	37	1975	84	1860	40	M56	62
1800	40	2195	90	2070	44	M64	70
2000	43	2425	96	2300	48	M64	70

# Conversions, Equivalents and Physical Data

**Table 59. EN 1092-1 Cast Steel Flange Standard—PN 40 (Nominal Pressure 40 bar)**

NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm		
		Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter
10	6	90	16	60	4	M12	14
15	6	95	16	65	4	M12	14
20	6.5	105	18	75	4	M12	14
25	7	115	18	85	4	M12	14
32	7	140	18	100	4	M16	18
40	7.5	150	18	110	4	M16	18
50	8	165	20	125	4	M16	18
65	8.5	185	22	145	8	M16	18
80	9	200	24	160	8	M16	18
100	10	235	24	190	8	M20	23
125	11	270	26	220	8	M24	27
150	12	300	28	250	8	M24	27
175	13	350	32	295	12	M27	30
200	14	375	34	320	12	M27	30
250	16	450	38	385	12	M30	33
300	17	515	42	450	16	M30	33
350	19	580	46	510	16	M33	36
400	21	660	50	585	16	M36	39
450	21	685	50	610	20	M36	39
500	21	755	52	670	20	M39	42
600	24	890	60	795	20	M45	48
700	27	995	64	900	24	M45	48
800	30	1140	72	1030	24	M52	56
900	33	1250	76	1140	28	M52	56
1000	36	1360	80	1250	28	M52	56
1200	42	1575	88	1460	32	M56	62
1400	47	1795	98	1680	36	M56	62
1600	54	2025	108	1900	40	M64	70

**Table 60. EN 1092-1 Cast Steel Flange Standard—PN 63 (Nominal Pressure 63 bar)**

NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm		
		Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter
10	10	100	20	70	4	M12	14
15	10	105	20	75	4	M12	14
25	10	140	24	100	4	M16	18
32	12	155	24	110	4	M20	23
40	10	170	28	125	4	M20	22
50	10	180	26	135	4	M20	22
65	10	205	26	160	8	M20	22
80	11	215	28	170	8	M20	22
100	12	250	30	200	8	M24	26
125	13	295	34	240	8	M27	30
150	14	345	36	280	8	M30	33
175	15	375	40	310	12	M30	33
200	16	415	42	345	12	M33	36
250	19	470	46	400	12	M33	36
300	21	530	52	460	16	M33	36
350	23	600	56	525	16	M36	39
400	26	670	60	585	16	M39	42
500	31	800	68	705	20	M45	48
600	35	930	76	820	20	M52	56
700	40	1045	84	935	24	M52	56
800	45	1165	92	1050	24	M56	62
900	50	1285	98	1170	28	M56	62
1000	55	1415	108	1290	28	M64	70
1200	64	1665	126	1530	32	M72X6	78

**Table 61. EN 1092-1 Cast Steel Flange Standard—PN 100 (Nominal Pressure 100 bar)**

NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm			NOMINAL BORE, mm	PIPE THICKNESS, mm	FLANGE, mm			BOLTING, mm		
		Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter			Outside Diameter	Thickness	Bolt Circle Diameter	Number of Bolts	Thread	Bolt Hole Diameter
10	10	100	20	70	4	M12	14	150	18	355	44	290	12	M30	33
15	10	105	20	75	4	M12	14	175	20	385	48	320	12	M30	33
25	10	140	24	100	4	M16	18	200	21	430	52	360	12	M33	36
32	12	155	24	110	4	M20	23	250	25	505	60	430	12	M36	39
40	10	170	28	125	4	M20	22	300	29	585	68	500	16	M39	42
50	10	195	30	145	4	M24	26	350	32	655	74	560	16	M45	48
65	11	220	34	170	8	M24	26	400	36	715	78	620	16	M45	48
80	12	230	36	180	8	M24	26	500	44	870	94	760	20	M52	56
100	14	265	40	210	8	M27	30	600	51	990	104	875	20	M56	62
125	16	315	40	250	8	M30	33	700	59	1145	120	1020	24	M64	70

**Table 62. EN 1092-1 Pressure/Temperature Ratings for Cast Steel Flanges**

PN	MATERIAL GROUP	MAXIMUM ALLOWABLE PRESSURE <sup>(1)</sup>															
		14 to 212°F / -10 to 100°C		302°F / 150°C		392°F / 200°C		482°F / 250°C		572°F / 300°C		662°F / 350°C		707°F / 375°C		752°F / 400°C	
		psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar	psig	bar
16	1C1	232	16.0	226	15.6	219	15.1	209	14.4	194	13.4	186	12.8	180	12.4	157	10.8
	1C2	218	15.0	218	15.0	218	15.0	225	15.5	216	14.9	206	14.2	199	13.7	157	10.8
25	1C1	363	25.0	354	24.4	344	23.7	326	22.5	303	20.9	290	20.0	281	19.4	245	16.9
	1C2	363	25.0	363	25.0	363	25.0	363	25.0	338	23.3	322	22.2	310	21.4	245	16.9
40	1C1	580	40.0	567	39.1	550	37.9	522	36.0	486	33.5	463	31.9	451	31.1	392	27.0
	1C2	580	40.0	580	40.0	580	40.0	580	40.0	540	37.2	516	35.6	496	34.2	392	27.0
63	1C1	914	63.0	892	61.5	864	59.6	824	56.8	764	52.7	730	50.3	711	49.0	616	42.5
	1C2	914	63.0	914	63.0	914	63.0	914	63.0	851	58.7	812	56.0	780	53.8	616	42.5
100	1C1	1450	100	1417	97.7	1374	94.7	1307	90.1	1252	86.3	1157	79.8	1128	77.8	979	67.5
	1C2	1450	100	1450	100	1450	100	1450	100	1350	93.1	1289	88.9	1239	85.4	979	67.5

1. These ratings apply only for flange types 05, 11, 12, 13 and 21 having nominal sizes up and including DN 600.

# Conversions, Equivalents and Physical Data

**Table 63. Drill Sizes for Pipe Taps**

NOMINAL PIPE SIZE, IN.	TAP DRILL SIZE, IN.	NOMINAL PIPE SIZE, IN.	TAP DRILL SIZE, IN.
1/8	11/32	1-1/2	1-23/32
1/4	7/16	2	2-3/16
3/8	19/32	2-1/2	2-9/16
1/2	23/32	3	3-3/16
3/4	15/16	4	4-3/16
1	1-5/32	5	5-5/16
1-1/4	1-1/2	6	6-5/16

**Table 64. Standard Twist Drill Sizes**

DESIGNATION	DIAMETER, IN.	AREA, SQ. IN.	DESIGNATION	DIAMETER, IN.	AREA, SQ. IN.	DESIGNATION	DIAMETER, IN.	AREA, SQ. IN.
1/2	0.5000	0.1963	3	0.213	0.03563	3/32	0.0938	0.00690
31/64	0.4844	0.1843	4	0.209	0.03431	42	0.0935	0.00687
15/32	0.4688	0.1726	5	0.2055	0.03317	43	0.0890	0.00622
29/64	0.4531	0.1613	6	0.204	0.03269	44	0.0860	0.00581
7/16	0.4375	0.1503	13/64	0.2031	0.03241	45	0.0820	0.00528
27/64	0.4219	0.1398	7	0.201	0.03173	46	0.0810	0.00515
Z	0.413	0.1340	8	0.199	0.03110	47	0.0785	0.00484
13/32	0.4063	0.1296	9	0.196	0.03017	5/64	0.0781	0.00479
Y	0.404	0.1282	10	0.1935	0.02940	48	0.0760	0.00454
Z	0.397	0.1238	11	0.191	0.02865	49	0.0730	0.00419
25/64	0.3906	0.1198	12	0.189	0.02806	50	0.0700	0.00385
W	0.386	0.1170	3/16	0.1875	0.02861	51	0.0670	0.00353
V	0.377	0.1116	13	0.185	0.02688	52	0.0635	0.00317
3/8	0.375	0.1104	14	0.182	0.02602	1/16	0.0625	0.00307
U	0.368	0.1064	15	0.1800	0.02554	53	0.0595	0.00278
23/64	0.3594	0.1014	16	0.1770	0.02461	54	0.0550	0.00238
T	0.358	0.1006	17	0.1730	0.02351	55	0.0520	0.00212
S	0.348	0.09511	11/64	0.1719	0.02320	3/64	0.0473	0.00173
11/32	0.3438	0.09281	18	0.1695	0.02256	56	0.0465	0.001698
R	0.339	0.09026	19	0.1660	0.02164	57	0.0430	0.001452
Q	0.332	0.08657	20	0.1610	0.02036	58	0.0420	0.001385
21/64	0.3281	0.08456	21	0.1590	0.01986	59	0.0410	0.001320
P	0.323	0.08194	22	0.1570	0.01936	60	0.0400	0.001257
O	0.316	0.07843	5/32	0.1563	0.01917	61	0.039	0.001195
5/16	0.3125	0.07670	23	0.1540	0.01863	62	0.038	0.001134
N	0.302	0.07163	24	0.1520	0.01815	63	0.037	0.001075
19/64	0.2969	0.06922	25	0.1495	0.01755	64	0.036	0.001018
M	0.295	0.06835	26	0.1470	0.01697	65	0.035	0.000962
L	0.29	0.06605	27	0.1440	0.01629	66	0.033	0.000855
9/32	0.2813	0.06213	9/64	0.1406	0.01553	67	0.032	0.000804
K	0.281	0.06202	28	0.1405	0.01549	1/32	0.0313	0.000765
J	0.277	0.06026	29	0.1360	0.01453	68	0.031	0.000755
I	0.272	0.05811	30	0.1285	0.01296	69	0.0292	0.000670
H	0.266	0.05557	1/8	0.1250	0.01227	70	0.028	0.000616
17/64	0.2656	0.05542	31	0.1200	0.01131	71	0.026	0.000531
G	0.261	0.05350	32	0.1160	0.01057	72	0.025	0.000491
F	0.257	0.05187	33	0.1130	0.01003	73	0.024	0.000452
E 1/4	0.2500	0.04909	34	0.1110	0.00968	74	0.0225	0.000398
D	0.246	0.04753	35	0.1100	0.00950	75	0.021	0.000346
C	0.242	0.04600	7/64	0.1094	0.00940	76	0.020	0.000314
B	0.238	0.04449	36	0.1065	0.00891	77	0.018	0.000254
15/64	0.2344	0.04314	37	0.1040	0.00849	78	0.016	0.000201
A	0.234	0.04301	38	0.1015	0.00809	1/64	0.0156	0.000191
1	0.228	0.04083	39	0.0995	0.00778	79	0.0145	0.000165
2	0.221	0.03836	40	0.0980	0.00754	80	0.0135	0.000143
7/32	0.2188	0.03758	41	0.0960	0.00724	----	----	----

Note: Designations are in fractions of an in., in standard twist drill letters or in standard twist drill numbers, the latter being the same as steel wire gauge numbers.

# Glossary of Terms

## A

**Absolute Pressure (abs press)** - Gauge pressure plus barometric pressure. Absolute pressure can be zero only in a perfect vacuum.

**Absolute Viscosity (abs visc)** - The product of fluid kinematic viscosity times its density. Absolute viscosity is a measure of fluid tendency to resist flow, without regard to its density. Sometimes the term dynamic viscosity is used in place of absolute viscosity. Refer to Viscosity, Absolute.

**Accuracy** - A measure of how close a regulator can keep downstream pressure ( $P_2$ ) to the setpoint. Regulator accuracy is expressed as percent droop or proportional band or offset in percent of setpoint or in units of pressure.

**ACFH** - Actual Cubic Feet per Hour. The actual volume of fluid measured by the meter. This is not SCFH (standard cubic feet per hour).

**Active/Working Regulator** - A regulator that is in service performing a control function.

**Adjusting Screw** - A screw used to change the compression setting of a loading spring.

**AGA** - The American Gas Association or Australian Gas Association.

**Airsets** - See Filter/Supply Regulators.

**ALPGA** - Australian Liquefied Petroleum Gas Association, Ltd.

**ANSI** - American National Standards Institute.

**API** - American Petroleum Institute.

**Appliance (Equipment)** - Any device that uses gas as a fuel or raw material to produce light, heat, power, refrigeration or air conditioning.

**ASME** - American Society of Mechanical Engineers.

**Aspirator** - Any device using fluid velocity effect to produce a low-pressure zone. Used in regulator control and combustion systems.

**Atmospheric Pressure** - The pressure exerted by the atmosphere at a given location and time. Sea level pressure is approximately 14.7 psia / 1.0 bar a.

**Automatic Control System** - A control system that operates without human intervention.

**Automatic Cutoff** - A device used on some regulators to close the main valve in the event of pressure deviation outside of a preset range. Must be reopened manually.

## B

**Backpressure Regulator** - This is a device that controls and responds to changes in its upstream/inlet pressure. Functions the same as a relief valve in that it opens on increasing upstream pressure.

**Barometer** - An instrument for measuring atmospheric pressure, usually in inches, centimeters or millimeters of mercury column.

**Barometric Pressure** - The atmospheric pressure at a specific place according to the current reading of a barometer.

**Bellows** - A flexible, thin-walled cylinder made up of corrugations one next to the other that can expand or contract under changing pressures.

**Bimetallic Thermal System** - A device working on the difference in coefficient of expansion between two metals to produce the power to position a valve plug in response to temperature change.

**Bleed** - Removal of fluid from a higher pressure area to a lower pressure area in a regulator pilot system.

**Bode Diagram** - A plot of log amplitude ratio and phase values on a log frequency base for a transfer function. (It is a common form of graphically presenting frequency response data.)

**Body** - Pressure retaining shell enclosing the restricting element.

**Boiler** - A closed vessel in which a liquid is heated or vaporized.

**Bonnet** - The regulator component that connects the valve body to the actuator.

**Boost** - The increase in control pressure above setpoint as flow is increased from low flow to maximum flow. Some regulators exhibit droop instead of boost.

**British Thermal Unit (BTU)** - The quantity of heat required to raise the temperature of one pound of water from by 1 degree Fahrenheit.

**Build-up** - In a relief valve, the pressure increase above setpoint required to produce a given flow rate.

**BSPT** - British Standard Pipe Thread.

## C

**$C_v$**  - A term used in a sizing equation. It is defined as the ratio of the gas sizing coefficient and the liquid sizing coefficient and provides a numerical indicator of the valve's recovery capabilities.

**Cage** - A hollow, cylindrical trim element that is a guide to align the movement of a valve plug with a seat ring and/or retains the seat ring in the valve body. The walls of the cage contain openings that usually determine the flow characteristic of the control valve.

**Capacity, Flow** - The amount of a specified fluid that will flow through a valve, specific length and configuration of tubing, a manifold, fitting or other component at a specified pressure drop in a fixed period of time. (SCFH, gpm, Nm<sup>3</sup>/h, Lpm, bph).

**Capacity, Rated** - The rate of flow through the regulator specified by the manufacturer for a given inlet pressure, outlet pressure, offset and size.

**Capacity, Wide-Open** - If a wide-open failure occurs, this is the amount a regulator will flow.

**Cavitation** - A phenomenon whereby liquid flowing through a valve under reduced pressure will form gaseous bubbles that will collapse upon pressure recovery, producing potential trim damage. This is a concern when high-pressure drops exist across the valve.

**Centipoise** - A unit for measurement of absolute viscosity. One centipoise is equal to one hundredth of a poise, the metric (cgs) unit of absolute viscosity. The absolute viscosity of water at 20°C is approximately one centipoise.

**Centistoke** - A unit for measurement of kinematic viscosity. One centistoke is equal to one hundredth of a stoke, the metric (cgs) unit of kinematic viscosity. The kinematic viscosity in centistokes times the density equals the absolute viscosity in centipoises.

**CFH** - Cubic Feet per Hour (ft<sup>3</sup>/h). Volumetric measurement of gas flow per hour, generally at line conditions.

**C<sub>g</sub> (Flow Coefficient)** - A term used in gas and steam valve sizing equations. The value of C<sub>g</sub> is proportional to flow rate and is used to predict flow based on physical size or flow area.

**CGA** - Canadian Gas Association.

**Coal/Coke Oven Gas** - A gas with a high sulfur content that is produced from baking coal. It may also contain tar that can cause sticking in moving parts of a regulator. Regulators with brass or copper parts should not be used with this gas. Often this gas requires the use of fluorocarbon.

**Compressibility Effect** - The change in density of gas or air under conditions of compression.

**Compression (Spring)** - The action on a spring which decreases its length relative to the force to which it is subjected.

**Condensate** - The liquid resulting when a vapor is cooled and/or when its pressure is increased.

**Control Line** - The external piping which connects the regulator actuator or pilot to the point on the main line where control is required.

**Control Valve** - A mechanically, electrically or hydraulically operated valve, using an external power source to effect its operation, that modifies the fluid flow characteristics in a process. It consists of a valve connected to an actuator mechanism that is capable of changing the position of the flow controlling element or closure member in the valve in response to a signal from the controlling device.

**Controller** - A device that operates automatically to regulate a controlled variable.

**Critical Flow** - The rate at which a fluid flows through an orifice when the stream velocity at the orifice is equal to the velocity of sound in the fluid. Under such conditions, the rate of flow may be increased by an increase in upstream pressure, but it will not be affected by a decrease in downstream pressure. Critical flow occurs when P<sub>2</sub> is approximately 1/2 of P<sub>1</sub> absolute.

**Critical Velocity** - The velocity at critical flow. Also called sonic velocity.

**CSA** - Canadian Standards Association.

**C<sub>s</sub> (Flow Coefficient)** - Steam valve sizing coefficient. At pressures below 1000 psig, a constant relationship exists between the gas sizing coefficient (C<sub>g</sub>) and the steam coefficient (C<sub>s</sub>). This relationship is expressed: C<sub>s</sub> = C<sub>g</sub> ÷ 20.

**C<sub>v</sub> (Flow Coefficient)** - Liquid sizing coefficient. It is numerically equal to the number of U.S. Gallons of water at 60°F that will flow through the valve in one minute when the pressure differential across the valve is one pound per square inch.

**Control Line** - The external piping which connects the regulator actuator or pilot to the point on the main line where control is required.

**Control Valve** - A mechanically, electrically or hydraulically operated valve, using an external power source to effect its operation, that modifies the fluid flow characteristics in a process. It consists of a valve connected to an actuator mechanism that is capable of changing the position of the flow controlling element or closure member in the valve in response to a signal from the controlling device.

**Controller** - A device that operates automatically to regulate a controlled variable.

**Critical Flow** - The rate at which a fluid flows through an orifice when the stream velocity at the orifice is equal to the velocity of sound in the fluid. Under such conditions, the rate of flow may be increased by an increase in upstream pressure, but it will not be affected by a decrease in downstream pressure. Critical flow occurs when P<sub>2</sub> is approximately 1/2 of P<sub>1</sub> absolute.

**Critical Velocity** - The velocity at critical flow. Also called sonic velocity.

**CSA** - Canadian Standards Association.

**C<sub>s</sub> (Flow Coefficient)** - Steam valve sizing coefficient. At pressures below 1000 psig, a constant relationship exists between the gas sizing coefficient (C<sub>g</sub>) and the steam coefficient (C<sub>s</sub>). This relationship is expressed: C<sub>s</sub> = C<sub>g</sub> ÷ 20.

**C<sub>v</sub> (Flow Coefficient)** - Liquid sizing coefficient. It is numerically equal to the number of U.S. Gallons of water at 60°F that will flow through the valve in one minute when the pressure differential across the valve is one pound per square inch.

## D

**Dead Band** - The range through which an input can be varied without initiating observable response.

**Delta P (DP) (ΔP) (Pressure Drop)** - The difference between the inlet and outlet pressures.

**Demand** - The rate at which fluid is delivered to or required by a system, part of a system or a piece of equipment, usually expressed in terms of volume per unit of time.

**Density** - The weight of a unit volume of a substance. Also called specific weight.

**Diaphragm** - A flexible membrane used in a regulator or relief valve to sense changes in downstream pressure or upstream pressure and respond to them, thus moving the restricting element or closure member to which it is attached.

**Diaphragm Actuated Regulator** - A regulator utilizing a diaphragm and actuator to position the valve plug.

**Diaphragm Case** - A housing used for supporting a diaphragm and establishing one or two pressure chambers.

**Diaphragm Effect** - The change in effective area of the diaphragm as the regulator strokes from low to high flow.

**Diaphragm Plate** - A plate used to transmit force in conjunction with a diaphragm and fluid pressure on a spring to the actuator stem or pusher post.

# Glossary of Terms

**Differential Pressure** - The difference in pressure between two points in a system.

**Differential Pressure Regulator** - A device that maintains a constant differential pressure between a reference pressure and the pressure of the controlled fluid.

**Digester Gas** - A gas produced by sewage treatment plants. This gas is used to power burners and engines. Because of its high methane content, stainless steel construction might be required.

**Disk** - A movable part that is positioned in the flow path to modify the rate of flow through the valve. It is often made of an elastomer material to improve shutoff capability.

**Downstream** - Any site beyond a reference point (often a valve or regulator) in the direction of fluid flow.

**Drift** - A change in setpoint over an extended period of time.

**Droop** - The amount a regulator deviates below its setpoint as flow increases. Some regulators exhibit boost instead of droop.

**DVGW** - Deutscher Verein des Gas- und Wasserfaches e.v. (German approval agency).

**Dynamic Unbalance** - The force exerted on a valve plug when fluid is flowing through the valve.

## E

**Effective Area** - In a diaphragm actuator, the part of the diaphragm area that generates operating force. The effective area is less than the total area. (The effective area of a diaphragm might change as it is stroked, usually being a maximum at the start and a minimum at the end of the travel range. Molded diaphragms have less change in effective area than flat-sheet diaphragms.)

**End Connection** - The style of joint used to make a pressure tight connection between the valve body and the pipeline.

**Entropy** - A thermodynamic quantity that measures the fraction of the total energy of a system that is not available for doing work.

**Enthalpy** - Total heat content, expressed in BTU per pound, above an arbitrary set of conditions chosen as the base or zero point.

**External Pressure Registration** - A regulator with a control line. The actuator pressure is isolated from the body outlet pressure within the regulator.

**External Static Line** - The same as control line.

## F

**Face-to-Face Dimension** - The dimension from the face of the inlet opening to the face of the outlet opening of the regulator.

**Fail-Closed** - In the event of a regulator failure, a condition wherein the valve port remains closed. All regulators can fail open or closed.

**Fail-Open** - In the event of a regulator failure, a condition wherein the valve port remains open. All regulators can fail open or closed.

**Filter/Supply Regulators** - Pressure reducing regulators used in air service to simultaneously filter and reduce pressure. Used to supply process control instruments pneumatic power. Also called airsets.

**First-Stage Regulator** - A regulator used to reduce inlet pressure to a set value being fed to another regulator in series.

**Fixed Factor Measurement** - The measurement of gas at a controlled elevated pressure without the use of an automatic correcting device to correct the volume for variation from base or contract pressure. This is accomplished by placing an accurate regulator upstream of the meter. Also known as PFM (Pressure Factor Measurement).

**Fixed Restriction** - A small diameter hole in the pilot or piloting system that determines gain.

**Flange** - End connections of regulator valve bodies used for bolting onto another fitting or pipe element.

**Flange Facing** - The finish on the end connection of valves.

**Flashing** - A condition when liquid changes to the vapor state caused by pressure reduction inside a valve.

**Flow Capacity** - The rated flow through a regulator under stated inlet, outlet and droop pressures.

**Flow Characteristic** - Relationship between flow through the valve and percent rated travel.

**Flow Coefficient** - See  $C_v$ ,  $C_s$ ,  $C_g$ ,  $C_1$ .

**Flow Rate** - The amount (mass, weight or volume) of fluid flowing through a valve body per unit of time.

**Fluid** - Materials in a liquid, gas or vapor state, as opposed to a solid.

**Fuel Gas** - A commonly distributed gas used for fuel, such as natural gas, propane, landfill gas, etc.

**Full Capacity Relief** - A relief valve that has the capability of maintaining downstream pressure to within certain limits in the event of some type of failure, by venting the excess gas to the atmosphere.

## G

**Gage Pressure** - (psig or bar g) The difference between atmospheric pressure and the pressure being measured. Also written as gauge pressure.

**Gas** - That state of matter which expands to fill the entire container which holds it. Gas is one of the forms of matter (solid, liquid and gas).

**Gas Utilization Equipment** - Any device which utilizes gas as a fuel or raw material or both.

**Gauge Pressure** - Pressure reading as shown on a gauge (psig or bar g). The difference between atmospheric pressure and the pressure the gauge is measuring. Also written as gauge pressure.

**Gauge, Pressure** - An instrument that measures the pressure of a fluid.

**Governor** - An attachment to a machine for automatic control or limitation of speed. Also, an archaic term used for a low-pressure, direct-operated, pressure reducing gas regulator.

## H

**Hard Facing** - A material harder than the surface to which it is applied. Used to resist galling or fluid erosion.

**Header** - A piping configuration where a number of pipes are combined at one location.

**Hunting** - A condition in which a regulator's outlet pressure slowly fluctuates on either side of a setpoint.

**Hysteresis** - A deviation from setpoint caused by friction and parts clearance.

## I

**Impulse Line** - See control line.

**Inch of Water Column** - A unit of pressure measurement. The pressure required to support a column of water one inch high. Typically reported as inches w.c. (water column); 27.68 inches of water column is equal to one pound per square inch (psi).

**Inlet Pressure** - The pressure at the inlet opening of a valve ( $P_1$ ).

**Inlet Pressure Sensitivity** - The increase or decrease in the outlet pressure caused by changes in the inlet pressure which results in differing degrees of force being applied to the seat disk and diaphragm.

**Internal Relief Valve** - A small, spring-loaded pressure relief valve contained within the regulator at the center of the diaphragm to prevent outlet pressure from exceeding a predetermined pressure.

**Isolation Valve** - Refer to Valve, Isolation.

**I/O** - Input/Output -- Electrical inputs and electrical outputs.

## J - K

**$K_m$**  - Value recovery coefficient - used in liquid sizing equations to determine  $\Delta P$  allowable for cavitation.

**Kinematic Viscosity (kin visc)** - The relative tendency of fluids to resist flow. The value of the kinematic viscosity includes the effect of the density of the fluid. The kinematic viscosity is equal to the absolute viscosity divided by the density. Refer to Viscosity, Kinematic.

## L

**LCD** - Liquid crystal display; readout panel which displays alphanumeric sequences in digital format.

**Landfill Gas** - A gas produced by decaying organic matter in a garbage landfill. This gas is used to power burners and engines. This gas has a high methane content and may contain other gases; therefore, stainless steel construction is usually required.

**Liquid Expansion Thermal System** - A closed system containing liquid whose expansion and contraction in response to temperature changes provides the power to position a valve member.

**Liquefied Petroleum Gas (LPG)** - Butane, propane or a mixture of the two, obtained from oil or gas wells or as a by-product from the refining of gasoline. It is sold in metal bottles under pressure as a liquid; hence, sometimes called bottled gas.

**Loading Element** - In a regulator, the means for placing a measured amount of force against the regulator's diaphragm. The loading element is commonly a spring.

**Loading Pressure** - The pressure employed to position a pneumatic actuator. (This is the pressure that actually works on the actuator diaphragm or piston to change the position of the valve plug.)

**Lockup Pressure** - Increase over setpoint when the regulator is at no-flow condition.

## M

**Maximum Allowable Operating Pressure (MAOP)** - The maximum pressure that the system may be operated at as determined by its components, taking into account function and a factor of safety based on yield of parts or fracture.

**Maximum Operating Pressure** - The maximum pressure existing in a piping system during normal operation.

**Measuring Element** - A diaphragm that senses (measures) changes in downstream pressure and causes the regulator restricting element to move toward the open or closed position.

**Meters Cubed per Hour (Normal or Standard)** - Refer to  $Nm^3/h$  or  $Sm^3/h$ .

**Minimum Controllable Flow** - The lowest flow at which a steady regulated condition of the controlled variable can be maintained.

**Modbus** - Protocol used for communications between electronic devices developed by Gould Modicon.

## N

**NACE** - National Association of Corrosion Engineers

**Natural Gas** - A hydrocarbon gas consisting mainly of methane.

**Needle Valve** - Refer to Valve, Needle.

# Glossary of Terms

**Nm<sup>3</sup>/h** - meters cubed per hour (normal); measurement of volume rate of a gas at atmospheric pressure and 0°C. Also refer to Sm<sup>3</sup>/h.

**NPT** - National Pipe Thread, a standard for tapered thread used on pipes and pipe fittings.

## O

**Offset** - The deviation from setpoint for a given flow. Negative offset is equivalent to droop.

**Operating Pressure** - The actual pressure at which a device operates under normal conditions. This pressure may be positive or negative with respect to atmospheric pressure.

**Orifice** - A fixed opening, normally the inside diameter of a seat ring, through which fluid passes. The term can also refer to the inlet or outlet of a regulator or pilot valve. Also called a port.

**Outlet Pressure (Reduced Pressure)** - The pressure leaving the outlet opening of a valve ( $P_2$ ).

**Over-Pressure Cut-Off Device** - A mechanical device incorporated in a gas pipework system to shutoff the supply of gas when the pressure at the sensing point rises to a predetermined value.

## P

$P_1$  - Inlet or upstream pressure.

$P_2$  - Outlet or downstream pressure.

**PFM (Pressure Factor Measurement)** - The measurement of gas at a controlled elevated pressure without the use of an automatic correcting device to correct the volume for variation from base or contract pressure. This is accomplished by placing an accurate regulator upstream of the meter. Also known as Fixed Factor Measurement

**PID** - Proportional/Integral/Derivative device. Usually used as a controller.

**Pilot (Amplifier)** - A relatively small controlling regulator that operates the main regulator. They are used to increase accuracy.

**Piston Actuated Regulator** - A regulator utilizing a piston rather than a diaphragm actuator.

**Pitot Tube** - A hollow tube that connects the area beneath the regulator diaphragm with the vena contracta area of gas flow. The pitot tube causes the diaphragm to sense a pressure lower than that which exists downstream of the regulator and thus allows the regulator to open more for any given change in downstream pressure. The result is increased regulator accuracy.

$P_L$  - Loading pressure. Pressure of fluid on the main diaphragm that is controlled by a pilot regulator.

**Plug** - Piece that throttles against an orifice to increase and decrease flow.

**Poise** - A metric unit for measuring absolute viscosity. One poise equals one dyne-second per square centimeter or one gram per centimeter second.

**Port** - A fixed opening, normally the inside diameter of a seat ring, through which fluid passes. The term can also refer to the inlet or outlet of a regulator or pilot valve. Also called an orifice.

**Powder Paint Coating** - A paint process that uses dry powder with no solvents for surface finish. Dry powder can be reused, thereby reducing waste and pollutants. The powder coating over a clean surface provides better corrosion resistance than liquid coat.

**Pressure** - Force per unit area.

**Pressure Buildup** - In a relief valve, the pressure increase above setpoint required to produce a given flow rate.

**Pressure Differential** - The difference in pressure between two points in a system.

**Pressure Drop** - The difference between the inlet and outlet pressures.

**Pressure Reducing Regulator** - A valve that satisfies downstream demand while maintaining a constant reduced pressure. As the pressure decreases, the valve opens to increase flow.

**Pressure Relief Valve** - A valve that opens and closes to ensure that pressure does not rise above a predetermined value.

**Propane** - An easily liquefiable hydrocarbon gas. Propane is one of the components of raw natural gas and it is also derived from petroleum refining processes. Its chemical formula is C<sub>3</sub>H<sub>8</sub>.

**Proportional Band (Amount of Deviation)** - The amount a regulator deviates from setpoint as the flow increases from minimum to maximum. Also referred to as droop or offset.

**psia - pounds per square inch, absolute** - The pressure above a perfect vacuum, calculated from the sum of the pressure gauge reading and the (local or ambient) atmospheric pressure (approximately 14.7).

**psid** - Pounds per square inch, differential.

**psig** - Pounds per square inch, gauge. The pressure above atmospheric pressure. Near sea level the atmospheric pressure is approximately 14.7 pounds per square inch.

## Q - R

**Range** - The region between the limits within which a quantity is measured, received or transmitted, expressed by stating the lower and upper range values (Example: 3 to 15 psi; -40 to 212°F / -40 to 100°C).

**Rangeability** - The ratio of maximum rated capacity to the minimum controllable flow within the specified accuracy band.

**Rate of Flow** - The volume of material passing a given point in a system per unit of time.

**Rated Working Pressure** - The maximum allowable pressure specified by the manufacturer.



**Reduced Pressure** - The pressure leaving the outlet opening of a valve ( $P_2$ ). More commonly called outlet pressure.

**Regulator, Direct-Operated** - See Pressure Reducing Regulator.

**Regulator, Pilot-Operated** - Two regulators connected so that one increases the effect of downstream pressure changes on the other. This arrangement is used to provide increased accuracy and flow capacity compared to direct-operated regulators.

**Relief Valve** - See Pressure Relief Valve.

**Relief Valve, Pilot-Operated** - Two relief valves connected so that one increases the effect of inlet pressure changes on the other. This arrangement is used to provide increased capacity and reduced buildup compared to other relief valve types.

**Relief Valve, Pop Type** - A spring-loaded poppet type relief valve.

**Repeatability** - The closeness of agreement of a regulated value when returned to the same steady-state conditions after upset(s).

**Reseat Point** - In a relief/backpressure valve which is opened by an increase in inlet pressure, the point where the valve closes.

**Restricting Element** - The element that restricts and controls fluid flow in a system. In a regulator this element is typically a disk and orifice combination or plug and cage assembly.

**RTD** - Resistance Temperature Detector. A resistance device used to measure temperature.

**RTU** - Remote Terminal Unit or Remote Telemetry Unit.

## S

**SAE Number Viscosity** - Refer to Viscosity, SAE Number.

**Saybolt Furol** - A scale used for measuring the viscosity of heavy oils. The instrument has a larger orifice and is used at a higher temperature than the Saybolt Universal instrument used for lighter oils.

**Saybolt Universal** - A scale used for measuring the viscosity of oil, expressed in seconds required for a specified amount of oil to flow through an orifice; hence, the larger the number of seconds, Saybolt Universal (SSU), the more viscous the oil.

**SCFH** - Standard cubic feet per hour. Volumetric gas measurement of flow per hour at standard or at base conditions.

**Seat** - The portion of the seat ring or valve body which a closure member contacts for shutoff.

**Seat Leakage** - Flow of fluid past a seat or seal when in the closed position.

**Seat Ring** - A separate piece inserted in a valve body to form a valve body port. It generally provides a seating surface for a plug or disk.

**Self-Contained Regulator** - Pressure control device that is powered by the process media pressure and does not require outside energy.

**Setpoint** - The pressure at which the regulator or relief valve is set to control.

**Set Pressure Range** - The range of pressures, specified by the manufacturer, within which the device can be adjusted.

**Sm<sup>3</sup>/h** - meters cubed per hour (standard); measurement of volume rate of a gas at atmospheric pressure and 60°F. Also refer to Nm<sup>3</sup>/h.

**Soft Seat** - An elastomeric, plastic or other readily deformable material used either in the valve plug or seat ring to provide tight shutoff with minimal force.

**Sonic Velocity** - The speed of sound for a particular gas at a given inlet pressure and temperature.

**Sour Gas** - Gaseous fuel that contains a relatively large proportion of sulfur or sulfur compounds. See the discussion on Sulfide Stress Cracking in the Technical Section.

**Specific Gravity** - The ratio of weight of a given volume of fluid to the weight of an equal volume of liquid/gas at stated temperature.

**Speed of Response (Stroking Speed)** - The amount of time it takes the valve plug or disk to travel from completely closed to completely open (0 to 100%).

**Spring** - Part used as the loading element in a regulator. Length is adjusted to establish setpoint.

**Spring Adjustment Screw** - A screw used to compress the spring to establish the regulator setpoint.

**Spring Rate (K)** - Spring rate is defined by the amount of force required to compress a spring a given distance. Spring rate is given in force/length (for example, lbf/in).

**Stability** - The ability to hold a steady controlled variable within the limits of stated accuracy of regulation.

**Standard Atmosphere** - The accepted normal atmospheric pressure at sea level, equal to 14.696 pounds per square inch.

**Standard Barometer** - The reading of a barometer for standard atmospheric pressure; equal to 29.92 inches of mercury column.

**Standard Gravity** - Standard accepted value for the force of gravity. It is equal to the force which will produce an acceleration of 32.17 feet per second per second.

**Standard Pressure** - The same as standard atmosphere; equal to a pressure of 14.696 pounds per square inch.

**Static Line** - See Control Line.

**Static Pressure** - The pressure in a fluid at rest.

**Static Unbalance** - The force exerted on a valve plug due to fluid pressure in the non-flowing condition.

**Stoke** - The cgs unit of kinematic viscosity. One stoke equals one centimeter squared per second.

**Supercompressibility** - Many gases are more compressible under high pressure at ordinary temperatures than indicated by Boyle's Law. These gases, measured at the high pressures, will occupy a greater volume when the pressure is reduced to near atmospheric pressure.

**SUS (or SSU) Viscosity** - Refer to Viscosity, SUS (or SSU).

# Glossary of Terms

## T - U

**Therm** - 100,000 BTU.

**Thermostat** - A device that automatically maintains a predetermined temperature in an appliance or component.

**Travel** - The amount of linear movement of the valve closure member from the closed position to the rated full-open position.

**Travel Indicator** - An external, visible device used to indicate the travel of the valve plug.

**Trim** - The replaceable internal parts of a regulator, usually made up of a seat ring or orifice, valve plug or disk and disk holder and stem; other replaceable internal parts may be considered trim.

**Under-Pressure Cut-Off Device** - A mechanical device incorporated in a gas pipe work system to shutoff the supply of gas when the pressure at the sensing point falls to a predetermined figure.

## V

**Vacuum Breaker** - A valve used to limit an increase in vacuum. An increase in vacuum (decrease in absolute pressure) beyond a certain value registers on the diaphragm. The valve disk will open permitting atmospheric, positive pressure or an upstream vacuum that has a higher absolute pressure than the downstream vacuum, to enter the system and restore to setpoint.

**Vacuum Regulator** - A device that maintains a vacuum at a setpoint. A decrease in this vacuum (increase in absolute pressure) beyond this value registers underneath the diaphragm and opens the valve. This permits the downstream vacuum of lower absolute pressure than the upstream vacuum to restore the upstream vacuum to its original pressure setting.

**Valve** - A device used for the control of fluid. It consists of a fluid retaining assembly, one or more parts between end openings and a movable closure member which opens, restricts or closes the port(s).

**Valve Body** - A pressure retaining housing for internal parts having inlet and outlet flow connections.

**Valve Closure Member** - The movable part which is positioned in the flow path to modify the rate of flow through the valve, often made of an elastomer material to improve shutoff.

**Valve Linkage** - A lever or levers connecting the diaphragm to the valve plug or valve plug stem.

**Valve Plug** - A movable part which provides a variable restriction in a port.

**Valve, Needle** - A small, adjustable valve in which the position of a pointed plug or needle relative to an orifice or tapered orifice permits or restricts fluid flow.

**Valve, Isolation** - Simple valves located in the piping system used to isolate individual equipment. They are designed to be operable by hand and installed to be readily accessible to the consumer.

**VDC** - Volts direct current.

**Vena Contracta** - The location where cross-sectional area of the flow stream is at its minimum size, where fluid velocity is at its highest level and fluid pressure is at its lowest level. (The vena contracta normally occurs just downstream of the actual physical restriction in a regulator.)

**Vent** - An opening in the regulator spring case to allow atmospheric pressure access to the diaphragm, thus allowing free movement of the diaphragm during operation.

**Viscosity** - The tendency of a fluid to resist flow.

**Viscosity, Absolute** - The product of a fluid's kinematic viscosity times its density. Absolute viscosity is a measure of a fluid's tendency to resist flow, without regard to its density. Sometimes the term dynamic viscosity is used in place of absolute viscosity.

**Viscosity, Kinematic** - The relative tendency of fluids to resist flow. The value of the kinematic viscosity includes the effect of the density of the fluid. The kinematic viscosity is equal to the absolute viscosity divided by the density.

**Viscosity, SAE Number** - The Society of Automotive Engineers' arbitrary numbers for classifying fluids according to their viscosities. The numbers in no way indicate the viscosity index of fluids.

**Viscosity, SUS (or SSU)** - Saybolt Universal Seconds (SUS), which is the time in seconds for 60 milliliters of oil to flow through a standard orifice at a given temperature (ASTM Designation D88.56).

**Volume Corrected** - The volume metered times metering pressure plus atmospheric pressure/base pressure equals volume corrected.

## W

**Water Column** - A unit of measurement. The pressure required to support a column of water one inch high. Typically reported as in. w.c. (water column); 27.68 inches of water is equal to one pound per square inch (psi).

**Weight, Specific** - The weight per unit volume of a substance. The same as density.

## X - Y - Z

**Yoke** - A structure by which the diaphragm case or cylinder assembly is supported rigidly on the bonnet assembly.



# Index

## Products

Type 63EG .....	30	CS200 Series .....	264
66 Series .....	44	CS400 Series .....	279
67C Series .....	49	CS800 Series .....	301
Type 99 .....	57	CSB400 Series .....	335
133 Series .....	64	CSB600 Series .....	343
Type 252 .....	74	CSB700 Series .....	352
289 Series .....	76	Type Dosaodor-D / Electronic Control Unit .....	361
Type 289P .....	83	Type Dosaodor-D / ROC809 .....	367
299H Series .....	88	Type DO200 .....	371
Type 310A .....	112	EZH Series .....	375
627 Series .....	120	Type EZH Relief .....	390
Type 627F .....	138	EZL Series .....	395
Type 627OSX .....	144	EZR Series .....	406
Type 630 .....	152	Type EZR Relief .....	426
Types 634 and 634M .....	164	FA, FAG Series .....	436
Type 912N .....	167	FL Series .....	447
971 Series .....	170	Type FL Relief .....	454
Types 1098-EGR and 1098H-EGR .....	173	Type H120 .....	459
1301 Series .....	182	H200 Series .....	461
1805 Series .....	186	Type HSR .....	463
Type 1805P .....	190	M Series .....	480
1808 Series .....	193	MIC, MIF, MIR Series .....	490
A/100 Series .....	199	OL Series .....	495
A/140 Series .....	202	Type OSE .....	496
Type B .....	205	Type P590 .....	501
Type B NG .....	208	R Series .....	502
B/240 Series .....	211	Type R622 .....	506
Types BLE and BLX .....	214	Regal 3 Series .....	511
BM5 Series .....	217	Type RPE .....	515
BM6X Series .....	222	Skids .....	517
BM7 Series .....	226	Types SR, SR11, SRS, STP, STL and Whisper Trim™ .....	519
CNF, CN, CF Series .....	229	VS100 Series .....	521
CP200 Series .....	233	VFA Series .....	527
CP400 Series .....	240	V Series .....	530
Cronos Series .....	257		

## Products by Application

### Accessories

#### **Butterfly Valve Soft Seated Body**

VFA Series ..... 527

#### **Electric Pilot Heater**

Type RPE. .... 515

#### **Filters**

Type 252 ..... 74

Type P590 ..... 501

FA, FAG Series ..... 436

#### **Heat Exchangers**

CF, CN, CNF Series ..... 229

#### **Silencers**

Types SR, SR11, SRS, STP, STL and Whisper Trim™..... 519

### City Gate / District Station

Type 99 ..... 57

133 Series..... 64

Type 310A..... 112

971 Series ..... 170

Types 1098-EGR and 1098H-EGR ..... 173

Cronos Series ..... 257

EZH Series ..... 375

EZL Series ..... 395

EZR Series..... 406

FL Series ..... 447

M Series ..... 480

### Commercial / Industrial Service

Type 99 ..... 57

133 Series..... 64

299H Series ..... 88

627 Series..... 120

Type 627F ..... 138

Type 912N ..... 167

Type 1098-EGR ..... 173

A/100 Series ..... 199

A/140 Series ..... 202

B/240 Series ..... 211

CP200 Series ..... 233

CP400 Series ..... 240

Cronos Series ..... 257

CS200 Series ..... 264

CS400 Series ..... 279

CS800 Series ..... 301

CSB400 Series ..... 335

CSB600 ..... 343

CSB700 ..... 352

EZL Series ..... 395

R Series ..... 502

Regal 3 Series ..... 511

### Farm Tap / Field

627 Series ..... 120

Type 627F ..... 138

Type 630 ..... 152

# Index

## Fixed Factor Billing / Pressure Factor Measurement

Type 99 .....	57
299H Series .....	88
Type 627F .....	138
Type 1098-EGR .....	173
CP200 Series .....	233
CP400 Series .....	240
CS200 Series .....	264
CS400 Series .....	279
CS800 Series .....	301
CSB400 Series .....	335

## Fuel Gas Regulators

66 Series .....	44
Type 99 .....	57
133 Series .....	64
299H Series .....	88
Type 912N .....	167
Type 1098-EGR .....	173
CS200 Series .....	264
CS400 Series .....	279
CS800 Series .....	301
CSB400 Series .....	335

## Odorizing Systems

Type Dosaodor-D / Electronic Control Unit .....	361
Type Dosaodor-D / ROC809 .....	367
OL Series .....	495

## Relief Valves / Backpressure Regulators

Type 63EG .....	30
289 Series .....	76
Type 289P .....	83
1805 Series .....	186
Type 1805P .....	190
1808 Series .....	193
Type EZR .....	406
Type EZH Relief .....	390

## Relief Valves / Backpressure Regulators (continued)

Type FL Relief .....	454
Type H120 .....	459
H200 Series .....	461
V Series .....	530

## Residential / Utilization Service

Type B .....	205
Type B NG .....	208
Type HSR .....	463
R Series .....	502
Type R622 .....	506

## Shutoff Devices

634 Series .....	164
BM5 Series .....	217
BM6X Series .....	222
Type BM7 .....	226
Type OSE .....	496
VS100 Series .....	521
Skids .....	517

## Supply Regulators

67C Series .....	49
1301 Series .....	182

## Transmission

Type 310A .....	112
Types BLE and BLX .....	214
Cronos Series .....	257
EZH Series .....	375
EZR Series .....	406
FL Series .....	447

## Underground Modules

M Series .....	480
----------------	-----

## Emerson.com

Our website is your 24/7 on-line resource for the latest information regarding pressure regulator products. You are invited to browse the website at anytime. Emerson product documentation is available on-line including product bulletins and installation manuals. Registered users may download these documents as well.

Our website is designed by those who know regulators to help you with your pressure regulator needs. **Emerson.com** will help you:

- Locate Sales Offices Worldwide
- Download Scalable Drawings
- Submit a Request For Quote (RFQ)
- Download:
  - Product Bulletins
  - Instruction Manuals
  - PED Multi-Language Guides
  - Product Brochures
  - Schematics
- Contact A Regulator Expert
- Find Technical References

Note: In addition to viewing and downloading documents, registered users are provided their own My Page which offers additional web features including Demos/Displays, Documentation Notification, Product Animations, Literature Search, Order Literature and Promotional Items.

[www.Emerson.com](http://www.Emerson.com)

# Notes

---





# Notes

---



# Notes

---

# Worldwide Contact Information

Emerson sales, service and technical support are as close as your telephone or on the web, anywhere in the world. Our distribution network offers a full complement of expert sales and support staff and more than 2,000 technical experts strategically located across nearly 200 offices worldwide.

## Internet:

[www.Emerson.com](http://www.Emerson.com)

## Information available:

- Local Sales Office contacts
- New technology and products
- Technical information library

## E-mail:

[WebAdmin.Regulators@Emerson.com](mailto:WebAdmin.Regulators@Emerson.com)

## Write:

Emerson Automation Solutions  
3200 Emerson Way  
McKinney, TX 75069  
USA

## Telephone:

Call one of the numbers listed below to be directed to your local Sales Office.


**United States** ..... 1 800 558 5853

**Outside the U.S.** ..... 1 972 548 3574

**Asia-Pacific** ..... +65 6770 8337

**Europe** ..... +39 051 419 0611

**Middle East and Africa** ..... +971 4811 8100



[www.Emerson.com](http://www.Emerson.com)



All the information found in the Emerson's Natural Gas Application Guide can also be found online at Emerson.com.

Download Regulator Toolkit at [www.emerson.com/regulator toolkit](http://www.emerson.com/regulator toolkit) that contains:

- Regulator Product Bulletins
- Instruction Manuals
- Product Schematics
- Product Animations

**Our Global Natural Gas Product Brands:**

**FISHER™ TARTARINI™**